

OIL AND GAS CONSERVATION COMMISSION
OF THE STATE OF COLORADO

PLUGGING RECORD

DEC 24 1959

OIL & GAS
CONSERVATION COMMISSION

INSTRUCTIONS

Within thirty (30) days after the plugging of any well, the owner or operator thereof shall file this form in duplicate for wells on Patented or Federal lands, and in triplicate for wells on State lands, give a detailed account of the manner in which the abandonment or plugging work was carried out, including the nature and quantities of materials used in plugging and the location and extent (by depths) of the plugs of different materials; records of the amount, size and location (by depths) of casings and junk left in the well; and a detailed statement of the volume and weight of mud fluid used.

Operator Ancora Corporation Field Wilcoat ☒
 Lease Name Morris Well No. 1 County Routt
 Location NE SE Section 14 Township 6 North Range 86 West Meridian 6th P.
 (Quarter Quarter)
1766 feet from South Section line and 664.29 feet from East Section Line
 Nor S E or W

TOTAL DEPTH 5250'DATE OF PLUGGING December 22, 1959 *Verbal 12-20-59*

DETAILS OF WORK

Baker Model N cast iron bridge plug, size 3 B, set in 7" casing at 2950 by McCullough Tool Company. Six sax of calseal set on top of it with McCullough dump bailer.

2258' of 7" casing shot off with McCullough jet shot, pulled and recovered.

Baker Model N cast iron bridge plug, size 6, set in 9-5/8" casing at 290', by McCullough Tool Company. Four sax calseal set on top of it with McCullough dump bailer.

Top of 9-5/8" casing capped.

AJJ	
DVR	
WRS	
HHM	
JAM	
FJP	
JJD	<i>[Signature]</i>
FILE	

I/we hereby swear (or affirm) that the statements herein made are a full and correct report:

Approved:

DEC 24 1959

Date

Company ANCORA CORPORATIONDate 12/23/59Address 635 Petroleum Club Bldg. Phone No. AM 6-3515

Director

By John H. Rathbone Title Geologist

(Signature)