



WELLBORE DIAGRAM

CURRENT WBD

2464' FSL & 2262' FWL

Operator:	Great Western Operating Co. LLC
Well Name:	Binder 24-20
Lease Number:	
Location:	NESW S20-T4N-R67W
Field:	Wattenberg
County, State:	Weld, CO
API Number:	05-123-32772
Diagram Date:	6/12/2019
Lat/Long	40.29809, -104.91491

KB ' 4916

GL ' 4902

Spud Date: 2/1/2012
Date TD Reached: 2/5/2012

Surface casing
 (12-1/4" Hole Size) 8-5/8" 24# csg set @ 521'
 w/ 370 sx cmt

Production casing
 (7-7/8" Hole Size) 4-1/2" 11.6# csg set @ 7739'
 w/ 585 sx cmt

Surface plug from 1200' to surface
 w/ 469 sx

Cut and pull csg from 2000'
 100sx Stub plug from
 2050' to 1650' (tag)

Set CICR @ 2850'

Mill and Underream from 2905'
 to 2985' Sqz 75sx thru Window

CIBP set @ 3000' 2sx

Spot 25 sx plug from 4000'
 to 3568'

CIBP w/ 25 sx @ 7213' to 6781'


TOC = 2770' (CBL)

Formation Tops (MD)

Greeley Sand	2500'
Parkman	3810'
Sussex	4412'
Shannon	4914'
Niobrara	7242'
Fort Hays	7550'
Codell	7572'

Perforations

7273'-7589'
 (reported top perf of 7061 is incorrect)



TVD = 7444' PBTVD = 7395'
 MD = 7755' PBMD = 7725'