GO

MAIN PASS 0 PSI

THE INFORMATION CONTAINED IN THIS REPORT IS THE PROPERTY OF GO PHYSICAL MODELING, INC. AND IS SUBMITTED IN CONFIDENCE. NEITHER THIS REPORT NOR ANY PART THEREOF MAY BE REPRODUCED OR TRANSMITTED IN ANY FORM OR BY ANY MEANS, ELECTRONIC OR MECHANICAL, INCLUDING PHOTOCOPYING, RECORDING, OR BY ANY INFORMATION STORAGE AND RETRIEVAL SYSTEM, WITHOUT THE EXPRESS WRITTEN PERMISSION OF GO PHYSICAL MODELING, INC.

CONTENTS

INTERACTIVE PROCESSED GO + COMPANY REPRESENTATION

Company: [redacted]
Well: [redacted]
Field: [redacted]
County: [redacted]
State: [redacted]
Country: [redacted]
Survey Date: [redacted]
Log Date: [redacted]
Run Number: [redacted]
Depth Datum: [redacted]
Elevation: [redacted]
Permanent Datum: [redacted]
Elevation: [redacted]
Log Measured From: [redacted]
Drilling Measured From: [redacted]

Gamma Ray (GAPI) | Depth | Resistivity (ohm.m)



MAIN PASS 0 SPI

REPEAT PASS 0 PSI

Database File	90848.db
Dataset Pathname	pass2
Presentation Format	rbl_all_8_2020
Dataset Creation	Fri May 22 13:45:12 2020
Charted by	Depth in Feet scaled 1:240

LTEN	3" Travel Time	3" Amplitude (mV)	AMPS1	5" Variable Density	SECTORS
0 (lb) 1000	400 (usec) 200	0 100	0 100	200 (usec) 1200	1 8
LSPD	Casing Collar Locator	3 "Amplified Amplitude	AMPS2	-409.6 (V) 204.7	-2 66
(ft/min)	0 Gamma Ray (GAPI) 200	0 (mV) 20	0 100		
500 -500		GCT_TEMP	AMPS3		
		(degF)	0 100		
			AMPS4		
			0 100		
			AMPS5		
			0 100		
			AMPS6		
			0 100		
			AMPS7		
			0 100		
			AMPS8		
			0 100		



LTEN	3" Travel Time	3" Amplitude (mV)	AMPS1	5" Variable Density	SECTORS
0 (lb) 1000	400 (usec) 200	0 100	0 100	200 (usec) 1200	1 8
LSPD	Casing Collar Locator	3 "Amplified Amplitude	AMPS2	-409.6 (V) 204.7	-2 66
(ft/min)	0 Gamma Ray (GAPI) 200	0 (mV) 20	0 100		
500 -500		GCT_TEMP	AMPS3		
		(degF)	0 100		
			AMPS4		
			0 100		
			AMPS5		
			0 100		
			AMPS6		
			0 100		
			AMPS7		
			0 100		
			AMPS8		
			0 100		

REPEAT PASS 0 PSI