Company	NOBLE ENERGY PRODUCTN
Well	PERKINS USX 7-17
Field	WATTENBERG
County	WELD
State	COLORADO
API #	05123514200
Other Services	GAMMA RAY C.C.L. CEMENT BOND - V.D.L.
Permanent Datum	GROUND LEVEL
Elevation	4578
Log Measured From	KELLY BUSHING
Drilling Measured From	KELLY BUSHING
Elevation	K.B. 4578 D.F. 4577 G.L. 4563
Date	10-Mar-20
Run Number	ONE
Depth Driller	7117
Depth Logger	7109
Bottom Logged Interval	7109
Top Logged Interval	0
Casing Driller	8.625 @ 0
Casing Logger	8.625 @ 0
Bit Size	7.875
Type Fluid in Hole	WATER BASED
Density	8.4
Viscosity	28
Ph	10
Fluid Loss	0
Source of Sample	FLOWLINE
Rm @ Measured Temp	0.1 @ 70
Rmf @ Measured Temp	0.1 @ 70
Rmc @ Measured Temp	0.1 @ 70
Source of Rmf and Rmc	CALC
Rm @ BHT	0.1 @ 70
Time Since Circulation	4 HRS
Time Since Circulation	4 HRS
Max Rec. Temperature	70
Equipment Number	3
Location	1
Recorded By	CHRISTOPHER
Witnessed By	MIKE

SECT. 7 TWP. 3N RGE. 68W

Company: NOBLE ENERGY PRODUCTN
Well: PERKINS USX 7-17
Field: WATTENBERG
County: WELD
State: COLORADO
API #: 05123514200

Comments

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not be liable for any loss, cost, damages or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set forth in our current Price Schedule.

Calibration Report

Database File: perkins-usx y 7-17.db
Dataset Pathname: pass4
Dataset Creation: Thu Mar 26 14:34:35 2020 by Log 7.0 81

Gamma Ray Calibration Report

Type / Serial: Probe2/758g / 101010

SHOP CALIBRATION — Thu Oct 17 07:40:20 2019

	Counts/Sec	Gain	Offset	Jig	Units
Background	0.0				cps
Calibrator	0.0				cps
	0.1000				GAPI/cps

PRIMARY VERIFICATION

Background	0.0				cps
Calibrator	0.0				cps
Difference			0.0		GAPI

BEFORE SURVEY VERIFICATION

Background	0.0				cps
Calibrator	0.0				cps
Difference			0.0		GAPI

AFTER SURVEY VERIFICATION

Background	0.0				cps
Calibrator	0.0				cps
Difference			0.0		GAPI

Segmented Cement Bond Log Calibration Report

Serial Number:	101024	
Tool Model:	Probe	
Calibration Casing Diameter:	4.500	in
Calibration Depth:	420.277	ft

Master Calibration, performed Thu Mar 26 14:29:07 2020

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	0.000	2.500	0.800	81.196	32.163	0.789
CAL	0.000	2.502				
5'	0.000	2.500	0.800	81.196	32.162	0.791
SUM						
S1	0.001	2.500	0.000	81.196	32.466	-0.018
S2	0.000	2.500	0.000	81.196	32.467	-0.020
S3	0.001	2.500	0.000	81.196	32.467	-0.020
S4	0.000	2.500	0.000	81.196	32.481	-0.007
S5	0.000	2.500	0.000	81.196	32.485	-0.010
S6	0.001	2.500	0.000	81.196	32.485	-0.017
S7	0.000	2.500	0.000	81.196	32.481	-0.008
S8	0.001	2.500	0.000	81.196	32.485	-0.017

Internal Reference Calibration, performed Wed Dec 31 17:00:00 1969

	Raw (v)		Calibrated (v)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.000	0.000	0.002	1.000	0.000

Air Zero Calibration, performed Fri Aug 02 12:48:57 2019

	Raw (v)	Calibrated (v)	Results
	Zero	Zero	Offset
3'	0.000	0.000	0.000
SUM	0.000	0.000	0.000
S1	0.000	0.000	0.000
S2	0.000	0.000	0.000
S3	0.000	0.000	0.000
S4	0.000	0.000	0.000
S5	0.000	0.000	0.000
S6	0.000	0.000	0.000
S7	0.000	0.000	0.000
S8	0.000	0.000	0.000

Database File: perkins-usx y 7-17.db
Dataset Pathname: pass4
Presentation Format: swing
Dataset Creation: Thu Mar 26 14:34:35 2020 by Log 7.0 81
Charted by: Depth in Feet scaled 1:240

50 CCL -5.5
0 GR (GAPI) 180
340 TT3 (usec) 240

0 AMP (mV) 100.0 AMP51 100 200 VDL 1000 RADIAL MAP
AMPLIFIED AMPS
0 (mV) 20.0 AMP53 100
0 AMP54 100
0 AMP55 100
0 AMP56 100
0 AMP57 100
0 AMP58 100



50 CCL -5.5
0 GR (GAPI) 180
340 TT3 (usec) 240
0 AMP (mV) 100.0 AMP51 100 200 VDL 1000 RADIAL MAP
AMPLIFIED AMPS
0 (mV) 20.0 AMP53 100
0 AMP54 100
0 AMP55 100
0 AMP56 100
0 AMP57 100
0 AMP58 100