

FORM
6Rev
02/20

State of Colorado Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Replug By Other Operator

Document Number:

402454800

Date Received:

07/29/2020

WELL ABANDONMENT REPORT

This form is to be submitted as an Intent to Abandon whenever an abandonment is planned on a borehole. After the abandonment is complete, this form shall again be submitted as a Subsequent Report of the actual work completed. The approved intent shall be valid for six months after the approval date, after that period, a new intent will be required. Attachments required with the Intent to Abandon are wellbore diagrams of the current configuration and the proposed configuration with plugs set.

A Subsequent Report of Abandonment shall indicate the actual work completed. Attachments required with a Subsequent Report are a wellbore diagram showing plugs that were set and casing remaining in the hole, the job summaries from all plugging contractors used, including wireline and cementing (third party verification) and any logs that may have been run during abandonment.

OGCC Operator Number: 10661

Contact Name: Matt Ostertag

Name of Operator: BISON OIL & GAS II LLC

Phone: (720) 6446997

Address: 518 17TH STREET #1800

Fax:

City: DENVER State: CO Zip: 80202

Email: mostertag@bisonog.com

For "Intent" 24 hour notice required,

Name: Petrie, Erica

Tel: (303) 726-3822

COGCC contact:

Email: erica.petrie@state.co.us

Type of Well Abandonment Report: ☒ Notice of Intent to Abandon ☐ Subsequent Report of Abandonment

API Number 05-123-05518-00

Well Name: DOTY-FEDERAL

Well Number: 1

Location: QtrQtr: NWNW Section: 27 Township: 8N Range: 60W Meridian: 6

County: WELD

Federal, Indian or State Lease Number:

Field Name: CROW

Field Number: 13600

Only Complete the Following Background Information for Intent to Abandon

Latitude: 40.638725 Longitude: -104.084859

GPS Data: GPS Quality Value: 1.6 Type of GPS Quality Value: PDOP Date of Measurement: 02/28/2019

GPS Instrument Operator's Name: RYAN WILLIAMS

Reason for Abandonment: ☐ Dry ☐ Production Sub-economic ☐ Mechanical Problems☒ Other Interim Statewide Horizontal Offset Policy- COACasing to be pulled: ☐ Yes ☒ No Estimated Depth:Fish in Hole: ☐ Yes ☒ No If yes, explain details belowWellbore has Uncemented Casing leaks: ☐ Yes ☒ No If yes, explain details below

Details:

Current and Previously Abandoned Zones

Formation	Perf. Top	Perf. Btm	Abandoned Date	Method of Isolation	Plug Depth
D SAND	6876	6906	09/03/1969	CEMENT	6740

Total: 1 zone(s)

Casing History

Casing Type	Size of Hole	Size of Casing	Weight Per Foot	Setting Depth	Sacks Cement	Cement Bot	Cement Top	Status
SURF	12+1/4	10+3/4	36	210	125	210	0	VISU
1ST	7+7/8	5+1/2	15	7,050	175	7,050		

Plugging Procedure for Intent and Subsequent Report

CIBP #1: Depth _____ with _____ sacks cmt on top. CIBP #2: Depth _____ with _____ sacks cmt on top.
CIBP #3: Depth _____ with _____ sacks cmt on top. CIBP #4: Depth _____ with _____ sacks cmt on top.
CIBP #5: Depth _____ with _____ sacks cmt on top.

NOTE: Two(2) sacks cement required on all CIBPs.

Set	75	sks cmt from	5850	ft. to	5650	ft.	Plug Type:	OPEN HOLE	Plug Tagged:	<input checked="" type="checkbox"/>
Set	40	sks cmt from	4690	ft. to	4590	ft.	Plug Type:	OPEN HOLE	Plug Tagged:	<input type="checkbox"/>
Set	40	sks cmt from	3950	ft. to	3850	ft.	Plug Type:	OPEN HOLE	Plug Tagged:	<input type="checkbox"/>
Set	40	sks cmt from	1700	ft. to	1600	ft.	Plug Type:	OPEN HOLE	Plug Tagged:	<input type="checkbox"/>
Set	15	sks cmt from	6740	ft. to	6610	ft.	Plug Type:	CASING	Plug Tagged:	<input type="checkbox"/>

Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth

Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth

Perforate and squeeze at _____ ft. with _____ sacks. Leave at least 100 ft. in casing _____ CICR Depth

(Cast Iron Cement Retainer Depth)

Set 225 sacks half in. half out surface casing from 600 ft. to 0 ft. Plug Tagged: ☒

Set _____ sacks at surface

Cut four feet below ground level, weld on plate Above Ground Dry-Hole Marker: ☐ Yes ☐ No

Set _____ sacks in rat hole Set _____ sacks in mouse hole

Additional Plugging Information for Subsequent Report Only

Casing Recovered: _____ ft. _____ inch casing Cut and Cap Date: _____
of _____

*Wireline Contractor: _____ *Cementing Contractor: _____

Type of Cement and Additives Used: _____

Flowline/Pipeline has been abandoned per Rule 1105 ☐ Yes ☐ No

Technical Detail/Comments:

Purpose is to re-enter and adequately re-plug prior to hydraulic stimulation of proposed horizontal well per DJ Basin Offset Policy, dated December 16, 2013.
Closed loop system will be used.
See attached Operations Summary for Re-entry and Re-plugging procedures.

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: _____ Print Name: Ariana Solis

Title: Regulatory Analyst Date: 7/29/2020 Email: asolis@bisonog.com

Based on the information provided herein, this Well Abandonment Report (Form 6) complies with COGCC Rules and applicable orders and is hereby approved.

COGCC Approved: Wolfe, Stephen Date: 8/17/2020

CONDITIONS OF APPROVAL, IF ANY:

Expiration Date: 2/16/2021

COA Type	Description
	<p>Venting</p> <p>Operator shall implement measures to control unnecessary and excessive venting, to protect the health and safety of the public, and to ensure that vapors and odors from well plugging operations do not constitute a nuisance or hazard to public welfare.</p>
	<p>Plugging</p> <p>1) Provide 48 hour notice of plugging MIRU via electronic Form 42.</p> <p>2) Properly abandon flowlines as per Rule 1105. File electronic Form 42 once abandonment complete. Within 30 days of an operator completing abandonment requirements for an off-location flowline or crude oil transfer line the operator must submit a Flowline Report, Form 44.</p> <p>3) Plugs and squeezes will be placed as stated in the Plugging Procedure section of the approved NOIA unless revised by COA or prior approval from COGCC is obtained.</p> <p>4) The wellbore must be static prior to placing cement plugs which are to be a minimum of 100' in length for all but surface plugs. Mechanical isolation requires a 25' cement plug, minimum.</p> <p>5) Place a 50' plug (minimum) at the surface, both inside the inner most casing and in all annular spaces. Surface plugs shall be circulated to surface. Confirm cement to surface in all strings during cut and cap.</p> <p>6) With the Form 6 SRA operator must provide written documentation which positively affirms each COA has been addressed.</p> <p>7) Contact COGCC Area Inspector prior to commencing plugging operations.</p> <p>8) Place 40 sx on top of existing 35 sx Niobrara isolation plug at 5850-5650'. Tag required on plugs if circulation is not maintained while pumping plug and displacing to depth, or otherwise specified in the approved plugging procedure.</p> <p>9) After placing the shallowest hydrocarbon isolating plug (5650'), operator must wait a sufficient time on all subsequent plugs to confirm static conditions. If at any time after placing this plug there is evidence of pressure or of fluid migration, contact COGCC Area Engineer before continuing operations.</p> <p>10) Place combined aquifer/shoe/surface cement plug at 600-0', adjust cement volume accordingly. Tag required if cement does not circulate to surface. Continue to place cement as planned from tag to surface or contact COGCC Area Engineer.</p>

Attachment Check List

Att Doc Num	Name
402454800	FORM 6 INTENT SUBMITTED
402454897	WELLBORE DIAGRAM
402454898	OPERATIONS SUMMARY
402454899	LOCATION PHOTO

Total Attach: 4 Files

General Comments

User Group	Comment	Comment Date
Engineer	<p>SB5 NA</p> <p>Log 123-06118 Doc #945158 Induction log 9/16/1966</p> <p>DWR Aquifer picks Top Depth Base Depth</p> <p>LARAMIE 0 164 50 214</p> <p>LARAMIE FOX HILLS 164 549 50 599</p> <p>PIERRE SHALE 549 854</p> <p>UPPER PIERRE 854 1554 50 1604</p> <p>Deepest water well 420 22 wells (2 mi) 50 470</p>	08/17/2020
Permit	<p>-Verified SHL lat./long</p> <p>-Verified perfed intervals via Doc. 249276</p> <p>-Passed Permit Review</p>	08/06/2020

Total: 2 comment(s)