



OIL AND GAS CONSERVATION COMMISSION OF THE STATE OF COLORADO

RECEIVED MAR 5 1963

OIL & GAS CONSERVATION COMMISSION

PLUGGING RECORD

INSTRUCTIONS

Within thirty (30) days after the plugging of any well, the owner or operator thereof shall file this form in duplicate for wells on Patented or Federal lands, and in triplicate for wells on State lands, give a detailed account of the manner in which the abandonment or plugging work was carried out, including the nature and quantities of materials used in plugging and the location and extent (by depths) of the plugs of different materials; records of the amount, size and location (by depths) of casings and junk left in the well; and a detailed statement of the volume and weight of mud fluid used.

Operator Ashland Oil & Refining Company Field Wildcat X
Lease Name H. A. Boyd Well No. 1 County Weld
Location SE SE Section 18 Township 8N Range 66W Meridian 6th PM
660 feet from S Section line and 610 feet from E Section Line
N or S E or W

TOTAL DEPTH 9106 DATE OF PLUGGING 2/25/63

DETAILS OF WORK

Filled hole with heavy mud from 9106 to 530ft. placed 25 sack cement plug from 530 to 450ft. Placed 10 sacks cement plug at top of 8-5/8" casing. Inserted 4-1/2" marker in cement which is 4ft. above the ground. Marker is properly inscribed with pertinent information pertaining to the well. The plugging procedure was as requested by Mr. W. R. Smith. Well was P & A on 2/25/63.

Location checked on 5/21/63, Jim

Table with 2 columns and 6 rows: DVR, WRS, HHM, JAM, FJP, JJD, FILE. JAM, FJP, and JJD have checkmarks.

I/we hereby swear (or affirm) that the statements herein made are a full and correct report:

Approved: Date MAR - 6 1963 Company Ashland Oil & Refining Co. Date 3-1-63
Address P.O. Box 2732 Phone No. 266-3096
Denver 1, Colorado
Director By John T. Chandler Title Petroleum Engineer
(Signature)