

BGGM (1900.0 to 2021.0) Dip: 66.28° Field: 51920.9 nT
Magnetic North is 7.87 degrees East of True North (at 1/15/2020)

To correct azimuth from Magnetic to True add 7.87 degrees



Planned Wellpath Report

BUFORD 33-4-4L (REV-B.0) PWP

Page 1 of 7



REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|---|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL,SEC.34) | | |

REPORT SETUP INFORMATION

| | | | |
|---------------------|---|------------------|-------------------------|
| Projection System | NAD83 / Lambert Colorado SP, Northern Zone (501), US feet | Software System | WellArchitect® 6.0 |
| North Reference | True | User | Painsetr |
| Scale | 0.999966 | Report Generated | 6/22/2020 at 1:16:45 PM |
| Convergence at slot | 0.54° East | Database | WA_Denver |

WELLPATH LOCATION

| | Local coordinates | | Grid coordinates | | Geographic coordinates | |
|-----------------------|-------------------|----------|------------------|-----------------|------------------------|---------------|
| | North[ft] | East[ft] | Easting[US ft] | Northing[US ft] | Latitude | Longitude |
| Slot Location | 149.36 | 75.64 | 3236260.36 | 1244939.32 | 40.0026600° | -104.6566300° |
| Facility Reference Pt | | | 3236186.14 | 1244789.26 | 40.0022500° | -104.6569000° |
| Field Reference Pt | | | 3230456.90 | 1245096.09 | 40.0032400° | -104.6773400° |

WELLPATH DATUM

| | | | |
|--------------------------|-------------------|---|-------------------|
| Calculation method | Minimum curvature | RIG (20.5') (RKB) to Facility Vertical Datum | 5157.50ft |
| Horizontal Reference Pt | Slot | RIG (20.5') (RKB) to Mean Sea Level | 5157.50ft |
| Vertical Reference Pt | RIG (20.5') (RKB) | RIG (20.5') (RKB) to Mud Line at Slot (SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL,SEC.34)) | 5157.50ft |
| MD Reference Pt | RIG (20.5') (RKB) | Section Origin | N 0.00, E 0.00 ft |
| Field Vertical Reference | Mean Sea Level | Section Azimuth | 345.48° |

Planned Wellpath Report

BUFORD 33-4-4L (REV-B.0) PWP

Page 2 of 7

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|---|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL,SEC.34) | | |

WELLPATH DATA (190 stations) † = interpolated, ‡ = extrapolated station

| MD [ft] | Inclination [°] | Azimuth [°] | TVD [ft] | Vert Sect [ft] | North [ft] | East [ft] | Grid East [US ft] | Grid North [US ft] | Latitude | Longitude | DLS [°/100ft] | Comments |
|------------|--------------------|----------------|-------------|-------------------|---------------|--------------|----------------------|-----------------------|------------|--------------|------------------|----------------|
| 0.00† | 0.000 | 248.369 | 0.00 | 0.00 | 0.00 | 0.00 | 3236260.36 | 1244939.32 | 40.0026600 | -104.6566300 | 0.00 | |
| 20.50 | 0.000 | 248.369 | 20.50 | 0.00 | 0.00 | 0.00 | 3236260.36 | 1244939.32 | 40.0026600 | -104.6566300 | 0.00 | Tie On |
| 120.50† | 0.000 | 248.369 | 120.50 | 0.00 | 0.00 | 0.00 | 3236260.36 | 1244939.32 | 40.0026600 | -104.6566300 | 0.00 | |
| 200.00 | 0.000 | 248.369 | 200.00 | 0.00 | 0.00 | 0.00 | 3236260.36 | 1244939.32 | 40.0026600 | -104.6566300 | 0.00 | End of Tangent |
| 220.50† | 0.410 | 248.369 | 220.50 | -0.01 | -0.03 | -0.07 | 3236260.29 | 1244939.29 | 40.0026599 | -104.6566302 | 2.00 | |
| 320.50† | 2.410 | 248.369 | 320.46 | -0.31 | -0.93 | -2.36 | 3236258.01 | 1244938.36 | 40.0026574 | -104.6566384 | 2.00 | |
| 420.50† | 4.410 | 248.369 | 420.28 | -1.05 | -3.13 | -7.88 | 3236252.50 | 1244936.12 | 40.0026514 | -104.6566581 | 2.00 | |
| 520.50† | 6.410 | 248.369 | 519.83 | -2.22 | -6.60 | -16.65 | 3236243.77 | 1244932.56 | 40.0026419 | -104.6566894 | 2.00 | |
| 620.50† | 8.410 | 248.369 | 618.99 | -3.81 | -11.36 | -28.64 | 3236231.83 | 1244927.69 | 40.0026288 | -104.6567322 | 2.00 | |
| 720.50† | 10.410 | 248.369 | 717.64 | -5.84 | -17.38 | -43.83 | 3236216.69 | 1244921.52 | 40.0026123 | -104.6567865 | 2.00 | |
| 820.50† | 12.410 | 248.369 | 815.66 | -8.28 | -24.68 | -62.22 | 3236198.37 | 1244914.06 | 40.0025923 | -104.6568521 | 2.00 | |
| 920.50† | 14.410 | 248.369 | 912.93 | -11.15 | -33.22 | -83.78 | 3236176.90 | 1244905.30 | 40.0025688 | -104.6569291 | 2.00 | |
| 1020.50† | 16.410 | 248.369 | 1009.33 | -14.44 | -43.02 | -108.48 | 3236152.29 | 1244895.27 | 40.0025419 | -104.6570172 | 2.00 | |
| 1120.50† | 18.410 | 248.369 | 1104.74 | -18.14 | -54.05 | -136.29 | 3236124.59 | 1244883.98 | 40.0025116 | -104.6571165 | 2.00 | |
| 1220.50† | 20.410 | 248.369 | 1199.05 | -22.26 | -66.30 | -167.18 | 3236093.82 | 1244871.44 | 40.0024780 | -104.6572268 | 2.00 | |
| 1242.54 | 20.851 | 248.369 | 1219.68 | -23.22 | -69.16 | -174.40 | 3236086.63 | 1244868.51 | 40.0024701 | -104.6572525 | 2.00 | End of Build |
| 1320.50† | 20.851 | 248.369 | 1292.54 | -26.65 | -79.39 | -200.20 | 3236060.93 | 1244858.03 | 40.0024421 | -104.6573446 | 0.00 | |
| 1420.50† | 20.851 | 248.369 | 1385.99 | -31.06 | -92.51 | -233.28 | 3236027.97 | 1244844.60 | 40.0024060 | -104.6574627 | 0.00 | |
| 1520.50† | 20.851 | 248.369 | 1479.44 | -35.46 | -105.63 | -266.37 | 3235995.01 | 1244831.16 | 40.0023700 | -104.6575808 | 0.00 | |
| 1620.50† | 20.851 | 248.369 | 1572.89 | -39.87 | -118.75 | -299.46 | 3235962.05 | 1244817.73 | 40.0023340 | -104.6576989 | 0.00 | |
| 1720.50† | 20.851 | 248.369 | 1666.34 | -44.27 | -131.87 | -332.54 | 3235929.09 | 1244804.30 | 40.0022980 | -104.6578170 | 0.00 | |
| 1820.50† | 20.851 | 248.369 | 1759.79 | -48.68 | -144.99 | -365.63 | 3235896.14 | 1244790.86 | 40.0022620 | -104.6579351 | 0.00 | |
| 1920.50† | 20.851 | 248.369 | 1853.24 | -53.08 | -158.12 | -398.72 | 3235863.18 | 1244777.43 | 40.0022259 | -104.6580532 | 0.00 | |
| 2020.50† | 20.851 | 248.369 | 1946.69 | -57.49 | -171.24 | -431.80 | 3235830.22 | 1244763.99 | 40.0021899 | -104.6581713 | 0.00 | |
| 2120.50† | 20.851 | 248.369 | 2040.14 | -61.89 | -184.36 | -464.89 | 3235797.26 | 1244750.56 | 40.0021539 | -104.6582894 | 0.00 | |
| 2220.50† | 20.851 | 248.369 | 2133.59 | -66.29 | -197.48 | -497.98 | 3235764.30 | 1244737.12 | 40.0021179 | -104.6584075 | 0.00 | |
| 2320.50† | 20.851 | 248.369 | 2227.05 | -70.70 | -210.60 | -531.06 | 3235731.34 | 1244723.69 | 40.0020819 | -104.6585256 | 0.00 | |
| 2420.50† | 20.851 | 248.369 | 2320.50 | -75.10 | -223.72 | -564.15 | 3235698.38 | 1244710.25 | 40.0020459 | -104.6586437 | 0.00 | |
| 2520.50† | 20.851 | 248.369 | 2413.95 | -79.51 | -236.84 | -597.24 | 3235665.42 | 1244696.82 | 40.0020098 | -104.6587618 | 0.00 | |
| 2620.50† | 20.851 | 248.369 | 2507.40 | -83.91 | -249.96 | -630.32 | 3235632.46 | 1244683.38 | 40.0019738 | -104.6588799 | 0.00 | |
| 2720.50† | 20.851 | 248.369 | 2600.85 | -88.32 | -263.08 | -663.41 | 3235599.50 | 1244669.95 | 40.0019378 | -104.6589980 | 0.00 | |
| 2820.50† | 20.851 | 248.369 | 2694.30 | -92.72 | -276.20 | -696.50 | 3235566.54 | 1244656.52 | 40.0019018 | -104.6591161 | 0.00 | |
| 2920.50† | 20.851 | 248.369 | 2787.75 | -97.13 | -289.33 | -729.58 | 3235533.58 | 1244643.08 | 40.0018657 | -104.6592342 | 0.00 | |
| 3020.50† | 20.851 | 248.369 | 2881.20 | -101.53 | -302.45 | -762.67 | 3235500.62 | 1244629.65 | 40.0018297 | -104.6593523 | 0.00 | |
| 3120.50† | 20.851 | 248.369 | 2974.65 | -105.94 | -315.57 | -795.76 | 3235467.66 | 1244616.21 | 40.0017937 | -104.6594704 | 0.00 | |
| 3220.50† | 20.851 | 248.369 | 3068.11 | -110.34 | -328.69 | -828.84 | 3235434.70 | 1244602.78 | 40.0017577 | -104.6595885 | 0.00 | |
| 3320.50† | 20.851 | 248.369 | 3161.56 | -114.75 | -341.81 | -861.93 | 3235401.75 | 1244589.34 | 40.0017217 | -104.6597066 | 0.00 | |
| 3420.50† | 20.851 | 248.369 | 3255.01 | -119.15 | -354.93 | -895.02 | 3235368.79 | 1244575.91 | 40.0016856 | -104.6598247 | 0.00 | |
| 3520.50† | 20.851 | 248.369 | 3348.46 | -123.56 | -368.05 | -928.10 | 3235335.83 | 1244562.47 | 40.0016496 | -104.6599428 | 0.00 | |
| 3620.50† | 20.851 | 248.369 | 3441.91 | -127.96 | -381.17 | -961.19 | 3235302.87 | 1244549.04 | 40.0016136 | -104.6600609 | 0.00 | |
| 3720.50† | 20.851 | 248.369 | 3535.36 | -132.37 | -394.29 | -994.28 | 3235269.91 | 1244535.60 | 40.0015776 | -104.6601790 | 0.00 | |
| 3820.50† | 20.851 | 248.369 | 3628.81 | -136.77 | -407.41 | -1027.37 | 3235236.95 | 1244522.17 | 40.0015416 | -104.6602971 | 0.00 | |
| 3920.50† | 20.851 | 248.369 | 3722.26 | -141.18 | -420.53 | -1060.45 | 3235203.99 | 1244508.74 | 40.0015055 | -104.6604152 | 0.00 | |
| 4020.50† | 20.851 | 248.369 | 3815.71 | -145.58 | -433.66 | -1093.54 | 3235171.03 | 1244495.30 | 40.0014695 | -104.6605333 | 0.00 | |
| 4120.50† | 20.851 | 248.369 | 3909.17 | -149.99 | -446.78 | -1126.63 | 3235138.07 | 1244481.87 | 40.0014335 | -104.6606514 | 0.00 | |

Planned Wellpath Report

BUFORD 33-4-4L (REV-B.0) PWP

Page 3 of 7

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|---|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL,SEC.34) | | |

WELLPATH DATA (190 stations) † = interpolated, ‡ = extrapolated station

| MD [ft] | Inclination [°] | Azimuth [°] | TVD [ft] | Vert Sect [ft] | North [ft] | East [ft] | Grid East [US ft] | Grid North [US ft] | Latitude | Longitude | DLS [°/100ft] | Comments |
|------------|--------------------|----------------|-------------|-------------------|---------------|--------------|----------------------|-----------------------|------------|--------------|------------------|----------------|
| 4220.50† | 20.851 | 248.369 | 4002.62 | -154.39 | -459.90 | -1159.71 | 3235105.11 | 1244468.43 | 40.0013975 | -104.6607695 | 0.00 | |
| 4320.50† | 20.851 | 248.369 | 4096.07 | -158.80 | -473.02 | -1192.80 | 3235072.15 | 1244455.00 | 40.0013614 | -104.6608876 | 0.00 | |
| 4420.50† | 20.851 | 248.369 | 4189.52 | -163.20 | -486.14 | -1225.89 | 3235039.19 | 1244441.56 | 40.0013254 | -104.6610057 | 0.00 | |
| 4520.50† | 20.851 | 248.369 | 4282.97 | -167.60 | -499.26 | -1258.97 | 3235006.23 | 1244428.13 | 40.0012894 | -104.6611238 | 0.00 | |
| 4620.50† | 20.851 | 248.369 | 4376.42 | -172.01 | -512.38 | -1292.06 | 3234973.27 | 1244414.69 | 40.0012534 | -104.6612419 | 0.00 | |
| 4720.50† | 20.851 | 248.369 | 4469.87 | -176.41 | -525.50 | -1325.15 | 3234940.31 | 1244401.26 | 40.0012174 | -104.6613600 | 0.00 | |
| 4820.50† | 20.851 | 248.369 | 4563.32 | -180.82 | -538.62 | -1358.23 | 3234907.36 | 1244387.82 | 40.0011813 | -104.6614781 | 0.00 | |
| 4920.50† | 20.851 | 248.369 | 4656.77 | -185.22 | -551.74 | -1391.32 | 3234874.40 | 1244374.39 | 40.0011453 | -104.6615962 | 0.00 | |
| 5020.50† | 20.851 | 248.369 | 4750.22 | -189.63 | -564.87 | -1424.41 | 3234841.44 | 1244360.95 | 40.0011093 | -104.6617143 | 0.00 | |
| 5120.50† | 20.851 | 248.369 | 4843.68 | -194.03 | -577.99 | -1457.49 | 3234808.48 | 1244347.52 | 40.0010733 | -104.6618324 | 0.00 | |
| 5220.50† | 20.851 | 248.369 | 4937.13 | -198.44 | -591.11 | -1490.58 | 3234775.52 | 1244334.09 | 40.0010372 | -104.6619505 | 0.00 | |
| 5320.50† | 20.851 | 248.369 | 5030.58 | -202.84 | -604.23 | -1523.67 | 3234742.56 | 1244320.65 | 40.0010012 | -104.6620686 | 0.00 | |
| 5420.50† | 20.851 | 248.369 | 5124.03 | -207.25 | -617.35 | -1556.75 | 3234709.60 | 1244307.22 | 40.0009652 | -104.6621867 | 0.00 | |
| 5520.50† | 20.851 | 248.369 | 5217.48 | -211.65 | -630.47 | -1589.84 | 3234676.64 | 1244293.78 | 40.0009292 | -104.6623048 | 0.00 | |
| 5620.50† | 20.851 | 248.369 | 5310.93 | -216.06 | -643.59 | -1622.93 | 3234643.68 | 1244280.35 | 40.0008931 | -104.6624229 | 0.00 | |
| 5720.50† | 20.851 | 248.369 | 5404.38 | -220.46 | -656.71 | -1656.01 | 3234610.72 | 1244266.91 | 40.0008571 | -104.6625410 | 0.00 | |
| 5820.50† | 20.851 | 248.369 | 5497.83 | -224.87 | -669.83 | -1689.10 | 3234577.76 | 1244253.48 | 40.0008211 | -104.6626591 | 0.00 | |
| 5920.50† | 20.851 | 248.369 | 5591.28 | -229.27 | -682.95 | -1722.19 | 3234544.80 | 1244240.04 | 40.0007851 | -104.6627772 | 0.00 | |
| 6020.50† | 20.851 | 248.369 | 5684.74 | -233.68 | -696.07 | -1755.27 | 3234511.84 | 1244226.61 | 40.0007490 | -104.6628952 | 0.00 | |
| 6120.50† | 20.851 | 248.369 | 5778.19 | -238.08 | -709.20 | -1788.36 | 3234478.88 | 1244213.17 | 40.0007130 | -104.6630133 | 0.00 | |
| 6220.50† | 20.851 | 248.369 | 5871.64 | -242.49 | -722.32 | -1821.45 | 3234445.92 | 1244199.74 | 40.0006770 | -104.6631314 | 0.00 | |
| 6320.50† | 20.851 | 248.369 | 5965.09 | -246.89 | -735.44 | -1854.54 | 3234412.97 | 1244186.31 | 40.0006410 | -104.6632495 | 0.00 | |
| 6420.50† | 20.851 | 248.369 | 6058.54 | -251.30 | -748.56 | -1887.62 | 3234380.01 | 1244172.87 | 40.0006049 | -104.6633676 | 0.00 | |
| 6520.50† | 20.851 | 248.369 | 6151.99 | -255.70 | -761.68 | -1920.71 | 3234347.05 | 1244159.44 | 40.0005689 | -104.6634857 | 0.00 | |
| 6620.50† | 20.851 | 248.369 | 6245.44 | -260.11 | -774.80 | -1953.80 | 3234314.09 | 1244146.00 | 40.0005329 | -104.6636038 | 0.00 | |
| 6720.50† | 20.851 | 248.369 | 6338.89 | -264.51 | -787.92 | -1986.88 | 3234281.13 | 1244132.57 | 40.0004969 | -104.6637219 | 0.00 | |
| 6820.50† | 20.851 | 248.369 | 6432.34 | -268.91 | -801.04 | -2019.97 | 3234248.17 | 1244119.13 | 40.0004608 | -104.6638400 | 0.00 | |
| 6920.50† | 20.851 | 248.369 | 6525.80 | -273.32 | -814.16 | -2053.06 | 3234215.21 | 1244105.70 | 40.0004248 | -104.6639581 | 0.00 | |
| 7020.50† | 20.851 | 248.369 | 6619.25 | -277.72 | -827.28 | -2086.14 | 3234182.25 | 1244092.26 | 40.0003888 | -104.6640762 | 0.00 | |
| 7120.50† | 20.851 | 248.369 | 6712.70 | -282.13 | -840.41 | -2119.23 | 3234149.29 | 1244078.83 | 40.0003528 | -104.6641943 | 0.00 | |
| 7220.50† | 20.851 | 248.369 | 6806.15 | -286.53 | -853.53 | -2152.32 | 3234116.33 | 1244065.39 | 40.0003167 | -104.6643124 | 0.00 | |
| 7320.50† | 20.851 | 248.369 | 6899.60 | -290.94 | -866.65 | -2185.40 | 3234083.37 | 1244051.96 | 40.0002807 | -104.6644305 | 0.00 | |
| 7341.07 | 20.851 | 248.369 | 6918.82 | -291.84 | -869.35 | -2192.21 | 3234076.59 | 1244049.20 | 40.0002733 | -104.6644548 | 0.00 | End of Tangent |
| 7420.50† | 19.511 | 271.209 | 6993.49 | -289.99 | -874.29 | -2218.65 | 3234050.20 | 1244044.01 | 40.0002597 | -104.6645492 | 10.00 | |
| 7520.50† | 22.024 | 298.787 | 7087.21 | -272.56 | -864.88 | -2251.87 | 3234016.90 | 1244053.10 | 40.0002855 | -104.6646677 | 10.00 | |
| 7620.50† | 27.956 | 318.046 | 7177.96 | -238.81 | -838.35 | -2284.05 | 3233984.46 | 1244079.32 | 40.0003584 | -104.6647826 | 10.00 | |
| 7720.50† | 35.635 | 330.303 | 7262.97 | -189.77 | -795.51 | -2314.23 | 3233953.88 | 1244121.87 | 40.0004760 | -104.6648903 | 10.00 | |
| 7820.50† | 44.152 | 338.518 | 7339.68 | -126.92 | -737.65 | -2341.49 | 3233926.08 | 1244179.47 | 40.0006348 | -104.6649876 | 10.00 | |
| 7920.50† | 53.098 | 344.493 | 7405.75 | -52.18 | -666.53 | -2364.99 | 3233901.90 | 1244250.35 | 40.0008300 | -104.6650716 | 10.00 | |
| 8020.50† | 62.280 | 349.191 | 7459.16 | 32.18 | -584.32 | -2384.03 | 3233882.08 | 1244332.38 | 40.0010557 | -104.6651395 | 10.00 | |
| 8120.50† | 71.596 | 353.150 | 7498.30 | 123.60 | -493.50 | -2398.02 | 3233867.22 | 1244423.05 | 40.0013050 | -104.6651895 | 10.00 | |
| 8220.50† | 80.985 | 356.697 | 7521.99 | 219.30 | -396.85 | -2406.55 | 3233857.78 | 1244519.61 | 40.0015703 | -104.6652200 | 10.00 | |
| 8315.56 | 89.941 | 359.898 | 7529.50† | 311.59 | -302.24 | -2409.34 | 3233854.08 | 1244614.19 | 40.0018300 | -104.6652300 | 10.00 | End of 3D Arc |
| 8320.50† | 89.941 | 359.898 | 7529.51 | 316.37 | -297.30 | -2409.35 | 3233854.03 | 1244619.13 | 40.0018436 | -104.6652300 | 0.00 | |
| 8420.50† | 89.941 | 359.898 | 7529.61 | 413.22 | -197.30 | -2409.53 | 3233852.90 | 1244719.12 | 40.0021181 | -104.6652307 | 0.00 | |

Planned Wellpath Report

BUFORD 33-4-4L (REV-B.0) PWP

Page 4 of 7

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|---|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL,SEC.34) | | |

WELLPATH DATA (190 stations) † = interpolated, ‡ = extrapolated station

| MD [ft] | Inclination [°] | Azimuth [°] | TVD [ft] | Vert Sect [ft] | North [ft] | East [ft] | Grid East [US ft] | Grid North [US ft] | Latitude | Longitude | DLS [°/100ft] | Comments |
|-----------|-----------------|-------------|----------|----------------|------------|-----------|-------------------|--------------------|------------|--------------|---------------|----------|
| 8520.50† | 89.941 | 359.898 | 7529.71 | 510.07 | -97.30 | -2409.71 | 3233851.77 | 1244819.11 | 40.0023926 | -104.6652314 | 0.00 | |
| 8620.50† | 89.941 | 359.898 | 7529.82 | 606.92 | 2.70 | -2409.88 | 3233850.64 | 1244919.10 | 40.0026671 | -104.6652320 | 0.00 | |
| 8720.50† | 89.941 | 359.898 | 7529.92 | 703.77 | 102.70 | -2410.06 | 3233849.51 | 1245019.09 | 40.0029416 | -104.6652327 | 0.00 | |
| 8820.50† | 89.941 | 359.898 | 7530.02 | 800.62 | 202.70 | -2410.24 | 3233848.38 | 1245119.08 | 40.0032161 | -104.6652334 | 0.00 | |
| 8920.50† | 89.941 | 359.898 | 7530.13 | 897.47 | 302.70 | -2410.42 | 3233847.26 | 1245219.07 | 40.0034906 | -104.6652340 | 0.00 | |
| 9020.50† | 89.941 | 359.898 | 7530.23 | 994.32 | 402.70 | -2410.59 | 3233846.13 | 1245319.06 | 40.0037651 | -104.6652347 | 0.00 | |
| 9120.50† | 89.941 | 359.898 | 7530.33 | 1091.17 | 502.70 | -2410.77 | 3233845.00 | 1245419.05 | 40.0040396 | -104.6652354 | 0.00 | |
| 9220.50† | 89.941 | 359.898 | 7530.44 | 1188.02 | 602.70 | -2410.95 | 3233843.87 | 1245519.04 | 40.0043141 | -104.6652361 | 0.00 | |
| 9320.50† | 89.941 | 359.898 | 7530.54 | 1284.86 | 702.70 | -2411.13 | 3233842.74 | 1245619.03 | 40.0045886 | -104.6652367 | 0.00 | |
| 9420.50† | 89.941 | 359.898 | 7530.64 | 1381.71 | 802.69 | -2411.31 | 3233841.61 | 1245719.02 | 40.0048631 | -104.6652374 | 0.00 | |
| 9520.50† | 89.941 | 359.898 | 7530.75 | 1478.56 | 902.69 | -2411.48 | 3233840.48 | 1245819.01 | 40.0051377 | -104.6652381 | 0.00 | |
| 9620.50† | 89.941 | 359.898 | 7530.85 | 1575.41 | 1002.69 | -2411.66 | 3233839.35 | 1245919.00 | 40.0054122 | -104.6652387 | 0.00 | |
| 9720.50† | 89.941 | 359.898 | 7530.96 | 1672.26 | 1102.69 | -2411.84 | 3233838.23 | 1246018.99 | 40.0056867 | -104.6652394 | 0.00 | |
| 9820.50† | 89.941 | 359.898 | 7531.06 | 1769.11 | 1202.69 | -2412.02 | 3233837.10 | 1246118.98 | 40.0059612 | -104.6652401 | 0.00 | |
| 9920.50† | 89.941 | 359.898 | 7531.16 | 1865.96 | 1302.69 | -2412.19 | 3233835.97 | 1246218.97 | 40.0062357 | -104.6652407 | 0.00 | |
| 10020.50† | 89.941 | 359.898 | 7531.27 | 1962.81 | 1402.69 | -2412.37 | 3233834.84 | 1246318.96 | 40.0065102 | -104.6652414 | 0.00 | |
| 10120.50† | 89.941 | 359.898 | 7531.37 | 2059.66 | 1502.69 | -2412.55 | 3233833.71 | 1246418.95 | 40.0067847 | -104.6652421 | 0.00 | |
| 10220.50† | 89.941 | 359.898 | 7531.47 | 2156.51 | 1602.69 | -2412.73 | 3233832.58 | 1246518.94 | 40.0070592 | -104.6652427 | 0.00 | |
| 10320.50† | 89.941 | 359.898 | 7531.58 | 2253.36 | 1702.69 | -2412.90 | 3233831.45 | 1246618.93 | 40.0073337 | -104.6652434 | 0.00 | |
| 10420.50† | 89.941 | 359.898 | 7531.68 | 2350.21 | 1802.69 | -2413.08 | 3233830.33 | 1246718.92 | 40.0076082 | -104.6652441 | 0.00 | |
| 10520.50† | 89.941 | 359.898 | 7531.78 | 2447.05 | 1902.69 | -2413.26 | 3233829.20 | 1246818.91 | 40.0078827 | -104.6652447 | 0.00 | |
| 10620.50† | 89.941 | 359.898 | 7531.89 | 2543.90 | 2002.69 | -2413.44 | 3233828.07 | 1246918.90 | 40.0081572 | -104.6652454 | 0.00 | |
| 10720.50† | 89.941 | 359.898 | 7531.99 | 2640.75 | 2102.69 | -2413.62 | 3233826.94 | 1247018.89 | 40.0084318 | -104.6652461 | 0.00 | |
| 10820.50† | 89.941 | 359.898 | 7532.09 | 2737.60 | 2202.69 | -2413.79 | 3233825.81 | 1247118.88 | 40.0087063 | -104.6652468 | 0.00 | |
| 10920.50† | 89.941 | 359.898 | 7532.20 | 2834.45 | 2302.69 | -2413.97 | 3233824.68 | 1247218.87 | 40.0089808 | -104.6652474 | 0.00 | |
| 11020.50† | 89.941 | 359.898 | 7532.30 | 2931.30 | 2402.69 | -2414.15 | 3233823.55 | 1247318.86 | 40.0092553 | -104.6652481 | 0.00 | |
| 11120.50† | 89.941 | 359.898 | 7532.41 | 3028.15 | 2502.69 | -2414.33 | 3233822.42 | 1247418.85 | 40.0095298 | -104.6652488 | 0.00 | |
| 11220.50† | 89.941 | 359.898 | 7532.51 | 3125.00 | 2602.69 | -2414.50 | 3233821.30 | 1247518.84 | 40.0098043 | -104.6652494 | 0.00 | |
| 11320.50† | 89.941 | 359.898 | 7532.61 | 3221.85 | 2702.69 | -2414.68 | 3233820.17 | 1247618.83 | 40.0100788 | -104.6652501 | 0.00 | |
| 11420.50† | 89.941 | 359.898 | 7532.72 | 3318.70 | 2802.69 | -2414.86 | 3233819.04 | 1247718.82 | 40.0103533 | -104.6652508 | 0.00 | |
| 11520.50† | 89.941 | 359.898 | 7532.82 | 3415.55 | 2902.69 | -2415.04 | 3233817.91 | 1247818.81 | 40.0106278 | -104.6652514 | 0.00 | |
| 11620.50† | 89.941 | 359.898 | 7532.92 | 3512.40 | 3002.69 | -2415.21 | 3233816.78 | 1247918.80 | 40.0109023 | -104.6652521 | 0.00 | |
| 11720.50† | 89.941 | 359.898 | 7533.03 | 3609.25 | 3102.69 | -2415.39 | 3233815.65 | 1248018.79 | 40.0111768 | -104.6652528 | 0.00 | |
| 11820.50† | 89.941 | 359.898 | 7533.13 | 3706.09 | 3202.69 | -2415.57 | 3233814.52 | 1248118.78 | 40.0114513 | -104.6652534 | 0.00 | |
| 11920.50† | 89.941 | 359.898 | 7533.23 | 3802.94 | 3302.69 | -2415.75 | 3233813.40 | 1248218.77 | 40.0117258 | -104.6652541 | 0.00 | |
| 12020.50† | 89.941 | 359.898 | 7533.34 | 3899.79 | 3402.69 | -2415.92 | 3233812.27 | 1248318.76 | 40.0120004 | -104.6652548 | 0.00 | |
| 12120.50† | 89.941 | 359.898 | 7533.44 | 3996.64 | 3502.69 | -2416.10 | 3233811.14 | 1248418.75 | 40.0122749 | -104.6652554 | 0.00 | |
| 12220.50† | 89.941 | 359.898 | 7533.55 | 4093.49 | 3602.69 | -2416.28 | 3233810.01 | 1248518.74 | 40.0125494 | -104.6652561 | 0.00 | |
| 12320.50† | 89.941 | 359.898 | 7533.65 | 4190.34 | 3702.69 | -2416.46 | 3233808.88 | 1248618.73 | 40.0128239 | -104.6652568 | 0.00 | |
| 12420.50† | 89.941 | 359.898 | 7533.75 | 4287.19 | 3802.69 | -2416.64 | 3233807.75 | 1248718.72 | 40.0130984 | -104.6652575 | 0.00 | |
| 12520.50† | 89.941 | 359.898 | 7533.86 | 4384.04 | 3902.69 | -2416.81 | 3233806.62 | 1248818.71 | 40.0133729 | -104.6652581 | 0.00 | |
| 12620.50† | 89.941 | 359.898 | 7533.96 | 4480.89 | 4002.69 | -2416.99 | 3233805.49 | 1248918.70 | 40.0136474 | -104.6652588 | 0.00 | |
| 12720.50† | 89.941 | 359.898 | 7534.06 | 4577.74 | 4102.69 | -2417.17 | 3233804.37 | 1249018.69 | 40.0139219 | -104.6652595 | 0.00 | |
| 12820.50† | 89.941 | 359.898 | 7534.17 | 4674.59 | 4202.69 | -2417.35 | 3233803.24 | 1249118.68 | 40.0141964 | -104.6652601 | 0.00 | |
| 12920.50† | 89.941 | 359.898 | 7534.27 | 4771.44 | 4302.69 | -2417.52 | 3233802.11 | 1249218.67 | 40.0144709 | -104.6652608 | 0.00 | |

Planned Wellpath Report

BUFORD 33-4-4L (REV-B.0) PWP

Page 5 of 7

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|---|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL,SEC.34) | | |

WELLPATH DATA (190 stations) † = interpolated, ‡ = extrapolated station

| MD [ft] | Inclination [°] | Azimuth [°] | TVD [ft] | Vert Sect [ft] | North [ft] | East [ft] | Grid East [US ft] | Grid North [US ft] | Latitude | Longitude | DLS [°/100ft] | Comments |
|------------|--------------------|----------------|-------------|-------------------|---------------|--------------|----------------------|-----------------------|------------|--------------|------------------|--------------------|
| 13020.50† | 89.941 | 359.898 | 7534.37 | 4868.28 | 4402.69 | -2417.70 | 3233800.98 | 1249318.66 | 40.0147454 | -104.6652615 | 0.00 | |
| 13120.50† | 89.941 | 359.898 | 7534.48 | 4965.13 | 4502.69 | -2417.88 | 3233799.85 | 1249418.65 | 40.0150199 | -104.6652621 | 0.00 | |
| 13199.97 | 89.941 | 359.898 | 7534.56 | 5042.10 | 4582.16 | -2418.02 | 3233798.95 | 1249498.11 | 40.0152381 | -104.6652627 | 0.00 | End of Tangent |
| 13220.50† | 89.941 | 359.488 | 7534.58 | 5062.00 | 4602.69 | -2418.13 | 3233798.65 | 1249518.64 | 40.0152944 | -104.6652631 | 2.00 | |
| 13320.50† | 89.941 | 357.488 | 7534.68 | 5159.43 | 4702.65 | -2420.77 | 3233795.06 | 1249618.56 | 40.0155688 | -104.6652725 | 2.00 | |
| 13420.50† | 89.941 | 355.488 | 7534.79 | 5257.58 | 4802.45 | -2426.90 | 3233787.98 | 1249718.30 | 40.0158428 | -104.6652944 | 2.00 | |
| 13476.50 | 89.941 | 354.368 | 7534.85 | 5312.82 | 4858.23 | -2431.85 | 3233782.50 | 1249774.03 | 40.0159959 | -104.6653121 | 2.00 | End of 3D Arc (J) |
| 13520.50† | 89.941 | 354.368 | 7534.89 | 5356.29 | 4902.02 | -2436.16 | 3233777.77 | 1249817.78 | 40.0161161 | -104.6653276 | 0.00 | |
| 13620.50† | 89.941 | 354.368 | 7534.99 | 5455.09 | 5001.54 | -2445.98 | 3233767.01 | 1249917.19 | 40.0163893 | -104.6653626 | 0.00 | |
| 13720.50† | 89.941 | 354.368 | 7535.10 | 5553.89 | 5101.06 | -2455.79 | 3233756.25 | 1250016.61 | 40.0166625 | -104.6653977 | 0.00 | |
| 13820.50† | 89.941 | 354.368 | 7535.20 | 5652.69 | 5200.57 | -2465.61 | 3233745.49 | 1250116.02 | 40.0169357 | -104.6654328 | 0.00 | |
| 13920.50† | 89.941 | 354.368 | 7535.30 | 5751.49 | 5300.09 | -2475.42 | 3233734.73 | 1250215.44 | 40.0172089 | -104.6654679 | 0.00 | |
| 14020.50† | 89.941 | 354.368 | 7535.40 | 5850.29 | 5399.61 | -2485.24 | 3233723.97 | 1250314.85 | 40.0174820 | -104.6655029 | 0.00 | |
| 14120.50† | 89.941 | 354.368 | 7535.51 | 5949.09 | 5499.12 | -2495.05 | 3233713.21 | 1250414.27 | 40.0177552 | -104.6655380 | 0.00 | |
| 14220.50† | 89.941 | 354.368 | 7535.61 | 6047.88 | 5598.64 | -2504.87 | 3233702.45 | 1250513.69 | 40.0180284 | -104.6655731 | 0.00 | |
| 14221.87 | 89.941 | 354.368 | 7535.61 | 6049.23 | 5600.00 | -2505.00 | 3233702.30 | 1250515.04 | 40.0180321 | -104.6655736 | 0.00 | End of Tangent (J) |
| 14320.50† | 89.941 | 356.340 | 7535.71 | 6146.40 | 5698.31 | -2512.99 | 3233693.38 | 1250613.27 | 40.0183020 | -104.6656021 | 2.00 | |
| 14420.50† | 89.941 | 358.340 | 7535.81 | 6244.26 | 5798.19 | -2517.63 | 3233687.79 | 1250713.10 | 40.0185762 | -104.6656187 | 2.00 | |
| 14520.50† | 89.941 | 0.340 | 7535.92 | 6341.34 | 5898.18 | -2518.78 | 3233685.69 | 1250813.07 | 40.0188507 | -104.6656229 | 2.00 | |
| 14581.38 | 89.941 | 1.558 | 7535.98 | 6400.02 | 5959.05 | -2517.77 | 3233686.12 | 1250873.95 | 40.0190178 | -104.6656193 | 2.00 | End of 3D Arc (J) |
| 14620.50† | 89.941 | 1.558 | 7536.02 | 6437.60 | 5998.16 | -2516.71 | 3233686.81 | 1250913.06 | 40.0191251 | -104.6656155 | 0.00 | |
| 14720.50† | 89.941 | 1.558 | 7536.12 | 6533.69 | 6098.12 | -2513.99 | 3233688.58 | 1251013.04 | 40.0193995 | -104.6656058 | 0.00 | |
| 14820.50† | 89.941 | 1.558 | 7536.23 | 6629.78 | 6198.08 | -2511.27 | 3233690.34 | 1251113.02 | 40.0196739 | -104.6655962 | 0.00 | |
| 14920.50† | 89.941 | 1.558 | 7536.33 | 6725.87 | 6298.05 | -2508.55 | 3233692.11 | 1251213.00 | 40.0199483 | -104.6655865 | 0.00 | |
| 15020.50† | 89.941 | 1.558 | 7536.43 | 6821.95 | 6398.01 | -2505.83 | 3233693.88 | 1251312.98 | 40.0202227 | -104.6655768 | 0.00 | |
| 15120.50† | 89.941 | 1.558 | 7536.54 | 6918.04 | 6497.97 | -2503.11 | 3233695.65 | 1251412.96 | 40.0204971 | -104.6655672 | 0.00 | |
| 15220.50† | 89.941 | 1.558 | 7536.64 | 7014.13 | 6597.93 | -2500.40 | 3233697.42 | 1251512.94 | 40.0207716 | -104.6655575 | 0.00 | |
| 15320.50† | 89.941 | 1.558 | 7536.74 | 7110.21 | 6697.90 | -2497.68 | 3233699.18 | 1251612.92 | 40.0210460 | -104.6655478 | 0.00 | |
| 15420.50† | 89.941 | 1.558 | 7536.85 | 7206.30 | 6797.86 | -2494.96 | 3233700.95 | 1251712.90 | 40.0213204 | -104.6655381 | 0.00 | |
| 15520.50† | 89.941 | 1.558 | 7536.95 | 7302.39 | 6897.82 | -2492.24 | 3233702.72 | 1251812.88 | 40.0215948 | -104.6655285 | 0.00 | |
| 15620.50† | 89.941 | 1.558 | 7537.05 | 7398.48 | 6997.79 | -2489.52 | 3233704.49 | 1251912.86 | 40.0218692 | -104.6655188 | 0.00 | |
| 15720.50† | 89.941 | 1.558 | 7537.16 | 7494.56 | 7097.75 | -2486.80 | 3233706.25 | 1252012.85 | 40.0221436 | -104.6655091 | 0.00 | |
| 15820.50† | 89.941 | 1.558 | 7537.26 | 7590.65 | 7197.71 | -2484.08 | 3233708.02 | 1252112.83 | 40.0224180 | -104.6654995 | 0.00 | |
| 15920.50† | 89.941 | 1.558 | 7537.36 | 7686.74 | 7297.68 | -2481.36 | 3233709.79 | 1252212.81 | 40.0226924 | -104.6654898 | 0.00 | |
| 16020.50† | 89.941 | 1.558 | 7537.47 | 7782.83 | 7397.64 | -2478.64 | 3233711.56 | 1252312.79 | 40.0229668 | -104.6654801 | 0.00 | |
| 16120.50† | 89.941 | 1.558 | 7537.57 | 7878.91 | 7497.60 | -2475.93 | 3233713.33 | 1252412.77 | 40.0232412 | -104.6654704 | 0.00 | |
| 16220.50† | 89.941 | 1.558 | 7537.68 | 7975.00 | 7597.56 | -2473.21 | 3233715.09 | 1252512.75 | 40.0235156 | -104.6654608 | 0.00 | |
| 16320.50† | 89.941 | 1.558 | 7537.78 | 8071.09 | 7697.53 | -2470.49 | 3233716.86 | 1252612.73 | 40.0237900 | -104.6654511 | 0.00 | |
| 16420.50† | 89.941 | 1.558 | 7537.88 | 8167.17 | 7797.49 | -2467.77 | 3233718.63 | 1252712.71 | 40.0240644 | -104.6654414 | 0.00 | |
| 16520.50† | 89.941 | 1.558 | 7537.99 | 8263.26 | 7897.45 | -2465.05 | 3233720.40 | 1252812.69 | 40.0243388 | -104.6654317 | 0.00 | |
| 16620.50† | 89.941 | 1.558 | 7538.09 | 8359.35 | 7997.42 | -2462.33 | 3233722.17 | 1252912.67 | 40.0246133 | -104.6654221 | 0.00 | |
| 16720.50† | 89.941 | 1.558 | 7538.19 | 8455.44 | 8097.38 | -2459.61 | 3233723.93 | 1253012.65 | 40.0248877 | -104.6654124 | 0.00 | |
| 16820.50† | 89.941 | 1.558 | 7538.30 | 8551.52 | 8197.34 | -2456.89 | 3233725.70 | 1253112.63 | 40.0251621 | -104.6654027 | 0.00 | |
| 16920.50† | 89.941 | 1.558 | 7538.40 | 8647.61 | 8297.31 | -2454.17 | 3233727.47 | 1253212.61 | 40.0254365 | -104.6653931 | 0.00 | |
| 17020.50† | 89.941 | 1.558 | 7538.50 | 8743.70 | 8397.27 | -2451.46 | 3233729.24 | 1253312.59 | 40.0257109 | -104.6653834 | 0.00 | |

Planned Wellpath Report

BUFORD 33-4-4L (REV-B.0) PWP

Page 6 of 7

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|---|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL,SEC.34) | | |

WELLPATH DATA (190 stations) † = interpolated, ‡ = extrapolated station

| MD [ft] | Inclination [°] | Azimuth [°] | TVD [ft] | Vert Sect [ft] | North [ft] | East [ft] | Grid East [US ft] | Grid North [US ft] | Latitude | Longitude | DLS [°/100ft] | Comments |
|-----------|-----------------|-------------|----------|----------------|------------|-----------|-------------------|--------------------|------------|--------------|---------------|--------------------|
| 17120.50† | 89.941 | 1.558 | 7538.61 | 8839.78 | 8497.23 | -2448.74 | 3233731.01 | 1253412.58 | 40.0259853 | -104.6653737 | 0.00 | |
| 17220.50† | 89.941 | 1.558 | 7538.71 | 8935.87 | 8597.19 | -2446.02 | 3233732.77 | 1253512.56 | 40.0262597 | -104.6653640 | 0.00 | |
| 17320.50† | 89.941 | 1.558 | 7538.81 | 9031.96 | 8697.16 | -2443.30 | 3233734.54 | 1253612.54 | 40.0265341 | -104.6653544 | 0.00 | |
| 17420.50† | 89.941 | 1.558 | 7538.92 | 9128.05 | 8797.12 | -2440.58 | 3233736.31 | 1253712.52 | 40.0268085 | -104.6653447 | 0.00 | |
| 17520.50† | 89.941 | 1.558 | 7539.02 | 9224.13 | 8897.08 | -2437.86 | 3233738.08 | 1253812.50 | 40.0270829 | -104.6653350 | 0.00 | |
| 17620.50† | 89.941 | 1.558 | 7539.12 | 9320.22 | 8997.05 | -2435.14 | 3233739.85 | 1253912.48 | 40.0273573 | -104.6653253 | 0.00 | |
| 17720.50† | 89.941 | 1.558 | 7539.23 | 9416.31 | 9097.01 | -2432.42 | 3233741.61 | 1254012.46 | 40.0276317 | -104.6653157 | 0.00 | |
| 17820.50† | 89.941 | 1.558 | 7539.33 | 9512.40 | 9196.97 | -2429.70 | 3233743.38 | 1254112.44 | 40.0279061 | -104.6653060 | 0.00 | |
| 17920.50† | 89.941 | 1.558 | 7539.43 | 9608.48 | 9296.94 | -2426.99 | 3233745.15 | 1254212.42 | 40.0281805 | -104.6652963 | 0.00 | |
| 17985.90 | 89.941 | 1.558 | 7539.50‡ | 9671.32 | 9362.31 | -2425.21 | 3233746.31 | 1254277.80 | 40.0283600 | -104.6652900 | 0.00 | End of Tangent (J) |

TARGETS

| Name | MD [ft] | TVD [ft] | North [ft] | East [ft] | Grid East [US ft] | Grid North [US ft] | Latitude | Longitude | Shape |
|---|---------------------------------------|----------|------------|-----------|-------------------|--------------------|------------|--------------|---------|
| SEC 28-T01N-R65W | N/A | 1.00 | 0.00 | -50.43 | 3236209.93 | 1244938.84 | 40.0026600 | -104.6568100 | polygon |
| | 2D Polygon: dimensions not calculated | | | | | | | | |
| SEC 33-T01N-R65W | N/A | 1.00 | 0.00 | -50.43 | 3236209.93 | 1244938.84 | 40.0026600 | -104.6568100 | polygon |
| | 2D Polygon: dimensions not calculated | | | | | | | | |
| SEC 34-T01N-R65W | N/A | 1.00 | 0.00 | -50.43 | 3236209.93 | 1244938.84 | 40.0026600 | -104.6568100 | polygon |
| | 2D Polygon: dimensions not calculated | | | | | | | | |
| 1) BUFORD 33-4-4L LP REV-1 (470'FSL & 1592'FEL,SEC.33) | 8315.56 | 7529.50 | -302.24 | -2409.34 | 3233854.08 | 1244614.19 | 40.0018300 | -104.6652300 | point |
| 2) BUFORD 33-4-4L BHL REV-1 (470'FNL & 1592'FEL,SEC.28) | 17985.90 | 7539.50 | 9362.31 | -2425.21 | 3233746.31 | 1254277.80 | 40.0283600 | -104.6652900 | point |

SURVEY PROGRAM - Ref Wellbore: BUFORD 33-4-4L PWB Ref Wellpath: BUFORD 33-4-4L (REV-B.0) PWP

| Start MD [ft] | End MD [ft] | Positional Uncertainty Model | Log Name/Comment | Wellbore |
|---------------|-------------|---|------------------|--------------------|
| 20.50 | 1500.00 | BH NaviTrak (2019) (Standard) | | BUFORD 33-4-4L PWB |
| 1500.00 | 17993.65 | BH AutoTrak Curve/eXpress (2019) (Standard) | | BUFORD 33-4-4L PWB |

Planned Wellpath Report

BUFORD 33-4-4L (REV-B.0) PWP

Page 7 of 7

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|---|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL,SEC.34) | | |

DESIGN COMMENTS

| MD [ft] | Inclination [°] | Azimuth [°] | TVD [ft] | Comment |
|------------|--------------------|----------------|-------------|--------------------|
| 20.50 | 0.000 | 248.369 | 20.50 | Tie On |
| 200.00 | 0.000 | 248.369 | 200.00 | End of Tangent |
| 1242.54 | 20.851 | 248.369 | 1219.68 | End of Build |
| 7341.07 | 20.851 | 248.369 | 6918.82 | End of Tangent |
| 8315.56 | 89.941 | 359.898 | 7529.50 | End of 3D Arc |
| 13199.97 | 89.941 | 359.898 | 7534.56 | End of Tangent |
| 13476.50 | 89.941 | 354.368 | 7534.85 | End of 3D Arc (J) |
| 14221.87 | 89.941 | 354.368 | 7535.61 | End of Tangent (J) |
| 14581.38 | 89.941 | 1.558 | 7535.98 | End of 3D Arc (J) |
| 17985.90 | 89.941 | 1.558 | 7539.50 | End of Tangent (J) |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 1 of 133

| REFERENCE WELLPATH IDENTIFICATION | | | |
|-----------------------------------|---|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL,SEC.34) | | |

| REPORT SETUP INFORMATION | | | |
|--------------------------|---|------------------|-------------------------|
| Projection System | NAD83 / Lambert Colorado SP, Northern Zone (501), US feet | Software System | WellArchitect® 6.0 |
| North Reference | True | User | Painsetr |
| Scale | 0.999966 | Report Generated | 6/22/2020 at 1:16:52 PM |
| Convergence at slot | 0.54° East | Database | WA_Denver |

| WELLPATH LOCATION | | | | | | |
|-----------------------|-------------------|----------|------------------|-----------------|------------------------|---------------|
| | Local coordinates | | Grid coordinates | | Geographic coordinates | |
| | North[ft] | East[ft] | Easting[US ft] | Northing[US ft] | Latitude | Longitude |
| Slot Location | 149.36 | 75.64 | 3236260.36 | 1244939.32 | 40.0026600° | -104.6566300° |
| Facility Reference Pt | | | 3236186.14 | 1244789.26 | 40.0022500° | -104.6569000° |
| Field Reference Pt | | | 3230456.90 | 1245096.09 | 40.0032400° | -104.6773400° |

| WELLPATH DATUM | | | |
|--------------------------|-------------------|---|-----------|
| Calculation method | Minimum Curvature | RIG (20.5') (RKB) to Facility Vertical Datum | 5157.50ft |
| Horizontal Reference Pt | Slot | RIG (20.5') (RKB) to Mean Sea Level | 5157.50ft |
| Vertical Reference Pt | RIG (20.5') (RKB) | RIG (20.5') (RKB) to Mud Line at Slot (SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL,SEC.34)) | 5157.50ft |
| MD Reference Pt | RIG (20.5') (RKB) | | |
| Field Vertical Reference | Mean Sea Level | | |

| POSITIONAL UNCERTAINTY CALCULATION SETTINGS | | | | | |
|---|------------------|------------------|---------|------------------------------|----------|
| Ellipse Confidence Limit | 3.50 Std Dev | Ellipse Start MD | 20.50ft | Surface Position Uncertainty | Included |
| Declination | 7.87° East of TN | Dip Angle | 66.28° | Mag Field Strength | 51921 nT |
| Slot Surface Uncertainty @1SD | | Horizontal | 0.100ft | Vertical | 1.000ft |
| Facility Surface Uncertainty @1SD | | Horizontal | 8.200ft | Vertical | 3.000ft |
| Positional Uncertainty values in the WELLPATH DATA table are the projection of the ellipsoid of uncertainty onto the vertical and horizontal planes | | | | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 2 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

PROXIMITY-SCAN RULE

| | | | |
|----------------------------|--|----------------------|-------|
| Rule Name | SPE WPTS Stop Drilling HSE Risk (2017) | Rule Based On | Ratio |
| Plane of Rule | Closest Approach | Threshold Value | 1.00 |
| Include Casing & Hole Size | yes | Apply Cone of Safety | no |

SURVEY PROGRAM - Ref Wellbore: BUFORD 33-4-4L PWB Ref Wellpath: BUFORD 33-4-4L (REV-B.0) PWP

| Start MD [ft] | End MD [ft] | Positional Uncertainty Model | Log Name/Comment | Wellbore |
|------------------|----------------|---|------------------|--------------------|
| 20.50 | 1500.00 | BH NaviTrak (2019) (Standard) | | BUFORD 33-4-4L PWB |
| 1500.00 | 17993.65 | BH AutoTrak Curve/eXpress (2019) (Standard) | | BUFORD 33-4-4L PWB |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 3 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CALCULATION RANGE & CUTOFF

| | | |
|------------------|-------------------|--------------------|
| From: 20.50ft MD | To: 17985.90ft MD | C-C Cutoff: (none) |
|------------------|-------------------|--------------------|

OFFSET WELL CLEARANCE SUMMARY (18 Offset Wellpaths selected) Ratios are calculated in Closest Approach plane

| Offset Facility | Offset Slot | Offset Well | Offset Wellbore | Offset Wellpath | Wellbore Status | C-C Clearance Distance | | | Rule Separation Ratio | | | |
|------------------|---|----------------------------|--------------------------------|--------------------------------|-----------------|------------------------|-------------------------|------------------------|--------------------------|-----------|--------------------------|-------------|
| | | | | | | Ref MD [ft] | Min C-C Clear Dist [ft] | Diverging from MD [ft] | Ref MD of Min Ratio [ft] | Min Ratio | Min Ratio Dvrg from [ft] | Rule Status |
| SEC.28-T01N-R65W | SLOT#01 EX. NECKIEN 1 (1015'FSL & 1460'FEL, SI) | EX. NECKIEN 1 | EX. NECKIEN 1 AWB | EX. NECKIEN 1 AWP | Drilling | 14161.81 | 155.50 | 14161.81 | 14155.54 | 0.36 | 14155.54 | FAIL |
| SEC.34-T01N-R65W | SLOT#01 EX) JORDAN 34-9 (600'FSL & 600'FWL, SEC.34) (PA) | JORDAN 34-9 | JORDAN 34-9 AWB | JORDAN 34-9 AWP | Drilling | 1510.33 | 48.47 | 8420.50 | 1514.88 | 0.55 | 8520.50 | FAIL |
| SEC.28-T01N-R65W | SLOT#01 EX. GLEN YOUNG 1 (1320'FNL & 1320'FEL, PA) | EX. GLEN YOUNG 1 | EX. GLEN YOUNG 1 AWB | EX. GLEN YOUNG 1 AWP | Drilling | 17104.20 | 291.45 | 17104.20 | 17086.59 | 0.63 | 17086.59 | FAIL |
| SEC.34-T01N-R65W | SLOT#03 BUFORD 33-5-1L (770'FSL & 794'FWL, SEC.34) | BUFORD 33-5-1L | BUFORD 33-5-1L PWB | BUFORD 33-5-1L (REV-A.0) PWP | Planned | 571.04 | 9.40 | 14520.50 | 576.04 | 0.96 | 17985.90 | FAIL |
| SEC.34-T01N-R65W | SLOT#05 BUFORD 33-4-2L (770'FSL & 844'FWL, SEC.34) | BUFORD 33-4-2L | BUFORD 33-4-2L PWB | BUFORD 33-4-2L (REV-A.0) PWP | Planned | 20.50 | 25.21 | 14520.50 | 17985.90 | 1.01 | 17985.90 | WARN |
| SEC.34-T01N-R65W | SLOT#07 BUFORD 33-3-1L (770'FSL & 894'FWL, SEC.34) | BUFORD 33-3-1L | BUFORD 33-3-1L PWB | BUFORD 33-3-1L (REV-B.0) PWP | Planned | 20.50 | 75.64 | 17985.90 | 7133.45 | 1.10 | 17985.90 | WARN |
| SEC.34-T01N-R65W | SLOT#06 BUFORD 33-3-3L (770'FSL & 869'FWL, SEC.34) | BUFORD 33-3-3L | BUFORD 33-3-3L PWB | BUFORD 33-3-3L (REV-A.0) PWP | Planned | 285.17 | 50.41 | 17985.90 | 17985.90 | 1.26 | 17985.90 | PASS |
| SEC.34-T01N-R65W | SLOT#02 BUFORD 33-5-3L (770'FSL & 769'FWL, SEC.34) | BUFORD 33-5-3L | BUFORD 33-5-3L PWB | BUFORD 33-5-3L (REV-A.0) PWP | Planned | 328.54 | 50.41 | 14520.50 | 17985.90 | 1.71 | 17985.90 | PASS |
| SEC.34-T01N-R65W | SLOT#09 BUFORD 33-2-2L (770'FSL & 944'FWL, SEC.34) | BUFORD 33-2-2L | BUFORD 33-2-2L PWB | BUFORD 33-2-2L (REV-B.0) PWP | Planned | 20.50 | 126.07 | 17985.90 | 17963.20 | 2.20 | 17963.20 | PASS |
| SEC.33-T01N-R65W | SLOT#01 EX. HSR-CHERRY KNOLLS 9-33 (1400'FSL & 660'FEL, DA) | EX. HSR-CHERRY KNOLLS 9-33 | EX. HSR-CHERRY KNOLLS 9-33 AWB | EX. HSR-CHERRY KNOLLS 9-33 AWP | Drilling | 9268.33 | 899.65 | 9268.33 | 9263.82 | 2.25 | 9263.82 | PASS |
| SEC.28-T01N-R65W | SLOT#01 EX. YOUNG 01N-65W-28-8N (230'FNL & 1275'FEL, PR) | EX. YOUNG 01N-65W-28-8N | EX. YOUNG 01N-65W-28-8N AWB | EX. YOUNG 01N-65W-28-8N AWP | Drilling | 17823.31 | 655.89 | 17823.31 | 17877.25 | 2.57 | 17877.25 | PASS |
| SEC.34-T01N-R65W | SLOT#08 BUFORD 33-2-4L (770'FSL & 919'FWL, SEC.34) | BUFORD 33-2-4L | BUFORD 33-2-4L PWB | BUFORD 33-2-4L (REV-A.0) PWP | Planned | 20.50 | 100.85 | 17985.90 | 17985.90 | 2.80 | 17985.90 | PASS |
| SEC.34-T01N-R65W | SLOT#11 BUFORD 33-1-1L (770'FSL & 994'FWL, SEC.34) | BUFORD 33-1-1L | BUFORD 33-1-1L PWB | BUFORD 33-1-1L (REV-A.0) PWP | Planned | 20.50 | 176.50 | 17985.90 | 17985.90 | 3.50 | 17985.90 | PASS |
| SEC.34-T01N-R65W | SLOT#10 BUFORD33-1-3L (770'FSL & 969'FWL, SEC.34) | BUFORD33-1-3L | BUFORD33-1-3L PWB | BUFORD33-1-3L (REV-A.0) PWP | Planned | 20.50 | 151.28 | 17985.90 | 17985.90 | 4.00 | 17985.90 | PASS |
| SEC.28-T01N-R65W | SLOT#02 EX. STRAWDER 1 (1590'FSL & 1600'FWL, SI) | EX. STRAWDER 1 | EX. STRAWDER 1 AWB | EX. STRAWDER 1 AWP | Drilling | 14691.74 | 2012.12 | 14691.74 | 14912.17 | 4.65 | 14912.17 | PASS |
| SEC.28-T01N-R65W | SLOT#2 EX. GLEN YOUNG 2 (1540'FNL & 1740'FWL, PA) | GLEN YOUNG 2 | GLEN YOUNG 2 AWB | GLEN YOUNG 2 AWP | Drilling | 16828.39 | 1956.38 | 16828.39 | 17189.32 | 5.80 | 17189.32 | PASS |
| SEC.27-T01N-R65W | SLOT#01 EX) ROWE 13N-27HZ (200'FNL & 286'FEL, SEC.27) (PR) | ROWE 13N-27HZ | ROWE 13N-27HZ | ROWE 13N-27HZ AWP | Drilling | 13448.84 | 2081.45 | 13448.84 | 14110.10 | 8.49 | 14110.10 | PASS |
| SEC.34-T01N-R65W | SLOT#01 JUDY 3-4 (620'FSL & 743'FWL, SEC.34) | JUDY 3-4 | JUDY 3-4 PWB | JUDY 3-4 (REV-A.0) PWP | Planned | 1050.67 | 110.95 | 1050.67 | 1167.88 | 8.95 | 6720.50 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 4 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. NECKIEN 1 AWB Offset Wellpath: EX. NECKIEN 1 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#01 EX. NECKIEN 1 (1015'FSL & 1460'FEL, SI) Well: EX. NECKIEN 1 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 20.50 | 20.50 | 0.00 | 0.00 | -20.50 | 83.00 | 5555.49 | -2344.35 | 337.12 | 6030.21 | 33.25 | 5996.95 | 205.89 | PASS |
| 120.50† | 120.50 | 0.00 | 0.00 | 17.00 | 120.50 | 5555.49 | -2344.35 | 337.12 | 6029.88 | 45.01 | 5984.87 | 146.87 | PASS |
| 200.00 | 200.00 | 0.00 | 0.00 | 96.52 | 200.00 | 5555.49 | -2344.35 | 337.12 | 6029.88 | 45.17 | 5984.72 | 146.32 | PASS |
| 220.50† | 220.50 | -0.03 | -0.07 | 117.03 | 220.50 | 5555.49 | -2344.35 | 337.12 | 6029.88 | 45.31 | 5984.57 | 145.80 | PASS |
| 320.50† | 320.46 | -0.93 | -2.36 | 217.06 | 320.46 | 5555.49 | -2344.35 | 337.15 | 6029.83 | 46.24 | 5983.59 | 142.60 | PASS |
| 420.50† | 420.28 | -3.13 | -7.88 | 316.93 | 420.28 | 5555.49 | -2344.35 | 337.20 | 6029.70 | 47.76 | 5981.94 | 137.64 | PASS |
| 520.50† | 519.83 | -6.60 | -16.65 | 416.54 | 519.83 | 5555.49 | -2344.35 | 337.29 | 6029.52 | 49.84 | 5979.68 | 131.41 | PASS |
| 620.50† | 618.99 | -11.36 | -28.64 | 515.77 | 618.99 | 5555.49 | -2344.35 | 337.41 | 6029.29 | 52.39 | 5976.90 | 124.47 | PASS |
| 720.50† | 717.64 | -17.38 | -43.83 | 614.47 | 717.64 | 5555.49 | -2344.35 | 337.57 | 6029.04 | 55.35 | 5973.69 | 117.30 | PASS |
| 820.50† | 815.66 | -24.68 | -62.22 | 712.55 | 815.66 | 5555.49 | -2344.35 | 337.76 | 6028.80 | 58.63 | 5970.17 | 110.26 | PASS |
| 920.50† | 912.93 | -33.22 | -83.78 | 809.88 | 912.93 | 5555.49 | -2344.35 | 337.98 | 6028.59 | 62.17 | 5966.43 | 103.55 | PASS |
| 1020.50† | 1009.33 | -43.02 | -108.48 | 906.34 | 1009.33 | 5555.49 | -2344.35 | 338.23 | 6028.47 | 65.91 | 5962.56 | 97.28 | PASS |
| 1120.50† | 1104.74 | -54.05 | -136.29 | 1001.81 | 1104.74 | 5555.49 | -2344.35 | 338.51 | 6028.47 | 69.82 | 5958.66 | 91.51 | PASS |
| 1220.50† | 1199.05 | -66.30 | -167.18 | 1096.18 | 1199.05 | 5555.49 | -2344.35 | 338.83 | 6028.65 | 73.84 | 5954.81 | 86.24 | PASS |
| 1242.54 | 1219.68 | -69.16 | -174.40 | 1116.82 | 1219.68 | 5555.49 | -2344.35 | 338.90 | 6028.72 | 74.75 | 5953.97 | 85.14 | PASS |
| 1320.50† | 1292.54 | -79.39 | -200.20 | 1189.72 | 1292.54 | 5555.49 | -2344.35 | 339.17 | 6029.04 | 77.97 | 5951.07 | 81.43 | PASS |
| 1420.50† | 1385.99 | -92.51 | -233.28 | 1283.23 | 1385.99 | 5555.49 | -2344.35 | 339.51 | 6029.64 | 82.21 | 5947.43 | 77.03 | PASS |
| 1520.50† | 1479.44 | -105.63 | -266.37 | 1376.74 | 1479.44 | 5555.49 | -2344.35 | 339.84 | 6030.45 | 86.49 | 5943.96 | 73.04 | PASS |
| 1620.50† | 1572.89 | -118.75 | -299.46 | 1470.24 | 1572.89 | 5555.49 | -2344.35 | 340.18 | 6031.47 | 90.82 | 5940.65 | 69.41 | PASS |
| 1720.50† | 1666.34 | -131.87 | -332.54 | 1563.75 | 1666.34 | 5555.49 | -2344.35 | 340.52 | 6032.70 | 95.22 | 5937.48 | 66.08 | PASS |
| 1820.50† | 1759.79 | -144.99 | -365.63 | 1657.26 | 1759.79 | 5555.49 | -2344.35 | 340.86 | 6034.14 | 99.69 | 5934.45 | 63.00 | PASS |
| 1920.50† | 1853.24 | -158.12 | -398.72 | 1750.77 | 1853.24 | 5555.49 | -2344.35 | 341.20 | 6035.79 | 104.22 | 5931.57 | 60.18 | PASS |
| 2020.50† | 1946.69 | -171.24 | -431.80 | 1844.28 | 1946.69 | 5555.49 | -2344.35 | 341.53 | 6037.65 | 108.80 | 5928.86 | 57.57 | PASS |
| 2120.50† | 2040.14 | -184.36 | -464.89 | 1937.78 | 2040.14 | 5555.49 | -2344.35 | 341.87 | 6039.72 | 113.41 | 5926.31 | 55.16 | PASS |
| 2220.50† | 2133.59 | -197.48 | -497.98 | 2031.29 | 2133.59 | 5555.49 | -2344.35 | 342.21 | 6042.00 | 118.07 | 5923.93 | 52.92 | PASS |
| 2320.50† | 2227.05 | -210.60 | -531.06 | 2124.80 | 2227.05 | 5555.49 | -2344.35 | 342.54 | 6044.49 | 122.76 | 5921.73 | 50.86 | PASS |
| 2420.50† | 2320.50 | -223.72 | -564.15 | 2218.31 | 2320.50 | 5555.49 | -2344.35 | 342.88 | 6047.18 | 127.48 | 5919.70 | 48.93 | PASS |
| 2520.50† | 2413.95 | -236.84 | -597.24 | 2311.82 | 2413.95 | 5555.49 | -2344.35 | 343.22 | 6050.09 | 132.23 | 5917.86 | 47.15 | PASS |
| 2620.50† | 2507.40 | -249.96 | -630.32 | 2405.32 | 2507.40 | 5555.49 | -2344.35 | 343.55 | 6053.20 | 137.00 | 5916.20 | 45.48 | PASS |
| 2720.50† | 2600.85 | -263.08 | -663.41 | 2498.83 | 2600.85 | 5555.49 | -2344.35 | 343.89 | 6056.52 | 141.79 | 5914.73 | 43.92 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 5 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. NECKIEN 1 AWB Offset Wellpath: EX. NECKIEN 1 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#01 EX. NECKIEN 1 (1015'FSL & 1460'FEL, SI) Well: EX. NECKIEN 1 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 2820.50† | 2694.30 | -276.20 | -696.50 | 2592.34 | 2694.30 | 5555.49 | -2344.35 | 344.22 | 6060.04 | 146.60 | 5913.45 | 42.47 | PASS |
| 2920.50† | 2787.75 | -289.33 | -729.58 | 2685.85 | 2787.75 | 5555.49 | -2344.35 | 344.56 | 6063.78 | 151.42 | 5912.35 | 41.10 | PASS |
| 3020.50† | 2881.20 | -302.45 | -762.67 | 2779.36 | 2881.20 | 5555.49 | -2344.35 | 344.89 | 6067.71 | 156.26 | 5911.45 | 39.82 | PASS |
| 3120.50† | 2974.65 | -315.57 | -795.76 | 2872.86 | 2974.65 | 5555.49 | -2344.35 | 345.22 | 6071.86 | 161.12 | 5910.74 | 38.62 | PASS |
| 3220.50† | 3068.11 | -328.69 | -828.84 | 2966.37 | 3068.11 | 5555.49 | -2344.35 | 345.56 | 6076.21 | 165.99 | 5910.22 | 37.48 | PASS |
| 3320.50† | 3161.56 | -341.81 | -861.93 | 3059.88 | 3161.56 | 5555.49 | -2344.35 | 345.89 | 6080.77 | 170.87 | 5909.90 | 36.41 | PASS |
| 3420.50† | 3255.01 | -354.93 | -895.02 | 3153.39 | 3255.01 | 5555.49 | -2344.35 | 346.22 | 6085.53 | 175.75 | 5909.77 | 35.41 | PASS |
| 3520.50† | 3348.46 | -368.05 | -928.10 | 3246.90 | 3348.46 | 5555.49 | -2344.35 | 346.55 | 6090.49 | 180.65 | 5909.84 | 34.45 | PASS |
| 3620.50† | 3441.91 | -381.17 | -961.19 | 3340.40 | 3441.91 | 5555.49 | -2344.35 | 346.89 | 6095.66 | 185.56 | 5910.10 | 33.55 | PASS |
| 3720.50† | 3535.36 | -394.29 | -994.28 | 3433.91 | 3535.36 | 5555.49 | -2344.35 | 347.22 | 6101.04 | 190.47 | 5910.56 | 32.69 | PASS |
| 3820.50† | 3628.81 | -407.41 | -1027.37 | 3527.42 | 3628.81 | 5555.49 | -2344.35 | 347.55 | 6106.61 | 195.40 | 5911.22 | 31.88 | PASS |
| 3920.50† | 3722.26 | -420.53 | -1060.45 | 3620.93 | 3722.26 | 5555.49 | -2344.35 | 347.88 | 6112.39 | 200.32 | 5912.06 | 31.11 | PASS |
| 4020.50† | 3815.71 | -433.66 | -1093.54 | 3714.44 | 3815.71 | 5555.49 | -2344.35 | 348.20 | 6118.37 | 205.26 | 5913.11 | 30.38 | PASS |
| 4120.50† | 3909.17 | -446.78 | -1126.63 | 3807.94 | 3909.17 | 5555.49 | -2344.35 | 348.53 | 6124.55 | 210.20 | 5914.35 | 29.68 | PASS |
| 4220.50† | 4002.62 | -459.90 | -1159.71 | 3901.45 | 4002.62 | 5555.49 | -2344.35 | 348.86 | 6130.93 | 215.14 | 5915.79 | 29.02 | PASS |
| 4320.50† | 4096.07 | -473.02 | -1192.80 | 3994.96 | 4096.07 | 5555.49 | -2344.35 | 349.19 | 6137.51 | 220.09 | 5917.42 | 28.38 | PASS |
| 4420.50† | 4189.52 | -486.14 | -1225.89 | 4088.47 | 4189.52 | 5555.49 | -2344.35 | 349.51 | 6144.29 | 225.05 | 5919.24 | 27.78 | PASS |
| 4520.50† | 4282.97 | -499.26 | -1258.97 | 4181.98 | 4282.97 | 5555.49 | -2344.35 | 349.84 | 6151.27 | 230.01 | 5921.26 | 27.20 | PASS |
| 4620.50† | 4376.42 | -512.38 | -1292.06 | 4275.48 | 4376.42 | 5555.49 | -2344.35 | 350.16 | 6158.44 | 234.97 | 5923.48 | 26.64 | PASS |
| 4720.50† | 4469.87 | -525.50 | -1325.15 | 4368.99 | 4469.87 | 5555.49 | -2344.35 | 350.49 | 6165.82 | 239.93 | 5925.88 | 26.12 | PASS |
| 4820.50† | 4563.32 | -538.62 | -1358.23 | 4462.50 | 4563.32 | 5555.49 | -2344.35 | 350.81 | 6173.38 | 244.90 | 5928.49 | 25.61 | PASS |
| 4920.50† | 4656.77 | -551.74 | -1391.32 | 4556.01 | 4656.77 | 5555.49 | -2344.35 | 351.13 | 6181.15 | 249.87 | 5931.28 | 25.12 | PASS |
| 5020.50† | 4750.22 | -564.87 | -1424.41 | 4649.52 | 4750.22 | 5555.49 | -2344.35 | 351.45 | 6189.11 | 254.84 | 5934.27 | 24.66 | PASS |
| 5120.50† | 4843.68 | -577.99 | -1457.49 | 4743.02 | 4843.68 | 5555.49 | -2344.35 | 351.77 | 6197.26 | 259.82 | 5937.44 | 24.21 | PASS |
| 5220.50† | 4937.13 | -591.11 | -1490.58 | 4836.53 | 4937.13 | 5555.49 | -2344.35 | 352.09 | 6205.61 | 264.80 | 5940.81 | 23.78 | PASS |
| 5320.50† | 5030.58 | -604.23 | -1523.67 | 4930.04 | 5030.58 | 5555.49 | -2344.35 | 352.41 | 6214.15 | 269.78 | 5944.37 | 23.36 | PASS |
| 5420.50† | 5124.03 | -617.35 | -1556.75 | 5023.55 | 5124.03 | 5555.49 | -2344.35 | 352.73 | 6222.88 | 274.76 | 5948.13 | 22.97 | PASS |
| 5520.50† | 5217.48 | -630.47 | -1589.84 | 5117.06 | 5217.48 | 5555.49 | -2344.35 | 353.05 | 6231.81 | 279.74 | 5952.06 | 22.58 | PASS |
| 5620.50† | 5310.93 | -643.59 | -1622.93 | 5210.56 | 5310.93 | 5555.49 | -2344.35 | 353.36 | 6240.92 | 284.73 | 5956.19 | 22.22 | PASS |
| 5720.50† | 5404.38 | -656.71 | -1656.01 | 5304.07 | 5404.38 | 5555.49 | -2344.35 | 353.68 | 6250.22 | 289.71 | 5960.51 | 21.86 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 6 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. NECKIEN 1 AWB Offset Wellpath: EX. NECKIEN 1 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#01 EX. NECKIEN 1 (1015'FSL & 1460'FEL, SI) Well: EX. NECKIEN 1 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|-----------------|-------------------|------------------|-------------------|--------------------|----------------------|---------------------|-------------------------|---------------------------|----------------------|----------------------------|--------------|----------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 5820.50† | 5497.83 | -669.83 | -1689.10 | 5397.58 | 5497.83 | 5555.49 | -2344.35 | 353.99 | 6259.71 | 294.70 | 5965.01 | 21.52 | PASS |
| 5920.50† | 5591.28 | -682.95 | -1722.19 | 5491.09 | 5591.28 | 5555.49 | -2344.35 | 354.31 | 6269.39 | 299.69 | 5969.70 | 21.19 | PASS |
| 6020.50† | 5684.74 | -696.07 | -1755.27 | 5584.60 | 5684.74 | 5555.49 | -2344.35 | 354.62 | 6279.26 | 304.68 | 5974.58 | 20.87 | PASS |
| 6120.50† | 5778.19 | -709.20 | -1788.36 | 5678.11 | 5778.19 | 5555.49 | -2344.35 | 354.93 | 6289.31 | 309.67 | 5979.64 | 20.56 | PASS |
| 6220.50† | 5871.64 | -722.32 | -1821.45 | 5771.61 | 5871.64 | 5555.49 | -2344.35 | 355.24 | 6299.55 | 314.66 | 5984.89 | 20.26 | PASS |
| 6320.50† | 5965.09 | -735.44 | -1854.54 | 5865.12 | 5965.09 | 5555.49 | -2344.35 | 355.55 | 6309.97 | 319.66 | 5990.31 | 19.98 | PASS |
| 6420.50† | 6058.54 | -748.56 | -1887.62 | 5958.63 | 6058.54 | 5555.49 | -2344.35 | 355.86 | 6320.57 | 324.65 | 5995.93 | 19.70 | PASS |
| 6520.50† | 6151.99 | -761.68 | -1920.71 | 6052.14 | 6151.99 | 5555.49 | -2344.35 | 356.16 | 6331.36 | 329.64 | 6001.72 | 19.43 | PASS |
| 6620.50† | 6245.44 | -774.80 | -1953.80 | 6145.65 | 6245.44 | 5555.49 | -2344.35 | 356.47 | 6342.33 | 334.64 | 6007.69 | 19.17 | PASS |
| 6720.50† | 6338.89 | -787.92 | -1986.88 | 6239.15 | 6338.89 | 5555.49 | -2344.35 | 356.78 | 6353.48 | 339.63 | 6013.85 | 18.92 | PASS |
| 6820.50† | 6432.34 | -801.04 | -2019.97 | 6332.66 | 6432.34 | 5555.49 | -2344.35 | 357.08 | 6364.81 | 344.63 | 6020.18 | 18.67 | PASS |
| 6920.50† | 6525.80 | -814.16 | -2053.06 | 6426.17 | 6525.80 | 5555.49 | -2344.35 | 357.38 | 6376.31 | 349.62 | 6026.69 | 18.44 | PASS |
| 7020.50† | 6619.25 | -827.28 | -2086.14 | 6519.68 | 6619.25 | 5555.49 | -2344.35 | 357.68 | 6388.00 | 354.62 | 6033.38 | 18.21 | PASS |
| 7120.50† | 6712.70 | -840.41 | -2119.23 | 6613.19 | 6712.70 | 5555.49 | -2344.35 | 357.98 | 6399.86 | 359.61 | 6040.24 | 17.98 | PASS |
| 7220.50† | 6806.15 | -853.53 | -2152.32 | 6706.69 | 6806.15 | 5555.49 | -2344.35 | 358.28 | 6411.89 | 364.61 | 6047.28 | 17.77 | PASS |
| 7320.50† | 6899.60 | -866.65 | -2185.40 | 6800.20 | 6899.60 | 5555.49 | -2344.35 | 358.58 | 6424.11 | 369.61 | 6054.50 | 17.56 | PASS |
| 7341.07 | 6918.82 | -869.35 | -2192.21 | 6819.43 | 6918.82 | 5555.49 | -2344.35 | 358.64 | 6426.64 | 370.63 | 6056.00 | 17.52 | PASS |
| 7420.50† | 6993.49 | -874.29 | -2218.65 | 6894.15 | 6993.49 | 5555.49 | -2344.35 | 358.88 | 6431.01 | 374.64 | 6056.37 | 17.34 | PASS |
| 7520.50† | 7087.21 | -864.88 | -2251.87 | 6987.93 | 7087.21 | 5555.49 | -2344.35 | 359.18 | 6421.04 | 379.73 | 6041.31 | 17.08 | PASS |
| 7620.50† | 7177.96 | -838.35 | -2284.05 | 7078.73 | 7177.96 | 5555.49 | -2344.35 | 359.46 | 6394.13 | 384.69 | 6009.44 | 16.79 | PASS |
| 7720.50† | 7262.97 | -795.51 | -2314.23 | 7163.80 | 7262.97 | 5555.49 | -2344.35 | 359.73 | 6351.07 | 389.29 | 5961.78 | 16.47 | PASS |
| 7820.50† | 7339.68 | -737.65 | -2341.49 | 7240.55 | 7339.68 | 5555.49 | -2344.35 | 359.97 | 6293.14 | 393.44 | 5899.70 | 16.15 | PASS |
| 7920.50† | 7405.75 | -666.53 | -2364.99 | 7306.66 | 7405.75 | 5555.49 | -2344.35 | 0.19 | 6222.05 | 397.00 | 5825.05 | 15.82 | PASS |
| 8020.50† | 7459.16 | -584.32 | -2384.03 | 7360.11 | 7459.16 | 5555.49 | -2344.35 | 0.37 | 6139.94 | 399.87 | 5740.06 | 15.50 | PASS |
| 8120.50† | 7498.30 | -493.50 | -2398.02 | 7399.27 | 7498.30 | 5555.49 | -2344.35 | 0.51 | 6049.23 | 401.97 | 5647.27 | 15.19 | PASS |
| 8220.50† | 7521.99 | -396.85 | -2406.55 | 7422.97 | 7521.99 | 5555.49 | -2344.35 | 0.60 | 5952.67 | 403.23 | 5549.44 | 14.90 | PASS |
| 8315.56 | 7529.50 | -302.24 | -2409.34 | 7430.49 | 7529.50 | 5555.49 | -2344.35 | 0.64 | 5858.09 | 403.63 | 5454.46 | 14.65 | PASS |
| 8320.50† | 7529.51 | -297.30 | -2409.35 | 7430.49 | 7529.51 | 5555.49 | -2344.35 | 0.64 | 5853.16 | 403.64 | 5449.52 | 14.64 | PASS |
| 8420.50† | 7529.61 | -197.30 | -2409.53 | 7430.59 | 7529.61 | 5555.49 | -2344.35 | 0.65 | 5753.16 | 403.65 | 5349.52 | 14.39 | PASS |
| 8520.50† | 7529.71 | -97.30 | -2409.71 | 7430.70 | 7529.71 | 5555.49 | -2344.35 | 0.66 | 5653.17 | 403.66 | 5249.51 | 14.13 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 7 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. NECKIEN 1 AWB Offset Wellpath: EX. NECKIEN 1 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#01 EX. NECKIEN 1 (1015'FSL & 1460'FEL, SI) Well: EX. NECKIEN 1 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 8620.50† | 7529.82 | 2.70 | -2409.88 | 7430.80 | 7529.82 | 5555.49 | -2344.35 | 0.68 | 5553.18 | 403.67 | 5149.51 | 13.88 | PASS | |
| 8720.50† | 7529.92 | 102.70 | -2410.06 | 7430.91 | 7529.92 | 5555.49 | -2344.35 | 0.69 | 5453.19 | 403.68 | 5049.51 | 13.63 | PASS | |
| 8820.50† | 7530.02 | 202.70 | -2410.24 | 7431.01 | 7530.02 | 5555.49 | -2344.35 | 0.71 | 5353.20 | 403.69 | 4949.51 | 13.38 | PASS | |
| 8920.50† | 7530.13 | 302.70 | -2410.42 | 7431.11 | 7530.13 | 5555.49 | -2344.35 | 0.72 | 5253.21 | 403.71 | 4849.50 | 13.13 | PASS | |
| 9020.50† | 7530.23 | 402.70 | -2410.59 | 7431.22 | 7530.23 | 5555.49 | -2344.35 | 0.74 | 5153.22 | 403.72 | 4749.50 | 12.88 | PASS | |
| 9120.50† | 7530.33 | 502.70 | -2410.77 | 7431.32 | 7530.33 | 5555.49 | -2344.35 | 0.75 | 5053.23 | 403.74 | 4649.50 | 12.63 | PASS | |
| 9220.50† | 7530.44 | 602.70 | -2410.95 | 7431.42 | 7530.44 | 5555.49 | -2344.35 | 0.77 | 4953.24 | 403.75 | 4549.49 | 12.38 | PASS | |
| 9320.50† | 7530.54 | 702.70 | -2411.13 | 7431.53 | 7530.54 | 5555.49 | -2344.35 | 0.79 | 4853.26 | 403.77 | 4449.49 | 12.13 | PASS | |
| 9420.50† | 7530.64 | 802.69 | -2411.31 | 7431.63 | 7530.64 | 5555.49 | -2344.35 | 0.81 | 4753.27 | 403.78 | 4349.49 | 11.88 | PASS | |
| 9520.50† | 7530.75 | 902.69 | -2411.48 | 7431.73 | 7530.75 | 5555.49 | -2344.35 | 0.83 | 4653.28 | 403.80 | 4249.48 | 11.63 | PASS | |
| 9620.50† | 7530.85 | 1002.69 | -2411.66 | 7431.84 | 7530.85 | 5555.49 | -2344.35 | 0.85 | 4553.29 | 403.81 | 4149.48 | 11.38 | PASS | |
| 9720.50† | 7530.96 | 1102.69 | -2411.84 | 7431.94 | 7530.96 | 5555.49 | -2344.35 | 0.87 | 4453.31 | 403.83 | 4049.48 | 11.13 | PASS | |
| 9820.50† | 7531.06 | 1202.69 | -2412.02 | 7432.05 | 7531.06 | 5555.49 | -2344.35 | 0.89 | 4353.32 | 403.85 | 3949.47 | 10.88 | PASS | |
| 9920.50† | 7531.16 | 1302.69 | -2412.19 | 7432.15 | 7531.16 | 5555.49 | -2344.35 | 0.91 | 4253.34 | 403.87 | 3849.47 | 10.63 | PASS | |
| 10020.50† | 7531.27 | 1402.69 | -2412.37 | 7432.25 | 7531.27 | 5555.49 | -2344.35 | 0.94 | 4153.36 | 403.89 | 3749.47 | 10.38 | PASS | |
| 10120.50† | 7531.37 | 1502.69 | -2412.55 | 7432.36 | 7531.37 | 5555.49 | -2344.35 | 0.96 | 4053.37 | 403.91 | 3649.46 | 10.13 | PASS | |
| 10220.50† | 7531.47 | 1602.69 | -2412.73 | 7432.46 | 7531.47 | 5555.49 | -2344.35 | 0.99 | 3953.39 | 403.93 | 3549.46 | 9.87 | PASS | |
| 10320.50† | 7531.58 | 1702.69 | -2412.90 | 7432.56 | 7531.58 | 5555.49 | -2344.35 | 1.02 | 3853.41 | 403.95 | 3449.46 | 9.62 | PASS | |
| 10420.50† | 7531.68 | 1802.69 | -2413.08 | 7432.67 | 7531.68 | 5555.49 | -2344.35 | 1.05 | 3753.43 | 403.98 | 3349.45 | 9.37 | PASS | |
| 10520.50† | 7531.78 | 1902.69 | -2413.26 | 7432.77 | 7531.78 | 5555.49 | -2344.35 | 1.08 | 3653.45 | 404.00 | 3249.45 | 9.12 | PASS | |
| 10620.50† | 7531.89 | 2002.69 | -2413.44 | 7432.88 | 7531.89 | 5555.49 | -2344.35 | 1.11 | 3553.47 | 404.02 | 3149.45 | 8.87 | PASS | |
| 10720.50† | 7531.99 | 2102.69 | -2413.62 | 7432.98 | 7531.99 | 5555.49 | -2344.35 | 1.15 | 3453.49 | 404.05 | 3049.44 | 8.62 | PASS | |
| 10820.50† | 7532.09 | 2202.69 | -2413.79 | 7433.08 | 7532.09 | 5555.49 | -2344.35 | 1.19 | 3353.52 | 404.08 | 2949.44 | 8.37 | PASS | |
| 10920.50† | 7532.20 | 2302.69 | -2413.97 | 7433.19 | 7532.20 | 5555.49 | -2344.35 | 1.23 | 3253.55 | 404.11 | 2849.44 | 8.12 | PASS | |
| 11020.50† | 7532.30 | 2402.69 | -2414.15 | 7433.29 | 7532.30 | 5555.49 | -2344.35 | 1.27 | 3153.57 | 404.14 | 2749.44 | 7.87 | PASS | |
| 11120.50† | 7532.41 | 2502.69 | -2414.33 | 7433.39 | 7532.41 | 5555.49 | -2344.35 | 1.31 | 3053.60 | 404.17 | 2649.43 | 7.62 | PASS | |
| 11220.50† | 7532.51 | 2602.69 | -2414.50 | 7433.50 | 7532.51 | 5555.49 | -2344.35 | 1.36 | 2953.63 | 404.20 | 2549.43 | 7.37 | PASS | |
| 11320.50† | 7532.61 | 2702.69 | -2414.68 | 7433.60 | 7532.61 | 5555.49 | -2344.35 | 1.41 | 2853.67 | 404.24 | 2449.43 | 7.12 | PASS | |
| 11420.50† | 7532.72 | 2802.69 | -2414.86 | 7433.70 | 7532.72 | 5555.49 | -2344.35 | 1.47 | 2753.70 | 404.27 | 2349.43 | 6.87 | PASS | |
| 11520.50† | 7532.82 | 2902.69 | -2415.04 | 7433.81 | 7532.82 | 5555.49 | -2344.35 | 1.53 | 2653.74 | 404.31 | 2249.43 | 6.62 | PASS | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 8 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. NECKIEN 1 AWB Offset Wellpath: EX. NECKIEN 1 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#01 EX. NECKIEN 1 (1015'FSL & 1460'FEL, SI) Well: EX. NECKIEN 1 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | |
| 11620.50† | 7532.92 | 3002.69 | -2415.21 | 7433.91 | 7532.92 | 5555.49 | -2344.35 | 1.59 | 2553.78 | 404.36 | 2149.43 | 6.37 | PASS | | |
| 11720.50† | 7533.03 | 3102.69 | -2415.39 | 7434.02 | 7533.03 | 5555.49 | -2344.35 | 1.66 | 2453.83 | 404.40 | 2049.43 | 6.12 | PASS | | |
| 11820.50† | 7533.13 | 3202.69 | -2415.57 | 7434.12 | 7533.13 | 5555.49 | -2344.35 | 1.73 | 2353.88 | 404.45 | 1949.43 | 5.87 | PASS | | |
| 11920.50† | 7533.23 | 3302.69 | -2415.75 | 7434.22 | 7533.23 | 5555.49 | -2344.35 | 1.82 | 2253.93 | 404.50 | 1849.43 | 5.62 | PASS | | |
| 12020.50† | 7533.34 | 3402.69 | -2415.92 | 7434.33 | 7533.34 | 5555.49 | -2344.35 | 1.90 | 2153.99 | 404.55 | 1749.44 | 5.37 | PASS | | |
| 12120.50† | 7533.44 | 3502.69 | -2416.10 | 7434.43 | 7533.44 | 5555.49 | -2344.35 | 2.00 | 2054.06 | 404.61 | 1649.44 | 5.12 | PASS | | |
| 12220.50† | 7533.55 | 3602.69 | -2416.28 | 7434.53 | 7533.55 | 5555.49 | -2344.35 | 2.11 | 1954.13 | 404.68 | 1549.45 | 4.87 | PASS | | |
| 12320.50† | 7533.65 | 3702.69 | -2416.46 | 7434.64 | 7533.65 | 5555.49 | -2344.35 | 2.23 | 1854.21 | 404.75 | 1449.46 | 4.62 | PASS | | |
| 12420.50† | 7533.75 | 3802.69 | -2416.64 | 7434.74 | 7533.75 | 5555.49 | -2344.35 | 2.36 | 1754.29 | 404.83 | 1349.47 | 4.37 | PASS | | |
| 12520.50† | 7533.86 | 3902.69 | -2416.81 | 7434.84 | 7533.86 | 5555.49 | -2344.35 | 2.51 | 1654.39 | 404.91 | 1249.48 | 4.12 | PASS | | |
| 12620.50† | 7533.96 | 4002.69 | -2416.99 | 7434.95 | 7533.96 | 5555.49 | -2344.35 | 2.68 | 1554.50 | 405.01 | 1149.49 | 3.87 | PASS | | |
| 12720.50† | 7534.06 | 4102.69 | -2417.17 | 7435.05 | 7534.06 | 5555.49 | -2344.35 | 2.87 | 1454.63 | 405.12 | 1049.51 | 3.62 | PASS | | |
| 12820.50† | 7534.17 | 4202.69 | -2417.35 | 7435.16 | 7534.17 | 5555.49 | -2344.35 | 3.09 | 1354.77 | 405.24 | 949.53 | 3.37 | PASS | | |
| 12920.50† | 7534.27 | 4302.69 | -2417.52 | 7435.26 | 7534.27 | 5555.49 | -2344.35 | 3.34 | 1254.94 | 405.38 | 849.56 | 3.12 | PASS | | |
| 13020.50† | 7534.37 | 4402.69 | -2417.70 | 7435.36 | 7534.37 | 5555.49 | -2344.35 | 3.64 | 1155.14 | 405.55 | 749.59 | 2.87 | PASS | | |
| 13120.50† | 7534.48 | 4502.69 | -2417.88 | 7435.47 | 7534.48 | 5555.49 | -2344.35 | 4.00 | 1055.37 | 405.74 | 649.63 | 2.62 | PASS | | |
| 13199.97 | 7534.56 | 4582.16 | -2418.02 | 7435.55 | 7534.56 | 5555.49 | -2344.35 | 4.33 | 976.12 | 405.92 | 570.19 | 2.42 | PASS | | |
| 13220.50† | 7534.58 | 4602.69 | -2418.13 | 7435.57 | 7534.58 | 5555.49 | -2344.35 | 4.43 | 955.66 | 405.98 | 549.68 | 2.37 | PASS | | |
| 13320.50† | 7534.68 | 4702.65 | -2420.77 | 7435.67 | 7534.68 | 5555.49 | -2344.35 | 5.12 | 856.26 | 406.35 | 449.91 | 2.12 | PASS | | |
| 13420.50† | 7534.79 | 4802.45 | -2426.90 | 7435.78 | 7534.79 | 5555.49 | -2344.35 | 6.26 | 757.55 | 406.97 | 350.58 | 1.87 | PASS | | |
| 13476.50 | 7534.85 | 4858.23 | -2431.85 | 7435.83 | 7534.85 | 5555.49 | -2344.35 | 7.15 | 702.72 | 407.47 | 295.26 | 1.73 | PASS | | |
| 13520.50† | 7534.89 | 4902.02 | -2436.16 | 7435.88 | 7534.89 | 5555.49 | -2344.35 | 8.00 | 659.89 | 407.94 | 251.95 | 1.62 | PASS | | |
| 13620.50† | 7534.99 | 5001.54 | -2445.98 | 7435.98 | 7534.99 | 5555.49 | -2344.35 | 10.40 | 563.20 | 409.31 | 153.89 | 1.38 | PASS | | |
| 13720.50† | 7535.10 | 5101.06 | -2455.79 | 7436.08 | 7535.10 | 5555.49 | -2344.35 | 13.78 | 467.90 | 411.31 | 56.59 | 1.14 | PASS | | |
| 13820.50† | 7535.20 | 5200.57 | -2465.61 | 7436.19 | 7535.20 | 5555.49 | -2344.35 | 18.86 | 375.06 | 414.40 | -39.34 | 0.90 | FAIL | | |
| 13920.50† | 7535.30 | 5300.09 | -2475.42 | 7436.29 | 7535.30 | 5555.49 | -2344.35 | 27.17 | 287.07 | 419.45 | -132.38 | 0.68 | FAIL | | |
| 14020.50† | 7535.40 | 5399.61 | -2485.24 | 7436.39 | 7535.40 | 5555.49 | -2344.35 | 42.11 | 210.11 | 427.37 | -217.26 | 0.49 | FAIL | | |
| 14120.50† | 7535.51 | 5499.12 | -2495.05 | 7436.50 | 7535.51 | 5555.49 | -2344.35 | 69.49 | 160.89 | 432.95 | -272.05 | 0.37 | FAIL | | |
| 14155.54† | 7535.54 | 5533.99 | -2498.49 | 7436.53 | 7535.54 | 5555.49 | -2344.35 | 82.06 | 155.63 | 430.57 | -274.94 | 0.36 | FAIL | | |
| 14161.81† | 7535.55 | 5540.23 | -2499.11 | 7436.54 | 7535.55 | 5555.49 | -2344.35 | 84.37 | 155.50 | 429.82 | -274.31 | 0.36 | FAIL | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 9 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. NECKIEN 1 AWP Offset Wellpath: EX. NECKIEN 1 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#01 EX. NECKIEN 1 (1015'FSL & 1460'FEL, SI) Well: EX. NECKIEN 1 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 14220.50† | 7535.61 | 5598.64 | -2504.87 | 7436.60 | 7535.61 | 5555.49 | -2344.35 | 105.05 | 166.21 | 419.71 | -253.50 | 0.39 | FAIL |
| 14221.87 | 7535.61 | 5600.00 | -2505.00 | 7436.60 | 7535.61 | 5555.49 | -2344.35 | 105.49 | 166.70 | 419.45 | -252.75 | 0.39 | FAIL |
| 14320.50† | 7535.71 | 5698.31 | -2512.99 | 7436.70 | 7535.71 | 5555.49 | -2344.35 | 130.26 | 220.98 | 405.07 | -184.08 | 0.54 | FAIL |
| 14420.50† | 7535.81 | 5798.19 | -2517.63 | 7436.80 | 7535.81 | 5555.49 | -2344.35 | 144.48 | 298.21 | 399.65 | -101.44 | 0.74 | FAIL |
| 14520.50† | 7535.92 | 5898.18 | -2518.78 | 7436.91 | 7535.92 | 5555.49 | -2344.35 | 153.02 | 384.53 | 398.26 | -13.74 | 0.97 | FAIL |
| 14581.38 | 7535.98 | 5959.05 | -2517.77 | 7436.97 | 7535.98 | 5555.49 | -2344.35 | 156.75 | 439.24 | 398.16 | 41.08 | 1.10 | PASS |
| 14620.50† | 7536.02 | 5998.16 | -2516.71 | 7437.01 | 7536.02 | 5555.49 | -2344.35 | 158.73 | 475.04 | 398.24 | 76.80 | 1.19 | PASS |
| 14720.50† | 7536.12 | 6098.12 | -2513.99 | 7437.11 | 7536.12 | 5555.49 | -2344.35 | 162.64 | 568.53 | 398.64 | 169.88 | 1.43 | PASS |
| 14820.50† | 7536.23 | 6198.08 | -2511.27 | 7437.22 | 7536.23 | 5555.49 | -2344.35 | 165.44 | 663.92 | 399.14 | 264.77 | 1.67 | PASS |
| 14920.50† | 7536.33 | 6298.05 | -2508.55 | 7437.32 | 7536.33 | 5555.49 | -2344.35 | 167.53 | 760.49 | 399.63 | 360.86 | 1.91 | PASS |
| 15020.50† | 7536.43 | 6398.01 | -2505.83 | 7437.42 | 7536.43 | 5555.49 | -2344.35 | 169.15 | 857.85 | 400.07 | 457.78 | 2.16 | PASS |
| 15120.50† | 7536.54 | 6497.97 | -2503.11 | 7437.53 | 7536.54 | 5555.49 | -2344.35 | 170.44 | 955.76 | 400.47 | 555.29 | 2.40 | PASS |
| 15220.50† | 7536.64 | 6597.93 | -2500.40 | 7437.63 | 7536.64 | 5555.49 | -2344.35 | 171.49 | 1054.06 | 400.81 | 653.24 | 2.65 | PASS |
| 15320.50† | 7536.74 | 6697.90 | -2497.68 | 7437.74 | 7536.74 | 5555.49 | -2344.35 | 172.36 | 1152.65 | 401.12 | 751.53 | 2.89 | PASS |
| 15420.50† | 7536.85 | 6797.86 | -2494.96 | 7437.84 | 7536.85 | 5555.49 | -2344.35 | 173.09 | 1251.46 | 401.39 | 850.07 | 3.14 | PASS |
| 15520.50† | 7536.95 | 6897.82 | -2492.24 | 7437.94 | 7536.95 | 5555.49 | -2344.35 | 173.71 | 1350.45 | 401.63 | 948.82 | 3.39 | PASS |
| 15620.50† | 7537.05 | 6997.79 | -2489.52 | 7438.05 | 7537.05 | 5555.49 | -2344.35 | 174.25 | 1449.58 | 401.85 | 1047.73 | 3.63 | PASS |
| 15720.50† | 7537.16 | 7097.75 | -2486.80 | 7438.15 | 7537.16 | 5555.49 | -2344.35 | 174.72 | 1548.82 | 402.05 | 1146.77 | 3.88 | PASS |
| 15820.50† | 7537.26 | 7197.71 | -2484.08 | 7438.25 | 7537.26 | 5555.49 | -2344.35 | 175.14 | 1648.15 | 402.23 | 1245.93 | 4.13 | PASS |
| 15920.50† | 7537.36 | 7297.68 | -2481.36 | 7438.36 | 7537.36 | 5555.49 | -2344.35 | 175.50 | 1747.56 | 402.39 | 1345.17 | 4.38 | PASS |
| 16020.50† | 7537.47 | 7397.64 | -2478.64 | 7438.46 | 7537.47 | 5555.49 | -2344.35 | 175.83 | 1847.04 | 402.54 | 1444.49 | 4.62 | PASS |
| 16120.50† | 7537.57 | 7497.60 | -2475.93 | 7438.56 | 7537.57 | 5555.49 | -2344.35 | 176.12 | 1946.56 | 402.68 | 1543.88 | 4.87 | PASS |
| 16220.50† | 7537.68 | 7597.56 | -2473.21 | 7438.67 | 7537.68 | 5555.49 | -2344.35 | 176.39 | 2046.13 | 402.81 | 1643.33 | 5.12 | PASS |
| 16320.50† | 7537.78 | 7697.53 | -2470.49 | 7438.77 | 7537.78 | 5555.49 | -2344.35 | 176.63 | 2145.75 | 402.93 | 1742.82 | 5.37 | PASS |
| 16420.50† | 7537.88 | 7797.49 | -2467.77 | 7438.87 | 7537.88 | 5555.49 | -2344.35 | 176.85 | 2245.39 | 403.04 | 1842.35 | 5.62 | PASS |
| 16520.50† | 7537.99 | 7897.45 | -2465.05 | 7438.98 | 7537.99 | 5555.49 | -2344.35 | 177.05 | 2345.07 | 403.14 | 1941.93 | 5.87 | PASS |
| 16620.50† | 7538.09 | 7997.42 | -2462.33 | 7439.08 | 7538.09 | 5555.49 | -2344.35 | 177.23 | 2444.77 | 403.24 | 2041.53 | 6.11 | PASS |
| 16720.50† | 7538.19 | 8097.38 | -2459.61 | 7439.18 | 7538.19 | 5555.49 | -2344.35 | 177.40 | 2544.50 | 403.34 | 2141.16 | 6.36 | PASS |
| 16820.50† | 7538.30 | 8197.34 | -2456.89 | 7439.29 | 7538.30 | 5555.49 | -2344.35 | 177.56 | 2644.25 | 403.42 | 2240.82 | 6.61 | PASS |
| 16920.50† | 7538.40 | 8297.31 | -2454.17 | 7439.39 | 7538.40 | 5555.49 | -2344.35 | 177.71 | 2744.01 | 403.51 | 2340.50 | 6.86 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 10 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. NECKIEN 1 AWB Offset Wellpath: EX. NECKIEN 1 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#01 EX. NECKIEN 1 (1015'FSL & 1460'FEL, SI) Well: EX. NECKIEN 1 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 17020.50† | 7538.50 | 8397.27 | -2451.46 | 7439.49 | 7538.50 | 5555.49 | -2344.35 | 177.84 | 2843.79 | 403.59 | 2440.20 | 7.11 | PASS |
| 17120.50† | 7538.61 | 8497.23 | -2448.74 | 7439.60 | 7538.61 | 5555.49 | -2344.35 | 177.97 | 2943.59 | 403.67 | 2539.92 | 7.35 | PASS |
| 17220.50† | 7538.71 | 8597.19 | -2446.02 | 7439.70 | 7538.71 | 5555.49 | -2344.35 | 178.09 | 3043.40 | 403.74 | 2639.66 | 7.60 | PASS |
| 17320.50† | 7538.81 | 8697.16 | -2443.30 | 7439.80 | 7538.81 | 5555.49 | -2344.35 | 178.20 | 3143.22 | 403.81 | 2739.41 | 7.85 | PASS |
| 17420.50† | 7538.92 | 8797.12 | -2440.58 | 7439.91 | 7538.92 | 5555.49 | -2344.35 | 178.30 | 3243.06 | 403.88 | 2839.18 | 8.10 | PASS |
| 17520.50† | 7539.02 | 8897.08 | -2437.86 | 7440.01 | 7539.02 | 5555.49 | -2344.35 | 178.40 | 3342.90 | 403.94 | 2938.96 | 8.35 | PASS |
| 17620.50† | 7539.12 | 8997.05 | -2435.14 | 7440.11 | 7539.12 | 5555.49 | -2344.35 | 178.49 | 3442.75 | 404.01 | 3038.74 | 8.60 | PASS |
| 17720.50† | 7539.23 | 9097.01 | -2432.42 | 7440.22 | 7539.23 | 5555.49 | -2344.35 | 178.58 | 3542.61 | 404.07 | 3138.54 | 8.84 | PASS |
| 17820.50† | 7539.33 | 9196.97 | -2429.70 | 7440.32 | 7539.33 | 5555.49 | -2344.35 | 178.66 | 3642.48 | 404.13 | 3238.35 | 9.09 | PASS |
| 17920.50† | 7539.43 | 9296.94 | -2426.99 | 7440.42 | 7539.43 | 5555.49 | -2344.35 | 178.74 | 3742.36 | 404.19 | 3338.17 | 9.34 | PASS |
| 17985.90 | 7539.50 | 9362.31 | -2425.21 | 7440.49 | 7539.50 | 5555.49 | -2344.35 | 178.78 | 3807.67 | 404.22 | 3403.45 | 9.50 | PASS |

POSITIONAL UNCERTAINTY - Offset Wellbore: EX. NECKIEN 1 AWB Offset Wellpath: EX. NECKIEN 1 AWP

| | | | | |
|-----------------------------------|------------|---------|----------|---------|
| Slot Surface Uncertainty @1SD | Horizontal | 0.100ft | Vertical | 1.000ft |
| Facility Surface Uncertainty @1SD | Horizontal | 8.200ft | Vertical | 3.000ft |

WELLPATH COMPOSITION - Offset Wellbore: EX. NECKIEN 1 AWB Offset Wellpath: EX. NECKIEN 1 AWP

| Start MD [ft] | End MD [ft] | Positional Uncertainty Model | Log Name/Comment | Wellbore | Survey Date |
|---------------|-------------|---|--|-------------------|-------------|
| 0.00 | 8061.00 | BH Drift Indicator - Inclination Only (Actual Survey) | ASSUMED VERTICAL TO TD FROM COGCC <8061> | EX. NECKIEN 1 AWB | |

OFFSET WELLPATH REFERENCE - Offset Wellbore: EX. NECKIEN 1 AWB Offset Wellpath: EX. NECKIEN 1 AWP

| | |
|---|---|
| MD Reference: Rig on SLOT#01 EX. NECKIEN 1 (1015'FSL & 1460'FEL, SI) (RT) | Offset TVD & local coordinates use Reference Wellpath settings (See WELLPATH DATUM on page 1 of this report) |
| Ellipse Start MD | 0.00ft |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 11 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: JORDAN 34-9 AWB Offset Wellpath: JORDAN 34-9 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.34-T01N-R65W | | Slot: SLOT#01 EX JORDAN 34-9 (600'FSL & 600'FWL, SEC.34) (PA) | | Well: JORDAN 34-9 | | Threshold Value=1.00 | | ↑ = interpolated, ‡ = extrapolated station | | | | | |
|----------------------------|--------------|---|---------------|-------------------|-----------------|----------------------|------------------|--|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 20.50 | 20.50 | 0.00 | 0.00 | 0.00 | 20.50 | -149.36 | -245.14 | 238.65 | 287.05 | 54.03 | 233.03 | 5.66 | PASS |
| 120.50† | 120.50 | 0.00 | 0.00 | 100.00 | 120.50 | -149.36 | -245.14 | 238.65 | 287.05 | 55.97 | 231.09 | 5.45 | PASS |
| 200.00 | 200.00 | 0.00 | 0.00 | 179.50 | 200.00 | -149.36 | -245.14 | 238.65 | 287.05 | 57.54 | 229.51 | 5.29 | PASS |
| 220.50† | 220.50 | -0.03 | -0.07 | 200.00 | 220.50 | -149.36 | -245.14 | 238.64 | 286.98 | 57.95 | 229.03 | 5.24 | PASS |
| 320.50† | 320.46 | -0.93 | -2.36 | 299.96 | 320.46 | -149.36 | -245.14 | 238.56 | 284.55 | 59.97 | 224.58 | 5.01 | PASS |
| 420.50† | 420.28 | -3.13 | -7.88 | 399.78 | 420.28 | -149.36 | -245.14 | 238.35 | 278.70 | 62.06 | 216.64 | 4.73 | PASS |
| 520.50† | 519.83 | -6.60 | -16.65 | 499.33 | 519.83 | -149.36 | -245.14 | 238.00 | 269.42 | 64.16 | 205.26 | 4.41 | PASS |
| 620.50† | 618.99 | -11.36 | -28.64 | 598.49 | 618.99 | -149.36 | -245.14 | 237.49 | 256.74 | 66.28 | 190.46 | 4.06 | PASS |
| 720.50† | 717.64 | -17.38 | -43.83 | 697.14 | 717.64 | -149.36 | -245.14 | 236.75 | 240.71 | 68.41 | 172.29 | 3.67 | PASS |
| 820.50† | 815.66 | -24.68 | -62.22 | 795.16 | 815.66 | -149.36 | -245.14 | 235.72 | 221.37 | 70.55 | 150.82 | 3.27 | PASS |
| 920.50† | 912.93 | -33.22 | -83.78 | 892.43 | 912.93 | -149.36 | -245.14 | 234.26 | 198.80 | 72.69 | 126.11 | 2.84 | PASS |
| 1020.50† | 1009.33 | -43.02 | -108.48 | 988.83 | 1009.33 | -149.36 | -245.14 | 232.11 | 173.15 | 74.82 | 98.33 | 2.39 | PASS |
| 1120.50† | 1104.74 | -54.05 | -136.29 | 1084.24 | 1104.74 | -149.36 | -245.14 | 228.79 | 144.67 | 76.95 | 67.72 | 1.93 | PASS |
| 1220.50† | 1199.05 | -66.30 | -167.18 | 1178.55 | 1199.05 | -149.36 | -245.14 | 223.18 | 113.91 | 79.07 | 34.84 | 1.46 | PASS |
| 1242.54 | 1219.68 | -69.16 | -174.40 | 1199.18 | 1219.68 | -149.36 | -245.14 | 221.41 | 106.93 | 79.54 | 27.40 | 1.36 | PASS |
| 1320.50† | 1292.54 | -79.39 | -200.20 | 1272.04 | 1292.54 | -149.36 | -245.14 | 212.71 | 83.16 | 81.18 | 1.98 | 1.03 | WARN |
| 1420.50† | 1385.99 | -92.51 | -233.28 | 1365.49 | 1385.99 | -149.36 | -245.14 | 191.78 | 58.07 | 83.34 | -25.27 | 0.68 | FAIL |
| 1510.33† | 1469.93 | -104.30 | -263.00 | 1449.43 | 1469.93 | -149.36 | -245.14 | 158.37 | 48.47 | 85.32 | -36.85 | 0.55 | FAIL |
| 1514.88† | 1474.19 | -104.89 | -264.51 | 1453.69 | 1474.19 | -149.36 | -245.14 | 156.46 | 48.50 | 85.42 | -36.92 | 0.55 | FAIL |
| 1520.50† | 1479.44 | -105.63 | -266.37 | 1458.94 | 1479.44 | -149.36 | -245.14 | 154.10 | 48.61 | 85.54 | -36.93 | 0.55 | FAIL |
| 1620.50† | 1572.89 | -118.75 | -299.46 | 1552.39 | 1572.89 | -149.36 | -245.14 | 119.40 | 62.35 | 87.59 | -25.24 | 0.70 | FAIL |
| 1720.50† | 1666.34 | -131.87 | -332.54 | 1645.84 | 1666.34 | -149.36 | -245.14 | 101.31 | 89.14 | 89.60 | -0.46 | 0.99 | FAIL |
| 1820.50† | 1759.79 | -144.99 | -365.63 | 1739.29 | 1759.79 | -149.36 | -245.14 | 92.07 | 120.57 | 91.65 | 28.93 | 1.33 | PASS |
| 1920.50† | 1853.24 | -158.12 | -398.72 | 1832.74 | 1853.24 | -149.36 | -245.14 | 86.74 | 153.83 | 93.72 | 60.11 | 1.67 | PASS |
| 2020.50† | 1946.69 | -171.24 | -431.80 | 1926.19 | 1946.69 | -149.36 | -245.14 | 83.32 | 187.95 | 95.80 | 92.14 | 2.00 | PASS |
| 2120.50† | 2040.14 | -184.36 | -464.89 | 2019.64 | 2040.14 | -149.36 | -245.14 | 80.95 | 222.52 | 97.91 | 124.62 | 2.33 | PASS |
| 2220.50† | 2133.59 | -197.48 | -497.98 | 2113.09 | 2133.59 | -149.36 | -245.14 | 79.22 | 257.38 | 100.02 | 157.36 | 2.64 | PASS |
| 2320.50† | 2227.05 | -210.60 | -531.06 | 2206.55 | 2227.05 | -149.36 | -245.14 | 77.91 | 292.41 | 102.15 | 190.27 | 2.94 | PASS |
| 2420.50† | 2320.50 | -223.72 | -564.15 | 2300.00 | 2320.50 | -149.36 | -245.14 | 76.88 | 327.57 | 104.28 | 223.29 | 3.23 | PASS |
| 2520.50† | 2413.95 | -236.84 | -597.24 | 2393.45 | 2413.95 | -149.36 | -245.14 | 76.05 | 362.81 | 106.42 | 256.38 | 3.50 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 12 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: JORDAN 34-9 AWB Offset Wellpath: JORDAN 34-9 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.34-T01N-R65W Slot: SLOT#01 EX JORDAN 34-9 (600'FSL & 600'FWL, SEC.34) (PA) | | | | | | Well: JORDAN 34-9 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | Sep Ratio | Rule Status |
|--|--------------|----------------|---------------|----------------|-----------------|---|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | | |
| 2620.50† | 2507.40 | -249.96 | -630.32 | 2486.90 | 2507.40 | -149.36 | -245.14 | 75.36 | 398.11 | 108.57 | 289.54 | 3.77 | PASS |
| 2720.50† | 2600.85 | -263.08 | -663.41 | 2580.35 | 2600.85 | -149.36 | -245.14 | 74.79 | 433.46 | 110.73 | 322.73 | 4.02 | PASS |
| 2820.50† | 2694.30 | -276.20 | -696.50 | 2673.80 | 2694.30 | -149.36 | -245.14 | 74.30 | 468.85 | 112.90 | 355.95 | 4.27 | PASS |
| 2920.50† | 2787.75 | -289.33 | -729.58 | 2767.25 | 2787.75 | -149.36 | -245.14 | 73.89 | 504.26 | 115.07 | 389.19 | 4.50 | PASS |
| 3020.50† | 2881.20 | -302.45 | -762.67 | 2860.70 | 2881.20 | -149.36 | -245.14 | 73.52 | 539.70 | 117.25 | 422.46 | 4.73 | PASS |
| 3120.50† | 2974.65 | -315.57 | -795.76 | 2954.15 | 2974.65 | -149.36 | -245.14 | 73.20 | 575.16 | 119.43 | 455.73 | 4.95 | PASS |
| 3220.50† | 3068.11 | -328.69 | -828.84 | 3047.61 | 3068.11 | -149.36 | -245.14 | 72.92 | 610.64 | 121.62 | 489.01 | 5.16 | PASS |
| 3320.50† | 3161.56 | -341.81 | -861.93 | 3141.06 | 3161.56 | -149.36 | -245.14 | 72.67 | 646.12 | 123.82 | 522.31 | 5.36 | PASS |
| 3420.50† | 3255.01 | -354.93 | -895.02 | 3234.51 | 3255.01 | -149.36 | -245.14 | 72.45 | 681.62 | 126.01 | 555.61 | 5.55 | PASS |
| 3520.50† | 3348.46 | -368.05 | -928.10 | 3327.96 | 3348.46 | -149.36 | -245.14 | 72.24 | 717.13 | 128.22 | 588.91 | 5.74 | PASS |
| 3620.50† | 3441.91 | -381.17 | -961.19 | 3421.41 | 3441.91 | -149.36 | -245.14 | 72.06 | 752.65 | 130.43 | 622.22 | 5.92 | PASS |
| 3720.50† | 3535.36 | -394.29 | -994.28 | 3514.86 | 3535.36 | -149.36 | -245.14 | 71.90 | 788.17 | 132.64 | 655.53 | 6.10 | PASS |
| 3820.50† | 3628.81 | -407.41 | -1027.37 | 3608.31 | 3628.81 | -149.36 | -245.14 | 71.74 | 823.70 | 134.85 | 688.84 | 6.26 | PASS |
| 3920.50† | 3722.26 | -420.53 | -1060.45 | 3701.76 | 3722.26 | -149.36 | -245.14 | 71.60 | 859.23 | 137.07 | 722.16 | 6.43 | PASS |
| 4020.50† | 3815.71 | -433.66 | -1093.54 | 3795.21 | 3815.71 | -149.36 | -245.14 | 71.47 | 894.77 | 139.30 | 755.48 | 6.58 | PASS |
| 4120.50† | 3909.17 | -446.78 | -1126.63 | 3888.67 | 3909.17 | -149.36 | -245.14 | 71.36 | 930.31 | 141.52 | 788.79 | 6.74 | PASS |
| 4220.50† | 4002.62 | -459.90 | -1159.71 | 3982.12 | 4002.62 | -149.36 | -245.14 | 71.25 | 965.86 | 143.75 | 822.11 | 6.88 | PASS |
| 4320.50† | 4096.07 | -473.02 | -1192.80 | 4075.57 | 4096.07 | -149.36 | -245.14 | 71.14 | 1001.41 | 145.98 | 855.43 | 7.02 | PASS |
| 4420.50† | 4189.52 | -486.14 | -1225.89 | 4169.02 | 4189.52 | -149.36 | -245.14 | 71.05 | 1036.96 | 148.22 | 888.75 | 7.16 | PASS |
| 4520.50† | 4282.97 | -499.26 | -1258.97 | 4262.47 | 4282.97 | -149.36 | -245.14 | 70.96 | 1072.52 | 150.46 | 922.06 | 7.30 | PASS |
| 4620.50† | 4376.42 | -512.38 | -1292.06 | 4355.92 | 4376.42 | -149.36 | -245.14 | 70.88 | 1108.08 | 152.70 | 955.38 | 7.42 | PASS |
| 4720.50† | 4469.87 | -525.50 | -1325.15 | 4449.37 | 4469.87 | -149.36 | -245.14 | 70.80 | 1143.64 | 154.94 | 988.70 | 7.55 | PASS |
| 4820.50† | 4563.32 | -538.62 | -1358.23 | 4542.82 | 4563.32 | -149.36 | -245.14 | 70.72 | 1179.20 | 157.19 | 1022.02 | 7.67 | PASS |
| 4920.50† | 4656.77 | -551.74 | -1391.32 | 4636.27 | 4656.77 | -149.36 | -245.14 | 70.66 | 1214.77 | 159.43 | 1055.33 | 7.79 | PASS |
| 5020.50† | 4750.22 | -564.87 | -1424.41 | 4729.72 | 4750.22 | -149.36 | -245.14 | 70.59 | 1250.33 | 161.68 | 1088.65 | 7.90 | PASS |
| 5120.50† | 4843.68 | -577.99 | -1457.49 | 4823.18 | 4843.68 | -149.36 | -245.14 | 70.53 | 1285.90 | 163.93 | 1121.96 | 8.01 | PASS |
| 5220.50† | 4937.13 | -591.11 | -1490.58 | 4916.63 | 4937.13 | -149.36 | -245.14 | 70.47 | 1321.47 | 166.19 | 1155.28 | 8.12 | PASS |
| 5320.50† | 5030.58 | -604.23 | -1523.67 | 5010.08 | 5030.58 | -149.36 | -245.14 | 70.42 | 1357.04 | 168.44 | 1188.59 | 8.23 | PASS |
| 5420.50† | 5124.03 | -617.35 | -1556.75 | 5103.53 | 5124.03 | -149.36 | -245.14 | 70.36 | 1392.61 | 170.70 | 1221.91 | 8.33 | PASS |
| 5520.50† | 5217.48 | -630.47 | -1589.84 | 5196.98 | 5217.48 | -149.36 | -245.14 | 70.31 | 1428.18 | 173.33 | 1254.86 | 8.41 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 13 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: JORDAN 34-9 AWB Offset Wellpath: JORDAN 34-9 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.34-T01N-R65W Slot: SLOT#01 EX JORDAN 34-9 (600'FSL & 600'FWL, SEC.34) (PA) | | | | | | Well: JORDAN 34-9 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | Sep Ratio | Rule Status |
|--|--------------|----------------|---------------|----------------|-----------------|---|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | | |
| 5620.50† | 5310.93 | -643.59 | -1622.93 | 5290.43 | 5310.93 | -149.36 | -245.14 | 70.27 | 1463.76 | 176.15 | 1287.60 | 8.48 | PASS |
| 5720.50† | 5404.38 | -656.71 | -1656.01 | 5383.88 | 5404.38 | -149.36 | -245.14 | 70.22 | 1499.33 | 178.98 | 1320.35 | 8.54 | PASS |
| 5820.50† | 5497.83 | -669.83 | -1689.10 | 5477.33 | 5497.83 | -149.36 | -245.14 | 70.18 | 1534.91 | 181.81 | 1353.09 | 8.61 | PASS |
| 5920.50† | 5591.28 | -682.95 | -1722.19 | 5570.78 | 5591.28 | -149.36 | -245.14 | 70.14 | 1570.48 | 184.65 | 1385.83 | 8.67 | PASS |
| 6020.50† | 5684.74 | -696.07 | -1755.27 | 5664.24 | 5684.74 | -149.36 | -245.14 | 70.10 | 1606.06 | 187.48 | 1418.58 | 8.73 | PASS |
| 6120.50† | 5778.19 | -709.20 | -1788.36 | 5757.69 | 5778.19 | -149.36 | -245.14 | 70.06 | 1641.64 | 190.32 | 1451.32 | 8.79 | PASS |
| 6220.50† | 5871.64 | -722.32 | -1821.45 | 5851.14 | 5871.64 | -149.36 | -245.14 | 70.03 | 1677.21 | 193.16 | 1484.06 | 8.85 | PASS |
| 6320.50† | 5965.09 | -735.44 | -1854.54 | 5944.59 | 5965.09 | -149.36 | -245.14 | 69.99 | 1712.79 | 195.99 | 1516.80 | 8.90 | PASS |
| 6420.50† | 6058.54 | -748.56 | -1887.62 | 6038.04 | 6058.54 | -149.36 | -245.14 | 69.96 | 1748.37 | 198.84 | 1549.54 | 8.95 | PASS |
| 6520.50† | 6151.99 | -761.68 | -1920.71 | 6131.49 | 6151.99 | -149.36 | -245.14 | 69.93 | 1783.95 | 201.68 | 1582.28 | 9.00 | PASS |
| 6620.50† | 6245.44 | -774.80 | -1953.80 | 6224.94 | 6245.44 | -149.36 | -245.14 | 69.90 | 1819.53 | 204.52 | 1615.01 | 9.05 | PASS |
| 6720.50† | 6338.89 | -787.92 | -1986.88 | 6318.39 | 6338.89 | -149.36 | -245.14 | 69.87 | 1855.11 | 207.36 | 1647.75 | 9.10 | PASS |
| 6820.50† | 6432.34 | -801.04 | -2019.97 | 6411.84 | 6432.34 | -149.36 | -245.14 | 69.84 | 1890.70 | 210.21 | 1680.49 | 9.15 | PASS |
| 6920.50† | 6525.80 | -814.16 | -2053.06 | 6505.30 | 6525.80 | -149.36 | -245.14 | 69.81 | 1926.28 | 213.06 | 1713.22 | 9.19 | PASS |
| 7020.50† | 6619.25 | -827.28 | -2086.14 | 6598.75 | 6619.25 | -149.36 | -245.14 | 69.78 | 1961.86 | 215.90 | 1745.96 | 9.24 | PASS |
| 7120.50† | 6712.70 | -840.41 | -2119.23 | 6692.20 | 6712.70 | -149.36 | -245.14 | 69.76 | 1997.44 | 218.75 | 1778.69 | 9.28 | PASS |
| 7220.50† | 6806.15 | -853.53 | -2152.32 | 6785.65 | 6806.15 | -149.36 | -245.14 | 69.74 | 2033.03 | 221.60 | 1811.42 | 9.32 | PASS |
| 7320.50† | 6899.60 | -866.65 | -2185.40 | 6879.10 | 6899.60 | -149.36 | -245.14 | 69.71 | 2068.61 | 224.45 | 1844.16 | 9.36 | PASS |
| 7341.07 | 6918.82 | -869.35 | -2192.21 | 6898.32 | 6918.82 | -149.36 | -245.14 | 69.71 | 2075.93 | 225.04 | 1850.89 | 9.37 | PASS |
| 7420.50† | 6993.49 | -874.29 | -2218.65 | 6972.99 | 6993.49 | -149.36 | -245.14 | 69.83 | 2102.45 | 227.32 | 1875.13 | 9.40 | PASS |
| 7520.50† | 7087.21 | -864.88 | -2251.87 | 7066.71 | 7087.21 | -149.36 | -245.14 | 70.38 | 2130.48 | 230.22 | 1900.26 | 9.40 | PASS |
| 7620.50† | 7177.96 | -838.35 | -2284.05 | 7157.46 | 7177.96 | -149.36 | -245.14 | 71.33 | 2152.18 | 233.11 | 1919.07 | 9.38 | PASS |
| 7720.50† | 7262.97 | -795.51 | -2314.23 | 7242.47 | 7262.97 | -149.36 | -245.14 | 72.66 | 2167.64 | 235.82 | 1931.82 | 9.33 | PASS |
| 7820.50† | 7339.68 | -737.65 | -2341.49 | 7319.18 | 7339.68 | -149.36 | -245.14 | 74.33 | 2177.33 | 238.22 | 1939.11 | 9.28 | PASS |
| 7920.50† | 7405.75 | -666.53 | -2364.99 | 7385.25 | 7405.75 | -149.36 | -245.14 | 76.29 | 2182.03 | 240.27 | 1941.76 | 9.22 | PASS |
| 8020.50† | 7459.16 | -584.32 | -2384.03 | 7438.66 | 7459.16 | -149.36 | -245.14 | 78.51 | 2182.67 | 241.91 | 1940.76 | 9.16 | PASS |
| 8120.50† | 7498.30 | -493.50 | -2398.02 | 7477.80 | 7498.30 | -149.36 | -245.14 | 80.92 | 2180.22 | 243.12 | 1937.10 | 9.10 | PASS |
| 8220.50† | 7521.99 | -396.85 | -2406.55 | 7501.49 | 7521.99 | -149.36 | -245.14 | 83.47 | 2175.54 | 243.86 | 1931.67 | 9.05 | PASS |
| 8315.56 | 7529.50 | -302.24 | -2409.34 | 7509.00 | 7529.50 | -149.36 | -245.14 | 85.96 | 2169.60 | 244.13 | 1925.47 | 9.02 | PASS |
| 8320.50† | 7529.51 | -297.30 | -2409.35 | 7509.01 | 7529.51 | -149.36 | -245.14 | 86.05 | 2169.27 | 244.13 | 1925.14 | 9.02 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 14 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: JORDAN 34-9 AWB Offset Wellpath: JORDAN 34-9 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.34-T01N-R65W Slot: SLOT#01 EX JORDAN 34-9 (600'FSL & 600'FWL, SEC.34) (PA) | | | | | | | | | | Well: JORDAN 34-9 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|---|----------------------|-----------|-------------|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | |
| 8420.50† | 7529.61 | -197.30 | -2409.53 | 7509.11 | 7529.61 | -149.36 | -245.14 | 88.73 | 2164.92 | 244.14 | 1920.78 | 9.00 | PASS | |
| 8520.50† | 7529.71 | -97.30 | -2409.71 | 7509.21 | 7529.71 | -149.36 | -245.14 | 91.38 | 2165.20 | 244.17 | 1921.02 | 9.00 | PASS | |
| 8620.50† | 7529.82 | 2.70 | -2409.88 | 7509.32 | 7529.82 | -149.36 | -245.14 | 94.02 | 2170.08 | 244.21 | 1925.88 | 9.02 | PASS | |
| 8720.50† | 7529.92 | 102.70 | -2410.06 | 7509.42 | 7529.92 | -149.36 | -245.14 | 96.64 | 2179.55 | 244.24 | 1935.31 | 9.06 | PASS | |
| 8820.50† | 7530.02 | 202.70 | -2410.24 | 7509.52 | 7530.02 | -149.36 | -245.14 | 99.24 | 2193.54 | 244.28 | 1949.26 | 9.11 | PASS | |
| 8920.50† | 7530.13 | 302.70 | -2410.42 | 7509.63 | 7530.13 | -149.36 | -245.14 | 101.79 | 2211.97 | 244.32 | 1967.65 | 9.19 | PASS | |
| 9020.50† | 7530.23 | 402.70 | -2410.59 | 7509.73 | 7530.23 | -149.36 | -245.14 | 104.30 | 2234.72 | 244.35 | 1990.37 | 9.28 | PASS | |
| 9120.50† | 7530.33 | 502.70 | -2410.77 | 7509.83 | 7530.33 | -149.36 | -245.14 | 106.76 | 2261.67 | 244.39 | 2017.28 | 9.39 | PASS | |
| 9220.50† | 7530.44 | 602.70 | -2410.95 | 7509.94 | 7530.44 | -149.36 | -245.14 | 109.15 | 2292.67 | 244.43 | 2048.24 | 9.52 | PASS | |
| 9320.50† | 7530.54 | 702.70 | -2411.13 | 7510.04 | 7530.54 | -149.36 | -245.14 | 111.47 | 2327.56 | 244.47 | 2083.09 | 9.66 | PASS | |
| 9420.50† | 7530.64 | 802.69 | -2411.31 | 7510.14 | 7530.64 | -149.36 | -245.14 | 113.73 | 2366.16 | 244.50 | 2121.65 | 9.82 | PASS | |
| 9520.50† | 7530.75 | 902.69 | -2411.48 | 7510.25 | 7530.75 | -149.36 | -245.14 | 115.90 | 2408.29 | 244.54 | 2163.76 | 9.99 | PASS | |
| 9620.50† | 7530.85 | 1002.69 | -2411.66 | 7510.35 | 7530.85 | -149.36 | -245.14 | 118.00 | 2453.78 | 244.57 | 2209.21 | 10.18 | PASS | |
| 9720.50† | 7530.96 | 1102.69 | -2411.84 | 7510.46 | 7530.96 | -149.36 | -245.14 | 120.02 | 2502.45 | 244.60 | 2257.84 | 10.38 | PASS | |
| 9820.50† | 7531.06 | 1202.69 | -2412.02 | 7510.56 | 7531.06 | -149.36 | -245.14 | 121.96 | 2554.10 | 244.63 | 2309.46 | 10.60 | PASS | |
| 9920.50† | 7531.16 | 1302.69 | -2412.19 | 7510.66 | 7531.16 | -149.36 | -245.14 | 123.82 | 2608.56 | 244.66 | 2363.90 | 10.82 | PASS | |
| 10020.50† | 7531.27 | 1402.69 | -2412.37 | 7510.77 | 7531.27 | -149.36 | -245.14 | 125.61 | 2665.67 | 244.69 | 2420.97 | 11.06 | PASS | |
| 10120.50† | 7531.37 | 1502.69 | -2412.55 | 7510.87 | 7531.37 | -149.36 | -245.14 | 127.32 | 2725.24 | 244.72 | 2480.53 | 11.30 | PASS | |
| 10220.50† | 7531.47 | 1602.69 | -2412.73 | 7510.97 | 7531.47 | -149.36 | -245.14 | 128.95 | 2787.14 | 244.74 | 2542.39 | 11.56 | PASS | |
| 10320.50† | 7531.58 | 1702.69 | -2412.90 | 7511.08 | 7531.58 | -149.36 | -245.14 | 130.51 | 2851.19 | 244.77 | 2606.43 | 11.82 | PASS | |
| 10420.50† | 7531.68 | 1802.69 | -2413.08 | 7511.18 | 7531.68 | -149.36 | -245.14 | 132.00 | 2917.27 | 244.79 | 2672.48 | 12.10 | PASS | |
| 10520.50† | 7531.78 | 1902.69 | -2413.26 | 7511.28 | 7531.78 | -149.36 | -245.14 | 133.42 | 2985.24 | 244.81 | 2740.43 | 12.38 | PASS | |
| 10620.50† | 7531.88 | 2002.69 | -2413.44 | 7511.39 | 7531.88 | -149.36 | -245.14 | 134.78 | 3054.97 | 244.83 | 2810.14 | 12.67 | PASS | |
| 10720.50† | 7531.99 | 2102.69 | -2413.62 | 7511.49 | 7531.99 | -149.36 | -245.14 | 136.08 | 3126.34 | 244.85 | 2881.49 | 12.96 | PASS | |
| 10820.50† | 7532.09 | 2202.69 | -2413.79 | 7511.59 | 7532.09 | -149.36 | -245.14 | 137.32 | 3199.25 | 244.87 | 2954.38 | 13.26 | PASS | |
| 10920.50† | 7532.20 | 2302.69 | -2413.97 | 7511.70 | 7532.20 | -149.36 | -245.14 | 138.51 | 3273.59 | 244.89 | 3028.70 | 13.57 | PASS | |
| 11020.50† | 7532.30 | 2402.69 | -2414.15 | 7511.80 | 7532.30 | -149.36 | -245.14 | 139.64 | 3349.26 | 244.91 | 3104.35 | 13.89 | PASS | |
| 11120.50† | 7532.41 | 2502.69 | -2414.33 | 7511.91 | 7532.41 | -149.36 | -245.14 | 140.72 | 3426.19 | 244.93 | 3181.26 | 14.20 | PASS | |
| 11220.50† | 7532.51 | 2602.69 | -2414.50 | 7512.01 | 7532.51 | -149.36 | -245.14 | 141.75 | 3504.27 | 244.94 | 3259.33 | 14.53 | PASS | |
| 11320.50† | 7532.61 | 2702.69 | -2414.68 | 7512.11 | 7532.61 | -149.36 | -245.14 | 142.74 | 3583.45 | 244.96 | 3338.49 | 14.85 | PASS | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 15 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: JORDAN 34-9 AWB Offset Wellpath: JORDAN 34-9 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.34-T01N-R65W Slot: SLOT#01 EX JORDAN 34-9 (600'FSL & 600'FWL, SEC.34) (PA) | | | | | | | | | | Well: JORDAN 34-9 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|---|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 11420.50† | 7532.72 | 2802.69 | -2414.86 | 7512.22 | 7532.72 | -149.36 | -245.14 | 143.69 | 3663.64 | 244.98 | 3418.67 | 15.19 | PASS |
| 11520.50† | 7532.82 | 2902.69 | -2415.04 | 7512.32 | 7532.82 | -149.36 | -245.14 | 144.58 | 3744.79 | 244.99 | 3499.80 | 15.52 | PASS |
| 11620.50† | 7532.92 | 3002.69 | -2415.21 | 7512.42 | 7532.92 | -149.36 | -245.14 | 145.45 | 3826.83 | 245.01 | 3581.82 | 15.86 | PASS |
| 11720.50† | 7533.03 | 3102.69 | -2415.39 | 7512.53 | 7533.03 | -149.36 | -245.14 | 146.28 | 3909.71 | 245.03 | 3664.68 | 16.20 | PASS |
| 11820.50† | 7533.13 | 3202.69 | -2415.57 | 7512.63 | 7533.13 | -149.36 | -245.14 | 147.08 | 3993.37 | 245.04 | 3748.33 | 16.55 | PASS |
| 11920.50† | 7533.23 | 3302.69 | -2415.75 | 7512.73 | 7533.23 | -149.36 | -245.14 | 147.84 | 4077.77 | 245.06 | 3832.71 | 16.90 | PASS |
| 12020.50† | 7533.34 | 3402.69 | -2415.92 | 7512.84 | 7533.34 | -149.36 | -245.14 | 148.57 | 4162.85 | 245.07 | 3917.78 | 17.25 | PASS |
| 12120.50† | 7533.44 | 3502.69 | -2416.10 | 7512.94 | 7533.44 | -149.36 | -245.14 | 149.27 | 4248.59 | 245.09 | 4003.50 | 17.60 | PASS |
| 12220.50† | 7533.55 | 3602.69 | -2416.28 | 7513.05 | 7533.55 | -149.36 | -245.14 | 149.94 | 4334.94 | 245.11 | 4089.84 | 17.96 | PASS |
| 12320.50† | 7533.65 | 3702.69 | -2416.46 | 7513.15 | 7533.65 | -149.36 | -245.14 | 150.59 | 4421.87 | 245.12 | 4176.74 | 18.32 | PASS |
| 12420.50† | 7533.75 | 3802.69 | -2416.64 | 7513.25 | 7533.75 | -149.36 | -245.14 | 151.21 | 4509.33 | 245.14 | 4264.19 | 18.68 | PASS |
| 12520.50† | 7533.86 | 3902.69 | -2416.81 | 7513.36 | 7533.86 | -149.36 | -245.14 | 151.81 | 4597.31 | 245.15 | 4352.15 | 19.05 | PASS |
| 12620.50† | 7533.96 | 4002.69 | -2416.99 | 7513.46 | 7533.96 | -149.36 | -245.14 | 152.39 | 4685.77 | 245.17 | 4440.60 | 19.41 | PASS |
| 12720.50† | 7534.06 | 4102.69 | -2417.17 | 7513.56 | 7534.06 | -149.36 | -245.14 | 152.94 | 4774.68 | 245.19 | 4529.50 | 19.78 | PASS |
| 12820.50† | 7534.17 | 4202.69 | -2417.35 | 7513.67 | 7534.17 | -149.36 | -245.14 | 153.48 | 4864.03 | 245.20 | 4618.83 | 20.15 | PASS |
| 12920.50† | 7534.27 | 4302.69 | -2417.52 | 7513.77 | 7534.27 | -149.36 | -245.14 | 153.99 | 4953.78 | 245.22 | 4708.56 | 20.52 | PASS |
| 13020.50† | 7534.37 | 4402.69 | -2417.70 | 7513.87 | 7534.37 | -149.36 | -245.14 | 154.49 | 5043.92 | 245.24 | 4798.68 | 20.89 | PASS |
| 13120.50† | 7534.48 | 4502.69 | -2417.88 | 7513.98 | 7534.48 | -149.36 | -245.14 | 154.97 | 5134.43 | 245.26 | 4889.17 | 21.26 | PASS |
| 13199.97 | 7534.56 | 4582.16 | -2418.02 | 7514.06 | 7534.56 | -149.36 | -245.14 | 155.33 | 5206.60 | 245.27 | 4961.33 | 21.56 | PASS |
| 13220.50† | 7534.58 | 4602.69 | -2418.13 | 7514.08 | 7534.58 | -149.36 | -245.14 | 155.43 | 5225.31 | 245.27 | 4980.03 | 21.64 | PASS |
| 13320.50† | 7534.68 | 4702.65 | -2420.77 | 7514.18 | 7534.68 | -149.36 | -245.14 | 155.85 | 5317.45 | 245.29 | 5072.17 | 22.02 | PASS |
| 13420.50† | 7534.79 | 4802.45 | -2426.90 | 7514.29 | 7534.79 | -149.36 | -245.14 | 156.22 | 5411.15 | 245.30 | 5165.85 | 22.41 | PASS |
| 13476.50 | 7534.85 | 4858.23 | -2431.85 | 7514.35 | 7534.85 | -149.36 | -245.14 | 156.41 | 5464.22 | 245.30 | 5218.92 | 22.63 | PASS |
| 13520.50† | 7534.89 | 4902.02 | -2436.16 | 7514.39 | 7534.89 | -149.36 | -245.14 | 156.55 | 5506.09 | 245.30 | 5260.79 | 22.80 | PASS |
| 13620.50† | 7534.99 | 5001.54 | -2445.98 | 7514.49 | 7534.99 | -149.36 | -245.14 | 156.86 | 5601.38 | 245.31 | 5356.07 | 23.19 | PASS |
| 13720.50† | 7535.10 | 5101.06 | -2455.79 | 7514.60 | 7535.10 | -149.36 | -245.14 | 157.17 | 5696.83 | 245.32 | 5451.51 | 23.59 | PASS |
| 13820.50† | 7535.20 | 5200.57 | -2465.61 | 7514.70 | 7535.20 | -149.36 | -245.14 | 157.46 | 5792.43 | 245.33 | 5547.10 | 23.98 | PASS |
| 13920.50† | 7535.30 | 5300.09 | -2475.42 | 7514.80 | 7535.30 | -149.36 | -245.14 | 157.74 | 5888.18 | 245.34 | 5642.84 | 24.38 | PASS |
| 14020.50† | 7535.40 | 5399.61 | -2485.24 | 7514.90 | 7535.40 | -149.36 | -245.14 | 158.02 | 5984.07 | 245.35 | 5738.71 | 24.78 | PASS |
| 14120.50† | 7535.51 | 5499.12 | -2495.05 | 7515.01 | 7535.51 | -149.36 | -245.14 | 158.28 | 6080.09 | 245.36 | 5834.72 | 25.17 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 16 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: JORDAN 34-9 AWB Offset Wellpath: JORDAN 34-9 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.34-T01N-R65W | | | | Slot: SLOT#01 EX JORDAN 34-9 (600'FSL & 600'FWL, SEC.34) (PA) | | Well: JORDAN 34-9 | | Threshold Value=1.00 | | † = interpolated, ‡ = extrapolated station | | | |
|----------------------------|-----------------|-------------------|------------------|---|--------------------|----------------------|---------------------|-------------------------|---------------------------|--|----------------------------|--------------|----------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 14220.50† | 7535.61 | 5598.64 | -2504.87 | 7515.11 | 7535.61 | -149.36 | -245.14 | 158.54 | 6176.23 | 245.38 | 5930.86 | 25.57 | PASS |
| 14221.87 | 7535.61 | 5600.00 | -2505.00 | 7515.11 | 7535.61 | -149.36 | -245.14 | 158.54 | 6177.55 | 245.38 | 5932.17 | 25.57 | PASS |
| 14320.50† | 7535.71 | 5698.31 | -2512.99 | 7515.21 | 7535.71 | -149.36 | -245.14 | 158.80 | 6272.03 | 245.39 | 6026.64 | 25.96 | PASS |
| 14420.50† | 7535.81 | 5798.19 | -2517.63 | 7515.31 | 7535.81 | -149.36 | -245.14 | 159.09 | 6366.91 | 245.41 | 6121.50 | 26.36 | PASS |
| 14520.50† | 7535.92 | 5898.18 | -2518.78 | 7515.42 | 7535.92 | -149.36 | -245.14 | 159.40 | 6460.82 | 245.43 | 6215.39 | 26.74 | PASS |
| 14581.38 | 7535.98 | 5959.05 | -2517.77 | 7515.48 | 7535.98 | -149.36 | -245.14 | 159.59 | 6517.48 | 245.45 | 6272.04 | 26.98 | PASS |
| 14620.50† | 7536.02 | 5998.16 | -2516.71 | 7515.52 | 7536.02 | -149.36 | -245.14 | 159.72 | 6553.77 | 245.45 | 6308.32 | 27.12 | PASS |
| 14720.50† | 7536.12 | 6098.12 | -2513.99 | 7515.62 | 7536.12 | -149.36 | -245.14 | 160.04 | 6646.70 | 245.48 | 6401.22 | 27.51 | PASS |
| 14820.50† | 7536.23 | 6198.08 | -2511.27 | 7515.73 | 7536.23 | -149.36 | -245.14 | 160.35 | 6739.83 | 245.51 | 6494.32 | 27.89 | PASS |
| 14920.50† | 7536.33 | 6298.05 | -2508.55 | 7515.83 | 7536.33 | -149.36 | -245.14 | 160.66 | 6833.16 | 245.54 | 6587.62 | 28.27 | PASS |
| 15020.50† | 7536.43 | 6398.01 | -2505.83 | 7515.93 | 7536.43 | -149.36 | -245.14 | 160.95 | 6926.67 | 245.57 | 6681.10 | 28.66 | PASS |
| 15120.50† | 7536.54 | 6497.97 | -2503.11 | 7516.04 | 7536.54 | -149.36 | -245.14 | 161.24 | 7020.36 | 245.60 | 6774.76 | 29.04 | PASS |
| 15220.50† | 7536.64 | 6597.93 | -2500.40 | 7516.14 | 7536.64 | -149.36 | -245.14 | 161.52 | 7114.22 | 245.63 | 6868.60 | 29.42 | PASS |
| 15320.50† | 7536.74 | 6697.90 | -2497.68 | 7516.24 | 7536.74 | -149.36 | -245.14 | 161.79 | 7208.25 | 245.65 | 6962.59 | 29.81 | PASS |
| 15420.50† | 7536.85 | 6797.86 | -2494.96 | 7516.35 | 7536.85 | -149.36 | -245.14 | 162.06 | 7302.43 | 245.68 | 7056.75 | 30.20 | PASS |
| 15520.50† | 7536.95 | 6897.82 | -2492.24 | 7516.45 | 7536.95 | -149.36 | -245.14 | 162.31 | 7396.77 | 245.71 | 7151.06 | 30.58 | PASS |
| 15620.50† | 7537.05 | 6997.79 | -2489.52 | 7516.55 | 7537.05 | -149.36 | -245.14 | 162.57 | 7491.26 | 245.74 | 7245.51 | 30.97 | PASS |
| 15720.50† | 7537.16 | 7097.75 | -2486.80 | 7516.66 | 7537.16 | -149.36 | -245.14 | 162.81 | 7585.88 | 245.77 | 7340.11 | 31.36 | PASS |
| 15820.50† | 7537.26 | 7197.71 | -2484.08 | 7516.76 | 7537.26 | -149.36 | -245.14 | 163.05 | 7680.64 | 245.80 | 7434.84 | 31.75 | PASS |
| 15920.50† | 7537.36 | 7297.68 | -2481.36 | 7516.86 | 7537.36 | -149.36 | -245.14 | 163.29 | 7775.54 | 245.83 | 7529.70 | 32.13 | PASS |
| 16020.50† | 7537.47 | 7397.64 | -2478.64 | 7516.97 | 7537.47 | -149.36 | -245.14 | 163.51 | 7870.56 | 245.87 | 7624.69 | 32.52 | PASS |
| 16120.50† | 7537.57 | 7497.60 | -2475.93 | 7517.07 | 7537.57 | -149.36 | -245.14 | 163.74 | 7965.70 | 245.90 | 7719.80 | 32.91 | PASS |
| 16220.50† | 7537.68 | 7597.56 | -2473.21 | 7517.18 | 7537.68 | -149.36 | -245.14 | 163.95 | 8060.96 | 245.93 | 7815.03 | 33.30 | PASS |
| 16320.50† | 7537.78 | 7697.53 | -2470.49 | 7517.28 | 7537.78 | -149.36 | -245.14 | 164.17 | 8156.33 | 245.96 | 7910.38 | 33.69 | PASS |
| 16420.50† | 7537.88 | 7797.49 | -2467.77 | 7517.38 | 7537.88 | -149.36 | -245.14 | 164.37 | 8251.82 | 245.99 | 8005.83 | 34.08 | PASS |
| 16520.50† | 7537.99 | 7897.45 | -2465.05 | 7517.49 | 7537.99 | -149.36 | -245.14 | 164.58 | 8347.41 | 246.02 | 8101.38 | 34.47 | PASS |
| 16620.50† | 7538.09 | 7997.42 | -2462.33 | 7517.59 | 7538.09 | -149.36 | -245.14 | 164.78 | 8443.10 | 246.05 | 8197.04 | 34.86 | PASS |
| 16720.50† | 7538.19 | 8097.38 | -2459.61 | 7517.69 | 7538.19 | -149.36 | -245.14 | 164.97 | 8538.89 | 246.09 | 8292.80 | 35.25 | PASS |
| 16820.50† | 7538.30 | 8197.34 | -2456.89 | 7517.80 | 7538.30 | -149.36 | -245.14 | 165.16 | 8634.77 | 246.12 | 8388.65 | 35.64 | PASS |
| 16920.50† | 7538.40 | 8297.31 | -2454.17 | 7517.90 | 7538.40 | -149.36 | -245.14 | 165.34 | 8730.75 | 246.15 | 8484.60 | 36.04 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 17 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: JORDAN 34-9 AWP Offset Wellpath: JORDAN 34-9 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.34-T01N-R65W Slot: SLOT#01 EX JORDAN 34-9 (600'FSL & 600'FWL, SEC.34) (PA) Well: JORDAN 34-9 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 17020.50† | 7538.50 | 8397.27 | -2451.46 | 7518.00 | 7538.50 | -149.36 | -245.14 | 165.53 | 8826.81 | 246.19 | 8580.63 | 36.43 | PASS |
| 17120.50† | 7538.61 | 8497.23 | -2448.74 | 7518.11 | 7538.61 | -149.36 | -245.14 | 165.70 | 8922.97 | 246.22 | 8676.75 | 36.82 | PASS |
| 17220.50† | 7538.71 | 8597.19 | -2446.02 | 7518.21 | 7538.71 | -149.36 | -245.14 | 165.88 | 9019.20 | 246.25 | 8772.95 | 37.21 | PASS |
| 17320.50† | 7538.81 | 8697.16 | -2443.30 | 7518.31 | 7538.81 | -149.36 | -245.14 | 166.05 | 9115.52 | 246.29 | 8869.24 | 37.60 | PASS |
| 17420.50† | 7538.92 | 8797.12 | -2440.58 | 7518.42 | 7538.92 | -149.36 | -245.14 | 166.21 | 9211.92 | 246.32 | 8965.60 | 38.00 | PASS |
| 17520.50† | 7539.02 | 8897.08 | -2437.86 | 7518.52 | 7539.02 | -149.36 | -245.14 | 166.38 | 9308.39 | 246.35 | 9062.04 | 38.39 | PASS |
| 17620.50† | 7539.12 | 8997.05 | -2435.14 | 7518.62 | 7539.12 | -149.36 | -245.14 | 166.54 | 9404.94 | 246.39 | 9158.55 | 38.78 | PASS |
| 17720.50† | 7539.23 | 9097.01 | -2432.42 | 7518.73 | 7539.23 | -149.36 | -245.14 | 166.69 | 9501.55 | 246.42 | 9255.13 | 39.17 | PASS |
| 17820.50† | 7539.33 | 9196.97 | -2429.70 | 7518.83 | 7539.33 | -149.36 | -245.14 | 166.84 | 9598.24 | 246.46 | 9351.78 | 39.57 | PASS |
| 17920.50† | 7539.43 | 9296.94 | -2426.99 | 7518.93 | 7539.43 | -149.36 | -245.14 | 166.99 | 9694.99 | 246.49 | 9448.50 | 39.96 | PASS |
| 17985.90 | 7539.50 | 9362.31 | -2425.21 | 7519.00 | 7539.50 | -149.36 | -245.14 | 167.09 | 9758.30 | 246.52 | 9511.78 | 40.22 | PASS |

POSITIONAL UNCERTAINTY - Offset Wellbore: JORDAN 34-9 AWP Offset Wellpath: JORDAN 34-9 AWP

| | | | | |
|-----------------------------------|------------|---------|----------|---------|
| Slot Surface Uncertainty @1SD | Horizontal | 8.200ft | Vertical | 3.000ft |
| Facility Surface Uncertainty @1SD | Horizontal | 8.200ft | Vertical | 3.000ft |

WELLPATH COMPOSITION - Offset Wellbore: JORDAN 34-9 AWP Offset Wellpath: JORDAN 34-9 AWP

| Start MD [ft] | End MD [ft] | Positional Uncertainty Model | Log Name/Comment | Wellbore | Survey Date |
|---------------|-------------|---|--|-----------------|-------------|
| 0.00 | 7970.00 | BH Drift Indicator - Inclination Only (Actual Survey) | ASSUMED VERTICAL TO TD FROM COGCC <7970> | JORDAN 34-9 AWP | 1/22/2020 |

OFFSET WELLPATH REFERENCE - Offset Wellbore: JORDAN 34-9 AWP Offset Wellpath: JORDAN 34-9 AWP

| | |
|---|--|
| MD Reference: Rig on SLOT#01 EX JORDAN 34-9 (600'FSL & 600'FWL, SEC.34) (PA) (RT) | Offset TVD & local coordinates use Reference Wellpath settings (See WELLPATH DATUM on page 1 of this report) |
| Ellipse Start MD | 0.00ft |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 18 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. GLEN YOUNG 1 AWP Offset Wellpath: EX. GLEN YOUNG 1 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#01 EX. GLEN YOUNG 1 (1320'FNL & 1320'FEL, PA) | | | | Well: EX. GLEN YOUNG 1 | | | | Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | |
|---|-----------------|-------------------|------------------|------------------------|--------------------|----------------------|---------------------|---|---------------------------|----------------------|----------------------------|--------------|----------------|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | |
| 20.50 | 20.50 | 0.00 | 0.00 | -20.50 | 77.00 | 8473.01 | -2157.84 | 345.71 | 8743.65 | 33.25 | 8710.40 | 298.59 | PASS | |
| 120.50† | 120.50 | 0.00 | 0.00 | 23.00 | 120.50 | 8473.01 | -2157.84 | 345.71 | 8743.47 | 45.02 | 8698.45 | 212.96 | PASS | |
| 200.00 | 200.00 | 0.00 | 0.00 | 102.52 | 200.00 | 8473.01 | -2157.84 | 345.71 | 8743.47 | 45.20 | 8698.27 | 212.07 | PASS | |
| 220.50† | 220.50 | -0.03 | -0.07 | 123.03 | 220.50 | 8473.01 | -2157.84 | 345.71 | 8743.48 | 45.36 | 8698.11 | 211.20 | PASS | |
| 320.50† | 320.46 | -0.93 | -2.36 | 223.06 | 320.46 | 8473.01 | -2157.84 | 345.73 | 8743.79 | 46.33 | 8697.46 | 206.39 | PASS | |
| 420.50† | 420.28 | -3.13 | -7.88 | 322.94 | 420.28 | 8473.01 | -2157.84 | 345.77 | 8744.56 | 47.88 | 8696.67 | 199.10 | PASS | |
| 520.50† | 519.83 | -6.60 | -16.65 | 422.55 | 519.83 | 8473.01 | -2157.84 | 345.83 | 8745.78 | 49.99 | 8695.79 | 190.01 | PASS | |
| 620.50† | 618.99 | -11.36 | -28.64 | 521.77 | 618.99 | 8473.01 | -2157.84 | 345.91 | 8747.46 | 52.57 | 8694.89 | 179.96 | PASS | |
| 720.50† | 717.64 | -17.38 | -43.83 | 620.48 | 717.64 | 8473.01 | -2157.84 | 346.02 | 8749.62 | 55.54 | 8694.08 | 169.62 | PASS | |
| 820.50† | 815.66 | -24.68 | -62.22 | 718.56 | 815.66 | 8473.01 | -2157.84 | 346.15 | 8752.28 | 58.84 | 8693.44 | 159.47 | PASS | |
| 920.50† | 912.93 | -33.22 | -83.78 | 815.88 | 912.93 | 8473.01 | -2157.84 | 346.30 | 8755.45 | 62.40 | 8693.05 | 149.82 | PASS | |
| 1020.50† | 1009.33 | -43.02 | -108.48 | 912.34 | 1009.33 | 8473.01 | -2157.84 | 346.47 | 8759.15 | 66.15 | 8693.00 | 140.83 | PASS | |
| 1120.50† | 1104.74 | -54.05 | -136.29 | 1007.82 | 1104.74 | 8473.01 | -2157.84 | 346.66 | 8763.42 | 70.06 | 8693.35 | 132.56 | PASS | |
| 1220.50† | 1199.05 | -66.30 | -167.18 | 1102.18 | 1199.05 | 8473.01 | -2157.84 | 346.88 | 8768.27 | 74.09 | 8694.18 | 125.01 | PASS | |
| 1242.54 | 1219.68 | -69.16 | -174.40 | 1122.82 | 1219.68 | 8473.01 | -2157.84 | 346.93 | 8769.42 | 75.00 | 8694.42 | 123.43 | PASS | |
| 1320.50† | 1292.54 | -79.39 | -200.20 | 1195.72 | 1292.54 | 8473.01 | -2157.84 | 347.11 | 8773.60 | 78.23 | 8695.37 | 118.12 | PASS | |
| 1420.50† | 1385.99 | -92.51 | -233.28 | 1289.23 | 1385.99 | 8473.01 | -2157.84 | 347.34 | 8779.07 | 82.47 | 8696.61 | 111.81 | PASS | |
| 1520.50† | 1479.44 | -105.63 | -266.37 | 1382.74 | 1479.44 | 8473.01 | -2157.84 | 347.57 | 8784.69 | 86.76 | 8697.94 | 106.08 | PASS | |
| 1620.50† | 1572.89 | -118.75 | -299.46 | 1476.25 | 1572.89 | 8473.01 | -2157.84 | 347.80 | 8790.45 | 91.09 | 8699.37 | 100.88 | PASS | |
| 1720.50† | 1666.34 | -131.87 | -332.54 | 1569.75 | 1666.34 | 8473.01 | -2157.84 | 348.02 | 8796.35 | 95.49 | 8700.86 | 96.08 | PASS | |
| 1820.50† | 1759.79 | -144.99 | -365.63 | 1663.26 | 1759.79 | 8473.01 | -2157.84 | 348.25 | 8802.39 | 99.96 | 8702.43 | 91.67 | PASS | |
| 1920.50† | 1853.24 | -158.12 | -398.72 | 1756.77 | 1853.24 | 8473.01 | -2157.84 | 348.48 | 8808.57 | 104.49 | 8704.09 | 87.61 | PASS | |
| 2020.50† | 1946.69 | -171.24 | -431.80 | 1850.28 | 1946.69 | 8473.01 | -2157.84 | 348.71 | 8814.89 | 109.06 | 8705.83 | 83.85 | PASS | |
| 2120.50† | 2040.14 | -184.36 | -464.89 | 1943.79 | 2040.14 | 8473.01 | -2157.84 | 348.94 | 8821.35 | 113.68 | 8707.67 | 80.38 | PASS | |
| 2220.50† | 2133.59 | -197.48 | -497.98 | 2037.30 | 2133.59 | 8473.01 | -2157.84 | 349.16 | 8827.94 | 118.33 | 8709.61 | 77.17 | PASS | |
| 2320.50† | 2227.05 | -210.60 | -531.06 | 2130.80 | 2227.05 | 8473.01 | -2157.84 | 349.39 | 8834.68 | 123.02 | 8711.66 | 74.18 | PASS | |
| 2420.50† | 2320.50 | -223.72 | -564.15 | 2224.31 | 2320.50 | 8473.01 | -2157.84 | 349.62 | 8841.55 | 127.74 | 8713.81 | 71.41 | PASS | |
| 2520.50† | 2413.95 | -236.84 | -597.24 | 2317.82 | 2413.95 | 8473.01 | -2157.84 | 349.84 | 8848.56 | 132.48 | 8716.08 | 68.83 | PASS | |
| 2620.50† | 2507.40 | -249.96 | -630.32 | 2411.33 | 2507.40 | 8473.01 | -2157.84 | 350.07 | 8855.71 | 137.25 | 8718.46 | 66.42 | PASS | |
| 2720.50† | 2600.85 | -263.08 | -663.41 | 2504.84 | 2600.85 | 8473.01 | -2157.84 | 350.29 | 8863.00 | 142.03 | 8720.96 | 64.17 | PASS | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 19 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. GLEN YOUNG 1 AWP Offset Wellpath: EX. GLEN YOUNG 1 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#01 EX. GLEN YOUNG 1 (1320'FNL & 1320'FEL, PA) Well: EX. GLEN YOUNG 1 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 2820.50† | 2694.30 | -276.20 | -696.50 | 2598.34 | 2694.30 | 8473.01 | -2157.84 | 350.52 | 8870.42 | 146.84 | 8723.58 | 62.07 | PASS |
| 2920.50† | 2787.75 | -289.33 | -729.58 | 2691.85 | 2787.75 | 8473.01 | -2157.84 | 350.74 | 8877.98 | 151.66 | 8726.32 | 60.09 | PASS |
| 3020.50† | 2881.20 | -302.45 | -762.67 | 2785.36 | 2881.20 | 8473.01 | -2157.84 | 350.97 | 8885.67 | 156.50 | 8729.17 | 58.23 | PASS |
| 3120.50† | 2974.65 | -315.57 | -795.76 | 2878.87 | 2974.65 | 8473.01 | -2157.84 | 351.19 | 8893.51 | 161.35 | 8732.15 | 56.49 | PASS |
| 3220.50† | 3068.11 | -328.69 | -828.84 | 2972.38 | 3068.11 | 8473.01 | -2157.84 | 351.41 | 8901.47 | 166.22 | 8735.26 | 54.84 | PASS |
| 3320.50† | 3161.56 | -341.81 | -861.93 | 3065.88 | 3161.56 | 8473.01 | -2157.84 | 351.64 | 8909.57 | 171.09 | 8738.48 | 53.29 | PASS |
| 3420.50† | 3255.01 | -354.93 | -895.02 | 3159.39 | 3255.01 | 8473.01 | -2157.84 | 351.86 | 8917.81 | 175.98 | 8741.83 | 51.83 | PASS |
| 3520.50† | 3348.46 | -368.05 | -928.10 | 3252.90 | 3348.46 | 8473.01 | -2157.84 | 352.08 | 8926.18 | 180.87 | 8745.31 | 50.44 | PASS |
| 3620.50† | 3441.91 | -381.17 | -961.19 | 3346.41 | 3441.91 | 8473.01 | -2157.84 | 352.30 | 8934.68 | 185.77 | 8748.91 | 49.13 | PASS |
| 3720.50† | 3535.36 | -394.29 | -994.28 | 3439.92 | 3535.36 | 8473.01 | -2157.84 | 352.52 | 8943.32 | 190.68 | 8752.64 | 47.88 | PASS |
| 3820.50† | 3628.81 | -407.41 | -1027.37 | 3533.42 | 3628.81 | 8473.01 | -2157.84 | 352.75 | 8952.09 | 195.60 | 8756.49 | 46.70 | PASS |
| 3920.50† | 3722.26 | -420.53 | -1060.45 | 3626.93 | 3722.26 | 8473.01 | -2157.84 | 352.97 | 8961.00 | 200.53 | 8760.47 | 45.57 | PASS |
| 4020.50† | 3815.71 | -433.66 | -1093.54 | 3720.44 | 3815.71 | 8473.01 | -2157.84 | 353.19 | 8970.03 | 205.46 | 8764.58 | 44.50 | PASS |
| 4120.50† | 3909.17 | -446.78 | -1126.63 | 3813.95 | 3909.17 | 8473.01 | -2157.84 | 353.41 | 8979.20 | 210.39 | 8768.81 | 43.48 | PASS |
| 4220.50† | 4002.62 | -459.90 | -1159.71 | 3907.46 | 4002.62 | 8473.01 | -2157.84 | 353.62 | 8988.50 | 215.33 | 8773.17 | 42.51 | PASS |
| 4320.50† | 4096.07 | -473.02 | -1192.80 | 4000.96 | 4096.07 | 8473.01 | -2157.84 | 353.84 | 8997.93 | 220.28 | 8777.65 | 41.58 | PASS |
| 4420.50† | 4189.52 | -486.14 | -1225.89 | 4094.47 | 4189.52 | 8473.01 | -2157.84 | 354.06 | 9007.50 | 225.23 | 8782.26 | 40.69 | PASS |
| 4520.50† | 4282.97 | -499.26 | -1258.97 | 4187.98 | 4282.97 | 8473.01 | -2157.84 | 354.28 | 9017.19 | 230.19 | 8787.00 | 39.85 | PASS |
| 4620.50† | 4376.42 | -512.38 | -1292.06 | 4281.49 | 4376.42 | 8473.01 | -2157.84 | 354.50 | 9027.01 | 235.14 | 8791.87 | 39.03 | PASS |
| 4720.50† | 4469.87 | -525.50 | -1325.15 | 4375.00 | 4469.87 | 8473.01 | -2157.84 | 354.71 | 9036.96 | 240.11 | 8796.86 | 38.26 | PASS |
| 4820.50† | 4563.32 | -538.62 | -1358.23 | 4468.50 | 4563.32 | 8473.01 | -2157.84 | 354.93 | 9047.04 | 245.07 | 8801.97 | 37.51 | PASS |
| 4920.50† | 4656.77 | -551.74 | -1391.32 | 4562.01 | 4656.77 | 8473.01 | -2157.84 | 355.15 | 9057.25 | 250.04 | 8807.21 | 36.79 | PASS |
| 5020.50† | 4750.22 | -564.87 | -1424.41 | 4655.52 | 4750.22 | 8473.01 | -2157.84 | 355.36 | 9067.59 | 255.01 | 8812.58 | 36.11 | PASS |
| 5120.50† | 4843.68 | -577.99 | -1457.49 | 4749.03 | 4843.68 | 8473.01 | -2157.84 | 355.58 | 9078.06 | 259.98 | 8818.07 | 35.45 | PASS |
| 5220.50† | 4937.13 | -591.11 | -1490.58 | 4842.54 | 4937.13 | 8473.01 | -2157.84 | 355.79 | 9088.65 | 264.96 | 8823.69 | 34.81 | PASS |
| 5320.50† | 5030.58 | -604.23 | -1523.67 | 4936.04 | 5030.58 | 8473.01 | -2157.84 | 356.00 | 9099.37 | 269.94 | 8829.43 | 34.20 | PASS |
| 5420.50† | 5124.03 | -617.35 | -1556.75 | 5029.55 | 5124.03 | 8473.01 | -2157.84 | 356.22 | 9110.22 | 274.92 | 8835.30 | 33.61 | PASS |
| 5520.50† | 5217.48 | -630.47 | -1589.84 | 5123.06 | 5217.48 | 8473.01 | -2157.84 | 356.43 | 9121.19 | 279.90 | 8841.29 | 33.04 | PASS |
| 5620.50† | 5310.93 | -643.59 | -1622.93 | 5216.57 | 5310.93 | 8473.01 | -2157.84 | 356.64 | 9132.29 | 284.89 | 8847.40 | 32.50 | PASS |
| 5720.50† | 5404.38 | -656.71 | -1656.01 | 5310.08 | 5404.38 | 8473.01 | -2157.84 | 356.85 | 9143.51 | 289.87 | 8853.64 | 31.97 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 20 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. GLEN YOUNG 1 AWP Offset Wellpath: EX. GLEN YOUNG 1 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#01 EX. GLEN YOUNG 1 (1320'FNL & 1320'FEL, PA) Well: EX. GLEN YOUNG 1 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 5820.50† | 5497.83 | -669.83 | -1689.10 | 5403.58 | 5497.83 | 8473.01 | -2157.84 | 357.07 | 9154.86 | 294.86 | 8860.00 | 31.46 | PASS |
| 5920.50† | 5591.28 | -682.95 | -1722.19 | 5497.09 | 5591.28 | 8473.01 | -2157.84 | 357.28 | 9166.33 | 299.85 | 8866.48 | 30.97 | PASS |
| 6020.50† | 5684.74 | -696.07 | -1755.27 | 5590.60 | 5684.74 | 8473.01 | -2157.84 | 357.49 | 9177.92 | 304.84 | 8873.09 | 30.49 | PASS |
| 6120.50† | 5778.19 | -709.20 | -1788.36 | 5684.11 | 5778.19 | 8473.01 | -2157.84 | 357.70 | 9189.64 | 309.83 | 8879.81 | 30.03 | PASS |
| 6220.50† | 5871.64 | -722.32 | -1821.45 | 5777.62 | 5871.64 | 8473.01 | -2157.84 | 357.91 | 9201.48 | 314.82 | 8886.66 | 29.59 | PASS |
| 6320.50† | 5965.09 | -735.44 | -1854.54 | 5871.12 | 5965.09 | 8473.01 | -2157.84 | 358.11 | 9213.45 | 319.81 | 8893.63 | 29.16 | PASS |
| 6420.50† | 6058.54 | -748.56 | -1887.62 | 5964.63 | 6058.54 | 8473.01 | -2157.84 | 358.32 | 9225.53 | 324.81 | 8900.72 | 28.74 | PASS |
| 6520.50† | 6151.99 | -761.68 | -1920.71 | 6058.14 | 6151.99 | 8473.01 | -2157.84 | 358.53 | 9237.74 | 329.80 | 8907.94 | 28.34 | PASS |
| 6620.50† | 6245.44 | -774.80 | -1953.80 | 6151.65 | 6245.44 | 8473.01 | -2157.84 | 358.74 | 9250.07 | 334.80 | 8915.27 | 27.95 | PASS |
| 6720.50† | 6338.89 | -787.92 | -1986.88 | 6245.16 | 6338.89 | 8473.01 | -2157.84 | 358.94 | 9262.51 | 339.80 | 8922.72 | 27.57 | PASS |
| 6820.50† | 6432.34 | -801.04 | -2019.97 | 6338.67 | 6432.34 | 8473.01 | -2157.84 | 359.15 | 9275.08 | 344.79 | 8930.29 | 27.20 | PASS |
| 6920.50† | 6525.80 | -814.16 | -2053.06 | 6432.17 | 6525.80 | 8473.01 | -2157.84 | 359.35 | 9287.77 | 349.79 | 8937.98 | 26.85 | PASS |
| 7020.50† | 6619.25 | -827.28 | -2086.14 | 6525.68 | 6619.25 | 8473.01 | -2157.84 | 359.56 | 9300.58 | 354.79 | 8945.78 | 26.50 | PASS |
| 7120.50† | 6712.70 | -840.41 | -2119.23 | 6619.19 | 6712.70 | 8473.01 | -2157.84 | 359.76 | 9313.50 | 359.79 | 8953.71 | 26.16 | PASS |
| 7220.50† | 6806.15 | -853.53 | -2152.32 | 6712.70 | 6806.15 | 8473.01 | -2157.84 | 359.97 | 9326.54 | 364.79 | 8961.75 | 25.84 | PASS |
| 7320.50† | 6899.60 | -866.65 | -2185.40 | 6806.21 | 6899.60 | 8473.01 | -2157.84 | 0.17 | 9339.70 | 369.79 | 8969.91 | 25.52 | PASS |
| 7341.07 | 6918.82 | -869.35 | -2192.21 | 6825.44 | 6918.82 | 8473.01 | -2157.84 | 0.21 | 9342.42 | 370.82 | 8971.61 | 25.46 | PASS |
| 7420.50† | 6993.49 | -874.29 | -2218.65 | 6900.15 | 6993.49 | 8473.01 | -2157.84 | 0.37 | 9347.50 | 374.83 | 8972.67 | 25.20 | PASS |
| 7520.50† | 7087.21 | -864.88 | -2251.87 | 6993.93 | 7087.21 | 8473.01 | -2157.84 | 0.58 | 9338.37 | 379.93 | 8958.44 | 24.83 | PASS |
| 7620.50† | 7177.96 | -838.35 | -2284.05 | 7084.73 | 7177.96 | 8473.01 | -2157.84 | 0.78 | 9312.22 | 384.89 | 8927.33 | 24.44 | PASS |
| 7720.50† | 7262.97 | -795.51 | -2314.23 | 7169.80 | 7262.97 | 8473.01 | -2157.84 | 0.97 | 9269.84 | 389.51 | 8880.33 | 24.03 | PASS |
| 7820.50† | 7339.68 | -737.65 | -2341.49 | 7246.56 | 7339.68 | 8473.01 | -2157.84 | 1.14 | 9212.49 | 393.67 | 8818.82 | 23.63 | PASS |
| 7920.50† | 7405.75 | -666.53 | -2364.99 | 7312.66 | 7405.75 | 8473.01 | -2157.84 | 1.30 | 9141.89 | 397.24 | 8744.65 | 23.24 | PASS |
| 8020.50† | 7459.16 | -584.32 | -2384.03 | 7366.11 | 7459.16 | 8473.01 | -2157.84 | 1.43 | 9060.15 | 400.12 | 8660.03 | 22.86 | PASS |
| 8120.50† | 7498.30 | -493.50 | -2398.02 | 7405.28 | 7498.30 | 8473.01 | -2157.84 | 1.53 | 8969.74 | 402.23 | 8567.51 | 22.51 | PASS |
| 8220.50† | 7521.99 | -396.85 | -2406.55 | 7428.97 | 7521.99 | 8473.01 | -2157.84 | 1.61 | 8873.36 | 403.50 | 8469.85 | 22.20 | PASS |
| 8315.56 | 7529.50 | -302.24 | -2409.34 | 7436.49 | 7529.50 | 8473.01 | -2157.84 | 1.64 | 8778.86 | 403.91 | 8374.95 | 21.94 | PASS |
| 8320.50† | 7529.51 | -297.30 | -2409.35 | 7436.49 | 7529.51 | 8473.01 | -2157.84 | 1.64 | 8773.92 | 403.91 | 8370.01 | 21.93 | PASS |
| 8420.50† | 7529.61 | -197.30 | -2409.53 | 7436.60 | 7529.61 | 8473.01 | -2157.84 | 1.66 | 8673.97 | 403.93 | 8270.04 | 21.68 | PASS |
| 8520.50† | 7529.71 | -97.30 | -2409.71 | 7436.70 | 7529.71 | 8473.01 | -2157.84 | 1.68 | 8574.02 | 403.95 | 8170.07 | 21.43 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 21 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. GLEN YOUNG 1 AWP Offset Wellpath: EX. GLEN YOUNG 1 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#01 EX. GLEN YOUNG 1 (1320'FNL & 1320'FEL, PA) Well: EX. GLEN YOUNG 1 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 8620.50† | 7529.82 | 2.70 | -2409.88 | 7436.81 | 7529.82 | 8473.01 | -2157.84 | 1.70 | 8474.07 | 403.97 | 8070.09 | 21.18 | PASS |
| 8720.50† | 7529.92 | 102.70 | -2410.06 | 7436.91 | 7529.92 | 8473.01 | -2157.84 | 1.73 | 8374.12 | 403.99 | 7970.12 | 20.92 | PASS |
| 8820.50† | 7530.02 | 202.70 | -2410.24 | 7437.01 | 7530.02 | 8473.01 | -2157.84 | 1.75 | 8274.17 | 404.02 | 7870.15 | 20.67 | PASS |
| 8920.50† | 7530.13 | 302.70 | -2410.42 | 7437.12 | 7530.13 | 8473.01 | -2157.84 | 1.77 | 8174.22 | 404.04 | 7770.18 | 20.42 | PASS |
| 9020.50† | 7530.23 | 402.70 | -2410.59 | 7437.22 | 7530.23 | 8473.01 | -2157.84 | 1.79 | 8074.28 | 404.06 | 7670.22 | 20.17 | PASS |
| 9120.50† | 7530.33 | 502.70 | -2410.77 | 7437.32 | 7530.33 | 8473.01 | -2157.84 | 1.82 | 7974.33 | 404.08 | 7570.25 | 19.92 | PASS |
| 9220.50† | 7530.44 | 602.70 | -2410.95 | 7437.43 | 7530.44 | 8473.01 | -2157.84 | 1.84 | 7874.39 | 404.11 | 7470.28 | 19.67 | PASS |
| 9320.50† | 7530.54 | 702.70 | -2411.13 | 7437.53 | 7530.54 | 8473.01 | -2157.84 | 1.87 | 7774.45 | 404.13 | 7370.31 | 19.42 | PASS |
| 9420.50† | 7530.64 | 802.69 | -2411.31 | 7437.63 | 7530.64 | 8473.01 | -2157.84 | 1.89 | 7674.51 | 404.16 | 7270.35 | 19.17 | PASS |
| 9520.50† | 7530.75 | 902.69 | -2411.48 | 7437.74 | 7530.75 | 8473.01 | -2157.84 | 1.92 | 7574.57 | 404.18 | 7170.38 | 18.92 | PASS |
| 9620.50† | 7530.85 | 1002.69 | -2411.66 | 7437.84 | 7530.85 | 8473.01 | -2157.84 | 1.95 | 7474.63 | 404.21 | 7070.42 | 18.67 | PASS |
| 9720.50† | 7530.96 | 1102.69 | -2411.84 | 7437.95 | 7530.96 | 8473.01 | -2157.84 | 1.97 | 7374.70 | 404.24 | 6970.46 | 18.42 | PASS |
| 9820.50† | 7531.06 | 1202.69 | -2412.02 | 7438.05 | 7531.06 | 8473.01 | -2157.84 | 2.00 | 7274.76 | 404.27 | 6870.50 | 18.16 | PASS |
| 9920.50† | 7531.16 | 1302.69 | -2412.19 | 7438.15 | 7531.16 | 8473.01 | -2157.84 | 2.03 | 7174.83 | 404.30 | 6770.54 | 17.91 | PASS |
| 10020.50† | 7531.27 | 1402.69 | -2412.37 | 7438.26 | 7531.27 | 8473.01 | -2157.84 | 2.06 | 7074.90 | 404.33 | 6670.58 | 17.66 | PASS |
| 10120.50† | 7531.37 | 1502.69 | -2412.55 | 7438.36 | 7531.37 | 8473.01 | -2157.84 | 2.09 | 6974.97 | 404.36 | 6570.62 | 17.41 | PASS |
| 10220.50† | 7531.47 | 1602.69 | -2412.73 | 7438.46 | 7531.47 | 8473.01 | -2157.84 | 2.13 | 6875.05 | 404.39 | 6470.66 | 17.16 | PASS |
| 10320.50† | 7531.58 | 1702.69 | -2412.90 | 7438.57 | 7531.58 | 8473.01 | -2157.84 | 2.16 | 6775.12 | 404.42 | 6370.70 | 16.91 | PASS |
| 10420.50† | 7531.68 | 1802.69 | -2413.08 | 7438.67 | 7531.68 | 8473.01 | -2157.84 | 2.19 | 6675.20 | 404.45 | 6270.75 | 16.66 | PASS |
| 10520.50† | 7531.78 | 1902.69 | -2413.26 | 7438.78 | 7531.78 | 8473.01 | -2157.84 | 2.23 | 6575.29 | 404.49 | 6170.80 | 16.41 | PASS |
| 10620.50† | 7531.89 | 2002.69 | -2413.44 | 7438.88 | 7531.89 | 8473.01 | -2157.84 | 2.26 | 6475.37 | 404.52 | 6070.85 | 16.16 | PASS |
| 10720.50† | 7531.99 | 2102.69 | -2413.62 | 7438.98 | 7531.99 | 8473.01 | -2157.84 | 2.30 | 6375.46 | 404.56 | 5970.90 | 15.91 | PASS |
| 10820.50† | 7532.09 | 2202.69 | -2413.79 | 7439.09 | 7532.09 | 8473.01 | -2157.84 | 2.34 | 6275.54 | 404.60 | 5870.95 | 15.65 | PASS |
| 10920.50† | 7532.20 | 2302.69 | -2413.97 | 7439.19 | 7532.20 | 8473.01 | -2157.84 | 2.38 | 6175.64 | 404.64 | 5771.00 | 15.40 | PASS |
| 11020.50† | 7532.30 | 2402.69 | -2414.15 | 7439.29 | 7532.30 | 8473.01 | -2157.84 | 2.42 | 6075.73 | 404.68 | 5671.06 | 15.15 | PASS |
| 11120.50† | 7532.41 | 2502.69 | -2414.33 | 7439.40 | 7532.41 | 8473.01 | -2157.84 | 2.46 | 5975.83 | 404.72 | 5571.11 | 14.90 | PASS |
| 11220.50† | 7532.51 | 2602.69 | -2414.50 | 7439.50 | 7532.51 | 8473.01 | -2157.84 | 2.50 | 5875.93 | 404.76 | 5471.17 | 14.65 | PASS |
| 11320.50† | 7532.61 | 2702.69 | -2414.68 | 7439.60 | 7532.61 | 8473.01 | -2157.84 | 2.55 | 5776.04 | 404.80 | 5371.23 | 14.40 | PASS |
| 11420.50† | 7532.72 | 2802.69 | -2414.86 | 7439.71 | 7532.72 | 8473.01 | -2157.84 | 2.60 | 5676.15 | 404.85 | 5271.30 | 14.15 | PASS |
| 11520.50† | 7532.82 | 2902.69 | -2415.04 | 7439.81 | 7532.82 | 8473.01 | -2157.84 | 2.64 | 5576.26 | 404.90 | 5171.36 | 13.90 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 22 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. GLEN YOUNG 1 AWB Offset Wellpath: EX. GLEN YOUNG 1 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#01 EX. GLEN YOUNG 1 (1320'FNL & 1320'FEL, PA) Well: EX. GLEN YOUNG 1 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 11620.50† | 7532.92 | 3002.69 | -2415.21 | 7439.92 | 7532.92 | 8473.01 | -2157.84 | 2.69 | 5476.38 | 404.95 | 5071.43 | 13.65 | PASS |
| 11720.50† | 7533.03 | 3102.69 | -2415.39 | 7440.02 | 7533.03 | 8473.01 | -2157.84 | 2.75 | 5376.50 | 405.00 | 4971.50 | 13.40 | PASS |
| 11820.50† | 7533.13 | 3202.69 | -2415.57 | 7440.12 | 7533.13 | 8473.01 | -2157.84 | 2.80 | 5276.62 | 405.05 | 4871.58 | 13.15 | PASS |
| 11920.50† | 7533.23 | 3302.69 | -2415.75 | 7440.23 | 7533.23 | 8473.01 | -2157.84 | 2.86 | 5176.75 | 405.10 | 4771.65 | 12.90 | PASS |
| 12020.50† | 7533.34 | 3402.69 | -2415.92 | 7440.33 | 7533.34 | 8473.01 | -2157.84 | 2.91 | 5076.89 | 405.16 | 4671.73 | 12.65 | PASS |
| 12120.50† | 7533.44 | 3502.69 | -2416.10 | 7440.43 | 7533.44 | 8473.01 | -2157.84 | 2.97 | 4977.03 | 405.22 | 4571.82 | 12.39 | PASS |
| 12220.50† | 7533.55 | 3602.69 | -2416.28 | 7440.54 | 7533.55 | 8473.01 | -2157.84 | 3.04 | 4877.18 | 405.28 | 4471.90 | 12.14 | PASS |
| 12320.50† | 7533.65 | 3702.69 | -2416.46 | 7440.64 | 7533.65 | 8473.01 | -2157.84 | 3.10 | 4777.33 | 405.34 | 4371.99 | 11.89 | PASS |
| 12420.50† | 7533.75 | 3802.69 | -2416.64 | 7440.74 | 7533.75 | 8473.01 | -2157.84 | 3.17 | 4677.49 | 405.40 | 4272.09 | 11.64 | PASS |
| 12520.50† | 7533.86 | 3902.69 | -2416.81 | 7440.85 | 7533.86 | 8473.01 | -2157.84 | 3.24 | 4577.66 | 405.47 | 4172.19 | 11.39 | PASS |
| 12620.50† | 7533.96 | 4002.69 | -2416.99 | 7440.95 | 7533.96 | 8473.01 | -2157.84 | 3.32 | 4477.83 | 405.54 | 4072.29 | 11.14 | PASS |
| 12720.50† | 7534.06 | 4102.69 | -2417.17 | 7441.06 | 7534.06 | 8473.01 | -2157.84 | 3.40 | 4378.01 | 405.61 | 3972.40 | 10.89 | PASS |
| 12820.50† | 7534.17 | 4202.69 | -2417.35 | 7441.16 | 7534.17 | 8473.01 | -2157.84 | 3.48 | 4278.20 | 405.69 | 3872.51 | 10.64 | PASS |
| 12920.50† | 7534.27 | 4302.69 | -2417.52 | 7441.26 | 7534.27 | 8473.01 | -2157.84 | 3.56 | 4178.40 | 405.77 | 3772.63 | 10.39 | PASS |
| 13020.50† | 7534.37 | 4402.69 | -2417.70 | 7441.37 | 7534.37 | 8473.01 | -2157.84 | 3.65 | 4078.61 | 405.85 | 3672.76 | 10.14 | PASS |
| 13120.50† | 7534.48 | 4502.69 | -2417.88 | 7441.47 | 7534.48 | 8473.01 | -2157.84 | 3.75 | 3978.83 | 405.94 | 3572.89 | 9.89 | PASS |
| 13199.97 | 7534.56 | 4582.16 | -2418.02 | 7441.55 | 7534.56 | 8473.01 | -2157.84 | 3.83 | 3899.54 | 406.02 | 3493.53 | 9.69 | PASS |
| 13220.50† | 7534.58 | 4602.69 | -2418.13 | 7441.57 | 7534.58 | 8473.01 | -2157.84 | 3.85 | 3879.07 | 406.04 | 3473.04 | 9.64 | PASS |
| 13320.50† | 7534.68 | 4702.65 | -2420.77 | 7441.68 | 7534.68 | 8473.01 | -2157.84 | 3.99 | 3779.52 | 406.16 | 3373.36 | 9.39 | PASS |
| 13420.50† | 7534.79 | 4802.45 | -2426.90 | 7441.78 | 7534.79 | 8473.01 | -2157.84 | 4.19 | 3680.41 | 406.34 | 3274.07 | 9.14 | PASS |
| 13476.50 | 7534.85 | 4858.23 | -2431.85 | 7441.84 | 7534.85 | 8473.01 | -2157.84 | 4.34 | 3625.15 | 406.47 | 3218.68 | 9.00 | PASS |
| 13520.50† | 7534.89 | 4902.02 | -2436.16 | 7441.88 | 7534.89 | 8473.01 | -2157.84 | 4.46 | 3581.82 | 406.57 | 3175.25 | 8.89 | PASS |
| 13620.50† | 7534.99 | 5001.54 | -2445.98 | 7441.99 | 7534.99 | 8473.01 | -2157.84 | 4.75 | 3483.41 | 406.83 | 3076.59 | 8.64 | PASS |
| 13720.50† | 7535.10 | 5101.06 | -2455.79 | 7442.09 | 7535.10 | 8473.01 | -2157.84 | 5.05 | 3385.10 | 407.10 | 2978.00 | 8.39 | PASS |
| 13820.50† | 7535.20 | 5200.57 | -2465.61 | 7442.19 | 7535.20 | 8473.01 | -2157.84 | 5.37 | 3286.88 | 407.39 | 2879.49 | 8.14 | PASS |
| 13920.50† | 7535.30 | 5300.09 | -2475.42 | 7442.29 | 7535.30 | 8473.01 | -2157.84 | 5.72 | 3188.78 | 407.71 | 2781.07 | 7.89 | PASS |
| 14020.50† | 7535.40 | 5399.61 | -2485.24 | 7442.40 | 7535.40 | 8473.01 | -2157.84 | 6.08 | 3090.80 | 408.04 | 2682.75 | 7.64 | PASS |
| 14120.50† | 7535.51 | 5499.12 | -2495.05 | 7442.50 | 7535.51 | 8473.01 | -2157.84 | 6.47 | 2992.95 | 408.40 | 2584.54 | 7.39 | PASS |
| 14220.50† | 7535.61 | 5598.64 | -2504.87 | 7442.60 | 7535.61 | 8473.01 | -2157.84 | 6.88 | 2895.25 | 408.79 | 2486.45 | 7.14 | PASS |
| 14221.87 | 7535.61 | 5600.00 | -2505.00 | 7442.60 | 7535.61 | 8473.01 | -2157.84 | 6.89 | 2893.91 | 408.80 | 2485.11 | 7.14 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 23 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. GLEN YOUNG 1 AWB Offset Wellpath: EX. GLEN YOUNG 1 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#01 EX. GLEN YOUNG 1 (1320'FNL & 1320'FEL, PA) Well: EX. GLEN YOUNG 1 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 14320.50† | 7535.71 | 5698.31 | -2512.99 | 7442.70 | 7535.71 | 8473.01 | -2157.84 | 7.29 | 2797.35 | 409.18 | 2388.16 | 6.89 | PASS |
| 14420.50† | 7535.81 | 5798.19 | -2517.63 | 7442.81 | 7535.81 | 8473.01 | -2157.84 | 7.66 | 2698.91 | 409.54 | 2289.37 | 6.65 | PASS |
| 14520.50† | 7535.92 | 5898.18 | -2518.78 | 7442.91 | 7535.92 | 8473.01 | -2157.84 | 7.98 | 2600.01 | 409.85 | 2190.16 | 6.40 | PASS |
| 14581.38 | 7535.98 | 5959.05 | -2517.77 | 7442.97 | 7535.98 | 8473.01 | -2157.84 | 8.15 | 2539.60 | 410.01 | 2129.58 | 6.24 | PASS |
| 14620.50† | 7536.02 | 5998.16 | -2516.71 | 7443.01 | 7536.02 | 8473.01 | -2157.84 | 8.25 | 2500.74 | 410.11 | 2090.63 | 6.15 | PASS |
| 14720.50† | 7536.12 | 6098.12 | -2513.99 | 7443.12 | 7536.12 | 8473.01 | -2157.84 | 8.53 | 2401.45 | 410.39 | 1991.06 | 5.90 | PASS |
| 14820.50† | 7536.23 | 6198.08 | -2511.27 | 7443.22 | 7536.23 | 8473.01 | -2157.84 | 8.83 | 2302.22 | 410.69 | 1891.53 | 5.65 | PASS |
| 14920.50† | 7536.33 | 6298.05 | -2508.55 | 7443.32 | 7536.33 | 8473.01 | -2157.84 | 9.16 | 2203.06 | 411.02 | 1792.05 | 5.40 | PASS |
| 15020.50† | 7536.43 | 6398.01 | -2505.83 | 7443.43 | 7536.43 | 8473.01 | -2157.84 | 9.52 | 2103.98 | 411.38 | 1692.60 | 5.15 | PASS |
| 15120.50† | 7536.54 | 6497.97 | -2503.11 | 7443.53 | 7536.54 | 8473.01 | -2157.84 | 9.92 | 2005.00 | 411.78 | 1593.22 | 4.91 | PASS |
| 15220.50† | 7536.64 | 6597.93 | -2500.40 | 7443.64 | 7536.64 | 8473.01 | -2157.84 | 10.35 | 1906.11 | 412.22 | 1493.89 | 4.66 | PASS |
| 15320.50† | 7536.74 | 6697.90 | -2497.68 | 7443.74 | 7536.74 | 8473.01 | -2157.84 | 10.84 | 1807.35 | 412.72 | 1394.63 | 4.41 | PASS |
| 15420.50† | 7536.85 | 6797.86 | -2494.96 | 7443.84 | 7536.85 | 8473.01 | -2157.84 | 11.38 | 1708.74 | 413.28 | 1295.46 | 4.17 | PASS |
| 15520.50† | 7536.95 | 6897.82 | -2492.24 | 7443.95 | 7536.95 | 8473.01 | -2157.84 | 11.99 | 1610.29 | 413.91 | 1196.38 | 3.92 | PASS |
| 15620.50† | 7537.05 | 6997.79 | -2489.52 | 7444.05 | 7537.05 | 8473.01 | -2157.84 | 12.67 | 1512.05 | 414.64 | 1097.42 | 3.67 | PASS |
| 15720.50† | 7537.16 | 7097.75 | -2486.80 | 7444.15 | 7537.16 | 8473.01 | -2157.84 | 13.45 | 1414.06 | 415.47 | 998.59 | 3.43 | PASS |
| 15820.50† | 7537.26 | 7197.71 | -2484.08 | 7444.26 | 7537.26 | 8473.01 | -2157.84 | 14.35 | 1316.37 | 416.44 | 899.92 | 3.18 | PASS |
| 15920.50† | 7537.36 | 7297.68 | -2481.36 | 7444.36 | 7537.36 | 8473.01 | -2157.84 | 15.39 | 1219.05 | 417.59 | 801.46 | 2.94 | PASS |
| 16020.50† | 7537.47 | 7397.64 | -2478.64 | 7444.46 | 7537.47 | 8473.01 | -2157.84 | 16.61 | 1122.21 | 418.96 | 703.25 | 2.69 | PASS |
| 16120.50† | 7537.57 | 7497.60 | -2475.93 | 7444.57 | 7537.57 | 8473.01 | -2157.84 | 18.06 | 1025.97 | 420.61 | 605.36 | 2.45 | PASS |
| 16220.50† | 7537.68 | 7597.56 | -2473.21 | 7444.67 | 7537.68 | 8473.01 | -2157.84 | 19.81 | 930.52 | 422.63 | 507.89 | 2.21 | PASS |
| 16320.50† | 7537.78 | 7697.53 | -2470.49 | 7444.77 | 7537.78 | 8473.01 | -2157.84 | 21.96 | 836.14 | 425.16 | 410.98 | 1.98 | PASS |
| 16420.50† | 7537.88 | 7797.49 | -2467.77 | 7444.88 | 7537.88 | 8473.01 | -2157.84 | 24.65 | 743.23 | 428.38 | 314.85 | 1.74 | PASS |
| 16520.50† | 7537.99 | 7897.45 | -2465.05 | 7444.98 | 7537.99 | 8473.01 | -2157.84 | 28.09 | 652.42 | 432.55 | 219.87 | 1.51 | PASS |
| 16620.50† | 7538.09 | 7997.42 | -2462.33 | 7445.08 | 7538.09 | 8473.01 | -2157.84 | 32.63 | 564.72 | 438.00 | 126.72 | 1.29 | PASS |
| 16720.50† | 7538.19 | 8097.38 | -2459.61 | 7445.19 | 7538.19 | 8473.01 | -2157.84 | 38.78 | 481.84 | 445.13 | 36.71 | 1.08 | WARN |
| 16820.50† | 7538.30 | 8197.34 | -2456.89 | 7445.29 | 7538.30 | 8473.01 | -2157.84 | 47.33 | 406.73 | 454.02 | -47.30 | 0.89 | FAIL |
| 16920.50† | 7538.40 | 8297.31 | -2454.17 | 7445.39 | 7538.40 | 8473.01 | -2157.84 | 59.33 | 344.51 | 463.34 | -118.82 | 0.74 | FAIL |
| 17020.50† | 7538.50 | 8397.27 | -2451.46 | 7445.50 | 7538.50 | 8473.01 | -2157.84 | 75.53 | 303.23 | 468.01 | -164.78 | 0.64 | FAIL |
| 17086.59† | 7538.57 | 8463.33 | -2449.66 | 7445.57 | 7538.57 | 8473.01 | -2157.84 | 88.10 | 291.98 | 464.71 | -172.73 | 0.63 | FAIL |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 24 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. GLEN YOUNG 1 AWB Offset Wellpath: EX. GLEN YOUNG 1 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#01 EX. GLEN YOUNG 1 (1320'FNL & 1320'FEL, PA) Well: EX. GLEN YOUNG 1 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 17104.20† | 7538.59 | 8480.94 | -2449.18 | 7445.58 | 7538.59 | 8473.01 | -2157.84 | 91.56 | 291.45 | 462.80 | -171.35 | 0.63 | FAIL |
| 17120.50† | 7538.61 | 8497.23 | -2448.74 | 7445.60 | 7538.61 | 8473.01 | -2157.84 | 94.76 | 291.90 | 460.66 | -168.75 | 0.63 | FAIL |
| 17220.50† | 7538.71 | 8597.19 | -2446.02 | 7445.70 | 7538.71 | 8473.01 | -2157.84 | 113.31 | 313.79 | 442.79 | -129.00 | 0.71 | FAIL |
| 17320.50† | 7538.81 | 8697.16 | -2443.30 | 7445.81 | 7538.81 | 8473.01 | -2157.84 | 128.14 | 362.94 | 425.18 | -62.24 | 0.85 | FAIL |
| 17420.50† | 7538.92 | 8797.12 | -2440.58 | 7445.91 | 7538.92 | 8473.01 | -2157.84 | 138.90 | 430.10 | 413.34 | 16.76 | 1.04 | WARN |
| 17520.50† | 7539.02 | 8897.08 | -2437.86 | 7446.01 | 7539.02 | 8473.01 | -2157.84 | 146.56 | 508.18 | 406.55 | 101.63 | 1.25 | PASS |
| 17620.50† | 7539.12 | 8997.05 | -2435.14 | 7446.12 | 7539.12 | 8473.01 | -2157.84 | 152.11 | 592.88 | 402.86 | 190.02 | 1.48 | PASS |
| 17720.50† | 7539.23 | 9097.01 | -2432.42 | 7446.22 | 7539.23 | 8473.01 | -2157.84 | 156.25 | 681.74 | 400.91 | 280.83 | 1.71 | PASS |
| 17820.50† | 7539.33 | 9196.97 | -2429.70 | 7446.32 | 7539.33 | 8473.01 | -2157.84 | 159.42 | 773.32 | 399.91 | 373.41 | 1.94 | PASS |
| 17920.50† | 7539.43 | 9296.94 | -2426.99 | 7446.43 | 7539.43 | 8473.01 | -2157.84 | 161.91 | 866.77 | 399.45 | 467.32 | 2.18 | PASS |
| 17985.90 | 7539.50 | 9362.31 | -2425.21 | 7446.50 | 7539.50 | 8473.01 | -2157.84 | 163.27 | 928.61 | 399.31 | 529.30 | 2.34 | PASS |

POSITIONAL UNCERTAINTY - Offset Wellbore: EX. GLEN YOUNG 1 AWB Offset Wellpath: EX. GLEN YOUNG 1 AWP

| | | | | |
|-----------------------------------|------------|---------|----------|---------|
| Slot Surface Uncertainty @1SD | Horizontal | 0.100ft | Vertical | 1.000ft |
| Facility Surface Uncertainty @1SD | Horizontal | 8.200ft | Vertical | 3.000ft |

WELLPATH COMPOSITION - Offset Wellbore: EX. GLEN YOUNG 1 AWB Offset Wellpath: EX. GLEN YOUNG 1 AWP

| Start MD [ft] | End MD [ft] | Positional Uncertainty Model | Log Name/Comment | Wellbore | Survey Date |
|---------------|-------------|---|--|----------------------|-------------|
| 0.00 | 8100.00 | BH Drift Indicator - Inclination Only (Actual Survey) | ASSUMED VERTICAL TO TD FROM COGCC <8100> | EX. GLEN YOUNG 1 AWB | |

OFFSET WELLPATH REFERENCE - Offset Wellbore: EX. GLEN YOUNG 1 AWB Offset Wellpath: EX. GLEN YOUNG 1 AWP

| | |
|--|---|
| MD Reference: Rig on SLOT#01 EX. GLEN YOUNG 1 (1320'FNL & 1320'FEL, SEC.28) (RT) | Offset TVD & local coordinates use Reference Wellpath settings (See WELLPATH DATUM on page 1 of this report) |
| Ellipse Start MD | 0.00ft |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 25 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770°FSL & 819°FSL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-5-1L PWB Offset Wellpath: BUFORD 33-5-1L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#03 BUFORD 33-5-1L (770°FSL & 794°FSL, SEC.34) Well: BUFORD 33-5-1L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | |
| 20.50 | 20.50 | 0.00 | 0.00 | 19.50 | 20.50 | 0.00 | -25.21 | 270.00 | 25.21 | 9.74 | 15.48 | 3.69 | PASS | | |
| 120.50† | 120.50 | 0.00 | 0.00 | 119.50 | 120.50 | 0.00 | -25.21 | 270.00 | 25.21 | 7.94 | 17.27 | 3.96 | PASS | | |
| 200.00 | 200.00 | 0.00 | 0.00 | 199.00 | 200.00 | 0.00 | -25.21 | 270.00 | 25.21 | 8.09 | 17.13 | 3.86 | PASS | | |
| 220.50† | 220.50 | -0.03 | -0.07 | 219.50 | 220.50 | 0.00 | -25.21 | 270.06 | 25.15 | 8.14 | 17.01 | 3.82 | PASS | | |
| 320.50† | 320.46 | -0.93 | -2.36 | 319.46 | 320.46 | 0.00 | -25.21 | 272.34 | 22.88 | 8.53 | 14.35 | 3.24 | PASS | | |
| 420.50† | 420.28 | -3.13 | -7.88 | 419.28 | 420.28 | 0.00 | -25.21 | 280.23 | 17.61 | 9.16 | 8.45 | 2.20 | PASS | | |
| 520.50† | 519.83 | -6.60 | -16.65 | 518.79 | 519.79 | -0.02 | -25.27 | 307.37 | 10.85 | 9.57 | 1.29 | 1.17 | PASS | | |
| 571.04† | 570.01 | -8.85 | -22.31 | 568.98 | 569.97 | -0.21 | -26.02 | 336.74 | 9.40 | 9.70 | -0.30 | 0.96 | FAIL | | |
| 576.04† | 574.96 | -9.08 | -22.91 | 573.94 | 574.94 | -0.24 | -26.14 | 339.95 | 9.42 | 9.73 | -0.31 | 0.96 | FAIL | | |
| 620.50† | 618.99 | -11.36 | -28.64 | 618.18 | 619.14 | -0.61 | -27.57 | 5.64 | 10.80 | 10.18 | 0.62 | 1.08 | WARN | | |
| 720.50† | 717.64 | -17.38 | -43.83 | 717.92 | 718.71 | -2.06 | -33.24 | 34.67 | 18.66 | 11.47 | 7.18 | 1.77 | PASS | | |
| 820.50† | 815.66 | -24.68 | -62.22 | 818.03 | 818.37 | -4.39 | -42.29 | 44.50 | 28.56 | 12.59 | 15.97 | 2.52 | PASS | | |
| 920.50† | 912.93 | -33.22 | -83.78 | 918.49 | 918.00 | -7.60 | -54.76 | 48.55 | 39.04 | 13.62 | 25.42 | 3.21 | PASS | | |
| 1020.50† | 1009.33 | -43.02 | -108.48 | 1019.31 | 1017.47 | -11.69 | -70.67 | 50.36 | 49.77 | 14.61 | 35.16 | 3.81 | PASS | | |
| 1120.50† | 1104.74 | -54.05 | -136.29 | 1120.49 | 1116.65 | -16.67 | -90.04 | 51.06 | 60.65 | 15.60 | 45.05 | 4.34 | PASS | | |
| 1220.50† | 1199.05 | -66.30 | -167.18 | 1222.03 | 1215.41 | -22.55 | -112.87 | 51.15 | 71.64 | 16.58 | 55.05 | 4.80 | PASS | | |
| 1242.54 | 1219.68 | -69.16 | -174.40 | 1244.45 | 1237.10 | -23.96 | -118.37 | 51.11 | 74.07 | 16.79 | 57.28 | 4.90 | PASS | | |
| 1320.50† | 1292.54 | -79.39 | -200.20 | 1324.02 | 1313.70 | -29.32 | -139.20 | 50.62 | 81.71 | 17.47 | 64.24 | 5.18 | PASS | | |
| 1420.50† | 1385.99 | -92.51 | -233.28 | 1426.54 | 1411.47 | -37.00 | -169.06 | 49.16 | 88.63 | 18.35 | 70.27 | 5.33 | PASS | | |
| 1520.50† | 1479.44 | -105.63 | -266.37 | 1529.34 | 1508.33 | -45.57 | -202.39 | 46.81 | 92.39 | 18.47 | 73.91 | 5.40 | PASS | | |
| 1620.50† | 1572.89 | -118.75 | -299.46 | 1632.15 | 1603.91 | -55.00 | -239.07 | 43.45 | 93.13 | 18.75 | 74.38 | 5.36 | PASS | | |
| 1720.50† | 1666.34 | -131.87 | -332.54 | 1734.71 | 1697.84 | -65.26 | -278.94 | 38.82 | 91.12 | 19.27 | 71.85 | 5.09 | PASS | | |
| 1820.50† | 1759.79 | -144.99 | -365.63 | 1836.77 | 1789.78 | -76.29 | -321.82 | 32.52 | 86.83 | 20.12 | 66.71 | 4.62 | PASS | | |
| 1920.50† | 1853.24 | -158.12 | -398.72 | 1938.06 | 1879.42 | -88.04 | -367.49 | 24.02 | 81.06 | 21.51 | 59.55 | 4.00 | PASS | | |
| 2020.50† | 1946.69 | -171.24 | -431.80 | 2037.59 | 1966.09 | -100.23 | -414.89 | 13.40 | 75.53 | 23.61 | 51.92 | 3.37 | PASS | | |
| 2120.50† | 2040.14 | -184.36 | -464.89 | 2136.27 | 2051.85 | -112.39 | -462.17 | 2.17 | 72.97 | 26.14 | 46.82 | 2.91 | PASS | | |
| 2220.50† | 2133.59 | -197.48 | -497.98 | 2234.95 | 2137.61 | -124.55 | -509.44 | 351.06 | 73.94 | 28.64 | 45.29 | 2.68 | PASS | | |
| 2320.50† | 2227.05 | -210.60 | -531.06 | 2333.64 | 2223.38 | -136.71 | -556.72 | 340.85 | 78.31 | 30.69 | 47.61 | 2.64 | PASS | | |
| 2420.50† | 2320.50 | -223.72 | -564.15 | 2432.32 | 2309.14 | -148.87 | -604.00 | 331.97 | 85.56 | 32.20 | 53.36 | 2.75 | PASS | | |
| 2520.50† | 2413.95 | -236.84 | -597.24 | 2531.01 | 2394.90 | -161.03 | -651.28 | 324.52 | 95.03 | 33.28 | 61.75 | 2.95 | PASS | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 26 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-5-1L PWB Offset Wellpath: BUFORD 33-5-1L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#03 BUFORD 33-5-1L (770'FSL & 794'FWL, SEC.34) | | | | Well: BUFORD 33-5-1L | | Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | |
|---|-----------------|-------------------|------------------|----------------------|--------------------|---|---------------------|-------------------------|---------------------------|----------------------|----------------------------|--------------|----------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 2620.50† | 2507.40 | -249.96 | -630.32 | 2629.69 | 2480.67 | -173.19 | -698.56 | 318.37 | 106.14 | 34.12 | 72.01 | 3.22 | PASS |
| 2720.50† | 2600.85 | -263.08 | -663.41 | 2728.38 | 2566.43 | -185.35 | -745.84 | 313.32 | 118.41 | 34.85 | 83.56 | 3.52 | PASS |
| 2820.50† | 2694.30 | -276.20 | -696.50 | 2827.06 | 2652.19 | -197.51 | -793.12 | 309.16 | 131.53 | 35.55 | 95.99 | 3.84 | PASS |
| 2920.50† | 2787.75 | -289.33 | -729.58 | 2925.74 | 2737.96 | -209.67 | -840.40 | 305.71 | 145.27 | 36.26 | 109.02 | 4.15 | PASS |
| 3020.50† | 2881.20 | -302.45 | -762.67 | 3024.43 | 2823.72 | -221.83 | -887.68 | 302.82 | 159.47 | 36.99 | 122.47 | 4.47 | PASS |
| 3120.50† | 2974.65 | -315.57 | -795.76 | 3123.11 | 2909.48 | -233.99 | -934.96 | 300.37 | 174.01 | 37.77 | 136.24 | 4.78 | PASS |
| 3220.50† | 3068.11 | -328.69 | -828.84 | 3221.80 | 2995.25 | -246.15 | -982.24 | 298.28 | 188.81 | 38.58 | 150.23 | 5.07 | PASS |
| 3320.50† | 3161.56 | -341.81 | -861.93 | 3320.48 | 3081.01 | -258.31 | -1029.51 | 296.48 | 203.82 | 39.43 | 164.40 | 5.36 | PASS |
| 3420.50† | 3255.01 | -354.93 | -895.02 | 3419.16 | 3166.78 | -270.47 | -1076.79 | 294.92 | 219.00 | 40.31 | 178.69 | 5.63 | PASS |
| 3520.50† | 3348.46 | -368.05 | -928.10 | 3517.85 | 3252.54 | -282.63 | -1124.07 | 293.55 | 234.31 | 41.23 | 193.08 | 5.88 | PASS |
| 3620.50† | 3441.91 | -381.17 | -961.19 | 3616.53 | 3338.30 | -294.79 | -1171.35 | 292.34 | 249.73 | 42.17 | 207.56 | 6.13 | PASS |
| 3720.50† | 3535.36 | -394.29 | -994.28 | 3715.22 | 3424.07 | -306.95 | -1218.63 | 291.27 | 265.23 | 43.14 | 222.09 | 6.36 | PASS |
| 3820.50† | 3628.81 | -407.41 | -1027.37 | 3813.90 | 3509.83 | -319.12 | -1265.91 | 290.31 | 280.81 | 44.14 | 236.68 | 6.58 | PASS |
| 3920.50† | 3722.26 | -420.53 | -1060.45 | 3912.59 | 3595.59 | -331.28 | -1313.19 | 289.45 | 296.46 | 45.15 | 251.31 | 6.78 | PASS |
| 4020.50† | 3815.71 | -433.66 | -1093.54 | 4011.27 | 3681.36 | -343.44 | -1360.47 | 288.68 | 312.16 | 46.19 | 265.97 | 6.98 | PASS |
| 4120.50† | 3909.17 | -446.78 | -1126.63 | 4109.95 | 3767.12 | -355.60 | -1407.75 | 287.97 | 327.90 | 47.24 | 280.66 | 7.16 | PASS |
| 4220.50† | 4002.62 | -459.90 | -1159.71 | 4208.64 | 3852.88 | -367.76 | -1455.03 | 287.33 | 343.69 | 48.31 | 295.38 | 7.34 | PASS |
| 4320.50† | 4096.07 | -473.02 | -1192.80 | 4307.32 | 3938.65 | -379.92 | -1502.30 | 286.74 | 359.50 | 49.39 | 310.11 | 7.50 | PASS |
| 4420.50† | 4189.52 | -486.14 | -1225.89 | 4406.01 | 4024.41 | -392.08 | -1549.58 | 286.20 | 375.35 | 50.48 | 324.87 | 7.66 | PASS |
| 4520.50† | 4282.97 | -499.26 | -1258.97 | 4504.69 | 4110.17 | -404.24 | -1596.86 | 285.71 | 391.22 | 51.59 | 339.63 | 7.81 | PASS |
| 4620.50† | 4376.42 | -512.38 | -1292.06 | 4603.37 | 4195.94 | -416.40 | -1644.14 | 285.25 | 407.12 | 52.71 | 354.41 | 7.95 | PASS |
| 4720.50† | 4469.87 | -525.50 | -1325.15 | 4702.06 | 4281.70 | -428.56 | -1691.42 | 284.83 | 423.04 | 53.84 | 369.20 | 8.08 | PASS |
| 4820.50† | 4563.32 | -538.62 | -1358.23 | 4800.74 | 4367.46 | -440.72 | -1738.70 | 284.43 | 438.98 | 54.97 | 384.00 | 8.21 | PASS |
| 4920.50† | 4656.77 | -551.74 | -1391.32 | 4899.43 | 4453.23 | -452.88 | -1785.98 | 284.06 | 454.93 | 56.12 | 398.81 | 8.33 | PASS |
| 5020.50† | 4750.22 | -564.87 | -1424.41 | 4998.11 | 4538.99 | -465.04 | -1833.26 | 283.72 | 470.90 | 57.27 | 413.62 | 8.44 | PASS |
| 5120.50† | 4843.68 | -577.99 | -1457.49 | 5096.79 | 4624.75 | -477.20 | -1880.54 | 283.40 | 486.88 | 58.43 | 428.44 | 8.55 | PASS |
| 5220.50† | 4937.13 | -591.11 | -1490.58 | 5195.48 | 4710.52 | -489.36 | -1927.82 | 283.10 | 502.87 | 59.60 | 443.27 | 8.65 | PASS |
| 5320.50† | 5030.58 | -604.23 | -1523.67 | 5294.16 | 4796.28 | -501.52 | -1975.09 | 282.82 | 518.87 | 60.77 | 458.10 | 8.75 | PASS |
| 5420.50† | 5124.03 | -617.35 | -1556.75 | 5392.85 | 4882.04 | -513.68 | -2022.37 | 282.55 | 534.89 | 61.95 | 472.94 | 8.85 | PASS |
| 5520.50† | 5217.48 | -630.47 | -1589.84 | 5491.53 | 4967.81 | -525.84 | -2069.65 | 282.30 | 550.91 | 63.13 | 487.78 | 8.94 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 27 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770°FSL & 819°FSL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-5-1L PWB Offset Wellpath: BUFORD 33-5-1L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W | | Slot: SLOT#03 BUFORD 33-5-1L (770°FSL & 794°FSL, SEC.34) | | Well: BUFORD 33-5-1L | | Threshold Value=1.00 | | † = interpolated, ‡ = extrapolated station | | | | | | | |
|----------------------------|-----------------|--|------------------|----------------------|--------------------|----------------------|---------------------|--|---------------------------|----------------------|----------------------------|--------------|----------------|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | |
| 5620.50† | 5310.93 | -643.59 | -1622.93 | 5590.22 | 5053.57 | -538.00 | -2116.93 | 282.07 | 566.94 | 64.32 | 502.62 | 9.03 | PASS | | |
| 5720.50† | 5404.38 | -656.71 | -1656.01 | 5688.90 | 5139.34 | -550.16 | -2164.21 | 281.84 | 582.98 | 65.52 | 517.46 | 9.11 | PASS | | |
| 5820.50† | 5497.83 | -669.83 | -1689.10 | 5787.58 | 5225.10 | -562.33 | -2211.49 | 281.63 | 599.03 | 66.71 | 532.31 | 9.19 | PASS | | |
| 5920.50† | 5591.28 | -682.95 | -1722.19 | 5886.27 | 5310.86 | -574.49 | -2258.77 | 281.43 | 615.08 | 67.91 | 547.16 | 9.26 | PASS | | |
| 6020.50† | 5684.74 | -696.07 | -1755.27 | 5984.95 | 5396.63 | -586.65 | -2306.05 | 281.24 | 631.14 | 69.12 | 562.02 | 9.34 | PASS | | |
| 6120.50† | 5778.19 | -709.20 | -1788.36 | 6083.64 | 5482.39 | -598.81 | -2353.33 | 281.06 | 647.20 | 70.33 | 576.87 | 9.40 | PASS | | |
| 6220.50† | 5871.64 | -722.32 | -1821.45 | 6182.32 | 5568.15 | -610.97 | -2400.61 | 280.88 | 663.27 | 71.54 | 591.73 | 9.47 | PASS | | |
| 6320.50† | 5965.09 | -735.44 | -1854.54 | 6281.00 | 5653.92 | -623.13 | -2447.89 | 280.72 | 679.34 | 72.76 | 606.59 | 9.54 | PASS | | |
| 6420.50† | 6058.54 | -748.56 | -1887.62 | 6379.69 | 5739.68 | -635.29 | -2495.16 | 280.56 | 695.42 | 73.97 | 621.45 | 9.60 | PASS | | |
| 6520.50† | 6151.99 | -761.68 | -1920.71 | 6478.37 | 5825.44 | -647.45 | -2542.44 | 280.41 | 711.50 | 75.20 | 636.31 | 9.66 | PASS | | |
| 6620.50† | 6245.44 | -774.80 | -1953.80 | 6577.06 | 5911.21 | -659.61 | -2589.72 | 280.27 | 727.59 | 76.42 | 651.17 | 9.71 | PASS | | |
| 6720.50† | 6338.89 | -787.92 | -1986.88 | 6675.74 | 5996.97 | -671.77 | -2637.00 | 280.13 | 743.68 | 77.65 | 666.03 | 9.77 | PASS | | |
| 6820.50† | 6432.34 | -801.04 | -2019.97 | 6774.43 | 6082.73 | -683.93 | -2684.28 | 280.00 | 759.77 | 78.87 | 680.90 | 9.82 | PASS | | |
| 6920.50† | 6525.80 | -814.16 | -2053.06 | 6873.11 | 6168.50 | -696.09 | -2731.56 | 279.87 | 775.87 | 80.10 | 695.76 | 9.87 | PASS | | |
| 7020.50† | 6619.25 | -827.28 | -2086.14 | 6971.79 | 6254.26 | -708.25 | -2778.84 | 279.75 | 791.97 | 81.34 | 710.63 | 9.92 | PASS | | |
| 7120.50† | 6712.70 | -840.41 | -2119.23 | 7070.48 | 6340.02 | -720.41 | -2826.12 | 279.63 | 808.07 | 82.57 | 725.50 | 9.97 | PASS | | |
| 7220.50† | 6806.15 | -853.53 | -2152.32 | 7169.16 | 6425.79 | -732.57 | -2873.40 | 279.52 | 824.17 | 83.81 | 740.36 | 10.02 | PASS | | |
| 7320.50† | 6899.60 | -866.65 | -2185.40 | 7267.85 | 6511.55 | -744.73 | -2920.68 | 279.41 | 840.28 | 85.05 | 755.23 | 10.06 | PASS | | |
| 7341.07 | 6918.82 | -869.35 | -2192.21 | 7288.14 | 6529.19 | -747.23 | -2930.40 | 279.39 | 843.59 | 85.30 | 758.29 | 10.07 | PASS | | |
| 7420.50† | 6993.49 | -874.29 | -2218.65 | 7366.32 | 6597.13 | -756.87 | -2967.85 | 278.91 | 855.68 | 85.83 | 769.85 | 10.15 | PASS | | |
| 7520.50† | 7087.21 | -884.88 | -2251.87 | 7462.52 | 6680.73 | -768.72 | -3013.94 | 277.19 | 869.04 | 85.26 | 783.78 | 10.38 | PASS | | |
| 7620.50† | 7177.96 | -898.35 | -2284.05 | 7549.55 | 6756.46 | -778.43 | -3055.69 | 274.44 | 881.29 | 83.57 | 797.72 | 10.74 | PASS | | |
| 7720.50† | 7262.97 | -915.51 | -2314.23 | 7632.73 | 6829.18 | -776.02 | -3095.80 | 271.43 | 894.09 | 81.91 | 812.19 | 11.12 | PASS | | |
| 7820.50† | 7339.68 | -937.65 | -2341.49 | 7723.36 | 6906.64 | -757.06 | -3138.55 | 268.61 | 907.31 | 80.79 | 826.52 | 11.45 | PASS | | |
| 7920.50† | 7405.75 | -966.53 | -2364.99 | 7823.29 | 6986.70 | -717.24 | -3182.77 | 266.45 | 920.29 | 80.60 | 839.69 | 11.64 | PASS | | |
| 8020.50† | 7459.16 | -984.32 | -2384.03 | 7934.31 | 7064.95 | -651.85 | -3226.02 | 265.41 | 932.16 | 81.21 | 850.95 | 11.70 | PASS | | |
| 8120.50† | 7498.30 | -993.50 | -2398.02 | 8057.34 | 7133.62 | -557.55 | -3264.05 | 265.77 | 941.86 | 82.20 | 859.66 | 11.68 | PASS | | |
| 8220.50† | 7521.99 | -996.85 | -2406.55 | 8191.23 | 7181.73 | -435.98 | -3290.78 | 267.47 | 948.24 | 83.32 | 864.92 | 11.60 | PASS | | |
| 8315.56 | 7529.50 | -992.24 | -2409.34 | 8324.73 | 7198.50 | -304.31 | -3300.23 | 269.87 | 950.40 | 84.53 | 865.86 | 11.45 | PASS | | |
| 8320.50† | 7529.51 | -997.30 | -2409.35 | 8330.31 | 7198.50 | -298.73 | -3300.24 | 269.91 | 950.40 | 84.55 | 865.85 | 11.45 | PASS | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 28 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770°FSL & 819°FSL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-5-1L PWB Offset Wellpath: BUFORD 33-5-1L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#03 BUFORD 33-5-1L (770°FSL & 794°FSL, SEC.34) Well: BUFORD 33-5-1L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 8420.50† | 7529.61 | -197.30 | -2409.53 | 8430.31 | 7198.50 | -198.73 | -3300.41 | 269.91 | 950.42 | 84.69 | 865.73 | 11.43 | PASS |
| 8520.50† | 7529.71 | -97.30 | -2409.71 | 8530.31 | 7198.50 | -98.73 | -3300.57 | 269.91 | 950.44 | 84.99 | 865.45 | 11.39 | PASS |
| 8620.50† | 7529.82 | 2.70 | -2409.88 | 8630.31 | 7198.50 | 1.27 | -3300.73 | 269.91 | 950.46 | 85.51 | 864.95 | 11.32 | PASS |
| 8720.50† | 7529.92 | 102.70 | -2410.06 | 8730.31 | 7198.50 | 101.27 | -3300.89 | 269.91 | 950.48 | 86.18 | 864.30 | 11.23 | PASS |
| 8820.50† | 7530.02 | 202.70 | -2410.24 | 8830.31 | 7198.50 | 201.27 | -3301.05 | 269.91 | 950.50 | 87.01 | 863.49 | 11.12 | PASS |
| 8920.50† | 7530.13 | 302.70 | -2410.42 | 8930.31 | 7198.50 | 301.26 | -3301.21 | 269.91 | 950.52 | 88.00 | 862.52 | 10.99 | PASS |
| 9020.50† | 7530.23 | 402.70 | -2410.59 | 9030.31 | 7198.50 | 401.26 | -3301.37 | 269.91 | 950.54 | 89.13 | 861.41 | 10.85 | PASS |
| 9120.50† | 7530.33 | 502.70 | -2410.77 | 9130.31 | 7198.50 | 501.26 | -3301.53 | 269.91 | 950.56 | 90.40 | 860.16 | 10.70 | PASS |
| 9220.50† | 7530.44 | 602.70 | -2410.95 | 9230.31 | 7198.50 | 601.26 | -3301.69 | 269.91 | 950.58 | 91.81 | 858.77 | 10.53 | PASS |
| 9320.50† | 7530.54 | 702.70 | -2411.13 | 9330.31 | 7198.50 | 701.26 | -3301.85 | 269.91 | 950.60 | 93.35 | 857.25 | 10.35 | PASS |
| 9420.50† | 7530.64 | 802.69 | -2411.31 | 9430.31 | 7198.50 | 801.26 | -3302.01 | 269.91 | 950.62 | 95.01 | 855.61 | 10.17 | PASS |
| 9520.50† | 7530.75 | 902.69 | -2411.48 | 9530.31 | 7198.50 | 901.26 | -3302.17 | 269.91 | 950.64 | 96.79 | 853.85 | 9.98 | PASS |
| 9620.50† | 7530.85 | 1002.69 | -2411.66 | 9630.31 | 7198.50 | 1001.26 | -3302.33 | 269.91 | 950.66 | 98.68 | 851.98 | 9.78 | PASS |
| 9720.50† | 7530.96 | 1102.69 | -2411.84 | 9730.31 | 7198.50 | 1101.26 | -3302.49 | 269.91 | 950.68 | 100.67 | 850.01 | 9.58 | PASS |
| 9820.50† | 7531.06 | 1202.69 | -2412.02 | 9830.31 | 7198.50 | 1201.26 | -3302.65 | 269.91 | 950.70 | 102.76 | 847.94 | 9.39 | PASS |
| 9920.50† | 7531.16 | 1302.69 | -2412.19 | 9930.31 | 7198.50 | 1301.26 | -3302.81 | 269.91 | 950.72 | 104.94 | 845.78 | 9.19 | PASS |
| 10020.50† | 7531.27 | 1402.69 | -2412.37 | 10030.31 | 7198.50 | 1401.26 | -3302.98 | 269.91 | 950.74 | 107.21 | 843.53 | 8.99 | PASS |
| 10120.50† | 7531.37 | 1502.69 | -2412.55 | 10130.31 | 7198.50 | 1501.26 | -3303.14 | 269.91 | 950.76 | 109.56 | 841.20 | 8.80 | PASS |
| 10220.50† | 7531.47 | 1602.69 | -2412.73 | 10230.31 | 7198.50 | 1601.26 | -3303.30 | 269.91 | 950.78 | 111.98 | 838.80 | 8.61 | PASS |
| 10320.50† | 7531.58 | 1702.69 | -2412.90 | 10330.31 | 7198.50 | 1701.26 | -3303.46 | 269.91 | 950.80 | 114.48 | 836.33 | 8.42 | PASS |
| 10420.50† | 7531.68 | 1802.69 | -2413.08 | 10430.31 | 7198.50 | 1801.26 | -3303.62 | 269.91 | 950.82 | 117.04 | 833.79 | 8.23 | PASS |
| 10520.50† | 7531.78 | 1902.69 | -2413.26 | 10530.31 | 7198.50 | 1901.26 | -3303.78 | 269.91 | 950.84 | 119.66 | 831.18 | 8.05 | PASS |
| 10620.50† | 7531.89 | 2002.69 | -2413.44 | 10630.31 | 7198.50 | 2001.26 | -3303.94 | 269.91 | 950.86 | 122.34 | 828.53 | 7.87 | PASS |
| 10720.50† | 7531.99 | 2102.69 | -2413.62 | 10730.31 | 7198.50 | 2101.26 | -3304.10 | 269.91 | 950.88 | 125.07 | 825.81 | 7.69 | PASS |
| 10820.50† | 7532.09 | 2202.69 | -2413.79 | 10830.31 | 7198.50 | 2201.26 | -3304.26 | 269.91 | 950.91 | 127.85 | 823.05 | 7.52 | PASS |
| 10920.50† | 7532.20 | 2302.69 | -2413.97 | 10930.31 | 7198.50 | 2301.26 | -3304.42 | 269.91 | 950.93 | 130.68 | 820.24 | 7.36 | PASS |
| 11020.50† | 7532.30 | 2402.69 | -2414.15 | 11030.31 | 7198.50 | 2401.26 | -3304.58 | 269.91 | 950.95 | 133.56 | 817.39 | 7.20 | PASS |
| 11120.50† | 7532.41 | 2502.69 | -2414.33 | 11130.31 | 7198.50 | 2501.26 | -3304.74 | 269.91 | 950.97 | 136.47 | 814.49 | 7.04 | PASS |
| 11220.50† | 7532.51 | 2602.69 | -2414.50 | 11230.31 | 7198.50 | 2601.26 | -3304.90 | 269.91 | 950.99 | 139.43 | 811.56 | 6.89 | PASS |
| 11320.50† | 7532.61 | 2702.69 | -2414.68 | 11330.31 | 7198.50 | 2701.26 | -3305.06 | 269.91 | 951.01 | 142.42 | 808.59 | 6.75 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 29 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-5-1L PWB Offset Wellpath: BUFORD 33-5-1L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#03 BUFORD 33-5-1L (770'FSL & 794'FWL,SEC.34) Well: BUFORD 33-5-1L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|-----------------|-------------------|------------------|-------------------|--------------------|----------------------|---------------------|-------------------------|---------------------------|----------------------|----------------------------|--------------|----------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 11420.50† | 7532.72 | 2802.69 | -2414.86 | 11430.31 | 7198.50 | 2801.26 | -3305.22 | 269.91 | 951.03 | 145.44 | 805.59 | 6.60 | PASS |
| 11520.50† | 7532.82 | 2902.69 | -2415.04 | 11530.31 | 7198.50 | 2901.26 | -3305.38 | 269.91 | 951.05 | 148.50 | 802.55 | 6.47 | PASS |
| 11620.50† | 7532.92 | 3002.69 | -2415.21 | 11630.31 | 7198.50 | 3001.26 | -3305.55 | 269.91 | 951.07 | 151.58 | 799.49 | 6.33 | PASS |
| 11720.50† | 7533.03 | 3102.69 | -2415.39 | 11730.31 | 7198.50 | 3101.26 | -3305.71 | 269.91 | 951.09 | 154.69 | 796.40 | 6.21 | PASS |
| 11820.50† | 7533.13 | 3202.69 | -2415.57 | 11830.31 | 7198.50 | 3201.26 | -3305.87 | 269.91 | 951.11 | 157.83 | 793.28 | 6.08 | PASS |
| 11920.50† | 7533.23 | 3302.69 | -2415.75 | 11930.31 | 7198.50 | 3301.26 | -3306.03 | 269.91 | 951.13 | 161.00 | 790.13 | 5.96 | PASS |
| 12020.50† | 7533.34 | 3402.69 | -2415.92 | 12030.31 | 7198.50 | 3401.26 | -3306.19 | 269.91 | 951.15 | 164.18 | 786.97 | 5.84 | PASS |
| 12120.50† | 7533.44 | 3502.69 | -2416.10 | 12130.31 | 7198.50 | 3501.26 | -3306.35 | 269.91 | 951.17 | 167.39 | 783.78 | 5.73 | PASS |
| 12220.50† | 7533.55 | 3602.69 | -2416.28 | 12230.31 | 7198.50 | 3601.26 | -3306.51 | 269.91 | 951.19 | 170.62 | 780.57 | 5.62 | PASS |
| 12320.50† | 7533.65 | 3702.69 | -2416.46 | 12330.31 | 7198.50 | 3701.26 | -3306.67 | 269.91 | 951.21 | 173.87 | 777.34 | 5.51 | PASS |
| 12420.50† | 7533.75 | 3802.69 | -2416.64 | 12430.31 | 7198.50 | 3801.26 | -3306.83 | 269.91 | 951.23 | 177.14 | 774.10 | 5.41 | PASS |
| 12520.50† | 7533.86 | 3902.69 | -2416.81 | 12530.31 | 7198.50 | 3901.26 | -3306.99 | 269.91 | 951.25 | 180.42 | 770.83 | 5.31 | PASS |
| 12620.50† | 7533.96 | 4002.69 | -2416.99 | 12630.31 | 7198.50 | 4001.26 | -3307.15 | 269.91 | 951.27 | 183.72 | 767.55 | 5.22 | PASS |
| 12720.50† | 7534.06 | 4102.69 | -2417.17 | 12730.31 | 7198.50 | 4101.26 | -3307.31 | 269.91 | 951.29 | 187.04 | 764.26 | 5.12 | PASS |
| 12820.50† | 7534.17 | 4202.69 | -2417.35 | 12830.31 | 7198.50 | 4201.26 | -3307.47 | 269.91 | 951.32 | 190.37 | 760.95 | 5.03 | PASS |
| 12920.50† | 7534.27 | 4302.69 | -2417.52 | 12930.31 | 7198.50 | 4301.26 | -3307.63 | 269.91 | 951.34 | 193.71 | 757.62 | 4.95 | PASS |
| 13020.50† | 7534.37 | 4402.69 | -2417.70 | 13030.31 | 7198.50 | 4401.26 | -3307.79 | 269.91 | 951.36 | 197.07 | 754.28 | 4.86 | PASS |
| 13120.50† | 7534.48 | 4502.69 | -2417.88 | 13130.31 | 7198.50 | 4501.26 | -3307.96 | 269.91 | 951.38 | 200.44 | 750.93 | 4.78 | PASS |
| 13199.97 | 7534.56 | 4582.16 | -2418.02 | 13209.78 | 7198.50 | 4580.73 | -3308.08 | 269.91 | 951.39 | 203.13 | 748.27 | 4.71 | PASS |
| 13220.50† | 7534.58 | 4602.69 | -2418.13 | 13230.31 | 7198.50 | 4601.26 | -3308.12 | 269.91 | 951.33 | 203.82 | 747.51 | 4.70 | PASS |
| 13320.50† | 7534.68 | 4702.65 | -2420.77 | 13330.27 | 7198.50 | 4701.22 | -3308.28 | 269.91 | 949.05 | 207.19 | 741.86 | 4.61 | PASS |
| 13420.50† | 7534.79 | 4802.45 | -2426.90 | 13430.09 | 7198.50 | 4801.04 | -3308.44 | 269.91 | 943.51 | 210.58 | 732.93 | 4.51 | PASS |
| 13476.50 | 7534.85 | 4858.23 | -2431.85 | 13485.88 | 7198.50 | 4856.83 | -3308.53 | 269.91 | 938.99 | 212.47 | 726.52 | 4.45 | PASS |
| 13520.50† | 7534.89 | 4902.02 | -2436.16 | 13529.67 | 7198.50 | 4900.62 | -3308.60 | 269.91 | 935.04 | 213.94 | 721.10 | 4.40 | PASS |
| 13620.50† | 7534.99 | 5001.54 | -2445.98 | 13629.20 | 7198.50 | 5000.15 | -3308.76 | 269.91 | 926.07 | 217.31 | 708.77 | 4.29 | PASS |
| 13720.50† | 7535.10 | 5101.06 | -2455.79 | 13728.74 | 7198.50 | 5099.68 | -3308.92 | 269.91 | 917.12 | 220.68 | 696.44 | 4.18 | PASS |
| 13820.50† | 7535.20 | 5200.57 | -2465.61 | 13828.27 | 7198.50 | 5199.22 | -3309.08 | 269.91 | 908.19 | 224.05 | 684.14 | 4.08 | PASS |
| 13920.50† | 7535.30 | 5300.09 | -2475.42 | 13927.80 | 7198.50 | 5298.75 | -3309.24 | 269.91 | 899.27 | 227.42 | 671.85 | 3.98 | PASS |
| 14020.50† | 7535.40 | 5399.61 | -2485.24 | 14027.33 | 7198.50 | 5398.28 | -3309.40 | 269.91 | 890.36 | 230.78 | 659.58 | 3.88 | PASS |
| 14120.50† | 7535.51 | 5499.12 | -2495.05 | 14126.87 | 7198.50 | 5497.82 | -3309.56 | 269.91 | 881.47 | 234.14 | 647.33 | 3.78 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 30 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770°FSL & 819°FSL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-5-1L PWB Offset Wellpath: BUFORD 33-5-1L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#03 BUFORD 33-5-1L (770°FSL & 794°FWL,SEC.34) Well: BUFORD 33-5-1L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 14220.50† | 7535.61 | 5598.64 | -2504.87 | 14226.40 | 7198.50 | 5597.35 | -3309.72 | 269.91 | 872.60 | 237.49 | 635.11 | 3.69 | PASS |
| 14221.87 | 7535.61 | 5600.00 | -2505.00 | 14227.76 | 7198.50 | 5598.71 | -3309.72 | 269.91 | 872.48 | 237.53 | 634.94 | 3.69 | PASS |
| 14320.50† | 7535.71 | 5698.31 | -2512.99 | 14326.08 | 7198.50 | 5697.03 | -3309.88 | 269.91 | 865.30 | 240.84 | 624.46 | 3.61 | PASS |
| 14420.50† | 7535.81 | 5798.19 | -2517.63 | 14425.97 | 7198.50 | 5796.92 | -3310.04 | 269.91 | 861.22 | 244.24 | 616.97 | 3.54 | PASS |
| 14520.50† | 7535.92 | 5898.18 | -2518.78 | 14525.96 | 7198.50 | 5896.91 | -3310.20 | 269.91 | 860.34 | 247.69 | 612.65 | 3.49 | PASS |
| 14581.38 | 7535.98 | 5959.05 | -2517.77 | 14586.83 | 7198.50 | 5957.78 | -3310.30 | 269.91 | 861.39 | 249.80 | 611.58 | 3.46 | PASS |
| 14620.50† | 7536.02 | 5998.16 | -2516.71 | 14625.93 | 7198.50 | 5996.88 | -3310.36 | 269.91 | 862.44 | 251.16 | 611.28 | 3.45 | PASS |
| 14720.50† | 7536.12 | 6098.12 | -2513.99 | 14725.89 | 7198.50 | 6096.84 | -3310.52 | 269.91 | 865.13 | 254.64 | 610.49 | 3.41 | PASS |
| 14820.50† | 7536.23 | 6198.08 | -2511.27 | 14825.85 | 7198.50 | 6196.80 | -3310.68 | 269.91 | 867.82 | 258.14 | 609.68 | 3.38 | PASS |
| 14920.50† | 7536.33 | 6298.05 | -2508.55 | 14925.81 | 7198.50 | 6296.76 | -3310.84 | 269.91 | 870.52 | 261.65 | 608.86 | 3.34 | PASS |
| 15020.50† | 7536.43 | 6398.01 | -2505.83 | 15025.77 | 7198.50 | 6396.72 | -3311.00 | 269.91 | 873.21 | 265.17 | 608.04 | 3.31 | PASS |
| 15120.50† | 7536.54 | 6497.97 | -2503.11 | 15125.73 | 7198.50 | 6496.67 | -3311.16 | 269.91 | 875.91 | 268.69 | 607.22 | 3.27 | PASS |
| 15220.50† | 7536.64 | 6597.93 | -2500.40 | 15225.69 | 7198.50 | 6596.63 | -3311.32 | 269.91 | 878.60 | 272.22 | 606.38 | 3.24 | PASS |
| 15320.50† | 7536.74 | 6697.90 | -2497.68 | 15325.64 | 7198.50 | 6696.59 | -3311.48 | 269.91 | 881.30 | 275.75 | 605.55 | 3.21 | PASS |
| 15420.50† | 7536.85 | 6797.86 | -2494.96 | 15425.60 | 7198.50 | 6796.55 | -3311.64 | 269.91 | 884.00 | 279.30 | 604.70 | 3.18 | PASS |
| 15520.50† | 7536.95 | 6897.82 | -2492.24 | 15525.56 | 7198.50 | 6896.51 | -3311.80 | 269.91 | 886.70 | 282.85 | 603.85 | 3.15 | PASS |
| 15620.50† | 7537.05 | 6997.79 | -2489.52 | 15625.52 | 7198.50 | 6996.47 | -3311.96 | 269.91 | 889.40 | 286.40 | 603.00 | 3.12 | PASS |
| 15720.50† | 7537.16 | 7097.75 | -2486.80 | 15725.48 | 7198.50 | 7096.42 | -3312.12 | 269.91 | 892.10 | 289.96 | 602.14 | 3.09 | PASS |
| 15820.50† | 7537.26 | 7197.71 | -2484.08 | 15825.44 | 7198.50 | 7196.38 | -3312.28 | 269.91 | 894.81 | 293.53 | 601.28 | 3.06 | PASS |
| 15920.50† | 7537.36 | 7297.68 | -2481.36 | 15925.39 | 7198.50 | 7296.34 | -3312.45 | 269.91 | 897.51 | 297.10 | 600.41 | 3.03 | PASS |
| 16020.50† | 7537.47 | 7397.64 | -2478.64 | 16025.35 | 7198.50 | 7396.30 | -3312.61 | 269.91 | 900.22 | 300.68 | 599.54 | 3.01 | PASS |
| 16120.50† | 7537.57 | 7497.60 | -2475.93 | 16125.31 | 7198.50 | 7496.26 | -3312.77 | 269.91 | 902.93 | 304.26 | 598.66 | 2.98 | PASS |
| 16220.50† | 7537.68 | 7597.56 | -2473.21 | 16225.27 | 7198.50 | 7596.22 | -3312.93 | 269.91 | 905.63 | 307.85 | 597.78 | 2.95 | PASS |
| 16320.50† | 7537.78 | 7697.53 | -2470.49 | 16325.23 | 7198.50 | 7696.17 | -3313.09 | 269.91 | 908.34 | 311.45 | 596.90 | 2.93 | PASS |
| 16420.50† | 7537.88 | 7797.49 | -2467.77 | 16425.19 | 7198.50 | 7796.13 | -3313.25 | 269.91 | 911.05 | 315.04 | 596.01 | 2.90 | PASS |
| 16520.50† | 7537.99 | 7897.45 | -2465.05 | 16525.15 | 7198.50 | 7896.09 | -3313.41 | 269.91 | 913.76 | 318.65 | 595.12 | 2.88 | PASS |
| 16620.50† | 7538.09 | 7997.42 | -2462.33 | 16625.10 | 7198.50 | 7996.05 | -3313.57 | 269.91 | 916.48 | 322.26 | 594.22 | 2.85 | PASS |
| 16720.50† | 7538.19 | 8097.38 | -2459.61 | 16725.06 | 7198.50 | 8096.01 | -3313.73 | 269.91 | 919.19 | 325.87 | 593.32 | 2.83 | PASS |
| 16820.50† | 7538.30 | 8197.34 | -2456.89 | 16825.02 | 7198.50 | 8195.97 | -3313.89 | 269.91 | 921.90 | 329.49 | 592.42 | 2.81 | PASS |
| 16920.50† | 7538.40 | 8297.31 | -2454.17 | 16924.98 | 7198.50 | 8295.92 | -3314.05 | 269.91 | 924.62 | 333.11 | 591.51 | 2.78 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 31 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-5-1L PWB Offset Wellpath: BUFORD 33-5-1L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#03 BUFORD 33-5-1L (770'FSL & 794'FWL, SEC.34) Well: BUFORD 33-5-1L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 17020.50† | 7538.50 | 8397.27 | -2451.46 | 17024.94 | 7198.50 | 8395.88 | -3314.21 | 269.91 | 927.34 | 336.73 | 590.60 | 2.76 | PASS |
| 17120.50† | 7538.61 | 8497.23 | -2448.74 | 17124.90 | 7198.50 | 8495.84 | -3314.37 | 269.91 | 930.05 | 340.36 | 589.69 | 2.74 | PASS |
| 17220.50† | 7538.71 | 8597.19 | -2446.02 | 17224.85 | 7198.50 | 8595.80 | -3314.53 | 269.91 | 932.77 | 344.00 | 588.77 | 2.72 | PASS |
| 17320.50† | 7538.81 | 8697.16 | -2443.30 | 17324.81 | 7198.50 | 8695.76 | -3314.69 | 269.91 | 935.49 | 347.64 | 587.85 | 2.70 | PASS |
| 17420.50† | 7538.92 | 8797.12 | -2440.58 | 17424.77 | 7198.50 | 8795.72 | -3314.85 | 269.91 | 938.21 | 351.28 | 586.93 | 2.68 | PASS |
| 17520.50† | 7539.02 | 8897.08 | -2437.86 | 17524.73 | 7198.50 | 8895.67 | -3315.01 | 269.91 | 940.93 | 354.92 | 586.01 | 2.66 | PASS |
| 17620.50† | 7539.12 | 8997.05 | -2435.14 | 17624.69 | 7198.50 | 8995.63 | -3315.18 | 269.91 | 943.65 | 358.57 | 585.09 | 2.64 | PASS |
| 17720.50† | 7539.23 | 9097.01 | -2432.42 | 17724.65 | 7198.50 | 9095.59 | -3315.34 | 269.91 | 946.38 | 362.23 | 584.15 | 2.62 | PASS |
| 17820.50† | 7539.33 | 9196.97 | -2429.70 | 17824.61 | 7198.50 | 9195.55 | -3315.50 | 269.91 | 949.10 | 365.88 | 583.22 | 2.60 | PASS |
| 17920.50† | 7539.43 | 9296.94 | -2426.99 | 17924.56 | 7198.50 | 9295.51 | -3315.66 | 269.91 | 951.83 | 369.54 | 582.28 | 2.58 | PASS |
| 17985.90 | 7539.50 | 9362.31 | -2425.21 | 17987.82 | 7198.50 | 9358.77 | -3315.76 | 269.77 | 953.61 | 374.44 | 579.17 | 2.56 | PASS |

POSITIONAL UNCERTAINTY - Offset Wellbore: BUFORD 33-5-1L PWB Offset Wellpath: BUFORD 33-5-1L (REV-A.0) PWP

| | | | | |
|-----------------------------------|------------|---------|----------|---------|
| Slot Surface Uncertainty @1SD | Horizontal | 0.100ft | Vertical | 1.000ft |
| Facility Surface Uncertainty @1SD | Horizontal | 8.200ft | Vertical | 3.000ft |

HOLE & CASING SECTIONS - Offset Wellbore: BUFORD 33-5-1L PWB Offset Wellpath: BUFORD 33-5-1L (REV-A.0) PWP

| String/Diameter | Start MD [ft] | End MD [ft] | Interval [ft] | Start TVD [ft] | End TVD [ft] | Start N/S [ft] | Start E/W [ft] | End N/S [ft] | End E/W [ft] |
|------------------------|---------------|-------------|---------------|----------------|--------------|----------------|----------------|--------------|--------------|
| 13.5in Open Hole | 20.50 | 1500.00 | 1479.50 | 21.50 | 1480.82 | 0.00 | -25.21 | -43.04 | -192.54 |
| 9.625in Casing Surface | 20.50 | 1500.00 | 1479.50 | 21.50 | 1480.82 | 0.00 | -25.21 | -43.04 | -192.54 |
| 8.5in Open Hole | 1500.00 | 17987.82 | 16487.82 | 1480.82 | 7198.50 | -43.04 | -192.54 | 9358.76 | -3315.76 |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 32 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

SURVEY PROGRAM - Offset Wellbore: BUFORD 33-5-1L PWB Offset Wellpath: BUFORD 33-5-1L (REV-A.0) PWP

| Start MD [ft] | End MD [ft] | Positional Uncertainty Model | Log Name/Comment | Wellbore |
|------------------|----------------|---|------------------|--------------------|
| 20.50 | 1500.00 | BH NaviTrak (2019) (Standard) | | BUFORD 33-5-1L PWB |
| 1500.00 | 17994.42 | BH AutoTrak Curve/eXpress (2019) (Standard) | | BUFORD 33-5-1L PWB |

OFFSET WELLPATH REFERENCE - Offset Wellbore: BUFORD 33-5-1L PWB Offset Wellpath: BUFORD 33-5-1L (REV-A.0) PWP

| | |
|---------------------------------|---|
| MD Reference: RIG (20.5') (RKB) | Offset TVD & local coordinates use Reference Wellpath settings (See WELLPATH DATUM on page 1 of this report) |
| Ellipse Start MD | 20.50ft |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 33 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770°FSL & 819°FSL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-4-2L PWB Offset Wellpath: BUFORD 33-4-2L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W | | Slot: SLOT#05 BUFORD 33-4-2L (770°FSL & 844°FSL, SEC.34) | | Well: BUFORD 33-4-2L | | Threshold Value=1.00 | | † = interpolated, ‡ = extrapolated station | | | | | | | | | |
|----------------------------|--------------|--|---------------|----------------------|-----------------|----------------------|------------------|--|---------------------|----------------|----------------------|-----------|-------------|--|--|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | | | |
| 20.50 | 20.50 | 0.00 | 0.00 | 20.50 | 20.50 | 0.00 | 25.21 | 90.00 | 25.21 | 9.75 | 15.47 | 3.68 | PASS | | | | |
| 120.50† | 120.50 | 0.00 | 0.00 | 120.50 | 120.50 | 0.00 | 25.21 | 90.00 | 25.21 | 9.81 | 15.40 | 3.64 | PASS | | | | |
| 200.00 | 200.00 | 0.00 | 0.00 | 200.00 | 200.00 | 0.00 | 25.21 | 90.00 | 25.21 | 9.96 | 15.25 | 3.55 | PASS | | | | |
| 220.50† | 220.50 | -0.03 | -0.07 | 220.50 | 220.50 | 0.00 | 25.21 | 89.94 | 25.28 | 10.01 | 15.27 | 3.53 | PASS | | | | |
| 320.50† | 320.46 | -0.93 | -2.36 | 320.46 | 320.46 | 0.00 | 25.21 | 88.06 | 27.59 | 10.41 | 17.18 | 3.67 | PASS | | | | |
| 420.50† | 420.28 | -3.13 | -7.88 | 420.28 | 420.28 | 0.00 | 25.21 | 84.60 | 33.25 | 11.11 | 22.14 | 4.11 | PASS | | | | |
| 520.50† | 519.83 | -6.60 | -16.65 | 520.13 | 520.13 | -0.02 | 25.15 | 81.05 | 42.31 | 11.86 | 30.45 | 4.87 | PASS | | | | |
| 620.50† | 618.99 | -11.36 | -28.64 | 621.24 | 621.20 | -0.76 | 22.76 | 78.35 | 52.53 | 12.71 | 39.81 | 5.56 | PASS | | | | |
| 720.50† | 717.64 | -17.38 | -43.83 | 722.73 | 722.51 | -2.56 | 16.95 | 76.30 | 62.75 | 13.74 | 49.02 | 6.03 | PASS | | | | |
| 820.50† | 815.66 | -24.68 | -62.22 | 824.60 | 823.90 | -5.44 | 7.67 | 74.61 | 72.96 | 14.75 | 58.21 | 6.41 | PASS | | | | |
| 920.50† | 912.93 | -33.22 | -83.78 | 926.85 | 925.27 | -9.40 | -5.10 | 73.15 | 83.13 | 15.74 | 67.38 | 6.73 | PASS | | | | |
| 1020.50† | 1009.33 | -43.02 | -108.48 | 1029.47 | 1026.46 | -14.45 | -21.39 | 71.84 | 93.25 | 16.73 | 76.52 | 7.00 | PASS | | | | |
| 1120.50† | 1104.74 | -54.05 | -136.29 | 1132.48 | 1127.35 | -20.59 | -41.20 | 70.62 | 103.31 | 17.71 | 85.60 | 7.24 | PASS | | | | |
| 1220.50† | 1199.05 | -66.30 | -167.18 | 1235.86 | 1227.79 | -27.84 | -64.56 | 69.46 | 113.30 | 18.68 | 94.62 | 7.44 | PASS | | | | |
| 1242.54 | 1219.68 | -69.16 | -174.40 | 1258.69 | 1249.85 | -29.58 | -70.18 | 69.20 | 115.49 | 18.88 | 96.61 | 7.48 | PASS | | | | |
| 1320.50† | 1292.54 | -79.39 | -200.20 | 1339.70 | 1327.73 | -36.19 | -91.49 | 68.33 | 122.16 | 19.54 | 102.62 | 7.60 | PASS | | | | |
| 1420.50† | 1385.99 | -92.51 | -233.28 | 1444.07 | 1427.08 | -45.65 | -122.02 | 67.16 | 127.52 | 20.34 | 107.18 | 7.55 | PASS | | | | |
| 1520.50† | 1479.44 | -105.63 | -266.37 | 1548.69 | 1525.43 | -56.21 | -156.08 | 65.86 | 129.31 | 20.76 | 108.55 | 7.47 | PASS | | | | |
| 1620.50† | 1572.89 | -118.75 | -299.46 | 1653.29 | 1622.39 | -67.83 | -193.54 | 64.32 | 127.53 | 20.88 | 106.65 | 7.31 | PASS | | | | |
| 1720.50† | 1666.34 | -131.87 | -332.54 | 1756.46 | 1716.61 | -80.27 | -233.67 | 62.44 | 122.34 | 21.07 | 101.27 | 6.93 | PASS | | | | |
| 1820.50† | 1759.79 | -144.99 | -365.63 | 1856.20 | 1807.29 | -92.58 | -273.35 | 60.40 | 116.27 | 21.34 | 94.93 | 6.47 | PASS | | | | |
| 1920.50† | 1853.24 | -158.12 | -398.72 | 1955.94 | 1897.96 | -104.88 | -313.04 | 58.15 | 110.34 | 21.72 | 88.62 | 6.00 | PASS | | | | |
| 2020.50† | 1946.69 | -171.24 | -431.80 | 2055.68 | 1988.64 | -117.19 | -352.72 | 55.65 | 104.57 | 22.22 | 82.35 | 5.51 | PASS | | | | |
| 2120.50† | 2040.14 | -184.36 | -464.89 | 2155.42 | 2079.31 | -129.49 | -392.40 | 52.88 | 98.99 | 22.88 | 76.11 | 5.03 | PASS | | | | |
| 2220.50† | 2133.59 | -197.48 | -497.98 | 2255.16 | 2169.99 | -141.80 | -432.08 | 49.80 | 93.63 | 23.71 | 69.92 | 4.54 | PASS | | | | |
| 2320.50† | 2227.05 | -210.60 | -531.06 | 2354.90 | 2260.66 | -154.10 | -471.77 | 46.38 | 88.53 | 24.76 | 63.77 | 4.07 | PASS | | | | |
| 2420.50† | 2320.50 | -223.72 | -564.15 | 2454.64 | 2351.34 | -166.40 | -511.45 | 42.60 | 83.75 | 26.07 | 57.68 | 3.61 | PASS | | | | |
| 2520.50† | 2413.95 | -236.84 | -597.24 | 2554.38 | 2442.01 | -178.71 | -551.13 | 38.42 | 79.32 | 27.67 | 51.66 | 3.18 | PASS | | | | |
| 2620.50† | 2507.40 | -249.96 | -630.32 | 2654.12 | 2532.69 | -191.01 | -590.82 | 33.83 | 75.33 | 29.59 | 45.75 | 2.79 | PASS | | | | |
| 2720.50† | 2600.85 | -263.08 | -663.41 | 2753.86 | 2623.36 | -203.32 | -630.50 | 28.84 | 71.84 | 31.85 | 40.00 | 2.44 | PASS | | | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 34 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-4-2L PWB Offset Wellpath: BUFORD 33-4-2L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#05 BUFORD 33-4-2L (770'FSL & 844'FWL, SEC.34) Well: BUFORD 33-4-2L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | |
| 2820.50† | 2694.30 | -276.20 | -696.50 | 2853.60 | 2714.04 | -215.62 | -670.18 | 23.48 | 68.93 | 34.43 | 34.50 | 2.13 | PASS | | |
| 2920.50† | 2787.75 | -289.33 | -729.58 | 2953.34 | 2804.71 | -227.93 | -709.87 | 17.80 | 66.68 | 37.28 | 29.40 | 1.88 | PASS | | |
| 3020.50† | 2881.20 | -302.45 | -762.67 | 3053.08 | 2895.39 | -240.23 | -749.55 | 11.91 | 65.14 | 40.31 | 24.84 | 1.68 | PASS | | |
| 3120.50† | 2974.65 | -315.57 | -795.76 | 3152.82 | 2986.06 | -252.54 | -789.23 | 5.91 | 64.39 | 43.38 | 21.00 | 1.53 | PASS | | |
| 3220.50† | 3068.11 | -328.69 | -828.84 | 3252.57 | 3076.74 | -264.84 | -828.92 | 359.94 | 64.43 | 46.38 | 18.05 | 1.43 | PASS | | |
| 3320.50† | 3161.56 | -341.81 | -861.93 | 3352.31 | 3167.41 | -277.15 | -868.60 | 354.11 | 65.27 | 49.18 | 16.09 | 1.36 | PASS | | |
| 3420.50† | 3255.01 | -354.93 | -895.02 | 3452.05 | 3258.09 | -289.45 | -908.28 | 348.55 | 66.88 | 51.70 | 15.18 | 1.32 | PASS | | |
| 3520.50† | 3348.46 | -368.05 | -928.10 | 3551.79 | 3348.76 | -301.76 | -947.97 | 343.32 | 69.21 | 53.91 | 15.30 | 1.31 | PASS | | |
| 3620.50† | 3441.91 | -381.17 | -961.19 | 3651.53 | 3439.44 | -314.06 | -987.65 | 338.48 | 72.18 | 55.80 | 16.38 | 1.32 | PASS | | |
| 3720.50† | 3535.36 | -394.29 | -994.28 | 3751.27 | 3530.11 | -326.37 | -1027.33 | 334.05 | 75.72 | 57.43 | 18.29 | 1.34 | PASS | | |
| 3820.50† | 3628.81 | -407.41 | -1027.37 | 3851.01 | 3620.79 | -338.67 | -1067.02 | 330.02 | 79.76 | 58.84 | 20.93 | 1.38 | PASS | | |
| 3920.50† | 3722.26 | -420.53 | -1060.45 | 3950.75 | 3711.46 | -350.97 | -1106.70 | 326.38 | 84.23 | 60.07 | 24.16 | 1.43 | PASS | | |
| 4020.50† | 3815.71 | -433.66 | -1093.54 | 4050.49 | 3802.14 | -363.28 | -1146.38 | 323.10 | 89.05 | 61.17 | 27.88 | 1.49 | PASS | | |
| 4120.50† | 3909.17 | -446.78 | -1126.63 | 4150.23 | 3892.81 | -375.58 | -1186.07 | 320.14 | 94.17 | 62.18 | 31.99 | 1.55 | PASS | | |
| 4220.50† | 4002.62 | -459.90 | -1159.71 | 4249.97 | 3983.49 | -387.89 | -1225.75 | 317.48 | 99.56 | 63.13 | 36.43 | 1.62 | PASS | | |
| 4320.50† | 4096.07 | -473.02 | -1192.80 | 4349.71 | 4074.16 | -400.19 | -1265.43 | 315.08 | 105.16 | 64.05 | 41.11 | 1.68 | PASS | | |
| 4420.50† | 4189.52 | -486.14 | -1225.89 | 4449.45 | 4164.84 | -412.50 | -1305.12 | 312.91 | 110.95 | 64.95 | 46.00 | 1.75 | PASS | | |
| 4520.50† | 4282.97 | -499.26 | -1258.97 | 4549.19 | 4255.51 | -424.80 | -1344.80 | 310.94 | 116.89 | 65.84 | 51.06 | 1.83 | PASS | | |
| 4620.50† | 4376.42 | -512.38 | -1292.06 | 4648.93 | 4346.19 | -437.11 | -1384.48 | 309.16 | 122.97 | 66.72 | 56.25 | 1.90 | PASS | | |
| 4720.50† | 4469.87 | -525.50 | -1325.15 | 4748.67 | 4436.86 | -449.41 | -1424.17 | 307.54 | 129.17 | 67.62 | 61.55 | 1.97 | PASS | | |
| 4820.50† | 4563.32 | -538.62 | -1358.23 | 4848.41 | 4527.54 | -461.72 | -1463.85 | 306.06 | 135.46 | 68.53 | 66.93 | 2.04 | PASS | | |
| 4920.50† | 4656.77 | -551.74 | -1391.32 | 4948.15 | 4618.21 | -474.02 | -1503.53 | 304.71 | 141.84 | 69.45 | 72.39 | 2.11 | PASS | | |
| 5020.50† | 4750.22 | -564.87 | -1424.41 | 5047.89 | 4708.89 | -486.33 | -1543.21 | 303.47 | 148.30 | 70.38 | 77.92 | 2.17 | PASS | | |
| 5120.50† | 4843.68 | -577.99 | -1457.49 | 5147.63 | 4799.56 | -498.63 | -1582.90 | 302.33 | 154.82 | 71.33 | 83.49 | 2.24 | PASS | | |
| 5220.50† | 4937.13 | -591.11 | -1490.58 | 5247.37 | 4890.24 | -510.94 | -1622.58 | 301.27 | 161.40 | 72.29 | 89.11 | 2.30 | PASS | | |
| 5320.50† | 5030.58 | -604.23 | -1523.67 | 5347.11 | 4980.91 | -523.24 | -1662.26 | 300.30 | 168.03 | 73.27 | 94.76 | 2.37 | PASS | | |
| 5420.50† | 5124.03 | -617.35 | -1556.75 | 5446.85 | 5071.59 | -535.54 | -1701.95 | 299.40 | 174.71 | 74.27 | 100.44 | 2.43 | PASS | | |
| 5520.50† | 5217.48 | -630.47 | -1589.84 | 5546.59 | 5162.26 | -547.85 | -1741.63 | 298.56 | 181.43 | 75.27 | 106.15 | 2.49 | PASS | | |
| 5620.50† | 5310.93 | -643.59 | -1622.93 | 5646.33 | 5252.94 | -560.15 | -1781.31 | 297.78 | 188.18 | 76.30 | 111.88 | 2.55 | PASS | | |
| 5720.50† | 5404.38 | -656.71 | -1656.01 | 5746.07 | 5343.61 | -572.46 | -1821.00 | 297.05 | 194.96 | 77.33 | 117.64 | 2.60 | PASS | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 35 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-4-2L PWB Offset Wellpath: BUFORD 33-4-2L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#05 BUFORD 33-4-2L (770'FSL & 844'FWL,SEC.34) Well: BUFORD 33-4-2L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 5820.50† | 5497.83 | -669.83 | -1689.10 | 5845.81 | 5434.29 | -584.76 | -1860.68 | 296.37 | 201.78 | 78.38 | 123.40 | 2.66 | PASS |
| 5920.50† | 5591.28 | -682.95 | -1722.19 | 5945.55 | 5524.96 | -597.07 | -1900.36 | 295.74 | 208.62 | 79.43 | 129.19 | 2.71 | PASS |
| 6020.50† | 5684.74 | -696.07 | -1755.27 | 6045.29 | 5615.64 | -609.37 | -1940.05 | 295.14 | 215.48 | 80.50 | 134.98 | 2.76 | PASS |
| 6120.50† | 5778.19 | -709.20 | -1788.36 | 6145.03 | 5706.31 | -621.68 | -1979.73 | 294.58 | 222.37 | 81.58 | 140.79 | 2.81 | PASS |
| 6220.50† | 5871.64 | -722.32 | -1821.45 | 6244.77 | 5796.99 | -633.98 | -2019.41 | 294.05 | 229.27 | 82.67 | 146.60 | 2.86 | PASS |
| 6320.50† | 5965.09 | -735.44 | -1854.54 | 6344.51 | 5887.66 | -646.29 | -2059.10 | 293.55 | 236.20 | 83.77 | 152.43 | 2.91 | PASS |
| 6420.50† | 6058.54 | -748.56 | -1887.62 | 6444.25 | 5978.34 | -658.59 | -2098.78 | 293.08 | 243.13 | 84.87 | 158.26 | 2.96 | PASS |
| 6520.50† | 6151.99 | -761.68 | -1920.71 | 6543.99 | 6069.01 | -670.90 | -2138.46 | 292.63 | 250.09 | 85.99 | 164.10 | 3.00 | PASS |
| 6620.50† | 6245.44 | -774.80 | -1953.80 | 6643.73 | 6159.69 | -683.20 | -2178.15 | 292.21 | 257.06 | 87.11 | 169.95 | 3.04 | PASS |
| 6720.50† | 6338.89 | -787.92 | -1986.88 | 6743.47 | 6250.36 | -695.51 | -2217.83 | 291.81 | 264.04 | 88.24 | 175.80 | 3.09 | PASS |
| 6820.50† | 6432.34 | -801.04 | -2019.97 | 6843.21 | 6341.04 | -707.81 | -2257.51 | 291.43 | 271.03 | 89.37 | 181.65 | 3.13 | PASS |
| 6920.50† | 6525.80 | -814.16 | -2053.06 | 6942.95 | 6431.71 | -720.11 | -2297.20 | 291.07 | 278.03 | 90.52 | 187.51 | 3.17 | PASS |
| 7020.50† | 6619.25 | -827.28 | -2086.14 | 7042.69 | 6522.39 | -732.42 | -2336.88 | 290.72 | 285.04 | 91.67 | 193.38 | 3.21 | PASS |
| 7120.50† | 6712.70 | -840.41 | -2119.23 | 7142.43 | 6613.06 | -744.72 | -2376.56 | 290.40 | 292.07 | 92.82 | 199.25 | 3.24 | PASS |
| 7220.50† | 6806.15 | -853.53 | -2152.32 | 7242.17 | 6703.74 | -757.03 | -2416.25 | 290.08 | 299.10 | 93.98 | 205.12 | 3.28 | PASS |
| 7320.50† | 6899.60 | -866.65 | -2185.40 | 7341.91 | 6794.41 | -769.33 | -2455.93 | 289.79 | 306.14 | 95.14 | 210.99 | 3.31 | PASS |
| 7341.07 | 6918.82 | -869.35 | -2192.21 | 7362.43 | 6813.06 | -771.86 | -2464.09 | 289.73 | 307.58 | 95.38 | 212.20 | 3.32 | PASS |
| 7420.50† | 6993.49 | -874.29 | -2218.65 | 7433.50 | 6877.82 | -778.98 | -2492.43 | 289.19 | 312.12 | 95.37 | 216.76 | 3.37 | PASS |
| 7520.50† | 7087.21 | -884.88 | -2251.87 | 7516.82 | 6953.96 | -775.07 | -2525.78 | 288.15 | 317.57 | 94.19 | 223.38 | 3.48 | PASS |
| 7620.50† | 7177.96 | -898.35 | -2284.05 | 7600.85 | 7028.94 | -756.57 | -2558.64 | 286.59 | 322.95 | 92.26 | 230.69 | 3.61 | PASS |
| 7720.50† | 7262.97 | -915.51 | -2314.23 | 7685.61 | 7100.36 | -723.68 | -2589.97 | 284.60 | 328.08 | 90.15 | 237.92 | 3.76 | PASS |
| 7820.50† | 7339.68 | -937.65 | -2341.49 | 7771.08 | 7165.85 | -677.10 | -2618.72 | 282.32 | 332.78 | 88.06 | 244.72 | 3.91 | PASS |
| 7920.50† | 7405.75 | -966.53 | -2364.99 | 7857.21 | 7223.09 | -618.03 | -2643.88 | 279.87 | 336.89 | 86.14 | 250.75 | 4.05 | PASS |
| 8020.50† | 7459.16 | -984.32 | -2384.03 | 7943.93 | 7269.96 | -548.20 | -2664.52 | 277.34 | 340.26 | 84.59 | 255.66 | 4.17 | PASS |
| 8120.50† | 7498.30 | -993.50 | -2398.02 | 8031.11 | 7304.66 | -469.83 | -2679.84 | 274.80 | 342.75 | 83.56 | 259.19 | 4.26 | PASS |
| 8220.50† | 7521.99 | -996.85 | -2406.55 | 8118.63 | 7325.79 | -385.55 | -2689.22 | 272.29 | 344.28 | 83.14 | 261.13 | 4.30 | PASS |
| 8315.56 | 7529.50 | -1002.24 | -2409.34 | 8201.97 | 7332.50 | -302.64 | -2692.30 | 269.92 | 344.78 | 83.27 | 261.51 | 4.30 | PASS |
| 8320.50† | 7529.51 | -297.30 | -2409.35 | 8206.85 | 7332.50 | -297.76 | -2692.31 | 269.91 | 344.78 | 83.29 | 261.49 | 4.30 | PASS |
| 8420.50† | 7529.61 | -197.30 | -2409.53 | 8306.85 | 7332.50 | -197.76 | -2692.47 | 269.91 | 344.83 | 83.74 | 261.09 | 4.27 | PASS |
| 8520.50† | 7529.71 | -97.30 | -2409.71 | 8406.85 | 7332.50 | -97.76 | -2692.63 | 269.91 | 344.88 | 84.37 | 260.51 | 4.24 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 36 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-4-2L PWB Offset Wellpath: BUFORD 33-4-2L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#05 BUFORD 33-4-2L (770'FSL & 844'FWL,SEC.34) Well: BUFORD 33-4-2L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|-----------------|-------------------|------------------|-------------------|--------------------|----------------------|---------------------|-------------------------|---------------------------|----------------------|----------------------------|--------------|----------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 8620.50† | 7529.82 | 2.70 | -2409.88 | 8506.85 | 7332.50 | 2.24 | -2692.80 | 269.91 | 344.92 | 85.15 | 259.78 | 4.20 | PASS |
| 8720.50† | 7529.92 | 102.70 | -2410.06 | 8606.85 | 7332.50 | 102.24 | -2692.96 | 269.91 | 344.97 | 86.05 | 258.92 | 4.15 | PASS |
| 8820.50† | 7530.02 | 202.70 | -2410.24 | 8706.85 | 7332.50 | 202.23 | -2693.12 | 269.91 | 345.02 | 87.09 | 257.93 | 4.10 | PASS |
| 8920.50† | 7530.13 | 302.70 | -2410.42 | 8806.85 | 7332.50 | 302.23 | -2693.29 | 269.91 | 345.07 | 88.25 | 256.82 | 4.05 | PASS |
| 9020.50† | 7530.23 | 402.70 | -2410.59 | 8906.85 | 7332.50 | 402.23 | -2693.45 | 269.91 | 345.11 | 89.53 | 255.58 | 3.99 | PASS |
| 9120.50† | 7530.33 | 502.70 | -2410.77 | 9006.85 | 7332.50 | 502.23 | -2693.61 | 269.91 | 345.16 | 90.92 | 254.24 | 3.92 | PASS |
| 9220.50† | 7530.44 | 602.70 | -2410.95 | 9106.85 | 7332.50 | 602.23 | -2693.78 | 269.91 | 345.21 | 92.42 | 252.79 | 3.86 | PASS |
| 9320.50† | 7530.54 | 702.70 | -2411.13 | 9206.85 | 7332.50 | 702.23 | -2693.94 | 269.91 | 345.26 | 94.02 | 251.23 | 3.79 | PASS |
| 9420.50† | 7530.64 | 802.69 | -2411.31 | 9306.85 | 7332.50 | 802.23 | -2694.10 | 269.91 | 345.30 | 95.72 | 249.58 | 3.72 | PASS |
| 9520.50† | 7530.75 | 902.69 | -2411.48 | 9406.85 | 7332.50 | 902.23 | -2694.26 | 269.91 | 345.35 | 97.52 | 247.84 | 3.65 | PASS |
| 9620.50† | 7530.85 | 1002.69 | -2411.66 | 9506.85 | 7332.50 | 1002.23 | -2694.43 | 269.91 | 345.40 | 99.39 | 246.01 | 3.58 | PASS |
| 9720.50† | 7530.96 | 1102.69 | -2411.84 | 9606.85 | 7332.50 | 1102.23 | -2694.59 | 269.91 | 345.45 | 101.35 | 244.10 | 3.51 | PASS |
| 9820.50† | 7531.06 | 1202.69 | -2412.02 | 9706.85 | 7332.50 | 1202.23 | -2694.75 | 269.91 | 345.49 | 103.39 | 242.11 | 3.44 | PASS |
| 9920.50† | 7531.16 | 1302.69 | -2412.19 | 9806.85 | 7332.50 | 1302.23 | -2694.92 | 269.91 | 345.54 | 105.49 | 240.05 | 3.36 | PASS |
| 10020.50† | 7531.27 | 1402.69 | -2412.37 | 9906.85 | 7332.50 | 1402.23 | -2695.08 | 269.91 | 345.59 | 107.67 | 237.92 | 3.29 | PASS |
| 10120.50† | 7531.37 | 1502.69 | -2412.55 | 10006.85 | 7332.50 | 1502.23 | -2695.24 | 269.91 | 345.64 | 109.90 | 235.74 | 3.23 | PASS |
| 10220.50† | 7531.47 | 1602.69 | -2412.73 | 10106.85 | 7332.50 | 1602.23 | -2695.41 | 269.91 | 345.69 | 112.20 | 233.49 | 3.16 | PASS |
| 10320.50† | 7531.58 | 1702.69 | -2412.90 | 10206.85 | 7332.50 | 1702.23 | -2695.57 | 269.91 | 345.73 | 114.55 | 231.19 | 3.09 | PASS |
| 10420.50† | 7531.68 | 1802.69 | -2413.08 | 10306.85 | 7332.50 | 1802.23 | -2695.73 | 269.91 | 345.78 | 116.95 | 228.83 | 3.03 | PASS |
| 10520.50† | 7531.78 | 1902.69 | -2413.26 | 10406.85 | 7332.50 | 1902.23 | -2695.90 | 269.91 | 345.83 | 119.40 | 226.43 | 2.96 | PASS |
| 10620.50† | 7531.89 | 2002.69 | -2413.44 | 10506.85 | 7332.50 | 2002.23 | -2696.06 | 269.91 | 345.88 | 121.90 | 223.98 | 2.90 | PASS |
| 10720.50† | 7531.99 | 2102.69 | -2413.62 | 10606.85 | 7332.50 | 2102.23 | -2696.22 | 269.91 | 345.92 | 124.44 | 221.49 | 2.84 | PASS |
| 10820.50† | 7532.09 | 2202.69 | -2413.79 | 10706.85 | 7332.50 | 2202.23 | -2696.38 | 269.91 | 345.97 | 127.01 | 218.96 | 2.78 | PASS |
| 10920.50† | 7532.20 | 2302.69 | -2413.97 | 10806.85 | 7332.50 | 2302.23 | -2696.55 | 269.91 | 346.02 | 129.63 | 216.39 | 2.72 | PASS |
| 11020.50† | 7532.30 | 2402.69 | -2414.15 | 10906.85 | 7332.50 | 2402.23 | -2696.71 | 269.91 | 346.07 | 132.28 | 213.79 | 2.67 | PASS |
| 11120.50† | 7532.41 | 2502.69 | -2414.33 | 11006.85 | 7332.50 | 2502.23 | -2696.87 | 269.91 | 346.12 | 134.96 | 211.15 | 2.61 | PASS |
| 11220.50† | 7532.51 | 2602.69 | -2414.50 | 11106.85 | 7332.50 | 2602.23 | -2697.04 | 269.91 | 346.16 | 137.68 | 208.49 | 2.56 | PASS |
| 11320.50† | 7532.61 | 2702.69 | -2414.68 | 11206.85 | 7332.50 | 2702.23 | -2697.20 | 269.91 | 346.21 | 140.42 | 205.79 | 2.51 | PASS |
| 11420.50† | 7532.72 | 2802.69 | -2414.86 | 11306.85 | 7332.50 | 2802.23 | -2697.36 | 269.91 | 346.26 | 143.19 | 203.07 | 2.46 | PASS |
| 11520.50† | 7532.82 | 2902.69 | -2415.04 | 11406.85 | 7332.50 | 2902.23 | -2697.53 | 269.91 | 346.31 | 145.98 | 200.32 | 2.41 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 37 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-4-2L PWB Offset Wellpath: BUFORD 33-4-2L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#05 BUFORD 33-4-2L (770'FSL & 844'FWL, SEC.34) Well: BUFORD 33-4-2L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 11620.50† | 7532.92 | 3002.69 | -2415.21 | 11506.85 | 7332.50 | 3002.23 | -2697.69 | 269.91 | 346.36 | 148.80 | 197.55 | 2.36 | PASS |
| 11720.50† | 7533.03 | 3102.69 | -2415.39 | 11606.85 | 7332.50 | 3102.23 | -2697.85 | 269.91 | 346.40 | 151.64 | 194.76 | 2.32 | PASS |
| 11820.50† | 7533.13 | 3202.69 | -2415.57 | 11706.85 | 7332.50 | 3202.23 | -2698.02 | 269.91 | 346.45 | 154.50 | 191.95 | 2.28 | PASS |
| 11920.50† | 7533.23 | 3302.69 | -2415.75 | 11806.85 | 7332.50 | 3302.23 | -2698.18 | 269.91 | 346.50 | 157.39 | 189.11 | 2.23 | PASS |
| 12020.50† | 7533.34 | 3402.69 | -2415.92 | 11906.85 | 7332.50 | 3402.23 | -2698.34 | 269.91 | 346.55 | 160.29 | 186.26 | 2.19 | PASS |
| 12120.50† | 7533.44 | 3502.69 | -2416.10 | 12006.84 | 7332.50 | 3502.23 | -2698.50 | 269.91 | 346.60 | 163.20 | 183.39 | 2.15 | PASS |
| 12220.50† | 7533.55 | 3602.69 | -2416.28 | 12106.84 | 7332.50 | 3602.23 | -2698.67 | 269.91 | 346.64 | 166.14 | 180.50 | 2.11 | PASS |
| 12320.50† | 7533.65 | 3702.69 | -2416.46 | 12206.84 | 7332.50 | 3702.23 | -2698.83 | 269.91 | 346.69 | 169.09 | 177.60 | 2.08 | PASS |
| 12420.50† | 7533.75 | 3802.69 | -2416.64 | 12306.84 | 7332.50 | 3802.23 | -2698.99 | 269.91 | 346.74 | 172.06 | 174.69 | 2.04 | PASS |
| 12520.50† | 7533.86 | 3902.69 | -2416.81 | 12406.84 | 7332.50 | 3902.23 | -2699.16 | 269.91 | 346.79 | 175.03 | 171.75 | 2.00 | PASS |
| 12620.50† | 7533.96 | 4002.69 | -2416.99 | 12506.84 | 7332.50 | 4002.23 | -2699.32 | 269.91 | 346.84 | 178.03 | 168.81 | 1.97 | PASS |
| 12720.50† | 7534.06 | 4102.69 | -2417.17 | 12606.84 | 7332.50 | 4102.23 | -2699.48 | 269.91 | 346.89 | 181.03 | 165.85 | 1.94 | PASS |
| 12820.50† | 7534.17 | 4202.69 | -2417.35 | 12706.84 | 7332.50 | 4202.23 | -2699.65 | 269.91 | 346.93 | 184.05 | 162.89 | 1.90 | PASS |
| 12920.50† | 7534.27 | 4302.69 | -2417.52 | 12806.84 | 7332.50 | 4302.23 | -2699.81 | 269.91 | 346.98 | 187.08 | 159.91 | 1.87 | PASS |
| 13020.50† | 7534.37 | 4402.69 | -2417.70 | 12906.84 | 7332.50 | 4402.23 | -2699.97 | 269.91 | 347.03 | 190.11 | 156.92 | 1.84 | PASS |
| 13120.50† | 7534.48 | 4502.69 | -2417.88 | 13006.84 | 7332.50 | 4502.23 | -2700.14 | 269.91 | 347.08 | 193.16 | 153.92 | 1.81 | PASS |
| 13199.97 | 7534.56 | 4582.16 | -2418.02 | 13086.32 | 7332.50 | 4581.70 | -2700.27 | 269.91 | 347.12 | 195.59 | 151.53 | 1.79 | PASS |
| 13220.50† | 7534.58 | 4602.69 | -2418.13 | 13106.84 | 7332.50 | 4602.23 | -2700.30 | 269.91 | 347.07 | 196.21 | 150.86 | 1.78 | PASS |
| 13320.50† | 7534.68 | 4702.65 | -2420.77 | 13206.81 | 7332.50 | 4702.19 | -2700.46 | 269.91 | 345.12 | 199.08 | 146.04 | 1.75 | PASS |
| 13420.50† | 7534.79 | 4802.45 | -2426.90 | 13306.63 | 7332.50 | 4802.01 | -2700.62 | 269.91 | 340.37 | 201.65 | 138.71 | 1.70 | PASS |
| 13476.50 | 7534.85 | 4858.23 | -2431.85 | 13362.41 | 7332.50 | 4857.80 | -2700.72 | 269.91 | 336.50 | 202.94 | 133.57 | 1.67 | PASS |
| 13520.50† | 7534.89 | 4902.02 | -2436.16 | 13406.21 | 7332.50 | 4901.59 | -2700.79 | 269.91 | 333.15 | 203.87 | 129.27 | 1.65 | PASS |
| 13620.50† | 7534.99 | 5001.54 | -2445.98 | 13505.74 | 7332.50 | 5001.12 | -2700.95 | 269.91 | 325.60 | 205.93 | 119.67 | 1.59 | PASS |
| 13720.50† | 7535.10 | 5101.06 | -2455.79 | 13605.27 | 7332.50 | 5100.66 | -2701.11 | 269.91 | 318.16 | 207.85 | 110.31 | 1.54 | PASS |
| 13820.50† | 7535.20 | 5200.57 | -2465.61 | 13704.81 | 7332.50 | 5200.19 | -2701.27 | 269.91 | 310.85 | 209.62 | 101.23 | 1.49 | PASS |
| 13920.50† | 7535.30 | 5300.09 | -2475.42 | 13804.34 | 7332.50 | 5299.72 | -2701.44 | 269.91 | 303.66 | 211.23 | 92.43 | 1.45 | PASS |
| 14020.50† | 7535.40 | 5399.61 | -2485.24 | 13903.87 | 7332.50 | 5399.25 | -2701.60 | 269.91 | 296.62 | 212.66 | 83.96 | 1.40 | PASS |
| 14120.50† | 7535.51 | 5499.12 | -2495.05 | 14003.41 | 7332.50 | 5498.79 | -2701.76 | 269.91 | 289.72 | 213.89 | 75.84 | 1.36 | PASS |
| 14220.50† | 7535.61 | 5598.64 | -2504.87 | 14102.94 | 7332.50 | 5598.32 | -2701.92 | 269.91 | 282.99 | 214.91 | 68.08 | 1.32 | PASS |
| 14221.87 | 7535.61 | 5600.00 | -2505.00 | 14104.30 | 7332.50 | 5599.68 | -2701.93 | 269.91 | 282.90 | 214.92 | 67.98 | 1.32 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 38 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-4-2L PWB Offset Wellpath: BUFORD 33-4-2L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#05 BUFORD 33-4-2L (770'FSL & 844'FWL, SEC.34) Well: BUFORD 33-4-2L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 14320.50† | 7535.71 | 5698.31 | -2512.99 | 14202.62 | 7332.50 | 5698.00 | -2702.09 | 269.91 | 277.58 | 216.07 | 61.52 | 1.29 | PASS |
| 14420.50† | 7535.81 | 5798.19 | -2517.63 | 14302.51 | 7332.50 | 5797.89 | -2702.25 | 269.91 | 274.63 | 217.87 | 56.76 | 1.27 | PASS |
| 14520.50† | 7535.92 | 5898.18 | -2518.78 | 14402.50 | 7332.50 | 5897.88 | -2702.41 | 269.91 | 274.04 | 220.43 | 53.61 | 1.25 | PASS |
| 14581.38 | 7535.98 | 5959.05 | -2517.77 | 14463.37 | 7332.50 | 5958.75 | -2702.51 | 269.91 | 274.83 | 222.39 | 52.45 | 1.24 | PASS |
| 14620.50† | 7536.02 | 5998.16 | -2516.71 | 14502.47 | 7332.50 | 5997.85 | -2702.57 | 269.91 | 275.62 | 223.74 | 51.88 | 1.24 | PASS |
| 14720.50† | 7536.12 | 6098.12 | -2513.99 | 14602.43 | 7332.50 | 6097.81 | -2702.74 | 269.91 | 277.65 | 227.22 | 50.43 | 1.23 | PASS |
| 14820.50† | 7536.23 | 6198.08 | -2511.27 | 14702.39 | 7332.50 | 6197.77 | -2702.90 | 269.91 | 279.69 | 230.72 | 48.97 | 1.22 | PASS |
| 14920.50† | 7536.33 | 6298.05 | -2508.55 | 14802.35 | 7332.50 | 6297.73 | -2703.06 | 269.91 | 281.75 | 234.24 | 47.51 | 1.21 | PASS |
| 15020.50† | 7536.43 | 6398.01 | -2505.83 | 14902.31 | 7332.50 | 6397.69 | -2703.23 | 269.91 | 283.82 | 237.77 | 46.05 | 1.20 | PASS |
| 15120.50† | 7536.54 | 6497.97 | -2503.11 | 15002.27 | 7332.50 | 6497.65 | -2703.39 | 269.91 | 285.91 | 241.32 | 44.58 | 1.19 | PASS |
| 15220.50† | 7536.64 | 6597.93 | -2500.40 | 15102.22 | 7332.50 | 6597.60 | -2703.55 | 269.91 | 288.01 | 244.88 | 43.12 | 1.18 | PASS |
| 15320.50† | 7536.74 | 6697.90 | -2497.68 | 15202.18 | 7332.50 | 6697.56 | -2703.72 | 269.91 | 290.12 | 248.46 | 41.66 | 1.17 | PASS |
| 15420.50† | 7536.85 | 6797.86 | -2494.96 | 15302.14 | 7332.50 | 6797.52 | -2703.88 | 269.91 | 292.24 | 252.05 | 40.20 | 1.16 | PASS |
| 15520.50† | 7536.95 | 6897.82 | -2492.24 | 15402.10 | 7332.50 | 6897.48 | -2704.04 | 269.91 | 294.38 | 255.65 | 38.73 | 1.15 | PASS |
| 15620.50† | 7537.05 | 6997.79 | -2489.52 | 15502.06 | 7332.50 | 6997.44 | -2704.21 | 269.91 | 296.53 | 259.27 | 37.27 | 1.15 | PASS |
| 15720.50† | 7537.16 | 7097.75 | -2486.80 | 15602.02 | 7332.50 | 7097.39 | -2704.37 | 269.91 | 298.70 | 262.89 | 35.80 | 1.14 | PASS |
| 15820.50† | 7537.26 | 7197.71 | -2484.08 | 15701.97 | 7332.50 | 7197.35 | -2704.53 | 269.91 | 300.87 | 266.53 | 34.34 | 1.13 | PASS |
| 15920.50† | 7537.36 | 7297.68 | -2481.36 | 15801.93 | 7332.50 | 7297.31 | -2704.69 | 269.91 | 303.06 | 270.18 | 32.88 | 1.12 | PASS |
| 16020.50† | 7537.47 | 7397.64 | -2478.64 | 15901.89 | 7332.50 | 7397.27 | -2704.86 | 269.91 | 305.26 | 273.84 | 31.42 | 1.12 | PASS |
| 16120.50† | 7537.57 | 7497.60 | -2475.93 | 16001.85 | 7332.50 | 7497.23 | -2705.02 | 269.91 | 307.47 | 277.52 | 29.96 | 1.11 | PASS |
| 16220.50† | 7537.68 | 7597.56 | -2473.21 | 16101.81 | 7332.50 | 7597.19 | -2705.18 | 269.91 | 309.69 | 281.20 | 28.50 | 1.10 | PASS |
| 16320.50† | 7537.78 | 7697.53 | -2470.49 | 16201.77 | 7332.50 | 7697.14 | -2705.35 | 269.91 | 311.93 | 284.89 | 27.04 | 1.10 | WARN |
| 16420.50† | 7537.88 | 7797.49 | -2467.77 | 16301.72 | 7332.50 | 7797.10 | -2705.51 | 269.91 | 314.17 | 288.59 | 25.58 | 1.09 | WARN |
| 16520.50† | 7537.99 | 7897.45 | -2465.05 | 16401.68 | 7332.50 | 7897.06 | -2705.67 | 269.91 | 316.42 | 292.30 | 24.12 | 1.08 | WARN |
| 16620.50† | 7538.09 | 7997.42 | -2462.33 | 16501.64 | 7332.50 | 7997.02 | -2705.84 | 269.91 | 318.69 | 296.02 | 22.67 | 1.08 | WARN |
| 16720.50† | 7538.19 | 8097.38 | -2459.61 | 16601.60 | 7332.50 | 8096.98 | -2706.00 | 269.91 | 320.96 | 299.75 | 21.21 | 1.07 | WARN |
| 16820.50† | 7538.30 | 8197.34 | -2456.89 | 16701.56 | 7332.50 | 8196.94 | -2706.16 | 269.91 | 323.24 | 303.48 | 19.76 | 1.07 | WARN |
| 16920.50† | 7538.40 | 8297.31 | -2454.17 | 16801.52 | 7332.50 | 8296.89 | -2706.32 | 269.91 | 325.54 | 307.23 | 18.31 | 1.06 | WARN |
| 17020.50† | 7538.50 | 8397.27 | -2451.46 | 16901.48 | 7332.50 | 8396.85 | -2706.49 | 269.91 | 327.84 | 310.98 | 16.86 | 1.05 | WARN |
| 17120.50† | 7538.61 | 8497.23 | -2448.74 | 17001.43 | 7332.50 | 8496.81 | -2706.65 | 269.91 | 330.15 | 314.74 | 15.41 | 1.05 | WARN |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 39 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|---|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL,SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-4-2L PWB Offset Wellpath: BUFORD 33-4-2L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#05 BUFORD 33-4-2L (770'FSL & 844'FWL,SEC.34) Well: BUFORD 33-4-2L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 17220.50† | 7538.71 | 8597.19 | -2446.02 | 17101.39 | 7332.50 | 8596.77 | -2706.81 | 269.91 | 332.47 | 318.50 | 13.97 | 1.04 | WARN |
| 17320.50† | 7538.81 | 8697.16 | -2443.30 | 17201.35 | 7332.50 | 8696.73 | -2706.98 | 269.91 | 334.80 | 322.27 | 12.53 | 1.04 | WARN |
| 17420.50† | 7538.92 | 8797.12 | -2440.58 | 17301.31 | 7332.50 | 8796.69 | -2707.14 | 269.91 | 337.14 | 326.05 | 11.08 | 1.03 | WARN |
| 17520.50† | 7539.02 | 8897.08 | -2437.86 | 17401.27 | 7332.50 | 8896.64 | -2707.30 | 269.91 | 339.48 | 329.84 | 9.65 | 1.03 | WARN |
| 17620.50† | 7539.12 | 8997.05 | -2435.14 | 17501.23 | 7332.50 | 8996.60 | -2707.47 | 269.91 | 341.84 | 333.63 | 8.21 | 1.02 | WARN |
| 17720.50† | 7539.23 | 9097.01 | -2432.42 | 17601.18 | 7332.50 | 9096.56 | -2707.63 | 269.91 | 344.20 | 337.43 | 6.77 | 1.02 | WARN |
| 17820.50† | 7539.33 | 9196.97 | -2429.70 | 17701.14 | 7332.50 | 9196.52 | -2707.79 | 269.91 | 346.57 | 341.23 | 5.34 | 1.02 | WARN |
| 17920.50† | 7539.43 | 9296.94 | -2426.99 | 17801.10 | 7332.50 | 9296.48 | -2707.95 | 269.91 | 348.95 | 345.04 | 3.91 | 1.01 | WARN |
| 17985.90 | 7539.50 | 9362.31 | -2425.21 | 17863.32 | 7332.50 | 9358.69 | -2708.06 | 269.27 | 350.52 | 348.33 | 2.19 | 1.01 | WARN |

POSITIONAL UNCERTAINTY - Offset Wellbore: BUFORD 33-4-2L PWB Offset Wellpath: BUFORD 33-4-2L (REV-A.0) PWP

| | | | | |
|-----------------------------------|------------|---------|----------|---------|
| Slot Surface Uncertainty @1SD | Horizontal | 0.100ft | Vertical | 1.000ft |
| Facility Surface Uncertainty @1SD | Horizontal | 8.200ft | Vertical | 3.000ft |

SURVEY PROGRAM - Offset Wellbore: BUFORD 33-4-2L PWB Offset Wellpath: BUFORD 33-4-2L (REV-A.0) PWP

| Start MD [ft] | End MD [ft] | Positional Uncertainty Model | Log Name/Comment | Wellbore |
|---------------|-------------|---|------------------|--------------------|
| 20.50 | 1500.00 | BH NaviTrak (2019) (Standard) | | BUFORD 33-4-2L PWB |
| 1500.00 | 17931.23 | BH AutoTrak Curve/eXpress (2019) (Standard) | | BUFORD 33-4-2L PWB |

OFFSET WELLPATH REFERENCE - Offset Wellbore: BUFORD 33-4-2L PWB Offset Wellpath: BUFORD 33-4-2L (REV-A.0) PWP

| | |
|---------------------------------|---|
| MD Reference: RIG (20.5') (RKB) | Offset TVD & local coordinates use Reference Wellpath settings (See WELLPATH DATUM on page 1 of this report) |
| Ellipse Start MD | 20.50ft |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 40 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770°FSL & 819°FSL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-3-1L PWB Offset Wellpath: BUFORD 33-3-1L (REV-B.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#07 BUFORD 33-3-1L (770°FSL & 894°FSL, SEC.34) Well: BUFORD 33-3-1L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | | |
| 20.50 | 20.50 | 0.00 | 0.00 | 21.50 | 20.50 | 0.00 | 75.64 | 90.00 | 75.64 | 9.75 | 65.89 | 12.43 | PASS | | | |
| 120.50† | 120.50 | 0.00 | 0.00 | 121.50 | 120.50 | 0.00 | 75.64 | 90.00 | 75.64 | 9.82 | 65.83 | 12.29 | PASS | | | |
| 200.00 | 200.00 | 0.00 | 0.00 | 201.00 | 200.00 | 0.00 | 75.64 | 90.00 | 75.64 | 9.96 | 65.68 | 11.98 | PASS | | | |
| 220.50† | 220.50 | -0.03 | -0.07 | 221.50 | 220.50 | 0.00 | 75.64 | 89.98 | 75.71 | 10.02 | 65.69 | 11.89 | PASS | | | |
| 320.50† | 320.46 | -0.93 | -2.36 | 321.46 | 320.46 | 0.00 | 75.64 | 89.31 | 78.00 | 10.41 | 67.59 | 11.52 | PASS | | | |
| 420.50† | 420.28 | -3.13 | -7.88 | 421.28 | 420.28 | 0.00 | 75.64 | 87.86 | 83.58 | 11.10 | 72.49 | 11.19 | PASS | | | |
| 520.50† | 519.83 | -6.60 | -16.65 | 520.83 | 519.83 | 0.00 | 75.64 | 85.91 | 92.53 | 11.84 | 80.69 | 11.28 | PASS | | | |
| 620.50† | 618.99 | -11.36 | -28.64 | 619.99 | 618.99 | 0.00 | 75.64 | 83.79 | 104.89 | 12.62 | 92.28 | 11.69 | PASS | | | |
| 720.50† | 717.64 | -17.38 | -43.83 | 719.44 | 718.44 | -0.02 | 75.58 | 81.73 | 120.67 | 13.42 | 107.25 | 12.36 | PASS | | | |
| 820.50† | 815.66 | -24.68 | -62.22 | 822.49 | 821.45 | -0.90 | 73.18 | 80.04 | 137.60 | 14.32 | 123.28 | 12.93 | PASS | | | |
| 920.50† | 912.93 | -33.22 | -83.78 | 926.21 | 924.97 | -3.06 | 67.26 | 78.71 | 154.49 | 15.36 | 139.13 | 13.23 | PASS | | | |
| 1020.50† | 1009.33 | -43.02 | -108.48 | 1030.61 | 1028.88 | -6.54 | 57.74 | 77.62 | 171.30 | 16.39 | 154.91 | 13.49 | PASS | | | |
| 1120.50† | 1104.74 | -54.05 | -136.29 | 1135.71 | 1133.03 | -11.35 | 44.58 | 76.72 | 187.98 | 17.42 | 170.57 | 13.70 | PASS | | | |
| 1220.50† | 1199.05 | -66.30 | -167.18 | 1241.50 | 1237.28 | -17.51 | 27.72 | 75.95 | 204.52 | 18.44 | 186.08 | 13.88 | PASS | | | |
| 1242.54 | 1219.68 | -69.16 | -174.40 | 1264.90 | 1260.25 | -19.05 | 23.50 | 75.79 | 208.13 | 18.65 | 189.49 | 13.92 | PASS | | | |
| 1320.50† | 1292.54 | -79.39 | -200.20 | 1348.15 | 1341.64 | -25.05 | 7.06 | 75.31 | 219.82 | 19.34 | 200.48 | 14.06 | PASS | | | |
| 1420.50† | 1385.99 | -92.51 | -233.28 | 1455.91 | 1446.17 | -34.02 | -17.49 | 74.84 | 231.54 | 20.17 | 211.37 | 14.06 | PASS | | | |
| 1520.50† | 1479.44 | -105.63 | -266.37 | 1564.48 | 1550.42 | -44.42 | -45.94 | 74.48 | 239.53 | 20.60 | 218.93 | 14.18 | PASS | | | |
| 1620.50† | 1572.89 | -118.75 | -299.46 | 1673.56 | 1653.93 | -56.22 | -78.25 | 74.22 | 243.74 | 20.75 | 222.99 | 14.30 | PASS | | | |
| 1720.50† | 1666.34 | -131.87 | -332.54 | 1782.85 | 1756.25 | -69.40 | -114.30 | 74.03 | 244.16 | 20.95 | 223.21 | 14.15 | PASS | | | |
| 1820.50† | 1759.79 | -144.99 | -365.63 | 1886.88 | 1852.43 | -83.00 | -151.53 | 73.85 | 241.38 | 21.21 | 220.16 | 13.78 | PASS | | | |
| 1920.50† | 1853.24 | -158.12 | -398.72 | 1986.83 | 1944.69 | -96.19 | -187.64 | 73.65 | 238.23 | 21.48 | 216.74 | 13.39 | PASS | | | |
| 2020.50† | 1946.69 | -171.24 | -431.80 | 2086.78 | 2036.95 | -109.38 | -223.74 | 73.44 | 235.08 | 21.84 | 213.25 | 12.95 | PASS | | | |
| 2120.50† | 2040.14 | -184.36 | -464.89 | 2186.72 | 2129.22 | -122.57 | -259.84 | 73.23 | 231.94 | 22.25 | 209.69 | 12.48 | PASS | | | |
| 2220.50† | 2133.59 | -197.48 | -497.98 | 2286.67 | 2221.48 | -135.76 | -295.95 | 73.01 | 228.80 | 22.71 | 206.09 | 12.01 | PASS | | | |
| 2320.50† | 2227.05 | -210.60 | -531.06 | 2386.62 | 2313.74 | -148.95 | -332.05 | 72.79 | 225.66 | 23.22 | 202.44 | 11.53 | PASS | | | |
| 2420.50† | 2320.50 | -223.72 | -564.15 | 2486.57 | 2406.00 | -162.14 | -368.15 | 72.56 | 222.52 | 23.77 | 198.75 | 11.04 | PASS | | | |
| 2520.50† | 2413.95 | -236.84 | -597.24 | 2586.51 | 2498.26 | -175.33 | -404.26 | 72.32 | 219.39 | 24.37 | 195.02 | 10.57 | PASS | | | |
| 2620.50† | 2507.40 | -249.96 | -630.32 | 2686.46 | 2590.52 | -188.52 | -440.36 | 72.08 | 216.26 | 25.01 | 191.26 | 10.10 | PASS | | | |
| 2720.50† | 2600.85 | -263.08 | -663.41 | 2786.41 | 2682.78 | -201.71 | -476.46 | 71.83 | 213.14 | 25.68 | 187.46 | 9.64 | PASS | | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 41 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-3-1L PWB Offset Wellpath: BUFORD 33-3-1L (REV-B.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#07 BUFORD 33-3-1L (770'FSL & 894'FWL,SEC.34) Well: BUFORD 33-3-1L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|-----------------|-------------------|------------------|-------------------|--------------------|----------------------|---------------------|-------------------------|---------------------------|----------------------|----------------------------|--------------|----------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 2820.50† | 2694.30 | -276.20 | -696.50 | 2886.36 | 2775.04 | -214.90 | -512.57 | 71.57 | 210.02 | 26.38 | 183.64 | 9.20 | PASS |
| 2920.50† | 2787.75 | -289.33 | -729.58 | 2986.30 | 2867.30 | -228.09 | -548.67 | 71.30 | 206.90 | 27.11 | 179.79 | 8.77 | PASS |
| 3020.50† | 2881.20 | -302.45 | -762.67 | 3086.25 | 2959.56 | -241.28 | -584.77 | 71.03 | 203.79 | 27.87 | 175.92 | 8.37 | PASS |
| 3120.50† | 2974.65 | -315.57 | -795.76 | 3186.20 | 3051.82 | -254.47 | -620.88 | 70.74 | 200.68 | 28.65 | 172.03 | 7.98 | PASS |
| 3220.50† | 3068.11 | -328.69 | -828.84 | 3286.15 | 3144.08 | -267.66 | -656.98 | 70.45 | 197.57 | 29.45 | 168.12 | 7.60 | PASS |
| 3320.50† | 3161.56 | -341.81 | -861.93 | 3386.09 | 3236.34 | -280.85 | -693.08 | 70.15 | 194.47 | 30.27 | 164.20 | 7.25 | PASS |
| 3420.50† | 3255.01 | -354.93 | -895.02 | 3486.04 | 3328.61 | -294.04 | -729.19 | 69.84 | 191.37 | 31.11 | 160.26 | 6.91 | PASS |
| 3520.50† | 3348.46 | -368.05 | -928.10 | 3585.99 | 3420.87 | -307.23 | -765.29 | 69.52 | 188.28 | 31.97 | 156.31 | 6.59 | PASS |
| 3620.50† | 3441.91 | -381.17 | -961.19 | 3685.94 | 3513.13 | -320.42 | -801.39 | 69.19 | 185.20 | 32.84 | 152.36 | 6.28 | PASS |
| 3720.50† | 3535.36 | -394.29 | -994.28 | 3785.88 | 3605.39 | -333.61 | -837.50 | 68.84 | 182.12 | 33.73 | 148.39 | 5.99 | PASS |
| 3820.50† | 3628.81 | -407.41 | -1027.37 | 3885.83 | 3697.65 | -346.81 | -873.60 | 68.49 | 179.04 | 34.63 | 144.41 | 5.71 | PASS |
| 3920.50† | 3722.26 | -420.53 | -1060.45 | 3985.78 | 3789.91 | -360.00 | -909.70 | 68.12 | 175.97 | 35.55 | 140.42 | 5.45 | PASS |
| 4020.50† | 3815.71 | -433.66 | -1093.54 | 4085.73 | 3882.17 | -373.19 | -945.81 | 67.74 | 172.91 | 36.48 | 136.43 | 5.20 | PASS |
| 4120.50† | 3909.17 | -446.78 | -1126.63 | 4185.67 | 3974.43 | -386.38 | -981.91 | 67.35 | 169.86 | 37.42 | 132.43 | 4.96 | PASS |
| 4220.50† | 4002.62 | -459.90 | -1159.71 | 4285.62 | 4066.69 | -399.57 | -1018.01 | 66.94 | 166.81 | 38.38 | 128.43 | 4.73 | PASS |
| 4320.50† | 4096.07 | -473.02 | -1192.80 | 4385.57 | 4158.95 | -412.76 | -1054.12 | 66.51 | 163.77 | 39.35 | 124.42 | 4.52 | PASS |
| 4420.50† | 4189.52 | -486.14 | -1225.89 | 4485.51 | 4251.21 | -425.95 | -1090.22 | 66.07 | 160.73 | 40.33 | 120.41 | 4.31 | PASS |
| 4520.50† | 4282.97 | -499.26 | -1258.97 | 4585.46 | 4343.47 | -439.14 | -1126.32 | 65.62 | 157.71 | 41.32 | 116.39 | 4.12 | PASS |
| 4620.50† | 4376.42 | -512.38 | -1292.06 | 4685.41 | 4435.73 | -452.33 | -1162.43 | 65.14 | 154.69 | 42.33 | 112.36 | 3.93 | PASS |
| 4720.50† | 4469.87 | -525.50 | -1325.15 | 4785.36 | 4528.00 | -465.52 | -1198.53 | 64.65 | 151.69 | 43.35 | 108.33 | 3.75 | PASS |
| 4820.50† | 4563.32 | -538.62 | -1358.23 | 4885.30 | 4620.26 | -478.71 | -1234.63 | 64.14 | 148.69 | 44.39 | 104.30 | 3.58 | PASS |
| 4920.50† | 4656.77 | -551.74 | -1391.32 | 4985.25 | 4712.52 | -491.90 | -1270.73 | 63.61 | 145.70 | 45.45 | 100.26 | 3.42 | PASS |
| 5020.50† | 4750.22 | -564.87 | -1424.41 | 5085.20 | 4804.78 | -505.09 | -1306.84 | 63.05 | 142.73 | 46.52 | 96.21 | 3.26 | PASS |
| 5120.50† | 4843.68 | -577.99 | -1457.49 | 5185.15 | 4897.04 | -518.28 | -1342.94 | 62.47 | 139.77 | 47.61 | 92.16 | 3.11 | PASS |
| 5220.50† | 4937.13 | -591.11 | -1490.58 | 5285.09 | 4989.30 | -531.47 | -1379.04 | 61.87 | 136.82 | 48.72 | 88.10 | 2.97 | PASS |
| 5320.50† | 5030.58 | -604.23 | -1523.67 | 5385.04 | 5081.56 | -544.66 | -1415.15 | 61.24 | 133.88 | 49.86 | 84.02 | 2.83 | PASS |
| 5420.50† | 5124.03 | -617.35 | -1556.75 | 5484.99 | 5173.82 | -557.85 | -1451.25 | 60.58 | 130.96 | 51.01 | 79.94 | 2.70 | PASS |
| 5520.50† | 5217.48 | -630.47 | -1589.84 | 5584.94 | 5266.08 | -571.04 | -1487.35 | 59.89 | 128.05 | 52.20 | 75.85 | 2.57 | PASS |
| 5620.50† | 5310.93 | -643.59 | -1622.93 | 5684.88 | 5358.34 | -584.23 | -1523.46 | 59.17 | 125.16 | 53.42 | 71.75 | 2.45 | PASS |
| 5720.50† | 5404.38 | -656.71 | -1656.01 | 5784.83 | 5450.60 | -597.42 | -1559.56 | 58.42 | 122.29 | 54.67 | 67.62 | 2.33 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 42 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-3-1L PWB Offset Wellpath: BUFORD 33-3-1L (REV-B.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#07 BUFORD 33-3-1L (770'FSL & 894'FWL,SEC.34) Well: BUFORD 33-3-1L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|-----------------|-------------------|------------------|-------------------|--------------------|----------------------|---------------------|-------------------------|---------------------------|----------------------|----------------------------|--------------|----------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 5820.50† | 5497.83 | -669.83 | -1689.10 | 5884.78 | 5542.86 | -610.61 | -1595.66 | 57.63 | 119.44 | 55.95 | 63.48 | 2.22 | PASS |
| 5920.50† | 5591.28 | -682.95 | -1722.19 | 5984.73 | 5635.12 | -623.80 | -1631.77 | 56.81 | 116.61 | 57.28 | 59.33 | 2.11 | PASS |
| 6020.50† | 5684.74 | -696.07 | -1755.27 | 6084.67 | 5727.39 | -636.99 | -1667.87 | 55.94 | 113.79 | 58.65 | 55.14 | 2.01 | PASS |
| 6120.50† | 5778.19 | -709.20 | -1788.36 | 6184.62 | 5819.65 | -650.18 | -1703.97 | 55.04 | 111.01 | 60.07 | 50.93 | 1.91 | PASS |
| 6220.50† | 5871.64 | -722.32 | -1821.45 | 6284.57 | 5911.91 | -663.37 | -1740.08 | 54.08 | 108.25 | 61.55 | 46.69 | 1.81 | PASS |
| 6320.50† | 5965.09 | -735.44 | -1854.54 | 6384.52 | 6004.17 | -676.56 | -1776.18 | 53.08 | 105.51 | 63.09 | 42.42 | 1.72 | PASS |
| 6420.50† | 6058.54 | -748.56 | -1887.62 | 6484.46 | 6096.43 | -689.75 | -1812.28 | 52.03 | 102.81 | 64.70 | 38.11 | 1.63 | PASS |
| 6520.50† | 6151.99 | -761.68 | -1920.71 | 6584.41 | 6188.69 | -702.94 | -1848.39 | 50.92 | 100.14 | 66.38 | 33.75 | 1.54 | PASS |
| 6620.50† | 6245.44 | -774.80 | -1953.80 | 6684.36 | 6280.95 | -716.13 | -1884.49 | 49.75 | 97.50 | 68.15 | 29.35 | 1.46 | PASS |
| 6720.50† | 6338.89 | -787.92 | -1986.88 | 6784.30 | 6373.21 | -729.33 | -1920.59 | 48.53 | 94.90 | 70.01 | 24.89 | 1.38 | PASS |
| 6820.50† | 6432.34 | -801.04 | -2019.97 | 6884.25 | 6465.47 | -742.52 | -1956.70 | 47.23 | 92.34 | 71.97 | 20.37 | 1.30 | PASS |
| 6920.50† | 6525.80 | -814.16 | -2053.06 | 6984.20 | 6557.73 | -755.71 | -1992.80 | 45.87 | 89.82 | 74.04 | 15.78 | 1.23 | PASS |
| 7020.50† | 6619.25 | -827.28 | -2086.14 | 7084.15 | 6649.99 | -768.90 | -2028.90 | 44.43 | 87.36 | 76.23 | 11.13 | 1.15 | PASS |
| 7120.50† | 6712.70 | -840.41 | -2119.23 | 7178.28 | 6737.09 | -779.12 | -2062.99 | 42.54 | 86.68 | 79.32 | 7.36 | 1.10 | WARN |
| 7133.45† | 6724.80 | -842.10 | -2123.51 | 7189.68 | 6747.70 | -779.40 | -2067.14 | 41.95 | 87.37 | 80.03 | 7.34 | 1.10 | PASS |
| 7220.50† | 6806.15 | -853.53 | -2152.32 | 7264.00 | 6816.69 | -774.54 | -2094.16 | 36.36 | 98.65 | 86.23 | 12.42 | 1.15 | PASS |
| 7320.50† | 6899.60 | -866.65 | -2185.40 | 7341.90 | 6887.31 | -757.18 | -2121.84 | 30.14 | 127.18 | 91.95 | 35.23 | 1.40 | PASS |
| 7341.07 | 6918.82 | -869.35 | -2192.21 | 7356.68 | 6900.36 | -752.50 | -2126.96 | 29.18 | 135.09 | 92.55 | 42.54 | 1.48 | PASS |
| 7420.50† | 6993.49 | -874.29 | -2218.65 | 7411.64 | 6947.56 | -731.37 | -2145.48 | 27.11 | 167.01 | 92.58 | 74.43 | 1.84 | PASS |
| 7520.50† | 7087.21 | -864.88 | -2251.87 | 7477.70 | 7000.83 | -698.46 | -2166.39 | 27.19 | 206.06 | 89.08 | 116.98 | 2.37 | PASS |
| 7620.50† | 7177.96 | -838.35 | -2284.05 | 7541.06 | 7047.48 | -659.78 | -2184.72 | 29.09 | 242.44 | 83.39 | 159.06 | 3.00 | PASS |
| 7720.50† | 7262.97 | -795.51 | -2314.23 | 7602.36 | 7087.69 | -616.37 | -2200.53 | 32.40 | 275.22 | 76.18 | 199.03 | 3.76 | PASS |
| 7820.50† | 7339.68 | -737.65 | -2341.49 | 7662.06 | 7121.56 | -569.09 | -2213.88 | 37.13 | 303.76 | 68.24 | 235.52 | 4.67 | PASS |
| 7920.50† | 7405.75 | -666.53 | -2364.99 | 7720.58 | 7149.17 | -518.71 | -2224.77 | 43.49 | 327.63 | 60.27 | 267.36 | 5.75 | PASS |
| 8020.50† | 7459.16 | -584.32 | -2384.03 | 7778.20 | 7170.56 | -465.91 | -2233.23 | 51.86 | 346.48 | 53.03 | 293.45 | 6.98 | PASS |
| 8120.50† | 7498.30 | -493.50 | -2398.02 | 7835.20 | 7185.74 | -411.34 | -2239.27 | 62.64 | 360.07 | 47.55 | 312.52 | 8.17 | PASS |
| 8220.50† | 7521.99 | -396.85 | -2406.55 | 7891.80 | 7194.72 | -355.61 | -2242.87 | 75.86 | 368.23 | 45.02 | 323.22 | 8.88 | PASS |
| 8315.56 | 7529.50 | -302.24 | -2409.34 | 7945.55 | 7197.50 | -301.97 | -2244.05 | 89.91 | 370.87 | 45.90 | 324.97 | 8.75 | PASS |
| 8320.50† | 7529.51 | -297.30 | -2409.35 | 7950.49 | 7197.50 | -297.03 | -2244.06 | 89.91 | 370.88 | 45.92 | 324.95 | 8.75 | PASS |
| 8420.50† | 7529.61 | -197.30 | -2409.53 | 8050.49 | 7197.50 | -197.03 | -2244.22 | 89.91 | 370.97 | 46.03 | 324.95 | 8.73 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 43 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-3-1L PWB Offset Wellpath: BUFORD 33-3-1L (REV-B.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#07 BUFORD 33-3-1L (770'FSL & 894'FWL, SEC.34) Well: BUFORD 33-3-1L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | |
| 8520.50† | 7529.71 | -97.30 | -2409.71 | 8150.49 | 7197.50 | -97.03 | -2244.39 | 89.91 | 371.07 | 46.32 | 324.76 | 8.67 | PASS | | |
| 8620.50† | 7529.82 | 2.70 | -2409.88 | 8250.49 | 7197.50 | 2.97 | -2244.55 | 89.91 | 371.17 | 46.69 | 324.48 | 8.60 | PASS | | |
| 8720.50† | 7529.92 | 102.70 | -2410.06 | 8350.49 | 7197.50 | 102.97 | -2244.72 | 89.91 | 371.27 | 47.23 | 324.04 | 8.49 | PASS | | |
| 8820.50† | 7530.02 | 202.70 | -2410.24 | 8450.49 | 7197.50 | 202.97 | -2244.88 | 89.91 | 371.37 | 47.90 | 323.47 | 8.37 | PASS | | |
| 8920.50† | 7530.13 | 302.70 | -2410.42 | 8550.49 | 7197.50 | 302.97 | -2245.05 | 89.91 | 371.47 | 48.70 | 322.77 | 8.22 | PASS | | |
| 9020.50† | 7530.23 | 402.70 | -2410.59 | 8650.49 | 7197.50 | 402.97 | -2245.21 | 89.91 | 371.57 | 49.62 | 321.95 | 8.06 | PASS | | |
| 9120.50† | 7530.33 | 502.70 | -2410.77 | 8750.49 | 7197.50 | 502.97 | -2245.38 | 89.91 | 371.66 | 50.65 | 321.02 | 7.88 | PASS | | |
| 9220.50† | 7530.44 | 602.70 | -2410.95 | 8850.49 | 7197.50 | 602.97 | -2245.54 | 89.91 | 371.76 | 51.78 | 319.98 | 7.69 | PASS | | |
| 9320.50† | 7530.54 | 702.70 | -2411.13 | 8950.49 | 7197.50 | 702.97 | -2245.71 | 89.91 | 371.86 | 53.01 | 318.85 | 7.50 | PASS | | |
| 9420.50† | 7530.64 | 802.69 | -2411.31 | 9050.49 | 7197.50 | 802.97 | -2245.87 | 89.91 | 371.96 | 54.33 | 317.63 | 7.31 | PASS | | |
| 9520.50† | 7530.75 | 902.69 | -2411.48 | 9150.49 | 7197.50 | 902.97 | -2246.04 | 89.91 | 372.06 | 55.74 | 316.32 | 7.11 | PASS | | |
| 9620.50† | 7530.85 | 1002.69 | -2411.66 | 9250.49 | 7197.50 | 1002.97 | -2246.20 | 89.91 | 372.16 | 57.22 | 314.94 | 6.92 | PASS | | |
| 9720.50† | 7530.96 | 1102.69 | -2411.84 | 9350.49 | 7197.50 | 1102.97 | -2246.37 | 89.91 | 372.25 | 58.77 | 313.48 | 6.72 | PASS | | |
| 9820.50† | 7531.06 | 1202.69 | -2412.02 | 9450.49 | 7197.50 | 1202.97 | -2246.53 | 89.91 | 372.35 | 60.39 | 311.96 | 6.53 | PASS | | |
| 9920.50† | 7531.16 | 1302.69 | -2412.19 | 9550.49 | 7197.50 | 1302.97 | -2246.70 | 89.91 | 372.45 | 62.06 | 310.39 | 6.34 | PASS | | |
| 10020.50† | 7531.27 | 1402.69 | -2412.37 | 9650.49 | 7197.50 | 1402.97 | -2246.86 | 89.91 | 372.55 | 63.79 | 308.76 | 6.16 | PASS | | |
| 10120.50† | 7531.37 | 1502.69 | -2412.55 | 9750.49 | 7197.50 | 1502.97 | -2247.03 | 89.91 | 372.65 | 65.57 | 307.08 | 5.99 | PASS | | |
| 10220.50† | 7531.47 | 1602.69 | -2412.73 | 9850.49 | 7197.50 | 1602.97 | -2247.19 | 89.91 | 372.75 | 67.40 | 305.35 | 5.82 | PASS | | |
| 10320.50† | 7531.58 | 1702.69 | -2412.90 | 9950.49 | 7197.50 | 1702.97 | -2247.36 | 89.91 | 372.85 | 69.26 | 303.58 | 5.65 | PASS | | |
| 10420.50† | 7531.68 | 1802.69 | -2413.08 | 10050.49 | 7197.50 | 1802.97 | -2247.52 | 89.91 | 372.94 | 71.17 | 301.78 | 5.49 | PASS | | |
| 10520.50† | 7531.78 | 1902.69 | -2413.26 | 10150.49 | 7197.50 | 1902.97 | -2247.69 | 89.91 | 373.04 | 73.10 | 299.94 | 5.34 | PASS | | |
| 10620.50† | 7531.89 | 2002.69 | -2413.44 | 10250.49 | 7197.50 | 2002.97 | -2247.85 | 89.91 | 373.14 | 75.07 | 298.07 | 5.19 | PASS | | |
| 10720.50† | 7531.99 | 2102.69 | -2413.62 | 10350.49 | 7197.50 | 2102.97 | -2248.02 | 89.91 | 373.24 | 77.07 | 296.17 | 5.05 | PASS | | |
| 10820.50† | 7532.09 | 2202.69 | -2413.79 | 10450.49 | 7197.50 | 2202.96 | -2248.18 | 89.91 | 373.34 | 79.10 | 294.24 | 4.92 | PASS | | |
| 10920.50† | 7532.20 | 2302.69 | -2413.97 | 10550.49 | 7197.50 | 2302.96 | -2248.35 | 89.91 | 373.44 | 81.15 | 292.28 | 4.79 | PASS | | |
| 11020.50† | 7532.30 | 2402.69 | -2414.15 | 10650.49 | 7197.50 | 2402.96 | -2248.51 | 89.91 | 373.54 | 83.23 | 290.31 | 4.66 | PASS | | |
| 11120.50† | 7532.41 | 2502.69 | -2414.33 | 10750.49 | 7197.50 | 2502.96 | -2248.67 | 89.91 | 373.63 | 85.32 | 288.31 | 4.54 | PASS | | |
| 11220.50† | 7532.51 | 2602.69 | -2414.50 | 10850.49 | 7197.50 | 2602.96 | -2248.84 | 89.91 | 373.73 | 87.44 | 286.30 | 4.43 | PASS | | |
| 11320.50† | 7532.61 | 2702.69 | -2414.68 | 10950.49 | 7197.50 | 2702.96 | -2249.00 | 89.91 | 373.83 | 89.57 | 284.26 | 4.32 | PASS | | |
| 11420.50† | 7532.72 | 2802.69 | -2414.86 | 11050.49 | 7197.50 | 2802.96 | -2249.17 | 89.91 | 373.93 | 91.72 | 282.21 | 4.22 | PASS | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 44 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-3-1L PWB Offset Wellpath: BUFORD 33-3-1L (REV-B.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#07 BUFORD 33-3-1L (770'FSL & 894'FWL, SEC.34) Well: BUFORD 33-3-1L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 11520.50† | 7532.82 | 2902.69 | -2415.04 | 11150.49 | 7197.50 | 2902.96 | -2249.33 | 89.91 | 374.03 | 93.88 | 280.15 | 4.12 | PASS |
| 11620.50† | 7532.92 | 3002.69 | -2415.21 | 11250.49 | 7197.50 | 3002.96 | -2249.50 | 89.91 | 374.13 | 96.06 | 278.07 | 4.02 | PASS |
| 11720.50† | 7533.03 | 3102.69 | -2415.39 | 11350.49 | 7197.50 | 3102.96 | -2249.66 | 89.91 | 374.22 | 98.25 | 275.97 | 3.93 | PASS |
| 11820.50† | 7533.13 | 3202.69 | -2415.57 | 11450.49 | 7197.50 | 3202.96 | -2249.83 | 89.91 | 374.32 | 100.46 | 273.87 | 3.84 | PASS |
| 11920.50† | 7533.23 | 3302.69 | -2415.75 | 11550.49 | 7197.50 | 3302.96 | -2249.99 | 89.91 | 374.42 | 102.67 | 271.75 | 3.75 | PASS |
| 12020.50† | 7533.34 | 3402.69 | -2415.92 | 11650.49 | 7197.50 | 3402.96 | -2250.16 | 89.91 | 374.52 | 104.90 | 269.62 | 3.67 | PASS |
| 12120.50† | 7533.44 | 3502.69 | -2416.10 | 11750.49 | 7197.50 | 3502.96 | -2250.32 | 89.91 | 374.62 | 107.13 | 267.48 | 3.59 | PASS |
| 12220.50† | 7533.55 | 3602.69 | -2416.28 | 11850.49 | 7197.50 | 3602.96 | -2250.49 | 89.91 | 374.72 | 109.38 | 265.34 | 3.52 | PASS |
| 12320.50† | 7533.65 | 3702.69 | -2416.46 | 11950.49 | 7197.50 | 3702.96 | -2250.65 | 89.91 | 374.82 | 111.64 | 263.18 | 3.44 | PASS |
| 12420.50† | 7533.75 | 3802.69 | -2416.64 | 12050.49 | 7197.50 | 3802.96 | -2250.82 | 89.91 | 374.91 | 113.90 | 261.02 | 3.37 | PASS |
| 12520.50† | 7533.86 | 3902.69 | -2416.81 | 12150.49 | 7197.50 | 3902.96 | -2250.98 | 89.91 | 375.01 | 116.17 | 258.85 | 3.31 | PASS |
| 12620.50† | 7533.96 | 4002.69 | -2416.99 | 12250.49 | 7197.50 | 4002.96 | -2251.15 | 89.91 | 375.11 | 118.45 | 256.67 | 3.24 | PASS |
| 12720.50† | 7534.06 | 4102.69 | -2417.17 | 12350.49 | 7197.50 | 4102.96 | -2251.31 | 89.91 | 375.21 | 120.73 | 254.48 | 3.18 | PASS |
| 12820.50† | 7534.17 | 4202.69 | -2417.35 | 12450.49 | 7197.50 | 4202.96 | -2251.48 | 89.91 | 375.31 | 123.02 | 252.29 | 3.12 | PASS |
| 12920.50† | 7534.27 | 4302.69 | -2417.52 | 12550.49 | 7197.50 | 4302.96 | -2251.64 | 89.91 | 375.41 | 125.32 | 250.09 | 3.06 | PASS |
| 13020.50† | 7534.37 | 4402.69 | -2417.70 | 12650.49 | 7197.50 | 4402.96 | -2251.81 | 89.91 | 375.51 | 127.62 | 247.89 | 3.00 | PASS |
| 13120.50† | 7534.48 | 4502.69 | -2417.88 | 12750.49 | 7197.50 | 4502.96 | -2251.97 | 89.91 | 375.61 | 129.93 | 245.68 | 2.95 | PASS |
| 13199.97 | 7534.56 | 4582.16 | -2418.02 | 12829.96 | 7197.50 | 4582.43 | -2252.10 | 89.91 | 375.68 | 131.76 | 243.92 | 2.91 | PASS |
| 13220.50† | 7534.58 | 4602.69 | -2418.13 | 12850.49 | 7197.50 | 4602.96 | -2252.14 | 89.91 | 375.74 | 132.24 | 243.49 | 2.90 | PASS |
| 13320.50† | 7534.68 | 4702.65 | -2420.77 | 12950.45 | 7197.50 | 4702.92 | -2252.30 | 89.91 | 376.93 | 134.83 | 242.10 | 2.85 | PASS |
| 13420.50† | 7534.79 | 4802.45 | -2426.90 | 13047.38 | 7197.50 | 4799.85 | -2252.07 | 90.85 | 379.91 | 137.45 | 242.46 | 2.82 | PASS |
| 13476.50 | 7534.85 | 4858.23 | -2431.85 | 13099.77 | 7197.50 | 4852.23 | -2250.81 | 91.90 | 382.90 | 138.98 | 243.92 | 2.81 | PASS |
| 13520.50† | 7534.89 | 4902.02 | -2436.16 | 13140.71 | 7197.50 | 4893.14 | -2249.16 | 92.72 | 385.85 | 140.30 | 245.55 | 2.80 | PASS |
| 13620.50† | 7534.99 | 5001.54 | -2445.98 | 13233.11 | 7197.50 | 4985.34 | -2243.29 | 94.57 | 394.01 | 143.52 | 250.50 | 2.80 | PASS |
| 13720.50† | 7535.10 | 5101.06 | -2455.79 | 13328.05 | 7197.50 | 5079.88 | -2234.59 | 95.47 | 404.16 | 147.65 | 256.51 | 2.79 | PASS |
| 13820.50† | 7535.20 | 5200.57 | -2465.61 | 13426.18 | 7197.50 | 5177.56 | -2225.24 | 95.47 | 415.14 | 152.62 | 262.52 | 2.77 | PASS |
| 13920.50† | 7535.30 | 5300.09 | -2475.42 | 13524.31 | 7197.50 | 5275.24 | -2215.89 | 95.47 | 426.71 | 157.75 | 268.96 | 2.75 | PASS |
| 14020.50† | 7535.40 | 5399.61 | -2485.24 | 13622.43 | 7197.50 | 5372.93 | -2206.54 | 95.47 | 438.82 | 162.98 | 275.84 | 2.73 | PASS |
| 14120.50† | 7535.51 | 5499.12 | -2495.05 | 13720.56 | 7197.50 | 5470.61 | -2197.19 | 95.47 | 451.42 | 168.27 | 283.16 | 2.72 | PASS |
| 14220.50† | 7535.61 | 5598.64 | -2504.87 | 13827.26 | 7197.50 | 5576.91 | -2188.06 | 93.93 | 463.85 | 175.23 | 288.62 | 2.69 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 45 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-3-1L PWB Offset Wellpath: BUFORD 33-3-1L (REV-B.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#07 BUFORD 33-3-1L (770'FSL & 894'FWL,SEC.34) Well: BUFORD 33-3-1L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 14221.87 | 7535.61 | 5600.00 | -2505.00 | 13828.77 | 7197.50 | 5578.42 | -2187.95 | 93.90 | 464.01 | 175.34 | 288.67 | 2.68 | PASS |
| 14320.50† | 7535.71 | 5698.31 | -2512.99 | 13939.05 | 7197.50 | 5688.56 | -2182.58 | 91.69 | 472.92 | 182.40 | 290.52 | 2.63 | PASS |
| 14420.50† | 7535.81 | 5798.19 | -2517.63 | 14052.05 | 7197.50 | 5801.54 | -2181.48 | 89.43 | 476.93 | 188.60 | 288.34 | 2.56 | PASS |
| 14520.50† | 7535.92 | 5898.18 | -2518.78 | 14156.12 | 7197.50 | 5905.59 | -2183.57 | 88.73 | 476.39 | 192.16 | 284.23 | 2.51 | PASS |
| 14581.38 | 7535.98 | 5959.05 | -2517.77 | 14216.95 | 7197.50 | 5966.41 | -2184.91 | 88.73 | 474.78 | 193.61 | 281.18 | 2.48 | PASS |
| 14620.50† | 7536.02 | 5998.16 | -2516.71 | 14256.02 | 7197.50 | 6005.47 | -2185.78 | 88.73 | 473.46 | 194.46 | 279.00 | 2.46 | PASS |
| 14720.50† | 7536.12 | 6098.12 | -2513.99 | 14355.90 | 7197.50 | 6105.33 | -2187.98 | 88.73 | 470.10 | 196.63 | 273.47 | 2.42 | PASS |
| 14820.50† | 7536.23 | 6198.08 | -2511.27 | 14455.78 | 7197.50 | 6205.18 | -2190.19 | 88.73 | 466.77 | 198.78 | 268.00 | 2.38 | PASS |
| 14920.50† | 7536.33 | 6298.05 | -2508.55 | 14555.66 | 7197.50 | 6305.03 | -2192.40 | 88.73 | 463.47 | 200.88 | 262.59 | 2.33 | PASS |
| 15020.50† | 7536.43 | 6398.01 | -2505.83 | 14655.54 | 7197.50 | 6404.89 | -2194.61 | 88.73 | 460.20 | 202.95 | 257.25 | 2.29 | PASS |
| 15120.50† | 7536.54 | 6497.97 | -2503.11 | 14755.41 | 7197.50 | 6504.74 | -2196.81 | 88.73 | 456.96 | 204.98 | 251.98 | 2.25 | PASS |
| 15220.50† | 7536.64 | 6597.93 | -2500.40 | 14855.29 | 7197.50 | 6604.60 | -2199.02 | 88.73 | 453.75 | 206.98 | 246.77 | 2.22 | PASS |
| 15320.50† | 7536.74 | 6697.90 | -2497.68 | 14955.17 | 7197.50 | 6704.45 | -2201.23 | 88.73 | 450.57 | 208.93 | 241.64 | 2.18 | PASS |
| 15420.50† | 7536.85 | 6797.86 | -2494.96 | 15055.05 | 7197.50 | 6804.30 | -2203.44 | 88.73 | 447.42 | 210.84 | 236.58 | 2.14 | PASS |
| 15520.50† | 7536.95 | 6897.82 | -2492.24 | 15154.93 | 7197.50 | 6904.16 | -2205.64 | 88.73 | 444.30 | 212.71 | 231.59 | 2.11 | PASS |
| 15620.50† | 7537.05 | 6997.79 | -2489.52 | 15254.81 | 7197.50 | 7004.01 | -2207.85 | 88.73 | 441.22 | 214.54 | 226.68 | 2.08 | PASS |
| 15720.50† | 7537.16 | 7097.75 | -2486.80 | 15354.69 | 7197.50 | 7103.87 | -2210.06 | 88.73 | 438.17 | 216.33 | 221.84 | 2.04 | PASS |
| 15820.50† | 7537.26 | 7197.71 | -2484.08 | 15454.56 | 7197.50 | 7203.72 | -2212.26 | 88.73 | 435.15 | 218.07 | 217.08 | 2.01 | PASS |
| 15920.50† | 7537.36 | 7297.68 | -2481.36 | 15554.44 | 7197.50 | 7303.58 | -2214.47 | 88.73 | 432.17 | 219.77 | 212.40 | 1.98 | PASS |
| 16020.50† | 7537.47 | 7397.64 | -2478.64 | 15654.32 | 7197.50 | 7403.43 | -2216.68 | 88.73 | 429.23 | 221.43 | 207.80 | 1.96 | PASS |
| 16120.50† | 7537.57 | 7497.60 | -2475.93 | 15754.20 | 7197.50 | 7503.28 | -2218.89 | 88.73 | 426.32 | 223.04 | 203.28 | 1.93 | PASS |
| 16220.50† | 7537.68 | 7597.56 | -2473.21 | 15854.08 | 7197.50 | 7603.14 | -2221.09 | 88.73 | 423.45 | 224.61 | 198.85 | 1.90 | PASS |
| 16320.50† | 7537.78 | 7697.53 | -2470.49 | 15953.96 | 7197.50 | 7702.99 | -2223.30 | 88.73 | 420.62 | 226.13 | 194.49 | 1.88 | PASS |
| 16420.50† | 7537.88 | 7797.49 | -2467.77 | 16053.84 | 7197.50 | 7802.85 | -2225.51 | 88.73 | 417.83 | 227.61 | 190.22 | 1.85 | PASS |
| 16520.50† | 7537.99 | 7897.45 | -2465.05 | 16153.71 | 7197.50 | 7902.70 | -2227.72 | 88.73 | 415.07 | 229.04 | 186.03 | 1.83 | PASS |
| 16620.50† | 7538.09 | 7997.42 | -2462.33 | 16253.59 | 7197.50 | 8002.55 | -2229.92 | 88.73 | 412.36 | 230.43 | 181.93 | 1.80 | PASS |
| 16720.50† | 7538.19 | 8097.38 | -2459.61 | 16353.47 | 7197.50 | 8102.41 | -2232.13 | 88.73 | 409.69 | 231.77 | 177.92 | 1.78 | PASS |
| 16820.50† | 7538.30 | 8197.34 | -2456.89 | 16453.35 | 7197.50 | 8202.26 | -2234.34 | 88.73 | 407.06 | 233.07 | 173.99 | 1.76 | PASS |
| 16920.50† | 7538.40 | 8297.31 | -2454.17 | 16553.23 | 7197.50 | 8302.12 | -2236.54 | 88.73 | 404.47 | 234.32 | 170.15 | 1.74 | PASS |
| 17020.50† | 7538.50 | 8397.27 | -2451.46 | 16653.11 | 7197.50 | 8401.97 | -2238.75 | 88.73 | 401.93 | 235.54 | 166.39 | 1.72 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 46 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-3-1L PWB Offset Wellpath: BUFORD 33-3-1L (REV-B.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#07 BUFORD 33-3-1L (770'FSL & 894'FWL, SEC.34) Well: BUFORD 33-3-1L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 17120.50† | 7538.61 | 8497.23 | -2448.74 | 16752.98 | 7197.50 | 8501.82 | -2240.96 | 88.73 | 399.43 | 236.70 | 162.73 | 1.70 | PASS |
| 17220.50† | 7538.71 | 8597.19 | -2446.02 | 16852.86 | 7197.50 | 8601.68 | -2243.17 | 88.73 | 396.98 | 237.82 | 159.16 | 1.68 | PASS |
| 17320.50† | 7538.81 | 8697.16 | -2443.30 | 16952.74 | 7197.50 | 8701.53 | -2245.37 | 88.73 | 394.57 | 238.91 | 155.66 | 1.66 | PASS |
| 17420.50† | 7538.92 | 8797.12 | -2440.58 | 17052.62 | 7197.50 | 8801.39 | -2247.58 | 88.73 | 392.21 | 239.96 | 152.25 | 1.65 | PASS |
| 17520.50† | 7539.02 | 8897.08 | -2437.86 | 17152.50 | 7197.50 | 8901.24 | -2249.79 | 88.73 | 389.90 | 240.97 | 148.94 | 1.63 | PASS |
| 17620.50† | 7539.12 | 8997.05 | -2435.14 | 17252.38 | 7197.50 | 9001.09 | -2252.00 | 88.73 | 387.64 | 241.93 | 145.71 | 1.61 | PASS |
| 17720.50† | 7539.23 | 9097.01 | -2432.42 | 17352.26 | 7197.50 | 9100.95 | -2254.20 | 88.73 | 385.43 | 242.87 | 142.56 | 1.60 | PASS |
| 17820.50† | 7539.33 | 9196.97 | -2429.70 | 17452.13 | 7197.50 | 9200.80 | -2256.41 | 88.73 | 383.27 | 243.77 | 139.50 | 1.58 | PASS |
| 17920.50† | 7539.43 | 9296.94 | -2426.99 | 17552.01 | 7197.50 | 9300.66 | -2258.62 | 88.73 | 381.16 | 244.64 | 136.52 | 1.57 | PASS |
| 17985.90 | 7539.50 | 9362.31 | -2425.21 | 17613.66 | 7197.50 | 9362.29 | -2259.98 | 90.01 | 379.82 | 244.64 | 135.18 | 1.56 | PASS |

POSITIONAL UNCERTAINTY - Offset Wellbore: BUFORD 33-3-1L PWB Offset Wellpath: BUFORD 33-3-1L (REV-B.0) PWP

| | | | | |
|-----------------------------------|------------|---------|----------|---------|
| Slot Surface Uncertainty @1SD | Horizontal | 0.100ft | Vertical | 1.000ft |
| Facility Surface Uncertainty @1SD | Horizontal | 8.200ft | Vertical | 3.000ft |

SURVEY PROGRAM - Offset Wellbore: BUFORD 33-3-1L PWB Offset Wellpath: BUFORD 33-3-1L (REV-B.0) PWP

| Start MD [ft] | End MD [ft] | Positional Uncertainty Model | Log Name/Comment | Wellbore |
|---------------|-------------|---|------------------|--------------------|
| 20.50 | 1500.00 | BH NaviTrak (2019) (Standard) | | BUFORD 33-3-1L PWB |
| 1500.00 | 17678.76 | BH AutoTrak Curve/eXpress (2019) (Standard) | | BUFORD 33-3-1L PWB |

OFFSET WELLPATH REFERENCE - Offset Wellbore: BUFORD 33-3-1L PWB Offset Wellpath: BUFORD 33-3-1L (REV-B.0) PWP

| | |
|---------------------------------|---|
| MD Reference: RIG (20.5') (RKB) | Offset TVD & local coordinates use Reference Wellpath settings (See WELLPATH DATUM on page 1 of this report) |
| Ellipse Start MD | 20.50ft |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 47 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-3-3L PWB Offset Wellpath: BUFORD 33-3-3L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#06 BUFORD 33-3-3L (770'FSL & 869'FWL, SEC.34) Well: BUFORD 33-3-3L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 20.50 | 20.50 | 0.00 | 0.00 | 21.50 | 20.50 | 0.00 | 50.43 | 90.00 | 50.43 | 9.75 | 40.68 | 8.06 | PASS |
| 120.50† | 120.50 | 0.00 | 0.00 | 121.50 | 120.50 | 0.00 | 50.43 | 90.00 | 50.43 | 9.82 | 40.61 | 7.96 | PASS |
| 200.00 | 200.00 | 0.00 | 0.00 | 201.02 | 200.02 | 0.00 | 50.43 | 90.00 | 50.43 | 9.96 | 40.46 | 7.77 | PASS |
| 220.50† | 220.50 | -0.03 | -0.07 | 221.85 | 220.85 | -0.04 | 50.35 | 90.01 | 50.42 | 10.02 | 40.40 | 7.70 | PASS |
| 285.17† | 285.16 | -0.47 | -1.18 | 287.56 | 286.55 | -0.57 | 49.22 | 90.12 | 50.41 | 10.30 | 40.11 | 7.35 | PASS |
| 320.50† | 320.46 | -0.93 | -2.36 | 323.46 | 322.43 | -1.14 | 48.02 | 90.23 | 50.42 | 10.49 | 39.92 | 7.14 | PASS |
| 420.50† | 420.28 | -3.13 | -7.88 | 425.07 | 423.84 | -3.77 | 42.44 | 90.74 | 50.45 | 11.40 | 39.05 | 6.26 | PASS |
| 520.50† | 519.83 | -6.60 | -16.65 | 526.68 | 524.97 | -7.94 | 33.60 | 91.53 | 50.53 | 12.31 | 38.22 | 5.59 | PASS |
| 620.50† | 618.99 | -11.36 | -28.64 | 628.27 | 625.68 | -13.64 | 21.53 | 92.61 | 50.66 | 13.18 | 37.48 | 5.08 | PASS |
| 720.50† | 717.64 | -17.38 | -43.83 | 729.85 | 725.84 | -20.86 | 6.24 | 93.97 | 50.86 | 14.10 | 36.76 | 4.63 | PASS |
| 820.50† | 815.66 | -24.68 | -62.22 | 831.42 | 825.32 | -29.59 | -12.24 | 95.61 | 51.14 | 15.00 | 36.14 | 4.28 | PASS |
| 920.50† | 912.93 | -33.22 | -83.78 | 932.96 | 923.99 | -39.81 | -33.90 | 97.52 | 51.51 | 15.93 | 35.59 | 3.98 | PASS |
| 1020.50† | 1009.33 | -43.02 | -108.48 | 1034.49 | 1021.74 | -51.52 | -58.70 | 99.69 | 52.00 | 16.88 | 35.12 | 3.72 | PASS |
| 1120.50† | 1104.74 | -54.05 | -136.29 | 1135.79 | 1118.24 | -64.66 | -86.53 | 102.04 | 52.64 | 17.87 | 34.76 | 3.50 | PASS |
| 1220.50† | 1199.05 | -66.30 | -167.18 | 1235.75 | 1213.07 | -78.16 | -115.14 | 102.84 | 55.18 | 18.91 | 36.27 | 3.43 | PASS |
| 1242.54 | 1219.68 | -69.16 | -174.40 | 1257.76 | 1233.95 | -81.14 | -121.44 | 102.75 | 56.14 | 19.16 | 36.98 | 3.44 | PASS |
| 1320.50† | 1292.54 | -79.39 | -200.20 | 1335.64 | 1307.82 | -91.66 | -143.73 | 102.26 | 59.77 | 19.91 | 39.86 | 3.50 | PASS |
| 1420.50† | 1385.99 | -92.51 | -233.28 | 1435.53 | 1402.58 | -105.16 | -172.32 | 101.72 | 64.43 | 20.88 | 43.55 | 3.58 | PASS |
| 1520.50† | 1479.44 | -105.63 | -266.37 | 1535.42 | 1497.33 | -118.65 | -200.91 | 101.25 | 69.10 | 21.50 | 47.60 | 3.72 | PASS |
| 1620.50† | 1572.89 | -118.75 | -299.46 | 1635.31 | 1592.09 | -132.15 | -229.50 | 100.84 | 73.77 | 21.81 | 51.95 | 3.91 | PASS |
| 1720.50† | 1666.34 | -131.87 | -332.54 | 1735.20 | 1686.84 | -145.65 | -258.09 | 100.48 | 78.44 | 22.20 | 56.24 | 4.09 | PASS |
| 1820.50† | 1759.79 | -144.99 | -365.63 | 1835.09 | 1781.60 | -159.14 | -286.68 | 100.16 | 83.12 | 22.66 | 60.45 | 4.24 | PASS |
| 1920.50† | 1853.24 | -158.12 | -398.72 | 1934.98 | 1876.35 | -172.64 | -315.27 | 99.87 | 87.80 | 23.19 | 64.61 | 4.36 | PASS |
| 2020.50† | 1946.69 | -171.24 | -431.80 | 2034.87 | 1971.10 | -186.14 | -343.86 | 99.62 | 92.48 | 23.78 | 68.70 | 4.47 | PASS |
| 2120.50† | 2040.14 | -184.36 | -464.89 | 2134.76 | 2065.86 | -199.63 | -372.45 | 99.38 | 97.16 | 24.42 | 72.73 | 4.56 | PASS |
| 2220.50† | 2133.59 | -197.48 | -497.98 | 2234.65 | 2160.61 | -213.13 | -401.04 | 99.17 | 101.84 | 25.12 | 76.72 | 4.63 | PASS |
| 2320.50† | 2227.05 | -210.60 | -531.06 | 2334.54 | 2255.37 | -226.63 | -429.63 | 98.98 | 106.53 | 25.86 | 80.67 | 4.69 | PASS |
| 2420.50† | 2320.50 | -223.72 | -564.15 | 2434.43 | 2350.12 | -240.12 | -458.22 | 98.80 | 111.21 | 26.64 | 84.57 | 4.73 | PASS |
| 2520.50† | 2413.95 | -236.84 | -597.24 | 2534.32 | 2444.88 | -253.62 | -486.81 | 98.64 | 115.90 | 27.46 | 88.44 | 4.77 | PASS |
| 2620.50† | 2507.40 | -249.96 | -630.32 | 2634.21 | 2539.63 | -267.12 | -515.40 | 98.49 | 120.59 | 28.31 | 92.27 | 4.79 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 48 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-3-3L PWB Offset Wellpath: BUFORD 33-3-3L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#06 BUFORD 33-3-3L (770'FSL & 869'FWL, SEC.34) Well: BUFORD 33-3-3L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | |
| 2720.50† | 2600.85 | -263.08 | -663.41 | 2734.10 | 2634.39 | -280.61 | -543.99 | 98.35 | 125.28 | 29.20 | 96.08 | 4.81 | PASS | | |
| 2820.50† | 2694.30 | -276.20 | -696.50 | 2833.98 | 2729.14 | -294.11 | -572.58 | 98.22 | 129.96 | 30.11 | 99.86 | 4.82 | PASS | | |
| 2920.50† | 2787.75 | -289.33 | -729.58 | 2933.87 | 2823.89 | -307.61 | -601.17 | 98.10 | 134.65 | 31.04 | 103.61 | 4.83 | PASS | | |
| 3020.50† | 2881.20 | -302.45 | -762.67 | 3033.76 | 2918.65 | -321.10 | -629.76 | 97.99 | 139.34 | 32.00 | 107.35 | 4.83 | PASS | | |
| 3120.50† | 2974.65 | -315.57 | -795.76 | 3133.65 | 3013.40 | -334.60 | -658.34 | 97.89 | 144.04 | 32.97 | 111.06 | 4.83 | PASS | | |
| 3220.50† | 3068.11 | -328.69 | -828.84 | 3233.54 | 3108.16 | -348.10 | -686.93 | 97.79 | 148.73 | 33.96 | 114.76 | 4.83 | PASS | | |
| 3320.50† | 3161.56 | -341.81 | -861.93 | 3333.43 | 3202.91 | -361.59 | -715.52 | 97.70 | 153.42 | 34.97 | 118.45 | 4.82 | PASS | | |
| 3420.50† | 3255.01 | -354.93 | -895.02 | 3433.32 | 3297.67 | -375.09 | -744.11 | 97.61 | 158.11 | 36.00 | 122.11 | 4.81 | PASS | | |
| 3520.50† | 3348.46 | -368.05 | -928.10 | 3533.21 | 3392.42 | -388.59 | -772.70 | 97.53 | 162.80 | 37.03 | 125.77 | 4.81 | PASS | | |
| 3620.50† | 3441.91 | -381.17 | -961.19 | 3633.10 | 3487.18 | -402.08 | -801.29 | 97.45 | 167.49 | 38.08 | 129.41 | 4.80 | PASS | | |
| 3720.50† | 3535.36 | -394.29 | -994.28 | 3732.99 | 3581.93 | -415.58 | -829.88 | 97.38 | 172.19 | 39.14 | 133.05 | 4.78 | PASS | | |
| 3820.50† | 3628.81 | -407.41 | -1027.37 | 3832.88 | 3676.69 | -429.08 | -858.47 | 97.31 | 176.88 | 40.21 | 136.67 | 4.77 | PASS | | |
| 3920.50† | 3722.26 | -420.53 | -1060.45 | 3932.77 | 3771.44 | -442.57 | -887.06 | 97.24 | 181.57 | 41.29 | 140.29 | 4.76 | PASS | | |
| 4020.50† | 3815.71 | -433.66 | -1093.54 | 4032.66 | 3866.19 | -456.07 | -915.65 | 97.18 | 186.27 | 42.37 | 143.89 | 4.75 | PASS | | |
| 4120.50† | 3909.17 | -446.78 | -1126.63 | 4132.55 | 3960.95 | -469.57 | -944.24 | 97.12 | 190.96 | 43.47 | 147.49 | 4.74 | PASS | | |
| 4220.50† | 4002.62 | -459.90 | -1159.71 | 4232.44 | 4055.70 | -483.06 | -972.83 | 97.07 | 195.65 | 44.57 | 151.08 | 4.72 | PASS | | |
| 4320.50† | 4096.07 | -473.02 | -1192.80 | 4332.33 | 4150.46 | -496.56 | -1001.42 | 97.01 | 200.35 | 45.68 | 154.67 | 4.71 | PASS | | |
| 4420.50† | 4189.52 | -486.14 | -1225.89 | 4432.22 | 4245.21 | -510.06 | -1030.01 | 96.96 | 205.04 | 46.79 | 158.25 | 4.70 | PASS | | |
| 4520.50† | 4282.97 | -499.26 | -1258.97 | 4532.11 | 4339.97 | -523.55 | -1058.60 | 96.91 | 209.74 | 47.91 | 161.83 | 4.68 | PASS | | |
| 4620.50† | 4376.42 | -512.38 | -1292.06 | 4632.00 | 4434.72 | -537.05 | -1087.19 | 96.87 | 214.43 | 49.03 | 165.40 | 4.67 | PASS | | |
| 4720.50† | 4469.87 | -525.50 | -1325.15 | 4731.89 | 4529.48 | -550.55 | -1115.78 | 96.82 | 219.12 | 50.16 | 168.96 | 4.66 | PASS | | |
| 4820.50† | 4563.32 | -538.62 | -1358.23 | 4831.78 | 4624.23 | -564.05 | -1144.37 | 96.78 | 223.82 | 51.30 | 172.52 | 4.65 | PASS | | |
| 4920.50† | 4656.77 | -551.74 | -1391.32 | 4931.67 | 4718.98 | -577.54 | -1172.96 | 96.74 | 228.51 | 52.43 | 176.08 | 4.63 | PASS | | |
| 5020.50† | 4750.22 | -564.87 | -1424.41 | 5031.56 | 4813.74 | -591.04 | -1201.55 | 96.70 | 233.21 | 53.57 | 179.63 | 4.62 | PASS | | |
| 5120.50† | 4843.68 | -577.99 | -1457.49 | 5131.45 | 4908.49 | -604.54 | -1230.14 | 96.66 | 237.90 | 54.72 | 183.18 | 4.61 | PASS | | |
| 5220.50† | 4937.13 | -591.11 | -1490.58 | 5231.34 | 5003.25 | -618.03 | -1258.73 | 96.62 | 242.60 | 55.87 | 186.73 | 4.60 | PASS | | |
| 5320.50† | 5030.58 | -604.23 | -1523.67 | 5331.23 | 5098.00 | -631.53 | -1287.31 | 96.59 | 247.29 | 57.02 | 190.28 | 4.59 | PASS | | |
| 5420.50† | 5124.03 | -617.35 | -1556.75 | 5431.11 | 5192.76 | -645.03 | -1315.90 | 96.56 | 251.99 | 58.17 | 193.82 | 4.58 | PASS | | |
| 5520.50† | 5217.48 | -630.47 | -1589.84 | 5531.00 | 5287.51 | -658.52 | -1344.49 | 96.52 | 256.68 | 59.33 | 197.36 | 4.57 | PASS | | |
| 5620.50† | 5310.93 | -643.59 | -1622.93 | 5630.89 | 5382.27 | -672.02 | -1373.08 | 96.49 | 261.38 | 60.49 | 200.89 | 4.56 | PASS | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 49 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770°FSL & 819°FSL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-3-3L PWB Offset Wellpath: BUFORD 33-3-3L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#06 BUFORD 33-3-3L (770°FSL & 869°FWL,SEC.34) | | | | Well: BUFORD 33-3-3L | | | | Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | |
|--|-----------------|-------------------|------------------|----------------------|--------------------|----------------------|---------------------|---|---------------------------|----------------------|----------------------------|--------------|----------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 5720.50† | 5404.38 | -656.71 | -1656.01 | 5730.78 | 5477.02 | -685.52 | -1401.67 | 96.46 | 266.07 | 61.65 | 204.43 | 4.55 | PASS |
| 5820.50† | 5497.83 | -669.83 | -1689.10 | 5830.67 | 5571.77 | -699.01 | -1430.26 | 96.43 | 270.77 | 62.81 | 207.96 | 4.53 | PASS |
| 5920.50† | 5591.28 | -682.95 | -1722.19 | 5930.56 | 5666.53 | -712.51 | -1458.85 | 96.40 | 275.47 | 63.98 | 211.49 | 4.53 | PASS |
| 6020.50† | 5684.74 | -696.07 | -1755.27 | 6030.45 | 5761.28 | -726.01 | -1487.44 | 96.38 | 280.16 | 65.15 | 215.01 | 4.52 | PASS |
| 6120.50† | 5778.19 | -709.20 | -1788.36 | 6130.34 | 5856.04 | -739.50 | -1516.03 | 96.35 | 284.86 | 66.32 | 218.54 | 4.51 | PASS |
| 6220.50† | 5871.64 | -722.32 | -1821.45 | 6230.23 | 5950.79 | -753.00 | -1544.62 | 96.33 | 289.55 | 67.49 | 222.06 | 4.50 | PASS |
| 6320.50† | 5965.09 | -735.44 | -1854.54 | 6330.12 | 6045.55 | -766.50 | -1573.21 | 96.30 | 294.25 | 68.66 | 225.59 | 4.49 | PASS |
| 6420.50† | 6058.54 | -748.56 | -1887.62 | 6430.01 | 6140.30 | -779.99 | -1601.80 | 96.28 | 298.94 | 69.84 | 229.11 | 4.48 | PASS |
| 6520.50† | 6151.99 | -761.68 | -1920.71 | 6529.90 | 6235.06 | -793.49 | -1630.39 | 96.25 | 303.64 | 71.01 | 232.63 | 4.47 | PASS |
| 6620.50† | 6245.44 | -774.80 | -1953.80 | 6629.79 | 6329.81 | -806.99 | -1658.98 | 96.23 | 308.34 | 72.19 | 236.15 | 4.46 | PASS |
| 6720.50† | 6338.89 | -787.92 | -1986.88 | 6729.68 | 6424.57 | -820.48 | -1687.57 | 96.21 | 313.03 | 73.37 | 239.66 | 4.45 | PASS |
| 6820.50† | 6432.34 | -801.04 | -2019.97 | 6829.57 | 6519.32 | -833.98 | -1716.16 | 96.19 | 317.73 | 74.55 | 243.18 | 4.45 | PASS |
| 6920.50† | 6525.80 | -814.16 | -2053.06 | 6929.46 | 6614.07 | -847.48 | -1744.75 | 96.17 | 322.42 | 75.73 | 246.69 | 4.44 | PASS |
| 7020.50† | 6619.25 | -827.28 | -2086.14 | 7029.35 | 6708.83 | -860.97 | -1773.34 | 96.15 | 327.12 | 76.91 | 250.21 | 4.43 | PASS |
| 7120.50† | 6712.70 | -840.41 | -2119.23 | 7131.47 | 6805.83 | -873.55 | -1802.61 | 95.98 | 331.70 | 77.94 | 253.76 | 4.43 | PASS |
| 7220.50† | 6806.15 | -853.53 | -2152.32 | 7235.08 | 6904.86 | -887.15 | -1832.51 | 93.21 | 335.17 | 77.16 | 258.01 | 4.53 | PASS |
| 7320.50† | 6899.60 | -866.65 | -2185.40 | 7330.26 | 6994.16 | -893.15 | -1859.51 | 87.63 | 339.60 | 74.55 | 265.06 | 4.76 | PASS |
| 7341.07 | 6918.82 | -869.35 | -2192.21 | 7348.42 | 7010.80 | -847.91 | -1864.54 | 86.26 | 341.01 | 74.25 | 266.75 | 4.80 | PASS |
| 7420.50† | 6993.49 | -874.29 | -2218.65 | 7415.99 | 7071.13 | -823.64 | -1882.80 | 81.43 | 348.41 | 72.15 | 276.26 | 5.05 | PASS |
| 7520.50† | 7087.21 | -864.88 | -2251.87 | 7497.26 | 7139.43 | -784.90 | -1903.49 | 77.07 | 361.24 | 70.93 | 290.31 | 5.34 | PASS |
| 7620.50† | 7177.96 | -838.35 | -2284.05 | 7575.20 | 7199.37 | -738.63 | -1921.66 | 74.61 | 376.47 | 70.41 | 306.06 | 5.61 | PASS |
| 7720.50† | 7262.97 | -795.51 | -2314.23 | 7650.56 | 7251.09 | -686.20 | -1937.37 | 73.83 | 392.57 | 69.91 | 322.67 | 5.89 | PASS |
| 7820.50† | 7339.68 | -737.65 | -2341.49 | 7723.95 | 7294.72 | -628.75 | -1950.64 | 74.43 | 408.22 | 69.02 | 339.20 | 6.22 | PASS |
| 7920.50† | 7405.75 | -666.53 | -2364.99 | 7795.84 | 7330.29 | -567.29 | -1961.48 | 76.18 | 422.33 | 67.86 | 354.47 | 6.55 | PASS |
| 8020.50† | 7459.16 | -584.32 | -2384.03 | 7866.61 | 7357.84 | -502.69 | -1969.91 | 78.85 | 434.08 | 66.69 | 367.39 | 6.86 | PASS |
| 8120.50† | 7498.30 | -493.50 | -2398.02 | 7936.59 | 7377.39 | -435.81 | -1975.92 | 82.22 | 442.85 | 65.78 | 377.07 | 7.10 | PASS |
| 8220.50† | 7521.99 | -396.85 | -2406.55 | 8006.07 | 7388.94 | -367.44 | -1979.52 | 86.06 | 448.24 | 65.38 | 382.86 | 7.24 | PASS |
| 8315.56 | 7529.50 | -302.24 | -2409.34 | 8072.12 | 7392.50 | -301.53 | -1980.70 | 89.91 | 450.00 | 65.55 | 384.45 | 7.24 | PASS |
| 8320.50† | 7529.51 | -297.30 | -2409.35 | 8077.06 | 7392.50 | -296.59 | -1980.71 | 89.91 | 450.00 | 65.52 | 384.48 | 7.25 | PASS |
| 8420.50† | 7529.61 | -197.30 | -2409.53 | 8177.06 | 7392.50 | -196.59 | -1980.88 | 89.91 | 450.04 | 64.84 | 385.21 | 7.33 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 50 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-3-3L PWB Offset Wellpath: BUFORD 33-3-3L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#06 BUFORD 33-3-3L (770'FSL & 869'FWL,SEC.34) Well: BUFORD 33-3-3L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|-----------------|-------------------|------------------|-------------------|--------------------|----------------------|---------------------|-------------------------|---------------------------|----------------------|----------------------------|--------------|----------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 8520.50† | 7529.71 | -97.30 | -2409.71 | 8277.06 | 7392.50 | -96.59 | -1981.04 | 89.91 | 450.09 | 65.22 | 384.87 | 7.29 | PASS |
| 8620.50† | 7529.82 | 2.70 | -2409.88 | 8377.06 | 7392.50 | 3.41 | -1981.21 | 89.91 | 450.13 | 64.37 | 385.77 | 7.39 | PASS |
| 8720.50† | 7529.92 | 102.70 | -2410.06 | 8477.06 | 7392.50 | 103.41 | -1981.38 | 89.91 | 450.17 | 64.49 | 385.69 | 7.37 | PASS |
| 8820.50† | 7530.02 | 202.70 | -2410.24 | 8577.06 | 7392.50 | 203.41 | -1981.54 | 89.91 | 450.22 | 64.84 | 385.37 | 7.33 | PASS |
| 8920.50† | 7530.13 | 302.70 | -2410.42 | 8677.06 | 7392.50 | 303.41 | -1981.71 | 89.91 | 450.26 | 65.42 | 384.83 | 7.26 | PASS |
| 9020.50† | 7530.23 | 402.70 | -2410.59 | 8777.06 | 7392.50 | 403.41 | -1981.87 | 89.91 | 450.30 | 66.23 | 384.07 | 7.17 | PASS |
| 9120.50† | 7530.33 | 502.70 | -2410.77 | 8877.06 | 7392.50 | 503.41 | -1982.04 | 89.91 | 450.34 | 67.25 | 383.10 | 7.06 | PASS |
| 9220.50† | 7530.44 | 602.70 | -2410.95 | 8977.06 | 7392.50 | 603.41 | -1982.21 | 89.91 | 450.39 | 68.47 | 381.92 | 6.92 | PASS |
| 9320.50† | 7530.54 | 702.70 | -2411.13 | 9077.06 | 7392.50 | 703.41 | -1982.37 | 89.91 | 450.43 | 69.89 | 380.54 | 6.77 | PASS |
| 9420.50† | 7530.64 | 802.69 | -2411.31 | 9177.06 | 7392.50 | 803.41 | -1982.54 | 89.91 | 450.47 | 71.48 | 378.99 | 6.61 | PASS |
| 9520.50† | 7530.75 | 902.69 | -2411.48 | 9277.06 | 7392.50 | 903.41 | -1982.70 | 89.91 | 450.52 | 73.24 | 377.27 | 6.45 | PASS |
| 9620.50† | 7530.85 | 1002.69 | -2411.66 | 9377.06 | 7392.50 | 1003.41 | -1982.87 | 89.91 | 450.56 | 75.16 | 375.40 | 6.27 | PASS |
| 9720.50† | 7530.96 | 1102.69 | -2411.84 | 9477.06 | 7392.50 | 1103.41 | -1983.03 | 89.91 | 450.60 | 77.22 | 373.38 | 6.10 | PASS |
| 9820.50† | 7531.06 | 1202.69 | -2412.02 | 9577.06 | 7392.50 | 1203.41 | -1983.20 | 89.91 | 450.65 | 79.41 | 371.23 | 5.92 | PASS |
| 9920.50† | 7531.16 | 1302.69 | -2412.19 | 9677.06 | 7392.50 | 1303.40 | -1983.37 | 89.91 | 450.69 | 81.72 | 368.96 | 5.75 | PASS |
| 10020.50† | 7531.27 | 1402.69 | -2412.37 | 9777.06 | 7392.50 | 1403.40 | -1983.53 | 89.91 | 450.73 | 84.15 | 366.59 | 5.57 | PASS |
| 10120.50† | 7531.37 | 1502.69 | -2412.55 | 9877.06 | 7392.50 | 1503.40 | -1983.70 | 89.91 | 450.78 | 86.67 | 364.11 | 5.40 | PASS |
| 10220.50† | 7531.47 | 1602.69 | -2412.73 | 9977.06 | 7392.50 | 1603.40 | -1983.86 | 89.91 | 450.82 | 89.28 | 361.54 | 5.24 | PASS |
| 10320.50† | 7531.58 | 1702.69 | -2412.90 | 10077.06 | 7392.50 | 1703.40 | -1984.03 | 89.91 | 450.86 | 91.97 | 358.89 | 5.08 | PASS |
| 10420.50† | 7531.68 | 1802.69 | -2413.08 | 10177.06 | 7392.50 | 1803.40 | -1984.20 | 89.91 | 450.91 | 94.74 | 356.16 | 4.92 | PASS |
| 10520.50† | 7531.78 | 1902.69 | -2413.26 | 10277.06 | 7392.50 | 1903.40 | -1984.36 | 89.91 | 450.95 | 97.58 | 353.37 | 4.78 | PASS |
| 10620.50† | 7531.89 | 2002.69 | -2413.44 | 10377.06 | 7392.50 | 2003.40 | -1984.53 | 89.91 | 450.99 | 100.48 | 350.51 | 4.63 | PASS |
| 10720.50† | 7531.99 | 2102.69 | -2413.62 | 10477.06 | 7392.50 | 2103.40 | -1984.69 | 89.91 | 451.04 | 103.44 | 347.60 | 4.49 | PASS |
| 10820.50† | 7532.09 | 2202.69 | -2413.79 | 10577.06 | 7392.50 | 2203.40 | -1984.86 | 89.91 | 451.08 | 106.45 | 344.63 | 4.36 | PASS |
| 10920.50† | 7532.20 | 2302.69 | -2413.97 | 10677.06 | 7392.50 | 2303.40 | -1985.02 | 89.91 | 451.12 | 109.51 | 341.61 | 4.24 | PASS |
| 11020.50† | 7532.30 | 2402.69 | -2414.15 | 10777.06 | 7392.50 | 2403.40 | -1985.19 | 89.91 | 451.17 | 112.61 | 338.56 | 4.12 | PASS |
| 11120.50† | 7532.41 | 2502.69 | -2414.33 | 10877.06 | 7392.50 | 2503.40 | -1985.36 | 89.91 | 451.21 | 115.75 | 335.46 | 4.00 | PASS |
| 11220.50† | 7532.51 | 2602.69 | -2414.50 | 10977.06 | 7392.50 | 2603.40 | -1985.52 | 89.91 | 451.25 | 118.93 | 332.33 | 3.89 | PASS |
| 11320.50† | 7532.61 | 2702.69 | -2414.68 | 11077.06 | 7392.50 | 2703.40 | -1985.69 | 89.91 | 451.30 | 122.14 | 329.16 | 3.79 | PASS |
| 11420.50† | 7532.72 | 2802.69 | -2414.86 | 11177.06 | 7392.50 | 2803.40 | -1985.85 | 89.91 | 451.34 | 125.38 | 325.96 | 3.69 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 51 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770°FSL & 819°FSL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-3-3L PWB Offset Wellpath: BUFORD 33-3-3L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W | | Slot: SLOT#06 BUFORD 33-3-3L (770°FSL & 869°FSL, SEC.34) | | Well: BUFORD 33-3-3L | | Threshold Value=1.00 | | † = interpolated, ‡ = extrapolated station | | | | | |
|----------------------------|-----------------|--|------------------|----------------------|--------------------|----------------------|---------------------|--|---------------------------|----------------------|----------------------------|--------------|----------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 11520.50† | 7532.82 | 2902.69 | -2415.04 | 11277.06 | 7392.50 | 2903.40 | -1986.02 | 89.91 | 451.38 | 128.65 | 322.73 | 3.59 | PASS |
| 11620.50† | 7532.92 | 3002.69 | -2415.21 | 11377.06 | 7392.50 | 3003.40 | -1986.19 | 89.91 | 451.43 | 131.95 | 319.48 | 3.50 | PASS |
| 11720.50† | 7533.03 | 3102.69 | -2415.39 | 11477.06 | 7392.50 | 3103.40 | -1986.35 | 89.91 | 451.47 | 135.27 | 316.20 | 3.41 | PASS |
| 11820.50† | 7533.13 | 3202.69 | -2415.57 | 11577.06 | 7392.50 | 3203.40 | -1986.52 | 89.91 | 451.51 | 138.61 | 312.90 | 3.32 | PASS |
| 11920.50† | 7533.23 | 3302.69 | -2415.75 | 11677.06 | 7392.50 | 3303.40 | -1986.68 | 89.91 | 451.56 | 141.97 | 309.58 | 3.24 | PASS |
| 12020.50† | 7533.34 | 3402.69 | -2415.92 | 11777.06 | 7392.50 | 3403.40 | -1986.85 | 89.91 | 451.60 | 145.35 | 306.24 | 3.17 | PASS |
| 12120.50† | 7533.44 | 3502.69 | -2416.10 | 11877.06 | 7392.50 | 3503.40 | -1987.01 | 89.91 | 451.64 | 148.76 | 302.89 | 3.09 | PASS |
| 12220.50† | 7533.55 | 3602.69 | -2416.28 | 11977.06 | 7392.50 | 3603.40 | -1987.18 | 89.91 | 451.69 | 152.17 | 299.51 | 3.02 | PASS |
| 12320.50† | 7533.65 | 3702.69 | -2416.46 | 12077.06 | 7392.50 | 3703.40 | -1987.35 | 89.91 | 451.73 | 155.60 | 296.13 | 2.95 | PASS |
| 12420.50† | 7533.75 | 3802.69 | -2416.64 | 12177.06 | 7392.50 | 3803.40 | -1987.51 | 89.91 | 451.77 | 159.05 | 292.72 | 2.89 | PASS |
| 12520.50† | 7533.86 | 3902.69 | -2416.81 | 12277.06 | 7392.50 | 3903.40 | -1987.68 | 89.91 | 451.82 | 162.51 | 289.31 | 2.82 | PASS |
| 12620.50† | 7533.96 | 4002.69 | -2416.99 | 12377.06 | 7392.50 | 4003.40 | -1987.84 | 89.91 | 451.86 | 165.98 | 285.88 | 2.76 | PASS |
| 12720.50† | 7534.06 | 4102.69 | -2417.17 | 12477.06 | 7392.50 | 4103.40 | -1988.01 | 89.91 | 451.90 | 169.47 | 282.44 | 2.71 | PASS |
| 12820.50† | 7534.17 | 4202.69 | -2417.35 | 12577.06 | 7392.50 | 4203.40 | -1988.18 | 89.91 | 451.95 | 172.96 | 278.98 | 2.65 | PASS |
| 12920.50† | 7534.27 | 4302.69 | -2417.52 | 12677.06 | 7392.50 | 4303.40 | -1988.34 | 89.91 | 451.99 | 176.47 | 275.52 | 2.60 | PASS |
| 13020.50† | 7534.37 | 4402.69 | -2417.70 | 12777.06 | 7392.50 | 4403.40 | -1988.51 | 89.91 | 452.04 | 179.98 | 272.05 | 2.55 | PASS |
| 13120.50† | 7534.48 | 4502.69 | -2417.88 | 12877.06 | 7392.50 | 4503.40 | -1988.67 | 89.91 | 452.08 | 183.51 | 268.57 | 2.50 | PASS |
| 13199.97 | 7534.56 | 4582.16 | -2418.02 | 12956.53 | 7392.50 | 4582.87 | -1988.80 | 89.91 | 452.11 | 186.31 | 265.80 | 2.46 | PASS |
| 13220.50† | 7534.58 | 4602.69 | -2418.13 | 12977.06 | 7392.50 | 4603.40 | -1988.84 | 89.91 | 452.19 | 187.04 | 265.16 | 2.45 | PASS |
| 13320.50† | 7534.68 | 4702.65 | -2420.77 | 13077.02 | 7392.50 | 4703.36 | -1989.00 | 89.91 | 454.57 | 190.67 | 263.91 | 2.41 | PASS |
| 13420.50† | 7534.79 | 4802.45 | -2426.90 | 13176.84 | 7392.50 | 4803.18 | -1989.17 | 89.91 | 460.27 | 194.48 | 265.79 | 2.40 | PASS |
| 13476.50 | 7534.85 | 4858.23 | -2431.85 | 13232.63 | 7392.50 | 4858.97 | -1989.26 | 89.91 | 464.91 | 196.67 | 268.24 | 2.39 | PASS |
| 13520.50† | 7534.89 | 4902.02 | -2436.16 | 13276.42 | 7392.50 | 4902.76 | -1989.33 | 89.91 | 468.97 | 198.40 | 270.56 | 2.39 | PASS |
| 13620.50† | 7534.99 | 5001.54 | -2445.98 | 13375.96 | 7392.50 | 5002.30 | -1989.50 | 89.91 | 478.20 | 202.36 | 275.85 | 2.39 | PASS |
| 13720.50† | 7535.10 | 5101.06 | -2455.79 | 13475.49 | 7392.50 | 5101.83 | -1989.66 | 89.91 | 487.45 | 206.32 | 281.13 | 2.39 | PASS |
| 13820.50† | 7535.20 | 5200.57 | -2465.61 | 13575.02 | 7392.50 | 5201.36 | -1989.83 | 89.91 | 496.72 | 210.28 | 286.44 | 2.39 | PASS |
| 13920.50† | 7535.30 | 5300.09 | -2475.42 | 13674.56 | 7392.50 | 5300.89 | -1989.99 | 89.91 | 506.00 | 214.24 | 291.76 | 2.39 | PASS |
| 14020.50† | 7535.40 | 5399.61 | -2485.24 | 13774.09 | 7392.50 | 5400.43 | -1990.16 | 89.91 | 515.29 | 218.20 | 297.09 | 2.39 | PASS |
| 14120.50† | 7535.51 | 5499.12 | -2495.05 | 13873.62 | 7392.50 | 5499.96 | -1990.33 | 89.91 | 524.60 | 222.16 | 302.44 | 2.39 | PASS |
| 14220.50† | 7535.61 | 5598.64 | -2504.87 | 13973.16 | 7392.50 | 5599.49 | -1990.49 | 89.91 | 533.91 | 226.12 | 307.80 | 2.39 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 52 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770°FSL & 819°FSL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-3-3L PWB Offset Wellpath: BUFORD 33-3-3L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#06 BUFORD 33-3-3L (770°FSL & 869°FWL,SEC.34) Well: BUFORD 33-3-3L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|-----------------|-------------------|------------------|-------------------|--------------------|----------------------|---------------------|-------------------------|---------------------------|----------------------|----------------------------|--------------|----------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 14221.87 | 7535.61 | 5600.00 | -2505.00 | 13974.51 | 7392.50 | 5600.85 | -1990.49 | 89.91 | 534.04 | 226.17 | 307.87 | 2.39 | PASS |
| 14320.50† | 7535.71 | 5698.31 | -2512.99 | 14072.83 | 7392.50 | 5699.17 | -1990.66 | 89.91 | 541.61 | 230.01 | 311.61 | 2.38 | PASS |
| 14420.50† | 7535.81 | 5798.19 | -2517.63 | 14172.73 | 7392.50 | 5799.07 | -1990.82 | 89.91 | 545.95 | 233.81 | 312.14 | 2.36 | PASS |
| 14520.50† | 7535.92 | 5898.18 | -2518.78 | 14272.72 | 7392.50 | 5899.06 | -1990.99 | 89.91 | 546.93 | 237.51 | 309.43 | 2.33 | PASS |
| 14581.38 | 7535.98 | 5959.05 | -2517.77 | 14333.59 | 7392.50 | 5959.93 | -1991.09 | 89.91 | 545.88 | 239.69 | 306.18 | 2.30 | PASS |
| 14620.50† | 7536.02 | 5998.16 | -2516.71 | 14372.69 | 7392.50 | 5999.03 | -1991.15 | 89.91 | 544.80 | 241.08 | 303.72 | 2.28 | PASS |
| 14720.50† | 7536.12 | 6098.12 | -2513.99 | 14472.65 | 7392.50 | 6098.99 | -1991.32 | 89.91 | 542.05 | 244.62 | 297.42 | 2.24 | PASS |
| 14820.50† | 7536.23 | 6198.08 | -2511.27 | 14572.61 | 7392.50 | 6198.94 | -1991.48 | 89.91 | 539.29 | 248.18 | 291.11 | 2.19 | PASS |
| 14920.50† | 7536.33 | 6298.05 | -2508.55 | 14672.57 | 7392.50 | 6298.90 | -1991.65 | 89.91 | 536.54 | 251.71 | 284.83 | 2.15 | PASS |
| 15020.50† | 7536.43 | 6398.01 | -2505.83 | 14772.52 | 7392.50 | 6398.86 | -1991.82 | 89.91 | 533.79 | 255.30 | 278.49 | 2.11 | PASS |
| 15120.50† | 7536.54 | 6497.97 | -2503.11 | 14872.48 | 7392.50 | 6498.82 | -1991.98 | 89.91 | 531.04 | 258.86 | 272.18 | 2.07 | PASS |
| 15220.50† | 7536.64 | 6597.93 | -2500.40 | 14972.44 | 7392.50 | 6598.78 | -1992.15 | 89.91 | 528.29 | 262.41 | 265.88 | 2.03 | PASS |
| 15320.50† | 7536.74 | 6697.90 | -2497.68 | 15072.40 | 7392.50 | 6698.74 | -1992.31 | 89.91 | 525.55 | 265.97 | 259.58 | 1.99 | PASS |
| 15420.50† | 7536.85 | 6797.86 | -2494.96 | 15172.36 | 7392.50 | 6798.69 | -1992.48 | 89.91 | 522.80 | 269.53 | 253.28 | 1.95 | PASS |
| 15520.50† | 7536.95 | 6897.82 | -2492.24 | 15272.32 | 7392.50 | 6898.65 | -1992.64 | 89.91 | 520.06 | 273.08 | 246.98 | 1.92 | PASS |
| 15620.50† | 7537.05 | 6997.79 | -2489.52 | 15372.27 | 7392.50 | 6998.61 | -1992.81 | 89.91 | 517.32 | 276.63 | 240.69 | 1.88 | PASS |
| 15720.50† | 7537.16 | 7097.75 | -2486.80 | 15472.23 | 7392.50 | 7098.57 | -1992.98 | 89.91 | 514.58 | 280.18 | 234.40 | 1.85 | PASS |
| 15820.50† | 7537.26 | 7197.71 | -2484.08 | 15572.19 | 7392.50 | 7198.53 | -1993.14 | 89.91 | 511.84 | 283.73 | 228.11 | 1.82 | PASS |
| 15920.50† | 7537.36 | 7297.68 | -2481.36 | 15672.15 | 7392.50 | 7298.48 | -1993.31 | 89.91 | 509.10 | 287.28 | 221.83 | 1.78 | PASS |
| 16020.50† | 7537.47 | 7397.64 | -2478.64 | 15772.11 | 7392.50 | 7398.44 | -1993.47 | 89.91 | 506.37 | 290.82 | 215.55 | 1.75 | PASS |
| 16120.50† | 7537.57 | 7497.60 | -2475.93 | 15872.07 | 7392.50 | 7498.40 | -1993.64 | 89.91 | 503.63 | 294.36 | 209.27 | 1.72 | PASS |
| 16220.50† | 7537.68 | 7597.56 | -2473.21 | 15972.02 | 7392.50 | 7598.36 | -1993.80 | 89.91 | 500.90 | 297.90 | 203.00 | 1.69 | PASS |
| 16320.50† | 7537.78 | 7697.53 | -2470.49 | 16071.98 | 7392.50 | 7698.32 | -1993.97 | 89.91 | 498.17 | 301.44 | 196.74 | 1.66 | PASS |
| 16420.50† | 7537.88 | 7797.49 | -2467.77 | 16171.94 | 7392.50 | 7798.28 | -1994.14 | 89.91 | 495.44 | 304.97 | 190.47 | 1.63 | PASS |
| 16520.50† | 7537.99 | 7897.45 | -2465.05 | 16271.90 | 7392.50 | 7898.23 | -1994.30 | 89.91 | 492.72 | 308.50 | 184.22 | 1.60 | PASS |
| 16620.50† | 7538.09 | 7997.42 | -2462.33 | 16371.86 | 7392.50 | 7998.19 | -1994.47 | 89.91 | 489.99 | 312.02 | 177.97 | 1.58 | PASS |
| 16720.50† | 7538.19 | 8097.38 | -2459.61 | 16471.82 | 7392.50 | 8098.15 | -1994.63 | 89.91 | 487.27 | 315.55 | 171.72 | 1.55 | PASS |
| 16820.50† | 7538.30 | 8197.34 | -2456.89 | 16571.77 | 7392.50 | 8198.11 | -1994.80 | 89.91 | 484.55 | 319.06 | 165.49 | 1.53 | PASS |
| 16920.50† | 7538.40 | 8297.31 | -2454.17 | 16671.73 | 7392.50 | 8298.07 | -1994.96 | 89.91 | 481.83 | 322.58 | 159.25 | 1.50 | PASS |
| 17020.50† | 7538.50 | 8397.27 | -2451.46 | 16771.69 | 7392.50 | 8398.03 | -1995.13 | 89.91 | 479.11 | 326.08 | 153.03 | 1.48 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 53 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-3-3L PWB Offset Wellpath: BUFORD 33-3-3L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#06 BUFORD 33-3-3L (770'FSL & 869'FWL, SEC.34) Well: BUFORD 33-3-3L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 17120.50† | 7538.61 | 8497.23 | -2448.74 | 16871.65 | 7392.50 | 8497.98 | -1995.30 | 89.91 | 476.40 | 329.59 | 146.81 | 1.45 | PASS |
| 17220.50† | 7538.71 | 8597.19 | -2446.02 | 16971.61 | 7392.50 | 8597.94 | -1995.46 | 89.91 | 473.69 | 333.09 | 140.60 | 1.43 | PASS |
| 17320.50† | 7538.81 | 8697.16 | -2443.30 | 17071.57 | 7392.50 | 8697.90 | -1995.63 | 89.91 | 470.97 | 336.58 | 134.39 | 1.40 | PASS |
| 17420.50† | 7538.92 | 8797.12 | -2440.58 | 17171.52 | 7392.50 | 8797.86 | -1995.79 | 89.91 | 468.27 | 340.07 | 128.19 | 1.38 | PASS |
| 17520.50† | 7539.02 | 8897.08 | -2437.86 | 17271.48 | 7392.50 | 8897.82 | -1995.96 | 89.91 | 465.56 | 343.56 | 122.00 | 1.36 | PASS |
| 17620.50† | 7539.12 | 8997.05 | -2435.14 | 17371.44 | 7392.50 | 8997.77 | -1996.13 | 89.91 | 462.86 | 347.03 | 115.82 | 1.34 | PASS |
| 17720.50† | 7539.23 | 9097.01 | -2432.42 | 17471.40 | 7392.50 | 9097.73 | -1996.29 | 89.91 | 460.15 | 350.51 | 109.65 | 1.32 | PASS |
| 17820.50† | 7539.33 | 9196.97 | -2429.70 | 17571.36 | 7392.50 | 9197.69 | -1996.46 | 89.91 | 457.45 | 353.97 | 103.48 | 1.30 | PASS |
| 17920.50† | 7539.43 | 9296.94 | -2426.99 | 17671.32 | 7392.50 | 9297.65 | -1996.62 | 89.91 | 454.76 | 357.43 | 97.32 | 1.28 | PASS |
| 17985.90 | 7539.50 | 9362.31 | -2425.21 | 17736.68 | 7392.50 | 9363.02 | -1996.73 | 89.91 | 452.99 | 359.69 | 93.31 | 1.26 | PASS |

POSITIONAL UNCERTAINTY - Offset Wellbore: BUFORD 33-3-3L PWB Offset Wellpath: BUFORD 33-3-3L (REV-A.0) PWP

| | | | | |
|-----------------------------------|------------|---------|----------|---------|
| Slot Surface Uncertainty @1SD | Horizontal | 0.100ft | Vertical | 1.000ft |
| Facility Surface Uncertainty @1SD | Horizontal | 8.200ft | Vertical | 3.000ft |

SURVEY PROGRAM - Offset Wellbore: BUFORD 33-3-3L PWB Offset Wellpath: BUFORD 33-3-3L (REV-A.0) PWP

| Start MD [ft] | End MD [ft] | Positional Uncertainty Model | Log Name/Comment | Wellbore |
|---------------|-------------|---|------------------|--------------------|
| 20.50 | 1500.00 | BH NaviTrak (2019) (Standard) | | BUFORD 33-3-3L PWB |
| 1500.00 | 17761.45 | BH AutoTrak Curve/eXpress (2019) (Standard) | | BUFORD 33-3-3L PWB |

OFFSET WELLPATH REFERENCE - Offset Wellbore: BUFORD 33-3-3L PWB Offset Wellpath: BUFORD 33-3-3L (REV-A.0) PWP

| | |
|---------------------------------|---|
| MD Reference: RIG (20.5') (RKB) | Offset TVD & local coordinates use Reference Wellpath settings (See WELLPATH DATUM on page 1 of this report) |
| Ellipse Start MD | 20.50ft |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 54 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-5-3L PWB Offset Wellpath: BUFORD 33-5-3L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#02 BUFORD 33-5-3L (770'FSL & 769'FWL, SEC.34) Well: BUFORD 33-5-3L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | | |
| 20.50 | 20.50 | 0.00 | 0.00 | 19.50 | 20.50 | 0.00 | -50.43 | 270.00 | 50.43 | 9.74 | 40.69 | 8.07 | PASS | | | |
| 120.50† | 120.50 | 0.00 | 0.00 | 119.50 | 120.50 | 0.00 | -50.43 | 270.00 | 50.43 | 7.94 | 42.49 | 8.29 | PASS | | | |
| 200.00 | 200.00 | 0.00 | 0.00 | 199.00 | 200.00 | 0.00 | -50.43 | 270.00 | 50.43 | 8.09 | 42.34 | 8.08 | PASS | | | |
| 220.50† | 220.50 | -0.03 | -0.07 | 219.18 | 220.18 | -0.02 | -50.49 | 270.01 | 50.42 | 8.14 | 42.28 | 8.01 | PASS | | | |
| 320.50† | 320.46 | -0.93 | -2.36 | 317.53 | 318.50 | -0.74 | -52.72 | 270.23 | 50.41 | 8.60 | 41.80 | 7.44 | PASS | | | |
| 328.54† | 328.50 | -1.06 | -2.68 | 325.44 | 326.40 | -0.84 | -53.04 | 270.26 | 50.41 | 8.66 | 41.74 | 7.37 | PASS | | | |
| 420.50† | 420.28 | -3.13 | -7.88 | 415.89 | 416.68 | -2.48 | -58.17 | 270.73 | 50.42 | 9.52 | 40.90 | 6.52 | PASS | | | |
| 520.50† | 519.83 | -6.60 | -16.65 | 514.24 | 514.61 | -5.26 | -66.82 | 271.54 | 50.46 | 10.43 | 40.04 | 5.81 | PASS | | | |
| 620.50† | 618.99 | -11.36 | -28.64 | 612.61 | 612.18 | -9.06 | -78.67 | 272.63 | 50.55 | 11.32 | 39.23 | 5.26 | PASS | | | |
| 720.50† | 717.64 | -17.38 | -43.83 | 710.98 | 709.27 | -13.87 | -93.71 | 274.02 | 50.69 | 12.23 | 38.46 | 4.80 | PASS | | | |
| 820.50† | 815.66 | -24.68 | -62.22 | 809.35 | 805.77 | -19.71 | -111.91 | 275.71 | 50.90 | 13.11 | 37.80 | 4.44 | PASS | | | |
| 920.50† | 912.93 | -33.22 | -83.78 | 907.74 | 901.56 | -26.55 | -133.25 | 277.68 | 51.20 | 14.01 | 37.19 | 4.12 | PASS | | | |
| 1020.50† | 1009.33 | -43.02 | -108.48 | 1006.13 | 996.53 | -34.40 | -157.72 | 279.93 | 51.60 | 14.93 | 36.67 | 3.86 | PASS | | | |
| 1120.50† | 1104.74 | -54.05 | -136.29 | 1104.53 | 1090.58 | -43.23 | -185.28 | 282.45 | 52.13 | 15.89 | 36.24 | 3.63 | PASS | | | |
| 1220.50† | 1199.05 | -66.30 | -167.18 | 1202.95 | 1183.59 | -53.05 | -215.91 | 285.21 | 52.81 | 16.92 | 35.89 | 3.42 | PASS | | | |
| 1242.54 | 1219.68 | -69.16 | -174.40 | 1224.64 | 1203.93 | -55.34 | -223.07 | 285.85 | 52.98 | 17.14 | 35.84 | 3.38 | PASS | | | |
| 1320.50† | 1292.54 | -79.39 | -200.20 | 1301.37 | 1275.44 | -63.84 | -249.56 | 287.49 | 54.51 | 17.95 | 36.56 | 3.31 | PASS | | | |
| 1420.50† | 1385.99 | -92.51 | -233.28 | 1399.64 | 1365.89 | -75.56 | -286.14 | 287.78 | 59.03 | 19.06 | 39.98 | 3.36 | PASS | | | |
| 1520.50† | 1479.44 | -105.63 | -266.37 | 1497.88 | 1454.96 | -88.21 | -325.59 | 286.39 | 66.41 | 19.86 | 46.54 | 3.62 | PASS | | | |
| 1620.50† | 1572.89 | -118.75 | -299.46 | 1597.50 | 1544.80 | -101.35 | -366.59 | 284.53 | 74.82 | 19.79 | 55.03 | 4.04 | PASS | | | |
| 1720.50† | 1666.34 | -131.87 | -332.54 | 1697.13 | 1634.64 | -114.50 | -407.58 | 283.04 | 83.29 | 20.14 | 63.16 | 4.42 | PASS | | | |
| 1820.50† | 1759.79 | -144.99 | -365.63 | 1796.75 | 1724.48 | -127.64 | -448.58 | 281.82 | 91.81 | 20.56 | 71.25 | 4.78 | PASS | | | |
| 1920.50† | 1853.24 | -158.12 | -398.72 | 1896.37 | 1814.32 | -140.78 | -489.57 | 280.80 | 100.35 | 21.04 | 79.31 | 5.10 | PASS | | | |
| 2020.50† | 1946.69 | -171.24 | -431.80 | 1995.99 | 1904.16 | -153.92 | -530.57 | 279.94 | 108.92 | 21.59 | 87.34 | 5.39 | PASS | | | |
| 2120.50† | 2040.14 | -184.36 | -464.89 | 2095.61 | 1993.99 | -167.07 | -571.56 | 279.21 | 117.51 | 22.19 | 95.32 | 5.65 | PASS | | | |
| 2220.50† | 2133.59 | -197.48 | -497.98 | 2195.23 | 2083.83 | -180.21 | -612.56 | 278.57 | 126.11 | 22.84 | 103.27 | 5.88 | PASS | | | |
| 2320.50† | 2227.05 | -210.60 | -531.06 | 2294.85 | 2173.67 | -193.35 | -653.56 | 278.02 | 134.72 | 23.54 | 111.19 | 6.09 | PASS | | | |
| 2420.50† | 2320.50 | -223.72 | -564.15 | 2394.47 | 2263.51 | -206.49 | -694.55 | 277.53 | 143.35 | 24.28 | 119.07 | 6.27 | PASS | | | |
| 2520.50† | 2413.95 | -236.84 | -597.24 | 2494.10 | 2353.35 | -219.63 | -735.55 | 277.09 | 151.98 | 25.06 | 126.92 | 6.43 | PASS | | | |
| 2620.50† | 2507.40 | -249.96 | -630.32 | 2593.72 | 2443.19 | -232.78 | -776.54 | 276.70 | 160.62 | 25.88 | 134.74 | 6.57 | PASS | | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 55 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-5-3L PWB Offset Wellpath: BUFORD 33-5-3L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#02 BUFORD 33-5-3L (770'FSL & 769'FWL, SEC.34) Well: BUFORD 33-5-3L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | |
| 2720.50† | 2600.85 | -263.08 | -663.41 | 2693.34 | 2533.03 | -245.92 | -817.54 | 276.35 | 169.26 | 26.73 | 142.54 | 6.69 | PASS | | |
| 2820.50† | 2694.30 | -276.20 | -696.50 | 2792.96 | 2622.87 | -259.06 | -858.53 | 276.04 | 177.91 | 27.61 | 150.31 | 6.80 | PASS | | |
| 2920.50† | 2787.75 | -289.33 | -729.58 | 2892.58 | 2712.71 | -272.20 | -899.53 | 275.75 | 186.57 | 28.51 | 158.05 | 6.89 | PASS | | |
| 3020.50† | 2881.20 | -302.45 | -762.67 | 2992.20 | 2802.55 | -285.35 | -940.53 | 275.49 | 195.22 | 29.44 | 165.78 | 6.97 | PASS | | |
| 3120.50† | 2974.65 | -315.57 | -795.76 | 3091.82 | 2892.38 | -298.49 | -981.52 | 275.25 | 203.88 | 30.39 | 173.49 | 7.05 | PASS | | |
| 3220.50† | 3068.11 | -328.69 | -828.84 | 3191.44 | 2982.22 | -311.63 | -1022.52 | 275.03 | 212.55 | 31.36 | 181.18 | 7.11 | PASS | | |
| 3320.50† | 3161.56 | -341.81 | -861.93 | 3291.07 | 3072.06 | -324.77 | -1063.51 | 274.83 | 221.21 | 32.35 | 188.86 | 7.16 | PASS | | |
| 3420.50† | 3255.01 | -354.93 | -895.02 | 3390.69 | 3161.90 | -337.92 | -1104.51 | 274.64 | 229.88 | 33.36 | 196.52 | 7.21 | PASS | | |
| 3520.50† | 3348.46 | -368.05 | -928.10 | 3490.31 | 3251.74 | -351.06 | -1145.50 | 274.47 | 238.55 | 34.38 | 204.17 | 7.25 | PASS | | |
| 3620.50† | 3441.91 | -381.17 | -961.19 | 3589.93 | 3341.58 | -364.20 | -1186.50 | 274.31 | 247.22 | 35.41 | 211.81 | 7.28 | PASS | | |
| 3720.50† | 3535.36 | -394.29 | -994.28 | 3689.55 | 3431.42 | -377.34 | -1227.50 | 274.16 | 255.89 | 36.45 | 219.44 | 7.31 | PASS | | |
| 3820.50† | 3628.81 | -407.41 | -1027.37 | 3789.17 | 3521.26 | -390.48 | -1268.49 | 274.02 | 264.57 | 37.51 | 227.06 | 7.34 | PASS | | |
| 3920.50† | 3722.26 | -420.53 | -1060.45 | 3888.79 | 3611.10 | -403.63 | -1309.49 | 273.88 | 273.24 | 38.57 | 234.67 | 7.36 | PASS | | |
| 4020.50† | 3815.71 | -433.66 | -1093.54 | 3988.42 | 3700.93 | -416.77 | -1350.48 | 273.76 | 281.92 | 39.65 | 242.27 | 7.38 | PASS | | |
| 4120.50† | 3909.17 | -446.78 | -1126.63 | 4088.04 | 3790.77 | -429.91 | -1391.48 | 273.64 | 290.60 | 40.73 | 249.87 | 7.40 | PASS | | |
| 4220.50† | 4002.62 | -459.90 | -1159.71 | 4187.66 | 3880.61 | -443.05 | -1432.47 | 273.53 | 299.28 | 41.83 | 257.45 | 7.41 | PASS | | |
| 4320.50† | 4096.07 | -473.02 | -1192.80 | 4287.28 | 3970.45 | -456.20 | -1473.47 | 273.43 | 307.96 | 42.92 | 265.03 | 7.43 | PASS | | |
| 4420.50† | 4189.52 | -486.14 | -1225.89 | 4386.90 | 4060.29 | -469.34 | -1514.47 | 273.33 | 316.64 | 44.03 | 272.61 | 7.44 | PASS | | |
| 4520.50† | 4282.97 | -499.26 | -1258.97 | 4486.52 | 4150.13 | -482.48 | -1555.46 | 273.24 | 325.32 | 45.14 | 280.18 | 7.45 | PASS | | |
| 4620.50† | 4376.42 | -512.38 | -1292.06 | 4586.14 | 4239.97 | -495.62 | -1596.46 | 273.15 | 334.00 | 46.26 | 287.74 | 7.46 | PASS | | |
| 4720.50† | 4469.87 | -525.50 | -1325.15 | 4685.76 | 4329.81 | -508.77 | -1637.45 | 273.07 | 342.69 | 47.38 | 295.30 | 7.46 | PASS | | |
| 4820.50† | 4563.32 | -538.62 | -1358.23 | 4785.39 | 4419.65 | -521.91 | -1678.45 | 272.99 | 351.37 | 48.51 | 302.86 | 7.47 | PASS | | |
| 4920.50† | 4656.77 | -551.74 | -1391.32 | 4885.01 | 4509.49 | -535.05 | -1719.44 | 272.91 | 360.05 | 49.64 | 310.41 | 7.47 | PASS | | |
| 5020.50† | 4750.22 | -564.87 | -1424.41 | 4984.63 | 4599.32 | -548.19 | -1760.44 | 272.84 | 368.74 | 50.78 | 317.96 | 7.48 | PASS | | |
| 5120.50† | 4843.68 | -577.99 | -1457.49 | 5084.25 | 4689.16 | -561.33 | -1801.44 | 272.77 | 377.42 | 51.92 | 325.50 | 7.48 | PASS | | |
| 5220.50† | 4937.13 | -591.11 | -1490.58 | 5183.87 | 4779.00 | -574.48 | -1842.43 | 272.71 | 386.11 | 53.07 | 333.04 | 7.48 | PASS | | |
| 5320.50† | 5030.58 | -604.23 | -1523.67 | 5283.49 | 4868.84 | -587.62 | -1883.43 | 272.64 | 394.79 | 54.21 | 340.58 | 7.48 | PASS | | |
| 5420.50† | 5124.03 | -617.35 | -1556.75 | 5383.11 | 4958.68 | -600.76 | -1924.42 | 272.58 | 403.48 | 55.37 | 348.11 | 7.49 | PASS | | |
| 5520.50† | 5217.48 | -630.47 | -1589.84 | 5482.73 | 5048.52 | -613.90 | -1965.42 | 272.53 | 412.17 | 56.52 | 355.65 | 7.49 | PASS | | |
| 5620.50† | 5310.93 | -643.59 | -1622.93 | 5582.36 | 5138.36 | -627.05 | -2006.41 | 272.47 | 420.85 | 57.68 | 363.18 | 7.49 | PASS | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 56 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770°FSL & 819°FSL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-5-3L PWB Offset Wellpath: BUFORD 33-5-3L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#02 BUFORD 33-5-3L (770°FSL & 769°FWL,SEC.34) Well: BUFORD 33-5-3L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|-----------------|-------------------|------------------|-------------------|--------------------|----------------------|---------------------|-------------------------|---------------------------|----------------------|----------------------------|--------------|----------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 5720.50† | 5404.38 | -656.71 | -1656.01 | 5681.98 | 5228.20 | -640.19 | -2047.41 | 272.42 | 429.54 | 58.84 | 370.70 | 7.49 | PASS |
| 5820.50† | 5497.83 | -669.83 | -1689.10 | 5781.60 | 5318.04 | -653.33 | -2088.40 | 272.37 | 438.23 | 60.00 | 378.23 | 7.49 | PASS |
| 5920.50† | 5591.28 | -682.95 | -1722.19 | 5881.22 | 5407.87 | -666.47 | -2129.40 | 272.32 | 446.91 | 61.16 | 385.75 | 7.49 | PASS |
| 6020.50† | 5684.74 | -696.07 | -1755.27 | 5980.84 | 5497.71 | -679.62 | -2170.40 | 272.27 | 455.60 | 62.33 | 393.27 | 7.49 | PASS |
| 6120.50† | 5778.19 | -709.20 | -1788.36 | 6080.46 | 5587.55 | -692.76 | -2211.39 | 272.23 | 464.29 | 63.50 | 400.79 | 7.48 | PASS |
| 6220.50† | 5871.64 | -722.32 | -1821.45 | 6180.08 | 5677.39 | -705.90 | -2252.39 | 272.18 | 472.98 | 64.67 | 408.31 | 7.48 | PASS |
| 6320.50† | 5965.09 | -735.44 | -1854.54 | 6279.70 | 5767.23 | -719.04 | -2293.38 | 272.14 | 481.67 | 65.84 | 415.82 | 7.48 | PASS |
| 6420.50† | 6058.54 | -748.56 | -1887.62 | 6379.33 | 5857.07 | -732.19 | -2334.38 | 272.10 | 490.36 | 67.02 | 423.34 | 7.48 | PASS |
| 6520.50† | 6151.99 | -761.68 | -1920.71 | 6478.95 | 5946.91 | -745.33 | -2375.37 | 272.06 | 499.05 | 68.20 | 430.85 | 7.48 | PASS |
| 6620.50† | 6245.44 | -774.80 | -1953.80 | 6578.57 | 6036.75 | -758.47 | -2416.37 | 272.02 | 507.74 | 69.37 | 438.36 | 7.48 | PASS |
| 6720.50† | 6338.89 | -787.92 | -1986.88 | 6678.19 | 6126.59 | -771.61 | -2457.37 | 271.99 | 516.43 | 70.55 | 445.87 | 7.47 | PASS |
| 6820.50† | 6432.34 | -801.04 | -2019.97 | 6777.81 | 6216.43 | -784.75 | -2498.36 | 271.95 | 525.11 | 71.74 | 453.38 | 7.47 | PASS |
| 6920.50† | 6525.80 | -814.16 | -2053.06 | 6877.43 | 6306.26 | -797.90 | -2539.36 | 271.92 | 533.80 | 72.92 | 460.89 | 7.47 | PASS |
| 7020.50† | 6619.25 | -827.28 | -2086.14 | 6977.05 | 6396.10 | -811.04 | -2580.35 | 271.88 | 542.49 | 74.10 | 468.39 | 7.47 | PASS |
| 7120.50† | 6712.70 | -840.41 | -2119.23 | 7076.68 | 6485.94 | -824.18 | -2621.35 | 271.85 | 551.18 | 75.29 | 475.90 | 7.47 | PASS |
| 7220.50† | 6806.15 | -853.53 | -2152.32 | 7176.30 | 6575.78 | -837.32 | -2662.34 | 271.82 | 559.88 | 76.47 | 483.40 | 7.46 | PASS |
| 7320.50† | 6899.60 | -866.65 | -2185.40 | 7275.92 | 6665.62 | -850.47 | -2703.34 | 271.79 | 568.57 | 77.66 | 490.90 | 7.46 | PASS |
| 7341.07 | 6918.82 | -869.35 | -2192.21 | 7296.41 | 6684.10 | -853.17 | -2711.77 | 271.78 | 570.35 | 77.91 | 492.45 | 7.46 | PASS |
| 7420.50† | 6993.49 | -874.29 | -2218.65 | 7375.28 | 6755.23 | -863.57 | -2744.23 | 271.17 | 577.16 | 78.32 | 498.84 | 7.51 | PASS |
| 7520.50† | 7087.21 | -884.88 | -2251.87 | 7473.01 | 6843.57 | -874.27 | -2784.55 | 268.99 | 585.83 | 77.65 | 508.18 | 7.69 | PASS |
| 7620.50† | 7177.96 | -898.35 | -2284.05 | 7573.54 | 6934.80 | -889.93 | -2826.22 | 266.67 | 595.03 | 77.06 | 517.97 | 7.87 | PASS |
| 7720.50† | 7262.97 | -915.51 | -2314.23 | 7678.43 | 7027.71 | -906.82 | -2868.69 | 264.71 | 604.49 | 76.99 | 527.50 | 8.01 | PASS |
| 7820.50† | 7339.68 | -937.65 | -2341.49 | 7788.10 | 7119.05 | -930.20 | -2910.48 | 263.43 | 613.79 | 77.36 | 536.43 | 8.09 | PASS |
| 7920.50† | 7405.75 | -966.53 | -2364.99 | 7902.79 | 7204.64 | -958.02 | -2949.70 | 263.03 | 622.45 | 77.95 | 544.49 | 8.14 | PASS |
| 8020.50† | 7459.16 | -984.32 | -2384.03 | 8022.42 | 7279.46 | -985.54 | -2984.04 | 263.61 | 629.94 | 78.56 | 551.39 | 8.17 | PASS |
| 8120.50† | 7498.30 | -1022.50 | -2398.02 | 8146.43 | 7338.05 | -1013.01 | -3011.01 | 265.11 | 635.76 | 79.11 | 556.65 | 8.19 | PASS |
| 8220.50† | 7521.99 | -1050.85 | -2406.55 | 8273.78 | 7375.29 | -1026.33 | -3028.26 | 267.35 | 639.44 | 79.71 | 559.73 | 8.17 | PASS |
| 8315.56 | 7529.50 | -1022.50 | -2409.34 | 8396.53 | 7387.50 | -1030.86 | -3034.09 | 269.85 | 640.68 | 80.40 | 560.28 | 8.12 | PASS |
| 8320.50† | 7529.51 | -1022.50 | -2409.35 | 8401.85 | 7387.50 | -1029.54 | -3034.10 | 269.89 | 640.68 | 80.41 | 560.28 | 8.12 | PASS |
| 8420.50† | 7529.61 | -1022.50 | -2409.53 | 8501.85 | 7387.47 | -1029.54 | -3034.29 | 269.89 | 640.73 | 80.31 | 560.41 | 8.13 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 57 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-5-3L PWB Offset Wellpath: BUFORD 33-5-3L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#02 BUFORD 33-5-3L (770'FSL & 769'FWL,SEC.34) Well: BUFORD 33-5-3L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|-----------------|-------------------|------------------|-------------------|--------------------|----------------------|---------------------|-------------------------|---------------------------|----------------------|----------------------------|--------------|----------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 8520.50† | 7529.71 | -97.30 | -2409.71 | 8601.85 | 7387.44 | -98.54 | -3034.48 | 269.89 | 640.77 | 80.44 | 560.32 | 8.12 | PASS |
| 8620.50† | 7529.82 | 2.70 | -2409.88 | 8701.85 | 7387.41 | 1.46 | -3034.67 | 269.89 | 640.81 | 80.85 | 559.96 | 8.07 | PASS |
| 8720.50† | 7529.92 | 102.70 | -2410.06 | 8801.85 | 7387.37 | 101.46 | -3034.86 | 269.89 | 640.85 | 81.39 | 559.46 | 8.02 | PASS |
| 8820.50† | 7530.02 | 202.70 | -2410.24 | 8901.85 | 7387.34 | 201.46 | -3035.05 | 269.89 | 640.90 | 82.12 | 558.77 | 7.95 | PASS |
| 8920.50† | 7530.13 | 302.70 | -2410.42 | 9001.85 | 7387.31 | 301.46 | -3035.24 | 269.89 | 640.94 | 83.02 | 557.92 | 7.86 | PASS |
| 9020.50† | 7530.23 | 402.70 | -2410.59 | 9101.85 | 7387.28 | 401.46 | -3035.43 | 269.89 | 640.98 | 84.09 | 556.89 | 7.76 | PASS |
| 9120.50† | 7530.33 | 502.70 | -2410.77 | 9201.85 | 7387.25 | 501.46 | -3035.62 | 269.89 | 641.02 | 85.33 | 555.70 | 7.64 | PASS |
| 9220.50† | 7530.44 | 602.70 | -2410.95 | 9301.85 | 7387.22 | 601.46 | -3035.81 | 269.89 | 641.07 | 86.71 | 554.35 | 7.52 | PASS |
| 9320.50† | 7530.54 | 702.70 | -2411.13 | 9401.85 | 7387.19 | 701.46 | -3036.00 | 269.89 | 641.11 | 88.25 | 552.86 | 7.39 | PASS |
| 9420.50† | 7530.64 | 802.69 | -2411.31 | 9501.85 | 7387.16 | 801.46 | -3036.20 | 269.89 | 641.15 | 89.92 | 551.23 | 7.25 | PASS |
| 9520.50† | 7530.75 | 902.69 | -2411.48 | 9601.85 | 7387.13 | 901.46 | -3036.39 | 269.89 | 641.20 | 91.73 | 549.47 | 7.10 | PASS |
| 9620.50† | 7530.85 | 1002.69 | -2411.66 | 9701.85 | 7387.10 | 1001.46 | -3036.58 | 269.89 | 641.24 | 93.66 | 547.58 | 6.95 | PASS |
| 9720.50† | 7530.96 | 1102.69 | -2411.84 | 9801.85 | 7387.06 | 1101.46 | -3036.77 | 269.89 | 641.28 | 95.71 | 545.57 | 6.80 | PASS |
| 9820.50† | 7531.06 | 1202.69 | -2412.02 | 9901.85 | 7387.03 | 1201.46 | -3036.96 | 269.89 | 641.32 | 97.87 | 543.46 | 6.65 | PASS |
| 9920.50† | 7531.16 | 1302.69 | -2412.19 | 10001.85 | 7387.00 | 1301.46 | -3037.15 | 269.89 | 641.37 | 100.12 | 541.24 | 6.50 | PASS |
| 10020.50† | 7531.27 | 1402.69 | -2412.37 | 10101.85 | 7386.97 | 1401.46 | -3037.34 | 269.89 | 641.41 | 102.48 | 538.93 | 6.35 | PASS |
| 10120.50† | 7531.37 | 1502.69 | -2412.55 | 10201.85 | 7386.94 | 1501.46 | -3037.53 | 269.89 | 641.45 | 104.92 | 536.53 | 6.20 | PASS |
| 10220.50† | 7531.47 | 1602.69 | -2412.73 | 10301.85 | 7386.91 | 1601.46 | -3037.72 | 269.89 | 641.50 | 107.44 | 534.05 | 6.05 | PASS |
| 10320.50† | 7531.58 | 1702.69 | -2412.90 | 10401.85 | 7386.88 | 1701.46 | -3037.91 | 269.89 | 641.54 | 110.04 | 531.50 | 5.91 | PASS |
| 10420.50† | 7531.68 | 1802.69 | -2413.08 | 10501.85 | 7386.85 | 1801.46 | -3038.10 | 269.89 | 641.58 | 112.72 | 528.87 | 5.76 | PASS |
| 10520.50† | 7531.78 | 1902.69 | -2413.26 | 10601.85 | 7386.82 | 1901.46 | -3038.29 | 269.89 | 641.63 | 115.45 | 526.17 | 5.63 | PASS |
| 10620.50† | 7531.89 | 2002.69 | -2413.44 | 10701.85 | 7386.78 | 2001.46 | -3038.48 | 269.89 | 641.67 | 118.25 | 523.42 | 5.49 | PASS |
| 10720.50† | 7531.99 | 2102.69 | -2413.62 | 10801.85 | 7386.75 | 2101.46 | -3038.67 | 269.89 | 641.71 | 121.11 | 520.60 | 5.36 | PASS |
| 10820.50† | 7532.09 | 2202.69 | -2413.79 | 10901.85 | 7386.72 | 2201.45 | -3038.87 | 269.89 | 641.76 | 124.02 | 517.74 | 5.23 | PASS |
| 10920.50† | 7532.20 | 2302.69 | -2413.97 | 11001.85 | 7386.69 | 2301.45 | -3039.06 | 269.89 | 641.80 | 126.98 | 514.82 | 5.11 | PASS |
| 11020.50† | 7532.30 | 2402.69 | -2414.15 | 11101.85 | 7386.66 | 2401.45 | -3039.25 | 269.89 | 641.84 | 129.98 | 511.86 | 4.99 | PASS |
| 11120.50† | 7532.41 | 2502.69 | -2414.33 | 11201.85 | 7386.63 | 2501.45 | -3039.44 | 269.89 | 641.89 | 133.03 | 508.86 | 4.87 | PASS |
| 11220.50† | 7532.51 | 2602.69 | -2414.50 | 11301.85 | 7386.60 | 2601.45 | -3039.63 | 269.89 | 641.93 | 136.12 | 505.81 | 4.76 | PASS |
| 11320.50† | 7532.61 | 2702.69 | -2414.68 | 11401.85 | 7386.57 | 2701.45 | -3039.82 | 269.89 | 641.97 | 139.24 | 502.73 | 4.65 | PASS |
| 11420.50† | 7532.72 | 2802.69 | -2414.86 | 11501.85 | 7386.54 | 2801.45 | -3040.01 | 269.89 | 642.02 | 142.40 | 499.62 | 4.55 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 58 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770°FSL & 819°FSL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-5-3L PWB Offset Wellpath: BUFORD 33-5-3L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#02 BUFORD 33-5-3L (770°FSL & 769°FWL,SEC.34) Well: BUFORD 33-5-3L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|-----------------|-------------------|------------------|-------------------|--------------------|----------------------|---------------------|-------------------------|---------------------------|----------------------|----------------------------|--------------|----------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 11520.50† | 7532.82 | 2902.69 | -2415.04 | 11601.85 | 7386.51 | 2901.45 | -3040.20 | 269.89 | 642.06 | 145.59 | 496.47 | 4.45 | PASS |
| 11620.50† | 7532.92 | 3002.69 | -2415.21 | 11701.85 | 7386.47 | 3001.45 | -3040.39 | 269.89 | 642.10 | 148.81 | 493.29 | 4.35 | PASS |
| 11720.50† | 7533.03 | 3102.69 | -2415.39 | 11801.85 | 7386.44 | 3101.45 | -3040.58 | 269.89 | 642.15 | 152.06 | 490.09 | 4.26 | PASS |
| 11820.50† | 7533.13 | 3202.69 | -2415.57 | 11901.85 | 7386.41 | 3201.45 | -3040.77 | 269.89 | 642.19 | 155.34 | 486.85 | 4.17 | PASS |
| 11920.50† | 7533.23 | 3302.69 | -2415.75 | 12001.85 | 7386.38 | 3301.45 | -3040.96 | 269.89 | 642.23 | 158.64 | 483.60 | 4.08 | PASS |
| 12020.50† | 7533.34 | 3402.69 | -2415.92 | 12101.85 | 7386.35 | 3401.45 | -3041.15 | 269.89 | 642.28 | 161.96 | 480.32 | 4.00 | PASS |
| 12120.50† | 7533.44 | 3502.69 | -2416.10 | 12201.85 | 7386.32 | 3501.45 | -3041.34 | 269.89 | 642.32 | 165.30 | 477.01 | 3.92 | PASS |
| 12220.50† | 7533.55 | 3602.69 | -2416.28 | 12301.85 | 7386.29 | 3601.45 | -3041.53 | 269.89 | 642.36 | 168.67 | 473.69 | 3.84 | PASS |
| 12320.50† | 7533.65 | 3702.69 | -2416.46 | 12401.85 | 7386.26 | 3701.45 | -3041.73 | 269.89 | 642.41 | 172.06 | 470.35 | 3.76 | PASS |
| 12420.50† | 7533.75 | 3802.69 | -2416.64 | 12501.85 | 7386.23 | 3801.45 | -3041.92 | 269.89 | 642.45 | 175.46 | 466.99 | 3.69 | PASS |
| 12520.50† | 7533.86 | 3902.69 | -2416.81 | 12601.85 | 7386.19 | 3901.45 | -3042.11 | 269.89 | 642.49 | 178.88 | 463.62 | 3.62 | PASS |
| 12620.50† | 7533.96 | 4002.69 | -2416.99 | 12701.85 | 7386.16 | 4001.45 | -3042.30 | 269.89 | 642.54 | 182.31 | 460.22 | 3.55 | PASS |
| 12720.50† | 7534.06 | 4102.69 | -2417.17 | 12801.85 | 7386.13 | 4101.45 | -3042.49 | 269.89 | 642.58 | 185.77 | 456.82 | 3.48 | PASS |
| 12820.50† | 7534.17 | 4202.69 | -2417.35 | 12901.85 | 7386.10 | 4201.45 | -3042.68 | 269.89 | 642.62 | 189.23 | 453.39 | 3.42 | PASS |
| 12920.50† | 7534.27 | 4302.69 | -2417.52 | 13001.85 | 7386.07 | 4301.45 | -3042.87 | 269.89 | 642.67 | 192.71 | 449.96 | 3.36 | PASS |
| 13020.50† | 7534.37 | 4402.69 | -2417.70 | 13101.85 | 7386.04 | 4401.45 | -3043.06 | 269.89 | 642.71 | 196.20 | 446.51 | 3.30 | PASS |
| 13120.50† | 7534.48 | 4502.69 | -2417.88 | 13201.85 | 7386.01 | 4501.45 | -3043.25 | 269.89 | 642.76 | 199.70 | 443.05 | 3.24 | PASS |
| 13199.97 | 7534.56 | 4582.16 | -2418.02 | 13281.32 | 7385.98 | 4580.92 | -3043.40 | 269.89 | 642.79 | 202.49 | 440.30 | 3.19 | PASS |
| 13220.50† | 7534.58 | 4602.69 | -2418.13 | 13301.85 | 7385.98 | 4601.45 | -3043.44 | 269.89 | 642.73 | 203.21 | 439.52 | 3.18 | PASS |
| 13320.50† | 7534.68 | 4702.65 | -2420.77 | 13401.81 | 7385.95 | 4701.41 | -3043.63 | 269.89 | 640.38 | 206.73 | 433.65 | 3.11 | PASS |
| 13420.50† | 7534.79 | 4802.45 | -2426.90 | 13501.63 | 7385.92 | 4801.23 | -3043.82 | 269.89 | 634.64 | 210.28 | 424.36 | 3.03 | PASS |
| 13476.50 | 7534.85 | 4858.23 | -2431.85 | 13557.42 | 7385.90 | 4857.02 | -3043.93 | 269.89 | 629.95 | 212.27 | 417.68 | 2.98 | PASS |
| 13520.50† | 7534.89 | 4902.02 | -2436.16 | 13601.21 | 7385.88 | 4900.82 | -3044.01 | 269.89 | 625.85 | 213.83 | 412.02 | 2.94 | PASS |
| 13620.50† | 7534.99 | 5001.54 | -2445.98 | 13700.75 | 7385.85 | 5000.35 | -3044.20 | 269.89 | 616.54 | 217.38 | 399.16 | 2.85 | PASS |
| 13720.50† | 7535.10 | 5101.06 | -2455.79 | 13800.29 | 7385.82 | 5099.89 | -3044.39 | 269.89 | 607.23 | 220.94 | 386.29 | 2.76 | PASS |
| 13820.50† | 7535.20 | 5200.57 | -2465.61 | 13899.82 | 7385.79 | 5199.42 | -3044.58 | 269.89 | 597.94 | 224.50 | 373.44 | 2.68 | PASS |
| 13920.50† | 7535.30 | 5300.09 | -2475.42 | 13999.36 | 7385.76 | 5298.96 | -3044.77 | 269.89 | 588.66 | 228.07 | 360.59 | 2.59 | PASS |
| 14020.50† | 7535.40 | 5399.61 | -2485.24 | 14098.89 | 7385.73 | 5398.49 | -3044.96 | 269.89 | 579.39 | 231.63 | 347.76 | 2.51 | PASS |
| 14120.50† | 7535.51 | 5499.12 | -2495.05 | 14198.43 | 7385.70 | 5498.03 | -3045.15 | 269.89 | 570.13 | 235.18 | 334.95 | 2.43 | PASS |
| 14220.50† | 7535.61 | 5598.64 | -2504.87 | 14297.96 | 7385.67 | 5597.56 | -3045.34 | 269.89 | 560.89 | 238.74 | 322.15 | 2.36 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 59 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770°FSL & 819°FSL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-5-3L PWB Offset Wellpath: BUFORD 33-5-3L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#02 BUFORD 33-5-3L (770°FSL & 769°FWL,SEC.34) Well: BUFORD 33-5-3L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|-----------------|-------------------|------------------|-------------------|--------------------|----------------------|---------------------|-------------------------|---------------------------|----------------------|----------------------------|--------------|----------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 14221.87 | 7535.61 | 5600.00 | -2505.00 | 14299.32 | 7385.67 | 5598.92 | -3045.34 | 269.89 | 560.76 | 238.78 | 321.98 | 2.36 | PASS |
| 14320.50† | 7535.71 | 5698.31 | -2512.99 | 14397.64 | 7385.64 | 5697.24 | -3045.53 | 269.89 | 553.29 | 242.28 | 311.01 | 2.29 | PASS |
| 14420.50† | 7535.81 | 5798.19 | -2517.63 | 14497.54 | 7385.61 | 5797.14 | -3045.72 | 269.89 | 549.04 | 245.85 | 303.19 | 2.24 | PASS |
| 14520.50† | 7535.92 | 5898.18 | -2518.78 | 14597.53 | 7385.57 | 5897.13 | -3045.91 | 269.89 | 548.15 | 249.44 | 298.71 | 2.21 | PASS |
| 14581.38 | 7535.98 | 5959.05 | -2517.77 | 14658.40 | 7385.56 | 5958.00 | -3046.03 | 269.89 | 549.26 | 251.63 | 297.63 | 2.19 | PASS |
| 14620.50† | 7536.02 | 5998.16 | -2516.71 | 14697.50 | 7385.54 | 5997.10 | -3046.10 | 269.89 | 550.37 | 253.03 | 297.33 | 2.18 | PASS |
| 14720.50† | 7536.12 | 6098.12 | -2513.99 | 14797.46 | 7385.51 | 6097.06 | -3046.29 | 269.89 | 553.20 | 256.63 | 296.57 | 2.16 | PASS |
| 14820.50† | 7536.23 | 6198.08 | -2511.27 | 14897.42 | 7385.48 | 6197.02 | -3046.48 | 269.89 | 556.04 | 260.25 | 295.79 | 2.14 | PASS |
| 14920.50† | 7536.33 | 6298.05 | -2508.55 | 14997.37 | 7385.45 | 6296.97 | -3046.68 | 269.89 | 558.88 | 263.87 | 295.01 | 2.13 | PASS |
| 15020.50† | 7536.43 | 6398.01 | -2505.83 | 15097.33 | 7385.42 | 6396.93 | -3046.87 | 269.89 | 561.71 | 267.49 | 294.22 | 2.11 | PASS |
| 15120.50† | 7536.54 | 6497.97 | -2503.11 | 15197.29 | 7385.39 | 6496.89 | -3047.06 | 269.89 | 564.55 | 271.13 | 293.43 | 2.09 | PASS |
| 15220.50† | 7536.64 | 6597.93 | -2500.40 | 15297.25 | 7385.36 | 6596.84 | -3047.25 | 269.89 | 567.39 | 274.77 | 292.63 | 2.07 | PASS |
| 15320.50† | 7536.74 | 6697.90 | -2497.68 | 15397.20 | 7385.33 | 6696.80 | -3047.44 | 269.89 | 570.23 | 278.41 | 291.82 | 2.05 | PASS |
| 15420.50† | 7536.85 | 6797.86 | -2494.96 | 15497.16 | 7385.30 | 6796.76 | -3047.63 | 269.89 | 573.07 | 282.06 | 291.01 | 2.04 | PASS |
| 15520.50† | 7536.95 | 6897.82 | -2492.24 | 15597.12 | 7385.26 | 6896.72 | -3047.82 | 269.89 | 575.92 | 285.72 | 290.20 | 2.02 | PASS |
| 15620.50† | 7537.05 | 6997.79 | -2489.52 | 15697.08 | 7385.23 | 6996.67 | -3048.01 | 269.89 | 578.76 | 289.38 | 289.38 | 2.01 | PASS |
| 15720.50† | 7537.16 | 7097.75 | -2486.80 | 15797.03 | 7385.20 | 7096.63 | -3048.20 | 269.89 | 581.60 | 293.05 | 288.55 | 1.99 | PASS |
| 15820.50† | 7537.26 | 7197.71 | -2484.08 | 15896.99 | 7385.17 | 7196.59 | -3048.39 | 269.89 | 584.45 | 296.72 | 287.72 | 1.98 | PASS |
| 15920.50† | 7537.36 | 7297.68 | -2481.36 | 15996.95 | 7385.14 | 7296.55 | -3048.58 | 269.89 | 587.29 | 300.40 | 286.89 | 1.96 | PASS |
| 16020.50† | 7537.47 | 7397.64 | -2478.64 | 16096.91 | 7385.11 | 7396.50 | -3048.77 | 269.89 | 590.14 | 304.08 | 286.06 | 1.95 | PASS |
| 16120.50† | 7537.57 | 7497.60 | -2475.93 | 16196.86 | 7385.08 | 7496.46 | -3048.96 | 269.89 | 592.98 | 307.77 | 285.22 | 1.93 | PASS |
| 16220.50† | 7537.68 | 7597.56 | -2473.21 | 16296.82 | 7385.05 | 7596.42 | -3049.15 | 269.89 | 595.83 | 311.46 | 284.37 | 1.92 | PASS |
| 16320.50† | 7537.78 | 7697.53 | -2470.49 | 16396.78 | 7385.02 | 7696.38 | -3049.34 | 269.89 | 598.68 | 315.15 | 283.53 | 1.90 | PASS |
| 16420.50† | 7537.88 | 7797.49 | -2467.77 | 16496.74 | 7384.99 | 7796.33 | -3049.53 | 269.89 | 601.52 | 318.85 | 282.68 | 1.89 | PASS |
| 16520.50† | 7537.99 | 7897.45 | -2465.05 | 16596.69 | 7384.95 | 7896.29 | -3049.73 | 269.89 | 604.37 | 322.55 | 281.82 | 1.88 | PASS |
| 16620.50† | 7538.09 | 7997.42 | -2462.33 | 16696.65 | 7384.92 | 7996.25 | -3049.92 | 269.89 | 607.22 | 326.26 | 280.96 | 1.87 | PASS |
| 16720.50† | 7538.19 | 8097.38 | -2459.61 | 16796.61 | 7384.89 | 8096.21 | -3050.11 | 269.89 | 610.07 | 329.97 | 280.10 | 1.85 | PASS |
| 16820.50† | 7538.30 | 8197.34 | -2456.89 | 16896.57 | 7384.86 | 8196.16 | -3050.30 | 269.89 | 612.92 | 333.68 | 279.24 | 1.84 | PASS |
| 16920.50† | 7538.40 | 8297.31 | -2454.17 | 16996.53 | 7384.83 | 8296.12 | -3050.49 | 269.89 | 615.77 | 337.40 | 278.38 | 1.83 | PASS |
| 17020.50† | 7538.50 | 8397.27 | -2451.46 | 17096.48 | 7384.80 | 8396.08 | -3050.68 | 269.89 | 618.62 | 341.12 | 277.51 | 1.82 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 60 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-5-3L PWB Offset Wellpath: BUFORD 33-5-3L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#02 BUFORD 33-5-3L (770'FSL & 769'FWL, SEC.34) Well: BUFORD 33-5-3L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 17120.50† | 7538.61 | 8497.23 | -2448.74 | 17196.44 | 7384.77 | 8496.04 | -3050.87 | 269.89 | 621.47 | 344.84 | 276.64 | 1.81 | PASS |
| 17220.50† | 7538.71 | 8597.19 | -2446.02 | 17296.40 | 7384.74 | 8595.99 | -3051.06 | 269.89 | 624.33 | 348.57 | 275.76 | 1.79 | PASS |
| 17320.50† | 7538.81 | 8697.16 | -2443.30 | 17396.36 | 7384.71 | 8695.95 | -3051.25 | 269.89 | 627.18 | 352.30 | 274.88 | 1.78 | PASS |
| 17420.50† | 7538.92 | 8797.12 | -2440.58 | 17496.31 | 7384.67 | 8795.91 | -3051.44 | 269.89 | 630.03 | 356.03 | 274.01 | 1.77 | PASS |
| 17520.50† | 7539.02 | 8897.08 | -2437.86 | 17596.27 | 7384.64 | 8895.86 | -3051.63 | 269.89 | 632.89 | 359.76 | 273.12 | 1.76 | PASS |
| 17620.50† | 7539.12 | 8997.05 | -2435.14 | 17696.23 | 7384.61 | 8995.82 | -3051.82 | 269.89 | 635.74 | 363.50 | 272.24 | 1.75 | PASS |
| 17720.50† | 7539.23 | 9097.01 | -2432.42 | 17796.19 | 7384.58 | 9095.78 | -3052.01 | 269.89 | 638.60 | 367.24 | 271.35 | 1.74 | PASS |
| 17820.50† | 7539.33 | 9196.97 | -2429.70 | 17896.14 | 7384.55 | 9195.74 | -3052.20 | 269.89 | 641.45 | 370.99 | 270.47 | 1.73 | PASS |
| 17920.50† | 7539.43 | 9296.94 | -2426.99 | 17996.10 | 7384.52 | 9295.69 | -3052.39 | 269.89 | 644.31 | 374.73 | 269.58 | 1.72 | PASS |
| 17985.90 | 7539.50 | 9362.31 | -2425.21 | 18059.14 | 7384.50 | 9358.73 | -3052.51 | 269.67 | 646.18 | 377.52 | 268.66 | 1.71 | PASS |

POSITIONAL UNCERTAINTY - Offset Wellbore: BUFORD 33-5-3L PWB Offset Wellpath: BUFORD 33-5-3L (REV-A.0) PWP

| | | | | |
|-----------------------------------|------------|---------|----------|---------|
| Slot Surface Uncertainty @1SD | Horizontal | 0.100ft | Vertical | 1.000ft |
| Facility Surface Uncertainty @1SD | Horizontal | 8.200ft | Vertical | 3.000ft |

HOLE & CASING SECTIONS - Offset Wellbore: BUFORD 33-5-3L PWB Offset Wellpath: BUFORD 33-5-3L (REV-A.0) PWP

| String/Diameter | Start MD [ft] | End MD [ft] | Interval [ft] | Start TVD [ft] | End TVD [ft] | Start N/S [ft] | Start E/W [ft] | End N/S [ft] | End E/W [ft] |
|------------------------|---------------|-------------|---------------|----------------|--------------|----------------|----------------|--------------|--------------|
| 13.5in Open Hole | 20.50 | 1500.00 | 1479.50 | 21.50 | 1456.87 | 0.00 | -50.43 | -88.49 | -326.46 |
| 9.625in Casing Surface | 20.50 | 1500.00 | 1479.50 | 21.50 | 1456.87 | 0.00 | -50.43 | -88.49 | -326.46 |
| 8.5in Open Hole | 1500.00 | 18059.14 | 16559.14 | 1456.87 | 7384.50 | -88.49 | -326.46 | 9358.73 | -3052.51 |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 61 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

SURVEY PROGRAM - Offset Wellbore: BUFORD 33-5-3L PWB Offset Wellpath: BUFORD 33-5-3L (REV-A.0) PWP

| Start MD [ft] | End MD [ft] | Positional Uncertainty Model | Log Name/Comment | Wellbore |
|------------------|----------------|---|------------------|--------------------|
| 20.50 | 1500.00 | BH NaviTrak (2019) (Standard) | | BUFORD 33-5-3L PWB |
| 1500.00 | 18059.14 | BH AutoTrak Curve/eXpress (2019) (Standard) | | BUFORD 33-5-3L PWB |

OFFSET WELLPATH REFERENCE - Offset Wellbore: BUFORD 33-5-3L PWB Offset Wellpath: BUFORD 33-5-3L (REV-A.0) PWP

| | |
|---------------------------------|---|
| MD Reference: RIG (20.5') (RKB) | Offset TVD & local coordinates use Reference Wellpath settings (See WELLPATH DATUM on page 1 of this report) |
| Ellipse Start MD | 20.50ft |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 62 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-2-2L PWB Offset Wellpath: BUFORD 33-2-2L (REV-B.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#09 BUFORD 33-2-2L (770'FSL & 944'FWL, SEC.34) Well: BUFORD 33-2-2L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | | |
| 20.50 | 20.50 | 0.00 | 0.00 | 20.50 | 20.50 | 0.00 | 126.07 | 90.00 | 126.07 | 9.75 | 116.32 | 21.19 | PASS | | | |
| 120.50† | 120.50 | 0.00 | 0.00 | 120.50 | 120.50 | 0.00 | 126.07 | 90.00 | 126.07 | 9.81 | 116.25 | 20.94 | PASS | | | |
| 200.00 | 200.00 | 0.00 | 0.00 | 200.00 | 200.00 | 0.00 | 126.07 | 90.00 | 126.07 | 9.96 | 116.11 | 20.42 | PASS | | | |
| 220.50† | 220.50 | -0.03 | -0.07 | 220.50 | 220.50 | 0.00 | 126.07 | 89.99 | 126.14 | 10.01 | 116.12 | 20.26 | PASS | | | |
| 320.50† | 320.46 | -0.93 | -2.36 | 320.46 | 320.46 | 0.00 | 126.07 | 89.58 | 128.43 | 10.41 | 118.02 | 19.37 | PASS | | | |
| 420.50† | 420.28 | -3.13 | -7.88 | 420.28 | 420.28 | 0.00 | 126.07 | 88.66 | 133.99 | 11.09 | 122.90 | 18.29 | PASS | | | |
| 520.50† | 519.83 | -6.60 | -16.65 | 519.83 | 519.83 | 0.00 | 126.07 | 87.35 | 142.87 | 11.83 | 131.04 | 17.71 | PASS | | | |
| 620.50† | 618.99 | -11.36 | -28.64 | 618.99 | 618.99 | 0.00 | 126.07 | 85.80 | 155.12 | 12.60 | 142.52 | 17.54 | PASS | | | |
| 720.50† | 717.64 | -17.38 | -43.83 | 717.64 | 717.64 | 0.00 | 126.07 | 84.16 | 170.79 | 13.40 | 157.39 | 17.71 | PASS | | | |
| 820.50† | 815.66 | -24.68 | -62.22 | 815.66 | 815.66 | 0.00 | 126.07 | 82.53 | 189.90 | 14.22 | 175.68 | 18.16 | PASS | | | |
| 920.50† | 912.93 | -33.22 | -83.78 | 913.92 | 913.92 | -0.01 | 126.04 | 81.01 | 212.43 | 15.03 | 197.40 | 18.87 | PASS | | | |
| 1020.50† | 1009.33 | -43.02 | -108.48 | 1018.80 | 1018.77 | -1.07 | 123.85 | 79.77 | 236.28 | 15.99 | 220.29 | 19.35 | PASS | | | |
| 1120.50† | 1104.74 | -54.05 | -136.29 | 1124.70 | 1124.47 | -3.83 | 118.14 | 78.83 | 260.09 | 17.04 | 243.05 | 19.61 | PASS | | | |
| 1220.50† | 1199.05 | -66.30 | -167.18 | 1231.63 | 1230.89 | -8.33 | 108.80 | 78.14 | 283.80 | 18.09 | 265.70 | 19.84 | PASS | | | |
| 1242.54 | 1219.68 | -69.16 | -174.40 | 1255.33 | 1254.42 | -9.56 | 106.25 | 78.01 | 289.00 | 18.30 | 270.70 | 19.91 | PASS | | | |
| 1320.50† | 1292.54 | -79.39 | -200.20 | 1339.86 | 1338.13 | -14.64 | 95.71 | 77.66 | 306.32 | 19.03 | 287.29 | 20.09 | PASS | | | |
| 1420.50† | 1385.99 | -92.51 | -233.28 | 1449.84 | 1446.47 | -22.85 | 78.69 | 77.41 | 325.33 | 19.91 | 305.42 | 20.18 | PASS | | | |
| 1520.50† | 1479.44 | -105.63 | -266.37 | 1561.29 | 1555.44 | -33.01 | 57.63 | 77.37 | 340.62 | 20.39 | 320.23 | 20.52 | PASS | | | |
| 1620.50† | 1572.89 | -118.75 | -299.46 | 1673.91 | 1664.54 | -45.14 | 32.49 | 77.50 | 352.14 | 20.58 | 331.56 | 20.98 | PASS | | | |
| 1720.50† | 1666.34 | -131.87 | -332.54 | 1787.37 | 1773.24 | -59.23 | 3.27 | 77.79 | 359.83 | 20.81 | 339.02 | 21.15 | PASS | | | |
| 1820.50† | 1759.79 | -144.99 | -365.63 | 1889.34 | 1870.19 | -72.97 | -25.20 | 78.05 | 365.05 | 21.07 | 343.99 | 21.14 | PASS | | | |
| 1920.50† | 1853.24 | -158.12 | -398.72 | 1989.19 | 1965.11 | -86.44 | -53.14 | 78.28 | 370.24 | 21.35 | 348.89 | 21.09 | PASS | | | |
| 2020.50† | 1946.69 | -171.24 | -431.80 | 2089.05 | 2060.03 | -99.92 | -81.07 | 78.51 | 375.43 | 21.75 | 353.68 | 20.91 | PASS | | | |
| 2120.50† | 2040.14 | -184.36 | -464.89 | 2188.90 | 2154.94 | -113.39 | -109.00 | 78.72 | 380.62 | 22.17 | 358.45 | 20.71 | PASS | | | |
| 2220.50† | 2133.59 | -197.48 | -497.98 | 2288.76 | 2249.86 | -126.87 | -136.93 | 78.93 | 385.82 | 22.65 | 363.17 | 20.45 | PASS | | | |
| 2320.50† | 2227.05 | -210.60 | -531.06 | 2388.62 | 2344.78 | -140.34 | -164.86 | 79.14 | 391.03 | 23.19 | 367.84 | 20.15 | PASS | | | |
| 2420.50† | 2320.50 | -223.72 | -564.15 | 2488.47 | 2439.70 | -153.81 | -192.79 | 79.34 | 396.24 | 23.77 | 372.46 | 19.82 | PASS | | | |
| 2520.50† | 2413.95 | -236.84 | -597.24 | 2588.33 | 2534.62 | -167.29 | -220.72 | 79.53 | 401.45 | 24.40 | 377.05 | 19.47 | PASS | | | |
| 2620.50† | 2507.40 | -249.96 | -630.32 | 2688.18 | 2629.53 | -180.76 | -248.66 | 79.72 | 406.67 | 25.07 | 381.60 | 19.10 | PASS | | | |
| 2720.50† | 2600.85 | -263.08 | -663.41 | 2788.04 | 2724.45 | -194.23 | -276.58 | 79.91 | 411.89 | 25.78 | 386.11 | 18.72 | PASS | | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 63 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-2-2L PWB Offset Wellpath: BUFORD 33-2-2L (REV-B.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W | | Slot: SLOT#09 BUFORD 33-2-2L (770'FSL & 944'FWL, SEC.34) | | Well: BUFORD 33-2-2L | | Threshold Value=1.00 | | ↑ = interpolated, † = extrapolated station | | | | | | | |
|----------------------------|-----------------|--|------------------|----------------------|--------------------|----------------------|---------------------|--|---------------------------|----------------------|----------------------------|--------------|----------------|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | |
| 2820.50† | 2694.30 | -276.20 | -696.50 | 2887.89 | 2819.37 | -207.71 | -304.52 | 80.09 | 417.11 | 26.52 | 390.60 | 18.34 | PASS | | |
| 2920.50† | 2787.75 | -289.33 | -729.58 | 2987.75 | 2914.29 | -221.18 | -332.45 | 80.26 | 422.34 | 27.29 | 395.05 | 17.95 | PASS | | |
| 3020.50† | 2881.20 | -302.45 | -762.67 | 3087.61 | 3009.21 | -234.65 | -360.38 | 80.44 | 427.57 | 28.08 | 399.49 | 17.58 | PASS | | |
| 3120.50† | 2974.65 | -315.57 | -795.76 | 3187.46 | 3104.13 | -248.13 | -388.31 | 80.60 | 432.81 | 28.91 | 403.90 | 17.20 | PASS | | |
| 3220.50† | 3068.11 | -328.69 | -828.84 | 3287.32 | 3199.04 | -261.60 | -416.24 | 80.77 | 438.05 | 29.76 | 408.29 | 16.84 | PASS | | |
| 3320.50† | 3161.56 | -341.81 | -861.93 | 3387.17 | 3293.96 | -275.07 | -444.17 | 80.92 | 443.29 | 30.63 | 412.66 | 16.49 | PASS | | |
| 3420.50† | 3255.01 | -354.93 | -895.02 | 3487.03 | 3388.88 | -288.55 | -472.11 | 81.08 | 448.53 | 31.51 | 417.02 | 16.15 | PASS | | |
| 3520.50† | 3348.46 | -368.05 | -928.10 | 3586.88 | 3483.80 | -302.02 | -500.04 | 81.23 | 453.78 | 32.42 | 421.36 | 15.82 | PASS | | |
| 3620.50† | 3441.91 | -381.17 | -961.19 | 3686.74 | 3578.72 | -315.50 | -527.97 | 81.38 | 459.03 | 33.34 | 425.69 | 15.50 | PASS | | |
| 3720.50† | 3535.36 | -394.29 | -994.28 | 3786.59 | 3673.63 | -328.97 | -555.90 | 81.53 | 464.29 | 34.28 | 430.01 | 15.19 | PASS | | |
| 3820.50† | 3628.81 | -407.41 | -1027.37 | 3886.45 | 3768.55 | -342.44 | -583.83 | 81.67 | 469.54 | 35.23 | 434.31 | 14.90 | PASS | | |
| 3920.50† | 3722.26 | -420.53 | -1060.45 | 3986.31 | 3863.47 | -355.92 | -611.76 | 81.81 | 474.80 | 36.20 | 438.61 | 14.62 | PASS | | |
| 4020.50† | 3815.71 | -433.66 | -1093.54 | 4086.16 | 3958.39 | -369.39 | -639.69 | 81.94 | 480.06 | 37.17 | 442.89 | 14.35 | PASS | | |
| 4120.50† | 3909.17 | -446.78 | -1126.63 | 4186.02 | 4053.31 | -382.86 | -667.62 | 82.07 | 485.33 | 38.16 | 447.17 | 14.09 | PASS | | |
| 4220.50† | 4002.62 | -459.90 | -1159.71 | 4285.87 | 4148.22 | -396.34 | -695.56 | 82.20 | 490.59 | 39.15 | 451.44 | 13.84 | PASS | | |
| 4320.50† | 4096.07 | -473.02 | -1192.80 | 4385.73 | 4243.14 | -409.81 | -723.49 | 82.33 | 495.86 | 40.16 | 455.70 | 13.60 | PASS | | |
| 4420.50† | 4189.52 | -486.14 | -1225.89 | 4485.58 | 4338.06 | -423.28 | -751.42 | 82.45 | 501.13 | 41.17 | 459.96 | 13.37 | PASS | | |
| 4520.50† | 4282.97 | -499.26 | -1258.97 | 4585.44 | 4432.98 | -436.76 | -779.35 | 82.58 | 506.41 | 42.20 | 464.21 | 13.15 | PASS | | |
| 4620.50† | 4376.42 | -512.38 | -1292.06 | 4685.29 | 4527.90 | -450.23 | -807.28 | 82.69 | 511.68 | 43.22 | 468.46 | 12.94 | PASS | | |
| 4720.50† | 4469.87 | -525.50 | -1325.15 | 4785.15 | 4622.82 | -463.70 | -835.21 | 82.81 | 516.96 | 44.26 | 472.70 | 12.74 | PASS | | |
| 4820.50† | 4563.32 | -538.62 | -1358.23 | 4885.01 | 4717.73 | -477.18 | -863.14 | 82.93 | 522.24 | 45.30 | 476.93 | 12.54 | PASS | | |
| 4920.50† | 4656.77 | -551.74 | -1391.32 | 4984.86 | 4812.65 | -490.65 | -891.07 | 83.04 | 527.52 | 46.35 | 481.17 | 12.36 | PASS | | |
| 5020.50† | 4750.22 | -564.87 | -1424.41 | 5084.72 | 4907.57 | -504.13 | -919.01 | 83.15 | 532.80 | 47.41 | 485.39 | 12.18 | PASS | | |
| 5120.50† | 4843.68 | -577.99 | -1457.49 | 5184.57 | 5002.49 | -517.60 | -946.94 | 83.26 | 538.09 | 48.47 | 489.62 | 12.01 | PASS | | |
| 5220.50† | 4937.13 | -591.11 | -1490.58 | 5284.43 | 5097.41 | -531.07 | -974.87 | 83.36 | 543.37 | 49.53 | 493.84 | 11.84 | PASS | | |
| 5320.50† | 5030.58 | -604.23 | -1523.67 | 5384.28 | 5192.32 | -544.55 | -1002.80 | 83.46 | 548.66 | 50.60 | 498.06 | 11.68 | PASS | | |
| 5420.50† | 5124.03 | -617.35 | -1556.75 | 5484.14 | 5287.24 | -558.02 | -1030.73 | 83.57 | 553.95 | 51.68 | 502.27 | 11.53 | PASS | | |
| 5520.50† | 5217.48 | -630.47 | -1589.84 | 5584.00 | 5382.16 | -571.49 | -1058.66 | 83.66 | 559.24 | 52.76 | 506.48 | 11.38 | PASS | | |
| 5620.50† | 5310.93 | -643.59 | -1622.93 | 5683.85 | 5477.08 | -584.97 | -1086.59 | 83.76 | 564.53 | 53.84 | 510.69 | 11.24 | PASS | | |
| 5720.50† | 5404.38 | -656.71 | -1656.01 | 5783.71 | 5572.00 | -598.44 | -1114.52 | 83.86 | 569.83 | 54.92 | 514.90 | 11.11 | PASS | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 64 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-2-2L PWB Offset Wellpath: BUFORD 33-2-2L (REV-B.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#09 BUFORD 33-2-2L (770'FSL & 944'FWL, SEC.34) Well: BUFORD 33-2-2L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|-----------------|-------------------|------------------|-------------------|--------------------|----------------------|---------------------|-------------------------|---------------------------|----------------------|----------------------------|--------------|----------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 5820.50† | 5497.83 | -669.83 | -1689.10 | 5883.56 | 5666.91 | -611.91 | -1142.46 | 83.95 | 575.12 | 56.01 | 519.11 | 10.98 | PASS |
| 5920.50† | 5591.28 | -682.95 | -1722.19 | 5983.42 | 5761.83 | -625.39 | -1170.39 | 84.04 | 580.42 | 57.11 | 523.31 | 10.85 | PASS |
| 6020.50† | 5684.74 | -696.07 | -1755.27 | 6083.27 | 5856.75 | -638.86 | -1198.32 | 84.14 | 585.72 | 58.20 | 527.51 | 10.73 | PASS |
| 6120.50† | 5778.19 | -709.20 | -1788.36 | 6183.13 | 5951.67 | -652.33 | -1226.25 | 84.22 | 591.01 | 59.30 | 531.71 | 10.61 | PASS |
| 6220.50† | 5871.64 | -722.32 | -1821.45 | 6282.98 | 6046.59 | -665.81 | -1254.18 | 84.31 | 596.32 | 60.41 | 535.91 | 10.50 | PASS |
| 6320.50† | 5965.09 | -735.44 | -1854.54 | 6382.84 | 6141.51 | -679.28 | -1282.11 | 84.40 | 601.62 | 61.51 | 540.11 | 10.39 | PASS |
| 6420.50† | 6058.54 | -748.56 | -1887.62 | 6482.70 | 6236.42 | -692.76 | -1310.04 | 84.48 | 606.92 | 62.62 | 544.30 | 10.28 | PASS |
| 6520.50† | 6151.99 | -761.68 | -1920.71 | 6582.55 | 6331.34 | -706.23 | -1337.98 | 84.56 | 612.23 | 63.73 | 548.49 | 10.18 | PASS |
| 6620.50† | 6245.44 | -774.80 | -1953.80 | 6682.41 | 6426.26 | -719.70 | -1365.91 | 84.65 | 617.53 | 64.84 | 552.69 | 10.08 | PASS |
| 6720.50† | 6338.89 | -787.92 | -1986.88 | 6782.26 | 6521.18 | -733.18 | -1393.84 | 84.73 | 622.84 | 65.96 | 556.88 | 9.99 | PASS |
| 6820.50† | 6432.34 | -801.04 | -2019.97 | 6882.12 | 6616.10 | -746.65 | -1421.77 | 84.81 | 628.15 | 67.08 | 561.07 | 9.89 | PASS |
| 6920.50† | 6525.80 | -814.16 | -2053.06 | 6981.97 | 6711.01 | -760.12 | -1449.70 | 84.88 | 633.45 | 68.20 | 565.26 | 9.80 | PASS |
| 7020.50† | 6619.25 | -827.28 | -2086.14 | 7081.83 | 6805.93 | -773.60 | -1477.63 | 84.96 | 638.76 | 69.32 | 569.45 | 9.72 | PASS |
| 7120.50† | 6712.70 | -840.41 | -2119.23 | 7172.74 | 6892.81 | -779.98 | -1503.21 | 84.40 | 644.65 | 70.07 | 574.58 | 9.69 | PASS |
| 7220.50† | 6806.15 | -853.53 | -2152.32 | 7257.22 | 6973.25 | -770.69 | -1526.92 | 82.46 | 652.61 | 71.02 | 581.59 | 9.68 | PASS |
| 7320.50† | 6899.60 | -866.65 | -2185.40 | 7332.64 | 7042.73 | -750.02 | -1547.44 | 79.64 | 664.15 | 70.12 | 594.02 | 9.98 | PASS |
| 7341.07 | 6918.82 | -869.35 | -2192.21 | 7346.82 | 7055.41 | -744.87 | -1551.18 | 79.01 | 667.13 | 70.23 | 596.90 | 10.01 | PASS |
| 7420.50† | 6993.49 | -874.29 | -2218.65 | 7399.49 | 7101.04 | -722.37 | -1564.67 | 76.92 | 679.95 | 69.85 | 610.10 | 10.26 | PASS |
| 7520.50† | 7087.21 | -864.88 | -2251.87 | 7462.82 | 7152.35 | -688.59 | -1579.86 | 75.30 | 697.79 | 69.89 | 627.90 | 10.53 | PASS |
| 7620.50† | 7177.96 | -838.35 | -2284.05 | 7523.62 | 7197.16 | -649.77 | -1593.14 | 74.73 | 716.44 | 70.01 | 646.43 | 10.79 | PASS |
| 7720.50† | 7262.97 | -795.51 | -2314.23 | 7582.51 | 7235.72 | -606.80 | -1604.59 | 75.11 | 734.81 | 69.90 | 664.91 | 11.09 | PASS |
| 7820.50† | 7339.68 | -737.65 | -2341.49 | 7639.95 | 7268.16 | -560.43 | -1614.25 | 76.31 | 751.93 | 69.48 | 682.45 | 11.42 | PASS |
| 7920.50† | 7405.75 | -666.53 | -2364.99 | 7696.31 | 7294.56 | -511.31 | -1622.13 | 78.20 | 767.00 | 68.85 | 698.15 | 11.76 | PASS |
| 8020.50† | 7459.16 | -584.32 | -2384.03 | 7751.86 | 7314.99 | -460.04 | -1628.26 | 80.66 | 779.37 | 68.21 | 711.16 | 12.07 | PASS |
| 8120.50† | 7498.30 | -493.50 | -2398.02 | 7806.85 | 7329.44 | -407.20 | -1632.63 | 83.57 | 788.54 | 67.74 | 720.80 | 12.31 | PASS |
| 8220.50† | 7521.99 | -396.85 | -2406.55 | 7861.49 | 7337.94 | -353.32 | -1635.25 | 86.77 | 794.15 | 67.54 | 726.60 | 12.43 | PASS |
| 8315.56 | 7529.50 | -302.24 | -2409.34 | 7913.80 | 7340.50 | -301.10 | -1636.11 | 89.92 | 795.99 | 67.70 | 728.29 | 12.43 | PASS |
| 8320.50† | 7529.51 | -297.30 | -2409.35 | 7918.74 | 7340.49 | -296.16 | -1636.12 | 89.92 | 796.00 | 67.67 | 728.33 | 12.44 | PASS |
| 8420.50† | 7529.61 | -197.30 | -2409.53 | 8018.74 | 7340.37 | -196.16 | -1636.30 | 89.92 | 796.05 | 67.00 | 729.05 | 12.57 | PASS |
| 8520.50† | 7529.71 | -97.30 | -2409.71 | 8118.74 | 7340.24 | -96.16 | -1636.48 | 89.92 | 796.10 | 66.69 | 729.42 | 12.63 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 65 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-2-2L PWB Offset Wellpath: BUFORD 33-2-2L (REV-B.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#09 BUFORD 33-2-2L (770'FSL & 944'FWL, SEC.34) Well: BUFORD 33-2-2L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | | |
| 8620.50† | 7529.82 | 2.70 | -2409.88 | 8218.74 | 7340.12 | 3.84 | -1636.66 | 89.92 | 796.16 | 66.61 | 729.55 | 12.65 | PASS | | | |
| 8720.50† | 7529.92 | 102.70 | -2410.06 | 8318.74 | 7339.99 | 103.84 | -1636.83 | 89.92 | 796.21 | 66.76 | 729.45 | 12.62 | PASS | | | |
| 8820.50† | 7530.02 | 202.70 | -2410.24 | 8418.74 | 7339.87 | 203.84 | -1637.01 | 89.92 | 796.27 | 67.14 | 729.12 | 12.54 | PASS | | | |
| 8920.50† | 7530.13 | 302.70 | -2410.42 | 8518.74 | 7339.75 | 303.84 | -1637.19 | 89.92 | 796.32 | 67.75 | 728.57 | 12.43 | PASS | | | |
| 9020.50† | 7530.23 | 402.70 | -2410.59 | 8618.74 | 7339.62 | 403.83 | -1637.37 | 89.92 | 796.37 | 68.58 | 727.79 | 12.27 | PASS | | | |
| 9120.50† | 7530.33 | 502.70 | -2410.77 | 8718.74 | 7339.50 | 503.83 | -1637.55 | 89.92 | 796.43 | 69.62 | 726.81 | 12.07 | PASS | | | |
| 9220.50† | 7530.44 | 602.70 | -2410.95 | 8818.74 | 7339.37 | 603.83 | -1637.72 | 89.92 | 796.48 | 70.87 | 725.62 | 11.85 | PASS | | | |
| 9320.50† | 7530.54 | 702.70 | -2411.13 | 8918.74 | 7339.25 | 703.83 | -1637.90 | 89.92 | 796.54 | 72.30 | 724.24 | 11.60 | PASS | | | |
| 9420.50† | 7530.64 | 802.69 | -2411.31 | 9018.74 | 7339.12 | 803.83 | -1638.08 | 89.92 | 796.59 | 73.91 | 722.68 | 11.33 | PASS | | | |
| 9520.50† | 7530.75 | 902.69 | -2411.48 | 9118.74 | 7339.00 | 903.83 | -1638.26 | 89.92 | 796.65 | 75.69 | 720.96 | 11.05 | PASS | | | |
| 9620.50† | 7530.85 | 1002.69 | -2411.66 | 9218.74 | 7338.88 | 1003.83 | -1638.44 | 89.92 | 796.70 | 77.62 | 719.08 | 10.76 | PASS | | | |
| 9720.50† | 7530.96 | 1102.69 | -2411.84 | 9318.74 | 7338.75 | 1103.83 | -1638.61 | 89.92 | 796.76 | 79.70 | 717.06 | 10.47 | PASS | | | |
| 9820.50† | 7531.06 | 1202.69 | -2412.02 | 9418.74 | 7338.63 | 1203.83 | -1638.79 | 89.92 | 796.81 | 81.91 | 714.90 | 10.17 | PASS | | | |
| 9920.50† | 7531.16 | 1302.69 | -2412.19 | 9518.74 | 7338.50 | 1303.83 | -1638.97 | 89.92 | 796.87 | 84.23 | 712.63 | 9.88 | PASS | | | |
| 10020.50† | 7531.27 | 1402.69 | -2412.37 | 9618.74 | 7338.38 | 1403.83 | -1639.15 | 89.92 | 796.92 | 86.67 | 710.25 | 9.59 | PASS | | | |
| 10120.50† | 7531.37 | 1502.69 | -2412.55 | 9718.74 | 7338.25 | 1503.83 | -1639.33 | 89.92 | 796.98 | 89.21 | 707.77 | 9.30 | PASS | | | |
| 10220.50† | 7531.47 | 1602.69 | -2412.73 | 9818.74 | 7338.13 | 1603.83 | -1639.50 | 89.92 | 797.03 | 91.84 | 705.19 | 9.03 | PASS | | | |
| 10320.50† | 7531.58 | 1702.69 | -2412.90 | 9918.74 | 7338.00 | 1703.83 | -1639.68 | 89.92 | 797.09 | 94.55 | 702.53 | 8.76 | PASS | | | |
| 10420.50† | 7531.68 | 1802.69 | -2413.08 | 10018.74 | 7337.88 | 1803.83 | -1639.86 | 89.92 | 797.14 | 97.34 | 699.80 | 8.50 | PASS | | | |
| 10520.50† | 7531.78 | 1902.69 | -2413.26 | 10118.74 | 7337.76 | 1903.83 | -1640.04 | 89.92 | 797.20 | 100.20 | 696.99 | 8.24 | PASS | | | |
| 10620.50† | 7531.89 | 2002.69 | -2413.44 | 10218.74 | 7337.63 | 2003.83 | -1640.22 | 89.92 | 797.25 | 103.12 | 694.13 | 8.00 | PASS | | | |
| 10720.50† | 7531.99 | 2102.69 | -2413.62 | 10318.74 | 7337.51 | 2103.83 | -1640.39 | 89.92 | 797.31 | 106.11 | 691.20 | 7.77 | PASS | | | |
| 10820.50† | 7532.09 | 2202.69 | -2413.79 | 10418.74 | 7337.38 | 2203.83 | -1640.57 | 89.92 | 797.36 | 109.14 | 688.22 | 7.54 | PASS | | | |
| 10920.50† | 7532.20 | 2302.69 | -2413.97 | 10518.74 | 7337.26 | 2303.83 | -1640.75 | 89.92 | 797.42 | 112.22 | 685.19 | 7.33 | PASS | | | |
| 11020.50† | 7532.30 | 2402.69 | -2414.15 | 10618.74 | 7337.13 | 2403.82 | -1640.93 | 89.92 | 797.47 | 115.35 | 682.12 | 7.12 | PASS | | | |
| 11120.50† | 7532.41 | 2502.69 | -2414.33 | 10718.74 | 7337.01 | 2503.82 | -1641.11 | 89.92 | 797.53 | 118.52 | 679.01 | 6.93 | PASS | | | |
| 11220.50† | 7532.51 | 2602.69 | -2414.50 | 10818.74 | 7336.89 | 2603.82 | -1641.28 | 89.92 | 797.58 | 121.73 | 675.86 | 6.74 | PASS | | | |
| 11320.50† | 7532.61 | 2702.69 | -2414.68 | 10918.74 | 7336.76 | 2703.82 | -1641.46 | 89.92 | 797.64 | 124.97 | 672.67 | 6.56 | PASS | | | |
| 11420.50† | 7532.72 | 2802.69 | -2414.86 | 11018.73 | 7336.64 | 2803.82 | -1641.64 | 89.92 | 797.69 | 128.24 | 669.45 | 6.39 | PASS | | | |
| 11520.50† | 7532.82 | 2902.69 | -2415.04 | 11118.73 | 7336.51 | 2903.82 | -1641.82 | 89.92 | 797.75 | 131.54 | 666.21 | 6.22 | PASS | | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 66 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-2-2L PWB Offset Wellpath: BUFORD 33-2-2L (REV-B.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#09 BUFORD 33-2-2L (770'FSL & 944'FWL, SEC.34) Well: BUFORD 33-2-2L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | |
| 11620.50† | 7532.92 | 3002.69 | -2415.21 | 11218.73 | 7336.39 | 3003.82 | -1642.00 | 89.92 | 797.81 | 134.87 | 662.94 | 6.06 | PASS | |
| 11720.50† | 7533.03 | 3102.69 | -2415.39 | 11318.73 | 7336.26 | 3103.82 | -1642.17 | 89.92 | 797.86 | 138.22 | 659.64 | 5.91 | PASS | |
| 11820.50† | 7533.13 | 3202.69 | -2415.57 | 11418.73 | 7336.14 | 3203.82 | -1642.35 | 89.92 | 797.92 | 141.60 | 656.32 | 5.77 | PASS | |
| 11920.50† | 7533.23 | 3302.69 | -2415.75 | 11518.73 | 7336.01 | 3303.82 | -1642.53 | 89.92 | 797.97 | 145.00 | 652.97 | 5.63 | PASS | |
| 12020.50† | 7533.34 | 3402.69 | -2415.92 | 11618.73 | 7335.89 | 3403.82 | -1642.71 | 89.92 | 798.03 | 148.42 | 649.61 | 5.50 | PASS | |
| 12120.50† | 7533.44 | 3502.69 | -2416.10 | 11718.73 | 7335.77 | 3503.82 | -1642.89 | 89.92 | 798.09 | 151.85 | 646.23 | 5.37 | PASS | |
| 12220.50† | 7533.55 | 3602.69 | -2416.28 | 11818.73 | 7335.64 | 3603.82 | -1643.06 | 89.92 | 798.14 | 155.31 | 642.83 | 5.25 | PASS | |
| 12320.50† | 7533.65 | 3702.69 | -2416.46 | 11918.73 | 7335.52 | 3703.82 | -1643.24 | 89.92 | 798.20 | 158.78 | 639.42 | 5.13 | PASS | |
| 12420.50† | 7533.75 | 3802.69 | -2416.64 | 12018.73 | 7335.39 | 3803.82 | -1643.42 | 89.92 | 798.25 | 162.26 | 635.99 | 5.02 | PASS | |
| 12520.50† | 7533.86 | 3902.69 | -2416.81 | 12118.73 | 7335.27 | 3903.82 | -1643.60 | 89.92 | 798.31 | 165.76 | 632.55 | 4.91 | PASS | |
| 12620.50† | 7533.96 | 4002.69 | -2416.99 | 12218.73 | 7335.14 | 4003.82 | -1643.78 | 89.92 | 798.37 | 169.27 | 629.09 | 4.81 | PASS | |
| 12720.50† | 7534.06 | 4102.69 | -2417.17 | 12318.73 | 7335.02 | 4103.82 | -1643.95 | 89.92 | 798.42 | 172.80 | 625.63 | 4.71 | PASS | |
| 12820.50† | 7534.17 | 4202.69 | -2417.35 | 12418.73 | 7334.90 | 4203.82 | -1644.13 | 89.92 | 798.48 | 176.33 | 622.15 | 4.61 | PASS | |
| 12920.50† | 7534.27 | 4302.69 | -2417.52 | 12518.73 | 7334.77 | 4303.82 | -1644.31 | 89.92 | 798.54 | 179.88 | 618.66 | 4.52 | PASS | |
| 13020.50† | 7534.37 | 4402.69 | -2417.70 | 12614.75 | 7334.65 | 4399.83 | -1644.44 | 90.21 | 798.64 | 182.96 | 615.68 | 4.44 | PASS | |
| 13120.50† | 7534.48 | 4502.69 | -2417.88 | 12693.46 | 7334.55 | 4478.53 | -1643.10 | 91.79 | 800.53 | 183.99 | 616.54 | 4.43 | PASS | |
| 13199.97 | 7534.56 | 4582.16 | -2418.02 | 12755.92 | 7334.48 | 4540.94 | -1640.49 | 93.04 | 803.92 | 184.75 | 619.17 | 4.43 | PASS | |
| 13220.50† | 7534.58 | 4602.69 | -2418.13 | 12772.03 | 7334.46 | 4557.02 | -1639.60 | 93.36 | 805.14 | 184.94 | 620.20 | 4.43 | PASS | |
| 13320.50† | 7534.68 | 4702.65 | -2420.77 | 12850.15 | 7334.36 | 4634.93 | -1633.98 | 94.92 | 814.71 | 185.84 | 628.86 | 4.46 | PASS | |
| 13420.50† | 7534.79 | 4802.45 | -2426.90 | 12927.82 | 7334.26 | 4712.23 | -1626.30 | 96.43 | 830.24 | 186.80 | 643.45 | 4.52 | PASS | |
| 13476.50 | 7534.85 | 4858.23 | -2431.85 | 12982.70 | 7334.20 | 4766.76 | -1620.17 | 96.43 | 841.10 | 188.90 | 652.20 | 4.53 | PASS | |
| 13520.50† | 7534.89 | 4902.02 | -2436.16 | 13025.73 | 7334.14 | 4809.52 | -1615.36 | 96.43 | 850.04 | 190.54 | 659.50 | 4.54 | PASS | |
| 13620.50† | 7534.99 | 5001.54 | -2445.98 | 13123.53 | 7334.02 | 4906.71 | -1604.44 | 96.43 | 870.38 | 194.32 | 676.07 | 4.55 | PASS | |
| 13720.50† | 7535.10 | 5101.06 | -2455.79 | 13223.03 | 7333.90 | 5005.59 | -1593.33 | 96.32 | 890.75 | 198.32 | 692.43 | 4.56 | PASS | |
| 13820.50† | 7535.20 | 5200.57 | -2465.61 | 13364.74 | 7333.72 | 5146.76 | -1581.27 | 93.48 | 908.59 | 207.45 | 701.14 | 4.45 | PASS | |
| 13920.50† | 7535.30 | 5300.09 | -2475.42 | 13508.72 | 7333.54 | 5290.64 | -1576.18 | 90.60 | 921.64 | 216.30 | 705.34 | 4.32 | PASS | |
| 14020.50† | 7535.40 | 5399.61 | -2485.24 | 13631.93 | 7333.39 | 5413.84 | -1577.17 | 89.10 | 930.38 | 222.56 | 707.82 | 4.24 | PASS | |
| 14120.50† | 7535.51 | 5499.12 | -2495.05 | 13731.59 | 7333.27 | 5513.49 | -1578.76 | 89.10 | 938.46 | 228.35 | 712.11 | 4.20 | PASS | |
| 14220.50† | 7535.61 | 5598.64 | -2504.87 | 13831.25 | 7333.15 | 5613.14 | -1580.35 | 89.10 | 946.54 | 230.15 | 716.39 | 4.17 | PASS | |
| 14221.87 | 7535.61 | 5600.00 | -2505.00 | 13832.61 | 7333.14 | 5614.50 | -1580.37 | 89.10 | 946.65 | 230.20 | 716.45 | 4.17 | PASS | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 67 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-2-2L PWB Offset Wellpath: BUFORD 33-2-2L (REV-B.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#09 BUFORD 33-2-2L (770'FSL & 944'FWL,SEC.34) Well: BUFORD 33-2-2L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|-----------------|-------------------|------------------|-------------------|--------------------|----------------------|---------------------|-------------------------|---------------------------|----------------------|----------------------------|--------------|----------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 14320.50† | 7535.71 | 5698.31 | -2512.99 | 13931.03 | 7333.02 | 5712.91 | -1581.94 | 89.10 | 952.97 | 233.92 | 719.05 | 4.13 | PASS |
| 14420.50† | 7535.81 | 5798.19 | -2517.63 | 14030.98 | 7332.90 | 5812.84 | -1583.53 | 89.10 | 956.00 | 237.67 | 718.33 | 4.07 | PASS |
| 14520.50† | 7535.92 | 5898.18 | -2518.78 | 14130.97 | 7332.77 | 5912.82 | -1585.13 | 89.10 | 955.61 | 241.37 | 714.24 | 4.01 | PASS |
| 14581.38 | 7535.98 | 5959.05 | -2517.77 | 14191.82 | 7332.70 | 5973.66 | -1586.10 | 89.10 | 953.71 | 243.59 | 710.12 | 3.96 | PASS |
| 14620.50† | 7536.02 | 5998.16 | -2516.71 | 14230.90 | 7332.65 | 6012.74 | -1586.72 | 89.10 | 952.08 | 245.00 | 707.08 | 3.93 | PASS |
| 14720.50† | 7536.12 | 6098.12 | -2513.99 | 14330.81 | 7332.53 | 6112.63 | -1588.31 | 89.10 | 947.91 | 248.61 | 699.30 | 3.86 | PASS |
| 14820.50† | 7536.23 | 6198.08 | -2511.27 | 14430.72 | 7332.40 | 6212.53 | -1589.91 | 89.10 | 943.75 | 252.24 | 691.51 | 3.79 | PASS |
| 14920.50† | 7536.33 | 6298.05 | -2508.55 | 14530.62 | 7332.28 | 6312.42 | -1591.50 | 89.10 | 939.59 | 255.87 | 683.72 | 3.71 | PASS |
| 15020.50† | 7536.43 | 6398.01 | -2505.83 | 14630.53 | 7332.16 | 6412.32 | -1593.09 | 89.10 | 935.43 | 259.50 | 675.93 | 3.65 | PASS |
| 15120.50† | 7536.54 | 6497.97 | -2503.11 | 14730.44 | 7332.03 | 6512.21 | -1594.69 | 89.10 | 931.27 | 263.13 | 668.14 | 3.58 | PASS |
| 15220.50† | 7536.64 | 6597.93 | -2500.40 | 14830.34 | 7331.91 | 6612.10 | -1596.28 | 89.10 | 927.11 | 266.77 | 660.35 | 3.51 | PASS |
| 15320.50† | 7536.74 | 6697.90 | -2497.68 | 14930.25 | 7331.79 | 6712.00 | -1597.87 | 89.10 | 922.96 | 270.40 | 652.56 | 3.45 | PASS |
| 15420.50† | 7536.85 | 6797.86 | -2494.96 | 15030.16 | 7331.66 | 6811.89 | -1599.47 | 89.10 | 918.80 | 274.04 | 644.77 | 3.39 | PASS |
| 15520.50† | 7536.95 | 6897.82 | -2492.24 | 15130.06 | 7331.54 | 6911.78 | -1601.06 | 89.10 | 914.65 | 277.67 | 636.98 | 3.33 | PASS |
| 15620.50† | 7537.05 | 6997.79 | -2489.52 | 15229.97 | 7331.42 | 7011.68 | -1602.65 | 89.10 | 910.50 | 281.31 | 629.20 | 3.27 | PASS |
| 15720.50† | 7537.16 | 7097.75 | -2486.80 | 15329.88 | 7331.29 | 7111.57 | -1604.25 | 89.10 | 906.35 | 284.94 | 621.41 | 3.21 | PASS |
| 15820.50† | 7537.26 | 7197.71 | -2484.08 | 15429.78 | 7331.17 | 7211.47 | -1605.84 | 89.10 | 902.20 | 288.58 | 613.63 | 3.16 | PASS |
| 15920.50† | 7537.36 | 7297.68 | -2481.36 | 15529.69 | 7331.04 | 7311.36 | -1607.43 | 89.10 | 898.06 | 292.21 | 605.84 | 3.10 | PASS |
| 16020.50† | 7537.47 | 7397.64 | -2478.64 | 15629.60 | 7330.92 | 7411.25 | -1609.03 | 89.10 | 893.91 | 295.85 | 598.06 | 3.05 | PASS |
| 16120.50† | 7537.57 | 7497.60 | -2475.93 | 15729.50 | 7330.80 | 7511.15 | -1610.62 | 89.10 | 889.77 | 299.48 | 590.29 | 3.00 | PASS |
| 16220.50† | 7537.68 | 7597.56 | -2473.21 | 15829.41 | 7330.67 | 7611.04 | -1612.21 | 89.10 | 885.63 | 303.12 | 582.51 | 2.95 | PASS |
| 16320.50† | 7537.78 | 7697.53 | -2470.49 | 15929.32 | 7330.55 | 7710.94 | -1613.81 | 89.10 | 881.49 | 306.75 | 574.74 | 2.90 | PASS |
| 16420.50† | 7537.88 | 7797.49 | -2467.77 | 16029.22 | 7330.43 | 7810.83 | -1615.40 | 89.10 | 877.35 | 310.39 | 566.97 | 2.85 | PASS |
| 16520.50† | 7537.99 | 7897.45 | -2465.05 | 16129.13 | 7330.30 | 7910.72 | -1616.99 | 89.10 | 873.22 | 314.02 | 559.20 | 2.80 | PASS |
| 16620.50† | 7538.09 | 7997.42 | -2462.33 | 16229.04 | 7330.18 | 8010.62 | -1618.59 | 89.10 | 869.08 | 317.65 | 551.44 | 2.76 | PASS |
| 16720.50† | 7538.19 | 8097.38 | -2459.61 | 16328.94 | 7330.06 | 8110.51 | -1620.18 | 89.10 | 864.95 | 321.28 | 543.67 | 2.71 | PASS |
| 16820.50† | 7538.30 | 8197.34 | -2456.89 | 16428.85 | 7329.93 | 8210.41 | -1621.77 | 89.10 | 860.82 | 324.90 | 535.92 | 2.67 | PASS |
| 16920.50† | 7538.40 | 8297.31 | -2454.17 | 16528.76 | 7329.81 | 8310.30 | -1623.37 | 89.10 | 856.69 | 328.53 | 528.16 | 2.63 | PASS |
| 17020.50† | 7538.50 | 8397.27 | -2451.46 | 16628.66 | 7329.69 | 8410.19 | -1624.96 | 89.10 | 852.56 | 332.15 | 520.41 | 2.59 | PASS |
| 17120.50† | 7538.61 | 8497.23 | -2448.74 | 16728.57 | 7329.56 | 8510.09 | -1626.55 | 89.10 | 848.44 | 335.78 | 512.66 | 2.55 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 68 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-2-2L PWB Offset Wellpath: BUFORD 33-2-2L (REV-B.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#09 BUFORD 33-2-2L (770'FSL & 944'FWL, SEC.34) Well: BUFORD 33-2-2L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 17220.50† | 7538.71 | 8597.19 | -2446.02 | 16828.48 | 7329.44 | 8609.98 | -1628.15 | 89.10 | 844.32 | 339.40 | 504.92 | 2.51 | PASS |
| 17320.50† | 7538.81 | 8697.16 | -2443.30 | 16939.71 | 7329.30 | 8721.19 | -1630.20 | 88.31 | 840.00 | 344.23 | 495.78 | 2.46 | PASS |
| 17420.50† | 7538.92 | 8797.12 | -2440.58 | 17043.10 | 7329.17 | 8824.53 | -1633.71 | 88.06 | 834.13 | 348.16 | 485.97 | 2.41 | PASS |
| 17520.50† | 7539.02 | 8897.08 | -2437.86 | 17142.91 | 7329.05 | 8924.28 | -1637.14 | 88.06 | 828.25 | 351.73 | 476.51 | 2.37 | PASS |
| 17620.50† | 7539.12 | 8997.05 | -2435.14 | 17242.73 | 7328.92 | 9024.03 | -1640.56 | 88.06 | 822.36 | 355.30 | 467.07 | 2.33 | PASS |
| 17720.50† | 7539.23 | 9097.01 | -2432.42 | 17342.54 | 7328.80 | 9123.78 | -1643.98 | 88.06 | 816.48 | 358.86 | 457.63 | 2.29 | PASS |
| 17820.50† | 7539.33 | 9196.97 | -2429.70 | 17442.35 | 7328.68 | 9223.54 | -1647.40 | 88.06 | 810.61 | 362.41 | 448.20 | 2.25 | PASS |
| 17920.50† | 7539.43 | 9296.94 | -2426.99 | 17542.16 | 7328.55 | 9323.29 | -1650.82 | 88.06 | 804.74 | 365.96 | 438.78 | 2.21 | PASS |
| 17963.20† | 7539.48 | 9339.62 | -2425.83 | 17584.78 | 7328.50 | 9365.89 | -1652.28 | 88.06 | 802.23 | 367.47 | 434.76 | 2.20 | PASS |
| 17985.90 | 7539.50 | 9362.31 | -2425.21 | 17584.78 | 7328.50 | 9365.89 | -1652.28 | 89.74 | 801.22 | 365.72 | 435.50 | 2.20 | PASS |

POSITIONAL UNCERTAINTY - Offset Wellbore: BUFORD 33-2-2L PWB Offset Wellpath: BUFORD 33-2-2L (REV-B.0) PWP

| | | | | |
|-----------------------------------|------------|---------|----------|---------|
| Slot Surface Uncertainty @1SD | Horizontal | 0.100ft | Vertical | 1.000ft |
| Facility Surface Uncertainty @1SD | Horizontal | 8.200ft | Vertical | 3.000ft |

SURVEY PROGRAM - Offset Wellbore: BUFORD 33-2-2L PWB Offset Wellpath: BUFORD 33-2-2L (REV-B.0) PWP

| Start MD [ft] | End MD [ft] | Positional Uncertainty Model | Log Name/Comment | Wellbore |
|---------------|-------------|---|------------------|--------------------|
| 20.50 | 1500.00 | BH NaviTrak (2019) (Standard) | | BUFORD 33-2-2L PWB |
| 1500.00 | 17650.27 | BH AutoTrak Curve/eXpress (2019) (Standard) | | BUFORD 33-2-2L PWB |

OFFSET WELLPATH REFERENCE - Offset Wellbore: BUFORD 33-2-2L PWB Offset Wellpath: BUFORD 33-2-2L (REV-B.0) PWP

| | |
|---------------------------------|---|
| MD Reference: RIG (20.5') (RKB) | Offset TVD & local coordinates use Reference Wellpath settings (See WELLPATH DATUM on page 1 of this report) |
| Ellipse Start MD | 20.50ft |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 69 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. HSR-CHERRY KNOLLS 9-33 AWB Offset Wellpath: EX. HSR-CHERRY KNOLLS 9-33 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.33-T01N-R65W Slot: SLOT#01 EX. HSR-CHERRY KNOLLS 9-33 (1400'FSL & 660'FEL, DA) Well: EX. HSR-CHERRY KNOLLS 9-33 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 20.50 | 20.50 | 0.00 | 0.00 | -8.00 | 20.50 | 652.12 | -1511.38 | 293.34 | 1646.07 | 33.26 | 1612.81 | 56.10 | PASS |
| 120.50† | 120.50 | 0.00 | 0.00 | 92.02 | 120.50 | 652.12 | -1511.38 | 293.34 | 1646.07 | 45.14 | 1600.93 | 39.90 | PASS |
| 200.00 | 200.00 | 0.00 | 0.00 | 171.56 | 200.00 | 652.12 | -1511.38 | 293.34 | 1646.07 | 45.72 | 1600.35 | 39.34 | PASS |
| 220.50† | 220.50 | -0.03 | -0.07 | 192.08 | 220.50 | 652.12 | -1511.38 | 293.34 | 1646.02 | 45.89 | 1600.13 | 39.19 | PASS |
| 320.50† | 320.46 | -0.93 | -2.36 | 292.10 | 320.46 | 652.12 | -1511.38 | 293.40 | 1644.28 | 47.26 | 1597.01 | 37.90 | PASS |
| 420.50† | 420.28 | -3.13 | -7.88 | 391.98 | 420.28 | 652.12 | -1511.38 | 293.55 | 1640.08 | 49.23 | 1590.84 | 36.16 | PASS |
| 520.50† | 519.83 | -6.60 | -16.65 | 491.59 | 519.83 | 652.12 | -1511.38 | 293.78 | 1633.45 | 51.70 | 1581.74 | 34.15 | PASS |
| 620.50† | 618.99 | -11.36 | -28.64 | 590.81 | 618.99 | 652.12 | -1511.38 | 294.11 | 1624.42 | 54.59 | 1569.83 | 32.02 | PASS |
| 720.50† | 717.64 | -17.38 | -43.83 | 689.52 | 717.64 | 652.12 | -1511.38 | 294.52 | 1613.05 | 57.82 | 1555.23 | 29.89 | PASS |
| 820.50† | 815.66 | -24.68 | -62.22 | 787.60 | 815.66 | 652.12 | -1511.38 | 295.03 | 1599.41 | 61.32 | 1538.09 | 27.82 | PASS |
| 920.50† | 912.93 | -33.22 | -83.78 | 884.93 | 912.93 | 652.12 | -1511.38 | 295.64 | 1583.59 | 65.04 | 1518.55 | 25.87 | PASS |
| 1020.50† | 1009.33 | -43.02 | -108.48 | 981.39 | 1009.33 | 652.12 | -1511.38 | 296.36 | 1565.68 | 68.93 | 1496.75 | 24.05 | PASS |
| 1120.50† | 1104.74 | -54.05 | -136.29 | 1076.86 | 1104.74 | 652.12 | -1511.38 | 297.18 | 1545.82 | 72.94 | 1472.88 | 22.36 | PASS |
| 1220.50† | 1199.05 | -66.30 | -167.18 | 1171.23 | 1199.05 | 652.12 | -1511.38 | 298.12 | 1524.14 | 77.05 | 1447.09 | 20.81 | PASS |
| 1242.54 | 1219.68 | -69.16 | -174.40 | 1191.86 | 1219.68 | 652.12 | -1511.38 | 298.35 | 1519.14 | 77.96 | 1441.18 | 20.48 | PASS |
| 1320.50† | 1292.54 | -79.39 | -200.20 | 1264.76 | 1292.54 | 652.12 | -1511.38 | 299.16 | 1501.44 | 81.22 | 1420.22 | 19.39 | PASS |
| 1420.50† | 1385.99 | -92.51 | -233.28 | 1358.27 | 1385.99 | 652.12 | -1511.38 | 300.23 | 1479.20 | 85.50 | 1393.70 | 18.10 | PASS |
| 1520.50† | 1479.44 | -105.63 | -266.37 | 1451.78 | 1479.44 | 652.12 | -1511.38 | 301.33 | 1457.48 | 89.82 | 1367.67 | 16.93 | PASS |
| 1620.50† | 1572.89 | -118.75 | -299.46 | 1545.29 | 1572.89 | 652.12 | -1511.38 | 302.46 | 1436.32 | 94.17 | 1342.15 | 15.88 | PASS |
| 1720.50† | 1666.34 | -131.87 | -332.54 | 1638.80 | 1666.34 | 652.12 | -1511.38 | 303.63 | 1415.74 | 98.59 | 1317.15 | 14.92 | PASS |
| 1820.50† | 1759.79 | -144.99 | -365.63 | 1732.31 | 1759.79 | 652.12 | -1511.38 | 304.83 | 1395.76 | 103.08 | 1292.68 | 14.05 | PASS |
| 1920.50† | 1853.24 | -158.12 | -398.72 | 1825.81 | 1853.24 | 652.12 | -1511.38 | 306.06 | 1376.41 | 107.62 | 1268.79 | 13.24 | PASS |
| 2020.50† | 1946.69 | -171.24 | -431.80 | 1919.32 | 1946.69 | 652.12 | -1511.38 | 307.33 | 1357.72 | 112.21 | 1245.51 | 12.51 | PASS |
| 2120.50† | 2040.14 | -184.36 | -464.89 | 2012.83 | 2040.14 | 652.12 | -1511.38 | 308.64 | 1339.72 | 116.84 | 1222.88 | 11.84 | PASS |
| 2220.50† | 2133.59 | -197.48 | -497.98 | 2106.34 | 2133.59 | 652.12 | -1511.38 | 309.98 | 1322.43 | 121.51 | 1200.91 | 11.22 | PASS |
| 2320.50† | 2227.05 | -210.60 | -531.06 | 2199.85 | 2227.05 | 652.12 | -1511.38 | 311.35 | 1305.88 | 126.22 | 1179.66 | 10.65 | PASS |
| 2420.50† | 2320.50 | -223.72 | -564.15 | 2293.35 | 2320.50 | 652.12 | -1511.38 | 312.76 | 1290.10 | 130.96 | 1159.14 | 10.13 | PASS |
| 2520.50† | 2413.95 | -236.84 | -597.24 | 2386.86 | 2413.95 | 652.12 | -1511.38 | 314.20 | 1275.11 | 135.72 | 1139.39 | 9.65 | PASS |
| 2620.50† | 2507.40 | -249.96 | -630.32 | 2480.37 | 2507.40 | 652.12 | -1511.38 | 315.68 | 1260.96 | 140.51 | 1120.45 | 9.21 | PASS |
| 2720.50† | 2600.85 | -263.08 | -663.41 | 2573.88 | 2600.85 | 652.12 | -1511.38 | 317.18 | 1247.66 | 145.33 | 1102.33 | 8.80 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 70 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. HSR-CHERRY KNOLLS 9-33 AWB Offset Wellpath: EX. HSR-CHERRY KNOLLS 9-33 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.33-T01N-R65W Slot: SLOT#01 EX. HSR-CHERRY KNOLLS 9-33 (1400'FSL & 660'FEL, DA) Well: EX. HSR-CHERRY KNOLLS 9-33 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 2820.50† | 2694.30 | -276.20 | -696.50 | 2667.39 | 2694.30 | 652.12 | -1511.38 | 318.72 | 1235.24 | 150.16 | 1085.08 | 8.42 | PASS |
| 2920.50† | 2787.75 | -289.33 | -729.58 | 2760.89 | 2787.75 | 652.12 | -1511.38 | 320.29 | 1223.74 | 155.01 | 1068.72 | 8.08 | PASS |
| 3020.50† | 2881.20 | -302.45 | -762.67 | 2854.40 | 2881.20 | 652.12 | -1511.38 | 321.89 | 1213.16 | 159.88 | 1053.28 | 7.76 | PASS |
| 3120.50† | 2974.65 | -315.57 | -795.76 | 2947.91 | 2974.65 | 652.12 | -1511.38 | 323.52 | 1203.55 | 164.77 | 1038.79 | 7.46 | PASS |
| 3220.50† | 3068.11 | -328.69 | -828.84 | 3041.42 | 3068.11 | 652.12 | -1511.38 | 325.17 | 1194.92 | 169.66 | 1025.26 | 7.19 | PASS |
| 3320.50† | 3161.56 | -341.81 | -861.93 | 3134.93 | 3161.56 | 652.12 | -1511.38 | 326.84 | 1187.30 | 174.57 | 1012.73 | 6.94 | PASS |
| 3420.50† | 3255.01 | -354.93 | -895.02 | 3228.43 | 3255.01 | 652.12 | -1511.38 | 328.53 | 1180.70 | 179.49 | 1001.21 | 6.70 | PASS |
| 3520.50† | 3348.46 | -368.05 | -928.10 | 3321.94 | 3348.46 | 652.12 | -1511.38 | 330.24 | 1175.14 | 184.41 | 990.73 | 6.49 | PASS |
| 3620.50† | 3441.91 | -381.17 | -961.19 | 3415.45 | 3441.91 | 652.12 | -1511.38 | 331.97 | 1170.64 | 189.35 | 981.29 | 6.29 | PASS |
| 3720.50† | 3535.36 | -394.29 | -994.28 | 3508.96 | 3535.36 | 652.12 | -1511.38 | 333.70 | 1167.21 | 194.29 | 972.92 | 6.11 | PASS |
| 3820.50† | 3628.81 | -407.41 | -1027.37 | 3602.47 | 3628.81 | 652.12 | -1511.38 | 335.45 | 1164.85 | 199.23 | 965.63 | 5.95 | PASS |
| 3920.50† | 3722.26 | -420.53 | -1060.45 | 3695.97 | 3722.26 | 652.12 | -1511.38 | 337.20 | 1163.58 | 204.17 | 959.41 | 5.79 | PASS |
| 4020.50† | 3815.71 | -433.66 | -1093.54 | 3789.48 | 3815.71 | 652.12 | -1511.38 | 338.95 | 1163.40 | 209.12 | 954.28 | 5.65 | PASS |
| 4120.50† | 3909.17 | -446.78 | -1126.63 | 3882.99 | 3909.17 | 652.12 | -1511.38 | 340.70 | 1164.31 | 214.07 | 950.24 | 5.52 | PASS |
| 4220.50† | 4002.62 | -459.90 | -1159.71 | 3976.50 | 4002.62 | 652.12 | -1511.38 | 342.45 | 1166.30 | 219.01 | 947.29 | 5.41 | PASS |
| 4320.50† | 4096.07 | -473.02 | -1192.80 | 4070.01 | 4096.07 | 652.12 | -1511.38 | 344.19 | 1169.37 | 223.96 | 945.41 | 5.30 | PASS |
| 4420.50† | 4189.52 | -486.14 | -1225.89 | 4163.51 | 4189.52 | 652.12 | -1511.38 | 345.92 | 1173.52 | 228.90 | 944.62 | 5.20 | PASS |
| 4520.50† | 4282.97 | -499.26 | -1258.97 | 4257.02 | 4282.97 | 652.12 | -1511.38 | 347.64 | 1178.72 | 233.84 | 944.88 | 5.11 | PASS |
| 4620.50† | 4376.42 | -512.38 | -1292.06 | 4350.53 | 4376.42 | 652.12 | -1511.38 | 349.33 | 1184.98 | 238.78 | 946.20 | 5.03 | PASS |
| 4720.50† | 4469.87 | -525.50 | -1325.15 | 4444.04 | 4469.87 | 652.12 | -1511.38 | 351.01 | 1192.26 | 243.71 | 948.55 | 4.96 | PASS |
| 4820.50† | 4563.32 | -538.62 | -1358.23 | 4537.55 | 4563.32 | 652.12 | -1511.38 | 352.67 | 1200.55 | 248.64 | 951.91 | 4.89 | PASS |
| 4920.50† | 4656.77 | -551.74 | -1391.32 | 4631.05 | 4656.77 | 652.12 | -1511.38 | 354.31 | 1209.84 | 253.57 | 956.27 | 4.83 | PASS |
| 5020.50† | 4750.22 | -564.87 | -1424.41 | 4724.56 | 4750.22 | 652.12 | -1511.38 | 355.91 | 1220.09 | 258.49 | 961.60 | 4.78 | PASS |
| 5120.50† | 4843.68 | -577.99 | -1457.49 | 4818.07 | 4843.68 | 652.12 | -1511.38 | 357.49 | 1231.29 | 263.40 | 967.88 | 4.73 | PASS |
| 5220.50† | 4937.13 | -591.11 | -1490.58 | 4911.58 | 4937.13 | 652.12 | -1511.38 | 359.04 | 1243.40 | 268.32 | 975.09 | 4.69 | PASS |
| 5320.50† | 5030.58 | -604.23 | -1523.67 | 5005.09 | 5030.58 | 652.12 | -1511.38 | 0.56 | 1256.41 | 273.22 | 983.18 | 4.65 | PASS |
| 5420.50† | 5124.03 | -617.35 | -1556.75 | 5098.59 | 5124.03 | 652.12 | -1511.38 | 2.05 | 1270.28 | 278.13 | 992.15 | 4.62 | PASS |
| 5520.50† | 5217.48 | -630.47 | -1589.84 | 5192.10 | 5217.48 | 652.12 | -1511.38 | 3.50 | 1284.99 | 283.03 | 1001.96 | 4.59 | PASS |
| 5620.50† | 5310.93 | -643.59 | -1622.93 | 5285.61 | 5310.93 | 652.12 | -1511.38 | 4.92 | 1300.50 | 287.92 | 1012.58 | 4.57 | PASS |
| 5720.50† | 5404.38 | -656.71 | -1656.01 | 5379.12 | 5404.38 | 652.12 | -1511.38 | 6.31 | 1316.80 | 292.82 | 1023.98 | 4.55 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 71 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. HSR-CHERRY KNOLLS 9-33 AWB Offset Wellpath: EX. HSR-CHERRY KNOLLS 9-33 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.33-T01N-R65W Slot: SLOT#01 EX. HSR-CHERRY KNOLLS 9-33 (1400'FSL & 660'FEL, DA) Well: EX. HSR-CHERRY KNOLLS 9-33 | | | | | | | | | | | | Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | |
|---|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|---|-------------|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | |
| 5820.50† | 5497.83 | -669.83 | -1689.10 | 5472.63 | 5497.83 | 652.12 | -1511.38 | 7.66 | 1333.85 | 297.71 | 1036.14 | 4.53 | PASS | |
| 5920.50† | 5591.28 | -682.95 | -1722.19 | 5566.13 | 5591.28 | 652.12 | -1511.38 | 8.97 | 1351.61 | 302.59 | 1049.02 | 4.51 | PASS | |
| 6020.50† | 5684.74 | -696.07 | -1755.27 | 5659.64 | 5684.74 | 652.12 | -1511.38 | 10.25 | 1370.08 | 307.48 | 1062.60 | 4.50 | PASS | |
| 6120.50† | 5778.19 | -709.20 | -1788.36 | 5753.15 | 5778.19 | 652.12 | -1511.38 | 11.50 | 1389.21 | 312.36 | 1076.85 | 4.49 | PASS | |
| 6220.50† | 5871.64 | -722.32 | -1821.45 | 5846.66 | 5871.64 | 652.12 | -1511.38 | 12.71 | 1408.98 | 317.24 | 1091.73 | 4.49 | PASS | |
| 6320.50† | 5965.09 | -735.44 | -1854.54 | 5940.17 | 5965.09 | 652.12 | -1511.38 | 13.89 | 1429.36 | 322.12 | 1107.24 | 4.48 | PASS | |
| 6420.50† | 6058.54 | -748.56 | -1887.62 | 6033.68 | 6058.54 | 652.12 | -1511.38 | 15.04 | 1450.33 | 327.00 | 1123.33 | 4.48 | PASS | |
| 6520.50† | 6151.99 | -761.68 | -1920.71 | 6127.18 | 6151.99 | 652.12 | -1511.38 | 16.15 | 1471.86 | 331.88 | 1139.98 | 4.48 | PASS | |
| 6620.50† | 6245.44 | -774.80 | -1953.80 | 6220.69 | 6245.44 | 652.12 | -1511.38 | 17.23 | 1493.93 | 336.75 | 1157.18 | 4.48 | PASS | |
| 6720.50† | 6338.89 | -787.92 | -1986.88 | 6314.20 | 6338.89 | 652.12 | -1511.38 | 18.27 | 1516.52 | 341.63 | 1174.89 | 4.48 | PASS | |
| 6820.50† | 6432.34 | -801.04 | -2019.97 | 6407.71 | 6432.34 | 652.12 | -1511.38 | 19.29 | 1539.59 | 346.51 | 1193.09 | 4.48 | PASS | |
| 6920.50† | 6525.80 | -814.16 | -2053.06 | 6501.22 | 6525.80 | 652.12 | -1511.38 | 20.27 | 1563.14 | 351.38 | 1211.76 | 4.49 | PASS | |
| 7020.50† | 6619.25 | -827.28 | -2086.14 | 6594.72 | 6619.25 | 652.12 | -1511.38 | 21.23 | 1587.13 | 356.26 | 1230.87 | 4.49 | PASS | |
| 7120.50† | 6712.70 | -840.41 | -2119.23 | 6688.23 | 6712.70 | 652.12 | -1511.38 | 22.16 | 1611.55 | 361.13 | 1250.42 | 4.50 | PASS | |
| 7220.50† | 6806.15 | -853.53 | -2152.32 | 6781.74 | 6806.15 | 652.12 | -1511.38 | 23.06 | 1636.39 | 366.01 | 1270.38 | 4.51 | PASS | |
| 7320.50† | 6899.60 | -866.65 | -2185.40 | 6875.25 | 6899.60 | 652.12 | -1511.38 | 23.93 | 1661.61 | 370.89 | 1290.73 | 4.52 | PASS | |
| 7341.07 | 6918.82 | -869.35 | -2192.21 | 6894.48 | 6918.82 | 652.12 | -1511.38 | 24.11 | 1666.85 | 371.89 | 1294.96 | 4.52 | PASS | |
| 7420.50† | 6993.49 | -874.29 | -2218.65 | 6969.20 | 6993.49 | 652.12 | -1511.38 | 24.86 | 1682.30 | 375.80 | 1306.51 | 4.51 | PASS | |
| 7520.50† | 7087.21 | -864.88 | -2251.87 | 7062.97 | 7087.21 | 652.12 | -1511.38 | 26.02 | 1688.08 | 380.77 | 1307.31 | 4.47 | PASS | |
| 7620.50† | 7177.96 | -838.35 | -2284.05 | 7153.77 | 7177.96 | 652.12 | -1511.38 | 27.40 | 1678.84 | 385.63 | 1293.21 | 4.39 | PASS | |
| 7720.50† | 7262.97 | -795.51 | -2314.23 | 7238.84 | 7262.97 | 652.12 | -1511.38 | 29.01 | 1655.35 | 390.15 | 1265.20 | 4.28 | PASS | |
| 7820.50† | 7339.68 | -737.65 | -2341.49 | 7315.60 | 7339.68 | 652.12 | -1511.38 | 30.85 | 1618.80 | 394.20 | 1224.60 | 4.14 | PASS | |
| 7920.50† | 7405.75 | -666.53 | -2364.99 | 7381.70 | 7405.75 | 652.12 | -1511.38 | 32.92 | 1570.82 | 397.66 | 1173.16 | 3.98 | PASS | |
| 8020.50† | 7459.16 | -584.32 | -2384.03 | 7435.15 | 7459.16 | 652.12 | -1511.38 | 35.21 | 1513.37 | 400.43 | 1112.94 | 3.81 | PASS | |
| 8120.50† | 7498.30 | -493.50 | -2398.02 | 7474.32 | 7498.30 | 652.12 | -1511.38 | 37.74 | 1448.65 | 402.42 | 1046.22 | 3.63 | PASS | |
| 8220.50† | 7521.99 | -396.85 | -2406.55 | 7498.01 | 7521.99 | 652.12 | -1511.38 | 40.48 | 1379.01 | 403.59 | 975.42 | 3.44 | PASS | |
| 8315.56 | 7529.50 | -302.24 | -2409.34 | 7505.53 | 7529.50 | 652.12 | -1511.38 | 43.26 | 1310.39 | 403.89 | 906.50 | 3.27 | PASS | |
| 8320.50† | 7529.51 | -297.30 | -2409.35 | 7505.54 | 7529.51 | 652.12 | -1511.38 | 43.41 | 1306.81 | 403.89 | 902.92 | 3.26 | PASS | |
| 8420.50† | 7529.61 | -197.30 | -2409.53 | 7505.64 | 7529.61 | 652.12 | -1511.38 | 46.60 | 1236.20 | 403.76 | 832.43 | 3.08 | PASS | |
| 8520.50† | 7529.71 | -97.30 | -2409.71 | 7505.74 | 7529.71 | 652.12 | -1511.38 | 50.16 | 1169.88 | 403.62 | 766.26 | 2.92 | PASS | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 72 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. HSR-CHERRY KNOLLS 9-33 AWP Offset Wellpath: EX. HSR-CHERRY KNOLLS 9-33 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.33-T01N-R65W Slot: SLOT#01 EX. HSR-CHERRY KNOLLS 9-33 (1400'FSL & 660'FEL, DA) Well: EX. HSR-CHERRY KNOLLS 9-33 | | | | | | | | | | | | | Threshold Value=1.00 † = interpolated, ‡ = extrapolated station |
|---|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|---|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 8620.50† | 7529.82 | 2.70 | -2409.88 | 7505.85 | 7529.82 | 652.12 | -1511.38 | 54.14 | 1108.63 | 403.44 | 705.19 | 2.77 | PASS |
| 8720.50† | 7529.92 | 102.70 | -2410.06 | 7505.95 | 7529.92 | 652.12 | -1511.38 | 58.56 | 1053.32 | 403.23 | 650.09 | 2.63 | PASS |
| 8820.50† | 7530.02 | 202.70 | -2410.24 | 7506.05 | 7530.02 | 652.12 | -1511.38 | 63.44 | 1004.95 | 402.98 | 601.96 | 2.51 | PASS |
| 8920.50† | 7530.13 | 302.70 | -2410.42 | 7506.16 | 7530.13 | 652.12 | -1511.38 | 68.76 | 964.55 | 402.71 | 561.84 | 2.41 | PASS |
| 9020.50† | 7530.23 | 402.70 | -2410.59 | 7506.26 | 7530.23 | 652.12 | -1511.38 | 74.50 | 933.16 | 402.42 | 530.74 | 2.33 | PASS |
| 9120.50† | 7530.33 | 502.70 | -2410.77 | 7506.37 | 7530.33 | 652.12 | -1511.38 | 80.57 | 911.72 | 402.14 | 509.58 | 2.28 | PASS |
| 9220.50† | 7530.44 | 602.70 | -2410.95 | 7506.47 | 7530.44 | 652.12 | -1511.38 | 86.86 | 900.92 | 401.87 | 499.05 | 2.25 | PASS |
| 9263.82† | 7530.48 | 646.02 | -2411.03 | 7506.51 | 7530.48 | 652.12 | -1511.38 | 89.61 | 899.66 | 401.77 | 497.89 | 2.25 | PASS |
| 9268.33† | 7530.49 | 650.52 | -2411.04 | 7506.52 | 7530.49 | 652.12 | -1511.38 | 89.90 | 899.65 | 401.76 | 497.89 | 2.25 | PASS |
| 9320.50† | 7530.54 | 702.70 | -2411.13 | 7506.57 | 7530.54 | 652.12 | -1511.38 | 93.22 | 901.16 | 401.66 | 499.51 | 2.26 | PASS |
| 9420.50† | 7530.64 | 802.69 | -2411.31 | 7506.68 | 7530.64 | 652.12 | -1511.38 | 99.50 | 912.43 | 401.50 | 510.93 | 2.29 | PASS |
| 9520.50† | 7530.75 | 902.69 | -2411.48 | 7506.78 | 7530.75 | 652.12 | -1511.38 | 105.56 | 934.33 | 401.41 | 532.91 | 2.34 | PASS |
| 9620.50† | 7530.85 | 1002.69 | -2411.66 | 7506.88 | 7530.85 | 652.12 | -1511.38 | 111.28 | 966.13 | 401.39 | 564.74 | 2.42 | PASS |
| 9720.50† | 7530.96 | 1102.69 | -2411.84 | 7506.99 | 7530.96 | 652.12 | -1511.38 | 116.58 | 1006.89 | 401.42 | 605.47 | 2.52 | PASS |
| 9820.50† | 7531.06 | 1202.69 | -2412.02 | 7507.09 | 7531.06 | 652.12 | -1511.38 | 121.44 | 1055.59 | 401.50 | 654.09 | 2.65 | PASS |
| 9920.50† | 7531.16 | 1302.69 | -2412.19 | 7507.20 | 7531.16 | 652.12 | -1511.38 | 125.84 | 1111.17 | 401.60 | 709.57 | 2.78 | PASS |
| 10020.50† | 7531.27 | 1402.69 | -2412.37 | 7507.30 | 7531.27 | 652.12 | -1511.38 | 129.80 | 1172.66 | 401.73 | 770.94 | 2.94 | PASS |
| 10120.50† | 7531.37 | 1502.69 | -2412.55 | 7507.40 | 7531.37 | 652.12 | -1511.38 | 133.35 | 1239.18 | 401.86 | 837.33 | 3.10 | PASS |
| 10220.50† | 7531.47 | 1602.69 | -2412.73 | 7507.51 | 7531.47 | 652.12 | -1511.38 | 136.52 | 1309.97 | 401.99 | 907.98 | 3.28 | PASS |
| 10320.50† | 7531.58 | 1702.69 | -2412.90 | 7507.61 | 7531.58 | 652.12 | -1511.38 | 139.37 | 1384.36 | 402.12 | 982.24 | 3.47 | PASS |
| 10420.50† | 7531.68 | 1802.69 | -2413.08 | 7507.71 | 7531.68 | 652.12 | -1511.38 | 141.91 | 1461.81 | 402.24 | 1059.57 | 3.66 | PASS |
| 10520.50† | 7531.78 | 1902.69 | -2413.26 | 7507.82 | 7531.78 | 652.12 | -1511.38 | 144.20 | 1541.85 | 402.35 | 1139.50 | 3.86 | PASS |
| 10620.50† | 7531.89 | 2002.69 | -2413.44 | 7507.92 | 7531.89 | 652.12 | -1511.38 | 146.26 | 1624.11 | 402.46 | 1221.65 | 4.07 | PASS |
| 10720.50† | 7531.99 | 2102.69 | -2413.62 | 7508.02 | 7531.99 | 652.12 | -1511.38 | 148.12 | 1708.27 | 402.57 | 1305.70 | 4.28 | PASS |
| 10820.50† | 7532.09 | 2202.69 | -2413.79 | 7508.13 | 7532.09 | 652.12 | -1511.38 | 149.80 | 1794.05 | 402.66 | 1391.39 | 4.49 | PASS |
| 10920.50† | 7532.20 | 2302.69 | -2413.97 | 7508.23 | 7532.20 | 652.12 | -1511.38 | 151.33 | 1881.24 | 402.75 | 1478.49 | 4.71 | PASS |
| 11020.50† | 7532.30 | 2402.69 | -2414.15 | 7508.34 | 7532.30 | 652.12 | -1511.38 | 152.72 | 1969.64 | 402.83 | 1566.81 | 4.93 | PASS |
| 11120.50† | 7532.41 | 2502.69 | -2414.33 | 7508.44 | 7532.41 | 652.12 | -1511.38 | 153.99 | 2059.11 | 402.91 | 1656.20 | 5.15 | PASS |
| 11220.50† | 7532.51 | 2602.69 | -2414.50 | 7508.54 | 7532.51 | 652.12 | -1511.38 | 155.16 | 2149.50 | 402.98 | 1746.52 | 5.38 | PASS |
| 11320.50† | 7532.61 | 2702.69 | -2414.68 | 7508.65 | 7532.61 | 652.12 | -1511.38 | 156.23 | 2240.71 | 403.05 | 1837.67 | 5.60 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 73 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. HSR-CHERRY KNOLLS 9-33 AWP Offset Wellpath: EX. HSR-CHERRY KNOLLS 9-33 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.33-T01N-R65W Slot: SLOT#01 EX. HSR-CHERRY KNOLLS 9-33 (1400'FSL & 660'FEL, DA) Well: EX. HSR-CHERRY KNOLLS 9-33 | | | | | | | | | | | | Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | |
|---|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|---|-------------|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | |
| 11420.50† | 7532.72 | 2802.69 | -2414.86 | 7508.75 | 7532.72 | 652.12 | -1511.38 | 157.21 | 2332.64 | 403.11 | 1929.53 | 5.83 | PASS | | |
| 11520.50† | 7532.82 | 2902.69 | -2415.04 | 7508.85 | 7532.82 | 652.12 | -1511.38 | 158.12 | 2425.21 | 403.17 | 2022.06 | 6.07 | PASS | | |
| 11620.50† | 7532.92 | 3002.69 | -2415.21 | 7508.96 | 7532.92 | 652.12 | -1511.38 | 158.97 | 2518.35 | 403.22 | 2115.13 | 6.30 | PASS | | |
| 11720.50† | 7533.03 | 3102.69 | -2415.39 | 7509.06 | 7533.03 | 652.12 | -1511.38 | 159.75 | 2612.00 | 403.27 | 2208.72 | 6.53 | PASS | | |
| 11820.50† | 7533.13 | 3202.69 | -2415.57 | 7509.16 | 7533.13 | 652.12 | -1511.38 | 160.48 | 2706.10 | 403.32 | 2302.77 | 6.77 | PASS | | |
| 11920.50† | 7533.23 | 3302.69 | -2415.75 | 7509.27 | 7533.23 | 652.12 | -1511.38 | 161.16 | 2800.61 | 403.37 | 2397.23 | 7.00 | PASS | | |
| 12020.50† | 7533.34 | 3402.69 | -2415.92 | 7509.37 | 7533.34 | 652.12 | -1511.38 | 161.80 | 2895.48 | 403.42 | 2492.07 | 7.24 | PASS | | |
| 12120.50† | 7533.44 | 3502.69 | -2416.10 | 7509.48 | 7533.44 | 652.12 | -1511.38 | 162.39 | 2990.70 | 403.46 | 2587.24 | 7.48 | PASS | | |
| 12220.50† | 7533.55 | 3602.69 | -2416.28 | 7509.58 | 7533.55 | 652.12 | -1511.38 | 162.95 | 3086.21 | 403.50 | 2682.71 | 7.71 | PASS | | |
| 12320.50† | 7533.65 | 3702.69 | -2416.46 | 7509.68 | 7533.65 | 652.12 | -1511.38 | 163.48 | 3182.00 | 403.54 | 2778.46 | 7.95 | PASS | | |
| 12420.50† | 7533.75 | 3802.69 | -2416.64 | 7509.79 | 7533.75 | 652.12 | -1511.38 | 163.97 | 3278.04 | 403.58 | 2874.47 | 8.19 | PASS | | |
| 12520.50† | 7533.86 | 3902.69 | -2416.81 | 7509.89 | 7533.86 | 652.12 | -1511.38 | 164.44 | 3374.31 | 403.61 | 2970.70 | 8.43 | PASS | | |
| 12620.50† | 7533.96 | 4002.69 | -2416.99 | 7509.99 | 7533.96 | 652.12 | -1511.38 | 164.88 | 3470.80 | 403.65 | 3067.15 | 8.67 | PASS | | |
| 12720.50† | 7534.06 | 4102.69 | -2417.17 | 7510.10 | 7534.06 | 652.12 | -1511.38 | 165.29 | 3567.47 | 403.68 | 3163.79 | 8.92 | PASS | | |
| 12820.50† | 7534.17 | 4202.69 | -2417.35 | 7510.20 | 7534.17 | 652.12 | -1511.38 | 165.69 | 3664.33 | 403.72 | 3260.61 | 9.16 | PASS | | |
| 12920.50† | 7534.27 | 4302.69 | -2417.52 | 7510.30 | 7534.27 | 652.12 | -1511.38 | 166.06 | 3761.35 | 403.75 | 3357.60 | 9.40 | PASS | | |
| 13020.50† | 7534.37 | 4402.69 | -2417.70 | 7510.41 | 7534.37 | 652.12 | -1511.38 | 166.42 | 3858.52 | 403.78 | 3454.74 | 9.64 | PASS | | |
| 13120.50† | 7534.48 | 4502.69 | -2417.88 | 7510.51 | 7534.48 | 652.12 | -1511.38 | 166.75 | 3955.83 | 403.81 | 3552.02 | 9.88 | PASS | | |
| 13199.97 | 7534.56 | 4582.16 | -2418.02 | 7510.59 | 7534.56 | 652.12 | -1511.38 | 167.01 | 4033.26 | 403.83 | 3629.43 | 10.08 | PASS | | |
| 13220.50† | 7534.58 | 4602.69 | -2418.13 | 7510.62 | 7534.58 | 652.12 | -1511.38 | 167.07 | 4053.29 | 403.84 | 3649.45 | 10.13 | PASS | | |
| 13320.50† | 7534.68 | 4702.65 | -2420.77 | 7510.72 | 7534.68 | 652.12 | -1511.38 | 167.35 | 4151.35 | 403.87 | 3747.49 | 10.37 | PASS | | |
| 13420.50† | 7534.79 | 4802.45 | -2426.90 | 7510.82 | 7534.79 | 652.12 | -1511.38 | 167.56 | 4250.11 | 403.89 | 3846.22 | 10.62 | PASS | | |
| 13476.50 | 7534.85 | 4858.23 | -2431.85 | 7510.88 | 7534.85 | 652.12 | -1511.38 | 167.66 | 4305.65 | 403.90 | 3901.75 | 10.76 | PASS | | |
| 13520.50† | 7534.89 | 4902.02 | -2436.16 | 7510.93 | 7534.89 | 652.12 | -1511.38 | 167.72 | 4349.35 | 403.91 | 3945.44 | 10.87 | PASS | | |
| 13620.50† | 7534.99 | 5001.54 | -2445.98 | 7511.03 | 7534.99 | 652.12 | -1511.38 | 167.87 | 4448.70 | 403.93 | 4044.77 | 11.11 | PASS | | |
| 13720.50† | 7535.10 | 5101.06 | -2455.79 | 7511.13 | 7535.10 | 652.12 | -1511.38 | 168.02 | 4548.07 | 403.95 | 4144.12 | 11.36 | PASS | | |
| 13820.50† | 7535.20 | 5200.57 | -2465.61 | 7511.23 | 7535.20 | 652.12 | -1511.38 | 168.15 | 4647.47 | 403.97 | 4243.50 | 11.61 | PASS | | |
| 13920.50† | 7535.30 | 5300.09 | -2475.42 | 7511.34 | 7535.30 | 652.12 | -1511.38 | 168.28 | 4746.89 | 403.99 | 4342.90 | 11.86 | PASS | | |
| 14020.50† | 7535.40 | 5399.61 | -2485.24 | 7511.44 | 7535.40 | 652.12 | -1511.38 | 168.41 | 4846.34 | 404.01 | 4442.33 | 12.11 | PASS | | |
| 14120.50† | 7535.51 | 5499.12 | -2495.05 | 7511.54 | 7535.51 | 652.12 | -1511.38 | 168.53 | 4945.81 | 404.03 | 4541.78 | 12.35 | PASS | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 74 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. HSR-CHERRY KNOLLS 9-33 AWP Offset Wellpath: EX. HSR-CHERRY KNOLLS 9-33 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.33-T01N-R65W Slot: SLOT#01 EX. HSR-CHERRY KNOLLS 9-33 (1400'FSL & 660'FEL, DA) Well: EX. HSR-CHERRY KNOLLS 9-33 | | | | | | | | | | | | Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | |
|---|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|---|-------------|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | |
| 14220.50† | 7535.61 | 5598.64 | -2504.87 | 7511.64 | 7535.61 | 652.12 | -1511.38 | 168.64 | 5045.30 | 404.05 | 4641.25 | 12.60 | PASS | |
| 14221.87 | 7535.61 | 5600.00 | -2505.00 | 7511.65 | 7535.61 | 652.12 | -1511.38 | 168.65 | 5046.66 | 404.05 | 4642.61 | 12.60 | PASS | |
| 14320.50† | 7535.71 | 5698.31 | -2512.99 | 7511.75 | 7535.71 | 652.12 | -1511.38 | 168.77 | 5144.63 | 404.07 | 4740.56 | 12.85 | PASS | |
| 14420.50† | 7535.81 | 5798.19 | -2517.63 | 7511.85 | 7535.81 | 652.12 | -1511.38 | 168.94 | 5243.53 | 404.09 | 4839.44 | 13.10 | PASS | |
| 14520.50† | 7535.92 | 5898.18 | -2518.78 | 7511.95 | 7535.92 | 652.12 | -1511.38 | 169.13 | 5341.91 | 404.12 | 4937.79 | 13.34 | PASS | |
| 14581.38 | 7535.98 | 5959.05 | -2517.77 | 7512.02 | 7535.98 | 652.12 | -1511.38 | 169.26 | 5401.51 | 404.14 | 4997.38 | 13.49 | PASS | |
| 14620.50† | 7536.02 | 5998.16 | -2516.71 | 7512.06 | 7536.02 | 652.12 | -1511.38 | 169.35 | 5439.74 | 404.15 | 5035.59 | 13.58 | PASS | |
| 14720.50† | 7536.12 | 6098.12 | -2513.99 | 7512.16 | 7536.12 | 652.12 | -1511.38 | 169.57 | 5537.52 | 404.18 | 5133.34 | 13.83 | PASS | |
| 14820.50† | 7536.23 | 6198.08 | -2511.27 | 7512.26 | 7536.23 | 652.12 | -1511.38 | 169.78 | 5635.38 | 404.21 | 5231.17 | 14.07 | PASS | |
| 14920.50† | 7536.33 | 6298.05 | -2508.55 | 7512.37 | 7536.33 | 652.12 | -1511.38 | 169.98 | 5733.31 | 404.24 | 5329.07 | 14.31 | PASS | |
| 15020.50† | 7536.43 | 6398.01 | -2505.83 | 7512.47 | 7536.43 | 652.12 | -1511.38 | 170.18 | 5831.31 | 404.27 | 5427.04 | 14.56 | PASS | |
| 15120.50† | 7536.54 | 6497.97 | -2503.11 | 7512.57 | 7536.54 | 652.12 | -1511.38 | 170.37 | 5929.38 | 404.30 | 5525.08 | 14.80 | PASS | |
| 15220.50† | 7536.64 | 6597.93 | -2500.40 | 7512.68 | 7536.64 | 652.12 | -1511.38 | 170.56 | 6027.51 | 404.33 | 5623.18 | 15.05 | PASS | |
| 15320.50† | 7536.74 | 6697.90 | -2497.68 | 7512.78 | 7536.74 | 652.12 | -1511.38 | 170.74 | 6125.70 | 404.36 | 5721.34 | 15.29 | PASS | |
| 15420.50† | 7536.85 | 6797.86 | -2494.96 | 7512.88 | 7536.85 | 652.12 | -1511.38 | 170.91 | 6223.95 | 404.38 | 5819.56 | 15.53 | PASS | |
| 15520.50† | 7536.95 | 6897.82 | -2492.24 | 7512.99 | 7536.95 | 652.12 | -1511.38 | 171.08 | 6322.25 | 404.41 | 5917.84 | 15.78 | PASS | |
| 15620.50† | 7537.05 | 6997.79 | -2489.52 | 7513.09 | 7537.05 | 652.12 | -1511.38 | 171.24 | 6420.61 | 404.44 | 6016.17 | 16.02 | PASS | |
| 15720.50† | 7537.16 | 7097.75 | -2486.80 | 7513.19 | 7537.16 | 652.12 | -1511.38 | 171.40 | 6519.02 | 404.47 | 6114.55 | 16.27 | PASS | |
| 15820.50† | 7537.26 | 7197.71 | -2484.08 | 7513.30 | 7537.26 | 652.12 | -1511.38 | 171.55 | 6617.47 | 404.50 | 6212.97 | 16.51 | PASS | |
| 15920.50† | 7537.36 | 7297.68 | -2481.36 | 7513.40 | 7537.36 | 652.12 | -1511.38 | 171.70 | 6715.97 | 404.53 | 6311.44 | 16.76 | PASS | |
| 16020.50† | 7537.47 | 7397.64 | -2478.64 | 7513.50 | 7537.47 | 652.12 | -1511.38 | 171.84 | 6814.52 | 404.56 | 6409.96 | 17.00 | PASS | |
| 16120.50† | 7537.57 | 7497.60 | -2475.93 | 7513.61 | 7537.57 | 652.12 | -1511.38 | 171.98 | 6913.10 | 404.58 | 6508.52 | 17.25 | PASS | |
| 16220.50† | 7537.68 | 7597.56 | -2473.21 | 7513.71 | 7537.68 | 652.12 | -1511.38 | 172.12 | 7011.73 | 404.61 | 6607.11 | 17.49 | PASS | |
| 16320.50† | 7537.78 | 7697.53 | -2470.49 | 7513.82 | 7537.78 | 652.12 | -1511.38 | 172.25 | 7110.39 | 404.64 | 6705.75 | 17.74 | PASS | |
| 16420.50† | 7537.88 | 7797.49 | -2467.77 | 7513.92 | 7537.88 | 652.12 | -1511.38 | 172.38 | 7209.09 | 404.67 | 6804.42 | 17.98 | PASS | |
| 16520.50† | 7537.99 | 7897.45 | -2465.05 | 7514.02 | 7537.99 | 652.12 | -1511.38 | 172.50 | 7307.83 | 404.70 | 6903.13 | 18.23 | PASS | |
| 16620.50† | 7538.09 | 7997.42 | -2462.33 | 7514.13 | 7538.09 | 652.12 | -1511.38 | 172.62 | 7406.60 | 404.72 | 7001.87 | 18.47 | PASS | |
| 16720.50† | 7538.19 | 8097.38 | -2459.61 | 7514.23 | 7538.19 | 652.12 | -1511.38 | 172.74 | 7505.40 | 404.75 | 7100.65 | 18.72 | PASS | |
| 16820.50† | 7538.30 | 8197.34 | -2456.89 | 7514.33 | 7538.30 | 652.12 | -1511.38 | 172.86 | 7604.23 | 404.78 | 7199.45 | 18.96 | PASS | |
| 16920.50† | 7538.40 | 8297.31 | -2454.17 | 7514.44 | 7538.40 | 652.12 | -1511.38 | 172.97 | 7703.10 | 404.81 | 7298.29 | 19.21 | PASS | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 75 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. HSR-CHERRY KNOLLS 9-33 AWB Offset Wellpath: EX. HSR-CHERRY KNOLLS 9-33 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.33-T01N-R65W Slot: SLOT#01 EX. HSR-CHERRY KNOLLS 9-33 (1400'FSL & 660'FEL, DA) Well: EX. HSR-CHERRY KNOLLS 9-33 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 17020.50† | 7538.50 | 8397.27 | -2451.46 | 7514.54 | 7538.50 | 652.12 | -1511.38 | 173.08 | 7801.99 | 404.84 | 7397.15 | 19.45 | PASS |
| 17120.50† | 7538.61 | 8497.23 | -2448.74 | 7514.64 | 7538.61 | 652.12 | -1511.38 | 173.19 | 7900.91 | 404.86 | 7496.05 | 19.70 | PASS |
| 17220.50† | 7538.71 | 8597.19 | -2446.02 | 7514.75 | 7538.71 | 652.12 | -1511.38 | 173.29 | 7999.86 | 404.89 | 7594.97 | 19.94 | PASS |
| 17320.50† | 7538.81 | 8697.16 | -2443.30 | 7514.85 | 7538.81 | 652.12 | -1511.38 | 173.39 | 8098.83 | 404.92 | 7693.91 | 20.19 | PASS |
| 17420.50† | 7538.92 | 8797.12 | -2440.58 | 7514.95 | 7538.92 | 652.12 | -1511.38 | 173.49 | 8197.83 | 404.95 | 7792.88 | 20.44 | PASS |
| 17520.50† | 7539.02 | 8897.08 | -2437.86 | 7515.06 | 7539.02 | 652.12 | -1511.38 | 173.59 | 8296.85 | 404.98 | 7891.88 | 20.68 | PASS |
| 17620.50† | 7539.12 | 8997.05 | -2435.14 | 7515.16 | 7539.12 | 652.12 | -1511.38 | 173.68 | 8395.90 | 405.01 | 7990.89 | 20.93 | PASS |
| 17720.50† | 7539.23 | 9097.01 | -2432.42 | 7515.26 | 7539.23 | 652.12 | -1511.38 | 173.78 | 8494.97 | 405.03 | 8089.93 | 21.17 | PASS |
| 17820.50† | 7539.33 | 9196.97 | -2429.70 | 7515.37 | 7539.33 | 652.12 | -1511.38 | 173.87 | 8594.06 | 405.06 | 8188.99 | 21.42 | PASS |
| 17920.50† | 7539.43 | 9296.94 | -2426.99 | 7515.47 | 7539.43 | 652.12 | -1511.38 | 173.95 | 8693.17 | 405.09 | 8288.08 | 21.66 | PASS |
| 17985.90 | 7539.50 | 9362.31 | -2425.21 | 7515.54 | 7539.50 | 652.12 | -1511.38 | 174.01 | 8757.99 | 405.11 | 8352.88 | 21.82 | PASS |

POSITIONAL UNCERTAINTY - Offset Wellbore: EX. HSR-CHERRY KNOLLS 9-33 AWB Offset Wellpath: EX. HSR-CHERRY KNOLLS 9-33 AWP

| | | | | |
|-----------------------------------|------------|---------|----------|---------|
| Slot Surface Uncertainty @1SD | Horizontal | 0.100ft | Vertical | 1.000ft |
| Facility Surface Uncertainty @1SD | Horizontal | 8.200ft | Vertical | 3.000ft |

WELLPATH COMPOSITION - Offset Wellbore: EX. HSR-CHERRY KNOLLS 9-33 AWB Offset Wellpath: EX. HSR-CHERRY KNOLLS 9-33 AWP

| Start MD [ft] | End MD [ft] | Positional Uncertainty Model | Log Name/Comment | Wellbore | Survey Date |
|---------------|-------------|---|--|--------------------------------|-------------|
| 0.00 | 8251.00 | BH Drift Indicator - Inclination Only (Actual Survey) | ASSUMED VERTICAL TO TD FROM COGCC <8251> | EX. HSR-CHERRY KNOLLS 9-33 AWB | |

OFFSET WELLPATH REFERENCE - Offset Wellbore: EX. HSR-CHERRY KNOLLS 9-33 AWB Offset Wellpath: EX. HSR-CHERRY KNOLLS 9-33 AWP

| | |
|---|--|
| MD Reference: Rig on SLOT#01 EX. HSR-CHERRY KNOLLS 9-33 (1400'FSL & 660'FEL, SEC.33) (RT) | Offset TVD & local coordinates use Reference Wellpath settings (See WELLPATH DATUM on page 1 of this report) |
| Ellipse Start MD | 0.00ft |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 76 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. YOUNG 01N-65W-28-8N AWP Offset Wellpath: EX. YOUNG 01N-65W-28-8N AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#01 EX. YOUNG 01N-65W-28-8N (230'FNL & 1275'FEL, PR) | | | | Well: EX. YOUNG 01N-65W-28-8N | | | | Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | |
|---|--------------|----------------|---------------|-------------------------------|-----------------|-------------------|------------------|---|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 20.50 | 20.50 | 0.00 | 0.00 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 340.64 | 9004.42 | 75.33 | 8929.09 | 126.15 | PASS |
| 120.50† | 120.50 | 0.00 | 0.00 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 340.64 | 8923.75 | 75.43 | 8848.32 | 124.84 | PASS |
| 200.00 | 200.00 | 0.00 | 0.00 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 340.64 | 8859.90 | 75.46 | 8784.44 | 123.90 | PASS |
| 220.50† | 220.50 | -0.03 | -0.07 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 340.64 | 8843.47 | 75.47 | 8768.01 | 123.66 | PASS |
| 320.50† | 320.46 | -0.93 | -2.36 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 340.67 | 8763.69 | 75.49 | 8688.20 | 122.51 | PASS |
| 420.50† | 420.28 | -3.13 | -7.88 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 340.73 | 8684.52 | 75.49 | 8609.03 | 121.40 | PASS |
| 520.50† | 519.83 | -6.60 | -16.65 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 340.83 | 8606.10 | 75.47 | 8530.62 | 120.33 | PASS |
| 620.50† | 618.99 | -11.36 | -28.64 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 340.97 | 8528.52 | 75.44 | 8453.08 | 119.30 | PASS |
| 720.50† | 717.64 | -17.38 | -43.83 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 341.15 | 8451.92 | 75.39 | 8376.54 | 118.32 | PASS |
| 820.50† | 815.66 | -24.68 | -62.22 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 341.36 | 8376.42 | 75.32 | 8301.10 | 117.37 | PASS |
| 920.50† | 912.93 | -33.22 | -83.78 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 341.61 | 8302.13 | 75.23 | 8226.90 | 116.47 | PASS |
| 1020.50† | 1009.33 | -43.02 | -108.48 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 341.90 | 8229.18 | 75.13 | 8154.05 | 115.61 | PASS |
| 1120.50† | 1104.74 | -54.05 | -136.29 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 342.22 | 8157.70 | 75.01 | 8082.69 | 114.79 | PASS |
| 1220.50† | 1199.05 | -66.30 | -167.18 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 342.58 | 8087.82 | 74.89 | 8012.93 | 114.01 | PASS |
| 1242.54 | 1219.68 | -69.16 | -174.40 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 342.66 | 8072.65 | 74.86 | 7997.79 | 113.84 | PASS |
| 1320.50† | 1292.54 | -79.39 | -200.20 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 342.96 | 8019.32 | 74.76 | 7944.55 | 113.24 | PASS |
| 1420.50† | 1385.99 | -92.51 | -233.28 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 343.35 | 7951.51 | 74.65 | 7876.86 | 112.47 | PASS |
| 1520.50† | 1479.44 | -105.63 | -266.37 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 343.73 | 7884.39 | 74.52 | 7809.87 | 111.73 | PASS |
| 1620.50† | 1572.89 | -118.75 | -299.46 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 344.11 | 7817.97 | 74.37 | 7743.60 | 111.01 | PASS |
| 1720.50† | 1666.34 | -131.87 | -332.54 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 344.49 | 7752.27 | 74.24 | 7678.03 | 110.29 | PASS |
| 1820.50† | 1759.79 | -144.99 | -365.63 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 344.87 | 7687.31 | 74.12 | 7613.19 | 109.55 | PASS |
| 1920.50† | 1853.24 | -158.12 | -398.72 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 345.25 | 7623.11 | 74.02 | 7549.09 | 108.79 | PASS |
| 2020.50† | 1946.69 | -171.24 | -431.80 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 345.63 | 7559.69 | 73.93 | 7485.76 | 108.02 | PASS |
| 2120.50† | 2040.14 | -184.36 | -464.89 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 346.01 | 7497.06 | 73.85 | 7423.21 | 107.24 | PASS |
| 2220.50† | 2133.59 | -197.48 | -497.98 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 346.39 | 7435.26 | 73.80 | 7361.46 | 106.45 | PASS |
| 2320.50† | 2227.05 | -210.60 | -531.06 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 346.77 | 7374.29 | 73.76 | 7300.53 | 105.63 | PASS |
| 2420.50† | 2320.50 | -223.72 | -564.15 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 347.14 | 7314.18 | 73.74 | 7240.44 | 104.80 | PASS |
| 2520.50† | 2413.95 | -236.84 | -597.24 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 347.52 | 7254.94 | 73.74 | 7181.21 | 103.95 | PASS |
| 2620.50† | 2507.40 | -249.96 | -630.32 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 347.89 | 7196.62 | 73.75 | 7122.86 | 103.09 | PASS |
| 2720.50† | 2600.85 | -263.08 | -663.41 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 348.27 | 7139.21 | 73.80 | 7065.42 | 102.21 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 77 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. YOUNG 01N-65W-28-8N AWP Offset Wellpath: EX. YOUNG 01N-65W-28-8N AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#01 EX. YOUNG 01N-65W-28-8N (230'FNL & 1275'FEL, PR) | | | | Well: EX. YOUNG 01N-65W-28-8N | | | | Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | |
|---|--------------|----------------|---------------|-------------------------------|-----------------|-------------------|------------------|---|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 2820.50† | 2694.30 | -276.20 | -696.50 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 348.64 | 7082.75 | 73.86 | 7008.90 | 101.31 | PASS |
| 2920.50† | 2787.75 | -289.33 | -729.58 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 349.01 | 7027.27 | 73.94 | 6953.32 | 100.39 | PASS |
| 3020.50† | 2881.20 | -302.45 | -762.67 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 349.39 | 6972.77 | 74.06 | 6898.72 | 99.45 | PASS |
| 3120.50† | 2974.65 | -315.57 | -795.76 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 349.76 | 6919.29 | 74.19 | 6845.10 | 98.50 | PASS |
| 3220.50† | 3068.11 | -328.69 | -828.84 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 350.13 | 6866.85 | 74.35 | 6792.50 | 97.53 | PASS |
| 3320.50† | 3161.56 | -341.81 | -861.93 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 350.50 | 6815.48 | 74.54 | 6740.94 | 96.54 | PASS |
| 3420.50† | 3255.01 | -354.93 | -895.02 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 350.86 | 6765.19 | 74.76 | 6690.43 | 95.53 | PASS |
| 3520.50† | 3348.46 | -368.05 | -928.10 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 351.23 | 6716.01 | 75.00 | 6641.01 | 94.51 | PASS |
| 3620.50† | 3441.91 | -381.17 | -961.19 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 351.60 | 6667.98 | 75.28 | 6592.70 | 93.48 | PASS |
| 3720.50† | 3535.36 | -394.29 | -994.28 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 351.96 | 6621.10 | 75.58 | 6545.52 | 92.42 | PASS |
| 3820.50† | 3628.81 | -407.41 | -1027.37 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 352.32 | 6575.41 | 75.91 | 6499.50 | 91.36 | PASS |
| 3920.50† | 3722.26 | -420.53 | -1060.45 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 352.69 | 6530.93 | 76.28 | 6454.66 | 90.29 | PASS |
| 4020.50† | 3815.71 | -433.66 | -1093.54 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 353.05 | 6487.69 | 76.67 | 6411.02 | 89.20 | PASS |
| 4120.50† | 3909.17 | -446.78 | -1126.63 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 353.41 | 6445.71 | 77.10 | 6368.62 | 88.11 | PASS |
| 4220.50† | 4002.62 | -459.90 | -1159.71 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 353.77 | 6405.02 | 77.56 | 6327.47 | 87.00 | PASS |
| 4320.50† | 4096.07 | -473.02 | -1192.80 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 354.12 | 6365.64 | 78.04 | 6287.59 | 85.90 | PASS |
| 4420.50† | 4189.52 | -486.14 | -1225.89 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 354.48 | 6327.59 | 78.56 | 6249.03 | 84.79 | PASS |
| 4520.50† | 4282.97 | -499.26 | -1258.97 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 354.83 | 6290.90 | 79.12 | 6211.79 | 83.68 | PASS |
| 4620.50† | 4376.42 | -512.38 | -1292.06 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 355.19 | 6255.60 | 79.70 | 6175.90 | 82.57 | PASS |
| 4720.50† | 4469.87 | -525.50 | -1325.15 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 355.54 | 6221.70 | 80.31 | 6141.39 | 81.46 | PASS |
| 4820.50† | 4563.32 | -538.62 | -1358.23 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 355.89 | 6189.24 | 80.95 | 6108.28 | 80.36 | PASS |
| 4920.50† | 4656.77 | -551.74 | -1391.32 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 356.24 | 6158.22 | 81.63 | 6076.60 | 79.26 | PASS |
| 5020.50† | 4750.22 | -564.87 | -1424.41 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 356.59 | 6128.69 | 82.33 | 6046.36 | 78.18 | PASS |
| 5120.50† | 4843.68 | -577.99 | -1457.49 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 356.94 | 6100.64 | 83.05 | 6017.59 | 77.10 | PASS |
| 5220.50† | 4937.13 | -591.11 | -1490.58 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 357.28 | 6074.12 | 83.81 | 5990.31 | 76.04 | PASS |
| 5320.50† | 5030.58 | -604.23 | -1523.67 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 357.63 | 6049.13 | 84.59 | 5964.54 | 75.00 | PASS |
| 5420.50† | 5124.03 | -617.35 | -1556.75 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 357.97 | 6025.70 | 85.40 | 5940.30 | 73.97 | PASS |
| 5520.50† | 5217.48 | -630.47 | -1589.84 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 358.31 | 6003.84 | 86.23 | 5917.61 | 72.95 | PASS |
| 5620.50† | 5310.93 | -643.59 | -1622.93 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 358.65 | 5983.57 | 87.08 | 5896.50 | 71.96 | PASS |
| 5720.50† | 5404.38 | -656.71 | -1656.01 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 358.99 | 5964.92 | 87.95 | 5876.97 | 70.99 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 78 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. YOUNG 01N-65W-28-8N AWP Offset Wellpath: EX. YOUNG 01N-65W-28-8N AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#01 EX. YOUNG 01N-65W-28-8N (230'FNL & 1275'FEL, PR) | | | | Well: EX. YOUNG 01N-65W-28-8N | | | | Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | |
|---|--------------|----------------|---------------|-------------------------------|-----------------|-------------------|------------------|---|---------------------|----------------|----------------------|-----------|-------------|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | |
| 5820.50† | 5497.83 | -669.83 | -1689.10 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 359.33 | 5947.88 | 88.84 | 5859.04 | 70.05 | PASS | |
| 5920.50† | 5591.28 | -682.95 | -1722.19 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 359.66 | 5932.48 | 89.75 | 5842.74 | 69.13 | PASS | |
| 6020.50† | 5684.74 | -696.07 | -1755.27 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 359.99 | 5918.73 | 90.67 | 5828.06 | 68.23 | PASS | |
| 6120.50† | 5778.19 | -709.20 | -1788.36 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 0.33 | 5906.65 | 91.61 | 5815.04 | 67.36 | PASS | |
| 6220.50† | 5871.64 | -722.32 | -1821.45 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 0.66 | 5896.23 | 92.56 | 5803.67 | 66.52 | PASS | |
| 6320.50† | 5965.09 | -735.44 | -1854.54 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 0.99 | 5887.50 | 93.52 | 5793.97 | 65.71 | PASS | |
| 6420.50† | 6058.54 | -748.56 | -1887.62 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 1.31 | 5880.45 | 94.49 | 5785.96 | 64.93 | PASS | |
| 6520.50† | 6151.99 | -761.68 | -1920.71 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 1.64 | 5875.09 | 95.47 | 5779.62 | 64.17 | PASS | |
| 6620.50† | 6245.44 | -774.80 | -1953.80 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 1.96 | 5871.44 | 96.46 | 5774.98 | 63.45 | PASS | |
| 6720.50† | 6338.89 | -787.92 | -1986.88 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 2.29 | 5869.48 | 97.44 | 5772.04 | 62.76 | PASS | |
| 6820.50† | 6432.34 | -801.04 | -2019.97 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 2.61 | 5869.23 | 98.43 | 5770.80 | 62.10 | PASS | |
| 6920.50† | 6525.80 | -814.16 | -2053.06 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 2.93 | 5870.69 | 99.43 | 5771.26 | 61.47 | PASS | |
| 7020.50† | 6619.25 | -827.28 | -2086.14 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 3.25 | 5873.84 | 100.42 | 5773.43 | 60.87 | PASS | |
| 7120.50† | 6712.70 | -840.41 | -2119.23 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 3.56 | 5878.70 | 101.40 | 5777.30 | 60.30 | PASS | |
| 7220.50† | 6806.15 | -853.53 | -2152.32 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 3.88 | 5885.25 | 102.39 | 5782.86 | 59.77 | PASS | |
| 7320.50† | 6899.60 | -866.65 | -2185.40 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 4.19 | 5893.49 | 103.37 | 5790.12 | 59.26 | PASS | |
| 7341.07 | 6918.82 | -869.35 | -2192.21 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 4.25 | 5895.39 | 103.57 | 5791.83 | 59.16 | PASS | |
| 7420.50† | 6993.49 | -874.29 | -2218.65 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 4.51 | 5897.94 | 104.40 | 5793.55 | 58.70 | PASS | |
| 7520.50† | 7087.21 | -864.88 | -2251.87 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 4.84 | 5887.12 | 105.72 | 5781.40 | 57.83 | PASS | |
| 7620.50† | 7177.96 | -838.35 | -2284.05 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 5.17 | 5860.89 | 107.14 | 5753.75 | 56.78 | PASS | |
| 7720.50† | 7262.97 | -795.51 | -2314.23 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 5.51 | 5819.85 | 108.37 | 5711.48 | 55.72 | PASS | |
| 7820.50† | 7339.68 | -737.65 | -2341.49 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 5.83 | 5764.96 | 109.47 | 5655.48 | 54.61 | PASS | |
| 7920.50† | 7405.75 | -666.53 | -2364.99 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 6.14 | 5697.50 | 110.45 | 5587.05 | 53.48 | PASS | |
| 8020.50† | 7459.16 | -584.32 | -2384.03 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 6.42 | 5619.11 | 111.27 | 5507.84 | 52.34 | PASS | |
| 8120.50† | 7498.30 | -493.50 | -2398.02 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 6.67 | 5531.77 | 111.92 | 5419.85 | 51.22 | PASS | |
| 8220.50† | 7521.99 | -396.85 | -2406.55 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 6.88 | 5437.77 | 112.40 | 5325.37 | 50.12 | PASS | |
| 8315.56 | 7529.50 | -302.24 | -2409.34 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 7.03 | 5344.58 | 112.71 | 5231.87 | 49.12 | PASS | |
| 8320.50† | 7529.51 | -297.30 | -2409.35 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 7.04 | 5339.68 | 112.73 | 5226.96 | 49.07 | PASS | |
| 8420.50† | 7529.61 | -197.30 | -2409.53 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 7.17 | 5240.57 | 112.99 | 5127.58 | 48.04 | PASS | |
| 8520.50† | 7529.71 | -97.30 | -2409.71 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 7.31 | 5141.49 | 113.27 | 5028.22 | 47.01 | PASS | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 79 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. YOUNG 01N-65W-28-8N AWP Offset Wellpath: EX. YOUNG 01N-65W-28-8N AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#01 EX. YOUNG 01N-65W-28-8N (230'FNL & 1275'FEL, PR) Well: EX. YOUNG 01N-65W-28-8N Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|-----------------|-------------------|------------------|-------------------|--------------------|----------------------|---------------------|-------------------------|---------------------------|----------------------|----------------------------|--------------|----------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 8620.50† | 7529.82 | 2.70 | -2409.88 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 7.46 | 5042.45 | 113.55 | 4928.89 | 45.98 | PASS |
| 8720.50† | 7529.92 | 102.70 | -2410.06 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 7.61 | 4943.44 | 113.86 | 4829.59 | 44.96 | PASS |
| 8820.50† | 7530.02 | 202.70 | -2410.24 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 7.77 | 4844.48 | 114.17 | 4730.31 | 43.93 | PASS |
| 8920.50† | 7530.13 | 302.70 | -2410.42 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 7.94 | 4745.56 | 114.50 | 4631.05 | 42.90 | PASS |
| 9020.50† | 7530.23 | 402.70 | -2410.59 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 8.11 | 4646.68 | 114.85 | 4531.83 | 41.88 | PASS |
| 9120.50† | 7530.33 | 502.70 | -2410.77 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 8.29 | 4547.86 | 115.21 | 4432.64 | 40.85 | PASS |
| 9220.50† | 7530.44 | 602.70 | -2410.95 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 8.48 | 4449.08 | 115.59 | 4333.49 | 39.83 | PASS |
| 9320.50† | 7530.54 | 702.70 | -2411.13 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 8.67 | 4350.37 | 116.00 | 4234.37 | 38.80 | PASS |
| 9420.50† | 7530.64 | 802.69 | -2411.31 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 8.88 | 4251.71 | 116.42 | 4135.29 | 37.78 | PASS |
| 9520.50† | 7530.75 | 902.69 | -2411.48 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 9.10 | 4153.12 | 116.86 | 4036.26 | 36.76 | PASS |
| 9620.50† | 7530.85 | 1002.69 | -2411.66 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 9.32 | 4054.59 | 117.33 | 3937.26 | 35.74 | PASS |
| 9720.50† | 7530.96 | 1102.69 | -2411.84 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 9.56 | 3956.14 | 117.83 | 3838.32 | 34.72 | PASS |
| 9820.50† | 7531.06 | 1202.69 | -2412.02 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 9.81 | 3857.78 | 118.35 | 3739.43 | 33.70 | PASS |
| 9920.50† | 7531.16 | 1302.69 | -2412.19 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 10.07 | 3759.49 | 118.90 | 3640.59 | 32.68 | PASS |
| 10020.50† | 7531.27 | 1402.69 | -2412.37 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 10.35 | 3661.30 | 119.48 | 3541.82 | 31.67 | PASS |
| 10120.50† | 7531.37 | 1502.69 | -2412.55 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 10.64 | 3563.21 | 120.10 | 3443.11 | 30.65 | PASS |
| 10220.50† | 7531.47 | 1602.69 | -2412.73 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 10.95 | 3465.23 | 120.76 | 3344.47 | 29.64 | PASS |
| 10320.50† | 7531.58 | 1702.69 | -2412.90 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 11.28 | 3367.37 | 121.46 | 3245.91 | 28.63 | PASS |
| 10420.50† | 7531.68 | 1802.69 | -2413.08 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 11.62 | 3269.63 | 122.20 | 3147.43 | 27.62 | PASS |
| 10520.50† | 7531.78 | 1902.69 | -2413.26 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 11.99 | 3172.04 | 123.00 | 3049.05 | 26.62 | PASS |
| 10620.50† | 7531.89 | 2002.69 | -2413.44 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 12.38 | 3074.61 | 123.84 | 2950.76 | 25.62 | PASS |
| 10720.50† | 7531.99 | 2102.69 | -2413.62 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 12.80 | 2977.34 | 124.75 | 2852.59 | 24.62 | PASS |
| 10820.50† | 7532.09 | 2202.69 | -2413.79 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 13.25 | 2880.26 | 125.72 | 2754.54 | 23.63 | PASS |
| 10920.50† | 7532.20 | 2302.69 | -2413.97 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 13.72 | 2783.39 | 126.76 | 2656.63 | 22.64 | PASS |
| 11020.50† | 7532.30 | 2402.69 | -2414.15 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 14.24 | 2686.74 | 127.88 | 2558.86 | 21.65 | PASS |
| 11120.50† | 7532.41 | 2502.69 | -2414.33 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 14.79 | 2590.36 | 129.09 | 2461.26 | 20.67 | PASS |
| 11220.50† | 7532.51 | 2602.69 | -2414.50 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 15.38 | 2494.25 | 130.40 | 2363.85 | 19.70 | PASS |
| 11320.50† | 7532.61 | 2702.69 | -2414.68 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 16.02 | 2398.46 | 131.82 | 2266.65 | 18.73 | PASS |
| 11420.50† | 7532.72 | 2802.69 | -2414.86 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 16.71 | 2303.04 | 133.36 | 2169.68 | 17.77 | PASS |
| 11520.50† | 7532.82 | 2902.69 | -2415.04 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 17.47 | 2208.01 | 135.03 | 2072.99 | 16.82 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 80 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. YOUNG 01N-65W-28-8N AWP Offset Wellpath: EX. YOUNG 01N-65W-28-8N AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#01 EX. YOUNG 01N-65W-28-8N (230'FNL & 1275'FEL, PR) Well: EX. YOUNG 01N-65W-28-8N Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 11620.50† | 7532.92 | 3002.69 | -2415.21 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 18.29 | 2113.45 | 136.85 | 1976.60 | 15.88 | PASS |
| 11720.50† | 7533.03 | 3102.69 | -2415.39 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 19.19 | 2019.41 | 138.85 | 1880.56 | 14.94 | PASS |
| 11820.50† | 7533.13 | 3202.69 | -2415.57 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 20.18 | 1925.97 | 141.04 | 1784.93 | 14.02 | PASS |
| 11920.50† | 7533.23 | 3302.69 | -2415.75 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 21.27 | 1833.23 | 143.45 | 1689.77 | 13.12 | PASS |
| 12020.50† | 7533.34 | 3402.69 | -2415.92 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 22.48 | 1741.28 | 146.11 | 1595.18 | 12.22 | PASS |
| 12120.50† | 7533.44 | 3502.69 | -2416.10 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 23.83 | 1650.28 | 149.04 | 1501.24 | 11.35 | PASS |
| 12220.50† | 7533.55 | 3602.69 | -2416.28 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 25.34 | 1560.37 | 152.28 | 1408.09 | 10.50 | PASS |
| 12320.50† | 7533.65 | 3702.69 | -2416.46 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 27.03 | 1471.77 | 155.88 | 1315.89 | 9.66 | PASS |
| 12420.50† | 7533.75 | 3802.69 | -2416.64 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 28.95 | 1384.72 | 159.86 | 1224.86 | 8.86 | PASS |
| 12520.50† | 7533.86 | 3902.69 | -2416.81 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 31.12 | 1299.54 | 164.28 | 1135.26 | 8.08 | PASS |
| 12620.50† | 7533.96 | 4002.69 | -2416.99 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 33.61 | 1216.61 | 169.15 | 1047.46 | 7.34 | PASS |
| 12720.50† | 7534.06 | 4102.69 | -2417.17 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 36.47 | 1136.44 | 174.50 | 961.93 | 6.64 | PASS |
| 12820.50† | 7534.17 | 4202.69 | -2417.35 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 39.77 | 1059.64 | 180.32 | 879.32 | 5.99 | PASS |
| 12920.50† | 7534.27 | 4302.69 | -2417.52 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 43.60 | 987.01 | 186.53 | 800.48 | 5.39 | PASS |
| 13020.50† | 7534.37 | 4402.69 | -2417.70 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 48.06 | 919.53 | 192.96 | 726.56 | 4.84 | PASS |
| 13120.50† | 7534.48 | 4502.69 | -2417.88 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 53.23 | 858.42 | 199.33 | 659.08 | 4.37 | PASS |
| 13199.97 | 7534.56 | 4582.16 | -2418.02 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 57.91 | 815.35 | 204.03 | 611.32 | 4.06 | PASS |
| 13220.50† | 7534.58 | 4602.69 | -2418.13 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 59.21 | 805.19 | 205.15 | 600.04 | 3.98 | PASS |
| 13320.50† | 7534.68 | 4702.65 | -2420.77 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 66.09 | 763.52 | 209.82 | 553.70 | 3.69 | PASS |
| 13420.50† | 7534.79 | 4802.45 | -2426.90 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 73.80 | 736.43 | 212.49 | 523.93 | 3.51 | PASS |
| 13476.50 | 7534.85 | 4858.23 | -2431.85 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 78.37 | 728.27 | 212.79 | 515.48 | 3.47 | PASS |
| 13520.50† | 7534.89 | 4902.02 | -2436.16 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 82.02 | 725.25 | 212.33 | 512.92 | 3.46 | PASS |
| 13620.50† | 7534.99 | 5001.54 | -2445.98 | 11808.00 | 7302.17 | 4997.37 | -1755.91 | 90.35 | 728.30 | 208.97 | 519.33 | 3.53 | PASS |
| 13720.50† | 7535.10 | 5101.06 | -2455.79 | 11714.87 | 7306.35 | 5090.38 | -1753.71 | 90.87 | 738.48 | 209.02 | 529.47 | 3.58 | PASS |
| 13820.50† | 7535.20 | 5200.57 | -2465.61 | 11620.97 | 7308.55 | 5184.21 | -1750.98 | 91.31 | 749.89 | 209.01 | 540.88 | 3.64 | PASS |
| 13920.50† | 7535.30 | 5300.09 | -2475.42 | 11518.19 | 7309.35 | 5286.96 | -1748.56 | 91.04 | 761.29 | 209.43 | 551.86 | 3.69 | PASS |
| 14020.50† | 7535.40 | 5399.61 | -2485.24 | 11414.50 | 7311.70 | 5390.60 | -1746.28 | 90.70 | 772.12 | 210.07 | 562.06 | 3.73 | PASS |
| 14120.50† | 7535.51 | 5499.12 | -2495.05 | 11313.35 | 7314.30 | 5491.69 | -1744.43 | 90.57 | 782.58 | 210.64 | 571.94 | 3.77 | PASS |
| 14220.50† | 7535.61 | 5598.64 | -2504.87 | 11217.51 | 7316.81 | 5587.48 | -1742.58 | 90.84 | 793.15 | 210.98 | 582.17 | 3.81 | PASS |
| 14221.87 | 7535.61 | 5600.00 | -2505.00 | 11216.22 | 7316.86 | 5588.77 | -1742.55 | 90.84 | 793.29 | 210.98 | 582.31 | 3.81 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 81 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. YOUNG 01N-65W-28-8N AWP Offset Wellpath: EX. YOUNG 01N-65W-28-8N AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#01 EX. YOUNG 01N-65W-28-8N (230'FNL & 1275'FEL, PR) Well: EX. YOUNG 01N-65W-28-8N Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | | |
|---|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | |
| 14320.50† | 7535.71 | 5698.31 | -2512.99 | 11090.36 | 7322.18 | 5714.50 | -1741.52 | 88.80 | 800.64 | 213.15 | 587.49 | 3.81 | PASS | | |
| 14420.50† | 7535.81 | 5798.19 | -2517.63 | 11001.81 | 7325.54 | 5802.99 | -1741.68 | 89.65 | 803.95 | 213.15 | 590.80 | 3.82 | PASS | | |
| 14520.50† | 7535.92 | 5898.18 | -2518.78 | 10880.08 | 7327.65 | 5924.68 | -1743.07 | 88.04 | 803.62 | 214.80 | 588.82 | 3.79 | PASS | | |
| 14581.38 | 7535.98 | 5959.05 | -2517.77 | 10806.77 | 7326.65 | 5997.88 | -1746.92 | 87.12 | 799.71 | 215.53 | 584.18 | 3.76 | PASS | | |
| 14620.50† | 7536.02 | 5998.16 | -2516.71 | 10780.64 | 7326.17 | 6023.98 | -1748.15 | 88.08 | 797.12 | 215.00 | 582.12 | 3.76 | PASS | | |
| 14720.50† | 7536.12 | 6098.12 | -2513.99 | 10707.51 | 7325.36 | 6097.08 | -1749.23 | 90.08 | 793.27 | 213.87 | 579.41 | 3.76 | PASS | | |
| 14820.50† | 7536.23 | 6198.08 | -2511.27 | 10609.93 | 7325.86 | 6194.66 | -1748.81 | 90.26 | 790.96 | 214.28 | 576.68 | 3.74 | PASS | | |
| 14920.50† | 7536.33 | 6298.05 | -2508.55 | 10508.63 | 7325.32 | 6295.96 | -1748.40 | 90.16 | 788.90 | 214.93 | 573.96 | 3.72 | PASS | | |
| 15020.50† | 7536.43 | 6398.01 | -2505.83 | 10380.68 | 7325.59 | 6423.88 | -1749.73 | 88.04 | 785.38 | 217.29 | 568.08 | 3.66 | PASS | | |
| 15120.50† | 7536.54 | 6497.97 | -2503.11 | 10268.82 | 7330.67 | 6535.56 | -1753.58 | 87.13 | 778.20 | 219.00 | 559.20 | 3.60 | PASS | | |
| 15220.50† | 7536.64 | 6597.93 | -2500.40 | 10135.17 | 7334.50 | 6668.82 | -1762.64 | 84.51 | 768.22 | 221.69 | 546.54 | 3.51 | PASS | | |
| 15320.50† | 7536.74 | 6697.90 | -2497.68 | 10049.08 | 7334.00 | 6754.54 | -1770.55 | 85.55 | 756.98 | 221.77 | 535.21 | 3.46 | PASS | | |
| 15420.50† | 7536.85 | 6797.86 | -2494.96 | 9981.86 | 7333.20 | 6821.64 | -1774.49 | 88.11 | 749.07 | 220.72 | 528.34 | 3.44 | PASS | | |
| 15520.50† | 7536.95 | 6897.82 | -2492.24 | 9888.91 | 7332.62 | 6914.55 | -1776.97 | 88.66 | 744.07 | 221.22 | 522.86 | 3.41 | PASS | | |
| 15620.50† | 7537.05 | 6997.79 | -2489.52 | 9808.50 | 7331.40 | 6994.94 | -1778.26 | 90.23 | 740.40 | 220.80 | 519.60 | 3.40 | PASS | | |
| 15720.50† | 7537.16 | 7097.75 | -2486.80 | 9727.61 | 7329.15 | 7075.79 | -1777.43 | 91.77 | 739.56 | 220.28 | 519.28 | 3.40 | PASS | | |
| 15820.50† | 7537.26 | 7197.71 | -2484.08 | 9592.10 | 7326.16 | 7211.23 | -1775.74 | 88.91 | 739.26 | 224.06 | 515.20 | 3.34 | PASS | | |
| 15920.50† | 7537.36 | 7297.68 | -2481.36 | 9483.52 | 7326.01 | 7319.76 | -1778.78 | 88.20 | 734.01 | 225.89 | 508.12 | 3.29 | PASS | | |
| 16020.50† | 7537.47 | 7397.64 | -2478.64 | 9395.33 | 7327.12 | 7407.92 | -1780.46 | 89.16 | 729.26 | 226.44 | 502.82 | 3.26 | PASS | | |
| 16120.50† | 7537.57 | 7497.60 | -2475.93 | 9302.20 | 7327.76 | 7501.05 | -1781.08 | 89.72 | 725.84 | 227.35 | 498.49 | 3.23 | PASS | | |
| 16220.50† | 7537.68 | 7597.56 | -2473.21 | 9194.65 | 7327.84 | 7608.55 | -1782.43 | 89.09 | 722.03 | 229.40 | 492.63 | 3.19 | PASS | | |
| 16320.50† | 7537.78 | 7697.53 | -2470.49 | 9101.15 | 7329.24 | 7702.07 | -1783.03 | 89.62 | 718.41 | 230.51 | 487.90 | 3.15 | PASS | | |
| 16420.50† | 7537.88 | 7797.49 | -2467.77 | 9002.00 | 7329.16 | 7801.22 | -1783.46 | 89.69 | 715.44 | 232.02 | 483.43 | 3.12 | PASS | | |
| 16520.50† | 7537.99 | 7897.45 | -2465.05 | 8901.09 | 7329.80 | 7902.13 | -1784.28 | 89.61 | 711.91 | 233.77 | 478.14 | 3.08 | PASS | | |
| 16620.50† | 7538.09 | 7997.42 | -2462.33 | 8812.76 | 7330.25 | 7990.45 | -1783.94 | 90.59 | 709.55 | 234.51 | 475.04 | 3.06 | PASS | | |
| 16720.50† | 7538.19 | 8097.38 | -2459.61 | 8716.81 | 7330.09 | 8086.39 | -1782.43 | 90.93 | 708.52 | 235.92 | 472.61 | 3.04 | PASS | | |
| 16820.50† | 7538.30 | 8197.34 | -2456.89 | 8604.71 | 7330.22 | 8198.49 | -1781.51 | 89.90 | 706.71 | 238.83 | 467.89 | 2.99 | PASS | | |
| 16920.50† | 7538.40 | 8297.31 | -2454.17 | 8499.46 | 7331.75 | 8303.72 | -1781.90 | 89.45 | 703.34 | 241.26 | 462.09 | 2.95 | PASS | | |
| 17020.50† | 7538.50 | 8397.27 | -2451.46 | 8406.33 | 7332.44 | 8396.84 | -1782.27 | 90.04 | 700.20 | 242.62 | 457.58 | 2.92 | PASS | | |
| 17120.50† | 7538.61 | 8497.23 | -2448.74 | 8304.13 | 7330.59 | 8499.02 | -1782.55 | 89.85 | 697.91 | 244.59 | 453.32 | 2.88 | PASS | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 82 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. YOUNG 01N-65W-28-8N AWB Offset Wellpath: EX. YOUNG 01N-65W-28-8N AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W | | Slot: SLOT#01 EX. YOUNG 01N-65W-28-8N (230'FNL & 1275'FEL, PR) | | Well: EX. YOUNG 01N-65W-28-8N | | Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | |
|----------------------------|--------------|--|---------------|-------------------------------|-----------------|---|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 17220.50† | 7538.71 | 8597.19 | -2446.02 | 8203.22 | 7328.12 | 8599.89 | -1783.88 | 89.77 | 694.82 | 246.41 | 448.41 | 2.85 | PASS |
| 17320.50† | 7538.81 | 8697.16 | -2443.30 | 8087.14 | 7328.01 | 8715.96 | -1785.45 | 88.36 | 691.05 | 249.79 | 441.26 | 2.80 | PASS |
| 17420.50† | 7538.92 | 8797.12 | -2440.58 | 7950.98 | 7331.13 | 8851.85 | -1793.04 | 85.17 | 682.26 | 254.70 | 427.56 | 2.71 | PASS |
| 17520.50† | 7539.02 | 8897.08 | -2437.86 | 7857.03 | 7334.51 | 8945.49 | -1799.82 | 85.66 | 671.76 | 256.56 | 415.20 | 2.64 | PASS |
| 17620.50† | 7539.12 | 8997.05 | -2435.14 | 7775.12 | 7337.85 | 9027.23 | -1803.93 | 87.26 | 663.22 | 257.57 | 405.64 | 2.60 | PASS |
| 17720.50† | 7539.23 | 9097.01 | -2432.42 | 7697.75 | 7339.29 | 9104.56 | -1805.79 | 89.31 | 657.80 | 257.90 | 399.90 | 2.57 | PASS |
| 17820.50† | 7539.33 | 9196.97 | -2429.70 | 7621.38 | 7337.22 | 9180.89 | -1805.94 | 91.48 | 655.89 | 257.56 | 398.33 | 2.57 | PASS |
| 17823.31† | 7539.33 | 9199.78 | -2429.63 | 7619.24 | 7337.10 | 9183.02 | -1805.92 | 91.54 | 655.89 | 257.54 | 398.35 | 2.57 | PASS |
| 17877.25† | 7539.39 | 9253.71 | -2428.16 | 7569.44 | 7332.42 | 9232.59 | -1805.88 | 91.94 | 656.14 | 257.82 | 398.32 | 2.57 | PASS |
| 17920.50† | 7539.43 | 9296.94 | -2426.99 | 7528.83 | 7325.57 | 9272.60 | -1806.75 | 92.25 | 656.53 | 257.71 | 398.82 | 2.57 | PASS |
| 17985.90 | 7539.50 | 9362.31 | -2425.21 | 7474.54 | 7314.17 | 9325.65 | -1808.23 | 93.40 | 657.86 | 256.52 | 401.34 | 2.59 | PASS |

POSITIONAL UNCERTAINTY - Offset Wellbore: EX. YOUNG 01N-65W-28-8N AWB Offset Wellpath: EX. YOUNG 01N-65W-28-8N AWP

| | | | | |
|-----------------------------------|------------|---------|----------|---------|
| Slot Surface Uncertainty @1SD | Horizontal | 0.100ft | Vertical | 1.000ft |
| Facility Surface Uncertainty @1SD | Horizontal | 8.200ft | Vertical | 3.000ft |

WELLPATH COMPOSITION - Offset Wellbore: EX. YOUNG 01N-65W-28-8N AWB Offset Wellpath: EX. YOUNG 01N-65W-28-8N AWP

| Start MD [ft] | End MD [ft] | Positional Uncertainty Model | Log Name/Comment | Wellbore | Survey Date |
|---------------|-------------|-------------------------------|---|-----------------------------|-------------|
| 0.00 | 11808.00 | ISCWSA MWD, Rev. 4 (Standard) | ENSIGN DIRECTIONAL MWD SURVEYS FROM COGCC <168 - 11753> | EX. YOUNG 01N-65W-28-8N AWB | 1/22/2020 |

OFFSET WELLPATH REFERENCE - Offset Wellbore: EX. YOUNG 01N-65W-28-8N AWB Offset Wellpath: EX. YOUNG 01N-65W-28-8N AWP

| | |
|--|--|
| MD Reference: Rig on SLOT#01 EX. YOUNG 01N-65W-28-8N (230'FNL & 1275'FEL, PR) (RT) | Offset TVD & local coordinates use Reference Wellpath settings (See WELLPATH DATUM on page 1 of this report) |
| Ellipse Start MD | 0.00ft |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 83 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-2-4L PWB Offset Wellpath: BUFORD 33-2-4L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#08 BUFORD 33-2-4L (770'FSL & 919'FWL, SEC.34) Well: BUFORD 33-2-4L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 20.50 | 20.50 | 0.00 | 0.00 | 20.50 | 20.50 | 0.00 | 100.85 | 90.00 | 100.85 | 9.75 | 91.11 | 16.81 | PASS |
| 120.50† | 120.50 | 0.00 | 0.00 | 120.50 | 120.50 | 0.00 | 100.85 | 90.00 | 100.85 | 9.81 | 91.04 | 16.61 | PASS |
| 200.00 | 200.00 | 0.00 | 0.00 | 200.00 | 200.00 | 0.00 | 100.85 | 90.00 | 100.85 | 9.96 | 90.89 | 16.20 | PASS |
| 220.50† | 220.50 | -0.03 | -0.07 | 221.12 | 221.12 | -0.04 | 100.79 | 90.01 | 100.86 | 10.02 | 90.84 | 16.06 | PASS |
| 320.50† | 320.46 | -0.93 | -2.36 | 324.15 | 324.11 | -1.48 | 98.61 | 90.31 | 101.03 | 10.48 | 90.55 | 14.93 | PASS |
| 420.50† | 420.28 | -3.13 | -7.88 | 427.16 | 426.92 | -4.95 | 93.34 | 91.03 | 101.45 | 11.36 | 90.09 | 13.21 | PASS |
| 520.50† | 519.83 | -6.60 | -16.65 | 530.14 | 529.41 | -10.45 | 84.98 | 92.17 | 102.15 | 12.24 | 89.92 | 11.89 | PASS |
| 620.50† | 618.99 | -11.36 | -28.64 | 633.09 | 631.44 | -17.97 | 73.56 | 93.70 | 103.17 | 13.08 | 90.08 | 10.90 | PASS |
| 720.50† | 717.64 | -17.38 | -43.83 | 735.99 | 732.86 | -27.49 | 59.10 | 95.61 | 104.54 | 13.99 | 90.55 | 10.05 | PASS |
| 820.50† | 815.66 | -24.68 | -62.22 | 838.82 | 833.54 | -39.00 | 41.61 | 97.86 | 106.33 | 14.86 | 91.47 | 9.41 | PASS |
| 920.50† | 912.93 | -33.22 | -83.78 | 940.45 | 932.30 | -52.18 | 21.60 | 100.20 | 108.81 | 15.75 | 93.06 | 8.91 | PASS |
| 1020.50† | 1009.33 | -43.02 | -108.48 | 1040.28 | 1029.16 | -65.48 | 1.40 | 101.55 | 113.89 | 16.65 | 97.24 | 8.68 | PASS |
| 1120.50† | 1104.74 | -54.05 | -136.29 | 1139.95 | 1125.86 | -78.75 | -18.77 | 101.87 | 121.94 | 17.63 | 104.30 | 8.64 | PASS |
| 1220.50† | 1199.05 | -66.30 | -167.18 | 1239.33 | 1222.28 | -91.99 | -38.87 | 101.32 | 132.90 | 18.69 | 114.22 | 8.77 | PASS |
| 1242.54 | 1219.68 | -69.16 | -174.40 | 1261.18 | 1243.48 | -94.90 | -43.29 | 101.11 | 135.71 | 18.93 | 116.79 | 8.82 | PASS |
| 1320.50† | 1292.54 | -79.39 | -200.20 | 1338.45 | 1318.45 | -105.19 | -58.93 | 100.35 | 145.93 | 19.66 | 126.27 | 9.06 | PASS |
| 1420.50† | 1385.99 | -92.51 | -233.28 | 1437.56 | 1414.61 | -118.39 | -78.98 | 99.52 | 159.06 | 20.61 | 138.45 | 9.33 | PASS |
| 1520.50† | 1479.44 | -105.63 | -266.37 | 1536.67 | 1510.77 | -131.59 | -99.03 | 98.82 | 172.22 | 21.20 | 151.02 | 9.77 | PASS |
| 1620.50† | 1572.89 | -118.75 | -299.46 | 1635.78 | 1606.93 | -144.80 | -119.08 | 98.22 | 185.40 | 21.47 | 163.93 | 10.37 | PASS |
| 1720.50† | 1666.34 | -131.87 | -332.54 | 1734.89 | 1703.08 | -158.00 | -139.13 | 97.69 | 198.60 | 21.81 | 176.78 | 10.92 | PASS |
| 1820.50† | 1759.79 | -144.99 | -365.63 | 1834.00 | 1799.24 | -171.20 | -159.18 | 97.23 | 211.81 | 22.22 | 189.59 | 11.40 | PASS |
| 1920.50† | 1853.24 | -158.12 | -398.72 | 1933.11 | 1895.40 | -184.40 | -179.23 | 96.83 | 225.04 | 22.68 | 202.35 | 11.82 | PASS |
| 2020.50† | 1946.69 | -171.24 | -431.80 | 2032.22 | 1991.56 | -197.60 | -199.28 | 96.47 | 238.27 | 23.20 | 215.07 | 12.19 | PASS |
| 2120.50† | 2040.14 | -184.36 | -464.89 | 2131.33 | 2087.72 | -210.80 | -219.34 | 96.15 | 251.51 | 23.77 | 227.74 | 12.51 | PASS |
| 2220.50† | 2133.59 | -197.48 | -497.98 | 2230.44 | 2183.88 | -224.00 | -239.39 | 95.86 | 264.77 | 24.39 | 240.38 | 12.78 | PASS |
| 2320.50† | 2227.05 | -210.60 | -531.06 | 2329.55 | 2280.03 | -237.20 | -259.44 | 95.59 | 278.02 | 25.04 | 252.98 | 13.01 | PASS |
| 2420.50† | 2320.50 | -223.72 | -564.15 | 2428.66 | 2376.19 | -250.40 | -279.49 | 95.36 | 291.28 | 25.74 | 265.54 | 13.21 | PASS |
| 2520.50† | 2413.95 | -236.84 | -597.24 | 2527.77 | 2472.35 | -263.60 | -299.54 | 95.14 | 304.55 | 26.47 | 278.08 | 13.37 | PASS |
| 2620.50† | 2507.40 | -249.96 | -630.32 | 2626.88 | 2568.51 | -276.80 | -319.59 | 94.94 | 317.82 | 27.23 | 290.59 | 13.50 | PASS |
| 2720.50† | 2600.85 | -263.08 | -663.41 | 2725.99 | 2664.67 | -290.00 | -339.64 | 94.75 | 331.09 | 28.03 | 303.07 | 13.61 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 84 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770°FSL & 819°FSL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-2-4L PWB Offset Wellpath: BUFORD 33-2-4L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#08 BUFORD 33-2-4L (770°FSL & 919°FSL, SEC.34) Well: BUFORD 33-2-4L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 2820.50† | 2694.30 | -276.20 | -696.50 | 2825.10 | 2760.83 | -303.21 | -359.69 | 94.58 | 344.37 | 28.84 | 315.53 | 13.69 | PASS |
| 2920.50† | 2787.75 | -289.33 | -729.58 | 2924.21 | 2856.98 | -316.41 | -379.74 | 94.43 | 357.65 | 29.69 | 327.96 | 13.76 | PASS |
| 3020.50† | 2881.20 | -302.45 | -762.67 | 3023.32 | 2953.14 | -329.61 | -399.80 | 94.28 | 370.93 | 30.55 | 340.38 | 13.81 | PASS |
| 3120.50† | 2974.65 | -315.57 | -795.76 | 3122.43 | 3049.30 | -342.81 | -419.85 | 94.15 | 384.22 | 31.43 | 352.79 | 13.85 | PASS |
| 3220.50† | 3068.11 | -328.69 | -828.84 | 3221.54 | 3145.46 | -356.01 | -439.90 | 94.02 | 397.50 | 32.33 | 365.17 | 13.88 | PASS |
| 3320.50† | 3161.56 | -341.81 | -861.93 | 3320.65 | 3241.62 | -369.21 | -459.95 | 93.90 | 410.79 | 33.25 | 377.54 | 13.90 | PASS |
| 3420.50† | 3255.01 | -354.93 | -895.02 | 3419.76 | 3337.78 | -382.41 | -480.00 | 93.79 | 424.08 | 34.18 | 389.90 | 13.91 | PASS |
| 3520.50† | 3348.46 | -368.05 | -928.10 | 3518.87 | 3433.93 | -395.61 | -500.05 | 93.68 | 437.37 | 35.12 | 402.25 | 13.92 | PASS |
| 3620.50† | 3441.91 | -381.17 | -961.19 | 3617.98 | 3530.09 | -408.81 | -520.10 | 93.59 | 450.67 | 36.08 | 414.59 | 13.92 | PASS |
| 3720.50† | 3535.36 | -394.29 | -994.28 | 3717.09 | 3626.25 | -422.01 | -540.15 | 93.49 | 463.96 | 37.05 | 426.91 | 13.91 | PASS |
| 3820.50† | 3628.81 | -407.41 | -1027.37 | 3816.20 | 3722.41 | -435.21 | -560.21 | 93.41 | 477.25 | 38.02 | 439.23 | 13.90 | PASS |
| 3920.50† | 3722.26 | -420.53 | -1060.45 | 3915.31 | 3818.57 | -448.42 | -580.26 | 93.32 | 490.55 | 39.01 | 451.54 | 13.89 | PASS |
| 4020.50† | 3815.71 | -433.66 | -1093.54 | 4014.41 | 3914.73 | -461.62 | -600.31 | 93.25 | 503.85 | 40.00 | 463.84 | 13.88 | PASS |
| 4120.50† | 3909.17 | -446.78 | -1126.63 | 4113.52 | 4010.88 | -474.82 | -620.36 | 93.17 | 517.14 | 41.01 | 476.14 | 13.86 | PASS |
| 4220.50† | 4002.62 | -459.90 | -1159.71 | 4212.63 | 4107.04 | -488.02 | -640.41 | 93.10 | 530.44 | 42.02 | 488.43 | 13.84 | PASS |
| 4320.50† | 4096.07 | -473.02 | -1192.80 | 4311.74 | 4203.20 | -501.22 | -660.46 | 93.03 | 543.74 | 43.03 | 500.71 | 13.82 | PASS |
| 4420.50† | 4189.52 | -486.14 | -1225.89 | 4410.85 | 4299.36 | -514.42 | -680.51 | 92.97 | 557.04 | 44.05 | 512.99 | 13.80 | PASS |
| 4520.50† | 4282.97 | -499.26 | -1258.97 | 4509.96 | 4395.52 | -527.62 | -700.56 | 92.91 | 570.34 | 45.08 | 525.26 | 13.78 | PASS |
| 4620.50† | 4376.42 | -512.38 | -1292.06 | 4609.07 | 4491.68 | -540.82 | -720.61 | 92.85 | 583.65 | 46.12 | 537.53 | 13.76 | PASS |
| 4720.50† | 4469.87 | -525.50 | -1325.15 | 4708.18 | 4587.83 | -554.02 | -740.67 | 92.79 | 596.95 | 47.16 | 549.79 | 13.74 | PASS |
| 4820.50† | 4563.32 | -538.62 | -1358.23 | 4807.29 | 4683.99 | -567.22 | -760.72 | 92.74 | 610.25 | 48.20 | 562.05 | 13.71 | PASS |
| 4920.50† | 4656.77 | -551.74 | -1391.32 | 4906.40 | 4780.15 | -580.42 | -780.77 | 92.69 | 623.55 | 49.25 | 574.31 | 13.69 | PASS |
| 5020.50† | 4750.22 | -564.87 | -1424.41 | 5005.51 | 4876.31 | -593.63 | -800.82 | 92.64 | 636.86 | 50.30 | 586.56 | 13.67 | PASS |
| 5120.50† | 4843.68 | -577.99 | -1457.49 | 5104.62 | 4972.47 | -606.83 | -820.87 | 92.59 | 650.16 | 51.35 | 598.81 | 13.64 | PASS |
| 5220.50† | 4937.13 | -591.11 | -1490.58 | 5203.73 | 5068.63 | -620.03 | -840.92 | 92.55 | 663.46 | 52.41 | 611.05 | 13.62 | PASS |
| 5320.50† | 5030.58 | -604.23 | -1523.67 | 5302.84 | 5164.78 | -633.23 | -860.97 | 92.51 | 676.77 | 53.47 | 623.30 | 13.60 | PASS |
| 5420.50† | 5124.03 | -617.35 | -1556.75 | 5401.95 | 5260.94 | -646.43 | -881.02 | 92.46 | 690.07 | 54.54 | 635.54 | 13.57 | PASS |
| 5520.50† | 5217.48 | -630.47 | -1589.84 | 5501.06 | 5357.10 | -659.63 | -901.08 | 92.42 | 703.38 | 55.60 | 647.77 | 13.55 | PASS |
| 5620.50† | 5310.93 | -643.59 | -1622.93 | 5600.17 | 5453.26 | -672.83 | -921.13 | 92.39 | 716.68 | 56.67 | 660.01 | 13.53 | PASS |
| 5720.50† | 5404.38 | -656.71 | -1656.01 | 5699.28 | 5549.42 | -686.03 | -941.18 | 92.35 | 729.99 | 57.75 | 672.24 | 13.50 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 85 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-2-4L PWB Offset Wellpath: BUFORD 33-2-4L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#08 BUFORD 33-2-4L (770'FSL & 919'FWL, SEC.34) Well: BUFORD 33-2-4L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | Sep Ratio | Rule Status |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | | |
| 5820.50† | 5497.83 | -669.83 | -1689.10 | 5798.39 | 5645.58 | -699.23 | -961.23 | 92.31 | 743.30 | 58.82 | 684.47 | 13.48 | PASS |
| 5920.50† | 5591.28 | -682.95 | -1722.19 | 5897.50 | 5741.73 | -712.43 | -981.28 | 92.28 | 756.60 | 59.90 | 696.70 | 13.46 | PASS |
| 6020.50† | 5684.74 | -696.07 | -1755.27 | 5996.61 | 5837.89 | -725.63 | -1001.33 | 92.25 | 769.91 | 60.98 | 708.93 | 13.44 | PASS |
| 6120.50† | 5778.19 | -709.20 | -1788.36 | 6095.72 | 5934.05 | -738.83 | -1021.38 | 92.21 | 783.22 | 62.06 | 721.16 | 13.42 | PASS |
| 6220.50† | 5871.64 | -722.32 | -1821.45 | 6194.83 | 6030.21 | -752.04 | -1041.43 | 92.18 | 796.52 | 63.14 | 733.38 | 13.40 | PASS |
| 6320.50† | 5965.09 | -735.44 | -1854.54 | 6293.94 | 6126.37 | -765.24 | -1061.49 | 92.15 | 809.83 | 64.23 | 745.60 | 13.38 | PASS |
| 6420.50† | 6058.54 | -748.56 | -1887.62 | 6393.05 | 6222.53 | -778.44 | -1081.54 | 92.12 | 823.14 | 65.31 | 757.82 | 13.36 | PASS |
| 6520.50† | 6151.99 | -761.68 | -1920.71 | 6492.16 | 6318.68 | -791.64 | -1101.59 | 92.10 | 836.45 | 66.40 | 770.04 | 13.34 | PASS |
| 6620.50† | 6245.44 | -774.80 | -1953.80 | 6591.27 | 6414.84 | -804.84 | -1121.64 | 92.07 | 849.75 | 67.49 | 782.26 | 13.32 | PASS |
| 6720.50† | 6338.89 | -787.92 | -1986.88 | 6690.38 | 6511.00 | -818.04 | -1141.69 | 92.04 | 863.06 | 68.58 | 794.48 | 13.30 | PASS |
| 6820.50† | 6432.34 | -801.04 | -2019.97 | 6789.49 | 6607.16 | -831.24 | -1161.74 | 92.02 | 876.37 | 69.68 | 806.69 | 13.28 | PASS |
| 6920.50† | 6525.80 | -814.16 | -2053.06 | 6888.60 | 6703.32 | -844.44 | -1181.79 | 91.99 | 889.68 | 70.77 | 818.91 | 13.26 | PASS |
| 7020.50† | 6619.25 | -827.28 | -2086.14 | 6987.71 | 6799.48 | -857.64 | -1201.84 | 91.97 | 902.99 | 71.87 | 831.12 | 13.24 | PASS |
| 7120.50† | 6712.70 | -840.41 | -2119.23 | 7087.46 | 6896.27 | -870.81 | -1222.03 | 91.94 | 916.29 | 72.96 | 843.33 | 13.23 | PASS |
| 7220.50† | 6806.15 | -853.53 | -2152.32 | 7190.89 | 6997.36 | -883.21 | -1243.12 | 91.24 | 929.29 | 73.40 | 855.89 | 13.33 | PASS |
| 7320.50† | 6899.60 | -866.65 | -2185.40 | 7287.35 | 7090.59 | -896.70 | -1262.61 | 89.51 | 942.39 | 73.61 | 868.78 | 13.48 | PASS |
| 7341.07 | 6918.82 | -869.35 | -2192.21 | 7305.91 | 7108.19 | -894.08 | -1266.28 | 89.06 | 945.21 | 73.57 | 871.65 | 13.53 | PASS |
| 7420.50† | 6993.49 | -874.29 | -2218.65 | 7375.12 | 7172.28 | -901.79 | -1279.69 | 87.41 | 956.77 | 72.11 | 884.66 | 13.99 | PASS |
| 7520.50† | 7087.21 | -884.88 | -2251.87 | 7458.57 | 7245.35 | -914.67 | -1295.00 | 85.80 | 972.38 | 73.19 | 899.20 | 13.99 | PASS |
| 7620.50† | 7177.96 | -898.35 | -2284.05 | 7538.78 | 7309.90 | -929.14 | -1308.54 | 84.78 | 988.43 | 73.11 | 915.32 | 14.24 | PASS |
| 7720.50† | 7262.97 | -915.51 | -2314.23 | 7616.50 | 7365.92 | -946.66 | -1320.31 | 84.32 | 1004.11 | 73.10 | 931.02 | 14.47 | PASS |
| 7820.50† | 7339.68 | -937.65 | -2341.49 | 7692.33 | 7413.39 | -968.45 | -1330.30 | 84.40 | 1018.70 | 72.95 | 945.76 | 14.71 | PASS |
| 7920.50† | 7405.75 | -966.53 | -2364.99 | 7766.71 | 7452.25 | -995.62 | -1338.51 | 84.94 | 1031.55 | 72.71 | 958.84 | 14.95 | PASS |
| 8020.50† | 7459.16 | -984.32 | -2384.03 | 7840.04 | 7482.44 | -1019.16 | -1344.91 | 85.86 | 1042.09 | 72.45 | 969.65 | 15.16 | PASS |
| 8120.50† | 7498.30 | -993.50 | -2398.02 | 7912.62 | 7503.91 | -1040.03 | -1349.49 | 87.08 | 1049.91 | 72.22 | 977.69 | 15.33 | PASS |
| 8220.50† | 7521.99 | -996.85 | -2406.55 | 7984.73 | 7516.60 | -1069.15 | -1352.24 | 88.50 | 1054.68 | 72.07 | 982.61 | 15.43 | PASS |
| 8315.56 | 7529.50 | -997.24 | -2409.34 | 8053.58 | 7520.50 | -1080.45 | -1353.16 | 89.90 | 1056.23 | 72.00 | 984.22 | 15.47 | PASS |
| 8320.50† | 7529.51 | -297.30 | -2409.35 | 8058.52 | 7520.51 | -295.52 | -1353.17 | 89.90 | 1056.23 | 71.98 | 984.25 | 15.48 | PASS |
| 8420.50† | 7529.61 | -197.30 | -2409.53 | 8158.52 | 7520.61 | -195.52 | -1353.33 | 89.90 | 1056.23 | 71.57 | 984.67 | 15.57 | PASS |
| 8520.50† | 7529.71 | -97.30 | -2409.71 | 8258.52 | 7520.71 | -95.52 | -1353.50 | 89.90 | 1056.24 | 71.48 | 984.76 | 15.59 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 86 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-2-4L PWB Offset Wellpath: BUFORD 33-2-4L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#08 BUFORD 33-2-4L (770'FSL & 919'FWL, SEC.34) Well: BUFORD 33-2-4L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 8620.50† | 7529.82 | 2.70 | -2409.88 | 8358.52 | 7520.82 | 4.48 | -1353.67 | 89.90 | 1056.25 | 71.62 | 984.64 | 15.56 | PASS |
| 8720.50† | 7529.92 | 102.70 | -2410.06 | 8458.52 | 7520.92 | 104.48 | -1353.84 | 89.90 | 1056.26 | 72.01 | 984.26 | 15.47 | PASS |
| 8820.50† | 7530.02 | 202.70 | -2410.24 | 8558.52 | 7521.02 | 204.48 | -1354.01 | 89.90 | 1056.27 | 72.60 | 983.67 | 15.34 | PASS |
| 8920.50† | 7530.13 | 302.70 | -2410.42 | 8658.52 | 7521.13 | 304.48 | -1354.18 | 89.90 | 1056.28 | 73.41 | 982.87 | 15.16 | PASS |
| 9020.50† | 7530.23 | 402.70 | -2410.59 | 8758.52 | 7521.23 | 404.48 | -1354.34 | 89.90 | 1056.29 | 74.43 | 981.86 | 14.94 | PASS |
| 9120.50† | 7530.33 | 502.70 | -2410.77 | 8858.52 | 7521.33 | 504.48 | -1354.51 | 89.90 | 1056.30 | 75.65 | 980.65 | 14.68 | PASS |
| 9220.50† | 7530.44 | 602.70 | -2410.95 | 8958.52 | 7521.44 | 604.48 | -1354.68 | 89.90 | 1056.31 | 77.05 | 979.26 | 14.40 | PASS |
| 9320.50† | 7530.54 | 702.70 | -2411.13 | 9058.52 | 7521.54 | 704.48 | -1354.85 | 89.90 | 1056.32 | 78.64 | 977.68 | 14.10 | PASS |
| 9420.50† | 7530.64 | 802.69 | -2411.31 | 9158.52 | 7521.64 | 804.48 | -1355.02 | 89.90 | 1056.33 | 80.39 | 975.94 | 13.77 | PASS |
| 9520.50† | 7530.75 | 902.69 | -2411.48 | 9258.52 | 7521.75 | 904.48 | -1355.19 | 89.90 | 1056.34 | 82.29 | 974.05 | 13.44 | PASS |
| 9620.50† | 7530.85 | 1002.69 | -2411.66 | 9358.52 | 7521.85 | 1004.48 | -1355.35 | 89.90 | 1056.35 | 84.34 | 972.01 | 13.10 | PASS |
| 9720.50† | 7530.96 | 1102.69 | -2411.84 | 9458.52 | 7521.96 | 1104.48 | -1355.52 | 89.90 | 1056.36 | 86.53 | 969.83 | 12.75 | PASS |
| 9820.50† | 7531.06 | 1202.69 | -2412.02 | 9558.52 | 7522.06 | 1204.48 | -1355.69 | 89.90 | 1056.37 | 88.83 | 967.53 | 12.40 | PASS |
| 9920.50† | 7531.16 | 1302.69 | -2412.19 | 9658.52 | 7522.16 | 1304.48 | -1355.86 | 89.90 | 1056.37 | 91.25 | 965.12 | 12.06 | PASS |
| 10020.50† | 7531.27 | 1402.69 | -2412.37 | 9758.52 | 7522.27 | 1404.48 | -1356.03 | 89.90 | 1056.38 | 93.78 | 962.60 | 11.72 | PASS |
| 10120.50† | 7531.37 | 1502.69 | -2412.55 | 9858.52 | 7522.37 | 1504.48 | -1356.20 | 89.90 | 1056.38 | 96.40 | 959.99 | 11.39 | PASS |
| 10220.50† | 7531.47 | 1602.69 | -2412.73 | 9958.52 | 7522.47 | 1604.48 | -1356.36 | 89.90 | 1056.40 | 99.11 | 957.29 | 11.06 | PASS |
| 10320.50† | 7531.58 | 1702.69 | -2412.90 | 10058.52 | 7522.58 | 1704.48 | -1356.53 | 89.90 | 1056.41 | 101.90 | 954.51 | 10.75 | PASS |
| 10420.50† | 7531.68 | 1802.69 | -2413.08 | 10158.52 | 7522.68 | 1804.48 | -1356.70 | 89.90 | 1056.42 | 104.77 | 951.65 | 10.44 | PASS |
| 10520.50† | 7531.78 | 1902.69 | -2413.26 | 10258.52 | 7522.78 | 1904.48 | -1356.87 | 89.90 | 1056.43 | 107.70 | 948.73 | 10.15 | PASS |
| 10620.50† | 7531.89 | 2002.69 | -2413.44 | 10358.52 | 7522.89 | 2004.48 | -1357.04 | 89.90 | 1056.44 | 110.70 | 945.74 | 9.86 | PASS |
| 10720.50† | 7531.99 | 2102.69 | -2413.62 | 10458.52 | 7522.99 | 2104.48 | -1357.21 | 89.90 | 1056.45 | 113.75 | 942.70 | 9.59 | PASS |
| 10820.50† | 7532.09 | 2202.69 | -2413.79 | 10558.52 | 7523.09 | 2204.48 | -1357.37 | 89.90 | 1056.46 | 116.85 | 939.61 | 9.32 | PASS |
| 10920.50† | 7532.20 | 2302.69 | -2413.97 | 10658.52 | 7523.20 | 2304.48 | -1357.54 | 89.90 | 1056.47 | 120.00 | 936.46 | 9.07 | PASS |
| 11020.50† | 7532.30 | 2402.69 | -2414.15 | 10758.52 | 7523.30 | 2404.48 | -1357.71 | 89.90 | 1056.48 | 123.20 | 933.28 | 8.83 | PASS |
| 11120.50† | 7532.41 | 2502.69 | -2414.33 | 10858.52 | 7523.40 | 2504.48 | -1357.88 | 89.90 | 1056.49 | 126.44 | 930.05 | 8.59 | PASS |
| 11220.50† | 7532.51 | 2602.69 | -2414.50 | 10958.52 | 7523.51 | 2604.48 | -1358.05 | 89.90 | 1056.50 | 129.72 | 926.78 | 8.37 | PASS |
| 11320.50† | 7532.61 | 2702.69 | -2414.68 | 11058.52 | 7523.61 | 2704.48 | -1358.22 | 89.90 | 1056.50 | 133.03 | 923.48 | 8.16 | PASS |
| 11420.50† | 7532.72 | 2802.69 | -2414.86 | 11158.52 | 7523.71 | 2804.48 | -1358.38 | 89.90 | 1056.51 | 136.37 | 920.14 | 7.95 | PASS |
| 11520.50† | 7532.82 | 2902.69 | -2415.04 | 11258.52 | 7523.82 | 2904.48 | -1358.55 | 89.90 | 1056.52 | 139.74 | 916.78 | 7.75 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 87 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-2-4L PWB Offset Wellpath: BUFORD 33-2-4L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#08 BUFORD 33-2-4L (770'FSL & 919'FWL,SEC.34) Well: BUFORD 33-2-4L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 11620.50† | 7532.92 | 3002.69 | -2415.21 | 11358.52 | 7523.92 | 3004.48 | -1358.72 | 89.90 | 1056.53 | 143.14 | 913.39 | 7.56 | PASS |
| 11720.50† | 7533.03 | 3102.69 | -2415.39 | 11458.52 | 7524.02 | 3104.48 | -1358.89 | 89.90 | 1056.54 | 146.57 | 909.97 | 7.38 | PASS |
| 11820.50† | 7533.13 | 3202.69 | -2415.57 | 11558.52 | 7524.13 | 3204.48 | -1359.06 | 89.90 | 1056.55 | 150.02 | 906.53 | 7.21 | PASS |
| 11920.50† | 7533.23 | 3302.69 | -2415.75 | 11658.52 | 7524.23 | 3304.48 | -1359.23 | 89.90 | 1056.56 | 153.49 | 903.07 | 7.04 | PASS |
| 12020.50† | 7533.34 | 3402.69 | -2415.92 | 11758.52 | 7524.33 | 3404.48 | -1359.39 | 89.90 | 1056.57 | 156.99 | 899.58 | 6.88 | PASS |
| 12120.50† | 7533.44 | 3502.69 | -2416.10 | 11858.52 | 7524.44 | 3504.48 | -1359.56 | 89.90 | 1056.58 | 160.50 | 896.08 | 6.73 | PASS |
| 12220.50† | 7533.55 | 3602.69 | -2416.28 | 11958.52 | 7524.54 | 3604.48 | -1359.73 | 89.90 | 1056.59 | 164.03 | 892.56 | 6.58 | PASS |
| 12320.50† | 7533.65 | 3702.69 | -2416.46 | 12058.52 | 7524.64 | 3704.48 | -1359.90 | 89.90 | 1056.60 | 167.58 | 889.02 | 6.43 | PASS |
| 12420.50† | 7533.75 | 3802.69 | -2416.64 | 12158.52 | 7524.75 | 3804.48 | -1360.07 | 89.90 | 1056.61 | 171.19 | 885.41 | 6.30 | PASS |
| 12520.50† | 7533.86 | 3902.69 | -2416.81 | 12258.52 | 7524.85 | 3904.48 | -1360.24 | 89.90 | 1056.62 | 174.72 | 881.90 | 6.17 | PASS |
| 12620.50† | 7533.96 | 4002.69 | -2416.99 | 12358.52 | 7524.95 | 4004.48 | -1360.40 | 89.90 | 1056.63 | 178.31 | 878.31 | 6.04 | PASS |
| 12720.50† | 7534.06 | 4102.69 | -2417.17 | 12458.52 | 7525.06 | 4104.48 | -1360.57 | 89.90 | 1056.64 | 181.92 | 874.72 | 5.92 | PASS |
| 12820.50† | 7534.17 | 4202.69 | -2417.35 | 12558.52 | 7525.16 | 4204.48 | -1360.74 | 89.90 | 1056.64 | 185.54 | 871.11 | 5.80 | PASS |
| 12920.50† | 7534.27 | 4302.69 | -2417.52 | 12658.52 | 7525.26 | 4304.48 | -1360.91 | 89.90 | 1056.65 | 189.17 | 867.49 | 5.68 | PASS |
| 13020.50† | 7534.37 | 4402.69 | -2417.70 | 12758.52 | 7525.37 | 4404.48 | -1361.08 | 89.90 | 1056.66 | 192.81 | 863.86 | 5.57 | PASS |
| 13120.50† | 7534.48 | 4502.69 | -2417.88 | 12858.52 | 7525.47 | 4504.48 | -1361.25 | 89.90 | 1056.67 | 196.46 | 860.21 | 5.47 | PASS |
| 13199.97 | 7534.56 | 4582.16 | -2418.02 | 12937.99 | 7525.55 | 4583.95 | -1361.38 | 89.90 | 1056.68 | 199.36 | 857.32 | 5.39 | PASS |
| 13220.50† | 7534.58 | 4602.69 | -2418.13 | 12958.52 | 7525.58 | 4604.47 | -1361.41 | 89.90 | 1056.76 | 200.11 | 856.64 | 5.37 | PASS |
| 13320.50† | 7534.68 | 4702.65 | -2420.77 | 13058.49 | 7525.68 | 4704.44 | -1361.58 | 89.90 | 1059.23 | 203.77 | 855.45 | 5.28 | PASS |
| 13420.50† | 7534.79 | 4802.45 | -2426.90 | 13158.30 | 7525.78 | 4804.26 | -1361.75 | 89.90 | 1065.18 | 207.47 | 857.71 | 5.22 | PASS |
| 13476.50 | 7534.85 | 4858.23 | -2431.85 | 13214.09 | 7525.84 | 4860.05 | -1361.84 | 89.90 | 1070.04 | 209.54 | 860.50 | 5.19 | PASS |
| 13520.50† | 7534.89 | 4902.02 | -2436.16 | 13257.89 | 7525.88 | 4903.84 | -1361.92 | 89.90 | 1074.29 | 211.16 | 863.12 | 5.17 | PASS |
| 13620.50† | 7534.99 | 5001.54 | -2445.98 | 13357.42 | 7525.99 | 5003.37 | -1362.09 | 89.90 | 1083.93 | 214.87 | 869.06 | 5.12 | PASS |
| 13720.50† | 7535.10 | 5101.06 | -2455.79 | 13456.95 | 7526.09 | 5102.91 | -1362.25 | 89.90 | 1093.58 | 218.60 | 874.98 | 5.08 | PASS |
| 13820.50† | 7535.20 | 5200.57 | -2465.61 | 13556.49 | 7526.19 | 5202.44 | -1362.42 | 89.90 | 1103.23 | 222.33 | 880.89 | 5.03 | PASS |
| 13920.50† | 7535.30 | 5300.09 | -2475.42 | 13656.02 | 7526.30 | 5301.97 | -1362.59 | 89.90 | 1112.87 | 226.08 | 886.80 | 4.99 | PASS |
| 14020.50† | 7535.40 | 5399.61 | -2485.24 | 13755.55 | 7526.40 | 5401.51 | -1362.76 | 89.90 | 1122.52 | 229.82 | 892.69 | 4.95 | PASS |
| 14120.50† | 7535.51 | 5499.12 | -2495.05 | 13855.09 | 7526.50 | 5501.04 | -1362.92 | 89.90 | 1132.17 | 233.58 | 898.58 | 4.91 | PASS |
| 14220.50† | 7535.61 | 5598.64 | -2504.87 | 13954.62 | 7526.61 | 5600.57 | -1363.09 | 89.90 | 1141.81 | 237.34 | 904.47 | 4.88 | PASS |
| 14221.87 | 7535.61 | 5600.00 | -2505.00 | 13955.98 | 7526.61 | 5601.93 | -1363.09 | 89.90 | 1141.94 | 237.39 | 904.55 | 4.88 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 88 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-2-4L PWB Offset Wellpath: BUFORD 33-2-4L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#08 BUFORD 33-2-4L (770'FSL & 919'FWL,SEC.34) Well: BUFORD 33-2-4L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|-----------------|-------------------|------------------|-------------------|--------------------|----------------------|---------------------|-------------------------|---------------------------|----------------------|----------------------------|--------------|----------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 14320.50† | 7535.71 | 5698.31 | -2512.99 | 14054.30 | 7526.71 | 5700.25 | -1363.26 | 89.90 | 1149.77 | 241.09 | 908.67 | 4.83 | PASS |
| 14420.50† | 7535.81 | 5798.19 | -2517.63 | 14154.19 | 7526.81 | 5800.15 | -1363.43 | 89.90 | 1154.24 | 244.86 | 909.38 | 4.78 | PASS |
| 14520.50† | 7535.92 | 5898.18 | -2518.78 | 14254.18 | 7526.92 | 5900.13 | -1363.60 | 89.90 | 1155.22 | 248.63 | 906.59 | 4.71 | PASS |
| 14581.38 | 7535.98 | 5959.05 | -2517.77 | 14315.05 | 7526.98 | 5961.01 | -1363.70 | 89.90 | 1154.11 | 250.91 | 903.20 | 4.66 | PASS |
| 14620.50† | 7536.02 | 5998.16 | -2516.71 | 14354.16 | 7527.02 | 6000.11 | -1363.76 | 89.90 | 1152.98 | 252.36 | 900.62 | 4.63 | PASS |
| 14720.50† | 7536.12 | 6098.12 | -2513.99 | 14454.11 | 7527.12 | 6100.07 | -1363.93 | 89.90 | 1150.09 | 256.10 | 894.00 | 4.55 | PASS |
| 14820.50† | 7536.23 | 6198.08 | -2511.27 | 14554.07 | 7527.23 | 6200.02 | -1364.10 | 89.90 | 1147.21 | 259.85 | 887.36 | 4.47 | PASS |
| 14920.50† | 7536.33 | 6298.05 | -2508.55 | 14654.03 | 7527.33 | 6299.98 | -1364.27 | 89.90 | 1144.32 | 263.60 | 880.72 | 4.39 | PASS |
| 15020.50† | 7536.43 | 6398.01 | -2505.83 | 14753.99 | 7527.43 | 6399.94 | -1364.44 | 89.90 | 1141.43 | 267.36 | 874.08 | 4.32 | PASS |
| 15120.50† | 7536.54 | 6497.97 | -2503.11 | 14853.95 | 7527.54 | 6499.90 | -1364.61 | 89.90 | 1138.55 | 271.12 | 867.43 | 4.25 | PASS |
| 15220.50† | 7536.64 | 6597.93 | -2500.40 | 14953.91 | 7527.64 | 6599.86 | -1364.77 | 89.90 | 1135.66 | 274.88 | 860.78 | 4.18 | PASS |
| 15320.50† | 7536.74 | 6697.90 | -2497.68 | 15053.86 | 7527.74 | 6699.81 | -1364.94 | 89.90 | 1132.77 | 278.65 | 854.12 | 4.11 | PASS |
| 15420.50† | 7536.85 | 6797.86 | -2494.96 | 15153.82 | 7527.85 | 6799.77 | -1365.11 | 89.90 | 1129.88 | 282.42 | 847.46 | 4.04 | PASS |
| 15520.50† | 7536.95 | 6897.82 | -2492.24 | 15253.78 | 7527.95 | 6899.73 | -1365.28 | 89.90 | 1127.00 | 286.20 | 840.80 | 3.98 | PASS |
| 15620.50† | 7537.05 | 6997.79 | -2489.52 | 15353.74 | 7528.05 | 6999.69 | -1365.45 | 89.90 | 1124.11 | 289.97 | 834.14 | 3.92 | PASS |
| 15720.50† | 7537.16 | 7097.75 | -2486.80 | 15453.70 | 7528.16 | 7099.65 | -1365.62 | 89.90 | 1121.22 | 293.75 | 827.47 | 3.86 | PASS |
| 15820.50† | 7537.26 | 7197.71 | -2484.08 | 15553.66 | 7528.26 | 7199.60 | -1365.78 | 89.90 | 1118.34 | 297.54 | 820.80 | 3.80 | PASS |
| 15920.50† | 7537.36 | 7297.68 | -2481.36 | 15653.61 | 7528.36 | 7299.56 | -1365.95 | 89.90 | 1115.45 | 301.32 | 814.13 | 3.74 | PASS |
| 16020.50† | 7537.47 | 7397.64 | -2478.64 | 15753.57 | 7528.47 | 7399.52 | -1366.12 | 89.90 | 1112.56 | 305.11 | 807.45 | 3.68 | PASS |
| 16120.50† | 7537.57 | 7497.60 | -2475.93 | 15853.53 | 7528.57 | 7499.48 | -1366.29 | 89.90 | 1109.68 | 308.90 | 800.77 | 3.63 | PASS |
| 16220.50† | 7537.68 | 7597.56 | -2473.21 | 15953.49 | 7528.67 | 7599.44 | -1366.46 | 89.90 | 1106.79 | 312.70 | 794.09 | 3.57 | PASS |
| 16320.50† | 7537.78 | 7697.53 | -2470.49 | 16053.45 | 7528.78 | 7699.40 | -1366.62 | 89.90 | 1103.90 | 316.49 | 787.41 | 3.52 | PASS |
| 16420.50† | 7537.88 | 7797.49 | -2467.77 | 16153.41 | 7528.88 | 7799.35 | -1366.79 | 89.90 | 1101.01 | 320.29 | 780.72 | 3.47 | PASS |
| 16520.50† | 7537.99 | 7897.45 | -2465.05 | 16253.36 | 7528.98 | 7899.31 | -1366.96 | 89.90 | 1098.13 | 324.09 | 774.03 | 3.42 | PASS |
| 16620.50† | 7538.09 | 7997.42 | -2462.33 | 16353.32 | 7529.09 | 7999.27 | -1367.13 | 89.90 | 1095.24 | 327.89 | 767.35 | 3.37 | PASS |
| 16720.50† | 7538.19 | 8097.38 | -2459.61 | 16453.28 | 7529.19 | 8099.23 | -1367.30 | 89.90 | 1092.35 | 331.70 | 760.65 | 3.32 | PASS |
| 16820.50† | 7538.30 | 8197.34 | -2456.89 | 16553.24 | 7529.29 | 8199.19 | -1367.47 | 89.90 | 1089.47 | 335.51 | 753.96 | 3.27 | PASS |
| 16920.50† | 7538.40 | 8297.31 | -2454.17 | 16653.20 | 7529.40 | 8299.14 | -1367.63 | 89.90 | 1086.58 | 339.31 | 747.26 | 3.23 | PASS |
| 17020.50† | 7538.50 | 8397.27 | -2451.46 | 16753.16 | 7529.50 | 8399.10 | -1367.80 | 89.90 | 1083.69 | 343.12 | 740.57 | 3.18 | PASS |
| 17120.50† | 7538.61 | 8497.23 | -2448.74 | 16853.11 | 7529.60 | 8499.06 | -1367.97 | 89.90 | 1080.80 | 346.94 | 733.87 | 3.14 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 89 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-2-4L PWB Offset Wellpath: BUFORD 33-2-4L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#08 BUFORD 33-2-4L (770'FSL & 919'FWL, SEC.34) Well: BUFORD 33-2-4L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASH [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 17220.50† | 7538.71 | 8597.19 | -2446.02 | 16953.07 | 7529.71 | 8599.02 | -1368.14 | 89.90 | 1077.92 | 350.75 | 727.17 | 3.10 | PASS |
| 17320.50† | 7538.81 | 8697.16 | -2443.30 | 17053.03 | 7529.81 | 8698.98 | -1368.31 | 89.90 | 1075.03 | 354.57 | 720.47 | 3.06 | PASS |
| 17420.50† | 7538.92 | 8797.12 | -2440.58 | 17152.99 | 7529.91 | 8798.93 | -1368.48 | 89.90 | 1072.14 | 358.38 | 713.76 | 3.01 | PASS |
| 17520.50† | 7539.02 | 8897.08 | -2437.86 | 17252.95 | 7530.02 | 8898.89 | -1368.64 | 89.90 | 1069.26 | 362.20 | 707.06 | 2.97 | PASS |
| 17620.50† | 7539.12 | 8997.05 | -2435.14 | 17352.91 | 7530.12 | 8998.85 | -1368.81 | 89.90 | 1066.37 | 366.02 | 700.35 | 2.93 | PASS |
| 17720.50† | 7539.23 | 9097.01 | -2432.42 | 17452.86 | 7530.22 | 9098.81 | -1368.98 | 89.90 | 1063.48 | 369.84 | 693.64 | 2.90 | PASS |
| 17820.50† | 7539.33 | 9196.97 | -2429.70 | 17552.82 | 7530.33 | 9198.77 | -1369.15 | 89.90 | 1060.60 | 373.67 | 686.93 | 2.86 | PASS |
| 17920.50† | 7539.43 | 9296.94 | -2426.99 | 17652.78 | 7530.43 | 9298.73 | -1369.32 | 89.90 | 1057.71 | 377.49 | 680.22 | 2.82 | PASS |
| 17985.90 | 7539.50 | 9362.31 | -2425.21 | 17718.15 | 7530.50 | 9364.09 | -1369.43 | 89.90 | 1055.82 | 379.99 | 675.83 | 2.80 | PASS |

POSITIONAL UNCERTAINTY - Offset Wellbore: BUFORD 33-2-4L PWB Offset Wellpath: BUFORD 33-2-4L (REV-A.0) PWP

| | | | | |
|-----------------------------------|------------|---------|----------|---------|
| Slot Surface Uncertainty @1SD | Horizontal | 0.100ft | Vertical | 1.000ft |
| Facility Surface Uncertainty @1SD | Horizontal | 8.200ft | Vertical | 3.000ft |

SURVEY PROGRAM - Offset Wellbore: BUFORD 33-2-4L PWB Offset Wellpath: BUFORD 33-2-4L (REV-A.0) PWP

| Start MD [ft] | End MD [ft] | Positional Uncertainty Model | Log Name/Comment | Wellbore |
|---------------|-------------|---|------------------|--------------------|
| 20.50 | 1500.00 | BH NaviTrak (2019) (Standard) | | BUFORD 33-2-4L PWB |
| 1500.00 | 17739.55 | BH AutoTrak Curve/eXpress (2019) (Standard) | | BUFORD 33-2-4L PWB |

OFFSET WELLPATH REFERENCE - Offset Wellbore: BUFORD 33-2-4L PWB Offset Wellpath: BUFORD 33-2-4L (REV-A.0) PWP

| | |
|---------------------------------|---|
| MD Reference: RIG (20.5') (RKB) | Offset TVD & local coordinates use Reference Wellpath settings (See WELLPATH DATUM on page 1 of this report) |
| Ellipse Start MD | 20.50ft |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 90 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770°FSL & 819°FSL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-1-1L PWB Offset Wellpath: BUFORD 33-1-1L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#11 BUFORD 33-1-1L (770°FSL & 994°FSL, SEC.34) Well: BUFORD 33-1-1L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | | |
| 20.50 | 20.50 | 0.00 | 0.00 | 18.50 | 20.50 | 0.00 | 176.50 | 90.00 | 176.50 | 9.74 | 166.76 | 29.99 | PASS | | | |
| 120.50† | 120.50 | 0.00 | 0.00 | 118.50 | 120.50 | 0.00 | 176.50 | 90.00 | 176.50 | 9.81 | 166.68 | 29.59 | PASS | | | |
| 200.00 | 200.00 | 0.00 | 0.00 | 198.00 | 200.00 | 0.00 | 176.50 | 90.00 | 176.50 | 9.96 | 166.53 | 28.86 | PASS | | | |
| 220.50† | 220.50 | -0.03 | -0.07 | 218.50 | 220.50 | 0.00 | 176.50 | 89.99 | 176.56 | 10.01 | 166.55 | 28.63 | PASS | | | |
| 320.50† | 320.46 | -0.93 | -2.36 | 318.46 | 320.46 | 0.00 | 176.50 | 89.70 | 178.85 | 10.40 | 168.45 | 27.24 | PASS | | | |
| 420.50† | 420.28 | -3.13 | -7.88 | 418.28 | 420.28 | 0.00 | 176.50 | 89.03 | 184.41 | 11.09 | 173.32 | 25.41 | PASS | | | |
| 520.50† | 519.83 | -6.60 | -16.65 | 517.83 | 519.83 | 0.00 | 176.50 | 88.04 | 193.26 | 11.82 | 181.44 | 24.17 | PASS | | | |
| 620.50† | 618.99 | -11.36 | -28.64 | 616.99 | 618.99 | 0.00 | 176.50 | 86.83 | 205.45 | 12.59 | 192.86 | 23.42 | PASS | | | |
| 720.50† | 717.64 | -17.38 | -43.83 | 715.64 | 717.64 | 0.00 | 176.50 | 85.49 | 221.01 | 13.38 | 207.63 | 23.09 | PASS | | | |
| 820.50† | 815.66 | -24.68 | -62.22 | 813.66 | 815.66 | 0.00 | 176.50 | 84.10 | 239.99 | 14.21 | 225.79 | 23.09 | PASS | | | |
| 920.50† | 912.93 | -33.22 | -83.78 | 910.93 | 912.93 | 0.00 | 176.50 | 82.73 | 262.39 | 15.07 | 247.32 | 23.32 | PASS | | | |
| 1020.50† | 1009.33 | -43.02 | -108.48 | 1007.33 | 1009.33 | 0.00 | 176.50 | 81.42 | 288.20 | 15.89 | 272.32 | 23.88 | PASS | | | |
| 1120.50† | 1104.74 | -54.05 | -136.29 | 1103.06 | 1105.06 | 0.00 | 176.49 | 80.20 | 317.42 | 16.74 | 300.68 | 24.57 | PASS | | | |
| 1220.50† | 1199.05 | -66.30 | -167.18 | 1209.48 | 1211.45 | -1.11 | 174.72 | 79.21 | 348.29 | 17.69 | 330.59 | 25.12 | PASS | | | |
| 1242.54 | 1219.68 | -69.16 | -174.40 | 1233.12 | 1235.07 | -1.64 | 173.88 | 79.03 | 355.09 | 17.91 | 337.19 | 25.22 | PASS | | | |
| 1320.50† | 1292.54 | -79.39 | -200.20 | 1317.62 | 1319.41 | -4.39 | 169.50 | 78.53 | 378.18 | 18.64 | 359.54 | 25.53 | PASS | | | |
| 1420.50† | 1385.99 | -92.51 | -233.28 | 1428.14 | 1429.42 | -9.97 | 160.59 | 78.16 | 404.77 | 19.58 | 385.18 | 25.70 | PASS | | | |
| 1520.50† | 1479.44 | -105.63 | -266.37 | 1540.83 | 1541.09 | -17.98 | 147.81 | 78.05 | 427.82 | 20.13 | 407.69 | 26.25 | PASS | | | |
| 1620.50† | 1572.89 | -118.75 | -299.46 | 1655.38 | 1653.91 | -28.50 | 131.02 | 78.16 | 447.24 | 20.33 | 426.91 | 27.11 | PASS | | | |
| 1720.50† | 1666.34 | -131.87 | -332.54 | 1771.48 | 1767.35 | -41.60 | 110.12 | 78.47 | 462.93 | 20.74 | 442.19 | 27.39 | PASS | | | |
| 1820.50† | 1759.79 | -144.99 | -365.63 | 1888.54 | 1880.62 | -57.27 | 85.12 | 78.99 | 474.84 | 20.90 | 453.93 | 27.83 | PASS | | | |
| 1920.50† | 1853.24 | -158.12 | -398.72 | 1987.98 | 1976.33 | -71.61 | 62.26 | 79.37 | 484.90 | 21.22 | 463.68 | 27.90 | PASS | | | |
| 2020.50† | 1946.69 | -171.24 | -431.80 | 2087.42 | 2072.04 | -85.94 | 39.39 | 79.74 | 494.99 | 21.59 | 473.40 | 27.89 | PASS | | | |
| 2120.50† | 2040.14 | -184.36 | -464.89 | 2186.87 | 2167.75 | -100.27 | 16.52 | 80.09 | 505.09 | 22.02 | 483.07 | 27.79 | PASS | | | |
| 2220.50† | 2133.59 | -197.48 | -497.98 | 2286.31 | 2263.46 | -114.60 | -6.34 | 80.43 | 515.21 | 22.52 | 492.69 | 27.59 | PASS | | | |
| 2320.50† | 2227.05 | -210.60 | -531.06 | 2385.75 | 2359.17 | -128.94 | -29.21 | 80.76 | 525.34 | 23.05 | 502.29 | 27.34 | PASS | | | |
| 2420.50† | 2320.50 | -223.72 | -564.15 | 2485.20 | 2454.89 | -143.27 | -52.08 | 81.07 | 535.49 | 23.65 | 511.85 | 27.03 | PASS | | | |
| 2520.50† | 2413.95 | -236.84 | -597.24 | 2584.64 | 2550.60 | -157.60 | -74.94 | 81.37 | 545.66 | 24.28 | 521.37 | 26.68 | PASS | | | |
| 2620.50† | 2507.40 | -249.96 | -630.32 | 2684.08 | 2646.31 | -171.94 | -97.81 | 81.66 | 555.84 | 24.97 | 530.87 | 26.30 | PASS | | | |
| 2720.50† | 2600.85 | -263.08 | -663.41 | 2783.53 | 2742.02 | -186.27 | -120.68 | 81.94 | 566.03 | 25.69 | 540.34 | 25.90 | PASS | | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 91 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770°FSL & 819°FSL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-1-1L PWB Offset Wellpath: BUFORD 33-1-1L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#11 BUFORD 33-1-1L (770°FSL & 994°FSL, SEC.34) Well: BUFORD 33-1-1L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 2820.50† | 2694.30 | -276.20 | -696.50 | 2882.97 | 2837.73 | -200.60 | -143.54 | 82.22 | 576.23 | 26.44 | 549.79 | 25.48 | PASS |
| 2920.50† | 2787.75 | -289.33 | -729.58 | 2982.41 | 2933.44 | -214.94 | -166.41 | 82.48 | 586.45 | 27.23 | 559.22 | 25.06 | PASS |
| 3020.50† | 2881.20 | -302.45 | -762.67 | 3081.86 | 3029.15 | -229.27 | -189.28 | 82.73 | 596.68 | 28.04 | 568.64 | 24.64 | PASS |
| 3120.50† | 2974.65 | -315.57 | -795.76 | 3181.30 | 3124.86 | -243.60 | -212.14 | 82.97 | 606.92 | 28.89 | 578.03 | 24.21 | PASS |
| 3220.50† | 3068.11 | -328.69 | -828.84 | 3280.74 | 3220.58 | -257.93 | -235.01 | 83.21 | 617.17 | 29.75 | 587.41 | 23.80 | PASS |
| 3320.50† | 3161.56 | -341.81 | -861.93 | 3380.19 | 3316.29 | -272.27 | -257.88 | 83.43 | 627.42 | 30.64 | 596.78 | 23.39 | PASS |
| 3420.50† | 3255.01 | -354.93 | -895.02 | 3479.63 | 3412.00 | -286.60 | -280.74 | 83.65 | 637.69 | 31.55 | 606.14 | 22.99 | PASS |
| 3520.50† | 3348.46 | -368.05 | -928.10 | 3579.07 | 3507.71 | -300.93 | -303.61 | 83.87 | 647.97 | 32.48 | 615.49 | 22.60 | PASS |
| 3620.50† | 3441.91 | -381.17 | -961.19 | 3678.52 | 3603.42 | -315.27 | -326.48 | 84.07 | 658.25 | 33.42 | 624.82 | 22.22 | PASS |
| 3720.50† | 3535.36 | -394.29 | -994.28 | 3777.96 | 3699.13 | -329.60 | -349.34 | 84.27 | 668.54 | 34.39 | 634.16 | 21.86 | PASS |
| 3820.50† | 3628.81 | -407.41 | -1027.37 | 3877.40 | 3794.84 | -343.93 | -372.21 | 84.47 | 678.84 | 35.36 | 643.48 | 21.51 | PASS |
| 3920.50† | 3722.26 | -420.53 | -1060.45 | 3976.85 | 3890.55 | -358.27 | -395.08 | 84.65 | 689.15 | 36.35 | 652.80 | 21.17 | PASS |
| 4020.50† | 3815.71 | -433.66 | -1093.54 | 4076.29 | 3986.27 | -372.60 | -417.94 | 84.84 | 699.46 | 37.35 | 662.11 | 20.85 | PASS |
| 4120.50† | 3909.17 | -446.78 | -1126.63 | 4175.73 | 4081.98 | -386.93 | -440.81 | 85.01 | 709.78 | 38.36 | 671.42 | 20.53 | PASS |
| 4220.50† | 4002.62 | -459.90 | -1159.71 | 4275.18 | 4177.69 | -401.26 | -463.68 | 85.19 | 720.11 | 39.38 | 680.73 | 20.23 | PASS |
| 4320.50† | 4096.07 | -473.02 | -1192.80 | 4374.62 | 4273.40 | -415.60 | -486.54 | 85.35 | 730.44 | 40.41 | 690.03 | 19.94 | PASS |
| 4420.50† | 4189.52 | -486.14 | -1225.89 | 4474.06 | 4369.11 | -429.93 | -509.41 | 85.51 | 740.78 | 41.45 | 699.33 | 19.67 | PASS |
| 4520.50† | 4282.97 | -499.26 | -1258.97 | 4573.51 | 4464.82 | -444.26 | -532.28 | 85.67 | 751.12 | 42.50 | 708.62 | 19.40 | PASS |
| 4620.50† | 4376.42 | -512.38 | -1292.06 | 4672.95 | 4560.53 | -458.60 | -555.14 | 85.83 | 761.47 | 43.55 | 717.92 | 19.14 | PASS |
| 4720.50† | 4469.87 | -525.50 | -1325.15 | 4772.39 | 4656.25 | -472.93 | -578.01 | 85.98 | 771.82 | 44.62 | 727.21 | 18.90 | PASS |
| 4820.50† | 4563.32 | -538.62 | -1358.23 | 4871.84 | 4751.96 | -487.26 | -600.88 | 86.12 | 782.18 | 45.68 | 736.50 | 18.66 | PASS |
| 4920.50† | 4656.77 | -551.74 | -1391.32 | 4971.28 | 4847.67 | -501.60 | -623.74 | 86.26 | 792.55 | 46.76 | 745.79 | 18.43 | PASS |
| 5020.50† | 4750.22 | -564.87 | -1424.41 | 5070.72 | 4943.38 | -515.93 | -646.61 | 86.40 | 802.91 | 47.84 | 755.07 | 18.22 | PASS |
| 5120.50† | 4843.68 | -577.99 | -1457.49 | 5170.17 | 5039.09 | -530.26 | -669.48 | 86.53 | 813.29 | 48.93 | 764.36 | 18.01 | PASS |
| 5220.50† | 4937.13 | -591.11 | -1490.58 | 5269.61 | 5134.80 | -544.59 | -692.34 | 86.67 | 823.66 | 50.02 | 773.65 | 17.81 | PASS |
| 5320.50† | 5030.58 | -604.23 | -1523.67 | 5369.05 | 5230.51 | -558.93 | -715.21 | 86.79 | 834.04 | 51.12 | 782.93 | 17.61 | PASS |
| 5420.50† | 5124.03 | -617.35 | -1556.75 | 5468.50 | 5326.22 | -573.26 | -738.08 | 86.92 | 844.43 | 52.22 | 792.21 | 17.43 | PASS |
| 5520.50† | 5217.48 | -630.47 | -1589.84 | 5567.94 | 5421.94 | -587.59 | -760.94 | 87.04 | 854.82 | 53.32 | 801.50 | 17.25 | PASS |
| 5620.50† | 5310.93 | -643.59 | -1622.93 | 5667.38 | 5517.65 | -601.93 | -783.81 | 87.16 | 865.21 | 54.43 | 810.78 | 17.07 | PASS |
| 5720.50† | 5404.38 | -656.71 | -1656.01 | 5766.83 | 5613.36 | -616.26 | -806.68 | 87.27 | 875.60 | 55.54 | 820.06 | 16.91 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 92 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-1-1L PWB Offset Wellpath: BUFORD 33-1-1L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#11 BUFORD 33-1-1L (770'FSL & 994'FWL, SEC.34) Well: BUFORD 33-1-1L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | Sep Ratio | Rule Status |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | | |
| 5820.50† | 5497.83 | -669.83 | -1689.10 | 5866.27 | 5709.07 | -630.59 | -829.54 | 87.39 | 886.00 | 56.66 | 829.34 | 16.74 | PASS |
| 5920.50† | 5591.28 | -682.95 | -1722.19 | 5965.71 | 5804.78 | -644.93 | -852.41 | 87.50 | 896.41 | 57.78 | 838.63 | 16.59 | PASS |
| 6020.50† | 5684.74 | -696.07 | -1755.27 | 6065.16 | 5900.49 | -659.26 | -875.28 | 87.60 | 906.81 | 58.90 | 847.91 | 16.44 | PASS |
| 6120.50† | 5778.19 | -709.20 | -1788.36 | 6164.60 | 5996.20 | -673.59 | -898.14 | 87.71 | 917.22 | 60.03 | 857.19 | 16.29 | PASS |
| 6220.50† | 5871.64 | -722.32 | -1821.45 | 6264.04 | 6091.91 | -687.92 | -921.01 | 87.81 | 927.63 | 61.16 | 866.47 | 16.16 | PASS |
| 6320.50† | 5965.09 | -735.44 | -1854.54 | 6363.49 | 6187.63 | -702.26 | -943.88 | 87.91 | 938.04 | 62.29 | 875.75 | 16.02 | PASS |
| 6420.50† | 6058.54 | -748.56 | -1887.62 | 6462.93 | 6283.34 | -716.59 | -966.74 | 88.01 | 948.46 | 63.42 | 885.04 | 15.89 | PASS |
| 6520.50† | 6151.99 | -761.68 | -1920.71 | 6562.37 | 6379.05 | -730.92 | -989.61 | 88.11 | 958.88 | 64.56 | 894.32 | 15.76 | PASS |
| 6620.50† | 6245.44 | -774.80 | -1953.80 | 6661.82 | 6474.76 | -745.26 | -1012.48 | 88.20 | 969.30 | 65.70 | 903.60 | 15.64 | PASS |
| 6720.50† | 6338.89 | -787.92 | -1986.88 | 6761.26 | 6570.47 | -759.59 | -1035.34 | 88.30 | 979.72 | 66.84 | 912.88 | 15.52 | PASS |
| 6820.50† | 6432.34 | -801.04 | -2019.97 | 6860.70 | 6666.18 | -773.92 | -1058.21 | 88.39 | 990.15 | 67.98 | 922.17 | 15.41 | PASS |
| 6920.50† | 6525.80 | -814.16 | -2053.06 | 6954.73 | 6757.32 | -779.67 | -1080.00 | 87.97 | 1000.82 | 69.16 | 931.66 | 15.29 | PASS |
| 7020.50† | 6619.25 | -827.28 | -2086.14 | 7042.57 | 6841.92 | -768.42 | -1100.26 | 86.58 | 1012.43 | 69.18 | 943.25 | 15.47 | PASS |
| 7120.50† | 6712.70 | -840.41 | -2119.23 | 7120.03 | 6913.77 | -745.43 | -1117.48 | 84.58 | 1026.13 | 69.41 | 956.72 | 15.62 | PASS |
| 7220.50† | 6806.15 | -853.53 | -2152.32 | 7185.55 | 6971.05 | -716.88 | -1131.24 | 82.38 | 1043.29 | 68.96 | 974.34 | 16.00 | PASS |
| 7320.50† | 6899.60 | -866.65 | -2185.40 | 7239.77 | 7015.21 | -687.33 | -1141.86 | 80.25 | 1065.13 | 69.00 | 996.13 | 16.32 | PASS |
| 7341.07 | 6918.82 | -869.35 | -2192.21 | 7249.66 | 7022.90 | -681.39 | -1143.71 | 79.84 | 1070.29 | 68.89 | 1001.39 | 16.43 | PASS |
| 7420.50† | 6993.49 | -874.29 | -2218.65 | 7286.79 | 7050.66 | -657.67 | -1150.39 | 78.54 | 1091.50 | 68.48 | 1023.02 | 16.86 | PASS |
| 7520.50† | 7087.21 | -864.88 | -2251.87 | 7332.84 | 7082.47 | -625.28 | -1158.06 | 77.65 | 1119.75 | 68.04 | 1051.70 | 17.42 | PASS |
| 7620.50† | 7177.96 | -838.35 | -2284.05 | 7378.35 | 7110.77 | -590.34 | -1164.90 | 77.51 | 1148.27 | 67.83 | 1080.44 | 17.92 | PASS |
| 7720.50† | 7262.97 | -795.51 | -2314.23 | 7423.47 | 7135.52 | -553.11 | -1170.89 | 78.03 | 1175.68 | 67.64 | 1108.04 | 18.41 | PASS |
| 7820.50† | 7339.68 | -737.65 | -2341.49 | 7468.31 | 7156.61 | -513.89 | -1176.01 | 79.13 | 1200.80 | 67.24 | 1133.56 | 18.92 | PASS |
| 7920.50† | 7405.75 | -666.53 | -2364.99 | 7512.95 | 7173.97 | -473.00 | -1180.24 | 80.72 | 1222.63 | 66.76 | 1155.87 | 19.41 | PASS |
| 8020.50† | 7459.16 | -584.32 | -2384.03 | 7557.44 | 7187.49 | -430.76 | -1183.55 | 82.71 | 1240.37 | 66.28 | 1174.09 | 19.85 | PASS |
| 8120.50† | 7498.30 | -493.50 | -2398.02 | 7601.84 | 7197.12 | -387.50 | -1185.94 | 85.00 | 1253.43 | 65.93 | 1187.51 | 20.17 | PASS |
| 8220.50† | 7521.99 | -396.85 | -2406.55 | 7646.18 | 7202.80 | -343.56 | -1187.38 | 87.50 | 1261.39 | 65.75 | 1195.64 | 20.36 | PASS |
| 8315.56 | 7529.50 | -302.24 | -2409.34 | 7689.35 | 7204.50 | -300.45 | -1187.87 | 89.92 | 1263.98 | 65.75 | 1198.22 | 20.40 | PASS |
| 8320.50† | 7529.51 | -297.30 | -2409.35 | 7694.28 | 7204.49 | -295.51 | -1187.87 | 89.92 | 1263.98 | 65.72 | 1198.26 | 20.41 | PASS |
| 8420.50† | 7529.61 | -197.30 | -2409.53 | 7794.28 | 7204.41 | -195.51 | -1188.04 | 89.92 | 1264.04 | 65.08 | 1198.96 | 20.62 | PASS |
| 8520.50† | 7529.71 | -97.30 | -2409.71 | 7894.28 | 7204.33 | -95.51 | -1188.21 | 89.92 | 1264.09 | 64.77 | 1199.32 | 20.73 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 93 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-1-1L PWB Offset Wellpath: BUFORD 33-1-1L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#11 BUFORD 33-1-1L (770'FSL & 994'FWL, SEC.34) Well: BUFORD 33-1-1L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 8620.50† | 7529.82 | 2.70 | -2409.88 | 7994.28 | 7204.25 | 4.49 | -1188.38 | 89.92 | 1264.15 | 64.90 | 1199.25 | 20.69 | PASS |
| 8720.50† | 7529.92 | 102.70 | -2410.06 | 8094.28 | 7204.16 | 104.49 | -1188.55 | 89.92 | 1264.20 | 64.89 | 1199.32 | 20.69 | PASS |
| 8820.50† | 7530.02 | 202.70 | -2410.24 | 8194.28 | 7204.08 | 204.49 | -1188.72 | 89.92 | 1264.26 | 65.30 | 1198.96 | 20.55 | PASS |
| 8920.50† | 7530.13 | 302.70 | -2410.42 | 8294.28 | 7204.00 | 304.49 | -1188.89 | 89.92 | 1264.32 | 65.95 | 1198.37 | 20.34 | PASS |
| 9020.50† | 7530.23 | 402.70 | -2410.59 | 8394.28 | 7203.92 | 404.49 | -1189.06 | 89.92 | 1264.37 | 66.82 | 1197.55 | 20.06 | PASS |
| 9120.50† | 7530.33 | 502.70 | -2410.77 | 8494.28 | 7203.83 | 504.49 | -1189.23 | 89.92 | 1264.43 | 67.90 | 1196.53 | 19.72 | PASS |
| 9220.50† | 7530.44 | 602.70 | -2410.95 | 8594.28 | 7203.75 | 604.49 | -1189.39 | 89.92 | 1264.49 | 69.19 | 1195.29 | 19.33 | PASS |
| 9320.50† | 7530.54 | 702.70 | -2411.13 | 8694.28 | 7203.67 | 704.49 | -1189.56 | 89.92 | 1264.54 | 70.67 | 1193.87 | 18.90 | PASS |
| 9420.50† | 7530.64 | 802.69 | -2411.31 | 8794.28 | 7203.58 | 804.49 | -1189.73 | 89.92 | 1264.60 | 72.34 | 1192.26 | 18.44 | PASS |
| 9520.50† | 7530.75 | 902.69 | -2411.48 | 8894.28 | 7203.50 | 904.49 | -1189.90 | 89.92 | 1264.66 | 74.16 | 1190.49 | 17.96 | PASS |
| 9620.50† | 7530.85 | 1002.69 | -2411.66 | 8994.28 | 7203.42 | 1004.49 | -1190.07 | 89.92 | 1264.71 | 76.15 | 1188.57 | 17.47 | PASS |
| 9720.50† | 7530.96 | 1102.69 | -2411.84 | 9094.28 | 7203.34 | 1104.49 | -1190.24 | 89.92 | 1264.77 | 78.27 | 1186.50 | 16.97 | PASS |
| 9820.50† | 7531.06 | 1202.69 | -2412.02 | 9194.28 | 7203.25 | 1204.49 | -1190.41 | 89.92 | 1264.83 | 80.52 | 1184.30 | 16.47 | PASS |
| 9920.50† | 7531.16 | 1302.69 | -2412.19 | 9294.28 | 7203.17 | 1304.49 | -1190.58 | 89.92 | 1264.88 | 82.90 | 1181.99 | 15.98 | PASS |
| 10020.50† | 7531.27 | 1402.69 | -2412.37 | 9394.28 | 7203.09 | 1404.49 | -1190.75 | 89.92 | 1264.94 | 85.38 | 1179.56 | 15.49 | PASS |
| 10120.50† | 7531.37 | 1502.69 | -2412.55 | 9494.28 | 7203.01 | 1504.49 | -1190.91 | 89.92 | 1265.00 | 87.96 | 1177.04 | 15.02 | PASS |
| 10220.50† | 7531.47 | 1602.69 | -2412.73 | 9594.28 | 7202.92 | 1604.49 | -1191.08 | 89.92 | 1265.05 | 90.63 | 1174.43 | 14.55 | PASS |
| 10320.50† | 7531.58 | 1702.69 | -2412.90 | 9694.28 | 7202.84 | 1704.49 | -1191.25 | 89.92 | 1265.11 | 93.38 | 1171.73 | 14.11 | PASS |
| 10420.50† | 7531.68 | 1802.69 | -2413.08 | 9794.28 | 7202.76 | 1804.48 | -1191.42 | 89.92 | 1265.17 | 96.20 | 1168.96 | 13.68 | PASS |
| 10520.50† | 7531.78 | 1902.69 | -2413.26 | 9894.28 | 7202.67 | 1904.48 | -1191.59 | 89.92 | 1265.22 | 99.10 | 1166.13 | 13.26 | PASS |
| 10620.50† | 7531.89 | 2002.69 | -2413.44 | 9994.28 | 7202.59 | 2004.48 | -1191.76 | 89.92 | 1265.28 | 102.05 | 1163.23 | 12.86 | PASS |
| 10720.50† | 7531.99 | 2102.69 | -2413.62 | 10094.28 | 7202.51 | 2104.48 | -1191.93 | 89.92 | 1265.34 | 105.07 | 1160.27 | 12.48 | PASS |
| 10820.50† | 7532.09 | 2202.69 | -2413.79 | 10194.28 | 7202.43 | 2204.48 | -1192.10 | 89.92 | 1265.40 | 108.13 | 1157.27 | 12.11 | PASS |
| 10920.50† | 7532.20 | 2302.69 | -2413.97 | 10294.28 | 7202.34 | 2304.48 | -1192.27 | 89.92 | 1265.45 | 111.24 | 1154.21 | 11.76 | PASS |
| 11020.50† | 7532.30 | 2402.69 | -2414.15 | 10394.28 | 7202.26 | 2404.48 | -1192.44 | 89.92 | 1265.51 | 114.39 | 1151.12 | 11.43 | PASS |
| 11120.50† | 7532.41 | 2502.69 | -2414.33 | 10494.28 | 7202.18 | 2504.48 | -1192.60 | 89.92 | 1265.57 | 117.59 | 1147.98 | 11.11 | PASS |
| 11220.50† | 7532.51 | 2602.69 | -2414.50 | 10594.28 | 7202.10 | 2604.48 | -1192.77 | 89.92 | 1265.62 | 120.81 | 1144.81 | 10.80 | PASS |
| 11320.50† | 7532.61 | 2702.69 | -2414.68 | 10694.28 | 7202.01 | 2704.48 | -1192.94 | 89.92 | 1265.68 | 124.08 | 1141.60 | 10.51 | PASS |
| 11420.50† | 7532.72 | 2802.69 | -2414.86 | 10794.28 | 7201.93 | 2804.48 | -1193.11 | 89.92 | 1265.74 | 127.37 | 1138.37 | 10.23 | PASS |
| 11520.50† | 7532.82 | 2902.69 | -2415.04 | 10894.28 | 7201.85 | 2904.48 | -1193.28 | 89.92 | 1265.79 | 130.69 | 1135.11 | 9.96 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 94 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-1-1L PWB Offset Wellpath: BUFORD 33-1-1L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#11 BUFORD 33-1-1L (770'FSL & 994'FWL,SEC.34) Well: BUFORD 33-1-1L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|-----------------|-------------------|------------------|-------------------|--------------------|----------------------|---------------------|-------------------------|---------------------------|----------------------|----------------------------|--------------|----------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 11620.50† | 7532.92 | 3002.69 | -2415.21 | 10994.28 | 7201.76 | 3004.48 | -1193.45 | 89.92 | 1265.85 | 134.04 | 1131.82 | 9.70 | PASS |
| 11720.50† | 7533.03 | 3102.69 | -2415.39 | 11094.28 | 7201.68 | 3104.48 | -1193.62 | 89.92 | 1265.91 | 137.41 | 1128.50 | 9.46 | PASS |
| 11820.50† | 7533.13 | 3202.69 | -2415.57 | 11194.28 | 7201.60 | 3204.48 | -1193.79 | 89.92 | 1265.97 | 140.80 | 1125.17 | 9.22 | PASS |
| 11920.50† | 7533.23 | 3302.69 | -2415.75 | 11294.28 | 7201.52 | 3304.48 | -1193.96 | 89.92 | 1266.02 | 144.21 | 1121.81 | 9.00 | PASS |
| 12020.50† | 7533.34 | 3402.69 | -2415.92 | 11394.28 | 7201.43 | 3404.48 | -1194.12 | 89.92 | 1266.08 | 147.64 | 1118.44 | 8.79 | PASS |
| 12120.50† | 7533.44 | 3502.69 | -2416.10 | 11494.28 | 7201.35 | 3504.48 | -1194.29 | 89.92 | 1266.14 | 151.10 | 1115.04 | 8.58 | PASS |
| 12220.50† | 7533.55 | 3602.69 | -2416.28 | 11594.28 | 7201.27 | 3604.48 | -1194.46 | 89.92 | 1266.19 | 154.56 | 1111.63 | 8.38 | PASS |
| 12320.50† | 7533.65 | 3702.69 | -2416.46 | 11694.28 | 7201.19 | 3704.48 | -1194.63 | 89.92 | 1266.25 | 158.04 | 1108.21 | 8.19 | PASS |
| 12420.50† | 7533.75 | 3802.69 | -2416.64 | 11794.28 | 7201.10 | 3804.48 | -1194.80 | 89.92 | 1266.31 | 161.53 | 1104.78 | 8.01 | PASS |
| 12520.50† | 7533.86 | 3902.69 | -2416.81 | 11894.28 | 7201.02 | 3904.48 | -1194.97 | 89.92 | 1266.37 | 165.05 | 1101.32 | 7.84 | PASS |
| 12620.50† | 7533.96 | 4002.69 | -2416.99 | 11994.28 | 7200.94 | 4004.48 | -1195.14 | 89.92 | 1266.42 | 168.57 | 1097.85 | 7.67 | PASS |
| 12720.50† | 7534.06 | 4102.69 | -2417.17 | 12094.28 | 7200.85 | 4104.48 | -1195.31 | 89.92 | 1266.48 | 172.11 | 1094.37 | 7.51 | PASS |
| 12820.50† | 7534.17 | 4202.69 | -2417.35 | 12194.28 | 7200.77 | 4204.48 | -1195.48 | 89.92 | 1266.54 | 175.65 | 1090.89 | 7.35 | PASS |
| 12920.50† | 7534.27 | 4302.69 | -2417.52 | 12294.28 | 7200.69 | 4304.48 | -1195.65 | 89.92 | 1266.60 | 179.21 | 1087.39 | 7.21 | PASS |
| 13020.50† | 7534.37 | 4402.69 | -2417.70 | 12394.28 | 7200.61 | 4404.48 | -1195.81 | 89.92 | 1266.65 | 182.77 | 1083.88 | 7.06 | PASS |
| 13120.50† | 7534.48 | 4502.69 | -2417.88 | 12494.28 | 7200.52 | 4504.48 | -1195.98 | 89.92 | 1266.71 | 186.35 | 1080.37 | 6.92 | PASS |
| 13199.97 | 7534.56 | 4582.16 | -2418.02 | 12573.75 | 7200.46 | 4583.95 | -1196.12 | 89.92 | 1266.76 | 189.19 | 1077.57 | 6.82 | PASS |
| 13220.50† | 7534.58 | 4602.69 | -2418.13 | 12594.28 | 7200.44 | 4604.47 | -1196.15 | 89.92 | 1266.84 | 189.92 | 1076.92 | 6.79 | PASS |
| 13320.50† | 7534.68 | 4702.65 | -2420.77 | 12694.24 | 7200.36 | 4704.44 | -1196.32 | 89.92 | 1269.27 | 193.53 | 1075.74 | 6.68 | PASS |
| 13420.50† | 7534.79 | 4802.45 | -2426.90 | 12794.06 | 7200.28 | 4804.26 | -1196.49 | 89.92 | 1275.07 | 197.21 | 1077.86 | 6.58 | PASS |
| 13476.50 | 7534.85 | 4858.23 | -2431.85 | 12849.85 | 7200.23 | 4860.05 | -1196.58 | 89.92 | 1279.78 | 199.29 | 1080.49 | 6.53 | PASS |
| 13520.50† | 7534.89 | 4902.02 | -2436.16 | 12893.64 | 7200.19 | 4903.84 | -1196.66 | 89.92 | 1283.90 | 200.92 | 1082.98 | 6.50 | PASS |
| 13620.50† | 7534.99 | 5001.54 | -2445.98 | 12993.17 | 7200.11 | 5003.37 | -1196.83 | 89.92 | 1293.26 | 204.65 | 1088.61 | 6.42 | PASS |
| 13720.50† | 7535.10 | 5101.06 | -2455.79 | 13092.71 | 7200.03 | 5102.90 | -1196.99 | 89.92 | 1302.63 | 208.40 | 1094.23 | 6.35 | PASS |
| 13820.50† | 7535.20 | 5200.57 | -2465.61 | 13192.24 | 7199.95 | 5202.44 | -1197.16 | 89.92 | 1312.00 | 212.16 | 1099.84 | 6.28 | PASS |
| 13920.50† | 7535.30 | 5300.09 | -2475.42 | 13291.77 | 7199.86 | 5301.97 | -1197.33 | 89.92 | 1321.38 | 215.93 | 1105.45 | 6.22 | PASS |
| 14020.50† | 7535.40 | 5399.61 | -2485.24 | 13391.31 | 7199.78 | 5401.50 | -1197.50 | 89.92 | 1330.76 | 219.70 | 1111.06 | 6.15 | PASS |
| 14120.50† | 7535.51 | 5499.12 | -2495.05 | 13490.84 | 7199.70 | 5501.04 | -1197.67 | 89.92 | 1340.14 | 223.48 | 1116.67 | 6.09 | PASS |
| 14220.50† | 7535.61 | 5598.64 | -2504.87 | 13590.37 | 7199.62 | 5600.57 | -1197.83 | 89.92 | 1349.53 | 227.26 | 1122.27 | 6.03 | PASS |
| 14221.87 | 7535.61 | 5600.00 | -2505.00 | 13591.73 | 7199.62 | 5601.93 | -1197.84 | 89.92 | 1349.66 | 227.31 | 1122.34 | 6.03 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 95 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-1-1L PWB Offset Wellpath: BUFORD 33-1-1L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#11 BUFORD 33-1-1L (770'FSL & 994'FWL,SEC.34) Well: BUFORD 33-1-1L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|-----------------|-------------------|------------------|-------------------|--------------------|----------------------|---------------------|-------------------------|---------------------------|----------------------|----------------------------|--------------|----------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 14320.50† | 7535.71 | 5698.31 | -2512.99 | 13690.05 | 7199.54 | 5700.25 | -1198.00 | 89.92 | 1357.28 | 231.01 | 1126.27 | 5.96 | PASS |
| 14420.50† | 7535.81 | 5798.19 | -2517.63 | 13789.95 | 7199.45 | 5800.14 | -1198.17 | 89.92 | 1361.66 | 234.75 | 1126.90 | 5.88 | PASS |
| 14520.50† | 7535.92 | 5898.18 | -2518.78 | 13889.94 | 7199.37 | 5900.13 | -1198.34 | 89.92 | 1362.66 | 238.45 | 1124.21 | 5.79 | PASS |
| 14581.38 | 7535.98 | 5959.05 | -2517.77 | 13950.81 | 7199.32 | 5961.00 | -1198.44 | 89.92 | 1361.61 | 240.67 | 1120.94 | 5.74 | PASS |
| 14620.50† | 7536.02 | 5998.16 | -2516.71 | 13989.91 | 7199.29 | 6000.11 | -1198.51 | 89.92 | 1360.53 | 242.08 | 1118.45 | 5.70 | PASS |
| 14720.50† | 7536.12 | 6098.12 | -2513.99 | 14089.87 | 7199.20 | 6100.06 | -1198.68 | 89.92 | 1357.78 | 245.71 | 1112.07 | 5.60 | PASS |
| 14820.50† | 7536.23 | 6198.08 | -2511.27 | 14189.83 | 7199.12 | 6200.02 | -1198.85 | 89.92 | 1355.03 | 249.35 | 1105.68 | 5.51 | PASS |
| 14920.50† | 7536.33 | 6298.05 | -2508.55 | 14289.78 | 7199.04 | 6299.98 | -1199.02 | 89.92 | 1352.28 | 252.99 | 1099.29 | 5.41 | PASS |
| 15020.50† | 7536.43 | 6398.01 | -2505.83 | 14389.74 | 7198.96 | 6399.94 | -1199.19 | 89.92 | 1349.53 | 256.63 | 1092.90 | 5.33 | PASS |
| 15120.50† | 7536.54 | 6497.97 | -2503.11 | 14489.70 | 7198.87 | 6499.90 | -1199.35 | 89.92 | 1346.78 | 260.28 | 1086.50 | 5.24 | PASS |
| 15220.50† | 7536.64 | 6597.93 | -2500.40 | 14589.66 | 7198.79 | 6599.85 | -1199.52 | 89.92 | 1344.03 | 263.92 | 1080.11 | 5.16 | PASS |
| 15320.50† | 7536.74 | 6697.90 | -2497.68 | 14689.62 | 7198.71 | 6699.81 | -1199.69 | 89.92 | 1341.28 | 267.57 | 1073.71 | 5.07 | PASS |
| 15420.50† | 7536.85 | 6797.86 | -2494.96 | 14789.57 | 7198.63 | 6799.77 | -1199.86 | 89.92 | 1338.53 | 271.22 | 1067.31 | 4.99 | PASS |
| 15520.50† | 7536.95 | 6897.82 | -2492.24 | 14889.53 | 7198.54 | 6899.73 | -1200.03 | 89.92 | 1335.79 | 274.88 | 1060.91 | 4.92 | PASS |
| 15620.50† | 7537.05 | 6997.79 | -2489.52 | 14989.49 | 7198.46 | 6999.68 | -1200.20 | 89.92 | 1333.04 | 278.53 | 1054.51 | 4.84 | PASS |
| 15720.50† | 7537.16 | 7097.75 | -2486.80 | 15089.45 | 7198.38 | 7099.64 | -1200.37 | 89.92 | 1330.30 | 282.19 | 1048.11 | 4.77 | PASS |
| 15820.50† | 7537.26 | 7197.71 | -2484.08 | 15189.41 | 7198.29 | 7199.60 | -1200.54 | 89.92 | 1327.55 | 285.84 | 1041.71 | 4.70 | PASS |
| 15920.50† | 7537.36 | 7297.68 | -2481.36 | 15289.36 | 7198.21 | 7299.56 | -1200.71 | 89.92 | 1324.81 | 289.50 | 1035.31 | 4.63 | PASS |
| 16020.50† | 7537.47 | 7397.64 | -2478.64 | 15389.32 | 7198.13 | 7399.52 | -1200.87 | 89.92 | 1322.06 | 293.16 | 1028.90 | 4.56 | PASS |
| 16120.50† | 7537.57 | 7497.60 | -2475.93 | 15489.28 | 7198.05 | 7499.47 | -1201.04 | 89.92 | 1319.32 | 296.82 | 1022.50 | 4.49 | PASS |
| 16220.50† | 7537.68 | 7597.56 | -2473.21 | 15589.24 | 7197.96 | 7599.43 | -1201.21 | 89.92 | 1316.58 | 300.48 | 1016.10 | 4.43 | PASS |
| 16320.50† | 7537.78 | 7697.53 | -2470.49 | 15689.20 | 7197.88 | 7699.39 | -1201.38 | 89.92 | 1313.84 | 304.14 | 1009.69 | 4.36 | PASS |
| 16420.50† | 7537.88 | 7797.49 | -2467.77 | 15789.16 | 7197.80 | 7799.35 | -1201.55 | 89.92 | 1311.10 | 307.80 | 1003.29 | 4.30 | PASS |
| 16520.50† | 7537.99 | 7897.45 | -2465.05 | 15889.11 | 7197.72 | 7899.31 | -1201.72 | 89.92 | 1308.36 | 311.47 | 996.89 | 4.24 | PASS |
| 16620.50† | 7538.09 | 7997.42 | -2462.33 | 15989.07 | 7197.63 | 7999.26 | -1201.89 | 89.92 | 1305.62 | 315.13 | 990.48 | 4.18 | PASS |
| 16720.50† | 7538.19 | 8097.38 | -2459.61 | 16089.03 | 7197.55 | 8099.22 | -1202.06 | 89.92 | 1302.88 | 318.79 | 984.08 | 4.13 | PASS |
| 16820.50† | 7538.30 | 8197.34 | -2456.89 | 16188.99 | 7197.47 | 8199.18 | -1202.23 | 89.92 | 1300.14 | 322.46 | 977.68 | 4.07 | PASS |
| 16920.50† | 7538.40 | 8297.31 | -2454.17 | 16288.95 | 7197.39 | 8299.14 | -1202.39 | 89.92 | 1297.40 | 326.12 | 971.28 | 4.02 | PASS |
| 17020.50† | 7538.50 | 8397.27 | -2451.46 | 16388.90 | 7197.30 | 8399.10 | -1202.56 | 89.92 | 1294.66 | 329.79 | 964.88 | 3.96 | PASS |
| 17120.50† | 7538.61 | 8497.23 | -2448.74 | 16488.86 | 7197.22 | 8499.05 | -1202.73 | 89.92 | 1291.93 | 333.45 | 958.47 | 3.91 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 96 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD 33-1-1L PWB Offset Wellpath: BUFORD 33-1-1L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#11 BUFORD 33-1-1L (770'FSL & 994'FWL, SEC.34) Well: BUFORD 33-1-1L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 17220.50† | 7538.71 | 8597.19 | -2446.02 | 16588.82 | 7197.14 | 8599.01 | -1202.90 | 89.92 | 1289.19 | 337.12 | 952.07 | 3.86 | PASS |
| 17320.50† | 7538.81 | 8697.16 | -2443.30 | 16688.78 | 7197.05 | 8698.97 | -1203.07 | 89.92 | 1286.46 | 340.78 | 945.67 | 3.81 | PASS |
| 17420.50† | 7538.92 | 8797.12 | -2440.58 | 16788.74 | 7196.97 | 8798.93 | -1203.24 | 89.92 | 1283.72 | 344.45 | 939.27 | 3.76 | PASS |
| 17520.50† | 7539.02 | 8897.08 | -2437.86 | 16888.69 | 7196.89 | 8898.89 | -1203.41 | 89.92 | 1280.99 | 348.11 | 932.88 | 3.71 | PASS |
| 17620.50† | 7539.12 | 8997.05 | -2435.14 | 16988.65 | 7196.81 | 8998.84 | -1203.58 | 89.92 | 1278.26 | 351.78 | 926.48 | 3.66 | PASS |
| 17720.50† | 7539.23 | 9097.01 | -2432.42 | 17088.61 | 7196.72 | 9098.80 | -1203.74 | 89.92 | 1275.52 | 355.44 | 920.08 | 3.62 | PASS |
| 17820.50† | 7539.33 | 9196.97 | -2429.70 | 17188.57 | 7196.64 | 9198.76 | -1203.91 | 89.92 | 1272.79 | 359.11 | 913.69 | 3.57 | PASS |
| 17920.50† | 7539.43 | 9296.94 | -2426.99 | 17288.53 | 7196.56 | 9298.72 | -1204.08 | 89.92 | 1270.06 | 362.77 | 907.29 | 3.53 | PASS |
| 17985.90 | 7539.50 | 9362.31 | -2425.21 | 17353.90 | 7196.50 | 9364.09 | -1204.19 | 89.92 | 1268.28 | 365.16 | 903.12 | 3.50 | PASS |

POSITIONAL UNCERTAINTY - Offset Wellbore: BUFORD 33-1-1L PWB Offset Wellpath: BUFORD 33-1-1L (REV-A.0) PWP

| | | | | |
|-----------------------------------|------------|---------|----------|---------|
| Slot Surface Uncertainty @1SD | Horizontal | 0.100ft | Vertical | 1.000ft |
| Facility Surface Uncertainty @1SD | Horizontal | 8.200ft | Vertical | 3.000ft |

SURVEY PROGRAM - Offset Wellbore: BUFORD 33-1-1L PWB Offset Wellpath: BUFORD 33-1-1L (REV-A.0) PWP

| Start MD [ft] | End MD [ft] | Positional Uncertainty Model | Log Name/Comment | Wellbore |
|---------------|-------------|---|------------------|--------------------|
| 20.50 | 1500.00 | BH NaviTrak (2019) (Standard) | | BUFORD 33-1-1L PWB |
| 1500.00 | 17429.83 | BH AutoTrak Curve/eXpress (2019) (Standard) | | BUFORD 33-1-1L PWB |

OFFSET WELLPATH REFERENCE - Offset Wellbore: BUFORD 33-1-1L PWB Offset Wellpath: BUFORD 33-1-1L (REV-A.0) PWP

| | |
|---------------------------------|---|
| MD Reference: RIG (20.5') (RKB) | Offset TVD & local coordinates use Reference Wellpath settings (See WELLPATH DATUM on page 1 of this report) |
| Ellipse Start MD | 20.50ft |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 97 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770°FSL & 819°FSL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD33-1-3L PWB Offset Wellpath: BUFORD33-1-3L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#10 BUFORD33-1-3L (770°FSL & 969°FSL, SEC.34) Well: BUFORD33-1-3L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 20.50 | 20.50 | 0.00 | 0.00 | 19.50 | 20.50 | 0.00 | 151.28 | 90.00 | 151.28 | 9.74 | 141.55 | 25.61 | PASS |
| 120.50† | 120.50 | 0.00 | 0.00 | 119.50 | 120.50 | 0.00 | 151.28 | 90.00 | 151.28 | 9.81 | 141.47 | 25.26 | PASS |
| 200.00 | 200.00 | 0.00 | 0.00 | 199.00 | 200.00 | 0.00 | 151.28 | 90.00 | 151.28 | 9.96 | 141.32 | 24.64 | PASS |
| 220.50† | 220.50 | -0.03 | -0.07 | 220.30 | 221.30 | -0.05 | 151.23 | 90.01 | 151.30 | 10.01 | 141.29 | 24.43 | PASS |
| 320.50† | 320.46 | -0.93 | -2.36 | 324.39 | 325.35 | -1.80 | 149.27 | 90.33 | 151.71 | 10.47 | 141.24 | 22.78 | PASS |
| 420.50† | 420.28 | -3.13 | -7.88 | 428.44 | 429.20 | -6.07 | 144.50 | 91.11 | 152.67 | 11.31 | 141.36 | 20.29 | PASS |
| 520.50† | 519.83 | -6.60 | -16.65 | 532.44 | 532.69 | -12.84 | 136.92 | 92.33 | 154.23 | 12.16 | 142.07 | 18.38 | PASS |
| 620.50† | 618.99 | -11.36 | -28.64 | 636.33 | 635.65 | -22.11 | 126.56 | 93.96 | 156.46 | 12.99 | 143.47 | 16.94 | PASS |
| 720.50† | 717.64 | -17.38 | -43.83 | 740.11 | 737.92 | -33.84 | 113.44 | 95.97 | 159.43 | 13.87 | 145.56 | 15.72 | PASS |
| 820.50† | 815.66 | -24.68 | -62.22 | 841.74 | 837.48 | -47.41 | 98.27 | 98.06 | 163.56 | 14.69 | 148.87 | 14.91 | PASS |
| 920.50† | 912.93 | -33.22 | -83.78 | 941.40 | 935.04 | -60.99 | 83.08 | 99.45 | 170.59 | 15.57 | 155.02 | 14.38 | PASS |
| 1020.50† | 1009.33 | -43.02 | -108.48 | 1040.87 | 1032.40 | -74.55 | 67.92 | 100.13 | 180.67 | 16.50 | 164.18 | 14.12 | PASS |
| 1120.50† | 1104.74 | -54.05 | -136.29 | 1140.01 | 1129.45 | -88.06 | 52.81 | 100.20 | 193.72 | 17.48 | 176.24 | 14.06 | PASS |
| 1220.50† | 1199.05 | -66.30 | -167.18 | 1238.70 | 1226.06 | -101.51 | 37.77 | 99.75 | 209.70 | 18.52 | 191.18 | 14.15 | PASS |
| 1242.54 | 1219.68 | -69.16 | -174.40 | 1260.38 | 1247.28 | -104.47 | 34.46 | 99.60 | 213.62 | 18.75 | 194.86 | 14.19 | PASS |
| 1320.50† | 1292.54 | -79.39 | -200.20 | 1337.03 | 1322.31 | -114.91 | 22.78 | 99.05 | 227.74 | 19.48 | 208.27 | 14.44 | PASS |
| 1420.50† | 1385.99 | -92.51 | -233.28 | 1435.33 | 1418.54 | -128.31 | 7.80 | 98.45 | 245.89 | 20.42 | 225.47 | 14.72 | PASS |
| 1520.50† | 1479.44 | -105.63 | -266.37 | 1533.64 | 1514.77 | -141.71 | -7.18 | 97.93 | 264.06 | 21.01 | 243.04 | 15.27 | PASS |
| 1620.50† | 1572.89 | -118.75 | -299.46 | 1631.95 | 1611.00 | -155.11 | -22.17 | 97.47 | 282.25 | 21.29 | 260.96 | 16.08 | PASS |
| 1720.50† | 1666.34 | -131.87 | -332.54 | 1730.26 | 1707.23 | -168.51 | -37.15 | 97.07 | 300.45 | 21.63 | 278.82 | 16.80 | PASS |
| 1820.50† | 1759.79 | -144.99 | -365.63 | 1828.56 | 1803.46 | -181.91 | -52.13 | 96.72 | 318.67 | 22.03 | 296.64 | 17.44 | PASS |
| 1920.50† | 1853.24 | -158.12 | -398.72 | 1926.87 | 1899.69 | -195.31 | -67.12 | 96.40 | 336.90 | 22.49 | 314.40 | 17.99 | PASS |
| 2020.50† | 1946.69 | -171.24 | -431.80 | 2025.18 | 1995.92 | -208.71 | -82.10 | 96.12 | 355.13 | 23.01 | 332.13 | 18.46 | PASS |
| 2120.50† | 2040.14 | -184.36 | -464.89 | 2123.49 | 2092.16 | -222.10 | -97.08 | 95.86 | 373.38 | 23.57 | 349.81 | 18.86 | PASS |
| 2220.50† | 2133.59 | -197.48 | -497.98 | 2221.80 | 2188.39 | -235.50 | -112.07 | 95.63 | 391.63 | 24.18 | 367.45 | 19.19 | PASS |
| 2320.50† | 2227.05 | -210.60 | -531.06 | 2320.10 | 2284.62 | -248.90 | -127.05 | 95.42 | 409.89 | 24.83 | 385.05 | 19.47 | PASS |
| 2420.50† | 2320.50 | -223.72 | -564.15 | 2418.41 | 2380.85 | -262.30 | -142.03 | 95.22 | 428.15 | 25.52 | 402.63 | 19.69 | PASS |
| 2520.50† | 2413.95 | -236.84 | -597.24 | 2516.72 | 2477.08 | -275.70 | -157.02 | 95.05 | 446.42 | 26.25 | 420.17 | 19.87 | PASS |
| 2620.50† | 2507.40 | -249.96 | -630.32 | 2615.03 | 2573.31 | -289.10 | -172.00 | 94.88 | 464.69 | 27.00 | 437.68 | 20.01 | PASS |
| 2720.50† | 2600.85 | -263.08 | -663.41 | 2713.34 | 2669.54 | -302.50 | -186.98 | 94.73 | 482.96 | 27.79 | 455.18 | 20.12 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 98 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770°FSL & 819°FSL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD33-1-3L PWB Offset Wellpath: BUFORD33-1-3L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#10 BUFORD33-1-3L (770°FSL & 969°FSL, SEC.34) Well: BUFORD33-1-3L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 2820.50† | 2694.30 | -276.20 | -696.50 | 2811.64 | 2765.77 | -315.90 | -201.97 | 94.59 | 501.24 | 28.60 | 472.64 | 20.20 | PASS |
| 2920.50† | 2787.75 | -289.33 | -729.58 | 2909.95 | 2862.00 | -329.30 | -216.95 | 94.46 | 519.52 | 29.43 | 490.09 | 20.26 | PASS |
| 3020.50† | 2881.20 | -302.45 | -762.67 | 3008.26 | 2958.24 | -342.69 | -231.93 | 94.34 | 537.81 | 30.29 | 507.52 | 20.30 | PASS |
| 3120.50† | 2974.65 | -315.57 | -795.76 | 3106.57 | 3054.47 | -356.09 | -246.92 | 94.22 | 556.09 | 31.16 | 524.93 | 20.32 | PASS |
| 3220.50† | 3068.11 | -328.69 | -828.84 | 3204.88 | 3150.70 | -369.49 | -261.90 | 94.12 | 574.38 | 32.05 | 542.33 | 20.32 | PASS |
| 3320.50† | 3161.56 | -341.81 | -861.93 | 3303.18 | 3246.93 | -382.89 | -276.88 | 94.02 | 592.67 | 32.95 | 559.72 | 20.32 | PASS |
| 3420.50† | 3255.01 | -354.93 | -895.02 | 3401.49 | 3343.16 | -396.29 | -291.87 | 93.92 | 610.96 | 33.87 | 577.09 | 20.31 | PASS |
| 3520.50† | 3348.46 | -368.05 | -928.10 | 3499.80 | 3439.39 | -409.69 | -306.85 | 93.83 | 629.25 | 34.81 | 594.45 | 20.29 | PASS |
| 3620.50† | 3441.91 | -381.17 | -961.19 | 3598.11 | 3535.62 | -423.09 | -321.83 | 93.75 | 647.55 | 35.75 | 611.80 | 20.26 | PASS |
| 3720.50† | 3535.36 | -394.29 | -994.28 | 3696.42 | 3631.85 | -436.49 | -336.82 | 93.67 | 665.84 | 36.71 | 629.14 | 20.23 | PASS |
| 3820.50† | 3628.81 | -407.41 | -1027.37 | 3794.72 | 3728.08 | -449.89 | -351.80 | 93.60 | 684.14 | 37.67 | 646.47 | 20.19 | PASS |
| 3920.50† | 3722.26 | -420.53 | -1060.45 | 3893.03 | 3824.32 | -463.29 | -366.78 | 93.53 | 702.44 | 38.65 | 663.79 | 20.15 | PASS |
| 4020.50† | 3815.71 | -433.66 | -1093.54 | 3991.34 | 3920.55 | -476.68 | -381.77 | 93.46 | 720.74 | 39.63 | 681.11 | 20.11 | PASS |
| 4120.50† | 3909.17 | -446.78 | -1126.63 | 4089.65 | 4016.78 | -490.08 | -396.75 | 93.40 | 739.04 | 40.62 | 698.42 | 20.06 | PASS |
| 4220.50† | 4002.62 | -459.90 | -1159.71 | 4187.96 | 4113.01 | -503.48 | -411.73 | 93.34 | 757.34 | 41.62 | 715.72 | 20.02 | PASS |
| 4320.50† | 4096.07 | -473.02 | -1192.80 | 4286.26 | 4209.24 | -516.88 | -426.72 | 93.28 | 775.64 | 42.62 | 733.02 | 19.97 | PASS |
| 4420.50† | 4189.52 | -486.14 | -1225.89 | 4384.57 | 4305.47 | -530.28 | -441.70 | 93.22 | 793.94 | 43.63 | 750.31 | 19.92 | PASS |
| 4520.50† | 4282.97 | -499.26 | -1258.97 | 4482.88 | 4401.70 | -543.68 | -456.68 | 93.17 | 812.24 | 44.65 | 767.60 | 19.88 | PASS |
| 4620.50† | 4376.42 | -512.38 | -1292.06 | 4581.19 | 4497.93 | -557.08 | -471.67 | 93.12 | 830.55 | 45.67 | 784.88 | 19.83 | PASS |
| 4720.50† | 4469.87 | -525.50 | -1325.15 | 4679.50 | 4594.16 | -570.48 | -486.65 | 93.07 | 848.85 | 46.69 | 802.16 | 19.78 | PASS |
| 4820.50† | 4563.32 | -538.62 | -1358.23 | 4777.80 | 4690.40 | -583.88 | -501.63 | 93.02 | 867.16 | 47.72 | 819.43 | 19.73 | PASS |
| 4920.50† | 4656.77 | -551.74 | -1391.32 | 4876.11 | 4786.63 | -597.27 | -516.62 | 92.98 | 885.46 | 48.76 | 836.71 | 19.69 | PASS |
| 5020.50† | 4750.22 | -564.87 | -1424.41 | 4974.42 | 4882.86 | -610.67 | -531.60 | 92.94 | 903.77 | 49.79 | 853.97 | 19.64 | PASS |
| 5120.50† | 4843.68 | -577.99 | -1457.49 | 5072.73 | 4979.09 | -624.07 | -546.58 | 92.90 | 922.07 | 50.84 | 871.24 | 19.60 | PASS |
| 5220.50† | 4937.13 | -591.11 | -1490.58 | 5171.04 | 5075.32 | -637.47 | -561.57 | 92.86 | 940.38 | 51.88 | 888.50 | 19.55 | PASS |
| 5320.50† | 5030.58 | -604.23 | -1523.67 | 5269.34 | 5171.55 | -650.87 | -576.55 | 92.82 | 958.69 | 52.93 | 905.76 | 19.51 | PASS |
| 5420.50† | 5124.03 | -617.35 | -1556.75 | 5367.65 | 5267.78 | -664.27 | -591.53 | 92.78 | 977.00 | 53.98 | 923.01 | 19.46 | PASS |
| 5520.50† | 5217.48 | -630.47 | -1589.84 | 5465.96 | 5364.01 | -677.67 | -606.51 | 92.75 | 995.30 | 55.03 | 940.27 | 19.42 | PASS |
| 5620.50† | 5310.93 | -643.59 | -1622.93 | 5564.27 | 5460.24 | -691.07 | -621.50 | 92.71 | 1013.61 | 56.09 | 957.52 | 19.38 | PASS |
| 5720.50† | 5404.38 | -656.71 | -1656.01 | 5662.58 | 5556.48 | -704.47 | -636.48 | 92.68 | 1031.92 | 57.15 | 974.77 | 19.33 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 99 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770°FSL & 819°FSL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD33-1-3L PWB Offset Wellpath: BUFORD33-1-3L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#10 BUFORD33-1-3L (770°FSL & 969°FSL, SEC.34) Well: BUFORD33-1-3L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | |
| 5820.50† | 5497.83 | -669.83 | -1689.10 | 5760.88 | 5652.71 | -717.87 | -651.46 | 92.65 | 1050.23 | 58.21 | 992.02 | 19.29 | PASS | | |
| 5920.50† | 5591.28 | -682.95 | -1722.19 | 5859.19 | 5748.94 | -731.26 | -666.45 | 92.62 | 1068.54 | 59.28 | 1009.26 | 19.25 | PASS | | |
| 6020.50† | 5684.74 | -696.07 | -1755.27 | 5957.50 | 5845.17 | -744.66 | -681.43 | 92.59 | 1086.85 | 60.34 | 1026.51 | 19.21 | PASS | | |
| 6120.50† | 5778.19 | -709.20 | -1788.36 | 6055.81 | 5941.40 | -758.06 | -696.41 | 92.56 | 1105.16 | 61.41 | 1043.75 | 19.18 | PASS | | |
| 6220.50† | 5871.64 | -722.32 | -1821.45 | 6154.12 | 6037.63 | -771.46 | -711.40 | 92.54 | 1123.47 | 62.48 | 1060.99 | 19.14 | PASS | | |
| 6320.50† | 5965.09 | -735.44 | -1854.54 | 6252.42 | 6133.86 | -784.86 | -726.38 | 92.51 | 1141.78 | 63.55 | 1078.23 | 19.10 | PASS | | |
| 6420.50† | 6058.54 | -748.56 | -1887.62 | 6350.73 | 6230.09 | -798.26 | -741.36 | 92.48 | 1160.09 | 64.62 | 1095.47 | 19.07 | PASS | | |
| 6520.50† | 6151.99 | -761.68 | -1920.71 | 6449.04 | 6326.32 | -811.66 | -756.35 | 92.46 | 1178.40 | 65.70 | 1112.70 | 19.03 | PASS | | |
| 6620.50† | 6245.44 | -774.80 | -1953.80 | 6547.35 | 6422.56 | -825.06 | -771.33 | 92.43 | 1196.71 | 66.77 | 1129.94 | 19.00 | PASS | | |
| 6720.50† | 6338.89 | -787.92 | -1986.88 | 6645.66 | 6518.79 | -838.46 | -786.31 | 92.41 | 1215.02 | 67.85 | 1147.17 | 18.96 | PASS | | |
| 6820.50† | 6432.34 | -801.04 | -2019.97 | 6743.96 | 6615.02 | -851.85 | -801.30 | 92.39 | 1233.33 | 68.93 | 1164.40 | 18.93 | PASS | | |
| 6920.50† | 6525.80 | -814.16 | -2053.06 | 6842.27 | 6711.25 | -865.25 | -816.28 | 92.37 | 1251.65 | 70.01 | 1181.63 | 18.90 | PASS | | |
| 7020.50† | 6619.25 | -827.28 | -2086.14 | 6940.66 | 6813.16 | -876.31 | -832.15 | 92.24 | 1269.84 | 71.13 | 1198.71 | 18.85 | PASS | | |
| 7120.50† | 6712.70 | -840.41 | -2119.23 | 7039.09 | 6915.92 | -887.21 | -848.20 | 91.34 | 1287.52 | 71.60 | 1215.92 | 18.98 | PASS | | |
| 7220.50† | 6806.15 | -853.53 | -2152.32 | 7137.43 | 7018.62 | -898.13 | -862.39 | 89.78 | 1305.42 | 71.97 | 1233.45 | 19.14 | PASS | | |
| 7320.50† | 6899.60 | -866.65 | -2185.40 | 7235.77 | 7121.32 | -909.06 | -876.41 | 87.87 | 1323.33 | 71.78 | 1251.95 | 19.48 | PASS | | |
| 7341.07 | 6918.82 | -869.35 | -2192.21 | 7241.57 | 7094.59 | -811.01 | -876.19 | 87.46 | 1328.98 | 71.69 | 1257.29 | 19.57 | PASS | | |
| 7420.50† | 6993.49 | -874.29 | -2218.65 | 7297.87 | 7142.49 | -782.44 | -883.73 | 86.06 | 1346.35 | 71.36 | 1275.00 | 19.92 | PASS | | |
| 7520.50† | 7087.21 | -884.88 | -2251.87 | 7366.15 | 7196.51 | -741.64 | -892.24 | 84.82 | 1369.57 | 70.94 | 1298.63 | 20.40 | PASS | | |
| 7620.50† | 7177.96 | -898.35 | -2284.05 | 7432.32 | 7243.93 | -696.15 | -899.73 | 84.14 | 1393.17 | 70.75 | 1322.42 | 20.81 | PASS | | |
| 7720.50† | 7262.97 | -911.51 | -2314.23 | 7496.97 | 7284.96 | -646.65 | -906.24 | 83.97 | 1416.01 | 70.63 | 1345.38 | 21.19 | PASS | | |
| 7820.50† | 7339.68 | -924.65 | -2341.49 | 7560.53 | 7319.68 | -593.74 | -911.76 | 84.25 | 1437.09 | 70.39 | 1366.70 | 21.58 | PASS | | |
| 7920.50† | 7405.75 | -937.79 | -2364.99 | 7623.31 | 7348.07 | -537.97 | -916.31 | 84.93 | 1455.52 | 70.06 | 1385.46 | 21.97 | PASS | | |
| 8020.50† | 7459.16 | -950.93 | -2384.03 | 7685.53 | 7370.10 | -479.92 | -919.87 | 85.92 | 1470.58 | 69.70 | 1400.88 | 22.32 | PASS | | |
| 8120.50† | 7498.30 | -963.50 | -2398.02 | 7747.37 | 7385.71 | -420.17 | -922.43 | 87.16 | 1481.70 | 69.38 | 1412.32 | 22.60 | PASS | | |
| 8220.50† | 7521.99 | -976.15 | -2406.55 | 7808.97 | 7394.84 | -359.30 | -923.98 | 88.55 | 1488.48 | 69.16 | 1419.32 | 22.78 | PASS | | |
| 8315.56 | 7529.50 | -989.24 | -2409.34 | 7868.30 | 7397.49 | -300.06 | -924.52 | 89.92 | 1490.68 | 69.02 | 1421.67 | 22.86 | PASS | | |
| 8320.50† | 7529.51 | -297.30 | -2409.35 | 7873.24 | 7397.48 | -295.12 | -924.53 | 89.92 | 1490.68 | 68.99 | 1421.70 | 22.87 | PASS | | |
| 8420.50† | 7529.61 | -197.30 | -2409.53 | 7973.24 | 7397.22 | -195.12 | -924.70 | 89.92 | 1490.72 | 68.51 | 1422.21 | 23.04 | PASS | | |
| 8520.50† | 7529.71 | -97.30 | -2409.71 | 8073.24 | 7396.96 | -95.12 | -924.87 | 89.92 | 1490.76 | 68.36 | 1422.40 | 23.09 | PASS | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 100 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD33-1-3L PWB Offset Wellpath: BUFORD33-1-3L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#10 BUFORD33-1-3L (770'FSL & 969'FWL, SEC.34) Well: BUFORD33-1-3L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | | |
| 8620.50† | 7529.82 | 2.70 | -2409.88 | 8173.24 | 7396.71 | 4.88 | -925.04 | 89.92 | 1490.80 | 71.94 | 1418.87 | 21.88 | PASS | | | |
| 8720.50† | 7529.92 | 102.70 | -2410.06 | 8273.24 | 7396.45 | 104.88 | -925.21 | 89.92 | 1490.84 | 68.80 | 1422.04 | 22.94 | PASS | | | |
| 8820.50† | 7530.02 | 202.70 | -2410.24 | 8373.23 | 7396.19 | 204.87 | -925.38 | 89.92 | 1490.88 | 69.36 | 1421.52 | 22.74 | PASS | | | |
| 8920.50† | 7530.13 | 302.70 | -2410.42 | 8473.23 | 7395.93 | 304.87 | -925.55 | 89.92 | 1490.92 | 70.15 | 1420.77 | 22.47 | PASS | | | |
| 9020.50† | 7530.23 | 402.70 | -2410.59 | 8573.23 | 7395.67 | 404.87 | -925.72 | 89.92 | 1490.96 | 71.16 | 1419.80 | 22.14 | PASS | | | |
| 9120.50† | 7530.33 | 502.70 | -2410.77 | 8673.23 | 7395.41 | 504.87 | -925.89 | 89.92 | 1491.00 | 72.37 | 1418.63 | 21.74 | PASS | | | |
| 9220.50† | 7530.44 | 602.70 | -2410.95 | 8773.23 | 7395.16 | 604.87 | -926.06 | 89.92 | 1491.04 | 73.78 | 1417.26 | 21.30 | PASS | | | |
| 9320.50† | 7530.54 | 702.70 | -2411.13 | 8873.23 | 7394.90 | 704.87 | -926.23 | 89.92 | 1491.08 | 75.38 | 1415.71 | 20.83 | PASS | | | |
| 9420.50† | 7530.64 | 802.69 | -2411.31 | 8973.23 | 7394.64 | 804.87 | -926.40 | 89.92 | 1491.13 | 77.14 | 1413.98 | 20.33 | PASS | | | |
| 9520.50† | 7530.75 | 902.69 | -2411.48 | 9073.23 | 7394.38 | 904.87 | -926.57 | 89.92 | 1491.17 | 79.07 | 1412.10 | 19.81 | PASS | | | |
| 9620.50† | 7530.85 | 1002.69 | -2411.66 | 9173.23 | 7394.12 | 1004.87 | -926.74 | 89.92 | 1491.21 | 81.14 | 1410.07 | 19.28 | PASS | | | |
| 9720.50† | 7530.96 | 1102.69 | -2411.84 | 9273.23 | 7393.86 | 1104.86 | -926.91 | 89.92 | 1491.25 | 83.35 | 1407.90 | 18.74 | PASS | | | |
| 9820.50† | 7531.06 | 1202.69 | -2412.02 | 9373.23 | 7393.60 | 1204.86 | -927.08 | 89.92 | 1491.29 | 85.69 | 1405.60 | 18.20 | PASS | | | |
| 9920.50† | 7531.16 | 1302.69 | -2412.19 | 9473.23 | 7393.35 | 1304.86 | -927.25 | 89.92 | 1491.33 | 88.13 | 1403.20 | 17.67 | PASS | | | |
| 10020.50† | 7531.27 | 1402.69 | -2412.37 | 9573.23 | 7393.09 | 1404.86 | -927.42 | 89.92 | 1491.37 | 90.69 | 1400.68 | 17.15 | PASS | | | |
| 10120.50† | 7531.37 | 1502.69 | -2412.55 | 9673.23 | 7392.83 | 1504.86 | -927.59 | 89.92 | 1491.41 | 93.34 | 1398.07 | 16.65 | PASS | | | |
| 10220.50† | 7531.47 | 1602.69 | -2412.73 | 9773.23 | 7392.57 | 1604.86 | -927.76 | 89.92 | 1491.45 | 96.08 | 1395.37 | 16.15 | PASS | | | |
| 10320.50† | 7531.58 | 1702.69 | -2412.90 | 9873.22 | 7392.31 | 1704.86 | -927.93 | 89.92 | 1491.49 | 98.90 | 1392.59 | 15.67 | PASS | | | |
| 10420.50† | 7531.68 | 1802.69 | -2413.08 | 9973.22 | 7392.05 | 1804.86 | -928.10 | 89.92 | 1491.54 | 101.79 | 1389.74 | 15.21 | PASS | | | |
| 10520.50† | 7531.78 | 1902.69 | -2413.26 | 10073.22 | 7391.79 | 1904.86 | -928.27 | 89.92 | 1491.58 | 104.75 | 1386.82 | 14.76 | PASS | | | |
| 10620.50† | 7531.89 | 2002.69 | -2413.44 | 10173.22 | 7391.54 | 2004.85 | -928.44 | 89.92 | 1491.62 | 107.77 | 1383.85 | 14.33 | PASS | | | |
| 10720.50† | 7531.99 | 2102.69 | -2413.62 | 10273.22 | 7391.28 | 2104.85 | -928.61 | 89.92 | 1491.66 | 110.85 | 1380.81 | 13.92 | PASS | | | |
| 10820.50† | 7532.09 | 2202.69 | -2413.79 | 10373.22 | 7391.02 | 2204.85 | -928.78 | 89.92 | 1491.70 | 113.98 | 1377.73 | 13.53 | PASS | | | |
| 10920.50† | 7532.20 | 2302.69 | -2413.97 | 10473.22 | 7390.76 | 2304.85 | -928.95 | 89.92 | 1491.74 | 117.15 | 1374.59 | 13.15 | PASS | | | |
| 11020.50† | 7532.30 | 2402.69 | -2414.15 | 10573.22 | 7390.50 | 2404.85 | -929.12 | 89.92 | 1491.79 | 120.37 | 1371.42 | 12.78 | PASS | | | |
| 11120.50† | 7532.41 | 2502.69 | -2414.33 | 10673.22 | 7390.24 | 2504.85 | -929.29 | 89.92 | 1491.83 | 123.63 | 1368.20 | 12.44 | PASS | | | |
| 11220.50† | 7532.51 | 2602.69 | -2414.50 | 10773.22 | 7389.99 | 2604.85 | -929.46 | 89.92 | 1491.87 | 126.63 | 1365.24 | 12.13 | PASS | | | |
| 11320.50† | 7532.61 | 2702.69 | -2414.68 | 10873.22 | 7389.73 | 2704.85 | -929.63 | 89.92 | 1491.91 | 130.25 | 1361.67 | 11.78 | PASS | | | |
| 11420.50† | 7532.72 | 2802.69 | -2414.86 | 10973.22 | 7389.47 | 2804.85 | -929.80 | 89.92 | 1491.96 | 133.60 | 1358.35 | 11.48 | PASS | | | |
| 11520.50† | 7532.82 | 2902.69 | -2415.04 | 11073.22 | 7389.21 | 2904.84 | -929.97 | 89.92 | 1492.00 | 136.99 | 1355.01 | 11.19 | PASS | | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 101 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD33-1-3L PWB Offset Wellpath: BUFORD33-1-3L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#10 BUFORD33-1-3L (770'FSL & 969'FWL, SEC.34) Well: BUFORD33-1-3L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 11620.50† | 7532.92 | 3002.69 | -2415.21 | 11173.22 | 7388.95 | 3004.84 | -930.14 | 89.92 | 1492.04 | 140.40 | 1351.64 | 10.91 | PASS |
| 11720.50† | 7533.03 | 3102.69 | -2415.39 | 11273.22 | 7388.69 | 3104.84 | -930.31 | 89.92 | 1492.08 | 143.84 | 1348.24 | 10.64 | PASS |
| 11820.50† | 7533.13 | 3202.69 | -2415.57 | 11373.21 | 7388.43 | 3204.84 | -930.48 | 89.92 | 1492.13 | 147.30 | 1344.83 | 10.38 | PASS |
| 11920.50† | 7533.23 | 3302.69 | -2415.75 | 11473.21 | 7388.18 | 3304.84 | -930.65 | 89.92 | 1492.17 | 150.78 | 1341.39 | 10.14 | PASS |
| 12020.50† | 7533.34 | 3402.69 | -2415.92 | 11573.21 | 7387.92 | 3404.84 | -930.82 | 89.92 | 1492.21 | 154.28 | 1337.93 | 9.90 | PASS |
| 12120.50† | 7533.44 | 3502.69 | -2416.10 | 11673.21 | 7387.66 | 3504.84 | -930.99 | 89.92 | 1492.25 | 157.80 | 1334.45 | 9.68 | PASS |
| 12220.50† | 7533.55 | 3602.69 | -2416.28 | 11773.21 | 7387.40 | 3604.84 | -931.16 | 89.92 | 1492.30 | 161.34 | 1330.96 | 9.46 | PASS |
| 12320.50† | 7533.65 | 3702.69 | -2416.46 | 11873.21 | 7387.14 | 3704.83 | -931.33 | 89.92 | 1492.34 | 164.89 | 1327.45 | 9.25 | PASS |
| 12420.50† | 7533.75 | 3802.69 | -2416.64 | 11973.21 | 7386.88 | 3804.83 | -931.50 | 89.92 | 1492.38 | 168.46 | 1323.93 | 9.05 | PASS |
| 12520.50† | 7533.86 | 3902.69 | -2416.81 | 12073.21 | 7386.63 | 3904.83 | -931.67 | 89.92 | 1492.43 | 172.04 | 1320.39 | 8.86 | PASS |
| 12620.50† | 7533.96 | 4002.69 | -2416.99 | 12173.21 | 7386.37 | 4004.83 | -931.84 | 89.92 | 1492.47 | 175.63 | 1316.84 | 8.67 | PASS |
| 12720.50† | 7534.06 | 4102.69 | -2417.17 | 12273.21 | 7386.11 | 4104.83 | -932.01 | 89.92 | 1492.51 | 179.24 | 1313.28 | 8.49 | PASS |
| 12820.50† | 7534.17 | 4202.69 | -2417.35 | 12373.21 | 7385.85 | 4204.83 | -932.18 | 89.92 | 1492.56 | 182.86 | 1309.70 | 8.32 | PASS |
| 12920.50† | 7534.27 | 4302.69 | -2417.52 | 12473.21 | 7385.59 | 4304.83 | -932.35 | 89.92 | 1492.60 | 186.48 | 1306.12 | 8.16 | PASS |
| 13020.50† | 7534.37 | 4402.69 | -2417.70 | 12573.21 | 7385.33 | 4404.83 | -932.52 | 89.92 | 1492.64 | 190.12 | 1302.52 | 8.00 | PASS |
| 13120.50† | 7534.48 | 4502.69 | -2417.88 | 12673.21 | 7385.07 | 4504.83 | -932.69 | 89.92 | 1492.69 | 193.77 | 1298.92 | 7.84 | PASS |
| 13199.97 | 7534.56 | 4582.16 | -2418.02 | 12752.68 | 7384.87 | 4584.30 | -932.82 | 89.92 | 1492.72 | 196.67 | 1296.05 | 7.73 | PASS |
| 13220.50† | 7534.58 | 4602.69 | -2418.13 | 12773.21 | 7384.82 | 4604.82 | -932.86 | 89.92 | 1492.81 | 197.42 | 1295.38 | 7.70 | PASS |
| 13320.50† | 7534.68 | 4702.65 | -2420.77 | 12873.17 | 7384.56 | 4704.79 | -933.03 | 89.92 | 1495.30 | 201.08 | 1294.22 | 7.57 | PASS |
| 13420.50† | 7534.79 | 4802.45 | -2426.90 | 12972.99 | 7384.30 | 4804.60 | -933.20 | 89.92 | 1501.26 | 204.79 | 1296.47 | 7.46 | PASS |
| 13476.50 | 7534.85 | 4858.23 | -2431.85 | 13028.78 | 7384.16 | 4860.39 | -933.29 | 89.92 | 1506.11 | 206.86 | 1299.25 | 7.40 | PASS |
| 13520.50† | 7534.89 | 4902.02 | -2436.16 | 13072.57 | 7384.04 | 4904.19 | -933.37 | 89.92 | 1510.35 | 208.49 | 1301.86 | 7.37 | PASS |
| 13620.50† | 7534.99 | 5001.54 | -2445.98 | 13172.10 | 7383.78 | 5003.72 | -933.54 | 89.92 | 1519.98 | 212.21 | 1307.77 | 7.28 | PASS |
| 13720.50† | 7535.10 | 5101.06 | -2455.79 | 13271.63 | 7383.53 | 5103.25 | -933.71 | 89.92 | 1529.62 | 215.95 | 1313.66 | 7.20 | PASS |
| 13820.50† | 7535.20 | 5200.57 | -2465.61 | 13371.17 | 7383.27 | 5202.78 | -933.87 | 89.92 | 1539.25 | 219.70 | 1319.55 | 7.12 | PASS |
| 13920.50† | 7535.30 | 5300.09 | -2475.42 | 13470.70 | 7383.01 | 5302.32 | -934.04 | 89.92 | 1548.89 | 223.46 | 1325.43 | 7.04 | PASS |
| 14020.50† | 7535.40 | 5399.61 | -2485.24 | 13570.23 | 7382.76 | 5401.85 | -934.21 | 89.92 | 1558.52 | 227.22 | 1331.30 | 6.96 | PASS |
| 14120.50† | 7535.51 | 5499.12 | -2495.05 | 13669.77 | 7382.50 | 5501.38 | -934.38 | 89.92 | 1568.15 | 230.98 | 1337.17 | 6.89 | PASS |
| 14220.50† | 7535.61 | 5598.64 | -2504.87 | 13769.30 | 7382.24 | 5600.91 | -934.55 | 89.92 | 1577.79 | 234.76 | 1343.03 | 6.82 | PASS |
| 14221.87 | 7535.61 | 5600.00 | -2505.00 | 13770.66 | 7382.24 | 5602.27 | -934.55 | 89.92 | 1577.92 | 234.81 | 1343.11 | 6.82 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 102 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD33-1-3L PWB Offset Wellpath: BUFORD33-1-3L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#10 BUFORD33-1-3L (770'FSL & 969'FWL, SEC.34) Well: BUFORD33-1-3L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | |
| 14320.50† | 7535.71 | 5698.31 | -2512.99 | 13868.98 | 7381.98 | 5700.59 | -934.72 | 89.92 | 1585.74 | 238.51 | 1347.23 | 6.74 | PASS | | |
| 14420.50† | 7535.81 | 5798.19 | -2517.63 | 13968.87 | 7381.73 | 5800.49 | -934.89 | 89.92 | 1590.22 | 242.28 | 1347.94 | 6.66 | PASS | | |
| 14520.50† | 7535.92 | 5898.18 | -2518.78 | 14068.86 | 7381.47 | 5900.47 | -935.06 | 89.92 | 1591.24 | 246.04 | 1345.19 | 6.56 | PASS | | |
| 14581.38 | 7535.98 | 5959.05 | -2517.77 | 14129.73 | 7381.31 | 5961.34 | -935.16 | 89.92 | 1590.15 | 248.31 | 1341.84 | 6.49 | PASS | | |
| 14620.50† | 7536.02 | 5998.16 | -2516.71 | 14168.83 | 7381.21 | 6000.45 | -935.23 | 89.92 | 1589.04 | 249.76 | 1339.27 | 6.45 | PASS | | |
| 14720.50† | 7536.12 | 6098.12 | -2513.99 | 14268.79 | 7380.95 | 6100.40 | -935.40 | 89.92 | 1586.20 | 253.48 | 1332.72 | 6.34 | PASS | | |
| 14820.50† | 7536.23 | 6198.08 | -2511.27 | 14368.75 | 7380.69 | 6200.36 | -935.57 | 89.92 | 1583.36 | 257.21 | 1326.14 | 6.24 | PASS | | |
| 14920.50† | 7536.33 | 6298.05 | -2508.55 | 14468.71 | 7380.43 | 6300.32 | -935.74 | 89.92 | 1580.52 | 260.95 | 1319.57 | 6.14 | PASS | | |
| 15020.50† | 7536.43 | 6398.01 | -2505.83 | 14568.66 | 7380.17 | 6400.27 | -935.91 | 89.92 | 1577.68 | 264.69 | 1312.99 | 6.04 | PASS | | |
| 15120.50† | 7536.54 | 6497.97 | -2503.11 | 14668.62 | 7379.92 | 6500.23 | -936.08 | 89.92 | 1574.84 | 268.43 | 1306.41 | 5.94 | PASS | | |
| 15220.50† | 7536.64 | 6597.93 | -2500.40 | 14768.58 | 7379.66 | 6600.19 | -936.25 | 89.92 | 1572.00 | 272.18 | 1299.82 | 5.85 | PASS | | |
| 15320.50† | 7536.74 | 6697.90 | -2497.68 | 14868.54 | 7379.40 | 6700.15 | -936.42 | 89.92 | 1569.17 | 275.93 | 1293.24 | 5.76 | PASS | | |
| 15420.50† | 7536.85 | 6797.86 | -2494.96 | 14968.49 | 7379.14 | 6800.10 | -936.59 | 89.92 | 1566.33 | 279.68 | 1286.65 | 5.67 | PASS | | |
| 15520.50† | 7536.95 | 6897.82 | -2492.24 | 15068.45 | 7378.88 | 6900.06 | -936.76 | 89.92 | 1563.49 | 283.44 | 1280.05 | 5.58 | PASS | | |
| 15620.50† | 7537.05 | 6997.79 | -2489.52 | 15168.41 | 7378.62 | 7000.02 | -936.93 | 89.92 | 1560.65 | 287.19 | 1273.46 | 5.50 | PASS | | |
| 15720.50† | 7537.16 | 7097.75 | -2486.80 | 15268.37 | 7378.37 | 7099.97 | -937.10 | 89.92 | 1557.82 | 290.95 | 1266.86 | 5.41 | PASS | | |
| 15820.50† | 7537.26 | 7197.71 | -2484.08 | 15368.32 | 7378.11 | 7199.93 | -937.27 | 89.92 | 1554.98 | 294.72 | 1260.26 | 5.33 | PASS | | |
| 15920.50† | 7537.36 | 7297.68 | -2481.36 | 15468.28 | 7377.85 | 7299.89 | -937.44 | 89.92 | 1552.14 | 298.48 | 1253.66 | 5.26 | PASS | | |
| 16020.50† | 7537.47 | 7397.64 | -2478.64 | 15568.24 | 7377.59 | 7399.85 | -937.61 | 89.92 | 1549.31 | 302.25 | 1247.06 | 5.18 | PASS | | |
| 16120.50† | 7537.57 | 7497.60 | -2475.93 | 15668.20 | 7377.33 | 7499.80 | -937.78 | 89.92 | 1546.47 | 306.01 | 1240.46 | 5.11 | PASS | | |
| 16220.50† | 7537.68 | 7597.56 | -2473.21 | 15768.15 | 7377.07 | 7599.76 | -937.95 | 89.92 | 1543.64 | 309.78 | 1233.85 | 5.03 | PASS | | |
| 16320.50† | 7537.78 | 7697.53 | -2470.49 | 15868.11 | 7376.82 | 7699.72 | -938.12 | 89.92 | 1540.80 | 313.56 | 1227.24 | 4.96 | PASS | | |
| 16420.50† | 7537.88 | 7797.49 | -2467.77 | 15968.07 | 7376.56 | 7799.67 | -938.29 | 89.92 | 1537.97 | 317.33 | 1220.64 | 4.90 | PASS | | |
| 16520.50† | 7537.99 | 7897.45 | -2465.05 | 16068.03 | 7376.30 | 7899.63 | -938.46 | 89.92 | 1535.13 | 321.11 | 1214.03 | 4.83 | PASS | | |
| 16620.50† | 7538.09 | 7997.42 | -2462.33 | 16167.99 | 7376.04 | 7999.59 | -938.63 | 89.92 | 1532.30 | 324.88 | 1207.41 | 4.76 | PASS | | |
| 16720.50† | 7538.19 | 8097.38 | -2459.61 | 16267.94 | 7375.78 | 8099.55 | -938.80 | 89.92 | 1529.46 | 328.66 | 1200.80 | 4.70 | PASS | | |
| 16820.50† | 7538.30 | 8197.34 | -2456.89 | 16367.90 | 7375.52 | 8199.50 | -938.97 | 89.92 | 1526.63 | 332.44 | 1194.19 | 4.64 | PASS | | |
| 16920.50† | 7538.40 | 8297.31 | -2454.17 | 16467.86 | 7375.27 | 8299.46 | -939.14 | 89.92 | 1523.79 | 336.22 | 1187.57 | 4.57 | PASS | | |
| 17020.50† | 7538.50 | 8397.27 | -2451.46 | 16567.82 | 7375.01 | 8399.42 | -939.31 | 89.92 | 1520.96 | 340.01 | 1180.96 | 4.51 | PASS | | |
| 17120.50† | 7538.61 | 8497.23 | -2448.74 | 16667.77 | 7374.75 | 8499.37 | -939.48 | 89.92 | 1518.13 | 343.79 | 1174.34 | 4.46 | PASS | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 103 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: BUFORD33-1-3L PWB Offset Wellpath: BUFORD33-1-3L (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#10 BUFORD33-1-3L (770'FSL & 969'FWL, SEC.34) Well: BUFORD33-1-3L Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 17220.50† | 7538.71 | 8597.19 | -2446.02 | 16767.73 | 7374.49 | 8599.33 | -939.65 | 89.92 | 1515.30 | 347.57 | 1167.72 | 4.40 | PASS |
| 17320.50† | 7538.81 | 8697.16 | -2443.30 | 16867.69 | 7374.23 | 8699.29 | -939.82 | 89.92 | 1512.46 | 351.36 | 1161.10 | 4.34 | PASS |
| 17420.50† | 7538.92 | 8797.12 | -2440.58 | 16967.65 | 7373.97 | 8799.25 | -939.99 | 89.92 | 1509.63 | 355.15 | 1154.48 | 4.29 | PASS |
| 17520.50† | 7539.02 | 8897.08 | -2437.86 | 17067.60 | 7373.72 | 8899.20 | -940.16 | 89.92 | 1506.80 | 358.94 | 1147.86 | 4.23 | PASS |
| 17620.50† | 7539.12 | 8997.05 | -2435.14 | 17167.56 | 7373.46 | 8999.16 | -940.33 | 89.92 | 1503.97 | 362.73 | 1141.24 | 4.18 | PASS |
| 17720.50† | 7539.23 | 9097.01 | -2432.42 | 17267.52 | 7373.20 | 9099.12 | -940.50 | 89.92 | 1501.14 | 366.52 | 1134.62 | 4.13 | PASS |
| 17820.50† | 7539.33 | 9196.97 | -2429.70 | 17367.48 | 7372.94 | 9199.07 | -940.67 | 89.92 | 1498.31 | 370.31 | 1128.00 | 4.08 | PASS |
| 17920.50† | 7539.43 | 9296.94 | -2426.99 | 17467.43 | 7372.68 | 9299.03 | -940.84 | 89.92 | 1495.47 | 374.10 | 1121.37 | 4.03 | PASS |
| 17985.90 | 7539.50 | 9362.31 | -2425.21 | 17532.80 | 7372.51 | 9364.40 | -940.95 | 89.92 | 1493.62 | 376.58 | 1117.05 | 4.00 | PASS |

POSITIONAL UNCERTAINTY - Offset Wellbore: BUFORD33-1-3L PWB Offset Wellpath: BUFORD33-1-3L (REV-A.0) PWP

| | | | | |
|-----------------------------------|------------|---------|----------|---------|
| Slot Surface Uncertainty @1SD | Horizontal | 0.100ft | Vertical | 1.000ft |
| Facility Surface Uncertainty @1SD | Horizontal | 8.200ft | Vertical | 3.000ft |

SURVEY PROGRAM - Offset Wellbore: BUFORD33-1-3L PWB Offset Wellpath: BUFORD33-1-3L (REV-A.0) PWP

| Start MD [ft] | End MD [ft] | Positional Uncertainty Model | Log Name/Comment | Wellbore |
|---------------|-------------|---|------------------|-------------------|
| 20.50 | 1500.00 | BH NaviTrak (2019) (Standard) | | BUFORD33-1-3L PWB |
| 1500.00 | 17557.17 | BH AutoTrak Curve/eXpress (2019) (Standard) | | BUFORD33-1-3L PWB |

OFFSET WELLPATH REFERENCE - Offset Wellbore: BUFORD33-1-3L PWB Offset Wellpath: BUFORD33-1-3L (REV-A.0) PWP

| | |
|---------------------------------|---|
| MD Reference: RIG (20.5') (RKB) | Offset TVD & local coordinates use Reference Wellpath settings (See WELLPATH DATUM on page 1 of this report) |
| Ellipse Start MD | 20.50ft |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 104 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. STRAWDER 1 AWB Offset Wellpath: EX. STRAWDER 1 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W | | Slot: SLOT#02 EX. STRAWDER 1 (1590'FSL & 1600'FWL, SI) | | Well: EX. STRAWDER 1 | | Threshold Value=1.00 | | † = interpolated, ‡ = extrapolated station | | | | | | |
|----------------------------|--------------|--|---------------|----------------------|-----------------|----------------------|------------------|--|---------------------|----------------|----------------------|-----------|-------------|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | |
| 20.50 | 20.50 | 0.00 | 0.00 | -20.50 | 69.00 | 6124.08 | -4526.15 | 323.53 | 7615.30 | 33.25 | 7582.04 | 260.04 | PASS | |
| 120.50† | 120.50 | 0.00 | 0.00 | 31.01 | 120.50 | 6124.08 | -4526.15 | 323.53 | 7615.14 | 45.04 | 7570.11 | 185.40 | PASS | |
| 200.00 | 200.00 | 0.00 | 0.00 | 110.53 | 200.00 | 6124.08 | -4526.15 | 323.53 | 7615.14 | 45.25 | 7569.89 | 184.42 | PASS | |
| 220.50† | 220.50 | -0.03 | -0.07 | 131.04 | 220.50 | 6124.08 | -4526.15 | 323.53 | 7615.13 | 45.42 | 7569.70 | 183.68 | PASS | |
| 320.50† | 320.46 | -0.93 | -2.36 | 231.06 | 320.46 | 6124.08 | -4526.15 | 323.55 | 7614.50 | 46.43 | 7568.07 | 179.31 | PASS | |
| 420.50† | 420.28 | -3.13 | -7.88 | 330.94 | 420.28 | 6124.08 | -4526.15 | 323.60 | 7612.98 | 48.03 | 7564.95 | 172.75 | PASS | |
| 520.50† | 519.83 | -6.60 | -16.65 | 430.55 | 519.83 | 6124.08 | -4526.15 | 323.66 | 7610.58 | 50.18 | 7560.40 | 164.67 | PASS | |
| 620.50† | 618.99 | -11.36 | -28.64 | 529.77 | 618.99 | 6124.08 | -4526.15 | 323.76 | 7607.32 | 52.79 | 7554.52 | 155.78 | PASS | |
| 720.50† | 717.64 | -17.38 | -43.83 | 628.48 | 717.64 | 6124.08 | -4526.15 | 323.88 | 7603.21 | 55.80 | 7547.41 | 146.66 | PASS | |
| 820.50† | 815.66 | -24.68 | -62.22 | 726.56 | 815.66 | 6124.08 | -4526.15 | 324.02 | 7598.28 | 59.12 | 7539.16 | 137.74 | PASS | |
| 920.50† | 912.93 | -33.22 | -83.78 | 823.89 | 912.93 | 6124.08 | -4526.15 | 324.19 | 7592.57 | 62.69 | 7529.87 | 129.26 | PASS | |
| 1020.50† | 1009.33 | -43.02 | -108.48 | 920.35 | 1009.33 | 6124.08 | -4526.15 | 324.39 | 7586.10 | 66.47 | 7519.64 | 121.35 | PASS | |
| 1120.50† | 1104.74 | -54.05 | -136.29 | 1015.82 | 1104.74 | 6124.08 | -4526.15 | 324.60 | 7578.93 | 70.39 | 7508.54 | 114.07 | PASS | |
| 1220.50† | 1199.05 | -66.30 | -167.18 | 1110.19 | 1199.05 | 6124.08 | -4526.15 | 324.85 | 7571.09 | 74.43 | 7496.66 | 107.41 | PASS | |
| 1242.54 | 1219.68 | -69.16 | -174.40 | 1130.83 | 1219.68 | 6124.08 | -4526.15 | 324.91 | 7569.28 | 75.34 | 7493.94 | 106.02 | PASS | |
| 1320.50† | 1292.54 | -79.39 | -200.20 | 1203.73 | 1292.54 | 6124.08 | -4526.15 | 325.11 | 7562.87 | 78.57 | 7484.30 | 101.34 | PASS | |
| 1420.50† | 1385.99 | -92.51 | -233.28 | 1297.24 | 1385.99 | 6124.08 | -4526.15 | 325.37 | 7554.78 | 82.82 | 7471.97 | 95.78 | PASS | |
| 1520.50† | 1479.44 | -105.63 | -266.37 | 1390.74 | 1479.44 | 6124.08 | -4526.15 | 325.64 | 7546.86 | 87.11 | 7459.75 | 90.74 | PASS | |
| 1620.50† | 1572.89 | -118.75 | -299.46 | 1484.25 | 1572.89 | 6124.08 | -4526.15 | 325.90 | 7539.09 | 91.45 | 7447.65 | 86.15 | PASS | |
| 1720.50† | 1666.34 | -131.87 | -332.54 | 1577.76 | 1666.34 | 6124.08 | -4526.15 | 326.17 | 7531.49 | 95.86 | 7435.63 | 81.94 | PASS | |
| 1820.50† | 1759.79 | -144.99 | -365.63 | 1671.27 | 1759.79 | 6124.08 | -4526.15 | 326.43 | 7524.05 | 100.33 | 7423.72 | 78.05 | PASS | |
| 1920.50† | 1853.24 | -158.12 | -398.72 | 1764.78 | 1853.24 | 6124.08 | -4526.15 | 326.70 | 7516.76 | 104.86 | 7411.90 | 74.48 | PASS | |
| 2020.50† | 1946.69 | -171.24 | -431.80 | 1858.28 | 1946.69 | 6124.08 | -4526.15 | 326.96 | 7509.64 | 109.44 | 7400.20 | 71.17 | PASS | |
| 2120.50† | 2040.14 | -184.36 | -464.89 | 1951.79 | 2040.14 | 6124.08 | -4526.15 | 327.23 | 7502.68 | 114.06 | 7388.62 | 68.12 | PASS | |
| 2220.50† | 2133.59 | -197.48 | -497.98 | 2045.30 | 2133.59 | 6124.08 | -4526.15 | 327.49 | 7495.89 | 118.72 | 7377.17 | 65.30 | PASS | |
| 2320.50† | 2227.05 | -210.60 | -531.06 | 2138.81 | 2227.05 | 6124.08 | -4526.15 | 327.76 | 7489.25 | 123.41 | 7365.84 | 62.68 | PASS | |
| 2420.50† | 2320.50 | -223.72 | -564.15 | 2232.32 | 2320.50 | 6124.08 | -4526.15 | 328.03 | 7482.78 | 128.14 | 7354.65 | 60.24 | PASS | |
| 2520.50† | 2413.95 | -236.84 | -597.24 | 2325.82 | 2413.95 | 6124.08 | -4526.15 | 328.30 | 7476.48 | 132.89 | 7343.59 | 57.97 | PASS | |
| 2620.50† | 2507.40 | -249.96 | -630.32 | 2419.33 | 2507.40 | 6124.08 | -4526.15 | 328.57 | 7470.34 | 137.66 | 7332.68 | 55.85 | PASS | |
| 2720.50† | 2600.85 | -263.08 | -663.41 | 2512.84 | 2600.85 | 6124.08 | -4526.15 | 328.84 | 7464.36 | 142.45 | 7321.91 | 53.88 | PASS | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 105 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. STRAWDER 1 AWB Offset Wellpath: EX. STRAWDER 1 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#02 EX. STRAWDER 1 (1590'FSL & 1600'FWL, SI) Well: EX. STRAWDER 1 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 2820.50† | 2694.30 | -276.20 | -696.50 | 2606.35 | 2694.30 | 6124.08 | -4526.15 | 329.11 | 7458.55 | 147.27 | 7311.28 | 52.03 | PASS |
| 2920.50† | 2787.75 | -289.33 | -729.58 | 2699.86 | 2787.75 | 6124.08 | -4526.15 | 329.38 | 7452.90 | 152.10 | 7300.80 | 50.29 | PASS |
| 3020.50† | 2881.20 | -302.45 | -762.67 | 2793.36 | 2881.20 | 6124.08 | -4526.15 | 329.65 | 7447.42 | 156.94 | 7290.48 | 48.66 | PASS |
| 3120.50† | 2974.65 | -315.57 | -795.76 | 2886.87 | 2974.65 | 6124.08 | -4526.15 | 329.92 | 7442.10 | 161.80 | 7280.30 | 47.13 | PASS |
| 3220.50† | 3068.11 | -328.69 | -828.84 | 2980.38 | 3068.11 | 6124.08 | -4526.15 | 330.19 | 7436.96 | 166.68 | 7270.28 | 45.69 | PASS |
| 3320.50† | 3161.56 | -341.81 | -861.93 | 3073.89 | 3161.56 | 6124.08 | -4526.15 | 330.46 | 7431.98 | 171.56 | 7260.41 | 44.33 | PASS |
| 3420.50† | 3255.01 | -354.93 | -895.02 | 3167.40 | 3255.01 | 6124.08 | -4526.15 | 330.73 | 7427.16 | 176.46 | 7250.70 | 43.04 | PASS |
| 3520.50† | 3348.46 | -368.05 | -928.10 | 3260.90 | 3348.46 | 6124.08 | -4526.15 | 331.00 | 7422.52 | 181.37 | 7241.15 | 41.82 | PASS |
| 3620.50† | 3441.91 | -381.17 | -961.19 | 3354.41 | 3441.91 | 6124.08 | -4526.15 | 331.28 | 7418.04 | 186.28 | 7231.76 | 40.67 | PASS |
| 3720.50† | 3535.36 | -394.29 | -994.28 | 3447.92 | 3535.36 | 6124.08 | -4526.15 | 331.55 | 7413.73 | 191.20 | 7222.52 | 39.58 | PASS |
| 3820.50† | 3628.81 | -407.41 | -1027.37 | 3541.43 | 3628.81 | 6124.08 | -4526.15 | 331.82 | 7409.58 | 196.14 | 7213.45 | 38.54 | PASS |
| 3920.50† | 3722.26 | -420.53 | -1060.45 | 3634.94 | 3722.26 | 6124.08 | -4526.15 | 332.10 | 7405.61 | 201.07 | 7204.54 | 37.55 | PASS |
| 4020.50† | 3815.71 | -433.66 | -1093.54 | 3728.44 | 3815.71 | 6124.08 | -4526.15 | 332.37 | 7401.81 | 206.02 | 7195.79 | 36.62 | PASS |
| 4120.50† | 3909.17 | -446.78 | -1126.63 | 3821.95 | 3909.17 | 6124.08 | -4526.15 | 332.65 | 7398.17 | 210.97 | 7187.20 | 35.72 | PASS |
| 4220.50† | 4002.62 | -459.90 | -1159.71 | 3915.46 | 4002.62 | 6124.08 | -4526.15 | 332.92 | 7394.71 | 215.93 | 7178.78 | 34.87 | PASS |
| 4320.50† | 4096.07 | -473.02 | -1192.80 | 4008.97 | 4096.07 | 6124.08 | -4526.15 | 333.19 | 7391.41 | 220.89 | 7170.52 | 34.06 | PASS |
| 4420.50† | 4189.52 | -486.14 | -1225.89 | 4102.48 | 4189.52 | 6124.08 | -4526.15 | 333.47 | 7388.29 | 225.86 | 7162.43 | 33.28 | PASS |
| 4520.50† | 4282.97 | -499.26 | -1258.97 | 4195.99 | 4282.97 | 6124.08 | -4526.15 | 333.74 | 7385.33 | 230.83 | 7154.50 | 32.54 | PASS |
| 4620.50† | 4376.42 | -512.38 | -1292.06 | 4289.49 | 4376.42 | 6124.08 | -4526.15 | 334.02 | 7382.55 | 235.81 | 7146.74 | 31.83 | PASS |
| 4720.50† | 4469.87 | -525.50 | -1325.15 | 4383.00 | 4469.87 | 6124.08 | -4526.15 | 334.30 | 7379.93 | 240.79 | 7139.15 | 31.15 | PASS |
| 4820.50† | 4563.32 | -538.62 | -1358.23 | 4476.51 | 4563.32 | 6124.08 | -4526.15 | 334.57 | 7377.49 | 245.77 | 7131.72 | 30.50 | PASS |
| 4920.50† | 4656.77 | -551.74 | -1391.32 | 4570.02 | 4656.77 | 6124.08 | -4526.15 | 334.85 | 7375.22 | 250.76 | 7124.46 | 29.87 | PASS |
| 5020.50† | 4750.22 | -564.87 | -1424.41 | 4663.53 | 4750.22 | 6124.08 | -4526.15 | 335.12 | 7373.12 | 255.75 | 7117.37 | 29.27 | PASS |
| 5120.50† | 4843.68 | -577.99 | -1457.49 | 4757.03 | 4843.68 | 6124.08 | -4526.15 | 335.40 | 7371.19 | 260.74 | 7110.44 | 28.69 | PASS |
| 5220.50† | 4937.13 | -591.11 | -1490.58 | 4850.54 | 4937.13 | 6124.08 | -4526.15 | 335.68 | 7369.43 | 265.74 | 7103.69 | 28.14 | PASS |
| 5320.50† | 5030.58 | -604.23 | -1523.67 | 4944.05 | 5030.58 | 6124.08 | -4526.15 | 335.95 | 7367.84 | 270.74 | 7097.10 | 27.61 | PASS |
| 5420.50† | 5124.03 | -617.35 | -1556.75 | 5037.56 | 5124.03 | 6124.08 | -4526.15 | 336.23 | 7366.43 | 275.74 | 7090.68 | 27.09 | PASS |
| 5520.50† | 5217.48 | -630.47 | -1589.84 | 5131.07 | 5217.48 | 6124.08 | -4526.15 | 336.51 | 7365.18 | 280.74 | 7084.44 | 26.60 | PASS |
| 5620.50† | 5310.93 | -643.59 | -1622.93 | 5224.57 | 5310.93 | 6124.08 | -4526.15 | 336.78 | 7364.11 | 285.75 | 7078.36 | 26.12 | PASS |
| 5720.50† | 5404.38 | -656.71 | -1656.01 | 5318.08 | 5404.38 | 6124.08 | -4526.15 | 337.06 | 7363.21 | 290.76 | 7072.45 | 25.66 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 106 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. STRAWDER 1 AWB Offset Wellpath: EX. STRAWDER 1 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#02 EX. STRAWDER 1 (1590'FSL & 1600'FWL, SI) Well: EX. STRAWDER 1 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | |
| 5820.50† | 5497.83 | -669.83 | -1689.10 | 5411.59 | 5497.83 | 6124.08 | -4526.15 | 337.34 | 7362.48 | 295.77 | 7066.71 | 25.22 | PASS | | |
| 5920.50† | 5591.28 | -682.95 | -1722.19 | 5505.10 | 5591.28 | 6124.08 | -4526.15 | 337.61 | 7361.93 | 300.78 | 7061.14 | 24.79 | PASS | | |
| 6020.50† | 5684.74 | -696.07 | -1755.27 | 5598.61 | 5684.74 | 6124.08 | -4526.15 | 337.89 | 7361.54 | 305.80 | 7055.75 | 24.38 | PASS | | |
| 6120.50† | 5778.19 | -709.20 | -1788.36 | 5692.11 | 5778.19 | 6124.08 | -4526.15 | 338.17 | 7361.33 | 310.81 | 7050.52 | 23.98 | PASS | | |
| 6220.50† | 5871.64 | -722.32 | -1821.45 | 5785.62 | 5871.64 | 6124.08 | -4526.15 | 338.44 | 7361.29 | 315.83 | 7045.46 | 23.59 | PASS | | |
| 6320.50† | 5965.09 | -735.44 | -1854.54 | 5879.13 | 5965.09 | 6124.08 | -4526.15 | 338.72 | 7361.42 | 320.85 | 7040.58 | 23.22 | PASS | | |
| 6420.50† | 6058.54 | -748.56 | -1887.62 | 5972.64 | 6058.54 | 6124.08 | -4526.15 | 339.00 | 7361.73 | 325.87 | 7035.86 | 22.86 | PASS | | |
| 6520.50† | 6151.99 | -761.68 | -1920.71 | 6066.15 | 6151.99 | 6124.08 | -4526.15 | 339.27 | 7362.20 | 330.89 | 7031.32 | 22.51 | PASS | | |
| 6620.50† | 6245.44 | -774.80 | -1953.80 | 6159.65 | 6245.44 | 6124.08 | -4526.15 | 339.55 | 7362.85 | 335.91 | 7026.94 | 22.17 | PASS | | |
| 6720.50† | 6338.89 | -787.92 | -1986.88 | 6253.16 | 6338.89 | 6124.08 | -4526.15 | 339.83 | 7363.67 | 340.93 | 7022.74 | 21.84 | PASS | | |
| 6820.50† | 6432.34 | -801.04 | -2019.97 | 6346.67 | 6432.34 | 6124.08 | -4526.15 | 340.11 | 7364.67 | 345.96 | 7018.71 | 21.52 | PASS | | |
| 6920.50† | 6525.80 | -814.16 | -2053.06 | 6440.18 | 6525.80 | 6124.08 | -4526.15 | 340.38 | 7365.83 | 350.98 | 7014.85 | 21.22 | PASS | | |
| 7020.50† | 6619.25 | -827.28 | -2086.14 | 6533.69 | 6619.25 | 6124.08 | -4526.15 | 340.66 | 7367.17 | 356.01 | 7011.16 | 20.92 | PASS | | |
| 7120.50† | 6712.70 | -840.41 | -2119.23 | 6627.19 | 6712.70 | 6124.08 | -4526.15 | 340.94 | 7368.67 | 361.04 | 7007.64 | 20.63 | PASS | | |
| 7220.50† | 6806.15 | -853.53 | -2152.32 | 6720.70 | 6806.15 | 6124.08 | -4526.15 | 341.21 | 7370.35 | 366.06 | 7004.29 | 20.34 | PASS | | |
| 7320.50† | 6899.60 | -866.65 | -2185.40 | 6814.21 | 6899.60 | 6124.08 | -4526.15 | 341.49 | 7372.20 | 371.09 | 7001.11 | 20.07 | PASS | | |
| 7341.07 | 6918.82 | -869.35 | -2192.21 | 6833.44 | 6918.82 | 6124.08 | -4526.15 | 341.54 | 7372.61 | 372.13 | 7000.48 | 20.02 | PASS | | |
| 7420.50† | 6993.49 | -874.29 | -2218.65 | 6908.16 | 6993.49 | 6124.08 | -4526.15 | 341.75 | 7368.97 | 376.15 | 6992.82 | 19.79 | PASS | | |
| 7520.50† | 7087.21 | -864.88 | -2251.87 | 7001.93 | 7087.21 | 6124.08 | -4526.15 | 341.98 | 7349.69 | 381.22 | 6968.47 | 19.47 | PASS | | |
| 7620.50† | 7177.96 | -838.35 | -2284.05 | 7092.74 | 7177.96 | 6124.08 | -4526.15 | 342.15 | 7314.54 | 386.10 | 6928.44 | 19.13 | PASS | | |
| 7720.50† | 7262.97 | -795.51 | -2314.23 | 7177.81 | 7262.97 | 6124.08 | -4526.15 | 342.27 | 7264.52 | 390.63 | 6873.90 | 18.78 | PASS | | |
| 7820.50† | 7339.68 | -737.65 | -2341.49 | 7254.56 | 7339.68 | 6124.08 | -4526.15 | 342.34 | 7201.12 | 394.67 | 6806.44 | 18.42 | PASS | | |
| 7920.50† | 7405.75 | -666.53 | -2364.99 | 7320.67 | 7405.75 | 6124.08 | -4526.15 | 342.35 | 7126.22 | 398.12 | 6728.10 | 18.07 | PASS | | |
| 8020.50† | 7459.16 | -584.32 | -2384.03 | 7374.11 | 7459.16 | 6124.08 | -4526.15 | 342.29 | 7042.11 | 400.85 | 6641.26 | 17.73 | PASS | | |
| 8120.50† | 7498.30 | -493.50 | -2398.02 | 7413.28 | 7498.30 | 6124.08 | -4526.15 | 342.17 | 6951.36 | 402.79 | 6548.57 | 17.42 | PASS | | |
| 8220.50† | 7521.99 | -396.85 | -2406.55 | 7436.98 | 7521.99 | 6124.08 | -4526.15 | 341.99 | 6856.77 | 403.89 | 6452.88 | 17.14 | PASS | | |
| 8315.56 | 7529.50 | -302.24 | -2409.34 | 7444.49 | 7529.50 | 6124.08 | -4526.15 | 341.77 | 6765.98 | 404.14 | 6361.84 | 16.90 | PASS | | |
| 8320.50† | 7529.51 | -297.30 | -2409.35 | 7444.50 | 7529.51 | 6124.08 | -4526.15 | 341.76 | 6761.29 | 404.13 | 6357.16 | 16.89 | PASS | | |
| 8420.50† | 7529.61 | -197.30 | -2409.53 | 7444.60 | 7529.61 | 6124.08 | -4526.15 | 341.49 | 6666.33 | 403.98 | 6262.36 | 16.66 | PASS | | |
| 8520.50† | 7529.71 | -97.30 | -2409.71 | 7444.71 | 7529.71 | 6124.08 | -4526.15 | 341.21 | 6571.53 | 403.82 | 6167.71 | 16.43 | PASS | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 107 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. STRAWDER 1 AWB Offset Wellpath: EX. STRAWDER 1 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#02 EX. STRAWDER 1 (1590'FSL & 1600'FWL, SI) Well: EX. STRAWDER 1 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 8620.50† | 7529.82 | 2.70 | -2409.88 | 7444.81 | 7529.82 | 6124.08 | -4526.15 | 340.93 | 6476.88 | 403.66 | 6073.22 | 16.20 | PASS |
| 8720.50† | 7529.92 | 102.70 | -2410.06 | 7444.91 | 7529.92 | 6124.08 | -4526.15 | 340.64 | 6382.39 | 403.50 | 5978.89 | 15.97 | PASS |
| 8820.50† | 7530.02 | 202.70 | -2410.24 | 7445.02 | 7530.02 | 6124.08 | -4526.15 | 340.34 | 6288.08 | 403.33 | 5884.74 | 15.74 | PASS |
| 8920.50† | 7530.13 | 302.70 | -2410.42 | 7445.12 | 7530.13 | 6124.08 | -4526.15 | 340.03 | 6193.94 | 403.17 | 5790.77 | 15.51 | PASS |
| 9020.50† | 7530.23 | 402.70 | -2410.59 | 7445.23 | 7530.23 | 6124.08 | -4526.15 | 339.71 | 6099.99 | 403.00 | 5696.99 | 15.28 | PASS |
| 9120.50† | 7530.33 | 502.70 | -2410.77 | 7445.33 | 7530.33 | 6124.08 | -4526.15 | 339.38 | 6006.23 | 402.82 | 5603.41 | 15.05 | PASS |
| 9220.50† | 7530.44 | 602.70 | -2410.95 | 7445.43 | 7530.44 | 6124.08 | -4526.15 | 339.04 | 5912.68 | 402.65 | 5510.03 | 14.82 | PASS |
| 9320.50† | 7530.54 | 702.70 | -2411.13 | 7445.54 | 7530.54 | 6124.08 | -4526.15 | 338.69 | 5819.34 | 402.47 | 5416.87 | 14.59 | PASS |
| 9420.50† | 7530.64 | 802.69 | -2411.31 | 7445.64 | 7530.64 | 6124.08 | -4526.15 | 338.33 | 5726.23 | 402.30 | 5323.94 | 14.37 | PASS |
| 9520.50† | 7530.75 | 902.69 | -2411.48 | 7445.74 | 7530.75 | 6124.08 | -4526.15 | 337.95 | 5633.36 | 402.12 | 5231.24 | 14.14 | PASS |
| 9620.50† | 7530.85 | 1002.69 | -2411.66 | 7445.85 | 7530.85 | 6124.08 | -4526.15 | 337.57 | 5540.73 | 401.94 | 5138.79 | 13.91 | PASS |
| 9720.50† | 7530.96 | 1102.69 | -2411.84 | 7445.95 | 7530.96 | 6124.08 | -4526.15 | 337.17 | 5448.36 | 401.75 | 5046.61 | 13.69 | PASS |
| 9820.50† | 7531.06 | 1202.69 | -2412.02 | 7446.05 | 7531.06 | 6124.08 | -4526.15 | 336.75 | 5356.27 | 401.57 | 4954.70 | 13.46 | PASS |
| 9920.50† | 7531.16 | 1302.69 | -2412.19 | 7446.16 | 7531.16 | 6124.08 | -4526.15 | 336.33 | 5264.47 | 401.38 | 4863.08 | 13.24 | PASS |
| 10020.50† | 7531.27 | 1402.69 | -2412.37 | 7446.26 | 7531.27 | 6124.08 | -4526.15 | 335.88 | 5172.97 | 401.20 | 4771.77 | 13.01 | PASS |
| 10120.50† | 7531.37 | 1502.69 | -2412.55 | 7446.37 | 7531.37 | 6124.08 | -4526.15 | 335.42 | 5081.79 | 401.01 | 4680.78 | 12.79 | PASS |
| 10220.50† | 7531.47 | 1602.69 | -2412.73 | 7446.47 | 7531.47 | 6124.08 | -4526.15 | 334.95 | 4990.94 | 400.82 | 4590.12 | 12.57 | PASS |
| 10320.50† | 7531.58 | 1702.69 | -2412.90 | 7446.57 | 7531.58 | 6124.08 | -4526.15 | 334.45 | 4900.46 | 400.64 | 4499.82 | 12.34 | PASS |
| 10420.50† | 7531.68 | 1802.69 | -2413.08 | 7446.68 | 7531.68 | 6124.08 | -4526.15 | 333.94 | 4810.35 | 400.45 | 4409.90 | 12.12 | PASS |
| 10520.50† | 7531.78 | 1902.69 | -2413.26 | 7446.78 | 7531.78 | 6124.08 | -4526.15 | 333.41 | 4720.64 | 400.27 | 4320.37 | 11.90 | PASS |
| 10620.50† | 7531.89 | 2002.69 | -2413.44 | 7446.88 | 7531.89 | 6124.08 | -4526.15 | 332.86 | 4631.35 | 400.09 | 4231.26 | 11.68 | PASS |
| 10720.50† | 7531.99 | 2102.69 | -2413.62 | 7446.99 | 7531.99 | 6124.08 | -4526.15 | 332.29 | 4542.51 | 399.91 | 4142.60 | 11.46 | PASS |
| 10820.50† | 7532.09 | 2202.69 | -2413.79 | 7447.09 | 7532.09 | 6124.08 | -4526.15 | 331.69 | 4454.14 | 399.74 | 4054.40 | 11.24 | PASS |
| 10920.50† | 7532.20 | 2302.69 | -2413.97 | 7447.19 | 7532.20 | 6124.08 | -4526.15 | 331.07 | 4366.27 | 399.57 | 3966.70 | 11.03 | PASS |
| 11020.50† | 7532.30 | 2402.69 | -2414.15 | 7447.30 | 7532.30 | 6124.08 | -4526.15 | 330.42 | 4278.94 | 399.41 | 3879.53 | 10.81 | PASS |
| 11120.50† | 7532.41 | 2502.69 | -2414.33 | 7447.40 | 7532.41 | 6124.08 | -4526.15 | 329.75 | 4192.17 | 399.26 | 3792.91 | 10.60 | PASS |
| 11220.50† | 7532.51 | 2602.69 | -2414.50 | 7447.51 | 7532.51 | 6124.08 | -4526.15 | 329.05 | 4106.00 | 399.11 | 3706.89 | 10.38 | PASS |
| 11320.50† | 7532.61 | 2702.69 | -2414.68 | 7447.61 | 7532.61 | 6124.08 | -4526.15 | 328.32 | 4020.48 | 398.98 | 3621.49 | 10.17 | PASS |
| 11420.50† | 7532.72 | 2802.69 | -2414.86 | 7447.71 | 7532.72 | 6124.08 | -4526.15 | 327.56 | 3935.63 | 398.86 | 3536.77 | 9.96 | PASS |
| 11520.50† | 7532.82 | 2902.69 | -2415.04 | 7447.82 | 7532.82 | 6124.08 | -4526.15 | 326.76 | 3851.52 | 398.76 | 3452.75 | 9.75 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 108 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. STRAWDER 1 AWB Offset Wellpath: EX. STRAWDER 1 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#02 EX. STRAWDER 1 (1590'FSL & 1600'FWL, SI) Well: EX. STRAWDER 1 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | |
| 11620.50† | 7532.92 | 3002.69 | -2415.21 | 7447.92 | 7532.92 | 6124.08 | -4526.15 | 325.93 | 3768.18 | 398.68 | 3369.50 | 9.54 | PASS | | |
| 11720.50† | 7533.03 | 3102.69 | -2415.39 | 7448.02 | 7533.03 | 6124.08 | -4526.15 | 325.06 | 3685.66 | 398.62 | 3287.05 | 9.33 | PASS | | |
| 11820.50† | 7533.13 | 3202.69 | -2415.57 | 7448.13 | 7533.13 | 6124.08 | -4526.15 | 324.15 | 3604.04 | 398.58 | 3205.46 | 9.12 | PASS | | |
| 11920.50† | 7533.23 | 3302.69 | -2415.75 | 7448.23 | 7533.23 | 6124.08 | -4526.15 | 323.20 | 3523.36 | 398.57 | 3124.79 | 8.92 | PASS | | |
| 12020.50† | 7533.34 | 3402.69 | -2415.92 | 7448.33 | 7533.34 | 6124.08 | -4526.15 | 322.21 | 3443.70 | 398.60 | 3045.10 | 8.72 | PASS | | |
| 12120.50† | 7533.44 | 3502.69 | -2416.10 | 7448.44 | 7533.44 | 6124.08 | -4526.15 | 321.17 | 3365.12 | 398.66 | 2966.46 | 8.52 | PASS | | |
| 12220.50† | 7533.55 | 3602.69 | -2416.28 | 7448.54 | 7533.55 | 6124.08 | -4526.15 | 320.08 | 3287.70 | 398.76 | 2888.94 | 8.32 | PASS | | |
| 12320.50† | 7533.65 | 3702.69 | -2416.46 | 7448.65 | 7533.65 | 6124.08 | -4526.15 | 318.94 | 3211.53 | 398.92 | 2812.62 | 8.12 | PASS | | |
| 12420.50† | 7533.75 | 3802.69 | -2416.64 | 7448.75 | 7533.75 | 6124.08 | -4526.15 | 317.74 | 3136.71 | 399.13 | 2737.58 | 7.93 | PASS | | |
| 12520.50† | 7533.86 | 3902.69 | -2416.81 | 7448.85 | 7533.86 | 6124.08 | -4526.15 | 316.48 | 3063.32 | 399.40 | 2663.91 | 7.74 | PASS | | |
| 12620.50† | 7533.96 | 4002.69 | -2416.99 | 7448.96 | 7533.96 | 6124.08 | -4526.15 | 315.17 | 2991.47 | 399.75 | 2591.72 | 7.55 | PASS | | |
| 12720.50† | 7534.06 | 4102.69 | -2417.17 | 7449.06 | 7534.06 | 6124.08 | -4526.15 | 313.79 | 2921.27 | 400.17 | 2521.11 | 7.36 | PASS | | |
| 12820.50† | 7534.17 | 4202.69 | -2417.35 | 7449.16 | 7534.17 | 6124.08 | -4526.15 | 312.34 | 2852.86 | 400.68 | 2452.18 | 7.18 | PASS | | |
| 12920.50† | 7534.27 | 4302.69 | -2417.52 | 7449.27 | 7534.27 | 6124.08 | -4526.15 | 310.82 | 2786.36 | 401.28 | 2385.07 | 7.00 | PASS | | |
| 13020.50† | 7534.37 | 4402.69 | -2417.70 | 7449.37 | 7534.37 | 6124.08 | -4526.15 | 309.23 | 2721.90 | 402.00 | 2319.91 | 6.83 | PASS | | |
| 13120.50† | 7534.48 | 4502.69 | -2417.88 | 7449.48 | 7534.48 | 6124.08 | -4526.15 | 307.56 | 2659.65 | 402.82 | 2256.83 | 6.66 | PASS | | |
| 13199.97 | 7534.56 | 4582.16 | -2418.02 | 7449.56 | 7534.56 | 6124.08 | -4526.15 | 306.18 | 2611.85 | 403.57 | 2208.28 | 6.53 | PASS | | |
| 13220.50† | 7534.58 | 4602.69 | -2418.13 | 7449.58 | 7534.58 | 6124.08 | -4526.15 | 305.82 | 2599.69 | 403.77 | 2195.92 | 6.49 | PASS | | |
| 13320.50† | 7534.68 | 4702.65 | -2420.77 | 7449.68 | 7534.68 | 6124.08 | -4526.15 | 304.02 | 2540.30 | 404.83 | 2135.47 | 6.33 | PASS | | |
| 13420.50† | 7534.79 | 4802.45 | -2426.90 | 7449.79 | 7534.79 | 6124.08 | -4526.15 | 302.19 | 2480.64 | 406.01 | 2074.64 | 6.16 | PASS | | |
| 13476.50 | 7534.85 | 4858.23 | -2431.85 | 7449.84 | 7534.85 | 6124.08 | -4526.15 | 301.15 | 2447.14 | 406.71 | 2040.43 | 6.07 | PASS | | |
| 13520.50† | 7534.89 | 4902.02 | -2436.16 | 7449.89 | 7534.89 | 6124.08 | -4526.15 | 300.32 | 2421.05 | 407.29 | 2013.76 | 5.99 | PASS | | |
| 13620.50† | 7534.99 | 5001.54 | -2445.98 | 7449.99 | 7534.99 | 6124.08 | -4526.15 | 298.35 | 2363.73 | 408.73 | 1955.01 | 5.83 | PASS | | |
| 13720.50† | 7535.10 | 5101.06 | -2455.79 | 7450.09 | 7535.10 | 6124.08 | -4526.15 | 296.30 | 2309.32 | 410.32 | 1899.00 | 5.67 | PASS | | |
| 13820.50† | 7535.20 | 5200.57 | -2465.61 | 7450.20 | 7535.20 | 6124.08 | -4526.15 | 294.14 | 2258.03 | 412.08 | 1845.95 | 5.52 | PASS | | |
| 13920.50† | 7535.30 | 5300.09 | -2475.42 | 7450.30 | 7535.30 | 6124.08 | -4526.15 | 291.89 | 2210.08 | 414.00 | 1796.08 | 5.38 | PASS | | |
| 14020.50† | 7535.40 | 5399.61 | -2485.24 | 7450.40 | 7535.40 | 6124.08 | -4526.15 | 289.54 | 2165.69 | 416.08 | 1749.61 | 5.25 | PASS | | |
| 14120.50† | 7535.51 | 5499.12 | -2495.05 | 7450.50 | 7535.51 | 6124.08 | -4526.15 | 287.10 | 2125.07 | 418.31 | 1706.76 | 5.12 | PASS | | |
| 14220.50† | 7535.61 | 5598.64 | -2504.87 | 7450.61 | 7535.61 | 6124.08 | -4526.15 | 284.57 | 2088.46 | 420.68 | 1667.78 | 5.00 | PASS | | |
| 14221.87 | 7535.61 | 5600.00 | -2505.00 | 7450.61 | 7535.61 | 6124.08 | -4526.15 | 284.54 | 2087.99 | 420.72 | 1667.28 | 5.00 | PASS | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 109 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. STRAWDER 1 AWB Offset Wellpath: EX. STRAWDER 1 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#02 EX. STRAWDER 1 (1590'FSL & 1600'FWL, SI) Well: EX. STRAWDER 1 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | |
| 14320.50† | 7535.71 | 5698.31 | -2512.99 | 7450.71 | 7535.71 | 6124.08 | -4526.15 | 281.94 | 2057.70 | 423.18 | 1634.52 | 4.90 | PASS | |
| 14420.50† | 7535.81 | 5798.19 | -2517.63 | 7450.81 | 7535.81 | 6124.08 | -4526.15 | 279.22 | 2034.79 | 425.79 | 1609.00 | 4.81 | PASS | |
| 14520.50† | 7535.92 | 5898.18 | -2518.78 | 7450.92 | 7535.92 | 6124.08 | -4526.15 | 276.42 | 2020.04 | 428.45 | 1591.59 | 4.75 | PASS | |
| 14581.38 | 7535.98 | 5959.05 | -2517.77 | 7450.98 | 7535.98 | 6124.08 | -4526.15 | 274.70 | 2015.15 | 430.07 | 1585.08 | 4.72 | PASS | |
| 14620.50† | 7536.02 | 5998.16 | -2516.71 | 7451.02 | 7536.02 | 6124.08 | -4526.15 | 273.59 | 2013.39 | 431.10 | 1582.29 | 4.70 | PASS | |
| 14691.74† | 7536.09 | 6069.37 | -2514.77 | 7451.10 | 7536.10 | 6124.08 | -4526.15 | 271.56 | 2012.12 | 432.96 | 1579.16 | 4.68 | PASS | |
| 14720.50† | 7536.12 | 6098.12 | -2513.99 | 7451.12 | 7536.12 | 6124.08 | -4526.15 | 270.74 | 2012.33 | 433.70 | 1578.63 | 4.67 | PASS | |
| 14820.50† | 7536.23 | 6198.08 | -2511.27 | 7451.23 | 7536.23 | 6124.08 | -4526.15 | 267.90 | 2016.24 | 436.22 | 1580.02 | 4.66 | PASS | |
| 14912.17† | 7536.32 | 6289.72 | -2508.78 | 7451.32 | 7536.32 | 6124.08 | -4526.15 | 265.31 | 2024.16 | 438.43 | 1585.74 | 4.65 | PASS | |
| 14920.50† | 7536.33 | 6298.05 | -2508.55 | 7451.33 | 7536.33 | 6124.08 | -4526.15 | 265.07 | 2025.09 | 438.62 | 1586.47 | 4.65 | PASS | |
| 15020.50† | 7536.43 | 6398.01 | -2505.83 | 7451.43 | 7536.43 | 6124.08 | -4526.15 | 262.28 | 2038.80 | 440.87 | 1597.93 | 4.66 | PASS | |
| 15120.50† | 7536.54 | 6497.97 | -2503.11 | 7451.54 | 7536.54 | 6124.08 | -4526.15 | 259.53 | 2057.30 | 442.95 | 1614.35 | 4.68 | PASS | |
| 15220.50† | 7536.64 | 6597.93 | -2500.40 | 7451.64 | 7536.64 | 6124.08 | -4526.15 | 256.83 | 2080.44 | 444.83 | 1635.61 | 4.71 | PASS | |
| 15320.50† | 7536.74 | 6697.90 | -2497.68 | 7451.74 | 7536.74 | 6124.08 | -4526.15 | 254.21 | 2108.07 | 446.51 | 1661.56 | 4.75 | PASS | |
| 15420.50† | 7536.85 | 6797.86 | -2494.96 | 7451.85 | 7536.85 | 6124.08 | -4526.15 | 251.65 | 2140.03 | 447.99 | 1692.04 | 4.81 | PASS | |
| 15520.50† | 7536.95 | 6897.82 | -2492.24 | 7451.95 | 7536.95 | 6124.08 | -4526.15 | 249.17 | 2176.12 | 449.26 | 1726.86 | 4.88 | PASS | |
| 15620.50† | 7537.05 | 6997.79 | -2489.52 | 7452.05 | 7537.05 | 6124.08 | -4526.15 | 246.78 | 2216.13 | 450.33 | 1765.80 | 4.96 | PASS | |
| 15720.50† | 7537.16 | 7097.75 | -2486.80 | 7452.16 | 7537.16 | 6124.08 | -4526.15 | 244.48 | 2259.86 | 451.21 | 1808.65 | 5.04 | PASS | |
| 15820.50† | 7537.26 | 7197.71 | -2484.08 | 7452.26 | 7537.26 | 6124.08 | -4526.15 | 242.27 | 2307.10 | 451.91 | 1855.20 | 5.14 | PASS | |
| 15920.50† | 7537.36 | 7297.68 | -2481.36 | 7452.36 | 7537.36 | 6124.08 | -4526.15 | 240.15 | 2357.64 | 452.44 | 1905.20 | 5.25 | PASS | |
| 16020.50† | 7537.47 | 7397.64 | -2478.64 | 7452.47 | 7537.47 | 6124.08 | -4526.15 | 238.12 | 2411.27 | 452.83 | 1958.44 | 5.36 | PASS | |
| 16120.50† | 7537.57 | 7497.60 | -2475.93 | 7452.57 | 7537.57 | 6124.08 | -4526.15 | 236.18 | 2467.79 | 453.08 | 2014.71 | 5.49 | PASS | |
| 16220.50† | 7537.68 | 7597.56 | -2473.21 | 7452.67 | 7537.68 | 6124.08 | -4526.15 | 234.33 | 2527.00 | 453.22 | 2073.79 | 5.62 | PASS | |
| 16320.50† | 7537.78 | 7697.53 | -2470.49 | 7452.78 | 7537.78 | 6124.08 | -4526.15 | 232.57 | 2588.72 | 453.24 | 2135.48 | 5.75 | PASS | |
| 16420.50† | 7537.88 | 7797.49 | -2467.77 | 7452.88 | 7537.88 | 6124.08 | -4526.15 | 230.89 | 2652.78 | 453.18 | 2199.59 | 5.90 | PASS | |
| 16520.50† | 7537.99 | 7897.45 | -2465.05 | 7452.98 | 7537.99 | 6124.08 | -4526.15 | 229.29 | 2719.00 | 453.05 | 2265.96 | 6.05 | PASS | |
| 16620.50† | 7538.09 | 7997.42 | -2462.33 | 7453.09 | 7538.09 | 6124.08 | -4526.15 | 227.77 | 2787.25 | 452.84 | 2334.40 | 6.20 | PASS | |
| 16720.50† | 7538.19 | 8097.38 | -2459.61 | 7453.19 | 7538.19 | 6124.08 | -4526.15 | 226.32 | 2857.36 | 452.59 | 2404.77 | 6.36 | PASS | |
| 16820.50† | 7538.30 | 8197.34 | -2456.89 | 7453.30 | 7538.30 | 6124.08 | -4526.15 | 224.95 | 2929.20 | 452.28 | 2476.92 | 6.53 | PASS | |
| 16920.50† | 7538.40 | 8297.31 | -2454.17 | 7453.40 | 7538.40 | 6124.08 | -4526.15 | 223.63 | 3002.66 | 451.94 | 2550.72 | 6.69 | PASS | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 110 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: EX. STRAWDER 1 AWB Offset Wellpath: EX. STRAWDER 1 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#02 EX. STRAWDER 1 (1590'FSL & 1600'FWL, SI) Well: EX. STRAWDER 1 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 17020.50† | 7538.50 | 8397.27 | -2451.46 | 7453.50 | 7538.50 | 6124.08 | -4526.15 | 222.39 | 3077.62 | 451.58 | 2626.04 | 6.87 | PASS |
| 17120.50† | 7538.61 | 8497.23 | -2448.74 | 7453.61 | 7538.61 | 6124.08 | -4526.15 | 221.20 | 3153.96 | 451.18 | 2702.78 | 7.04 | PASS |
| 17220.50† | 7538.71 | 8597.19 | -2446.02 | 7453.71 | 7538.71 | 6124.08 | -4526.15 | 220.07 | 3231.60 | 450.77 | 2780.83 | 7.22 | PASS |
| 17320.50† | 7538.81 | 8697.16 | -2443.30 | 7453.81 | 7538.81 | 6124.08 | -4526.15 | 218.99 | 3310.44 | 450.35 | 2860.09 | 7.41 | PASS |
| 17420.50† | 7538.92 | 8797.12 | -2440.58 | 7453.92 | 7538.92 | 6124.08 | -4526.15 | 217.96 | 3390.39 | 449.92 | 2940.47 | 7.59 | PASS |
| 17520.50† | 7539.02 | 8897.08 | -2437.86 | 7454.02 | 7539.02 | 6124.08 | -4526.15 | 216.98 | 3471.38 | 449.48 | 3021.90 | 7.78 | PASS |
| 17620.50† | 7539.12 | 8997.05 | -2435.14 | 7454.12 | 7539.12 | 6124.08 | -4526.15 | 216.05 | 3553.34 | 449.04 | 3104.30 | 7.98 | PASS |
| 17720.50† | 7539.23 | 9097.01 | -2432.42 | 7454.23 | 7539.23 | 6124.08 | -4526.15 | 215.16 | 3636.21 | 448.60 | 3187.61 | 8.17 | PASS |
| 17820.50† | 7539.33 | 9196.97 | -2429.70 | 7454.33 | 7539.33 | 6124.08 | -4526.15 | 214.30 | 3719.91 | 448.16 | 3271.76 | 8.37 | PASS |
| 17920.50† | 7539.43 | 9296.94 | -2426.99 | 7454.43 | 7539.43 | 6124.08 | -4526.15 | 213.49 | 3804.40 | 447.72 | 3356.68 | 8.56 | PASS |
| 17985.90 | 7539.50 | 9362.31 | -2425.21 | 7454.50 | 7539.50 | 6124.08 | -4526.15 | 212.98 | 3860.06 | 447.44 | 3412.62 | 8.70 | PASS |

POSITIONAL UNCERTAINTY - Offset Wellbore: EX. STRAWDER 1 AWB Offset Wellpath: EX. STRAWDER 1 AWP

| | | | | |
|-----------------------------------|------------|---------|----------|---------|
| Slot Surface Uncertainty @1SD | Horizontal | 0.100ft | Vertical | 1.000ft |
| Facility Surface Uncertainty @1SD | Horizontal | 8.200ft | Vertical | 3.000ft |

WELLPATH COMPOSITION - Offset Wellbore: EX. STRAWDER 1 AWB Offset Wellpath: EX. STRAWDER 1 AWP

| Start MD [ft] | End MD [ft] | Positional Uncertainty Model | Log Name/Comment | Wellbore | Survey Date |
|---------------|-------------|---|--|--------------------|-------------|
| 0.00 | 8020.00 | BH Drift Indicator - Inclination Only (Actual Survey) | ASSUMED VERTICAL TO TD FROM COGCG <8020> | EX. STRAWDER 1 AWB | |

OFFSET WELLPATH REFERENCE - Offset Wellbore: EX. STRAWDER 1 AWB Offset Wellpath: EX. STRAWDER 1 AWP

| | |
|--|---|
| MD Reference: Rig on SLOT#02 EX. STRAWDER 1 (1590'FSL & 1600'FWL, SI) (RT) | Offset TVD & local coordinates use Reference Wellpath settings (See WELLPATH DATUM on page 1 of this report) |
| Ellipse Start MD | 0.00ft |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 111 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: GLEN YOUNG 2 AWB Offset Wellpath: GLEN YOUNG 2 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W | | Slot: SLOT#2 EX. GLEN YOUNG 2 (1540'FNL & 1740'FWL, PA) | | Well: GLEN YOUNG 2 | | Threshold Value=1.00 | | ↑ = interpolated, ‡ = extrapolated station | | | | | | | |
|----------------------------|--------------|---|---------------|--------------------|-----------------|----------------------|------------------|--|---------------------|----------------|----------------------|-----------|-------------|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | |
| 20.50 | 20.50 | 0.00 | 0.00 | -20.50 | 107.00 | 8258.42 | -4412.34 | 331.89 | 9363.64 | 33.25 | 9330.39 | 319.77 | PASS | | |
| 120.50† | 120.50 | 0.00 | 0.00 | -7.00 | 120.50 | 8258.42 | -4412.34 | 331.89 | 9363.24 | 33.26 | 9329.98 | 319.67 | PASS | | |
| 200.00 | 200.00 | 0.00 | 0.00 | 72.50 | 200.00 | 8258.42 | -4412.34 | 331.89 | 9363.24 | 43.86 | 9319.38 | 220.72 | PASS | | |
| 220.50† | 220.50 | -0.03 | -0.07 | 93.00 | 220.50 | 8258.42 | -4412.34 | 331.89 | 9363.23 | 44.27 | 9318.97 | 218.62 | PASS | | |
| 320.50† | 320.46 | -0.93 | -2.36 | 192.96 | 320.46 | 8258.42 | -4412.34 | 331.90 | 9362.96 | 46.31 | 9316.65 | 208.65 | PASS | | |
| 420.50† | 420.28 | -3.13 | -7.88 | 292.78 | 420.28 | 8258.42 | -4412.34 | 331.94 | 9362.29 | 48.43 | 9313.86 | 199.23 | PASS | | |
| 520.50† | 519.83 | -6.60 | -16.65 | 392.33 | 519.83 | 8258.42 | -4412.34 | 331.99 | 9361.24 | 50.61 | 9310.63 | 190.36 | PASS | | |
| 620.50† | 618.99 | -11.36 | -28.64 | 491.49 | 618.99 | 8258.42 | -4412.34 | 332.07 | 9359.81 | 52.84 | 9306.97 | 182.06 | PASS | | |
| 720.50† | 717.64 | -17.38 | -43.83 | 590.14 | 717.64 | 8258.42 | -4412.34 | 332.17 | 9358.03 | 55.12 | 9302.91 | 174.30 | PASS | | |
| 820.50† | 815.66 | -24.68 | -62.22 | 688.16 | 815.66 | 8258.42 | -4412.34 | 332.29 | 9355.92 | 57.44 | 9298.48 | 167.06 | PASS | | |
| 920.50† | 912.93 | -33.22 | -83.78 | 785.43 | 912.93 | 8258.42 | -4412.34 | 332.43 | 9353.49 | 59.78 | 9293.71 | 160.31 | PASS | | |
| 1020.50† | 1009.33 | -43.02 | -108.48 | 881.83 | 1009.33 | 8258.42 | -4412.34 | 332.60 | 9350.78 | 62.15 | 9288.63 | 154.01 | PASS | | |
| 1120.50† | 1104.74 | -54.05 | -136.29 | 977.24 | 1104.74 | 8258.42 | -4412.34 | 332.78 | 9347.82 | 64.54 | 9283.28 | 148.13 | PASS | | |
| 1220.50† | 1199.05 | -66.30 | -167.18 | 1071.55 | 1199.05 | 8258.42 | -4412.34 | 332.98 | 9344.64 | 66.94 | 9277.70 | 142.64 | PASS | | |
| 1242.54 | 1219.68 | -69.16 | -174.40 | 1092.18 | 1219.68 | 8258.42 | -4412.34 | 333.03 | 9343.92 | 67.47 | 9276.44 | 141.48 | PASS | | |
| 1320.50† | 1292.54 | -79.39 | -200.20 | 1165.04 | 1292.54 | 8258.42 | -4412.34 | 333.20 | 9341.37 | 69.37 | 9272.01 | 137.50 | PASS | | |
| 1420.50† | 1385.99 | -92.51 | -233.28 | 1258.49 | 1385.99 | 8258.42 | -4412.34 | 333.42 | 9338.23 | 71.82 | 9266.41 | 132.66 | PASS | | |
| 1520.50† | 1479.44 | -105.63 | -266.37 | 1351.94 | 1479.44 | 8258.42 | -4412.34 | 333.63 | 9335.23 | 74.25 | 9260.98 | 128.19 | PASS | | |
| 1620.50† | 1572.89 | -118.75 | -299.46 | 1445.39 | 1572.89 | 8258.42 | -4412.34 | 333.85 | 9332.36 | 76.67 | 9255.69 | 124.04 | PASS | | |
| 1720.50† | 1666.34 | -131.87 | -332.54 | 1538.84 | 1666.34 | 8258.42 | -4412.34 | 334.07 | 9329.62 | 79.11 | 9250.51 | 120.11 | PASS | | |
| 1820.50† | 1759.79 | -144.99 | -365.63 | 1632.29 | 1759.79 | 8258.42 | -4412.34 | 334.29 | 9327.02 | 81.58 | 9245.44 | 116.37 | PASS | | |
| 1920.50† | 1853.24 | -158.12 | -398.72 | 1725.74 | 1853.24 | 8258.42 | -4412.34 | 334.51 | 9324.55 | 84.07 | 9240.48 | 112.83 | PASS | | |
| 2020.50† | 1946.69 | -171.24 | -431.80 | 1819.19 | 1946.69 | 8258.42 | -4412.34 | 334.72 | 9322.22 | 86.59 | 9235.64 | 109.47 | PASS | | |
| 2120.50† | 2040.14 | -184.36 | -464.89 | 1912.64 | 2040.14 | 8258.42 | -4412.34 | 334.94 | 9320.03 | 89.12 | 9230.90 | 106.28 | PASS | | |
| 2220.50† | 2133.59 | -197.48 | -497.98 | 2006.09 | 2133.59 | 8258.42 | -4412.34 | 335.16 | 9317.97 | 91.68 | 9226.29 | 103.25 | PASS | | |
| 2320.50† | 2227.05 | -210.60 | -531.06 | 2099.55 | 2227.05 | 8258.42 | -4412.34 | 335.38 | 9316.04 | 94.25 | 9221.79 | 100.36 | PASS | | |
| 2420.50† | 2320.50 | -223.72 | -564.15 | 2193.00 | 2320.50 | 8258.42 | -4412.34 | 335.60 | 9314.25 | 96.84 | 9217.42 | 97.62 | PASS | | |
| 2520.50† | 2413.95 | -236.84 | -597.24 | 2286.45 | 2413.95 | 8258.42 | -4412.34 | 335.82 | 9312.60 | 99.44 | 9213.16 | 95.01 | PASS | | |
| 2620.50† | 2507.40 | -249.96 | -630.32 | 2379.90 | 2507.40 | 8258.42 | -4412.34 | 336.04 | 9311.08 | 102.06 | 9209.03 | 92.53 | PASS | | |
| 2720.50† | 2600.85 | -263.08 | -663.41 | 2473.35 | 2600.85 | 8258.42 | -4412.34 | 336.25 | 9309.70 | 104.69 | 9205.02 | 90.16 | PASS | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 112 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: GLEN YOUNG 2 AWP Offset Wellpath: GLEN YOUNG 2 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#2 EX. GLEN YOUNG 2 (1540'FNL & 1740'FWL, PA) Well: GLEN YOUNG 2 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 2820.50† | 2694.30 | -276.20 | -696.50 | 2566.80 | 2694.30 | 8258.42 | -4412.34 | 336.47 | 9308.46 | 107.33 | 9201.13 | 87.90 | PASS |
| 2920.50† | 2787.75 | -289.33 | -729.58 | 2660.25 | 2787.75 | 8258.42 | -4412.34 | 336.69 | 9307.35 | 109.98 | 9197.37 | 85.74 | PASS |
| 3020.50† | 2881.20 | -302.45 | -762.67 | 2753.70 | 2881.20 | 8258.42 | -4412.34 | 336.91 | 9306.37 | 112.64 | 9193.74 | 83.68 | PASS |
| 3120.50† | 2974.65 | -315.57 | -795.76 | 2847.15 | 2974.65 | 8258.42 | -4412.34 | 337.13 | 9305.53 | 115.31 | 9190.23 | 81.71 | PASS |
| 3220.50† | 3068.11 | -328.69 | -828.84 | 2940.61 | 3068.11 | 8258.42 | -4412.34 | 337.35 | 9304.83 | 117.98 | 9186.85 | 79.83 | PASS |
| 3320.50† | 3161.56 | -341.81 | -861.93 | 3034.06 | 3161.56 | 8258.42 | -4412.34 | 337.57 | 9304.27 | 120.67 | 9183.60 | 78.03 | PASS |
| 3420.50† | 3255.01 | -354.93 | -895.02 | 3127.51 | 3255.01 | 8258.42 | -4412.34 | 337.79 | 9303.84 | 123.36 | 9180.48 | 76.30 | PASS |
| 3520.50† | 3348.46 | -368.05 | -928.10 | 3220.96 | 3348.46 | 8258.42 | -4412.34 | 338.01 | 9303.55 | 126.06 | 9177.48 | 74.64 | PASS |
| 3620.50† | 3441.91 | -381.17 | -961.19 | 3314.41 | 3441.91 | 8258.42 | -4412.34 | 338.23 | 9303.39 | 128.77 | 9174.62 | 73.06 | PASS |
| 3720.50† | 3535.36 | -394.29 | -994.28 | 3407.86 | 3535.36 | 8258.42 | -4412.34 | 338.45 | 9303.37 | 131.48 | 9171.89 | 71.53 | PASS |
| 3820.50† | 3628.81 | -407.41 | -1027.37 | 3501.31 | 3628.81 | 8258.42 | -4412.34 | 338.66 | 9303.48 | 134.20 | 9169.28 | 70.07 | PASS |
| 3920.50† | 3722.26 | -420.53 | -1060.45 | 3594.76 | 3722.26 | 8258.42 | -4412.34 | 338.88 | 9303.73 | 136.92 | 9166.81 | 68.66 | PASS |
| 4020.50† | 3815.71 | -433.66 | -1093.54 | 3688.21 | 3815.71 | 8258.42 | -4412.34 | 339.10 | 9304.12 | 139.65 | 9164.47 | 67.31 | PASS |
| 4120.50† | 3909.17 | -446.78 | -1126.63 | 3781.67 | 3909.17 | 8258.42 | -4412.34 | 339.32 | 9304.65 | 142.38 | 9162.26 | 66.01 | PASS |
| 4220.50† | 4002.62 | -459.90 | -1159.71 | 3875.12 | 4002.62 | 8258.42 | -4412.34 | 339.54 | 9305.31 | 145.12 | 9160.19 | 64.76 | PASS |
| 4320.50† | 4096.07 | -473.02 | -1192.80 | 3968.57 | 4096.07 | 8258.42 | -4412.34 | 339.76 | 9306.10 | 147.86 | 9158.24 | 63.55 | PASS |
| 4420.50† | 4189.52 | -486.14 | -1225.89 | 4062.02 | 4189.52 | 8258.42 | -4412.34 | 339.98 | 9307.03 | 150.61 | 9156.43 | 62.39 | PASS |
| 4520.50† | 4282.97 | -499.26 | -1258.97 | 4155.47 | 4282.97 | 8258.42 | -4412.34 | 340.20 | 9308.10 | 153.35 | 9154.75 | 61.26 | PASS |
| 4620.50† | 4376.42 | -512.38 | -1292.06 | 4248.92 | 4376.42 | 8258.42 | -4412.34 | 340.42 | 9309.31 | 156.11 | 9153.20 | 60.18 | PASS |
| 4720.50† | 4469.87 | -525.50 | -1325.15 | 4342.37 | 4469.87 | 8258.42 | -4412.34 | 340.64 | 9310.65 | 158.86 | 9151.78 | 59.14 | PASS |
| 4820.50† | 4563.32 | -538.62 | -1358.23 | 4435.82 | 4563.32 | 8258.42 | -4412.34 | 340.85 | 9312.12 | 161.62 | 9150.50 | 58.13 | PASS |
| 4920.50† | 4656.77 | -551.74 | -1391.32 | 4529.27 | 4656.77 | 8258.42 | -4412.34 | 341.07 | 9313.73 | 164.38 | 9149.35 | 57.15 | PASS |
| 5020.50† | 4750.22 | -564.87 | -1424.41 | 4622.72 | 4750.22 | 8258.42 | -4412.34 | 341.29 | 9315.48 | 167.14 | 9148.34 | 56.21 | PASS |
| 5120.50† | 4843.68 | -577.99 | -1457.49 | 4716.18 | 4843.68 | 8258.42 | -4412.34 | 341.51 | 9317.36 | 169.91 | 9147.46 | 55.30 | PASS |
| 5220.50† | 4937.13 | -591.11 | -1490.58 | 4809.63 | 4937.13 | 8258.42 | -4412.34 | 341.73 | 9319.38 | 172.68 | 9146.71 | 54.42 | PASS |
| 5320.50† | 5030.58 | -604.23 | -1523.67 | 4903.08 | 5030.58 | 8258.42 | -4412.34 | 341.95 | 9321.54 | 175.45 | 9146.09 | 53.56 | PASS |
| 5420.50† | 5124.03 | -617.35 | -1556.75 | 4996.53 | 5124.03 | 8258.42 | -4412.34 | 342.17 | 9323.82 | 178.22 | 9145.61 | 52.74 | PASS |
| 5520.50† | 5217.48 | -630.47 | -1589.84 | 5089.98 | 5217.48 | 8258.42 | -4412.34 | 342.38 | 9326.25 | 180.99 | 9145.26 | 51.93 | PASS |
| 5620.50† | 5310.93 | -643.59 | -1622.93 | 5183.43 | 5310.93 | 8258.42 | -4412.34 | 342.60 | 9328.81 | 183.77 | 9145.04 | 51.16 | PASS |
| 5720.50† | 5404.38 | -656.71 | -1656.01 | 5276.88 | 5404.38 | 8258.42 | -4412.34 | 342.82 | 9331.50 | 186.54 | 9144.96 | 50.41 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 113 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: GLEN YOUNG 2 AWP Offset Wellpath: GLEN YOUNG 2 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W | | Slot: SLOT#2 EX. GLEN YOUNG 2 (1540'FNL & 1740'FWL, PA) | | Well: GLEN YOUNG 2 | | Threshold Value=1.00 | | ↑ = interpolated, ↓ = extrapolated station | | | | | | | |
|----------------------------|-----------------|---|------------------|--------------------|--------------------|----------------------|---------------------|--|---------------------------|----------------------|----------------------------|--------------|----------------|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | |
| 5820.50† | 5497.83 | -669.83 | -1689.10 | 5370.33 | 5497.83 | 8258.42 | -4412.34 | 343.04 | 9334.33 | 189.32 | 9145.01 | 49.67 | PASS | | |
| 5920.50† | 5591.28 | -682.95 | -1722.19 | 5463.78 | 5591.28 | 8258.42 | -4412.34 | 343.26 | 9337.30 | 192.10 | 9145.20 | 48.97 | PASS | | |
| 6020.50† | 5684.74 | -696.07 | -1755.27 | 5557.24 | 5684.74 | 8258.42 | -4412.34 | 343.47 | 9340.40 | 194.88 | 9145.51 | 48.28 | PASS | | |
| 6120.50† | 5778.19 | -709.20 | -1788.36 | 5650.69 | 5778.19 | 8258.42 | -4412.34 | 343.69 | 9343.63 | 197.67 | 9145.96 | 47.61 | PASS | | |
| 6220.50† | 5871.64 | -722.32 | -1821.45 | 5744.14 | 5871.64 | 8258.42 | -4412.34 | 343.91 | 9347.00 | 200.45 | 9146.55 | 46.96 | PASS | | |
| 6320.50† | 5965.09 | -735.44 | -1854.54 | 5837.59 | 5965.09 | 8258.42 | -4412.34 | 344.13 | 9350.50 | 203.24 | 9147.27 | 46.33 | PASS | | |
| 6420.50† | 6058.54 | -748.56 | -1887.62 | 5931.04 | 6058.54 | 8258.42 | -4412.34 | 344.34 | 9354.14 | 206.02 | 9148.12 | 45.72 | PASS | | |
| 6520.50† | 6151.99 | -761.68 | -1920.71 | 6024.49 | 6151.99 | 8258.42 | -4412.34 | 344.56 | 9357.91 | 208.81 | 9149.10 | 45.12 | PASS | | |
| 6620.50† | 6245.44 | -774.80 | -1953.80 | 6117.94 | 6245.44 | 8258.42 | -4412.34 | 344.78 | 9361.81 | 211.60 | 9150.22 | 44.54 | PASS | | |
| 6720.50† | 6338.89 | -787.92 | -1986.88 | 6211.39 | 6338.89 | 8258.42 | -4412.34 | 344.99 | 9365.85 | 214.39 | 9151.47 | 43.98 | PASS | | |
| 6820.50† | 6432.34 | -801.04 | -2019.97 | 6304.84 | 6432.34 | 8258.42 | -4412.34 | 345.21 | 9370.02 | 217.17 | 9152.85 | 43.43 | PASS | | |
| 6920.50† | 6525.80 | -814.16 | -2053.06 | 6398.30 | 6525.80 | 8258.42 | -4412.34 | 345.42 | 9374.33 | 219.96 | 9154.37 | 42.89 | PASS | | |
| 7020.50† | 6619.25 | -827.28 | -2086.14 | 6491.75 | 6619.25 | 8258.42 | -4412.34 | 345.64 | 9378.77 | 222.75 | 9156.01 | 42.37 | PASS | | |
| 7120.50† | 6712.70 | -840.41 | -2119.23 | 6585.20 | 6712.70 | 8258.42 | -4412.34 | 345.86 | 9383.34 | 225.55 | 9157.79 | 41.86 | PASS | | |
| 7220.50† | 6806.15 | -853.53 | -2152.32 | 6678.65 | 6806.15 | 8258.42 | -4412.34 | 346.07 | 9388.04 | 228.34 | 9159.71 | 41.37 | PASS | | |
| 7320.50† | 6899.60 | -866.65 | -2185.40 | 6772.10 | 6899.60 | 8258.42 | -4412.34 | 346.29 | 9392.88 | 231.13 | 9161.75 | 40.89 | PASS | | |
| 7341.07 | 6918.82 | -869.35 | -2192.21 | 6791.32 | 6918.82 | 8258.42 | -4412.34 | 346.33 | 9393.89 | 231.70 | 9162.19 | 40.79 | PASS | | |
| 7420.50† | 6993.49 | -874.29 | -2218.65 | 6865.99 | 6993.49 | 8258.42 | -4412.34 | 346.49 | 9392.48 | 233.94 | 9158.53 | 40.39 | PASS | | |
| 7520.50† | 7087.21 | -864.88 | -2251.87 | 6959.71 | 7087.21 | 8258.42 | -4412.34 | 346.68 | 9375.62 | 236.81 | 9138.81 | 39.83 | PASS | | |
| 7620.50† | 7177.96 | -838.35 | -2284.05 | 7050.46 | 7177.96 | 8258.42 | -4412.34 | 346.83 | 9342.43 | 239.57 | 9102.86 | 39.23 | PASS | | |
| 7720.50† | 7262.97 | -795.51 | -2314.23 | 7135.47 | 7262.97 | 8258.42 | -4412.34 | 346.95 | 9293.85 | 242.08 | 9051.77 | 38.62 | PASS | | |
| 7820.50† | 7339.68 | -737.65 | -2341.49 | 7212.18 | 7339.68 | 8258.42 | -4412.34 | 347.04 | 9231.34 | 244.30 | 8987.05 | 38.01 | PASS | | |
| 7920.50† | 7405.75 | -666.53 | -2364.99 | 7278.25 | 7405.75 | 8258.42 | -4412.34 | 347.08 | 9156.77 | 246.15 | 8910.62 | 37.41 | PASS | | |
| 8020.50† | 7459.16 | -584.32 | -2384.03 | 7331.66 | 7459.16 | 8258.42 | -4412.34 | 347.08 | 9072.38 | 247.59 | 8824.79 | 36.85 | PASS | | |
| 8120.50† | 7498.30 | -493.50 | -2398.02 | 7370.80 | 7498.30 | 8258.42 | -4412.34 | 347.04 | 8980.74 | 248.56 | 8732.18 | 36.34 | PASS | | |
| 8220.50† | 7521.99 | -396.85 | -2406.55 | 7394.49 | 7521.99 | 8258.42 | -4412.34 | 346.95 | 8884.65 | 249.07 | 8635.59 | 35.87 | PASS | | |
| 8315.56 | 7529.50 | -302.24 | -2409.34 | 7402.00 | 7529.50 | 8258.42 | -4412.34 | 346.83 | 8791.87 | 249.11 | 8542.76 | 35.49 | PASS | | |
| 8320.50† | 7529.51 | -297.30 | -2409.35 | 7402.01 | 7529.51 | 8258.42 | -4412.34 | 346.82 | 8787.06 | 249.10 | 8537.96 | 35.48 | PASS | | |
| 8420.50† | 7529.61 | -197.30 | -2409.53 | 7402.11 | 7529.61 | 8258.42 | -4412.34 | 346.68 | 8689.68 | 248.92 | 8440.76 | 35.11 | PASS | | |
| 8520.50† | 7529.71 | -97.30 | -2409.71 | 7402.21 | 7529.71 | 8258.42 | -4412.34 | 346.52 | 8592.36 | 248.73 | 8343.63 | 34.74 | PASS | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 114 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: GLEN YOUNG 2 AWP Offset Wellpath: GLEN YOUNG 2 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#2 EX. GLEN YOUNG 2 (1540'FNL & 1740'FWL, PA) Well: GLEN YOUNG 2 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | |
|---|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | |
| 8620.50† | 7529.82 | 2.70 | -2409.88 | 7402.32 | 7529.82 | 8258.42 | -4412.34 | 346.37 | 8495.11 | 248.55 | 8246.56 | 34.37 | PASS | |
| 8720.50† | 7529.92 | 102.70 | -2410.06 | 7402.42 | 7529.92 | 8258.42 | -4412.34 | 346.21 | 8397.92 | 248.36 | 8149.56 | 34.01 | PASS | |
| 8820.50† | 7530.02 | 202.70 | -2410.24 | 7402.52 | 7530.02 | 8258.42 | -4412.34 | 346.04 | 8300.79 | 248.17 | 8052.62 | 33.64 | PASS | |
| 8920.50† | 7530.13 | 302.70 | -2410.42 | 7402.63 | 7530.13 | 8258.42 | -4412.34 | 345.88 | 8203.74 | 247.98 | 7955.76 | 33.27 | PASS | |
| 9020.50† | 7530.23 | 402.70 | -2410.59 | 7402.73 | 7530.23 | 8258.42 | -4412.34 | 345.70 | 8106.75 | 247.78 | 7858.97 | 32.90 | PASS | |
| 9120.50† | 7530.33 | 502.70 | -2410.77 | 7402.83 | 7530.33 | 8258.42 | -4412.34 | 345.53 | 8009.84 | 247.59 | 7762.26 | 32.54 | PASS | |
| 9220.50† | 7530.44 | 602.70 | -2410.95 | 7402.94 | 7530.44 | 8258.42 | -4412.34 | 345.35 | 7913.01 | 247.39 | 7665.62 | 32.17 | PASS | |
| 9320.50† | 7530.54 | 702.70 | -2411.13 | 7403.04 | 7530.54 | 8258.42 | -4412.34 | 345.17 | 7816.26 | 247.18 | 7569.07 | 31.80 | PASS | |
| 9420.50† | 7530.64 | 802.69 | -2411.31 | 7403.14 | 7530.64 | 8258.42 | -4412.34 | 344.98 | 7719.58 | 246.98 | 7472.61 | 31.43 | PASS | |
| 9520.50† | 7530.75 | 902.69 | -2411.48 | 7403.25 | 7530.75 | 8258.42 | -4412.34 | 344.78 | 7623.00 | 246.77 | 7376.23 | 31.07 | PASS | |
| 9620.50† | 7530.85 | 1002.69 | -2411.66 | 7403.35 | 7530.85 | 8258.42 | -4412.34 | 344.58 | 7526.51 | 246.56 | 7279.94 | 30.70 | PASS | |
| 9720.50† | 7530.96 | 1102.69 | -2411.84 | 7403.46 | 7530.96 | 8258.42 | -4412.34 | 344.38 | 7430.11 | 246.35 | 7183.75 | 30.33 | PASS | |
| 9820.50† | 7531.06 | 1202.69 | -2412.02 | 7403.56 | 7531.06 | 8258.42 | -4412.34 | 344.17 | 7333.80 | 246.14 | 7087.66 | 29.97 | PASS | |
| 9920.50† | 7531.16 | 1302.69 | -2412.19 | 7403.66 | 7531.16 | 8258.42 | -4412.34 | 343.96 | 7237.59 | 245.92 | 6991.67 | 29.60 | PASS | |
| 10020.50† | 7531.27 | 1402.69 | -2412.37 | 7403.77 | 7531.27 | 8258.42 | -4412.34 | 343.74 | 7141.49 | 245.70 | 6895.79 | 29.23 | PASS | |
| 10120.50† | 7531.37 | 1502.69 | -2412.55 | 7403.87 | 7531.37 | 8258.42 | -4412.34 | 343.51 | 7045.50 | 245.48 | 6800.01 | 28.86 | PASS | |
| 10220.50† | 7531.47 | 1602.69 | -2412.73 | 7403.97 | 7531.47 | 8258.42 | -4412.34 | 343.28 | 6949.62 | 245.26 | 6704.36 | 28.50 | PASS | |
| 10320.50† | 7531.58 | 1702.69 | -2412.90 | 7404.08 | 7531.58 | 8258.42 | -4412.34 | 343.04 | 6853.86 | 245.04 | 6608.82 | 28.13 | PASS | |
| 10420.50† | 7531.68 | 1802.69 | -2413.08 | 7404.18 | 7531.68 | 8258.42 | -4412.34 | 342.79 | 6758.22 | 244.81 | 6513.41 | 27.76 | PASS | |
| 10520.50† | 7531.78 | 1902.69 | -2413.26 | 7404.28 | 7531.78 | 8258.42 | -4412.34 | 342.54 | 6662.70 | 244.58 | 6418.12 | 27.40 | PASS | |
| 10620.50† | 7531.89 | 2002.69 | -2413.44 | 7404.39 | 7531.89 | 8258.42 | -4412.34 | 342.28 | 6567.33 | 244.35 | 6322.97 | 27.03 | PASS | |
| 10720.50† | 7531.99 | 2102.69 | -2413.62 | 7404.49 | 7531.99 | 8258.42 | -4412.34 | 342.01 | 6472.09 | 244.12 | 6227.97 | 26.66 | PASS | |
| 10820.50† | 7532.09 | 2202.69 | -2413.79 | 7404.59 | 7532.09 | 8258.42 | -4412.34 | 341.74 | 6377.00 | 243.89 | 6133.10 | 26.30 | PASS | |
| 10920.50† | 7532.20 | 2302.69 | -2413.97 | 7404.70 | 7532.20 | 8258.42 | -4412.34 | 341.45 | 6282.06 | 243.66 | 6038.40 | 25.93 | PASS | |
| 11020.50† | 7532.30 | 2402.69 | -2414.15 | 7404.80 | 7532.30 | 8258.42 | -4412.34 | 341.16 | 6187.27 | 243.43 | 5943.85 | 25.56 | PASS | |
| 11120.50† | 7532.41 | 2502.69 | -2414.33 | 7404.91 | 7532.41 | 8258.42 | -4412.34 | 340.86 | 6092.66 | 243.19 | 5849.47 | 25.20 | PASS | |
| 11220.50† | 7532.51 | 2602.69 | -2414.50 | 7405.01 | 7532.51 | 8258.42 | -4412.34 | 340.55 | 5998.22 | 242.96 | 5755.26 | 24.83 | PASS | |
| 11320.50† | 7532.61 | 2702.69 | -2414.68 | 7405.11 | 7532.61 | 8258.42 | -4412.34 | 340.22 | 5903.97 | 242.73 | 5661.24 | 24.46 | PASS | |
| 11420.50† | 7532.72 | 2802.69 | -2414.86 | 7405.22 | 7532.72 | 8258.42 | -4412.34 | 339.89 | 5809.90 | 242.49 | 5567.41 | 24.10 | PASS | |
| 11520.50† | 7532.82 | 2902.69 | -2415.04 | 7405.32 | 7532.82 | 8258.42 | -4412.34 | 339.55 | 5716.04 | 242.26 | 5473.77 | 23.73 | PASS | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 115 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: GLEN YOUNG 2 AWB Offset Wellpath: GLEN YOUNG 2 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#2 EX. GLEN YOUNG 2 (1540'FNL & 1740'FWL, PA) Well: GLEN YOUNG 2 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | | |
|---|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | |
| 11620.50† | 7532.92 | 3002.69 | -2415.21 | 7405.42 | 7532.92 | 8258.42 | -4412.34 | 339.19 | 5622.39 | 242.04 | 5380.35 | 23.36 | PASS | | |
| 11720.50† | 7533.03 | 3102.69 | -2415.39 | 7405.53 | 7533.03 | 8258.42 | -4412.34 | 338.83 | 5528.96 | 241.81 | 5287.15 | 23.00 | PASS | | |
| 11820.50† | 7533.13 | 3202.69 | -2415.57 | 7405.63 | 7533.13 | 8258.42 | -4412.34 | 338.45 | 5435.76 | 241.59 | 5194.17 | 22.63 | PASS | | |
| 11920.50† | 7533.23 | 3302.69 | -2415.75 | 7405.73 | 7533.23 | 8258.42 | -4412.34 | 338.06 | 5342.82 | 241.37 | 5101.44 | 22.26 | PASS | | |
| 12020.50† | 7533.34 | 3402.69 | -2415.92 | 7405.84 | 7533.34 | 8258.42 | -4412.34 | 337.65 | 5250.13 | 241.16 | 5008.96 | 21.89 | PASS | | |
| 12120.50† | 7533.44 | 3502.69 | -2416.10 | 7405.94 | 7533.44 | 8258.42 | -4412.34 | 337.23 | 5157.71 | 240.96 | 4916.75 | 21.53 | PASS | | |
| 12220.50† | 7533.55 | 3602.69 | -2416.28 | 7406.05 | 7533.55 | 8258.42 | -4412.34 | 336.79 | 5065.58 | 240.76 | 4824.82 | 21.16 | PASS | | |
| 12320.50† | 7533.65 | 3702.69 | -2416.46 | 7406.15 | 7533.65 | 8258.42 | -4412.34 | 336.34 | 4973.76 | 240.58 | 4733.18 | 20.79 | PASS | | |
| 12420.50† | 7533.75 | 3802.69 | -2416.64 | 7406.25 | 7533.75 | 8258.42 | -4412.34 | 335.87 | 4882.25 | 240.40 | 4641.85 | 20.43 | PASS | | |
| 12520.50† | 7533.86 | 3902.69 | -2416.81 | 7406.36 | 7533.86 | 8258.42 | -4412.34 | 335.39 | 4791.09 | 240.24 | 4550.85 | 20.06 | PASS | | |
| 12620.50† | 7533.96 | 4002.69 | -2416.99 | 7406.46 | 7533.96 | 8258.42 | -4412.34 | 334.88 | 4700.29 | 240.09 | 4460.19 | 19.69 | PASS | | |
| 12720.50† | 7534.06 | 4102.69 | -2417.17 | 7406.56 | 7534.06 | 8258.42 | -4412.34 | 334.35 | 4609.86 | 239.96 | 4369.90 | 19.32 | PASS | | |
| 12820.50† | 7534.17 | 4202.69 | -2417.35 | 7406.67 | 7534.17 | 8258.42 | -4412.34 | 333.81 | 4519.84 | 239.85 | 4279.99 | 18.95 | PASS | | |
| 12920.50† | 7534.27 | 4302.69 | -2417.52 | 7406.77 | 7534.27 | 8258.42 | -4412.34 | 333.24 | 4430.25 | 239.76 | 4190.49 | 18.58 | PASS | | |
| 13020.50† | 7534.37 | 4402.69 | -2417.70 | 7406.87 | 7534.37 | 8258.42 | -4412.34 | 332.65 | 4341.12 | 239.70 | 4101.41 | 18.21 | PASS | | |
| 13120.50† | 7534.48 | 4502.69 | -2417.88 | 7406.98 | 7534.48 | 8258.42 | -4412.34 | 332.03 | 4252.46 | 239.67 | 4012.79 | 17.84 | PASS | | |
| 13199.97 | 7534.56 | 4582.16 | -2418.02 | 7407.06 | 7534.56 | 8258.42 | -4412.34 | 331.52 | 4182.37 | 239.67 | 3942.70 | 17.55 | PASS | | |
| 13220.50† | 7534.58 | 4602.69 | -2418.13 | 7407.08 | 7534.58 | 8258.42 | -4412.34 | 331.39 | 4164.29 | 239.67 | 3924.62 | 17.47 | PASS | | |
| 13320.50† | 7534.68 | 4702.65 | -2420.77 | 7407.18 | 7534.68 | 8258.42 | -4412.34 | 330.75 | 4075.52 | 239.70 | 3835.83 | 17.10 | PASS | | |
| 13420.50† | 7534.79 | 4802.45 | -2426.90 | 7407.29 | 7534.79 | 8258.42 | -4412.34 | 330.12 | 3985.69 | 239.76 | 3745.93 | 16.72 | PASS | | |
| 13476.50 | 7534.85 | 4858.23 | -2431.85 | 7407.35 | 7534.85 | 8258.42 | -4412.34 | 329.78 | 3934.92 | 239.81 | 3695.11 | 16.50 | PASS | | |
| 13520.50† | 7534.89 | 4902.02 | -2436.16 | 7407.39 | 7534.89 | 8258.42 | -4412.34 | 329.51 | 3894.96 | 239.85 | 3655.11 | 16.33 | PASS | | |
| 13620.50† | 7534.95 | 5001.54 | -2445.98 | 7407.49 | 7534.99 | 8258.42 | -4412.34 | 328.88 | 3804.45 | 239.98 | 3564.48 | 15.94 | PASS | | |
| 13720.50† | 7535.10 | 5101.06 | -2455.79 | 7407.60 | 7535.10 | 8258.42 | -4412.34 | 328.22 | 3714.44 | 240.15 | 3474.29 | 15.55 | PASS | | |
| 13820.50† | 7535.20 | 5200.57 | -2465.61 | 7407.70 | 7535.20 | 8258.42 | -4412.34 | 327.52 | 3624.94 | 240.37 | 3384.57 | 15.17 | PASS | | |
| 13920.50† | 7535.30 | 5300.09 | -2475.42 | 7407.80 | 7535.30 | 8258.42 | -4412.34 | 326.79 | 3536.01 | 240.65 | 3295.36 | 14.78 | PASS | | |
| 14020.50† | 7535.40 | 5399.61 | -2485.24 | 7407.90 | 7535.40 | 8258.42 | -4412.34 | 326.02 | 3447.69 | 240.99 | 3206.70 | 14.39 | PASS | | |
| 14120.50† | 7535.51 | 5499.12 | -2495.05 | 7408.01 | 7535.51 | 8258.42 | -4412.34 | 325.21 | 3360.02 | 241.41 | 3118.61 | 14.00 | PASS | | |
| 14220.50† | 7535.61 | 5598.64 | -2504.87 | 7408.11 | 7535.61 | 8258.42 | -4412.34 | 324.35 | 3273.06 | 241.90 | 3031.15 | 13.61 | PASS | | |
| 14221.87 | 7535.61 | 5600.00 | -2505.00 | 7408.11 | 7535.61 | 8258.42 | -4412.34 | 324.34 | 3271.87 | 241.91 | 3029.96 | 13.60 | PASS | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 116 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: GLEN YOUNG 2 AWP Offset Wellpath: GLEN YOUNG 2 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#2 EX. GLEN YOUNG 2 (1540'FNL & 1740'FWL, PA) Well: GLEN YOUNG 2 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 14320.50† | 7535.71 | 5698.31 | -2512.99 | 7408.21 | 7535.71 | 8258.42 | -4412.34 | 323.43 | 3187.75 | 242.50 | 2945.24 | 13.22 | PASS |
| 14420.50† | 7535.81 | 5798.19 | -2517.63 | 7408.31 | 7535.81 | 8258.42 | -4412.34 | 322.40 | 3105.26 | 243.27 | 2862.00 | 12.84 | PASS |
| 14520.50† | 7535.92 | 5898.18 | -2518.78 | 7408.42 | 7535.92 | 8258.42 | -4412.34 | 321.26 | 3025.94 | 244.21 | 2781.73 | 12.46 | PASS |
| 14581.38 | 7535.98 | 5959.05 | -2517.77 | 7408.48 | 7535.98 | 8258.42 | -4412.34 | 320.51 | 2979.34 | 244.88 | 2734.46 | 12.23 | PASS |
| 14620.50† | 7536.02 | 5998.16 | -2516.71 | 7408.52 | 7536.02 | 8258.42 | -4412.34 | 320.01 | 2949.95 | 245.35 | 2704.60 | 12.09 | PASS |
| 14720.50† | 7536.12 | 6098.12 | -2513.99 | 7408.62 | 7536.12 | 8258.42 | -4412.34 | 318.69 | 2875.87 | 246.69 | 2629.18 | 11.72 | PASS |
| 14820.50† | 7536.23 | 6198.08 | -2511.27 | 7408.73 | 7536.23 | 8258.42 | -4412.34 | 317.30 | 2803.40 | 248.24 | 2555.16 | 11.35 | PASS |
| 14920.50† | 7536.33 | 6298.05 | -2508.55 | 7408.83 | 7536.33 | 8258.42 | -4412.34 | 315.84 | 2732.67 | 250.01 | 2482.66 | 10.99 | PASS |
| 15020.50† | 7536.43 | 6398.01 | -2505.83 | 7408.93 | 7536.43 | 8258.42 | -4412.34 | 314.30 | 2663.81 | 252.03 | 2411.79 | 10.62 | PASS |
| 15120.50† | 7536.54 | 6497.97 | -2503.11 | 7409.04 | 7536.54 | 8258.42 | -4412.34 | 312.68 | 2596.98 | 254.30 | 2342.68 | 10.26 | PASS |
| 15220.50† | 7536.64 | 6597.93 | -2500.40 | 7409.14 | 7536.64 | 8258.42 | -4412.34 | 310.97 | 2532.34 | 256.85 | 2275.49 | 9.91 | PASS |
| 15320.50† | 7536.74 | 6697.90 | -2497.68 | 7409.24 | 7536.74 | 8258.42 | -4412.34 | 309.18 | 2470.06 | 259.70 | 2210.36 | 9.56 | PASS |
| 15420.50† | 7536.85 | 6797.86 | -2494.96 | 7409.35 | 7536.85 | 8258.42 | -4412.34 | 307.30 | 2410.31 | 262.85 | 2147.46 | 9.22 | PASS |
| 15520.50† | 7536.95 | 6897.82 | -2492.24 | 7409.45 | 7536.95 | 8258.42 | -4412.34 | 305.32 | 2353.30 | 266.31 | 2086.98 | 8.88 | PASS |
| 15620.50† | 7537.05 | 6997.79 | -2489.52 | 7409.55 | 7537.05 | 8258.42 | -4412.34 | 303.25 | 2299.23 | 270.10 | 2029.13 | 8.55 | PASS |
| 15720.50† | 7537.16 | 7097.75 | -2486.80 | 7409.66 | 7537.16 | 8258.42 | -4412.34 | 301.08 | 2248.30 | 274.19 | 1974.11 | 8.24 | PASS |
| 15820.50† | 7537.26 | 7197.71 | -2484.08 | 7409.76 | 7537.26 | 8258.42 | -4412.34 | 298.82 | 2200.75 | 278.58 | 1922.16 | 7.94 | PASS |
| 15920.50† | 7537.36 | 7297.68 | -2481.36 | 7409.86 | 7537.36 | 8258.42 | -4412.34 | 296.45 | 2156.78 | 283.26 | 1873.52 | 7.65 | PASS |
| 16020.50† | 7537.47 | 7397.64 | -2478.64 | 7409.97 | 7537.47 | 8258.42 | -4412.34 | 294.00 | 2116.63 | 288.19 | 1828.44 | 7.38 | PASS |
| 16120.50† | 7537.57 | 7497.60 | -2475.93 | 7410.07 | 7537.57 | 8258.42 | -4412.34 | 291.45 | 2080.52 | 293.32 | 1787.19 | 7.12 | PASS |
| 16220.50† | 7537.68 | 7597.56 | -2473.21 | 7410.18 | 7537.68 | 8258.42 | -4412.34 | 288.82 | 2048.65 | 298.61 | 1750.04 | 6.89 | PASS |
| 16320.50† | 7537.78 | 7697.53 | -2470.49 | 7410.28 | 7537.78 | 8258.42 | -4412.34 | 286.11 | 2021.23 | 304.01 | 1717.23 | 6.68 | PASS |
| 16420.50† | 7537.88 | 7797.49 | -2467.77 | 7410.38 | 7537.88 | 8258.42 | -4412.34 | 283.33 | 1998.45 | 309.43 | 1689.02 | 6.48 | PASS |
| 16520.50† | 7537.99 | 7897.45 | -2465.05 | 7410.49 | 7537.99 | 8258.42 | -4412.34 | 280.50 | 1980.46 | 314.81 | 1665.66 | 6.32 | PASS |
| 16620.50† | 7538.09 | 7997.42 | -2462.33 | 7410.59 | 7538.09 | 8258.42 | -4412.34 | 277.62 | 1967.40 | 320.07 | 1647.33 | 6.17 | PASS |
| 16720.50† | 7538.19 | 8097.38 | -2459.61 | 7410.69 | 7538.19 | 8258.42 | -4412.34 | 274.71 | 1959.36 | 325.13 | 1634.22 | 6.05 | PASS |
| 16820.50† | 7538.30 | 8197.34 | -2456.89 | 7410.80 | 7538.30 | 8258.42 | -4412.34 | 271.79 | 1956.40 | 329.93 | 1626.47 | 5.95 | PASS |
| 16828.39† | 7538.30 | 8205.23 | -2456.68 | 7410.80 | 7538.30 | 8258.42 | -4412.34 | 271.56 | 1956.38 | 330.30 | 1626.09 | 5.94 | PASS |
| 16920.50† | 7538.40 | 8297.31 | -2454.17 | 7410.90 | 7538.40 | 8258.42 | -4412.34 | 268.86 | 1958.55 | 334.40 | 1624.15 | 5.88 | PASS |
| 17020.50† | 7538.50 | 8397.27 | -2451.46 | 7411.00 | 7538.50 | 8258.42 | -4412.34 | 265.95 | 1965.79 | 338.49 | 1627.30 | 5.83 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 117 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: GLEN YOUNG 2 AWB Offset Wellpath: GLEN YOUNG 2 AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.28-T01N-R65W Slot: SLOT#2 EX. GLEN YOUNG 2 (1540'FNL & 1740'FWL, PA) Well: GLEN YOUNG 2 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|---|-----------------|-------------------|------------------|-------------------|--------------------|----------------------|---------------------|-------------------------|---------------------------|----------------------|----------------------------|--------------|----------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 17120.50† | 7538.61 | 8497.23 | -2448.74 | 7411.11 | 7538.61 | 8258.42 | -4412.34 | 263.07 | 1978.07 | 342.15 | 1635.92 | 5.80 | PASS |
| 17189.32† | 7538.68 | 8566.03 | -2446.87 | 7411.18 | 7538.68 | 8258.42 | -4412.34 | 261.11 | 1989.40 | 344.42 | 1644.98 | 5.80 | PASS |
| 17220.50† | 7538.71 | 8597.19 | -2446.02 | 7411.21 | 7538.71 | 8258.42 | -4412.34 | 260.23 | 1995.29 | 345.37 | 1649.92 | 5.80 | PASS |
| 17320.50† | 7538.81 | 8697.16 | -2443.30 | 7411.31 | 7538.81 | 8258.42 | -4412.34 | 257.44 | 2017.33 | 348.12 | 1669.20 | 5.81 | PASS |
| 17420.50† | 7538.92 | 8797.12 | -2440.58 | 7411.42 | 7538.92 | 8258.42 | -4412.34 | 254.72 | 2044.02 | 350.41 | 1693.61 | 5.85 | PASS |
| 17520.50† | 7539.02 | 8897.08 | -2437.86 | 7411.52 | 7539.02 | 8258.42 | -4412.34 | 252.08 | 2075.20 | 352.25 | 1722.95 | 5.91 | PASS |
| 17620.50† | 7539.12 | 8997.05 | -2435.14 | 7411.62 | 7539.12 | 8258.42 | -4412.34 | 249.52 | 2110.66 | 353.66 | 1757.00 | 5.99 | PASS |
| 17720.50† | 7539.23 | 9097.01 | -2432.42 | 7411.73 | 7539.23 | 8258.42 | -4412.34 | 247.05 | 2150.18 | 354.66 | 1795.53 | 6.08 | PASS |
| 17820.50† | 7539.33 | 9196.97 | -2429.70 | 7411.83 | 7539.33 | 8258.42 | -4412.34 | 244.67 | 2193.56 | 355.29 | 1838.27 | 6.20 | PASS |
| 17920.50† | 7539.43 | 9296.94 | -2426.99 | 7411.93 | 7539.43 | 8258.42 | -4412.34 | 242.39 | 2240.56 | 355.58 | 1884.98 | 6.32 | PASS |
| 17985.90 | 7539.50 | 9362.31 | -2425.21 | 7412.00 | 7539.50 | 8258.42 | -4412.34 | 240.95 | 2273.16 | 355.61 | 1917.55 | 6.41 | PASS |

POSITIONAL UNCERTAINTY - Offset Wellbore: GLEN YOUNG 2 AWB Offset Wellpath: GLEN YOUNG 2 AWP

| | | | | |
|-----------------------------------|------------|---------|----------|---------|
| Slot Surface Uncertainty @1SD | Horizontal | 0.100ft | Vertical | 1.000ft |
| Facility Surface Uncertainty @1SD | Horizontal | 8.200ft | Vertical | 3.000ft |

HOLE & CASING SECTIONS - Offset Wellbore: GLEN YOUNG 2 AWB Offset Wellpath: GLEN YOUNG 2 AWP

| String/Diameter | Start MD [ft] | End MD [ft] | Interval [ft] | Start TVD [ft] | End TVD [ft] | Start N/S [ft] | Start E/W [ft] | End N/S [ft] | End E/W [ft] |
|-----------------|---------------|-------------|---------------|----------------|--------------|----------------|----------------|--------------|--------------|
| 5.5in Casing | 0.00 | 8002.00 | 8002.00 | 107.00 | 8109.00 | 8258.42 | -4412.34 | 8258.42 | -4412.34 |

WELLPATH COMPOSITION - Offset Wellbore: GLEN YOUNG 2 AWB Offset Wellpath: GLEN YOUNG 2 AWP

| Start MD [ft] | End MD [ft] | Positional Uncertainty Model | Log Name/Comment | Wellbore | Survey Date |
|---------------|-------------|---|------------------------|------------------|-------------|
| 0.00 | 8100.00 | BH Drift Indicator - Inclination Only (Actual Survey) | DRIFT INDICATOR <8100> | GLEN YOUNG 2 AWB | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 118 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

OFFSET WELLPATH REFERENCE - Offset Wellbore: GLEN YOUNG 2 AWB Offset Wellpath: GLEN YOUNG 2 AWP

| | |
|---|---|
| MD Reference: Rig on SLOT#2 EX. GLEN YOUNG 2 (1540'FNL & 1740'FWL, PA) (RT) | Offset TVD & local coordinates use Reference Wellpath settings (See WELLPATH DATUM on page 1 of this report) |
| Ellipse Start MD | 0.00ft |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 119 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: ROWE 13N-27HZ Offset Wellpath: ROWE 13N-27HZ AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.27-T01N-R65W | | Slot: SLOT#01 EX ROWE 13N-27HZ (200'FNL & 286'FEL, SEC.27) (PR) | | Well: ROWE 13N-27HZ | | Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | |
|----------------------------|-----------------|---|------------------|---------------------|--------------------|---|---------------------|-------------------------|---------------------------|----------------------|----------------------------|--------------|----------------|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | |
| 20.50 | 20.50 | 0.00 | 0.00 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 355.78 | 8843.07 | 138.11 | 8704.95 | 65.90 | PASS | |
| 120.50† | 120.50 | 0.00 | 0.00 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 355.78 | 8760.99 | 138.80 | 8622.19 | 64.95 | PASS | |
| 200.00 | 200.00 | 0.00 | 0.00 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 355.78 | 8696.00 | 139.33 | 8556.68 | 64.22 | PASS | |
| 220.50† | 220.50 | -0.03 | -0.07 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 355.78 | 8679.30 | 139.46 | 8539.84 | 64.04 | PASS | |
| 320.50† | 320.46 | -0.93 | -2.36 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 355.81 | 8598.44 | 140.11 | 8458.33 | 63.14 | PASS | |
| 420.50† | 420.28 | -3.13 | -7.88 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 355.87 | 8518.72 | 140.72 | 8378.00 | 62.27 | PASS | |
| 520.50† | 519.83 | -6.60 | -16.65 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 355.98 | 8440.28 | 141.31 | 8298.97 | 61.43 | PASS | |
| 620.50† | 618.99 | -11.36 | -28.64 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 356.12 | 8363.25 | 141.86 | 8221.39 | 60.63 | PASS | |
| 720.50† | 717.64 | -17.38 | -43.83 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 356.29 | 8287.75 | 142.37 | 8145.38 | 59.86 | PASS | |
| 820.50† | 815.66 | -24.68 | -62.22 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 356.51 | 8213.94 | 142.85 | 8071.09 | 59.12 | PASS | |
| 920.50† | 912.93 | -33.22 | -83.78 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 356.76 | 8141.94 | 143.29 | 7998.65 | 58.42 | PASS | |
| 1020.50† | 1009.33 | -43.02 | -108.48 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 357.04 | 8071.89 | 143.68 | 7928.21 | 57.75 | PASS | |
| 1120.50† | 1104.74 | -54.05 | -136.29 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 357.36 | 8003.92 | 144.03 | 7859.90 | 57.13 | PASS | |
| 1220.50† | 1199.05 | -66.30 | -167.18 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 357.72 | 7938.19 | 144.33 | 7793.86 | 56.53 | PASS | |
| 1242.54 | 1219.68 | -69.16 | -174.40 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 357.80 | 7924.02 | 144.39 | 7779.63 | 56.41 | PASS | |
| 1320.50† | 1292.54 | -79.39 | -200.20 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 358.09 | 7874.31 | 144.59 | 7729.72 | 55.97 | PASS | |
| 1420.50† | 1385.99 | -92.51 | -233.28 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 358.47 | 7811.22 | 144.86 | 7666.37 | 55.42 | PASS | |
| 1520.50† | 1479.44 | -105.63 | -266.37 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 358.84 | 7748.92 | 145.11 | 7603.81 | 54.88 | PASS | |
| 1620.50† | 1572.89 | -118.75 | -299.46 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 359.22 | 7687.41 | 145.35 | 7542.06 | 54.35 | PASS | |
| 1720.50† | 1666.34 | -131.87 | -332.54 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 359.59 | 7626.71 | 145.59 | 7481.13 | 53.83 | PASS | |
| 1820.50† | 1759.79 | -144.99 | -365.63 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 359.95 | 7566.85 | 145.82 | 7421.03 | 53.32 | PASS | |
| 1920.50† | 1853.24 | -158.12 | -398.72 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 0.32 | 7507.85 | 146.06 | 7361.78 | 52.81 | PASS | |
| 2020.50† | 1946.69 | -171.24 | -431.80 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 0.69 | 7449.72 | 146.30 | 7303.41 | 52.32 | PASS | |
| 2120.50† | 2040.14 | -184.36 | -464.89 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 1.05 | 7392.48 | 146.54 | 7245.94 | 51.83 | PASS | |
| 2220.50† | 2133.59 | -197.48 | -497.98 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 1.41 | 7336.16 | 146.77 | 7189.39 | 51.35 | PASS | |
| 2320.50† | 2227.05 | -210.60 | -531.06 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 1.77 | 7280.78 | 147.01 | 7133.77 | 50.88 | PASS | |
| 2420.50† | 2320.50 | -223.72 | -564.15 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 2.13 | 7226.36 | 147.24 | 7079.12 | 50.42 | PASS | |
| 2520.50† | 2413.95 | -236.84 | -597.24 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 2.48 | 7172.92 | 147.47 | 7025.45 | 49.96 | PASS | |
| 2620.50† | 2507.40 | -249.96 | -630.32 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 2.83 | 7120.48 | 147.70 | 6972.78 | 49.52 | PASS | |
| 2720.50† | 2600.85 | -263.08 | -663.41 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 3.19 | 7069.07 | 147.93 | 6921.14 | 49.08 | PASS | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 120 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: ROWE 13N-27HZ Offset Wellpath: ROWE 13N-27HZ AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.27-T01N-R65W Slot: SLOT#01 EX ROWE 13N-27HZ (200'FNL & 286'FEL, SEC.27) (PR) | | | | Well: ROWE 13N-27HZ | | | | Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | |
|--|-----------------|-------------------|------------------|---------------------|--------------------|----------------------|---------------------|---|---------------------------|----------------------|----------------------------|--------------|----------------|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | |
| 2820.50† | 2694.30 | -276.20 | -696.50 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 3.53 | 7018.71 | 148.15 | 6870.56 | 48.66 | PASS | | |
| 2920.50† | 2787.75 | -289.33 | -729.58 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 3.88 | 6969.42 | 148.37 | 6821.05 | 48.24 | PASS | | |
| 3020.50† | 2881.20 | -302.45 | -762.67 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 4.23 | 6921.22 | 148.58 | 6772.64 | 47.84 | PASS | | |
| 3120.50† | 2974.65 | -315.57 | -795.76 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 4.57 | 6874.14 | 148.79 | 6725.34 | 47.44 | PASS | | |
| 3220.50† | 3068.11 | -328.69 | -828.84 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 4.91 | 6828.20 | 149.00 | 6679.20 | 47.06 | PASS | | |
| 3320.50† | 3161.56 | -341.81 | -861.93 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 5.25 | 6783.42 | 149.20 | 6634.22 | 46.68 | PASS | | |
| 3420.50† | 3255.01 | -354.93 | -895.02 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 5.59 | 6739.83 | 149.40 | 6590.43 | 46.32 | PASS | | |
| 3520.50† | 3348.46 | -368.05 | -928.10 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 5.92 | 6697.45 | 149.59 | 6547.86 | 45.97 | PASS | | |
| 3620.50† | 3441.91 | -381.17 | -961.19 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 6.26 | 6656.30 | 149.77 | 6506.53 | 45.63 | PASS | | |
| 3720.50† | 3535.36 | -394.29 | -994.28 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 6.59 | 6616.41 | 149.94 | 6466.46 | 45.30 | PASS | | |
| 3820.50† | 3628.81 | -407.41 | -1027.37 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 6.92 | 6577.79 | 150.11 | 6427.68 | 44.99 | PASS | | |
| 3920.50† | 3722.26 | -420.53 | -1060.45 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 7.24 | 6540.48 | 150.27 | 6390.21 | 44.68 | PASS | | |
| 4020.50† | 3815.71 | -433.66 | -1093.54 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 7.57 | 6504.49 | 150.42 | 6354.06 | 44.39 | PASS | | |
| 4120.50† | 3909.17 | -446.78 | -1126.63 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 7.89 | 6469.84 | 150.56 | 6319.28 | 44.11 | PASS | | |
| 4220.50† | 4002.62 | -459.90 | -1159.71 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 8.21 | 6436.56 | 150.70 | 6285.86 | 43.84 | PASS | | |
| 4320.50† | 4096.07 | -473.02 | -1192.80 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 8.53 | 6404.67 | 150.82 | 6253.85 | 43.59 | PASS | | |
| 4420.50† | 4189.52 | -486.14 | -1225.89 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 8.85 | 6374.19 | 150.93 | 6223.26 | 43.35 | PASS | | |
| 4520.50† | 4282.97 | -499.26 | -1258.97 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 9.16 | 6345.14 | 151.04 | 6194.11 | 43.12 | PASS | | |
| 4620.50† | 4376.42 | -512.38 | -1292.06 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 9.48 | 6317.54 | 151.13 | 6166.42 | 42.91 | PASS | | |
| 4720.50† | 4469.87 | -525.50 | -1325.15 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 9.79 | 6291.41 | 151.21 | 6140.20 | 42.71 | PASS | | |
| 4820.50† | 4563.32 | -538.62 | -1358.23 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 10.09 | 6266.77 | 151.28 | 6115.49 | 42.52 | PASS | | |
| 4920.50† | 4656.77 | -551.74 | -1391.32 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 10.40 | 6243.63 | 151.33 | 6092.29 | 42.35 | PASS | | |
| 5020.50† | 4750.22 | -564.87 | -1424.41 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 10.71 | 6222.01 | 151.37 | 6070.63 | 42.19 | PASS | | |
| 5120.50† | 4843.68 | -577.99 | -1457.49 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 11.01 | 6201.92 | 151.40 | 6050.52 | 42.04 | PASS | | |
| 5220.50† | 4937.13 | -591.11 | -1490.58 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 11.31 | 6183.39 | 151.42 | 6031.97 | 41.91 | PASS | | |
| 5320.50† | 5030.58 | -604.23 | -1523.67 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 11.61 | 6166.43 | 151.43 | 6015.01 | 41.80 | PASS | | |
| 5420.50† | 5124.03 | -617.35 | -1556.75 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 11.90 | 6151.05 | 151.42 | 5999.63 | 41.69 | PASS | | |
| 5520.50† | 5217.48 | -630.47 | -1589.84 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 12.20 | 6137.25 | 151.39 | 5985.86 | 41.61 | PASS | | |
| 5620.50† | 5310.93 | -643.59 | -1622.93 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 12.49 | 6125.06 | 151.35 | 5973.71 | 41.54 | PASS | | |
| 5720.50† | 5404.38 | -656.71 | -1656.01 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 12.78 | 6114.48 | 151.30 | 5963.18 | 41.48 | PASS | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 121 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: ROWE 13N-27HZ Offset Wellpath: ROWE 13N-27HZ AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.27-T01N-R65W | | Slot: SLOT#01 EX ROWE 13N-27HZ (200'FNL & 286'FEL, SEC.27) (PR) | | Well: ROWE 13N-27HZ | | Threshold Value=1.00 | | † = interpolated, ‡ = extrapolated station | | | | | | | |
|----------------------------|-----------------|---|------------------|---------------------|--------------------|----------------------|---------------------|--|---------------------------|----------------------|----------------------------|--------------|----------------|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | |
| 5820.50† | 5497.83 | -669.83 | -1689.10 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 13.07 | 6105.52 | 151.24 | 5954.28 | 41.44 | PASS | | |
| 5920.50† | 5591.28 | -682.95 | -1722.19 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 13.35 | 6098.19 | 151.16 | 5947.03 | 41.41 | PASS | | |
| 6020.50† | 5684.74 | -696.07 | -1755.27 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 13.64 | 6092.49 | 151.06 | 5941.42 | 41.40 | PASS | | |
| 6120.50† | 5778.19 | -709.20 | -1788.36 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 13.92 | 6088.42 | 150.96 | 5937.47 | 41.40 | PASS | | |
| 6220.50† | 5871.64 | -722.32 | -1821.45 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 14.20 | 6086.00 | 150.84 | 5935.16 | 41.42 | PASS | | |
| 6320.50† | 5965.09 | -735.44 | -1854.54 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 14.48 | 6085.22 | 150.70 | 5934.52 | 41.45 | PASS | | |
| 6420.50† | 6058.54 | -748.56 | -1887.62 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 14.76 | 6086.08 | 150.55 | 5935.53 | 41.50 | PASS | | |
| 6520.50† | 6151.99 | -761.68 | -1920.71 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 15.03 | 6088.59 | 150.39 | 5938.20 | 41.56 | PASS | | |
| 6620.50† | 6245.44 | -774.80 | -1953.80 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 15.30 | 6092.74 | 150.22 | 5942.51 | 41.64 | PASS | | |
| 6720.50† | 6338.89 | -787.92 | -1986.88 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 15.57 | 6098.52 | 150.03 | 5948.48 | 41.73 | PASS | | |
| 6820.50† | 6432.34 | -801.04 | -2019.97 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 15.84 | 6105.93 | 149.84 | 5956.10 | 41.84 | PASS | | |
| 6920.50† | 6525.80 | -814.16 | -2053.06 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 16.11 | 6114.98 | 149.63 | 5965.35 | 41.96 | PASS | | |
| 7020.50† | 6619.25 | -827.28 | -2086.14 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 16.38 | 6125.64 | 149.41 | 5976.23 | 42.10 | PASS | | |
| 7120.50† | 6712.70 | -840.41 | -2119.23 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 16.64 | 6137.91 | 149.18 | 5988.73 | 42.25 | PASS | | |
| 7220.50† | 6806.15 | -853.53 | -2152.32 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 16.90 | 6151.78 | 148.94 | 6002.85 | 42.41 | PASS | | |
| 7320.50† | 6899.60 | -866.65 | -2185.40 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 17.16 | 6167.25 | 148.69 | 6018.56 | 42.59 | PASS | | |
| 7341.07 | 6918.82 | -869.35 | -2192.21 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 17.21 | 6170.62 | 148.63 | 6021.99 | 42.63 | PASS | | |
| 7420.50† | 6993.49 | -874.29 | -2218.65 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 17.43 | 6179.09 | 148.42 | 6030.67 | 42.75 | PASS | | |
| 7520.50† | 7087.21 | -864.88 | -2251.87 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 17.75 | 6176.30 | 148.25 | 6028.05 | 42.79 | PASS | | |
| 7620.50† | 7177.96 | -838.35 | -2284.05 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 18.11 | 6158.58 | 148.10 | 6010.48 | 42.71 | PASS | | |
| 7720.50† | 7262.97 | -795.51 | -2314.23 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 18.51 | 6126.35 | 147.76 | 5978.59 | 42.58 | PASS | | |
| 7820.50† | 7339.68 | -737.65 | -2341.49 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 18.92 | 6080.37 | 147.28 | 5933.08 | 42.40 | PASS | | |
| 7920.50† | 7405.75 | -666.53 | -2364.99 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 19.35 | 6021.74 | 146.72 | 5875.02 | 42.16 | PASS | | |
| 8020.50† | 7459.16 | -584.32 | -2384.03 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 19.79 | 5951.89 | 146.09 | 5805.81 | 41.86 | PASS | | |
| 8120.50† | 7498.30 | -493.50 | -2398.02 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 20.22 | 5872.60 | 145.41 | 5727.19 | 41.50 | PASS | | |
| 8220.50† | 7521.99 | -396.85 | -2406.55 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 20.63 | 5785.93 | 144.71 | 5641.22 | 41.09 | PASS | | |
| 8315.56 | 7529.50 | -302.24 | -2409.34 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 20.99 | 5698.85 | 144.07 | 5554.78 | 40.65 | PASS | | |
| 8320.50† | 7529.51 | -297.30 | -2409.35 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 21.01 | 5694.25 | 144.04 | 5550.21 | 40.63 | PASS | | |
| 8420.50† | 7529.61 | -197.30 | -2409.53 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 21.38 | 5601.16 | 143.37 | 5457.79 | 40.16 | PASS | | |
| 8520.50† | 7529.71 | -97.30 | -2409.71 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 21.76 | 5508.31 | 142.70 | 5365.61 | 39.68 | PASS | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 122 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: ROWE 13N-27HZ Offset Wellpath: ROWE 13N-27HZ AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.27-T01N-R65W Slot: SLOT#01 EX ROWE 13N-27HZ (200'FNL & 286'FEL, SEC.27) (PR) Well: ROWE 13N-27HZ Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | |
| 8620.50† | 7529.82 | 2.70 | -2409.88 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 22.15 | 5415.72 | 142.02 | 5273.70 | 39.20 | PASS | |
| 8720.50† | 7529.92 | 102.70 | -2410.06 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 22.56 | 5323.40 | 141.33 | 5182.06 | 38.73 | PASS | |
| 8820.50† | 7530.02 | 202.70 | -2410.24 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 22.98 | 5231.36 | 140.64 | 5090.71 | 38.25 | PASS | |
| 8920.50† | 7530.13 | 302.70 | -2410.42 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 23.42 | 5139.61 | 139.94 | 4999.67 | 37.77 | PASS | |
| 9020.50† | 7530.23 | 402.70 | -2410.59 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 23.87 | 5048.18 | 139.24 | 4908.94 | 37.29 | PASS | |
| 9120.50† | 7530.33 | 502.70 | -2410.77 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 24.34 | 4957.08 | 138.54 | 4818.54 | 36.81 | PASS | |
| 9220.50† | 7530.44 | 602.70 | -2410.95 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 24.83 | 4866.33 | 137.83 | 4728.50 | 36.33 | PASS | |
| 9320.50† | 7530.54 | 702.70 | -2411.13 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 25.34 | 4775.95 | 137.13 | 4638.82 | 35.84 | PASS | |
| 9420.50† | 7530.64 | 802.69 | -2411.31 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 25.86 | 4685.96 | 136.43 | 4549.53 | 35.35 | PASS | |
| 9520.50† | 7530.75 | 902.69 | -2411.48 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 26.41 | 4596.38 | 135.74 | 4460.64 | 34.86 | PASS | |
| 9620.50† | 7530.85 | 1002.69 | -2411.66 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 26.98 | 4507.24 | 135.06 | 4372.18 | 34.36 | PASS | |
| 9720.50† | 7530.96 | 1102.69 | -2411.84 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 27.57 | 4418.57 | 134.39 | 4284.18 | 33.85 | PASS | |
| 9820.50† | 7531.06 | 1202.69 | -2412.02 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 28.18 | 4330.39 | 133.74 | 4196.64 | 33.34 | PASS | |
| 9920.50† | 7531.16 | 1302.69 | -2412.19 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 28.83 | 4242.73 | 133.12 | 4109.61 | 32.82 | PASS | |
| 10020.50† | 7531.27 | 1402.69 | -2412.37 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 29.49 | 4155.63 | 132.53 | 4023.10 | 32.30 | PASS | |
| 10120.50† | 7531.37 | 1502.69 | -2412.55 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 30.19 | 4069.13 | 131.98 | 3937.15 | 31.76 | PASS | |
| 10220.50† | 7531.47 | 1602.69 | -2412.73 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 30.92 | 3983.26 | 131.47 | 3851.78 | 31.21 | PASS | |
| 10320.50† | 7531.58 | 1702.69 | -2412.90 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 31.68 | 3898.06 | 131.02 | 3767.03 | 30.65 | PASS | |
| 10420.50† | 7531.68 | 1802.69 | -2413.08 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 32.47 | 3813.58 | 130.64 | 3682.94 | 30.08 | PASS | |
| 10520.50† | 7531.78 | 1902.69 | -2413.26 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 33.30 | 3729.86 | 130.33 | 3599.53 | 29.49 | PASS | |
| 10620.50† | 7531.89 | 2002.69 | -2413.44 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 34.16 | 3646.97 | 130.12 | 3516.85 | 28.88 | PASS | |
| 10720.50† | 7531.99 | 2102.69 | -2413.62 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 35.07 | 3564.96 | 130.01 | 3434.95 | 28.26 | PASS | |
| 10820.50† | 7532.09 | 2202.69 | -2413.79 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 36.02 | 3483.88 | 130.02 | 3353.87 | 27.61 | PASS | |
| 10920.50† | 7532.20 | 2302.69 | -2413.97 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 37.02 | 3403.81 | 130.17 | 3273.65 | 26.94 | PASS | |
| 11020.50† | 7532.30 | 2402.69 | -2414.15 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 38.06 | 3324.83 | 130.47 | 3194.35 | 26.25 | PASS | |
| 11120.50† | 7532.41 | 2502.69 | -2414.33 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 39.15 | 3247.00 | 130.96 | 3116.03 | 25.54 | PASS | |
| 11220.50† | 7532.51 | 2602.69 | -2414.50 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 40.30 | 3170.41 | 131.65 | 3038.76 | 24.80 | PASS | |
| 11320.50† | 7532.61 | 2702.69 | -2414.68 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 41.50 | 3095.16 | 132.57 | 2962.59 | 24.04 | PASS | |
| 11420.50† | 7532.72 | 2802.69 | -2414.86 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 42.76 | 3021.35 | 133.74 | 2887.61 | 23.25 | PASS | |
| 11520.50† | 7532.82 | 2902.69 | -2415.04 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 44.09 | 2949.08 | 135.18 | 2813.89 | 22.45 | PASS | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 123 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: ROWE 13N-27HZ Offset Wellpath: ROWE 13N-27HZ AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.27-T01N-R65W Slot: SLOT#01 EX ROWE 13N-27HZ (200'FNL & 286'FEL, SEC.27) (PR) Well: ROWE 13N-27HZ Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | |
| 11620.50† | 7532.92 | 3002.69 | -2415.21 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 45.48 | 2878.47 | 136.93 | 2741.54 | 21.62 | PASS | |
| 11720.50† | 7533.03 | 3102.69 | -2415.39 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 46.94 | 2809.64 | 139.00 | 2670.64 | 20.78 | PASS | |
| 11820.50† | 7533.13 | 3202.69 | -2415.57 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 48.48 | 2742.74 | 141.41 | 2601.32 | 19.93 | PASS | |
| 11920.50† | 7533.23 | 3302.69 | -2415.75 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 50.09 | 2677.89 | 144.20 | 2533.70 | 19.07 | PASS | |
| 12020.50† | 7533.34 | 3402.69 | -2415.92 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 51.78 | 2615.27 | 147.36 | 2467.91 | 18.21 | PASS | |
| 12120.50† | 7533.44 | 3502.69 | -2416.10 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 53.55 | 2555.03 | 150.92 | 2404.10 | 17.36 | PASS | |
| 12220.50† | 7533.55 | 3602.69 | -2416.28 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 55.41 | 2497.33 | 154.89 | 2342.44 | 16.52 | PASS | |
| 12320.50† | 7533.65 | 3702.69 | -2416.46 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 57.35 | 2442.37 | 159.26 | 2283.12 | 15.70 | PASS | |
| 12420.50† | 7533.75 | 3802.69 | -2416.64 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 59.38 | 2390.34 | 164.02 | 2226.32 | 14.91 | PASS | |
| 12520.50† | 7533.86 | 3902.69 | -2416.81 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 61.50 | 2341.42 | 169.16 | 2172.25 | 14.15 | PASS | |
| 12620.50† | 7533.96 | 4002.69 | -2416.99 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 63.71 | 2295.81 | 174.66 | 2121.15 | 13.43 | PASS | |
| 12720.50† | 7534.06 | 4102.69 | -2417.17 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 66.01 | 2253.72 | 180.49 | 2073.23 | 12.75 | PASS | |
| 12820.50† | 7534.17 | 4202.69 | -2417.35 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 68.39 | 2215.35 | 186.59 | 2028.76 | 12.11 | PASS | |
| 12920.50† | 7534.27 | 4302.69 | -2417.52 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 70.85 | 2180.89 | 192.93 | 1987.97 | 11.52 | PASS | |
| 13020.50† | 7534.37 | 4402.69 | -2417.70 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 73.38 | 2150.54 | 199.43 | 1951.11 | 10.98 | PASS | |
| 13120.50† | 7534.48 | 4502.69 | -2417.88 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 75.98 | 2124.46 | 206.03 | 1918.43 | 10.49 | PASS | |
| 13199.97 | 7534.56 | 4582.16 | -2418.02 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 78.10 | 2106.89 | 211.31 | 1895.59 | 10.14 | PASS | |
| 13220.50† | 7534.58 | 4602.69 | -2418.13 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 78.65 | 2102.89 | 212.66 | 1890.23 | 10.06 | PASS | |
| 13320.50† | 7534.68 | 4702.65 | -2420.77 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 81.37 | 2088.25 | 219.28 | 1868.97 | 9.68 | PASS | |
| 13420.50† | 7534.79 | 4802.45 | -2426.90 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 84.13 | 2081.78 | 225.80 | 1855.98 | 9.37 | PASS | |
| 13448.84† | 7534.82 | 4830.69 | -2429.26 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 84.91 | 2081.45 | 227.61 | 1853.84 | 9.29 | PASS | |
| 13476.50 | 7534.85 | 4858.23 | -2431.85 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 85.68 | 2081.77 | 229.36 | 1852.41 | 9.22 | PASS | |
| 13520.50† | 7534.89 | 4902.02 | -2436.16 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 86.90 | 2083.24 | 232.09 | 1851.15 | 9.12 | PASS | |
| 13620.50† | 7534.99 | 5001.54 | -2445.98 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 89.66 | 2090.02 | 238.06 | 1851.96 | 8.91 | PASS | |
| 13720.50† | 7535.10 | 5101.06 | -2455.79 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 92.39 | 2101.55 | 243.68 | 1857.88 | 8.75 | PASS | |
| 13820.50† | 7535.20 | 5200.57 | -2465.61 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 95.09 | 2117.75 | 248.88 | 1868.87 | 8.63 | PASS | |
| 13920.50† | 7535.30 | 5300.09 | -2475.42 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 97.74 | 2138.50 | 253.64 | 1884.86 | 8.55 | PASS | |
| 14020.50† | 7535.40 | 5399.61 | -2485.24 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 100.33 | 2163.68 | 257.94 | 1905.74 | 8.50 | PASS | |
| 14110.10† | 7535.50 | 5488.77 | -2494.03 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 102.60 | 2189.87 | 261.40 | 1928.47 | 8.49 | PASS | |
| 14120.50† | 7535.51 | 5499.12 | -2495.05 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 102.86 | 2193.13 | 261.78 | 1931.35 | 8.49 | PASS | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 124 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: ROWE 13N-27HZ Offset Wellpath: ROWE 13N-27HZ AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.27-T01N-R65W Slot: SLOT#01 EX ROWE 13N-27HZ (200'FNL & 286'FEL, SEC.27) (PR) | | | | | | Well: ROWE 13N-27HZ | | Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|---------------------|------------------|---|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 14220.50† | 7535.61 | 5598.64 | -2504.87 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 105.31 | 2226.69 | 265.17 | 1961.52 | 8.51 | PASS |
| 14221.87 | 7535.61 | 5600.00 | -2505.00 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 105.35 | 2227.18 | 265.21 | 1961.96 | 8.51 | PASS |
| 14320.50† | 7535.71 | 5698.31 | -2512.99 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 107.71 | 2262.61 | 268.11 | 1994.50 | 8.55 | PASS |
| 14420.50† | 7535.81 | 5798.19 | -2517.63 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 110.06 | 2299.15 | 270.68 | 2028.47 | 8.61 | PASS |
| 14520.50† | 7535.92 | 5898.18 | -2518.78 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 112.36 | 2336.21 | 272.85 | 2063.36 | 8.67 | PASS |
| 14581.38 | 7535.98 | 5959.05 | -2517.77 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 113.75 | 2359.01 | 273.99 | 2085.02 | 8.72 | PASS |
| 14620.50† | 7536.02 | 5998.16 | -2516.71 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 114.63 | 2373.99 | 274.65 | 2099.34 | 8.76 | PASS |
| 14720.50† | 7536.12 | 6098.12 | -2513.99 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 116.82 | 2414.74 | 276.08 | 2138.66 | 8.86 | PASS |
| 14820.50† | 7536.23 | 6198.08 | -2511.27 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 118.94 | 2458.88 | 277.18 | 2181.70 | 8.99 | PASS |
| 14920.50† | 7536.33 | 6298.05 | -2508.55 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 120.98 | 2506.24 | 277.97 | 2228.27 | 9.13 | PASS |
| 15020.50† | 7536.43 | 6398.01 | -2505.83 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 122.94 | 2556.63 | 278.47 | 2278.16 | 9.30 | PASS |
| 15120.50† | 7536.54 | 6497.97 | -2503.11 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 124.82 | 2609.89 | 278.73 | 2331.16 | 9.48 | PASS |
| 15220.50† | 7536.64 | 6597.93 | -2500.40 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 126.63 | 2665.83 | 278.76 | 2387.07 | 9.69 | PASS |
| 15320.50† | 7536.74 | 6697.90 | -2497.68 | 13690.00 | 7295.32 | 5013.99 | -369.78 | 128.36 | 2724.29 | 278.58 | 2445.71 | 9.91 | PASS |
| 15420.50† | 7536.85 | 6797.86 | -2494.96 | 13676.85 | 7294.93 | 5024.12 | -361.40 | 129.74 | 2785.09 | 278.02 | 2507.07 | 10.15 | PASS |
| 15520.50† | 7536.95 | 6897.82 | -2492.24 | 13613.97 | 7293.05 | 5072.53 | -321.33 | 130.06 | 2846.75 | 276.60 | 2570.16 | 10.43 | PASS |
| 15620.50† | 7537.05 | 6997.79 | -2489.52 | 13570.93 | 7291.49 | 5105.36 | -293.54 | 130.75 | 2909.28 | 275.45 | 2633.83 | 10.70 | PASS |
| 15720.50† | 7537.16 | 7097.75 | -2486.80 | 13526.95 | 7289.74 | 5138.58 | -264.77 | 131.40 | 2972.70 | 274.27 | 2698.43 | 10.98 | PASS |
| 15820.50† | 7537.26 | 7197.71 | -2484.08 | 13479.16 | 7287.79 | 5174.35 | -233.13 | 131.95 | 3036.94 | 273.01 | 2763.93 | 11.27 | PASS |
| 15920.50† | 7537.36 | 7297.68 | -2481.36 | 13429.36 | 7285.91 | 5211.31 | -199.81 | 132.44 | 3101.88 | 271.72 | 2830.17 | 11.57 | PASS |
| 16020.50† | 7537.47 | 7397.64 | -2478.64 | 13326.81 | 7283.28 | 5287.43 | -131.15 | 131.95 | 3166.75 | 269.79 | 2896.96 | 11.90 | PASS |
| 16120.50† | 7537.57 | 7497.60 | -2475.93 | 13240.14 | 7283.27 | 5351.95 | -73.29 | 131.77 | 3231.28 | 268.13 | 2963.14 | 12.22 | PASS |
| 16220.50† | 7537.68 | 7597.56 | -2473.21 | 13151.14 | 7285.39 | 5418.44 | -14.16 | 131.55 | 3295.32 | 266.52 | 3028.80 | 12.54 | PASS |
| 16320.50† | 7537.78 | 7697.53 | -2470.49 | 13106.64 | 7287.00 | 5451.50 | 15.58 | 132.10 | 3359.77 | 265.38 | 3094.39 | 12.84 | PASS |
| 16420.50† | 7537.88 | 7797.49 | -2467.77 | 13068.34 | 7288.58 | 5479.70 | 41.45 | 132.73 | 3424.98 | 264.29 | 3160.69 | 13.14 | PASS |
| 16520.50† | 7537.99 | 7897.45 | -2465.05 | 13038.43 | 7290.10 | 5501.43 | 61.95 | 133.48 | 3491.14 | 263.26 | 3227.88 | 13.45 | PASS |
| 16620.50† | 7538.09 | 7997.42 | -2462.33 | 13009.27 | 7291.85 | 5522.34 | 82.19 | 134.21 | 3558.26 | 262.21 | 3296.06 | 13.76 | PASS |
| 16720.50† | 7538.19 | 8097.38 | -2459.61 | 12966.44 | 7294.75 | 5552.64 | 112.32 | 134.70 | 3626.26 | 261.03 | 3365.23 | 14.09 | PASS |
| 16820.50† | 7538.30 | 8197.34 | -2456.89 | 12904.97 | 7298.55 | 5596.02 | 155.72 | 134.88 | 3694.61 | 259.71 | 3434.90 | 14.43 | PASS |
| 16920.50† | 7538.40 | 8297.31 | -2454.17 | 12863.26 | 7300.70 | 5625.31 | 185.32 | 135.35 | 3763.38 | 258.54 | 3504.84 | 14.77 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 125 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: ROWE 13N-27HZ Offset Wellpath: ROWE 13N-27HZ AWP Offset Wellbore Status: Actual: Drilling

| Facility: SEC.27-T01N-R65W Slot: SLOT#01 EX ROWE 13N-27HZ (200'FNL & 286'FEL, SEC.27) (PR) Well: ROWE 13N-27HZ Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 17020.50† | 7538.50 | 8397.27 | -2451.46 | 12822.11 | 7302.36 | 5654.01 | 214.77 | 135.82 | 3832.75 | 257.37 | 3575.38 | 15.11 | PASS |
| 17120.50† | 7538.61 | 8497.23 | -2448.74 | 12772.99 | 7303.88 | 5688.06 | 250.14 | 136.15 | 3902.63 | 256.14 | 3646.48 | 15.46 | PASS |
| 17220.50† | 7538.71 | 8597.19 | -2446.02 | 12725.02 | 7305.08 | 5721.13 | 284.86 | 136.48 | 3972.91 | 254.94 | 3717.97 | 15.82 | PASS |
| 17320.50† | 7538.81 | 8697.16 | -2443.30 | 12689.35 | 7305.77 | 5745.55 | 310.86 | 136.98 | 4043.72 | 253.80 | 3789.92 | 16.17 | PASS |
| 17420.50† | 7538.92 | 8797.12 | -2440.58 | 12654.27 | 7306.29 | 5769.35 | 336.62 | 137.47 | 4115.14 | 252.67 | 3862.47 | 16.53 | PASS |
| 17520.50† | 7539.02 | 8897.08 | -2437.86 | 12596.63 | 7306.71 | 5808.18 | 379.22 | 137.64 | 4187.04 | 251.43 | 3935.61 | 16.91 | PASS |
| 17620.50† | 7539.12 | 8997.05 | -2435.14 | 12396.98 | 7301.66 | 5945.29 | 524.20 | 135.88 | 4257.62 | 249.66 | 4007.96 | 17.31 | PASS |
| 17720.50† | 7539.23 | 9097.01 | -2432.42 | 12130.97 | 7291.07 | 6135.19 | 710.08 | 133.31 | 4325.42 | 248.15 | 4077.27 | 17.70 | PASS |
| 17820.50† | 7539.33 | 9196.97 | -2429.70 | 12072.28 | 7290.39 | 6177.87 | 750.36 | 133.51 | 4392.02 | 247.22 | 4144.80 | 18.04 | PASS |
| 17920.50† | 7539.43 | 9296.94 | -2426.99 | 12014.32 | 7290.84 | 6219.79 | 790.38 | 133.72 | 4458.93 | 246.31 | 4212.62 | 18.38 | PASS |
| 17985.90 | 7539.50 | 9362.31 | -2425.21 | 11954.47 | 7291.91 | 6263.05 | 831.73 | 133.58 | 4502.70 | 245.74 | 4256.96 | 18.61 | PASS |

POSITIONAL UNCERTAINTY - Offset Wellbore: ROWE 13N-27HZ Offset Wellpath: ROWE 13N-27HZ AWP

| | | | | |
|-----------------------------------|------------|---------|----------|---------|
| Slot Surface Uncertainty @1SD | Horizontal | 0.100ft | Vertical | 1.000ft |
| Facility Surface Uncertainty @1SD | Horizontal | 8.200ft | Vertical | 3.000ft |

WELLPATH COMPOSITION - Offset Wellbore: ROWE 13N-27HZ Offset Wellpath: ROWE 13N-27HZ AWP

| Start MD [ft] | End MD [ft] | Positional Uncertainty Model | Log Name/Comment | Wellbore | Survey Date |
|---------------|-------------|-------------------------------|---------------------------------------|---------------|-------------|
| 1295.00 | 13690.00 | ISCWSA MWD, Rev. 4 (Standard) | MWD SURVEYS FROM COGCC <1295 - 13623> | ROWE 13N-27HZ | 1/23/2020 |

OFFSET WELLPATH REFERENCE - Offset Wellbore: ROWE 13N-27HZ Offset Wellpath: ROWE 13N-27HZ AWP

| | |
|--------------------------------------|---|
| MD Reference: XTREME 8 (17'KB) (RKB) | Offset TVD & local coordinates use Reference Wellpath settings (See WELLPATH DATUM on page 1 of this report) |
| Ellipse Start MD | 17.00ft |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 126 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: JUDY 3-4 PWB Offset Wellpath: JUDY 3-4 (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#01 JUDY 3-4 (620'FSL & 743'FWL, SEC.34) Well: JUDY 3-4 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 20.50 | 20.50 | 0.00 | 0.00 | 19.00 | 20.50 | -149.36 | -75.64 | 206.86 | 167.42 | 9.75 | 157.67 | 28.36 | PASS |
| 120.50† | 120.50 | 0.00 | 0.00 | 119.00 | 120.50 | -149.36 | -75.64 | 206.86 | 167.42 | 9.82 | 157.60 | 28.03 | PASS |
| 200.00 | 200.00 | 0.00 | 0.00 | 198.50 | 200.00 | -149.36 | -75.64 | 206.86 | 167.42 | 9.96 | 157.46 | 27.34 | PASS |
| 220.50† | 220.50 | -0.03 | -0.07 | 219.00 | 220.50 | -149.36 | -75.64 | 206.84 | 167.36 | 10.01 | 157.35 | 27.10 | PASS |
| 320.50† | 320.46 | -0.93 | -2.36 | 318.96 | 320.46 | -149.36 | -75.64 | 206.28 | 165.53 | 10.37 | 155.16 | 25.28 | PASS |
| 420.50† | 420.28 | -3.13 | -7.88 | 418.78 | 420.28 | -149.36 | -75.64 | 204.86 | 161.17 | 10.94 | 150.22 | 22.59 | PASS |
| 520.50† | 519.83 | -6.60 | -16.65 | 518.33 | 519.83 | -149.36 | -75.64 | 202.45 | 154.46 | 11.55 | 142.91 | 19.88 | PASS |
| 620.50† | 618.99 | -11.36 | -28.64 | 617.49 | 618.99 | -149.36 | -75.64 | 198.81 | 145.79 | 12.18 | 133.60 | 17.30 | PASS |
| 720.50† | 717.64 | -17.38 | -43.83 | 716.14 | 717.64 | -149.36 | -75.64 | 193.55 | 135.75 | 12.82 | 122.93 | 14.91 | PASS |
| 820.50† | 815.66 | -24.68 | -62.22 | 814.16 | 815.66 | -149.36 | -75.64 | 186.14 | 125.40 | 13.48 | 111.92 | 12.79 | PASS |
| 920.50† | 912.93 | -33.22 | -83.78 | 911.43 | 912.93 | -149.36 | -75.64 | 175.99 | 116.42 | 14.19 | 102.23 | 11.02 | PASS |
| 1020.50† | 1009.33 | -43.02 | -108.48 | 1007.83 | 1009.33 | -149.36 | -75.64 | 162.84 | 111.29 | 14.96 | 96.33 | 9.78 | PASS |
| 1050.67† | 1038.22 | -46.22 | -116.54 | 1036.72 | 1038.22 | -149.36 | -75.64 | 158.37 | 110.95 | 15.32 | 95.64 | 9.44 | PASS |
| 1120.50† | 1104.74 | -54.05 | -136.29 | 1103.24 | 1104.74 | -149.36 | -75.64 | 147.53 | 112.97 | 16.05 | 96.92 | 9.04 | PASS |
| 1167.88† | 1149.57 | -59.70 | -150.55 | 1148.07 | 1149.57 | -149.36 | -75.64 | 140.12 | 116.83 | 16.59 | 100.24 | 8.95 | PASS |
| 1220.50† | 1199.05 | -66.30 | -167.18 | 1197.55 | 1199.05 | -149.36 | -75.64 | 132.22 | 123.61 | 17.20 | 106.41 | 9.05 | PASS |
| 1242.54 | 1219.68 | -69.16 | -174.40 | 1218.18 | 1219.68 | -149.36 | -75.64 | 129.08 | 127.22 | 17.45 | 109.77 | 9.15 | PASS |
| 1320.50† | 1292.54 | -79.39 | -200.20 | 1291.04 | 1292.54 | -149.36 | -75.64 | 119.33 | 142.86 | 18.28 | 124.58 | 9.72 | PASS |
| 1420.50† | 1385.99 | -92.51 | -233.28 | 1384.49 | 1385.99 | -149.36 | -75.64 | 109.83 | 167.58 | 19.21 | 148.36 | 10.74 | PASS |
| 1520.50† | 1479.44 | -105.63 | -266.37 | 1477.94 | 1479.44 | -149.36 | -75.64 | 102.91 | 195.68 | 19.87 | 175.81 | 12.07 | PASS |
| 1620.50† | 1572.89 | -118.75 | -299.46 | 1571.33 | 1572.82 | -150.24 | -75.75 | 98.01 | 225.91 | 20.07 | 205.83 | 13.79 | PASS |
| 1720.50† | 1666.34 | -131.87 | -332.54 | 1665.55 | 1666.96 | -154.10 | -76.25 | 94.96 | 257.25 | 20.22 | 237.03 | 15.60 | PASS |
| 1820.50† | 1759.79 | -144.99 | -365.63 | 1760.55 | 1761.69 | -161.10 | -77.15 | 93.20 | 288.93 | 20.44 | 268.49 | 17.31 | PASS |
| 1920.50† | 1853.24 | -158.12 | -398.72 | 1856.13 | 1856.71 | -171.28 | -78.46 | 92.36 | 320.54 | 20.75 | 299.80 | 18.88 | PASS |
| 2020.50† | 1946.69 | -171.24 | -431.80 | 1952.08 | 1951.71 | -184.66 | -80.18 | 92.19 | 351.91 | 21.14 | 330.77 | 20.28 | PASS |
| 2120.50† | 2040.14 | -184.36 | -464.89 | 2048.20 | 2046.36 | -201.22 | -82.31 | 92.52 | 383.00 | 21.64 | 361.36 | 21.47 | PASS |
| 2220.50† | 2133.59 | -197.48 | -497.98 | 2144.25 | 2140.33 | -220.91 | -84.84 | 93.25 | 413.85 | 22.25 | 391.60 | 22.44 | PASS |
| 2320.50† | 2227.05 | -210.60 | -531.06 | 2239.40 | 2232.94 | -242.60 | -87.63 | 94.13 | 444.62 | 22.96 | 421.66 | 23.22 | PASS |
| 2420.50† | 2320.50 | -223.72 | -564.15 | 2334.31 | 2325.28 | -264.32 | -90.43 | 94.90 | 475.48 | 23.75 | 451.73 | 23.85 | PASS |
| 2520.50† | 2413.95 | -236.84 | -597.24 | 2429.21 | 2417.62 | -286.05 | -93.22 | 95.58 | 506.42 | 24.58 | 481.85 | 24.40 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 127 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: JUDY 3-4 PWB Offset Wellpath: JUDY 3-4 (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#01 JUDY 3-4 (620'FSL & 743'FWL, SEC.34) Well: JUDY 3-4 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 2620.50† | 2507.40 | -249.96 | -630.32 | 2524.12 | 2509.97 | -307.77 | -96.02 | 96.18 | 537.43 | 25.51 | 511.92 | 24.78 | PASS |
| 2720.50† | 2600.85 | -263.08 | -663.41 | 2619.02 | 2602.31 | -329.50 | -98.81 | 96.71 | 568.50 | 26.46 | 542.03 | 25.11 | PASS |
| 2820.50† | 2694.30 | -276.20 | -696.50 | 2713.93 | 2694.65 | -351.22 | -101.60 | 97.19 | 599.60 | 27.46 | 572.14 | 25.37 | PASS |
| 2920.50† | 2787.75 | -289.33 | -729.58 | 2808.83 | 2787.00 | -372.95 | -104.40 | 97.62 | 630.75 | 28.50 | 602.26 | 25.57 | PASS |
| 3020.50† | 2881.20 | -302.45 | -762.67 | 2903.74 | 2879.34 | -394.67 | -107.19 | 98.01 | 661.94 | 29.57 | 632.37 | 25.72 | PASS |
| 3120.50† | 2974.65 | -315.57 | -795.76 | 2998.65 | 2971.68 | -416.40 | -109.99 | 98.36 | 693.15 | 30.66 | 662.49 | 25.83 | PASS |
| 3220.50† | 3068.11 | -328.69 | -828.84 | 3093.55 | 3064.03 | -438.12 | -112.78 | 98.69 | 724.39 | 31.78 | 692.61 | 25.92 | PASS |
| 3320.50† | 3161.56 | -341.81 | -861.93 | 3188.46 | 3156.37 | -459.85 | -115.57 | 98.99 | 755.65 | 32.92 | 722.73 | 25.97 | PASS |
| 3420.50† | 3255.01 | -354.93 | -895.02 | 3283.36 | 3248.71 | -481.57 | -118.37 | 99.26 | 786.93 | 34.09 | 752.85 | 26.01 | PASS |
| 3520.50† | 3348.46 | -368.05 | -928.10 | 3378.27 | 3341.06 | -503.30 | -121.16 | 99.52 | 818.23 | 35.26 | 782.97 | 26.03 | PASS |
| 3620.50† | 3441.91 | -381.17 | -961.19 | 3473.17 | 3433.40 | -525.02 | -123.96 | 99.75 | 849.55 | 36.46 | 813.09 | 26.04 | PASS |
| 3720.50† | 3535.36 | -394.29 | -994.28 | 3568.08 | 3525.74 | -546.75 | -126.75 | 99.97 | 880.87 | 37.67 | 843.21 | 26.03 | PASS |
| 3820.50† | 3628.81 | -407.41 | -1027.37 | 3662.99 | 3618.09 | -568.47 | -129.55 | 100.17 | 912.22 | 38.89 | 873.33 | 26.02 | PASS |
| 3920.50† | 3722.26 | -420.53 | -1060.45 | 3757.89 | 3710.43 | -590.20 | -132.34 | 100.36 | 943.57 | 40.12 | 903.45 | 26.00 | PASS |
| 4020.50† | 3815.71 | -433.66 | -1093.54 | 3852.80 | 3802.77 | -611.92 | -135.13 | 100.54 | 974.93 | 41.36 | 933.57 | 25.98 | PASS |
| 4120.50† | 3909.17 | -446.78 | -1126.63 | 3947.70 | 3895.12 | -633.65 | -137.93 | 100.70 | 1006.30 | 42.61 | 963.69 | 25.95 | PASS |
| 4220.50† | 4002.62 | -459.90 | -1159.71 | 4042.61 | 3987.46 | -655.37 | -140.72 | 100.86 | 1037.68 | 43.87 | 993.82 | 25.92 | PASS |
| 4320.50† | 4096.07 | -473.02 | -1192.80 | 4137.51 | 4079.80 | -677.10 | -143.52 | 101.01 | 1069.07 | 45.13 | 1023.94 | 25.89 | PASS |
| 4420.50† | 4189.52 | -486.14 | -1225.89 | 4232.42 | 4172.15 | -698.82 | -146.31 | 101.15 | 1100.46 | 46.40 | 1054.06 | 25.85 | PASS |
| 4520.50† | 4282.97 | -499.26 | -1258.97 | 4327.33 | 4264.49 | -720.55 | -149.10 | 101.28 | 1131.87 | 47.68 | 1084.18 | 25.81 | PASS |
| 4620.50† | 4376.42 | -512.38 | -1292.06 | 4422.23 | 4356.83 | -742.27 | -151.90 | 101.40 | 1163.27 | 48.96 | 1114.31 | 25.77 | PASS |
| 4720.50† | 4469.87 | -525.50 | -1325.15 | 4517.14 | 4449.18 | -764.00 | -154.69 | 101.52 | 1194.69 | 50.25 | 1144.43 | 25.73 | PASS |
| 4820.50† | 4563.32 | -538.62 | -1358.23 | 4612.04 | 4541.52 | -785.72 | -157.49 | 101.63 | 1226.10 | 51.55 | 1174.56 | 25.70 | PASS |
| 4920.50† | 4656.77 | -551.74 | -1391.32 | 4706.95 | 4633.86 | -807.45 | -160.28 | 101.73 | 1257.52 | 52.84 | 1204.68 | 25.66 | PASS |
| 5020.50† | 4750.22 | -564.87 | -1424.41 | 4801.85 | 4726.21 | -829.17 | -163.07 | 101.84 | 1288.95 | 54.14 | 1234.81 | 25.62 | PASS |
| 5120.50† | 4843.68 | -577.99 | -1457.49 | 4896.76 | 4818.55 | -850.90 | -165.87 | 101.93 | 1320.38 | 55.45 | 1264.93 | 25.58 | PASS |
| 5220.50† | 4937.13 | -591.11 | -1490.58 | 4991.67 | 4910.89 | -872.62 | -168.66 | 102.02 | 1351.82 | 56.76 | 1295.06 | 25.54 | PASS |
| 5320.50† | 5030.58 | -604.23 | -1523.67 | 5086.57 | 5003.24 | -894.35 | -171.46 | 102.11 | 1383.25 | 58.07 | 1325.18 | 25.50 | PASS |
| 5420.50† | 5124.03 | -617.35 | -1556.75 | 5181.48 | 5095.58 | -916.07 | -174.25 | 102.19 | 1414.69 | 59.38 | 1355.31 | 25.46 | PASS |
| 5520.50† | 5217.48 | -630.47 | -1589.84 | 5276.38 | 5187.92 | -937.80 | -177.04 | 102.27 | 1446.14 | 60.70 | 1385.44 | 25.43 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 128 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: JUDY 3-4 PWB Offset Wellpath: JUDY 3-4 (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#01 JUDY 3-4 (620'FSL & 743'FWL, SEC.34) Well: JUDY 3-4 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 5620.50† | 5310.93 | -643.59 | -1622.93 | 5371.29 | 5280.27 | -959.52 | -179.84 | 102.35 | 1477.59 | 62.02 | 1415.56 | 25.39 | PASS |
| 5720.50† | 5404.38 | -656.71 | -1656.01 | 5466.19 | 5372.61 | -981.25 | -182.63 | 102.42 | 1509.03 | 63.34 | 1445.69 | 25.35 | PASS |
| 5820.50† | 5497.83 | -669.83 | -1689.10 | 5561.10 | 5464.96 | -1002.97 | -185.43 | 102.49 | 1540.49 | 64.67 | 1475.82 | 25.32 | PASS |
| 5920.50† | 5591.28 | -682.95 | -1722.19 | 5656.01 | 5557.30 | -1024.70 | -188.22 | 102.56 | 1571.94 | 66.00 | 1505.95 | 25.29 | PASS |
| 6020.50† | 5684.74 | -696.07 | -1755.27 | 5750.91 | 5649.64 | -1046.43 | -191.02 | 102.62 | 1603.40 | 67.32 | 1536.07 | 25.25 | PASS |
| 6120.50† | 5778.19 | -709.20 | -1788.36 | 5845.82 | 5741.99 | -1068.15 | -193.81 | 102.69 | 1634.86 | 68.65 | 1566.20 | 25.22 | PASS |
| 6220.50† | 5871.64 | -722.32 | -1821.45 | 5940.72 | 5834.33 | -1089.88 | -196.60 | 102.75 | 1666.32 | 69.99 | 1596.33 | 25.19 | PASS |
| 6320.50† | 5965.09 | -735.44 | -1854.54 | 6035.63 | 5926.67 | -1111.60 | -199.40 | 102.80 | 1697.78 | 71.32 | 1626.46 | 25.15 | PASS |
| 6420.50† | 6058.54 | -748.56 | -1887.62 | 6130.53 | 6019.02 | -1133.33 | -202.19 | 102.86 | 1729.24 | 72.66 | 1656.59 | 25.12 | PASS |
| 6520.50† | 6151.99 | -761.68 | -1920.71 | 6225.44 | 6111.36 | -1155.05 | -204.99 | 102.91 | 1760.71 | 73.99 | 1686.72 | 25.09 | PASS |
| 6620.50† | 6245.44 | -774.80 | -1953.80 | 6324.72 | 6208.15 | -1176.96 | -207.80 | 102.97 | 1792.10 | 75.36 | 1716.74 | 25.05 | PASS |
| 6720.50† | 6338.89 | -787.92 | -1986.88 | 6426.14 | 6307.72 | -1196.05 | -210.26 | 102.94 | 1823.17 | 76.65 | 1746.51 | 25.03 | PASS |
| 6820.50† | 6432.34 | -801.04 | -2019.97 | 6527.49 | 6407.84 | -1211.62 | -212.26 | 102.80 | 1853.91 | 77.84 | 1776.07 | 25.05 | PASS |
| 6920.50† | 6525.80 | -814.16 | -2053.06 | 6628.52 | 6508.14 | -1223.64 | -213.81 | 102.55 | 1884.36 | 78.90 | 1805.46 | 25.10 | PASS |
| 7020.50† | 6619.25 | -827.28 | -2086.14 | 6728.99 | 6608.24 | -1232.10 | -214.90 | 102.21 | 1914.57 | 79.86 | 1834.71 | 25.18 | PASS |
| 7120.50† | 6712.70 | -840.41 | -2119.23 | 6828.65 | 6707.77 | -1237.05 | -215.53 | 101.77 | 1944.59 | 80.69 | 1863.89 | 25.30 | PASS |
| 7220.50† | 6806.15 | -853.53 | -2152.32 | 6927.05 | 6806.15 | -1238.57 | -215.73 | 101.25 | 1974.50 | 81.42 | 1893.08 | 25.45 | PASS |
| 7320.50† | 6899.60 | -866.65 | -2185.40 | 7020.50 | 6899.60 | -1238.57 | -215.73 | 100.69 | 2004.48 | 82.06 | 1922.42 | 25.62 | PASS |
| 7341.07 | 6918.82 | -869.35 | -2192.21 | 7039.72 | 6918.82 | -1238.57 | -215.73 | 100.58 | 2010.67 | 82.20 | 1928.48 | 25.66 | PASS |
| 7420.50† | 6993.49 | -874.29 | -2218.65 | 7114.39 | 6993.49 | -1238.57 | -215.73 | 100.31 | 2035.78 | 82.71 | 1953.08 | 25.81 | PASS |
| 7520.50† | 7087.21 | -884.88 | -2251.87 | 7208.11 | 7087.21 | -1238.57 | -215.73 | 100.40 | 2070.15 | 83.34 | 1986.80 | 26.04 | PASS |
| 7620.50† | 7177.96 | -898.35 | -2284.05 | 7298.86 | 7177.96 | -1238.57 | -215.73 | 100.95 | 2106.69 | 84.02 | 2022.67 | 26.27 | PASS |
| 7720.50† | 7262.97 | -905.51 | -2314.23 | 7383.87 | 7262.97 | -1238.57 | -215.73 | 101.92 | 2144.77 | 84.73 | 2060.03 | 26.51 | PASS |
| 7820.50† | 7339.68 | -917.65 | -2341.49 | 7460.58 | 7339.68 | -1238.57 | -215.73 | 103.26 | 2183.98 | 85.30 | 2098.68 | 26.81 | PASS |
| 7920.50† | 7405.75 | -926.53 | -2364.99 | 7526.65 | 7405.75 | -1238.57 | -215.73 | 104.90 | 2224.09 | 85.70 | 2138.39 | 27.17 | PASS |
| 8020.50† | 7459.16 | -934.32 | -2384.03 | 7580.06 | 7459.16 | -1238.57 | -215.73 | 106.79 | 2264.86 | 85.93 | 2178.92 | 27.59 | PASS |
| 8120.50† | 7498.30 | -943.50 | -2398.02 | 7619.20 | 7498.30 | -1238.57 | -215.73 | 108.85 | 2305.98 | 86.04 | 2219.94 | 28.05 | PASS |
| 8220.50† | 7521.99 | -950.85 | -2406.55 | 7642.89 | 7521.99 | -1238.57 | -215.73 | 111.02 | 2346.95 | 86.05 | 2260.90 | 28.55 | PASS |
| 8315.56 | 7529.50 | -957.24 | -2409.34 | 7650.40 | 7529.50 | -1238.57 | -215.73 | 113.12 | 2385.09 | 85.98 | 2299.11 | 29.04 | PASS |
| 8320.50† | 7529.51 | -297.30 | -2409.35 | 7650.40 | 7529.51 | -1238.57 | -215.73 | 113.22 | 2387.04 | 85.97 | 2301.07 | 29.07 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 129 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: JUDY 3-4 PWB Offset Wellpath: JUDY 3-4 (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#01 JUDY 3-4 (620'FSL & 743'FWL, SEC.34) Well: JUDY 3-4 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | | |
| 8420.50† | 7529.61 | -197.30 | -2409.53 | 7650.51 | 7529.61 | -1238.57 | -215.73 | 115.39 | 2428.38 | 85.74 | 2342.63 | 29.65 | PASS | | | |
| 8520.50† | 7529.71 | -97.30 | -2409.71 | 7650.61 | 7529.71 | -1238.57 | -215.73 | 117.48 | 2473.06 | 85.53 | 2387.53 | 30.28 | PASS | | | |
| 8620.50† | 7529.82 | 2.70 | -2409.88 | 7650.72 | 7529.82 | -1238.57 | -215.73 | 119.50 | 2520.93 | 85.29 | 2435.63 | 30.95 | PASS | | | |
| 8720.50† | 7529.92 | 102.70 | -2410.06 | 7650.82 | 7529.92 | -1238.57 | -215.73 | 121.44 | 2571.79 | 85.03 | 2486.76 | 31.68 | PASS | | | |
| 8820.50† | 7530.02 | 202.70 | -2410.24 | 7650.92 | 7530.02 | -1238.57 | -215.73 | 123.30 | 2625.48 | 84.76 | 2540.72 | 32.45 | PASS | | | |
| 8920.50† | 7530.13 | 302.70 | -2410.42 | 7651.03 | 7530.13 | -1238.57 | -215.73 | 125.08 | 2681.82 | 84.47 | 2597.36 | 33.27 | PASS | | | |
| 9020.50† | 7530.23 | 402.70 | -2410.59 | 7651.13 | 7530.23 | -1238.57 | -215.73 | 126.79 | 2740.66 | 84.17 | 2656.49 | 34.13 | PASS | | | |
| 9120.50† | 7530.33 | 502.70 | -2410.77 | 7651.23 | 7530.33 | -1238.57 | -215.73 | 128.42 | 2801.83 | 83.86 | 2717.97 | 35.03 | PASS | | | |
| 9220.50† | 7530.44 | 602.70 | -2410.95 | 7651.34 | 7530.44 | -1238.57 | -215.73 | 129.99 | 2865.18 | 83.55 | 2781.63 | 35.96 | PASS | | | |
| 9320.50† | 7530.54 | 702.70 | -2411.13 | 7651.44 | 7530.54 | -1238.57 | -215.73 | 131.49 | 2930.58 | 83.24 | 2847.34 | 36.92 | PASS | | | |
| 9420.50† | 7530.64 | 802.69 | -2411.31 | 7651.54 | 7530.64 | -1238.57 | -215.73 | 132.91 | 2997.89 | 82.94 | 2914.95 | 37.92 | PASS | | | |
| 9520.50† | 7530.75 | 902.69 | -2411.48 | 7651.65 | 7530.75 | -1238.57 | -215.73 | 134.28 | 3066.98 | 82.63 | 2984.35 | 38.95 | PASS | | | |
| 9620.50† | 7530.85 | 1002.69 | -2411.66 | 7651.75 | 7530.85 | -1238.57 | -215.73 | 135.59 | 3137.74 | 82.33 | 3055.40 | 40.00 | PASS | | | |
| 9720.50† | 7530.96 | 1102.69 | -2411.84 | 7651.85 | 7530.96 | -1238.57 | -215.73 | 136.83 | 3210.05 | 82.04 | 3128.01 | 41.07 | PASS | | | |
| 9820.50† | 7531.06 | 1202.69 | -2412.02 | 7651.96 | 7531.06 | -1238.57 | -215.73 | 138.02 | 3283.82 | 81.76 | 3202.06 | 42.17 | PASS | | | |
| 9920.50† | 7531.16 | 1302.69 | -2412.19 | 7652.06 | 7531.16 | -1238.57 | -215.73 | 139.16 | 3358.94 | 81.48 | 3277.47 | 43.29 | PASS | | | |
| 10020.50† | 7531.27 | 1402.69 | -2412.37 | 7652.17 | 7531.27 | -1238.57 | -215.73 | 140.25 | 3435.34 | 81.21 | 3354.13 | 44.43 | PASS | | | |
| 10120.50† | 7531.37 | 1502.69 | -2412.55 | 7652.27 | 7531.37 | -1238.57 | -215.73 | 141.29 | 3512.92 | 80.95 | 3431.97 | 45.59 | PASS | | | |
| 10220.50† | 7531.47 | 1602.69 | -2412.73 | 7652.37 | 7531.47 | -1238.57 | -215.73 | 142.29 | 3591.60 | 80.70 | 3510.90 | 46.77 | PASS | | | |
| 10320.50† | 7531.58 | 1702.69 | -2412.90 | 7652.48 | 7531.58 | -1238.57 | -215.73 | 143.24 | 3671.33 | 80.46 | 3590.87 | 47.96 | PASS | | | |
| 10420.50† | 7531.68 | 1802.69 | -2413.08 | 7652.58 | 7531.68 | -1238.57 | -215.73 | 144.15 | 3752.02 | 80.22 | 3671.80 | 49.16 | PASS | | | |
| 10520.50† | 7531.78 | 1902.69 | -2413.26 | 7652.68 | 7531.78 | -1238.57 | -215.73 | 145.03 | 3833.63 | 80.00 | 3753.63 | 50.38 | PASS | | | |
| 10620.50† | 7531.89 | 2002.69 | -2413.44 | 7652.79 | 7531.89 | -1238.57 | -215.73 | 145.86 | 3916.09 | 79.79 | 3836.30 | 51.61 | PASS | | | |
| 10720.50† | 7531.99 | 2102.69 | -2413.62 | 7652.89 | 7531.99 | -1238.57 | -215.73 | 146.66 | 3999.35 | 79.58 | 3919.76 | 52.85 | PASS | | | |
| 10820.50† | 7532.09 | 2202.69 | -2413.79 | 7652.99 | 7532.09 | -1238.57 | -215.73 | 147.43 | 4083.36 | 79.39 | 4003.97 | 54.10 | PASS | | | |
| 10920.50† | 7532.20 | 2302.69 | -2413.97 | 7653.10 | 7532.20 | -1238.57 | -215.73 | 148.17 | 4168.07 | 79.20 | 4088.87 | 55.36 | PASS | | | |
| 11020.50† | 7532.30 | 2402.69 | -2414.15 | 7653.20 | 7532.30 | -1238.57 | -215.73 | 148.88 | 4253.45 | 79.02 | 4174.43 | 56.63 | PASS | | | |
| 11120.50† | 7532.41 | 2502.69 | -2414.33 | 7653.31 | 7532.41 | -1238.57 | -215.73 | 149.56 | 4339.46 | 78.85 | 4260.60 | 57.91 | PASS | | | |
| 11220.50† | 7532.51 | 2602.69 | -2414.50 | 7653.41 | 7532.51 | -1238.57 | -215.73 | 150.21 | 4426.05 | 78.69 | 4347.36 | 59.19 | PASS | | | |
| 11320.50† | 7532.61 | 2702.69 | -2414.68 | 7653.51 | 7532.61 | -1238.57 | -215.73 | 150.84 | 4513.20 | 78.54 | 4434.66 | 60.48 | PASS | | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 130 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: JUDY 3-4 PWB Offset Wellpath: JUDY 3-4 (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#01 JUDY 3-4 (620'FSL & 743'FWL, SEC.34) Well: JUDY 3-4 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|--|--|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status | | |
| 11420.50† | 7532.72 | 2802.69 | -2414.86 | 7653.62 | 7532.72 | -1238.57 | -215.73 | 151.45 | 4600.87 | 78.39 | 4522.47 | 61.78 | PASS | | |
| 11520.50† | 7532.82 | 2902.69 | -2415.04 | 7653.72 | 7532.82 | -1238.57 | -215.73 | 152.03 | 4689.03 | 78.26 | 4610.78 | 63.08 | PASS | | |
| 11620.50† | 7532.92 | 3002.69 | -2415.21 | 7653.82 | 7532.92 | -1238.57 | -215.73 | 152.59 | 4777.66 | 78.13 | 4699.54 | 64.39 | PASS | | |
| 11720.50† | 7533.03 | 3102.69 | -2415.39 | 7653.93 | 7533.03 | -1238.57 | -215.73 | 153.13 | 4866.73 | 78.00 | 4788.73 | 65.70 | PASS | | |
| 11820.50† | 7533.13 | 3202.69 | -2415.57 | 7654.03 | 7533.13 | -1238.57 | -215.73 | 153.65 | 4956.22 | 77.89 | 4878.33 | 67.01 | PASS | | |
| 11920.50† | 7533.23 | 3302.69 | -2415.75 | 7654.13 | 7533.23 | -1238.57 | -215.73 | 154.15 | 5046.10 | 77.78 | 4968.33 | 68.33 | PASS | | |
| 12020.50† | 7533.34 | 3402.69 | -2415.92 | 7654.24 | 7533.34 | -1238.57 | -215.73 | 154.64 | 5136.36 | 77.67 | 5058.69 | 69.65 | PASS | | |
| 12120.50† | 7533.44 | 3502.69 | -2416.10 | 7654.34 | 7533.44 | -1238.57 | -215.73 | 155.10 | 5226.97 | 77.58 | 5149.40 | 70.97 | PASS | | |
| 12220.50† | 7533.55 | 3602.69 | -2416.28 | 7654.44 | 7533.55 | -1238.57 | -215.73 | 155.56 | 5317.92 | 77.48 | 5240.43 | 72.30 | PASS | | |
| 12320.50† | 7533.65 | 3702.69 | -2416.46 | 7654.55 | 7533.65 | -1238.57 | -215.73 | 155.99 | 5409.19 | 77.40 | 5331.79 | 73.63 | PASS | | |
| 12420.50† | 7533.75 | 3802.69 | -2416.64 | 7654.65 | 7533.75 | -1238.57 | -215.73 | 156.42 | 5500.76 | 77.32 | 5423.44 | 74.96 | PASS | | |
| 12520.50† | 7533.86 | 3902.69 | -2416.81 | 7654.76 | 7533.86 | -1238.57 | -215.73 | 156.82 | 5592.62 | 77.24 | 5515.37 | 76.29 | PASS | | |
| 12620.50† | 7533.96 | 4002.69 | -2416.99 | 7654.86 | 7533.96 | -1238.57 | -215.73 | 157.22 | 5684.75 | 77.17 | 5607.58 | 77.62 | PASS | | |
| 12720.50† | 7534.06 | 4102.69 | -2417.17 | 7654.96 | 7534.06 | -1238.57 | -215.73 | 157.60 | 5777.15 | 77.11 | 5700.04 | 78.95 | PASS | | |
| 12820.50† | 7534.17 | 4202.69 | -2417.35 | 7655.07 | 7534.17 | -1238.57 | -215.73 | 157.97 | 5869.79 | 77.05 | 5792.74 | 80.28 | PASS | | |
| 12920.50† | 7534.27 | 4302.69 | -2417.52 | 7655.17 | 7534.27 | -1238.57 | -215.73 | 158.33 | 5962.67 | 76.99 | 5885.68 | 81.62 | PASS | | |
| 13020.50† | 7534.37 | 4402.69 | -2417.70 | 7655.27 | 7534.37 | -1238.57 | -215.73 | 158.68 | 6055.78 | 76.94 | 5978.84 | 82.95 | PASS | | |
| 13120.50† | 7534.48 | 4502.69 | -2417.88 | 7655.38 | 7534.48 | -1238.57 | -215.73 | 159.01 | 6149.11 | 76.90 | 6072.21 | 84.28 | PASS | | |
| 13199.97 | 7534.56 | 4582.16 | -2418.02 | 7655.46 | 7534.56 | -1238.57 | -215.73 | 159.28 | 6223.43 | 76.86 | 6146.56 | 85.34 | PASS | | |
| 13220.50† | 7534.58 | 4602.69 | -2418.13 | 7655.48 | 7534.58 | -1238.57 | -215.73 | 159.34 | 6242.67 | 76.85 | 6165.82 | 85.62 | PASS | | |
| 13320.50† | 7534.68 | 4702.65 | -2420.77 | 7655.58 | 7534.68 | -1238.57 | -215.73 | 159.64 | 6337.22 | 76.81 | 6260.41 | 86.97 | PASS | | |
| 13420.50† | 7534.79 | 4802.45 | -2426.90 | 7655.69 | 7534.79 | -1238.57 | -215.73 | 159.90 | 6432.98 | 76.77 | 6356.22 | 88.33 | PASS | | |
| 13476.50 | 7534.85 | 4858.23 | -2431.85 | 7655.74 | 7534.85 | -1238.57 | -215.73 | 160.02 | 6487.08 | 76.75 | 6410.34 | 89.10 | PASS | | |
| 13520.50† | 7534.89 | 4902.02 | -2436.16 | 7655.79 | 7534.89 | -1238.57 | -215.73 | 160.12 | 6529.72 | 76.73 | 6452.99 | 89.71 | PASS | | |
| 13620.50† | 7534.99 | 5001.54 | -2445.98 | 7655.89 | 7534.99 | -1238.57 | -215.73 | 160.33 | 6626.69 | 76.69 | 6550.00 | 91.09 | PASS | | |
| 13720.50† | 7535.10 | 5101.06 | -2455.79 | 7655.99 | 7535.10 | -1238.57 | -215.73 | 160.54 | 6723.75 | 76.66 | 6647.09 | 92.46 | PASS | | |
| 13820.50† | 7535.20 | 5200.57 | -2465.61 | 7656.10 | 7535.20 | -1238.57 | -215.73 | 160.74 | 6820.89 | 76.63 | 6744.26 | 93.83 | PASS | | |
| 13920.50† | 7535.30 | 5300.09 | -2475.42 | 7656.20 | 7535.30 | -1238.57 | -215.73 | 160.94 | 6918.12 | 76.61 | 6841.51 | 95.20 | PASS | | |
| 14020.50† | 7535.40 | 5399.61 | -2485.24 | 7656.30 | 7535.40 | -1238.57 | -215.73 | 161.13 | 7015.42 | 76.59 | 6938.83 | 96.57 | PASS | | |
| 14120.50† | 7535.51 | 5499.12 | -2495.05 | 7656.41 | 7535.51 | -1238.57 | -215.73 | 161.31 | 7112.80 | 76.58 | 7036.22 | 97.93 | PASS | | |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 131 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: JUDY 3-4 PWB Offset Wellpath: JUDY 3-4 (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#01 JUDY 3-4 (620'FSL & 743'FWL, SEC.34) Well: JUDY 3-4 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|--------------|----------------|---------------|----------------|-----------------|-------------------|------------------|-------------------|---------------------|----------------|----------------------|-----------|-------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 14220.50† | 7535.61 | 5598.64 | -2504.87 | 7656.51 | 7535.61 | -1238.57 | -215.73 | 161.49 | 7210.25 | 76.56 | 7133.68 | 99.29 | PASS |
| 14221.87 | 7535.61 | 5600.00 | -2505.00 | 7656.51 | 7535.61 | -1238.57 | -215.73 | 161.49 | 7211.58 | 76.56 | 7135.02 | 99.31 | PASS |
| 14320.50† | 7535.71 | 5698.31 | -2512.99 | 7656.61 | 7535.71 | -1238.57 | -215.73 | 161.68 | 7307.37 | 76.55 | 7230.82 | 100.64 | PASS |
| 14420.50† | 7535.81 | 5798.19 | -2517.63 | 7656.71 | 7535.81 | -1238.57 | -215.73 | 161.89 | 7403.70 | 76.55 | 7327.16 | 101.98 | PASS |
| 14520.50† | 7535.92 | 5898.18 | -2518.78 | 7656.82 | 7535.92 | -1238.57 | -215.73 | 162.12 | 7499.16 | 76.55 | 7422.61 | 103.29 | PASS |
| 14581.38 | 7535.98 | 5959.05 | -2517.77 | 7656.88 | 7535.98 | -1238.57 | -215.73 | 162.26 | 7556.80 | 76.56 | 7480.25 | 104.07 | PASS |
| 14620.50† | 7536.02 | 5998.16 | -2516.71 | 7656.92 | 7536.02 | -1238.57 | -215.73 | 162.36 | 7593.73 | 76.56 | 7517.17 | 104.58 | PASS |
| 14720.50† | 7536.12 | 6098.12 | -2513.99 | 7657.02 | 7536.12 | -1238.57 | -215.73 | 162.61 | 7688.24 | 76.57 | 7611.67 | 105.86 | PASS |
| 14820.50† | 7536.23 | 6198.08 | -2511.27 | 7657.13 | 7536.23 | -1238.57 | -215.73 | 162.85 | 7782.89 | 76.60 | 7706.29 | 107.13 | PASS |
| 14920.50† | 7536.33 | 6298.05 | -2508.55 | 7657.23 | 7536.33 | -1238.57 | -215.73 | 163.08 | 7877.67 | 76.62 | 7801.05 | 108.40 | PASS |
| 15020.50† | 7536.43 | 6398.01 | -2505.83 | 7657.33 | 7536.43 | -1238.57 | -215.73 | 163.31 | 7972.58 | 76.65 | 7895.93 | 109.66 | PASS |
| 15120.50† | 7536.54 | 6497.97 | -2503.11 | 7657.44 | 7536.54 | -1238.57 | -215.73 | 163.53 | 8067.61 | 76.68 | 7990.93 | 110.93 | PASS |
| 15220.50† | 7536.64 | 6597.93 | -2500.40 | 7657.54 | 7536.64 | -1238.57 | -215.73 | 163.75 | 8162.76 | 76.71 | 8086.05 | 112.19 | PASS |
| 15320.50† | 7536.74 | 6697.90 | -2497.68 | 7657.64 | 7536.74 | -1238.57 | -215.73 | 163.96 | 8258.02 | 76.74 | 8181.28 | 113.44 | PASS |
| 15420.50† | 7536.85 | 6797.86 | -2494.96 | 7657.75 | 7536.85 | -1238.57 | -215.73 | 164.17 | 8353.39 | 76.78 | 8276.61 | 114.70 | PASS |
| 15520.50† | 7536.95 | 6897.82 | -2492.24 | 7657.85 | 7536.95 | -1238.57 | -215.73 | 164.37 | 8448.87 | 76.82 | 8372.06 | 115.95 | PASS |
| 15620.50† | 7537.05 | 6997.79 | -2489.52 | 7657.95 | 7537.05 | -1238.57 | -215.73 | 164.57 | 8544.46 | 76.86 | 8467.60 | 117.20 | PASS |
| 15720.50† | 7537.16 | 7097.75 | -2486.80 | 7658.06 | 7537.16 | -1238.57 | -215.73 | 164.76 | 8640.14 | 76.90 | 8563.24 | 118.44 | PASS |
| 15820.50† | 7537.26 | 7197.71 | -2484.08 | 7658.16 | 7537.26 | -1238.57 | -215.73 | 164.95 | 8735.92 | 76.94 | 8658.98 | 119.68 | PASS |
| 15920.50† | 7537.36 | 7297.68 | -2481.36 | 7658.26 | 7537.36 | -1238.57 | -215.73 | 165.14 | 8831.80 | 76.99 | 8754.81 | 120.92 | PASS |
| 16020.50† | 7537.47 | 7397.64 | -2478.64 | 7658.37 | 7537.47 | -1238.57 | -215.73 | 165.32 | 8927.76 | 77.04 | 8850.73 | 122.16 | PASS |
| 16120.50† | 7537.57 | 7497.60 | -2475.93 | 7658.47 | 7537.57 | -1238.57 | -215.73 | 165.50 | 9023.82 | 77.09 | 8946.73 | 123.39 | PASS |
| 16220.50† | 7537.68 | 7597.56 | -2473.21 | 7658.57 | 7537.68 | -1238.57 | -215.73 | 165.67 | 9119.95 | 77.14 | 9042.82 | 124.61 | PASS |
| 16320.50† | 7537.78 | 7697.53 | -2470.49 | 7658.68 | 7537.78 | -1238.57 | -215.73 | 165.84 | 9216.17 | 77.19 | 9138.98 | 125.84 | PASS |
| 16420.50† | 7537.88 | 7797.49 | -2467.77 | 7658.78 | 7537.88 | -1238.57 | -215.73 | 166.01 | 9312.47 | 77.25 | 9235.23 | 127.06 | PASS |
| 16520.50† | 7537.99 | 7897.45 | -2465.05 | 7658.88 | 7537.99 | -1238.57 | -215.73 | 166.17 | 9408.85 | 77.30 | 9331.55 | 128.27 | PASS |
| 16620.50† | 7538.09 | 7997.42 | -2462.33 | 7658.99 | 7538.09 | -1238.57 | -215.73 | 166.33 | 9505.30 | 77.36 | 9427.94 | 129.48 | PASS |
| 16720.50† | 7538.19 | 8097.38 | -2459.61 | 7659.09 | 7538.19 | -1238.57 | -215.73 | 166.49 | 9601.83 | 77.42 | 9524.40 | 130.69 | PASS |
| 16820.50† | 7538.30 | 8197.34 | -2456.89 | 7659.19 | 7538.30 | -1238.57 | -215.73 | 166.64 | 9698.42 | 77.49 | 9620.93 | 131.89 | PASS |
| 16920.50† | 7538.40 | 8297.31 | -2454.17 | 5516.41 | 5421.47 | -992.74 | -184.11 | 166.27 | 9794.88 | 76.46 | 9718.42 | 135.10 | PASS |

Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 132 of 133

REFERENCE WELLPATH IDENTIFICATION

| | | | |
|----------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

CLEARANCE DATA - Offset Wellbore: JUDY 3-4 PWB Offset Wellpath: JUDY 3-4 (REV-A.0) PWP Offset Wellbore Status: Plan: Planned

| Facility: SEC.34-T01N-R65W Slot: SLOT#01 JUDY 3-4 (620'FSL & 743'FWL, SEC.34) Well: JUDY 3-4 Threshold Value=1.00 † = interpolated, ‡ = extrapolated station | | | | | | | | | | | | | |
|--|-----------------|-------------------|------------------|-------------------|--------------------|----------------------|---------------------|-------------------------|---------------------------|----------------------|----------------------------|--------------|----------------|
| Ref MD [ft] | Ref TVD [ft] | Ref North [ft] | Ref East [ft] | Offset MD [ft] | Offset TVD [ft] | Offset North [ft] | Offset East [ft] | Horiz Bearing [°] | C-C Clear Dist [ft] | Rule MASD [ft] | Available Space [ft] | Sep Ratio | Rule Status |
| 17020.50† | 7538.50 | 8397.27 | -2451.46 | 5493.55 | 5399.23 | -987.51 | -183.44 | 166.41 | 9889.11 | 76.63 | 9812.48 | 136.07 | PASS |
| 17120.50† | 7538.61 | 8497.23 | -2448.74 | 5470.69 | 5376.98 | -982.28 | -182.77 | 166.56 | 9983.40 | 76.81 | 9906.59 | 137.03 | PASS |
| 17220.50† | 7538.71 | 8597.19 | -2446.02 | 5447.82 | 5354.74 | -977.04 | -182.09 | 166.70 | 10077.75 | 76.99 | 10000.76 | 137.98 | PASS |
| 17320.50† | 7538.81 | 8697.16 | -2443.30 | 5424.96 | 5332.49 | -971.81 | -181.42 | 166.83 | 10172.16 | 77.18 | 10094.99 | 138.92 | PASS |
| 17420.50† | 7538.92 | 8797.12 | -2440.58 | 5402.10 | 5310.25 | -966.58 | -180.75 | 166.97 | 10266.63 | 77.37 | 10189.26 | 139.85 | PASS |
| 17520.50† | 7539.02 | 8897.08 | -2437.86 | 5379.24 | 5288.00 | -961.34 | -180.07 | 167.10 | 10361.14 | 77.56 | 10283.59 | 140.78 | PASS |
| 17620.50† | 7539.12 | 8997.05 | -2435.14 | 5356.37 | 5265.76 | -956.11 | -179.40 | 167.23 | 10455.71 | 77.75 | 10377.96 | 141.69 | PASS |
| 17720.50† | 7539.23 | 9097.01 | -2432.42 | 5333.51 | 5243.51 | -950.88 | -178.73 | 167.36 | 10550.33 | 77.95 | 10472.38 | 142.59 | PASS |
| 17820.50† | 7539.33 | 9196.97 | -2429.70 | 5310.65 | 5221.27 | -945.64 | -178.05 | 167.48 | 10645.00 | 78.15 | 10566.85 | 143.48 | PASS |
| 17920.50† | 7539.43 | 9296.94 | -2426.99 | 5287.79 | 5199.02 | -940.41 | -177.38 | 167.61 | 10739.72 | 78.35 | 10661.37 | 144.37 | PASS |
| 17985.90 | 7539.50 | 9362.31 | -2425.21 | 5272.84 | 5184.47 | -936.99 | -176.94 | 167.69 | 10801.68 | 78.48 | 10723.20 | 144.94 | PASS |

POSITIONAL UNCERTAINTY - Offset Wellbore: JUDY 3-4 PWB Offset Wellpath: JUDY 3-4 (REV-A.0) PWP

| | | | | |
|-----------------------------------|------------|---------|----------|---------|
| Slot Surface Uncertainty @1SD | Horizontal | 0.100ft | Vertical | 1.000ft |
| Facility Surface Uncertainty @1SD | Horizontal | 8.200ft | Vertical | 3.000ft |

SURVEY PROGRAM - Offset Wellbore: JUDY 3-4 PWB Offset Wellpath: JUDY 3-4 (REV-A.0) PWP

| Start MD [ft] | End MD [ft] | Positional Uncertainty Model | Log Name/Comment | Wellbore |
|---------------|-------------|--|------------------|--------------|
| 17.00 | 1500.00 | BHI NaviTrak (Rotating+Axial Corr) | | JUDY 3-4 PWB |
| 1500.00 | 7698.40 | BHI AutoTrak Curve (Axial Corr, Short spacing) | | JUDY 3-4 PWB |



Closest Approach Clearance Report

BUFORD 33-4-4L (REV-B.0) PWP
SPE WPTS Stop Drilling HSE Risk (2017)
Page 133 of 133



| REFERENCE WELLPATH IDENTIFICATION | | | |
|-----------------------------------|--|-----------|--------------------|
| Operator | CONFLUENCE RESOURCES | Well | BUFORD 33-4-4L |
| Field | WELD COUNTY (NAD83, TRUE NORTH) | API/Legal | |
| Facility | SEC.34-T01N-R65W | Wellbore | BUFORD 33-4-4L PWB |
| Slot | SLOT#04 BUFORD 33-4-4L (770'FSL & 819'FWL, SEC.34) | | |

| OFFSET WELLPATH REFERENCE - Offset Wellbore: JUDY 3-4 PWB Offset Wellpath: JUDY 3-4 (REV-A.0) PWP | |
|--|---|
| MD Reference: RIG (17'KB) (RKB) | Offset TVD & local coordinates use Reference Wellpath settings (See WELLPATH DATUM on page 1 of this report) |
| Ellipse Start MD | 17.00ft |