

Cement Verification Report - Cementer's Well Service, Inc.

P.O. BOX 336220 • GREELEY, CO 80633 • (970) 353-7299 • FAX (970) 353-7712

COGCC Operator Guidance

RULE #308.A.B(2)A.ii



CLIENT: PDC - Petroleum Development Corp	Cementor's FIELD TICKET #	210171
--	------------------------------	--------

Requested Operator Guidance:

1) Well Name & Number	Lease	Vega	Well No.	8N
2) Well API Number	05-1234-8467-0000			
3) Job Date	8/28/20	Time on	1:00	24 hr time
4) Job Type	New Well Surface			
5) Cementing Company	Cementor's Well Service, Inc	Contact	Nate Kvamme - 303-324-4296	
6) Ambient conditions	clear / rain / snow / other		temp deg F	
7) Slurry Description				
a) Purpose	Surface - 9 5/8" CSG, 12 1/4" hole			
b) Cement Class	Type I / II			
c) Cement Yield	1.61	cuft / sk		
d) Cement Density	13.9	PPG		
e) Number of sks	530	sks (94# equiv)		
f) Cement Volume (dry)	530	cuft (ft^3)		
g) Mix Fluid Type				
Water / Cement	8.5	Gal / sk		
h) Slurry mixed	151.9	BBLs slurry		
i) Additives used	1.50%	CaCl2		
	3.00%	Bentonite		
j) Displacement Fluid Vol	127.9	BBLs H2O		
k) Method of Placement				
l) Set Depth	1,695	feet (ft)		
m) Stage tool depth	n/a			
n) Float Collar Depth	1,655	feet (ft)		
o) Designed Top of Cement	n/a	to surface		
p) Centralizer depths	81; 285; 490; 695; 899; 1,105; 1,309; 1,513			feet (ft)
8) Charts - (pressure, density, pump rate)				
Landed Plug @	700	psi	Final Lift Pressure @	500 psi
Cement Density (as weighed during job) @	14.0 PPG			
9) Job notes				
a) Plug down	<input checked="" type="radio"/> Y / <input type="radio"/> N	Time	2:30	24 hr time
b) Floats held	<input checked="" type="radio"/> Y / <input type="radio"/> N			
c) Full Returns	<input checked="" type="radio"/> Y / <input type="radio"/> N	Lost Circulation	<input checked="" type="radio"/> Y / <input type="radio"/> N	
d) Cement to surface	<input checked="" type="radio"/> Y / <input type="radio"/> N	25	BBLs to surface	
e) If no returns, top off	BBLs			
f) Top off detail				