RELIANCE
OILFIELD SERVICES

# Radial Cement Bond
# Gamma Ray
# Casing Collar Log

Company TEP Rocky Mountain LLC
Well Chevron GM 632-19
Field Grand Valley
County Garfield State Colorado
Location: API # : 05-045-24361
SEC 20 TWP 6S RGE 96W
Other Services: --

| | | | |
|---|---|---|---|
| Permanent Datum | Ground Level | Elevation 5752.1' | Elevation<br>K.B. 5776.1'<br>D.F. ---<br>G.L. 5752.1' |
| Log Measured From | Kelly Bushing | 24 FT | |
| Drilling Measured From | Kelly Bushing | | |

Company TEP Rocky Mountain LLC
Well Chevron GM 632-19
Field Grand Valley
County Garfield
State Colorado

| | |
|---|---|
| Date | 01-FEB-2021 |
| Run Number | One |
| Depth Driller | 7786 FT |
| Depth Logger | 7707 FT |
| Bottom Logged Interval | 7695 FT |
| Top Log Interval | Surface |
| Open Hole Size | 8.750" |
| Type Fluid | Water |
| Density / Viscosity | 8.34 lb/gal |
| Max. Recorded Temp. | 230°F |
| Estimated Cement Top | See Log |
| Time Well Ready | ROA |
| Time Logger on Bottom | 15:00 |
| Equipment Number | HD-0331 |
| Location | Grand Junction, CO |
| Recorded By | Z. Fisher |
| Witnessed By | -- |

| Borehole Record | | | | Tubing Record | | | |
|---|---|---|---|---|---|---|---|
| Run Number | Bit | From | To | Size | Weight | From | To |
| | | | | | | | |
| | | | | | | | |

| Casing Record | Size (in) | Wgt (lbs/Ft) | Grade | Top | Bottom |
|---|---|---|---|---|---|
| Surface Casing | 9 5/8 | 36 | J-55 | Surface | 1028 FT |
| Intermediate #1 | 4 1/2 | 11.6 | P-110 | Surface | 7745 FT |
| Intermediate #2 | | | | | |
| Liner | | | | | |

<<< Fold Here >>>

All interpretations are opinions based on inferences from electrical or other measurements and we cannot and do not guarantee the accuracy or correctness of any interpretation, and we shall not, except in the case of gross or willful negligence on our part, be liable or responsible for any loss, costs, damages, or expenses incurred or sustained by anyone resulting from any interpretation made by any of our officers, agents or employees. These interpretations are also subject to our general terms and conditions set out in our current Price Schedule.

## Comments

Log ran as per customer request
Depth referenced to Kelly Bushing at 24 FT
Marker Joint logged from 4564 - 4586 FT
Recorded with 0 PSI Surface Induced Pressure

Thank you for choosing Reliance Oilfield Services, LLC!

---

RELIANCE
OILFIELD SERVICES

## Main Pass

Recorded With 0 PSI Surface Induced Pressure

| | |
|---|---|
| Database File | tep\new folder\tep_chevron gm 632-19_rbl_02-01-21.db |
| Dataset Pathname | main.1 |
| Presentation Format | ros_radii_tep |
| Dataset Creation | Wed Feb 03 13:22:31 2021 |
| Charted by | Depth in Feet scaled 1:240 |

| Gamma Ray | | 3' Amplitude | 5' Variable Density Log | Sector Map | Average Amplitude |
|---|---|---|---|---|---|
| 0 (GAPI) 200 | | 0 (mV) 100 | 200 (usec) 1200 | | 0 150 |
| Casing Collar Locator | | 3' Amplitude x 5 | | | Mimimum Amplitude |
| Line Speed | | 0 (mV) 20 | | | 0 150 |
| -150 (ft/min) 150 | | 3' Travel Time | | | Maximum Amplitude |
| Line Tension | | 300 (usec) 200 | | | 0 150 |
| 0 (lb) 2000 | | | | | |
| Differential Temperature | | | | | |
| -2 (degF) 2 | | | | | |
| Temperature | | | | | |
| 0 (degF) 20 | | | | | |

142.6
3800
144.6
3900
146.5
4000
148.6
4100
150.3
4200
152.6
4300
4400
4500
Marker Joint
4600
4700
4800
4900
5000
5100
5200
5300
5400
5500
5600
5700
5800
5900
6000
6100
6200
6300
6400
6500
6600
6700
6800
6900
7000
7100
7200
7300
217.7
7400
223.4
7500
t (°F)
228.3
7600
dt(°F)
t (°F)
LTEN
LSPD
GR
CCL
3' Amp
3' Ampx5
3' TT
Sectors
7700

| | | | | |
|---|---|---|---|---|
| Gamma Ray<br>0 (GAPI) 200 | 3' Amplitude<br>0 (mV) 100 | 5' Variable Density Log<br>200 (usec) 1200 | Sector Map | Average Amplitude<br>0 150 |
| *Casing Collar Locator* | 3' Amplitude x 5<br>0 (mV) 20 | | | Mimimum Amplitude<br>0 150 |
| Line Speed<br>-150 (ft/min) 150 | 3' Travel Time<br>300 (usec) 200 | | | Maximum Amplitude<br>0 150 |
| Line Tension<br>0 (lb) 2000 | | | | |
| Differential Temperature<br>-2 (degF) 2 | | | | |
| Temperature<br>0 (degF) 20 | | | | |

**RELIANCE**
OILFIELD SERVICES

## Repeat Pass

Recorded With 0 PSI Surface Induced Pressure

| | |
|---|---|
| Database File | tep\new folder\tep_chevron gm 632-19_rbl_02-01-21.db |
| Dataset Pathname | repeat.2 |
| Presentation Format | ros_radii_tep |
| Dataset Creation | Wed Feb 03 13:40:50 2021 |
| Charted by | Depth in Feet scaled 1:240 |

| | | | | |
|---|---|---|---|---|
| Gamma Ray<br>0 (GAPI) 200 | 3' Amplitude<br>0 (mV) 100 | 5' Variable Density Log<br>200 (usec) 1200 | Sector Map | Average Amplitude<br>0 150 |
| Line Speed<br>-150 (ft/min) 150 | 3' Amplitude x 5<br>0 (mV) 20 | | | Mimimum Amplitude<br>0 150 |
| Line Tension<br>0 (lb) 2000 | 3' Travel Time<br>300 (usec) 200 | | | Maximum Amplitude<br>0 150 |
| Differential Temperature<br>-2 (degF) 2 | | | | |
| Temperature<br>0 (degF) 20 | | | | |



| | | | | |
|---|---|---|---|---|
| Gamma Ray<br>0 (GAPI) 200 | 3' Amplitude<br>0 (mV) 100 | 5' Variable Density Log<br>200 (usec) 1200 | Sector Map | Average Amplitude<br>0 150 |
| Line Speed<br>-150 (ft/min) 150 | 3' Amplitude x 5<br>0 (mV) 20 | | | Mimimum Amplitude<br>0 150 |
| Line Tension<br>0 (lb) 2000 | 3' Travel Time<br>300 (usec) 200 | | | Maximum Amplitude<br>0 150 |
| Differential Temperature<br>-2 (degF) 2 | | | | |
| Temperature<br>0 (degF) 20 | | | | |

| Sensor | Offset (ft) | Schematic | Description | Length (ft) | O.D. (in) | Weight (lb) |
|---|---|---|---|---|---|---|
| | |  | Titan CHD-14375 GO<br>Titan 1-7/16" Assembled Electric Cable Head with 1" Fishing Neck | 1.03 | 1.44 | 3.60 |
| | | | BTA-MUD<br>BTA 2-3/4" Roller 6 Arm Centralizer with Reversible Ends | 2.92 | 2.72 | 25.00 |
| TEMP | 14.19 | | | | | |
| | | | Probe Radii-2750 RBT (ROFS-RBT-0002)<br>Probe 2-3/4" Radial Cement Bond Tool with Integral Temperature Sub | 9.39 | 2.75 | 105.00 |
| WVFS8 | 11.96 | | | | | |
| WVFS7 | 11.96 | | | | | |
| WVFS6 | 11.96 | | | | | |
| WVFS5 | 11.96 | | | | | |
| WVFS4 | 11.96 | | | | | |
| WVFS3 | 11.96 | | | | | |
| WVFS2 | 11.96 | | | | | |
| WVFS1 | 11.96 | | | | | |
| WVFCAL | 11.96 | | | | | |
| WVF3FT | 11.96 | | | | | |
| WVF5FT | 10.96 | | | | | |
| | | | BTA-MUD<br>BTA 2-3/4" Roller 6 Arm Centralizer with Reversible Ends | 2.92 | 2.72 | 25.00 |
| CCL | 3.88 | | | | | |
| | | | Probe GR-CCL ANL-2750 A (FW1305-083)<br>Probe 2.75" Analog 4 Channel Pulse Gamma Ray/CCL Combined | 4.54 | 2.75 | 55.00 |
| GR | 1.14 | | | | | |
| | | | GO BN-14375<br>GO 1-7/16" Bull Nose with Go Box Top | 0.25 | 1.44 | 1.00 |

| | |
|---|---|
| Dataset: | tep_chevron gm 632-19_rbl_02-01-21.db: field/well/run1/main.1 |
| Total length: | 21.05 ft |
| Total weight: | 214.60 lb |
| O.D.: | 2.75 in |

## Calibration Report

| | |
|---|---|
| Database File | c:\programdata\warrior\data\tep\new folder\tep_chevron gm 632-19_rbl_02-01-21.db |
| Dataset Pathname | main.1 |
| Dataset Creation | Wed Feb 03 13:22:31 2021 |

### Gamma Ray Calibration Report

| | | |
|---|---|---|
| Serial Number: | FW1305-083 | |
| Tool Model: | 2750 A | |
| Performed: | Sun Nov 12 05:37:57 2017 | |
| Calibrator Value: | 637.0 | GAPI |
| Background Reading: | 95.7 | cps |
| Calibrator Reading: | 982.0 | cps |
| Sensitivity: | 0.7188 | GAPI/cps |

### Segmented Cement Bond Log Calibration Report

| | | |
|---|---|---|
| Serial Number: | ROFS-RBT-0002 | |
| Tool Model: | 2750 RBT | |
| Calibration Casing Diameter: | 4.500 | in |
| Calibration Depth: | 31.479 | ft |

Master Calibration, performed (Derived):

| | Raw (v) | | Calibrated (mv) | | Results | |
|---|---|---|---|---|---|---|
| | Zero | Cal | Zero | Cal | Gain | Offset |
| 3' | 0.004 | 0.642 | 0.800 | 81.196 | 125.994 | 0.341 |
| CAL | 0.003 | 0.764 | | | | |
| 5' | 0.007 | 0.674 | 0.800 | 81.196 | 120.488 | 0.005 |
| SUM | | | | | | |
| S1 | 0.003 | 0.581 | 0.000 | 100.000 | 173.049 | -0.525 |
| S2 | 0.010 | 0.618 | 0.000 | 100.000 | 164.350 | -1.601 |
| S3 | 0.008 | 0.656 | 0.000 | 100.000 | 154.266 | -1.266 |
| S4 | 0.006 | 0.692 | 0.000 | 100.000 | 145.735 | -0.905 |
| S5 | 0.006 | 0.683 | 0.000 | 100.000 | 147.612 | -0.892 |
| S6 | 0.005 | 0.654 | 0.000 | 100.000 | 154.020 | -0.737 |
| S7 | 0.004 | 0.612 | 0.000 | 100.000 | 164.629 | -0.740 |
| S8 | 0.007 | 0.606 | 0.000 | 100.000 | 166.820 | -1.170 |

Internal Reference Calibration, performed (Not Performed):

| | Raw (v) | | Calibrated (v) | | Results | |
|---|---|---|---|---|---|---|
| | Zero | Cal | Zero | Cal | Gain | Offset |
| CAL | 0.000 | 0.000 | 0.003 | 0.764 | 1.000 | 0.000 |

Air Zero Calibration, performed Mon Feb 1 11:12:18 2021:

| | Raw (v) | Calibrated (v) | Results |
|---|---|---|---|
| | Zero | Zero | Offset |
| 3' | 0.000 | 0.000 | 0.000 |
| 5' | 0.000 | 0.000 | 0.000 |
| SUM | | | |
| S1 | 0.000 | 0.000 | 0.000 |
| S2 | 0.000 | 0.000 | 0.000 |
| S3 | 0.000 | 0.000 | 0.000 |
| S4 | 0.000 | 0.000 | 0.000 |
| S5 | 0.000 | 0.000 | 0.000 |
| S6 | 0.000 | 0.000 | 0.000 |
| S7 | 0.000 | 0.000 | 0.000 |
| S8 | 0.000 | 0.000 | 0.000 |

### Temperature Calibration Report

| | | |
|---|---|---|
| Serial Number: | ROFS-RBT-0002 | |
| Tool Model: | 2750 RBT | |
| Performed: | Wed Oct 14 10:20:48 2020 | |
| | Reference | Reading |
| Low Reference: | 100.00 degF | 109.31 degF |
| High Reference: | 235.00 degF | 267.00 degF |
| Gain: | 0.86 | |
| Offset: | 6.43 | |
| Delta Spacing | 1 | |

**RELIANCE**
OILFIELD SERVICES

| | |
|---|---|
| Company | TEP Rocky Mountain LLC |
| Well | Chevron GM 632-19 |
| Field | Grand Valley |
| County | Garfield |
| State | Colorado |