

Cement Verification Report - Cementer's Well Service, Inc.

P.O. BOX 336220 • GREELEY, CO 80633 • (970) 353-7299 • FAX (970) 353-7712

COGCC Operator Guidance

RULE #308.A.B(2)A.ii



CLIENT: PDC - Petroleum Development Corp	Cementer's FIELD TICKET #	300011
--	------------------------------	--------

Requested Operator Guidance:

1) Well Name & Number	Lease	Erwin	Well No.	6N
2) Well API Number	05-123-49377 -			
3) Job Date	11/15/20	Time on	18:30	24 hr time
4) Job Type	New Well Surface			
5) Cementing Company	Cementer's Well Service, Inc	Contact	Nate Kvamme - 303-324-4296	
6) Ambient conditions	clear / rain / snow / other	-	temp deg F	
7) Slurry Description				
a) Purpose	Surface - 9 5/8" CSG, 12 1/4" hole			
b) Cement Class	Type I / II			
c) Cement Yield	1.61	cuft / sk		
d) Cement Density	13.9	PPG		
e) Number of sks	540	sks (94# equiv)		
f) Cement Volume (dry)	540	cuft (ft^3)		
g) Mix Fluid Type				
Water / Cement	8.5	Gal / sk		
h) Slurry mixed	154.8	BBLs slurry		
i) Additives used	1.50%	CaCl2	3.00%	Bentonite
Total Water Used	285.5	BBLs H2O		
j) Displacement Fluid Vol	126.2	BBLs H2O		
k) Method of Placement				
l) Set Depth	1,689	feet (ft)		
m) Stage tool depth	n/a			
n) Float Collar Depth	1,633	feet (ft)		
o) Designed Top of Cement	n/a	to surface		
p) Centralizer depths	- feet (ft)			
8) Charts - (pressure, density, pump rate)				
Landed Plug @	900	psi	Final Lift Pressure @	650 psi
Cement Density (as weighed during job) @	14.0	PPG		
9) Job notes				
a) Plug down	Y/N	Time	22:00	24 hr time
b) Floats held	Y/N			
c) Full Returns	Y/N	Lost Circulation	Y/N	
d) Cement to surface	Y/N	26.0	BBLs to surface	
e) If no returns, top off	BBLs			
f) Top off detail				



Centralizer Depths

Well Name: Erwin 6N

Surface, Set Depth: 1,688.5ftKB

API 05123493770000		Surface Legal Location SWSE 27 5N 64W		Field Name Wattenberg		State CO		Well Configuration Type Horizontal					
Ground Elevation (ft) 4,640.00		Original KB Elevation (ft) 4,668.00		KB-Ground Distance (ft) 28.00		Spud Date 1/23/2021 07:45		Rig Release Date 1/26/2021 12:00		On Production Date		Abandon Date	

Casing Run Tally

Run #	Ref #	Item Des	OD (in)	Wt (lb/ft)	Grade	Run?	Len (ft)	Centralized?	Ext Jwlry	Connections	Top (ftKB)	Cum Len (ft)
2		Casing Joints	9 5/8	36.00	J-55	Yes	40.27	Yes		LT&C	1,646.4	42.12
7		Casing Joints	9 5/8	36.00	J-55	Yes	38.95	Yes		LT&C	1,446.7	241.81
12		Casing Joints	9 5/8	36.00	J-55	Yes	37.85	Yes		LT&C	1,246.7	441.76
17		Casing Joints	9 5/8	36.00	J-55	Yes	40.55	Yes		LT&C	1,043.8	644.73
22		Casing Joints	9 5/8	36.00	J-55	Yes	40.25	Yes		LT&C	841.2	847.27
27		Casing Joints	9 5/8	36.00	J-55	Yes	41.60	Yes		LT&C	636.4	1,052.15
32		Casing Joints	9 5/8	36.00	J-55	Yes	39.20	Yes		LT&C	437.3	1,251.17
37		Casing Joints	9 5/8	36.00	J-55	Yes	40.94	Yes		LT&C	235.4	1,453.10