



GMT Exploration Company, LLC

Elbert County, CO (NAD 83)

Ruby-Crystal Pad

RUBY 6-65 22-27 4HN

Wellbore #1

Plan: Design #1

Standard Planning Report

24 May, 2019







Project: Elbert County, CO (NAD 83)
Site: Ruby-Crystal Pad
Well: RUBY 6-65 22-27 4HN
Wellbore: Wellbore #1
Design: Design #1

GMT Exploration Company, LLC

Geodetic System: US State Plane 1983
Datum: North American Datum 1983
Ellipsoid: GRS 1980
Zone: Colorado Central Zone
System Datum: Mean Sea Level

WELL DETAILS: RUBY 6-65 22-27 4HN					
+N/-S	+E/-W	Northing	Ground Level: Easting	6179.00 Latitude	Longitude
0.00	0.00	1612493.88	3240990.14	39.511962	-104.645826

SECTION DETAILS									
MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	Vsect	Target
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
350.00	0.00	0.00	350.00	0.00	0.00	0.00	0.00	0.00	
1569.64	24.39	288.07	1533.13	79.33	-243.11	2.00	288.07	14.98	
6559.87	24.39	288.07	6077.91	718.63	-2202.36	0.00	0.00	135.67	
7779.52	0.00	0.00	7261.04	797.95	-2445.47	2.00	180.00	150.64	
8079.52	0.00	0.00	7561.04	797.95	-2445.47	0.00	0.00	150.64	
8979.52	90.00	181.04	8134.00	225.09	-2455.87	10.00	0.00	687.70	FTP-RUBY 6-65 22-27 4HN
15727.31	90.00	181.04	8134.00	-6521.59	-2578.26	0.00	0.00	7012.72	LTP-RUBY 6-65 22-27 4HN
15777.31	90.00	181.04	8134.00	-6571.59	-2579.17	0.00	0.00	7059.59	BHL-RUBY 6-65 22-27 4HN



Database:	Local	Local Co-ordinate Reference:	Well RUBY 6-65 22-27 4HN
Company:	GMT Exploration Company, LLC	TVD Reference:	KB @ 6199.00usft
Project:	Elbert County, CO (NAD 83)	MD Reference:	KB @ 6199.00usft
Site:	Ruby-Crystal Pad	North Reference:	True
Well:	RUBY 6-65 22-27 4HN	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Project	Elbert County, CO (NAD 83)		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	Colorado Central Zone		

Site		Ruby-Crystal Pad				
Site Position:		Northing:	1,613,266.75 usft	Latitude:	39.514130	
From:	Lat/Long	Easting:	3,239,201.95 usft	Longitude:	-104.652138	
Position Uncertainty:		0.00 usft	Slot Radius:	13-3/16 "	Grid Convergence:	0.53 °

Well	RUBY 6-65 22-27 4HN					
Well Position	+N/-S	-789.53 usft	Northing:	1,612,493.88 usft	Latitude:	39.511962
	+E/-W	1,780.90 usft	Easting:	3,240,990.14 usft	Longitude:	-104.645826
Position Uncertainty		0.00 usft	Wellhead Elevation:		Ground Level:	6,179.00 usft

Wellbore	Wellbore #1				
Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	IGRF2015	5/21/2019	7.87	66.11	51,710.27713998

Design	Design #1			
Audit Notes:				
Version:	Phase:	PLAN	Tie On Depth:	0.00
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)
	0.00	0.00	0.00	201.43

Plan Survey Tool Program	Date	5/24/2019		
Depth From (usft)	Depth To (usft)	Survey (Wellbore)	Tool Name	Remarks
1	0.00	15,777.31	Design #1 (Wellbore #1)	MWD
				OWSG MWD - Standard

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
350.00	0.00	0.00	350.00	0.00	0.00	0.00	0.00	0.00	0.00	
1,569.64	24.39	288.07	1,533.13	79.33	-243.11	2.00	2.00	0.00	288.07	
6,559.87	24.39	288.07	6,077.91	718.63	-2,202.36	0.00	0.00	0.00	0.00	
7,779.52	0.00	0.00	7,261.04	797.95	-2,445.47	2.00	-2.00	0.00	180.00	
8,079.52	0.00	0.00	7,561.04	797.95	-2,445.47	0.00	0.00	0.00	0.00	
8,979.52	90.00	181.04	8,134.00	225.09	-2,455.87	10.00	10.00	0.00	0.00	FTP-RUBY 6-65 22
15,727.31	90.00	181.04	8,134.00	-6,521.59	-2,578.26	0.00	0.00	0.00	0.00	LTP-RUBY 6-65 22
15,777.31	90.00	181.04	8,134.00	-6,571.59	-2,579.17	0.00	0.00	0.00	0.00	BHL-RUBY 6-65 22

Database:	Local	Local Co-ordinate Reference:	Well RUBY 6-65 22-27 4HN
Company:	GMT Exploration Company, LLC	TVD Reference:	KB @ 6199.00usft
Project:	Elbert County, CO (NAD 83)	MD Reference:	KB @ 6199.00usft
Site:	Ruby-Crystal Pad	North Reference:	True
Well:	RUBY 6-65 22-27 4HN	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
SHL-RUBY 6-65 22-27 4HN									
100.00	0.00	0.00	100.00	0.00	0.00	0.00	0.00	0.00	0.00
200.00	0.00	0.00	200.00	0.00	0.00	0.00	0.00	0.00	0.00
300.00	0.00	0.00	300.00	0.00	0.00	0.00	0.00	0.00	0.00
350.00	0.00	0.00	350.00	0.00	0.00	0.00	0.00	0.00	0.00
Build: 2°/100' @ 350.00' MD									
400.00	1.00	288.07	400.00	0.14	-0.41	0.03	2.00	2.00	0.00
500.00	3.00	288.07	499.93	1.22	-3.73	0.23	2.00	2.00	0.00
600.00	5.00	288.07	599.68	3.38	-10.36	0.64	2.00	2.00	0.00
700.00	7.00	288.07	699.13	6.62	-20.30	1.25	2.00	2.00	0.00
800.00	9.00	288.07	798.15	10.94	-33.53	2.07	2.00	2.00	0.00
900.00	11.00	288.07	896.63	16.33	-50.04	3.08	2.00	2.00	0.00
1,000.00	13.00	288.07	994.44	22.78	-69.80	4.30	2.00	2.00	0.00
1,100.00	15.00	288.07	1,091.46	30.28	-92.80	5.72	2.00	2.00	0.00
1,200.00	17.00	288.07	1,187.58	38.83	-119.00	7.33	2.00	2.00	0.00
1,300.00	19.00	288.07	1,282.68	48.42	-148.38	9.14	2.00	2.00	0.00
1,400.00	21.00	288.07	1,376.65	59.02	-180.89	11.14	2.00	2.00	0.00
1,500.00	23.00	288.07	1,469.36	70.64	-216.50	13.34	2.00	2.00	0.00
1,569.64	24.39	288.07	1,533.13	79.33	-243.11	14.98	2.00	2.00	0.00
Hold: 24.39° Inc, 288.07° Azm									
1,600.00	24.39	288.07	1,560.78	83.22	-255.03	15.71	0.00	0.00	0.00
1,700.00	24.39	288.07	1,651.85	96.03	-294.29	18.13	0.00	0.00	0.00
1,800.00	24.39	288.07	1,742.93	108.84	-333.55	20.55	0.00	0.00	0.00
1,900.00	24.39	288.07	1,834.00	121.65	-372.81	22.97	0.00	0.00	0.00
2,000.00	24.39	288.07	1,925.07	134.46	-412.08	25.38	0.00	0.00	0.00
2,100.00	24.39	288.07	2,016.15	147.27	-451.34	27.80	0.00	0.00	0.00
2,200.00	24.39	288.07	2,107.22	160.08	-490.60	30.22	0.00	0.00	0.00
2,300.00	24.39	288.07	2,198.29	172.89	-529.86	32.64	0.00	0.00	0.00
2,400.00	24.39	288.07	2,289.37	185.70	-569.12	35.06	0.00	0.00	0.00
2,500.00	24.39	288.07	2,380.44	198.51	-608.38	37.48	0.00	0.00	0.00
2,600.00	24.39	288.07	2,471.51	211.33	-647.65	39.89	0.00	0.00	0.00
2,700.00	24.39	288.07	2,562.59	224.14	-686.91	42.31	0.00	0.00	0.00
2,800.00	24.39	288.07	2,653.66	236.95	-726.17	44.73	0.00	0.00	0.00
2,900.00	24.39	288.07	2,744.74	249.76	-765.43	47.15	0.00	0.00	0.00
3,000.00	24.39	288.07	2,835.81	262.57	-804.69	49.57	0.00	0.00	0.00
3,100.00	24.39	288.07	2,926.88	275.38	-843.96	51.99	0.00	0.00	0.00
3,200.00	24.39	288.07	3,017.96	288.19	-883.22	54.41	0.00	0.00	0.00
3,300.00	24.39	288.07	3,109.03	301.00	-922.48	56.82	0.00	0.00	0.00
3,400.00	24.39	288.07	3,200.10	313.81	-961.74	59.24	0.00	0.00	0.00
3,500.00	24.39	288.07	3,291.18	326.63	-1,001.00	61.66	0.00	0.00	0.00
3,600.00	24.39	288.07	3,382.25	339.44	-1,040.26	64.08	0.00	0.00	0.00
3,700.00	24.39	288.07	3,473.32	352.25	-1,079.53	66.50	0.00	0.00	0.00
3,800.00	24.39	288.07	3,564.40	365.06	-1,118.79	68.92	0.00	0.00	0.00
3,900.00	24.39	288.07	3,655.47	377.87	-1,158.05	71.34	0.00	0.00	0.00
4,000.00	24.39	288.07	3,746.54	390.68	-1,197.31	73.75	0.00	0.00	0.00
4,100.00	24.39	288.07	3,837.62	403.49	-1,236.57	76.17	0.00	0.00	0.00
4,200.00	24.39	288.07	3,928.69	416.30	-1,275.84	78.59	0.00	0.00	0.00
4,300.00	24.39	288.07	4,019.76	429.11	-1,315.10	81.01	0.00	0.00	0.00
4,400.00	24.39	288.07	4,110.84	441.92	-1,354.36	83.43	0.00	0.00	0.00
4,500.00	24.39	288.07	4,201.91	454.74	-1,393.62	85.85	0.00	0.00	0.00
4,600.00	24.39	288.07	4,292.99	467.55	-1,432.88	88.27	0.00	0.00	0.00
4,700.00	24.39	288.07	4,384.06	480.36	-1,472.14	90.68	0.00	0.00	0.00

Database:	Local	Local Co-ordinate Reference:	Well RUBY 6-65 22-27 4HN
Company:	GMT Exploration Company, LLC	TVD Reference:	KB @ 6199.00usft
Project:	Elbert County, CO (NAD 83)	MD Reference:	KB @ 6199.00usft
Site:	Ruby-Crystal Pad	North Reference:	True
Well:	RUBY 6-65 22-27 4HN	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
4,800.00	24.39	288.07	4,475.13	493.17	-1,511.41	93.10	0.00	0.00	0.00
4,900.00	24.39	288.07	4,566.21	505.98	-1,550.67	95.52	0.00	0.00	0.00
5,000.00	24.39	288.07	4,657.28	518.79	-1,589.93	97.94	0.00	0.00	0.00
5,100.00	24.39	288.07	4,748.35	531.60	-1,629.19	100.36	0.00	0.00	0.00
5,200.00	24.39	288.07	4,839.43	544.41	-1,668.45	102.78	0.00	0.00	0.00
5,300.00	24.39	288.07	4,930.50	557.22	-1,707.71	105.20	0.00	0.00	0.00
5,400.00	24.39	288.07	5,021.57	570.04	-1,746.98	107.61	0.00	0.00	0.00
5,500.00	24.39	288.07	5,112.65	582.85	-1,786.24	110.03	0.00	0.00	0.00
5,600.00	24.39	288.07	5,203.72	595.66	-1,825.50	112.45	0.00	0.00	0.00
5,700.00	24.39	288.07	5,294.79	608.47	-1,864.76	114.87	0.00	0.00	0.00
5,800.00	24.39	288.07	5,385.87	621.28	-1,904.02	117.29	0.00	0.00	0.00
5,900.00	24.39	288.07	5,476.94	634.09	-1,943.29	119.71	0.00	0.00	0.00
6,000.00	24.39	288.07	5,568.02	646.90	-1,982.55	122.12	0.00	0.00	0.00
6,100.00	24.39	288.07	5,659.09	659.71	-2,021.81	124.54	0.00	0.00	0.00
6,200.00	24.39	288.07	5,750.16	672.52	-2,061.07	126.96	0.00	0.00	0.00
6,300.00	24.39	288.07	5,841.24	685.33	-2,100.33	129.38	0.00	0.00	0.00
6,400.00	24.39	288.07	5,932.31	698.15	-2,139.59	131.80	0.00	0.00	0.00
6,500.00	24.39	288.07	6,023.38	710.96	-2,178.86	134.22	0.00	0.00	0.00
6,559.87	24.39	288.07	6,077.91	718.63	-2,202.36	135.67	0.00	0.00	0.00
Drop: 2°/100' @ 6559.87' MD									
6,600.00	23.59	288.07	6,114.57	723.69	-2,217.87	136.62	2.00	-2.00	0.00
6,700.00	21.59	288.07	6,206.89	735.60	-2,254.39	138.87	2.00	-2.00	0.00
6,800.00	19.59	288.07	6,300.50	746.51	-2,287.82	140.93	2.00	-2.00	0.00
6,900.00	17.59	288.07	6,395.28	756.40	-2,318.13	142.80	2.00	-2.00	0.00
7,000.00	15.59	288.07	6,491.11	765.26	-2,345.27	144.47	2.00	-2.00	0.00
7,100.00	13.59	288.07	6,587.88	773.07	-2,369.22	145.94	2.00	-2.00	0.00
7,200.00	11.59	288.07	6,685.47	779.83	-2,389.94	147.22	2.00	-2.00	0.00
7,300.00	9.59	288.07	6,783.76	785.53	-2,407.41	148.30	2.00	-2.00	0.00
7,400.00	7.59	288.07	6,882.64	790.17	-2,421.61	149.17	2.00	-2.00	0.00
7,500.00	5.59	288.07	6,981.97	793.73	-2,432.52	149.84	2.00	-2.00	0.00
7,600.00	3.59	288.07	7,081.64	796.21	-2,440.13	150.31	2.00	-2.00	0.00
7,700.00	1.59	288.07	7,181.54	797.61	-2,444.42	150.58	2.00	-2.00	0.00
7,779.52	0.00	0.00	7,261.04	797.95	-2,445.47	150.64	2.00	-2.00	0.00
Hold: 0.00° Inc, 0.00° Azm									
7,800.00	0.00	0.00	7,281.53	797.95	-2,445.47	150.64	0.00	0.00	0.00
7,900.00	0.00	0.00	7,381.53	797.95	-2,445.47	150.64	0.00	0.00	0.00
8,000.00	0.00	0.00	7,481.53	797.95	-2,445.47	150.64	0.00	0.00	0.00
8,079.52	0.00	0.00	7,561.04	797.95	-2,445.47	150.64	0.00	0.00	0.00
KOP: 10°/100' @ 8079.52' MD - KOP-RUBY 6-65 22-27 4HN									
8,100.00	2.05	181.04	7,581.52	797.59	-2,445.48	150.98	10.00	10.00	0.00
8,150.00	7.05	181.04	7,631.35	793.62	-2,445.55	154.70	10.00	10.00	0.00
8,200.00	12.05	181.04	7,680.64	785.33	-2,445.70	162.47	10.00	10.00	0.00
8,250.00	17.05	181.04	7,729.02	772.78	-2,445.93	174.24	10.00	10.00	0.00
8,300.00	22.05	181.04	7,776.13	756.06	-2,446.23	189.92	10.00	10.00	0.00
8,350.00	27.05	181.04	7,821.59	735.29	-2,446.61	209.38	10.00	10.00	0.00
8,400.00	32.05	181.04	7,865.07	710.65	-2,447.06	232.49	10.00	10.00	0.00
8,450.00	37.05	181.04	7,906.24	682.31	-2,447.57	259.06	10.00	10.00	0.00
8,500.00	42.05	181.04	7,944.79	650.49	-2,448.15	288.89	10.00	10.00	0.00
8,550.00	47.05	181.04	7,980.41	615.43	-2,448.78	321.76	10.00	10.00	0.00
8,600.00	52.05	181.04	8,012.84	577.40	-2,449.47	357.41	10.00	10.00	0.00
8,650.00	57.05	181.04	8,041.83	536.69	-2,450.21	395.58	10.00	10.00	0.00
8,700.00	62.05	181.04	8,067.16	493.60	-2,450.99	435.97	10.00	10.00	0.00
8,750.00	67.05	181.04	8,088.64	448.48	-2,451.81	478.27	10.00	10.00	0.00



Database:	Local	Local Co-ordinate Reference:	Well RUBY 6-65 22-27 4HN
Company:	GMT Exploration Company, LLC	TVD Reference:	KB @ 6199.00usft
Project:	Elbert County, CO (NAD 83)	MD Reference:	KB @ 6199.00usft
Site:	Ruby-Crystal Pad	North Reference:	True
Well:	RUBY 6-65 22-27 4HN	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
8,800.00	72.05	181.04	8,106.11	401.65	-2,452.66	522.17	10.00	10.00	0.00
8,850.00	77.05	181.04	8,119.42	353.48	-2,453.54	567.33	10.00	10.00	0.00
8,900.00	82.05	181.04	8,128.49	304.34	-2,454.43	613.41	10.00	10.00	0.00
8,950.00	87.05	181.04	8,133.24	254.59	-2,455.33	660.05	10.00	10.00	0.00
8,979.52	90.00	181.04	8,134.00	225.09	-2,455.87	687.70	10.00	10.00	0.00
LP: 8979.52' MD, 90.00° Inc, 181.04° Azm - FTP-RUBY 6-65 22-27 4HN									
9,000.00	90.00	181.04	8,134.00	204.61	-2,456.24	706.90	0.00	0.00	0.00
9,100.00	90.00	181.04	8,134.00	104.62	-2,458.05	800.64	0.00	0.00	0.00
9,200.00	90.00	181.04	8,134.00	4.64	-2,459.86	894.37	0.00	0.00	0.00
9,300.00	90.00	181.04	8,134.00	-95.34	-2,461.68	988.11	0.00	0.00	0.00
9,400.00	90.00	181.04	8,134.00	-195.33	-2,463.49	1,081.84	0.00	0.00	0.00
9,500.00	90.00	181.04	8,134.00	-295.31	-2,465.31	1,175.58	0.00	0.00	0.00
9,600.00	90.00	181.04	8,134.00	-395.29	-2,467.12	1,269.31	0.00	0.00	0.00
9,700.00	90.00	181.04	8,134.00	-495.28	-2,468.93	1,363.05	0.00	0.00	0.00
9,800.00	90.00	181.04	8,134.00	-595.26	-2,470.75	1,456.78	0.00	0.00	0.00
9,900.00	90.00	181.04	8,134.00	-695.24	-2,472.56	1,550.51	0.00	0.00	0.00
10,000.00	90.00	181.04	8,134.00	-795.23	-2,474.38	1,644.25	0.00	0.00	0.00
10,100.00	90.00	181.04	8,134.00	-895.21	-2,476.19	1,737.98	0.00	0.00	0.00
10,200.00	90.00	181.04	8,134.00	-995.19	-2,478.00	1,831.72	0.00	0.00	0.00
10,300.00	90.00	181.04	8,134.00	-1,095.18	-2,479.82	1,925.45	0.00	0.00	0.00
10,400.00	90.00	181.04	8,134.00	-1,195.16	-2,481.63	2,019.19	0.00	0.00	0.00
10,500.00	90.00	181.04	8,134.00	-1,295.14	-2,483.44	2,112.92	0.00	0.00	0.00
10,600.00	90.00	181.04	8,134.00	-1,395.13	-2,485.26	2,206.66	0.00	0.00	0.00
10,700.00	90.00	181.04	8,134.00	-1,495.11	-2,487.07	2,300.39	0.00	0.00	0.00
10,800.00	90.00	181.04	8,134.00	-1,595.10	-2,488.89	2,394.13	0.00	0.00	0.00
10,900.00	90.00	181.04	8,134.00	-1,695.08	-2,490.70	2,487.86	0.00	0.00	0.00
11,000.00	90.00	181.04	8,134.00	-1,795.06	-2,492.51	2,581.60	0.00	0.00	0.00
11,100.00	90.00	181.04	8,134.00	-1,895.05	-2,494.33	2,675.33	0.00	0.00	0.00
11,200.00	90.00	181.04	8,134.00	-1,995.03	-2,496.14	2,769.07	0.00	0.00	0.00
11,300.00	90.00	181.04	8,134.00	-2,095.01	-2,497.96	2,862.80	0.00	0.00	0.00
11,400.00	90.00	181.04	8,134.00	-2,195.00	-2,499.77	2,956.54	0.00	0.00	0.00
11,500.00	90.00	181.04	8,134.00	-2,294.98	-2,501.58	3,050.27	0.00	0.00	0.00
11,600.00	90.00	181.04	8,134.00	-2,394.96	-2,503.40	3,144.00	0.00	0.00	0.00
11,700.00	90.00	181.04	8,134.00	-2,494.95	-2,505.21	3,237.74	0.00	0.00	0.00
11,800.00	90.00	181.04	8,134.00	-2,594.93	-2,507.02	3,331.47	0.00	0.00	0.00
11,900.00	90.00	181.04	8,134.00	-2,694.91	-2,508.84	3,425.21	0.00	0.00	0.00
12,000.00	90.00	181.04	8,134.00	-2,794.90	-2,510.65	3,518.94	0.00	0.00	0.00
12,100.00	90.00	181.04	8,134.00	-2,894.88	-2,512.47	3,612.68	0.00	0.00	0.00
12,200.00	90.00	181.04	8,134.00	-2,994.87	-2,514.28	3,706.41	0.00	0.00	0.00
12,300.00	90.00	181.04	8,134.00	-3,094.85	-2,516.09	3,800.15	0.00	0.00	0.00
12,400.00	90.00	181.04	8,134.00	-3,194.83	-2,517.91	3,893.88	0.00	0.00	0.00
12,500.00	90.00	181.04	8,134.00	-3,294.82	-2,519.72	3,987.62	0.00	0.00	0.00
12,600.00	90.00	181.04	8,134.00	-3,394.80	-2,521.54	4,081.35	0.00	0.00	0.00
12,700.00	90.00	181.04	8,134.00	-3,494.78	-2,523.35	4,175.09	0.00	0.00	0.00
12,800.00	90.00	181.04	8,134.00	-3,594.77	-2,525.16	4,268.82	0.00	0.00	0.00
12,900.00	90.00	181.04	8,134.00	-3,694.75	-2,526.98	4,362.56	0.00	0.00	0.00
13,000.00	90.00	181.04	8,134.00	-3,794.73	-2,528.79	4,456.29	0.00	0.00	0.00
13,100.00	90.00	181.04	8,134.00	-3,894.72	-2,530.60	4,550.02	0.00	0.00	0.00
13,200.00	90.00	181.04	8,134.00	-3,994.70	-2,532.42	4,643.76	0.00	0.00	0.00
13,300.00	90.00	181.04	8,134.00	-4,094.68	-2,534.23	4,737.49	0.00	0.00	0.00
13,400.00	90.00	181.04	8,134.00	-4,194.67	-2,536.05	4,831.23	0.00	0.00	0.00
13,500.00	90.00	181.04	8,134.00	-4,294.65	-2,537.86	4,924.96	0.00	0.00	0.00
13,600.00	90.00	181.04	8,134.00	-4,394.63	-2,539.67	5,018.70	0.00	0.00	0.00
13,700.00	90.00	181.04	8,134.00	-4,494.62	-2,541.49	5,112.43	0.00	0.00	0.00

Database:	Local	Local Co-ordinate Reference:	Well RUBY 6-65 22-27 4HN
Company:	GMT Exploration Company, LLC	TVD Reference:	KB @ 6199.00usft
Project:	Elbert County, CO (NAD 83)	MD Reference:	KB @ 6199.00usft
Site:	Ruby-Crystal Pad	North Reference:	True
Well:	RUBY 6-65 22-27 4HN	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
13,800.00	90.00	181.04	8,134.00	-4,594.60	-2,543.30	5,206.17	0.00	0.00	0.00
13,900.00	90.00	181.04	8,134.00	-4,694.59	-2,545.12	5,299.90	0.00	0.00	0.00
14,000.00	90.00	181.04	8,134.00	-4,794.57	-2,546.93	5,393.64	0.00	0.00	0.00
14,100.00	90.00	181.04	8,134.00	-4,894.55	-2,548.74	5,487.37	0.00	0.00	0.00
14,200.00	90.00	181.04	8,134.00	-4,994.54	-2,550.56	5,581.11	0.00	0.00	0.00
14,300.00	90.00	181.04	8,134.00	-5,094.52	-2,552.37	5,674.84	0.00	0.00	0.00
14,400.00	90.00	181.04	8,134.00	-5,194.50	-2,554.18	5,768.58	0.00	0.00	0.00
14,500.00	90.00	181.04	8,134.00	-5,294.49	-2,556.00	5,862.31	0.00	0.00	0.00
14,600.00	90.00	181.04	8,134.00	-5,394.47	-2,557.81	5,956.05	0.00	0.00	0.00
14,700.00	90.00	181.04	8,134.00	-5,494.45	-2,559.63	6,049.78	0.00	0.00	0.00
14,800.00	90.00	181.04	8,134.00	-5,594.44	-2,561.44	6,143.51	0.00	0.00	0.00
14,900.00	90.00	181.04	8,134.00	-5,694.42	-2,563.25	6,237.25	0.00	0.00	0.00
15,000.00	90.00	181.04	8,134.00	-5,794.40	-2,565.07	6,330.98	0.00	0.00	0.00
15,100.00	90.00	181.04	8,134.00	-5,894.39	-2,566.88	6,424.72	0.00	0.00	0.00
15,200.00	90.00	181.04	8,134.00	-5,994.37	-2,568.70	6,518.45	0.00	0.00	0.00
15,300.00	90.00	181.04	8,134.00	-6,094.36	-2,570.51	6,612.19	0.00	0.00	0.00
15,400.00	90.00	181.04	8,134.00	-6,194.34	-2,572.32	6,705.92	0.00	0.00	0.00
15,500.00	90.00	181.04	8,134.00	-6,294.32	-2,574.14	6,799.66	0.00	0.00	0.00
15,600.00	90.00	181.04	8,134.00	-6,394.31	-2,575.95	6,893.39	0.00	0.00	0.00
15,700.00	90.00	181.04	8,134.00	-6,494.29	-2,577.76	6,987.13	0.00	0.00	0.00
15,727.31	90.00	181.04	8,134.00	-6,521.59	-2,578.26	7,012.73	0.00	0.00	0.00
Hold: 90.00° Inc, 181.04° Azm - LTP-RUBY 6-65 22-27 4HN									
15,777.31	90.00	181.04	8,134.00	-6,571.59	-2,579.17	7,059.59	0.00	0.00	0.00
TD @ 15777.31' MD/8134.00' TVD - BHL-RUBY 6-65 22-27 4HN									

Design Targets									
Target Name	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
SHL-RUBY 6-65 22-2' - plan hits target center - Point	0.00	0.00	0.00	0.00	0.00	1,612,493.88	3,240,990.14	39.511962	-104.645826
KOP-RUBY 6-65 22-2' - plan hits target center - Point	0.00	0.00	7,561.04	797.95	-2,445.47	1,613,268.80	3,238,537.27	39.514153	-104.654494
BHL-RUBY 6-65 22-2' - plan hits target center - Point	0.00	0.00	8,134.00	-6,571.59	-2,579.17	1,605,898.33	3,238,472.88	39.493920	-104.654965
FTP-RUBY 6-65 22-2' - plan hits target center - Point	0.00	0.00	8,134.00	225.09	-2,455.87	1,612,695.87	3,238,532.27	39.512580	-104.654531
LTP-RUBY 6-65 22-2' - plan hits target center - Point	0.00	0.00	8,134.00	-6,521.59	-2,578.26	1,605,948.33	3,238,473.31	39.494057	-104.654962

Database:	Local	Local Co-ordinate Reference:	Well RUBY 6-65 22-27 4HN
Company:	GMT Exploration Company, LLC	TVD Reference:	KB @ 6199.00usft
Project:	Elbert County, CO (NAD 83)	MD Reference:	KB @ 6199.00usft
Site:	Ruby-Crystal Pad	North Reference:	True
Well:	RUBY 6-65 22-27 4HN	Survey Calculation Method:	Minimum Curvature
Wellbore:	Wellbore #1		
Design:	Design #1		

Formations						
Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)	
459.03	459.00	Denver				
1,570.60	1,534.00	Upper Arapahoe				
2,339.21	2,234.00	Laramie - Fox Hills				
2,525.87	2,404.00	Pierre Shale (Base of Fox Hills)				
6,066.96	5,629.00	Sussex Sandstone				
8,492.26	7,939.00	Sharon Springs Shale				
8,505.70	7,949.00	Niobrara				
8,519.44	7,959.00	Niobrara A				
8,793.29	8,104.00	Niobrara B Top				

Plan Annotations					
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates			
		+N/-S (usft)	+E/-W (usft)	Comment	
350.00	350.00	0.00	0.00	Build: 2°/100' @ 350.00' MD	
1,569.64	1,533.13	79.33	-243.11	Hold: 24.39° Inc, 288.07° Azm	
6,559.87	6,077.91	718.63	-2,202.36	Drop: 2°/100' @ 6559.87' MD	
7,779.52	7,261.04	797.95	-2,445.47	Hold: 0.00° Inc, 0.00° Azm	
8,079.52	7,561.04	797.95	-2,445.47	KOP: 10°/100' @ 8079.52' MD	
8,979.52	8,134.00	225.09	-2,455.87	LP: 8979.52' MD, 90.00° Inc, 181.04° Azm	
15,727.31	8,134.00	-6,521.59	-2,578.26	Hold: 90.00° Inc, 181.04° Azm	
15,777.31	8,134.00	-6,571.59	-2,579.17	TD @ 15777.31' MD/8134.00' TVD	