

Schematic, not to Scale

Drilled by MFSCo.  
by rotary 1941

Present Status of Well  
W. B. Lashar Well No. 2  
Section 25, T12N, R101W  
West Hiawatha Field

Revised 6/5/73 CRO

#### Surface Casing

10 3/4", 45.5 # 10 Thd Csg

11 jts, 245'9" Net, including Baker guide shoe.  
Landed at 258'3" or 12.5' below KB. Cmt'd w/ 185 sx  
last 50 sx treated. Cmt returns in cellar.

#### Production Casing

7" x 75" 10 Csg - landed on Bowen casing ring at  
3300'8" or 11.8' below KB. Cmt'd with 265 sx cmt. Last 50  
sx treated.

Note: New 4 1/2" production casing ran and cmt'd 1/24/73.

4 1/2", K-55 # N-80, 11.6 #, LT&C and ST&C, 8rd Thd Net

1 pc. 4 1/2" OD, 11.6 # K-55, 8rd Thd, ST&C	22.14
100 joints 4 1/2" OD, 11.6 # K-55, 8rd Thd, ST&C	3133.46
4 joints 4 1/2" OD, 11.6 # N-80, 8rd Thd, LT&C	121.79
1 Baker Model G differential float collar	2.73
1 Baker guide shoe	.66
Total	3280.78

The above csg was landed at 3289.36' KBM or 8.58' below  
KB in a NSCo. 8" 3000 psi Type B casing flange. Cmt'd w/  
170 sx regular Type G cement. Good returns throughout.  
Landed in casing slips w/ indicator weight of 32,000 pounds.  
Cut off casing & installed NSCo. 8" 3000 psi by 6" 3000 psi  
type B tubing spool.

#### Tubing Report

2 3/8" OD, Seal Lok Tubing was run as follows:

1 NSCo Type H-1 Tubing hanger	.45
1 2 3/8" 8rd EUE by 2 3/8" seal lock change nipple	.71
106 jts 2 3/8" OD, 4.6 #, J-55 seal lock tubing	3223.19
1 2 3/8" seal lock Coupling	
1 2 3/8" 8rd EUE by 2 3/8" seal lock change nipple	.33
1 Baker pump out float	.75
Total	3225.05'

Tubing landed at 3232.05' KBM or 7' below KB  
in a NSCo. 3000 psi tubing spool.

Kelly Bushing

casing flange

Production floor  
6839'6"

5'5" collar filled

258'3" 10 3/4" 45.5 # 10 Thd Csg

CMT w/ 185 sx reg cmt

CMT returns to surface.

Top of cement at 1890' KBM  
from Dresser-Atlas cement bond  
log dated 5/26/73.

Perfs. 2904' to 2914' w/ 2 HPF  
Jumbo jet shots

Perforations measured from Dresser  
Atlas cmt Bond Log dated 5/26/73

2 3/8" OD tubing Landed at 3225' KBM

Perfs 3230' to 3256' w/ 2 HPF  
Jumbo jet shots

3258 PBD by wireline  
9-2-76

PBTD 3295'

4 1/2" OD casing Landed at 3289.36' KBM

