

FORM
5A

Rev
09/20

State of Colorado

Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:

402602482

Date Received:

03/15/2021

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 10633

2. Name of Operator: CRESTONE PEAK RESOURCES OPERATING LLC

3. Address: 1801 CALIFORNIA STREET #2500

City: DENVER State: CO Zip: 80202

4. Contact Name: Lindsey Organ

Phone: (303) 7743958

Fax:

Email: lindsey.organ@crestonepr.com

5. API Number 05-014-20646-00

7. Well Name: BICKLER

8. Location: QtrQtr: NESW Section: 34 Township: 1N Range: 68W Meridian: 6

9. Field Name: WATTENBERG Field Code: 90750

6. County: BROOMFIELD

Well Number: 23-34

Completed Interval

FORMATION: CODELL Status: COMMINGLED Treatment Type: HYDRAULIC FRACTURING
Treatment Date: 07/25/2012 End Date: 07/25/2012 Date this Formation was Completed: 08/28/2012
Perforations Top: 8067 Bottom: 8087 No. Holes: 80 Hole size: 0.41 Open Hole: ☐

Describe the Formation Treatment, including the following: type of fluid used (gel, slickwater, etc.), type and concentration of acid used (HCl, HF, etc.), types and amounts of proppant(s) used, depth details of multiple zones, and method used to determine flowback volume.

4596 bbls of water, 16 bbls of additives (GW-45LF, GBW-21, HighPerm CRB, BC-3, BF-9L, ClayCare, XLW-14, XLW-22C, FRW-20, NE-945, Flo-Back 40, BioClear 1000) and 0 bbl HCL in a 1 stage frac with 125020 lbs of silica quartz proppant

This formation is commingled with another formation: ☒ Yes ☐ No
Total fluid used in treatment (bbl): 4612 Max pressure during treatment (psi): 4906
Total gas used in treatment (mcf): Fluid density at initial fracture (lbs/gal):
Type of gas used in treatment: Min frac gradient (psi/ft): 1.04
Total acid used in treatment (bbl): 0 Number of staged intervals: 1
Recycled or Reused Fluids used in treatment (bbl): 0 Flowback volume recovered (bbl):
Fresh water used in treatment (bbl): 4612 Disposition method for flowback: DISPOSAL
Total proppant used (lbs): 125020

Fracture stimulations must be reported on FracFocus.org

Test Information:

Hours: Bbl oil: Mcf Gas: Bbl H2O:
Date: Calculated 24 hour rate: Bbl oil: Mcf Gas: Bbl H2O: GOR:
Test Method: Casing PSI: Tubing PSI: Choke Size:
Gas Disposition: Gas Type: Btu Gas: API Gravity Oil:
Tubing Size: Tubing Setting Depth: Tbg setting date: Packer Depth:
Reason for Non-Production:
Date formation Abandoned: Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt
** Bridge Plug Depth: ** Sacks cement on top: ** Wireline and Cement Job Summary must be attached.

FORMATION: NIOBRARA Status: COMMINGLED Treatment Type: HYDRAULIC FRACTURING
Treatment Date: 08/01/2012 End Date: 08/01/2012 Date this Formation was Completed: 08/28/2012
Perforations Top: 7810 Bottom: 7826 No. Holes: 32 Hole size: 0.71 Open Hole: ☐

Describe the Formation Treatment, including the following: type of fluid used (gel, slickwater, etc.), type and concentration of acid used (HCl, HF, etc.), types and amounts of proppant(s) used, depth details of multiple zones, and method used to determine flowback volume.

3293 bbls of water, 12 bbls of additives (GW-45LF, GBW-21, GBW-5, HighPerm CRB, BC-3, BF-9L, ClayCare, XLW-14, XLW-22C, FRW-20, NE-945, Flo-Back 40, BioClear 1000) and 0 bbl HCL in a stage frac with 250320 lbs of silica quartz proppant

This formation is commingled with another formation: ☒ Yes ☐ No
Total fluid used in treatment (bbl): 3305 Max pressure during treatment (psi): 5608
Total gas used in treatment (mcf): Fluid density at initial fracture (lbs/gal):
Type of gas used in treatment: Min frac gradient (psi/ft): 0.95
Total acid used in treatment (bbl): 0 Number of staged intervals: 1
Recycled or Reused Fluids used in treatment (bbl): 0 Flowback volume recovered (bbl):
Fresh water used in treatment (bbl): 3305 Disposition method for flowback: DISPOSAL
Total proppant used (lbs): 250320

Fracture stimulations must be reported on FracFocus.org

Test Information:

Hours: _____ Bbl oil: _____ Mcf Gas: _____ Bbl H2O: _____
Date: _____ Calculated 24 hour rate: _____ Bbl oil: _____ Mcf Gas: _____ Bbl H2O: _____ GOR: _____
Test Method: _____ Casing PSI: _____ Tubing PSI: _____ Choke Size: _____
Gas Disposition: _____ Gas Type: _____ Btu Gas: _____ API Gravity Oil: _____
Tubing Size: _____ Tubing Setting Depth: _____ Tbg setting date: _____ Packer Depth: _____
Reason for Non-Production: _____
Date formation Abandoned: _____ Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt _____
** Bridge Plug Depth: _____ ** Sacks cement on top: _____ ** Wireline and Cement Job Summary must be attached.

Comment:

Encana Oil & Gas was the well operator when this hydraulic fracture treatment occurred. Crestone used best available information from third party treatment reports to fill out this form 5A.

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: _____ Print Name: Lindsey Organ
Title: Regulatory Coordinator Date: 3/15/2021 Email: lindsey.organ@crestonepr.com

Attachment List

Att Doc Num **Name**

402602482 FORM 5A SUBMITTED

Total Attach: 1 Files

General Comments

User Group **Comment**

Comment Date

User Group	Comment	Comment Date
		Stamp Upon Approval

Total: 0 comment(s)