

Kerr-McGee Oil & Gas Onshore LP

1099 18th Street, Suite 1800 Denver, CO 80202
(720) 929-6000



August 3, 2021

Julie Murphy
Director, Colorado Oil and Gas Conservation Commission
Department of Natural Resources
The Chancery Building
1120 Lincoln Street, Suite 801
Denver, CO 80203

Re: Request for Exception to Rule 408.r

SBJ 13-1HZ (Doc No. 402496868) SBJ
13-2HZ (Doc No. 402496869) SBJ 13-
3HZ (Doc No. 402496871) SBJ 13-
4HZ (Doc No. 402496873) SBJ 13-
5HZ (Doc No. 402496874) SBJ 13-
6HZ (Doc No. 402496875)

Township 4 North, Range 68 West
Section 13: SWNW
Weld County, Colorado

SBJ 13-7HZ (Doc No. 402496876)
SBJ 13-8HZ (Doc No. 402496877)
SBJ 13-9HZ (Doc No. 402496878)
SBJ 13-10HZ (Doc No. 402496879)
SBJ 13-11HZ (Doc No. 402496880)
SBJ 13-12HZ (Doc No. 402496881)
SBJ 13-13HZ (Doc No. 402496882)

Dear Director Murphy:

Kerr-McGee Oil & Gas Onshore LP ("KMG") respectfully requests approval for an exception to Rule 408.r to only run a cased-hole pulsed neutron, gamma-ray, and cement bond log from the kickoff point into the surface casing on one of the first wells drilled on this multi-well location. A cement bond log with cased-hole gamma ray log will be run on production casing or on intermediate casing if production liner is run. The other wells on this multi-well location will be logged with only a cement bond log with cased-hole gamma ray log from kickoff point into the surface casing. Rule 408.r of the Colorado Oil and Gas Commission's Rules and Regulations requires wells to be logged with a minimum of a resistivity log with gamma ray. The above-named wells are requested to be exempt from this requirement due to the proximity of existing well(s) with acceptable resistivity logs with gamma ray. The available log(s) meet the offsetting well surface hole distance and bearing requirements.

One of the first wells drilled will be logged with a cased-hole pulsed neutron, gamma ray, and cement bond log. The other wells on this multi-well location will run a cement bond and gamma ray log from the kickoff point into the surface casing. The Drilling Completion Report (Form 5) submitted for each well will indicate that no open-hole logs were run.

The existing well(s) within seven hundred fifty (750) feet with acceptable resistivity logs with gamma ray are listed in the table below:

Well Name	Well Number	API Number	Distance from Well(s)	Azimuth (Degrees)	COGCC Document Identifier Number — Log File
Dundee	3	05-123-12777	512	301	996971

Should you have any questions, please contact our office. Thank you for your consideration.

Sincerely,

Kerr-McGee Oil and Gas Onshore LP

Samantha Petite
Samantha Petite
Regulatory Analyst