

CNTY:	Weld	FTG:	990 FNL and 1650 FWL	IP GAS:	0
STATE:	CO	Q-Q:	NENW	IP OIL:	0
ROTARY SPUD:	27-Jun-55	SEC.:	12	IP WTR:	0
COMP/PA:	6-Jul-55	TWS:	7N	CUM GAS:	0
STATUS:	DA	RGE:	59W	CUM OIL:	0
WBD DATE:	31-Aug-21	BY:	SMB	CUM WTR:	0
LAT/LONG:	40.593836/-103.929057			LAST PROD:	n/a

CURRENT WELLBORE DIAGRAM

KBE:	<u>4877</u>	'
KB:	<u>22</u>	'
GLE:	4855	'

WCR 119 & Hwy 14. S 1/10. E Into.

CASING HEAD: [None](#)
WELLHEAD: [None](#)

Plug #3

TD (ft): 6610 '

PBTD (ft): 0 '

CASING RECORD						
HOLE (in)	SIZE (in)	WT (lb/ft)	GRADE	TOP (ft)	BTM (ft)	JTS
12 1/4	10 3/4	32.75	H40	0	169	

Float Collar @

TUBING RECORD COND: _____ DATE: _____

SIZE (in)	WT (lb/ft)	GRADE	TOP (ft)	TALLY (ft)	JTS

ITEM	DESC	SIZE (in)	TALLY (ft)	JTS

PERFORATION RECORD

[illegible]

WELLWORK HISTORY

DA since 1955

Plug 1 = 20 sx from 6560 to 6500

Plug 2 = 10 sx from 160 to 140

Plug 3 = 5 sx at surface

Plug #1

OPEN HOLE

8-3/4" Hole to 6590 '

OPEN HOLE

TD @ 6610 '
6-1/4" Hole