
Main Pass
Run 01 GR CCL
Run 02 GR CCL
Run 03 GR CCL
Run 04 GR CCL
Run 05 GR CCL
Run 06 GR CCL
Run 07 GR CCL
Run 08 GR CCL
Run 09 GR CCL
Run 10 GR CCL
Run







Repeat Pass

Recorded With 0 PSI Surface Induced Pressure

Database File: log_rg-44-7-297_rdd_8-9-2021_1field_federal rg 44-7-297_rdd_08-09-21.db
Dataset Pathname: repeat3
Presentation Format: cbl_rpdb_3in
Dataset Creation: Tue Aug 10 13:20:33 2021
Charted by: Depth in Feet scaled 1:240

Sensor	Offset (ft)	Schematic	Description	Length (ft)	O.D. (in)	Weight (lb)
mSec_Count	23.78		STD BLCH-14375	1.04	1.44	1.00
RBT_Status	23.78		Standard 5-7/16" Braided Line Cable Head with 1" Fishing Neck			
Error_Ct	23.78					
			BTA-AWD	2.92	2.72	25.00
			BTA 2-3/4" Roller 6 Arm Centralizer with Reversible Ends			
RBT_HV	19.83					
RBT_TEMP	17.92					
			RBT5-RADN-2707 (RBT2707_Base)	9.20	2.75	
RBT_ACCZ	14.88		Probe 2.75" RADN 6 Sector Bond Tool w/ Temperature			
RBT_ACCY	14.88					
RBT_ACCX	14.88					
WVF3SYNC	14.88					
WVF5B	14.88					
WVF5T	14.88					
WVF5R	14.88					
WVF5S	14.88					
WVF5H	14.88					
WVF5G	14.88					
WVF5Z	14.88					
WVF5I	14.88		BTA-AWD	2.92	2.72	25.00
WVFCAL	14.88		BTA 2-3/4" Roller 6 Arm Centralizer with Reversible Ends			
WVF3FT	14.88					
WVF5FT	13.88					
CCL	6.80					
			Probe GR-CCL-ARL-2750 A (FW1305-083)	4.54	2.75	55.00
			Probe 2.75" Analog 4 Channel Pulse Gamma Ray/CCL Combined			
GR	4.06					
			CENT-BC275-5000	2.83	2.75	24.00
			Probe 2.75" Bowspring Centralizer			
			Plug-FA150-0000	0.33	1.38	1.00
			1.56" Ball Plug			

Dataset: log_federal rg 44-7-297_rdd_08-09-21.db: field/well/run1/main.5
Total length: 23.78 ft
Total weight: 131.00 lb
O.D.: 2.75 in

Calibration Report

Database File: c:\programdata\wavrion\database_rg 44-7-297_rdd_8-9-2021_1field_federal rg 44-7-297_rdd_08-09-21.db
Dataset Pathname: main.5
Dataset Creation: Tue Aug 10 11:14:01 2021

Gamma Ray Calibration Report

Serial Number: FW1305-083
Tool Model: 2750 A
Performed: Sun Nov 12 05:37:57 2017

Calibrator Value: 637.0 GAPI

Background Reading: 95.7 cps
Calibrator Reading: 562.0 cps

Sensitivity: 0.7188 GAPI/cps

Segmented Cement Bond Log Calibration Report

Serial Number: RBT2707_Base
Tool Model: RADN-2707

Calibration Casing Diameter: 4.500 in
Calibration Depth: 28.242 ft

Master Calibration, performed (Derived)

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3	-0.003	0.813	0.250	81.196	99.149	0.557
CAL	-0.004	0.754				
5	-0.005	0.617	0.250	81.196	130.092	0.930
SUM						
S1	-0.004	0.834	0.000	100.000	119.308	0.457
S2	-0.001	0.844	0.000	100.000	118.344	0.144
S3	-0.002	0.844	0.000	100.000	118.170	0.224
S4	-0.003	0.821	0.000	100.000	121.368	0.304
S5	-0.003	0.777	0.000	100.000	128.755	0.403
S6	-0.003	0.770	0.000	100.000	129.874	0.443
S7	-0.000	0.788	0.000	100.000	126.897	0.035
S8	-0.006	0.799	0.000	100.000	124.242	0.692

Air Zero Calibration, performed Mon Aug. 9 08:10:58 2021

	Raw (v)		Calibrated (v)		Results	
	Zero		Zero		Offset	
3	0.000		0.000		0.000	
5	0.000		0.000		0.000	
SUM						
S1	0.000		0.000		0.000	
S2	0.000		0.000		0.000	
S3	0.000		0.000		0.000	
S4	0.000		0.000		0.000	
S5	0.000		0.000		0.000	
S6	0.000		0.000		0.000	
S7	0.000		0.000		0.000	
S8	0.000		0.000		0.000	

Inclinometer Calibration Report

Performed: Wed Mar. 22 09:49:34 2019

	Low Read	High Read	Low Ref	High Ref	
X Accelerometer	-923.00	912.00	-1.00	1.00	gee
Y Accelerometer	-895.00	877.00	-1.00	1.00	gee
Z Accelerometer	-0.10	860.00	0.00	1.00	gee

RELIANCE WIRELINE SERVICES

Company	TEP Rocky Mountain LLC
Well	Federal RG 44-7-297
Field	Sulphur Creek
County	Rio Blanco
State	Colorado