

FORM  
5A

Rev  
09/20

State of Colorado

Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:

401663854

Date Received:

09/28/2021

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 10071

2. Name of Operator: HIGHPOINT OPERATING CORPORATION

3. Address: 555 17TH ST STE 3700

City: DENVER State: CO Zip: 80202

4. Contact Name: Kate Miller

Phone: (720) 440-6116

Fax:

Email: regulatory@bonanzacrk.com

5. API Number 05-123-45715-00

7. Well Name: Anschutz-Williams

8. Location: QtrQtr: NWSW Section: 27 Township: 5N Range: 61W Meridian: 6

9. Field Name: WATTENBERG Field Code: 90750

6. County: WELD

Well Number: 5-61-27-3225B

## Completed Interval

FORMATION: NIOBRARA Status: PRODUCING Treatment Type: HYDRAULIC FRACTURING  
Treatment Date: 03/25/2018 End Date: 04/28/2018 Date this Formation was Completed: 05/14/2018  
Perforations Top: 6512 Bottom: 16117 No. Holes: 2880 Hole size: 37/100 Open Hole: ☐

Describe the Formation Treatment, including the following: type of fluid used (gel, slickwater, etc.), type and concentration of acid used (HCl, HF, etc.), types and amounts of proppant(s) used, depth details of multiple zones, and method used to determine flowback volume.

80 STAGE WET SHOE PLUG AND PERF 12,475,320 LBS 20/40 SAND, 1,289,200 LBS 100# MESH, 1,131 BBLS 15% HCL ACID, AND 171,380 BBLS SLICKWATER

This formation is commingled with another formation: ☐ Yes ☒ No

Total fluid used in treatment (bbl): 172511 Max pressure during treatment (psi): 8439  
Total gas used in treatment (mcf): 0 Fluid density at initial fracture (lbs/gal): 8.34  
Type of gas used in treatment: Min frac gradient (psi/ft): 0.78  
Total acid used in treatment (bbl): 1131 Number of staged intervals: 80  
Recycled or Reused Fluids used in treatment (bbl): 0 Flowback volume recovered (bbl): 52282  
Fresh water used in treatment (bbl): 171380 Disposition method for flowback: DISPOSAL  
Total proppant used (lbs): 13764520

Fracture stimulations must be reported on [FracFocus.org](https://www.fracfocus.org)

### Test Information:

06/12/2018 Hours: 24 Bbl oil: 41 Mcf Gas: 22 Bbl H2O: 547  
Date Calculated 24 hour rate: Bbl oil: 41 Mcf Gas: 22 Bbl H2O: 547 GOR: 537  
Test Method: FLOWING Casing PSI: 1116 Tubing PSI: 531 Choke Size: 14/34  
Gas Disposition: SOLD Gas Type: DRY Btu Gas: 1638 API Gravity Oil: 64  
Tubing Size: 2 + 3/8 Tubing Setting Depth: 6172 Tbg setting date: 05/14/2018 Packer Depth:  
Reason for Non-Production:  
Date formation Abandoned: Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt  
\*\* Bridge Plug Depth: \*\* Sacks cement on top: \*\* Wireline and Cement Job Summary must be attached.

### Comment:

1. The bottom of the completed interval is at 2386' FNL and 495' FEL of Section 26.
2. The wellbore beyond the unit boundary setback is physically isolated by: wet shoe sub and float collar
3. HighPoint Operating Corporation certifies that none of the wellbore beyond the unit boundary setback was completed.

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: Print Name: Ashley Noonan  
Title: Sr. Regulatory Analyst Date: 9/28/2021 Email: regulatory@bonanzacrk.com

## Attachment List

Att Doc Num	Name
401663854	FORM 5A SUBMITTED

Total Attach: 1 Files

### General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
		Stamp Upon Approval

Total: 0 comment(s)