

FORM  
2

Rev  
12/20

State of Colorado  
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203  
Phone: (303) 894-2100 Fax: (303) 894-2109



Document Number:

402378550

(SUBMITTED)

Date Received:

10/29/2021

APPLICATION FOR PERMIT TO:

☒ Drill ☐ Deepen ☐ Re-enter ☐ Recomplete and Operate

Amend ☐

TYPE OF WELL OIL ☒ GAS ☐ COALBED ☐ OTHER: \_\_\_\_\_

Refill ☐

ZONE TYPE SINGLE ZONE ☒ MULTIPLE ZONES ☐ COMMINGLE ZONES ☐

Sidetrack ☐

Well Name: Blehm Well Number: 11  
Name of Operator: BAYSWATER EXPLORATION & PRODUCTION LLC COGCC Operator Number: 10261  
Address: 730 17TH ST STE 500  
City: DENVER State: CO Zip: 80202  
Contact Name: Lauren Walsh Phone: (720)881 4502 Fax: ( )  
Email: lwalsh@bayswater.us

RECLAMATION FINANCIAL ASSURANCE

Plugging and Abandonment Bond Surety ID: 20080034

WELL LOCATION INFORMATION

Surface Location

QtrQtr: Lot 3 Sec: 18 Twp: 7N Rng: 66W Meridian: 6  
Footage at Surface: 2585 Feet FSL 1708 Feet FWL  
Latitude: 40.574264 Longitude: -104.825688  
GPS Data: GPS Quality Value: 1.6 Type of GPS Quality Value: PDOP Date of Measurement: 02/20/2020  
Ground Elevation: 5078  
Field Name: WATTENBERG Field Number: 90750

Well Plan: is ☐ Directional ☒ Horizontal (highly deviated) ☐ Vertical

If Well plan is Directional or Horizontal attach Deviated Drilling Plan and Directional Data.

Subsurface Locations

Top of Productive Zone (TPZ)

Sec: 13 Twp: 7N Rng: 67W Footage at TPZ: 796 FSL 160 FEL  
Measured Depth of TPZ: 8424 True Vertical Depth of TPZ: 7441 FNL/FSL FEL/FWL

Base of Productive Zone (BPZ)

Sec: 14 Twp: 7N Rng: 67W Footage at BPZ: 782 FSL 160 FWL  
Measured Depth of BPZ: 18043 True Vertical Depth of BPZ: 7311 FNL/FSL FEL/FWL

Bottom Hole Location (BHL)

Sec: 14 Twp: 7N Rng: 67W Footage at BHL: 782 FSL 160 FWL  
FNL/FSL FEL/FWL

## LOCAL GOVERNMENT PERMITTING INFORMATION

County: WELD

Municipality: N/A

Is the Surface Location of this Well in an area designated as one of State interest and subject to the requirements of § 24-65.1-108 C.R.S.? Yes

Per § 34-60-106(1)(f)(I)(A) C.R.S., the following questions pertain to the Relevant Local Government approval of the siting of the proposed Oil and Gas Location.

SB 19-181 provides that when "applying for a permit to drill," operators must include proof that they sought a local government siting permit and the disposition of that permit application, or that the local government does not have siting regulations. § 34-60-106(1)(f)(I)(A) C.R.S.

Does the Relevant Local Government regulate the siting of Oil and Gas Locations, with respect to this Location? ☒ Yes ☐ No

☒ If yes, in checking this box, I hereby certify that an application has been filed with the local government with jurisdiction to approve the siting of the proposed oil and gas location.

The disposition of the application filed with the Relevant Local Government is: Approved Date of Final Disposition: 01/27/2021

Comments: 1041WOGLA20-0083 submitted 12/3/2020, approved 1/27/2021.

## SURFACE AND MINERAL OWNERSHIP AT WELL'S OIL & GAS LOCATION

Surface Owner of the land at this Well's Oil and Gas Location: ☒ Fee ☐ State ☐ Federal ☐ Indian

Mineral Owner beneath this Well's Oil and Gas Location: ☒ Fee ☐ State ☐ Federal ☐ Indian

Surface Owner Protection Financial Assurance (if applicable): \_\_\_\_\_ Surety ID Number (if applicable): \_\_\_\_\_

### MINERALS DEVELOPED BY WELL

The ownership of all the minerals that will be developed by this Well is (check all that apply):

- ☒ Fee  
☐ State  
☐ Federal  
☐ Indian  
☐ N/A

## LEASE INFORMATION

Using standard QtrQtr, Section, Township, Range format describe one entire mineral lease as follows:

\* If this Well is within a unit, describe a lease that will be developed by the Well.

\* If this Well is not subject to a unit, describe the lease that will be produced by the Well.

(Attach a Lease Map or Lease Description or Lease if necessary.)

All, Sec 13, T7N, R67W

Total Acres in Described Lease: 640 Described Mineral Lease is: ☒ Fee ☐ State ☐ Federal ☐ Indian

Federal or State Lease # \_\_\_\_\_

## SAFETY SETBACK INFORMATION

Distance from Well to nearest:

Building: 584 Feet  
Building Unit: 819 Feet  
Public Road: 2175 Feet  
Above Ground Utility: 1052 Feet

### INSTRUCTIONS:

- Specify all distances per Rule 308.b.(1).
- Enter 5280 for distance greater than 1 mile.
- Building - nearest building of any type. If nearest Building is a Building Unit, enter same distance for both.
- Building Unit – as defined in 100 Series Rules.

Railroad: 5280 Feet  
Property Line: 14 Feet

## OBJECTIVE FORMATIONS

Objective Formation(s)	Formation Code	Spacing Order Number(s)	Unit Acreage Assigned to Well	Unit Configuration (N/2, SE/4, etc.)
CODELL	CODL	407-3241	1280	13, 14: All

Federal or State Unit Name (if appl): Unit Number:

## SUBSURFACE MINERAL SETBACKS

Enter 5280 for distance greater than 1 mile.

Is this Well within a unit? Yes

If YES:

Enter the minimum distance from the Completed Zone of this Well to the Unit Boundary: 160 Feet

Enter the minimum distance from the Completed Zone of this Well to the Completed Zone of an offset Well within the same unit permitted or completed in the same formation: 449 Feet

If NO:

Enter the minimum distance from the Completed Zone of this Well to the Lease Line of the described lease: Feet

Enter the minimum distance from the Completed Zone of this Well to the Completed Zone of an offset Well producing from the same lease and permitted or completed in the same formation: Feet

## Exception Location

☐ If this Well requires the approval of a Rule 401.c Exception Location, enter the Rule or spacing order number and attach the Exception Location Request and Waivers.

## SPACING & FORMATIONS COMMENTS

## DRILLING PROGRAM

Proposed Total Measured Depth: 18043 Feet TVD at Proposed Total Measured Depth 7311 Feet

Distance from the proposed wellbore to nearest existing or proposed wellbore belonging to another operator, including plugged wells:

Enter distance if less than or equal to 1,500 feet: 178 Feet ☐ No well belonging to another operator within 1,500 feet

Will a closed-loop drilling system be used? Yes

Is H<sub>2</sub>S gas reasonably expected to be encountered during drilling operations at concentrations greater than or equal to 100 ppm? No If yes, attach an H<sub>2</sub>S Drilling Plan unless a plan was already submitted with the Form 2A per Rule 304.c.(10).

Will there be hydraulic fracture treatment at a depth less than 2,000 feet in this well? No

Will salt sections be encountered during drilling? No

Will salt based (>15,000 ppm Cl) drilling fluids be used? No

Will oil based drilling fluids be used? Yes

BOP Equipment Type: ☒ Annular Preventor ☒ Double Ram ☒ Rotating Head ☐ None

Beneficial reuse or land application plan submitted?

Reuse Facility ID: or Document Number:

**CASING PROGRAM**

<u>Casing Type</u>	<u>Size of Hole</u>	<u>Size of Casing</u>	<u>Grade</u>	<u>Wt/Ft</u>	<u>Csg/Liner Top</u>	<u>Setting Depth</u>	<u>Sacks Cmt</u>	<u>Cmt Btm</u>	<u>Cmt Top</u>
CONDUCTOR	26	16	N/A	43	0	80	400	80	0
SURF	13+1/2	9+5/8	J-55	36	0	1500	660	1500	0
1ST	8+1/2	5+1/2	P-110	20	0	18043	7311	18043	2500

☐ Conductor Casing is NOT planned

**POTENTIAL FLOW AND CONFINING FORMATIONS**

<u>Zone Type</u>	<u>Formation /Hazard</u>	<u>Top M.D.</u>	<u>Top T.V.D.</u>	<u>Bottom M.D.</u>	<u>Bottom T.V.D.</u>	<u>TDS (mg/L)</u>	<u>Data Source</u>	<u>Comment</u>
Groundwater	Groundwater	0	0	205	205	501-1000	Groundwater Sample	Sample Site ID 766369, 753716
Groundwater	Groundwater	205	205	1190	1190	501-1000	Other	Area Report Microsoft PowerPoint - UPWQ_PPT_01-29Hearing
Confining Layer	Confining Layer	1190	1190	3800	3600			
Hydrocarbon	Hydrocarbon	3800	3600	4300	3980			
Hydrocarbon	Hydrocarbon	4500	4153	4800	4416			
Hydrocarbon	Hydrocarbon	5200	4742	5600	5082			
Confining Layer	Confining Layer	5600	5082	7600	6983			
Confining Layer	Confining Layer	7600	6983	7700	7025			
Hydrocarbon	Hydrocarbon	7700	7025	8000	7309			
Confining Layer	Ft Hays	8000	7309	8100	7351			Not Productive
Hydrocarbon	Codell	8100	7351	18043	7311			The TVD of the deepest hydrocarbon zone is the bottom of the well and not the bottom of the formation. The formation is not planned to be exited.

**OPERATOR COMMENTS AND SUBMITTAL**

Comments: Nearest wellbore in proposed unit is the Blehm 10 per anti-collision.

Nearest permitted or existing wellbore belonging to another operator is the Stout 1N (API #05-123-50477) DG Status per anti-collision.

Drake PC MM14-15D (API: 05-123-33878) PR Status is <150' @ 126'. Well is Bayswater operated; no 408.u is required.

This application is in a Comprehensive Area Plan No CAP #: \_\_\_\_\_

Oil and Gas Development Plan Name Blehm 18-I Pad OGDID #: 480293

Location ID: 481002

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: \_\_\_\_\_ Print Name: Justin Garrett

Title: Regulatory Analyst Date: 10/29/2021 Email: regulatory@ascentgeomatics.c



Based on the information provided herein, this Application for Permit-to-Drill complies with COGCC Rules, applicable orders, and SB 19-181 and is hereby approved.

COGCC Approved: \_\_\_\_\_ Director of COGCC Date: \_\_\_\_\_  
Expiration Date: \_\_\_\_\_

API NUMBER

05

### Conditions Of Approval

All representations, stipulations and conditions of approval stated in the Form 2A for this location shall constitute representations, stipulations and conditions of approval for this Form 2 Permit-to-Drill and are enforceable to the same extent as all other representations, stipulations and conditions of approval stated in this Permit-to-Drill.

#### COA Type

#### Description

### Best Management Practices

<u>No</u>	<u>BMP/COA Type</u>	<u>Description</u>
1	Drilling/Completion Operations	Blowout Prevention Equipment ("BOPE"): A double ram and annular preventer will be used during drilling. Stabbing valves shall be installed in the event of reverse circulation and shall be prior tested with low and high pressure fluid.
2	Drilling/Completion Operations	Bradenhead Monitoring: Operator acknowledges and will comply with COGCC Policy for Bradenhead Monitoring during Hydraulic Fracturing Treatments in the Greater Wattenberg Area dated May 29, 2012.
3	Drilling/Completion Operations	Anti-collision: Operator will perform an anti-collision evaluation of all active (producing, shut in, or temporarily abandoned) offset wellbores that have the potential of being within 150 feet of a proposed well prior to drilling operations for the proposed well. Notice shall be given to all offset operators prior to drilling.
4	Drilling/Completion Operations	Open Hole Logging Exception: One of the first wells drilled on the pad will be logged with Cased hole Neutron Log with Gamma Ray Log from the kick-off point to into the surface casing. All wells on the pad will have a cement bond log with gamma-ray run on production casing (or on intermediate casing if production liner is run) into the surface casing. The horizontal portion of every well will be logged with a measured while-drilling gamma-ray log. The Form 5, Completion Report, for each well on the pad will list all logs run in that well and have those logs attached. The Form 5 for each well shall clearly state "Open Hole Logging Exception - No open-hole logs were run" , will clearly identify the type of log and the well (by API#) in which open hole logs were run.

Total: 4 comment(s)

### Attachment List

<u>Att Doc Num</u>	<u>Name</u>
402485130	SURFACE AGRMT/SURETY
402791264	EXCEPTION LOC REQUEST
402791265	DIRECTIONAL DATA
402791266	DEVIATED DRILLING PLAN
402803002	OPEN HOLE LOGGING EXCEPTION
402854623	WELL LOCATION PLAT

Total Attach: 6 Files

## General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
		Stamp Upon Approval

Total: 0 comment(s)



## Public Comments

No public comments were received on this application during the comment period.

