
Halliburton
Sperry-Sun
Drilling Services
Well Planning Report
Geodetic Report
Report Date: 10-Jan-2013
Survey / DLS Computation: Minimum Curvature / Lubinski
Vertical Section Azimuth: 0.000°
Vertical Section Origin: 0.000 ft, 0.000 ft
TVD Reference Datum: Rotary Table
TVD Reference Elevation: 0.000 ft above MSL
Seabed / Ground Elevation: 0.000 ft above MSL
Magnetic Declination: 0.000°
Total Field Strength: 0.000 nT
Magnetic Dip Angle: 0.000°
Declination Date: 10-Jan-2013
Magnetic Model: IGRF2010
North Reference: True North
Grid Convergence: 0.000°
Total Corr Mag North->True North: 0.000°
Local Coordinates Referenced To: Well Head
Comments
Measured Depth (ft)
Inclination (°)
Azimuth (°)
True Vertical Depth (ft)
Vertical Section (ft)
Northing (ft)
Easting (ft)
Dogleg Severity (°/100ft)
Build Rate (°/100ft)
Turn Rate (°/100ft)
Tool Face (°)
Tie On
Survey Program
Survey Tool Description
Survey Error Model
Survey Start Date
Survey End Date
Survey Type
Survey



Calibration Report

Database File: helfrich4.db
Dataset Pathname: pass1
Dataset Creation: Mon Oct 18 12:16:20 2021 by Log 7.0 B1

Gamma Ray Calibration Report

Serial Number:	061120GR	
Tool Model:	PROBE	
Performed:	Mon Oct 18 12:18:01 2021	
Calibrator Value:	1.0	GAPI
Background Reading:	0.0	cps
Calibrator Reading:	1.0	cps
Sensitivity:	0.8000	GAPI/cps

Cement Bond Log Calibration Report

Serial Number:	5.5dig040201		
Tool Model:	Probe275Digital		
Performed:	Mon Oct 18 12:13:53 2021		
Depth:	3972.57	ft	
Casing Diameter:	4.5	in	
	3' Spacing	5' Spacing	
Signal Zero:	0.25	0	mV
Calibrated Amplitude:	81.1961	81.1961	mV
Reading at Signal Zero:	0	0	V
Reading in Free Pipe:	2.36917	2.045	V
Gain:	34.1665	39.7048	
Offset:	0.25	0	