

Header Information	measured depth (ft)	inclination (°)	azimuth (°)	true vertical depth (ft)	northing +N/-S (ft)	easting +E/-W (ft)
Operator Name	725	0.09	27.5	725	0.65	-0.95
HIGHPOINT OPERATING CORPORATION	872	0.2	160.1	872	0.51	-0.81
Operator Number	963	0.3	248.7	963	0.27	-0.98
10071	1054	0.5	228.9	1053.99	-0.08	-1.5
Well Name and Number	1146	0.2	190.7	1145.99	-0.5	-1.83
WILL 6-62-15-0362CDH	1238	0.2	165.2	1237.99	-0.81	-1.82
API Number if available (Format=05-123-12345-00)	1329	0.5	207.4	1328.99	-1.32	-1.97
05-123-40123-00	1421	0.9	170	1420.98	-2.39	-2.02
Location: (Format=SWSE 16 9N35W)	1513	0.4	320.1	1512.98	-2.85	-2.11
NENW 15 6N62W	1604	0.6	316.6	1603.98	-2.26	-2.64
Citing Type: Planned or Actual	1696	0.7	353.5	1695.97	-1.35	-3.03
ACTUAL	1787	0.7	24.3	1786.96	-0.29	-2.87
Deviation Indicator	1878	1.6	32.8	1877.94	1.28	-1.95
Horizontal	1970	0.7	22.3	1969.93	2.88	-1.04
North Reference	2061	2.6	310.8	2060.89	4.74	-2.39
True	2153	2.8	312.8	2152.79	7.63	-5.62
Grid Type	2244	6.2	305	2243.49	11.96	-11.28
	2336	5.3	305.5	2335.03	17.28	-18.81
	2431	4	320.3	2429.72	22.38	-24.5
	2525	5.3	300.9	2523.41	27.13	-30.32
	2620	8.5	305.8	2617.71	33.49	-39.78
	2715	7.5	301.9	2711.79	40.88	-50.74
	2809	8.8	301.8	2804.84	47.91	-62.06
	2903	8.6	299.8	2897.76	55.19	-74.26
	2998	9.1	311	2991.63	63.65	-86.1
	3093	9	311.9	3085.45	73.54	-97.3
	3187	8.7	310.4	3178.33	83.06	-108.19
	3282	7.5	312.3	3272.38	91.89	-118.24
	3376	6.8	304.4	3365.65	99.16	-127.37
	3471	6.8	307.2	3459.98	105.74	-136.49
	3565	6.9	310.1	3553.31	112.74	-145.25
	3660	7.7	305.6	3647.54	120.12	-154.79
	3755	8.4	305.5	3741.61	127.85	-165.61
	3851	8.3	308.2	3836.59	136.21	-176.76
	3945	8	306.4	3929.64	144.29	-187.36
	4040	9.2	317.6	4023.58	153.82	-197.8
	4134	8.7	316.9	4116.43	164.56	-207.73
	4228	8.2	312.3	4209.41	174.26	-217.54
	4323	8.3	314	4303.43	183.59	-227.49
	4416	7.7	311	4395.52	192.34	-237.02
	4511	7.3	310.2	4489.71	200.41	-246.43
	4605	6.5	308.1	4583.03	207.55	-255.18
	4700	5.6	305.4	4677.5	213.55	-263.19
	4794	5.2	300.1	4771.08	218.34	-270.61
	4888	5.4	291.4	4864.68	222.09	-278.42
	4983	6.6	288.6	4959.16	225.47	-287.75
	5077	5.9	298.8	5052.6	229.52	-297.11
	5172	6.1	313.7	5147.09	235.36	-305.04
	5266	6.1	330.5	5240.56	243.15	-311.11
	5361	4.2	343.1	5335.18	250.88	-314.6
	5456	3.6	338.2	5429.96	256.97	-316.72
	5550	3.1	331.4	5523.8	261.95	-319.04
	5644	2.1	349.7	5617.7	265.87	-320.56
	5731	1.4	18.7	5704.66	268.45	-320.5

5761	0.8	79.3	5734.66	268.83	-320.18
5793	2.5	146.7	5766.65	268.29	-319.58
5825	4.9	158.6	5798.58	266.44	-318.7
5872	9.8	159.9	5845.18	260.81	-316.59
5920	14.7	164.6	5892.07	251.09	-313.57
5967	17.8	173	5937.19	238.21	-311.11
6015	20.9	169.3	5982.48	222.51	-308.62
6062	25.3	169.7	6025.7	204.38	-305.27
6109	29.6	173.7	6067.4	182.95	-302.2
6156	33.9	180.2	6107.37	158.29	-300.97
6203	39.1	180.5	6145.14	130.34	-301.14
6250	42	183.1	6180.85	99.81	-302.12
6297	46.5	184	6214.51	67.09	-304.16
6344	52.8	183.3	6244.92	31.36	-306.43
6391	58.8	182.1	6271.33	-7.45	-308.25
6438	64.5	179.4	6293.64	-48.79	-308.76
6486	70.3	176.6	6312.08	-93.05	-307.19
6519	77.2	178.6	6321	-124	-305