

FORM
5A

Rev
09/20

State of Colorado

Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:

401776246

Date Received:

COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 10071

2. Name of Operator: HIGHPOINT OPERATING CORPORATION

3. Address: 555 17TH ST STE 3700

City: DENVER State: CO Zip: 80202

4. Contact Name: Kate Miller

Phone: (303) 241-6910

Fax:

Email: regulatory@civiresources.com

5. API Number 05-123-46084-00

7. Well Name: Anschutz State

6. County: WELD

Well Number: 5-62-26-3340C

8. Location: QtrQtr: NESE Section: 27 Township: 5N Range: 62W Meridian: 6

9. Field Name: WATTENBERG Field Code: 90750

Completed Interval

FORMATION: NIOBRARA Status: PRODUCING Treatment Type: HYDRAULIC FRACTURING
Treatment Date: 06/18/2018 End Date: 07/25/2018 Date this Formation was Completed: 08/28/2018
Perforations Top: 6752 Bottom: 16524 No. Holes: 1116 Hole size: 37/100 Open Hole: ☐

Describe the Formation Treatment, including the following: type of fluid used (gel, slickwater, etc.), type and concentration of acid used (HCl, HF, etc.), types and amounts of proppant(s) used, depth details of multiple zones, and method used to determine flowback volume.

61 STAGE WET SHOE PLUG AND PERF: 9,099,356 LBS 20/40 SAND, 797,104 LBS 100# MESH, 1,214 BBLS 15% HCL ACID, AND 323,230 BBLS SLICKWATER

This formation is commingled with another formation: ☐ Yes ☒ No
Total fluid used in treatment (bbl): 324444 Max pressure during treatment (psi): 8221
Total gas used in treatment (mcf): 0 Fluid density at initial fracture (lbs/gal): 8.34
Type of gas used in treatment: Min frac gradient (psi/ft): 0.76
Total acid used in treatment (bbl): 1214 Number of staged intervals: 61
Recycled or Reused Fluids used in treatment (bbl): 0 Flowback volume recovered (bbl): 13844
Fresh water used in treatment (bbl): 323230 Disposition method for flowback: DISPOSAL
Total proppant used (lbs): 9896460

Fracture stimulations must be reported on [FracFocus.org](https://www.fracfocus.org)

Test Information:

09/26/2018 Hours: 24 Bbl oil: 299 Mcf Gas: 182 Bbl H2O: 350
Date Calculated 24 hour rate: Bbl oil: 299 Mcf Gas: 182 Bbl H2O: 350 GOR: 609
Test Method: FLOWING Casing PSI: 1069 Tubing PSI: 845 Choke Size: 16/64
Gas Disposition: SOLD Gas Type: DRY Btu Gas: 1411 API Gravity Oil: 36
Tubing Size: 2 + 3/8 Tubing Setting Depth: 6500 Tbg setting date: 08/07/2018 Packer Depth:
Reason for Non-Production:
Date formation Abandoned: Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt
** Bridge Plug Depth: ** Sacks cement on top: ** Wireline and Cement Job Summary must be attached.

Comment:

1. The bottom of the completed interval is at 2100' FSL and 498' FEL of Section 25.
2. The wellbore beyond the unit boundary setback is physically isolated by: wet shoe sub and float collar
3. HighPoint Operating Corporation certifies that none of the wellbore beyond the unit boundary setback was completed.

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: Print Name: Ashley Noonan
Title: Sr. Regulatory Analyst Date: Email: regulatory@civiresources.com

Attachment List

Att Doc Num	Name
-------------	------

--	--

Total Attach: 0 Files

General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
Permit	Returned to Draft 10/27/2021 for Highpoint AOC Batch 4.	10/27/2021

Total: 1 comment(s)