

# OIL AND GAS CONSERVATION COMMISSION DEPARTMENT OF NATURAL RESOURCES OF THE STATE OF COLORADO

DEC 16 1971



File in duplicate for Patented and Federal lands.  
File in triplicate for State lands.

COLORADO OIL &amp; GAS COMMISSION

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		5. LEASE DESIGNATION AND SERIAL NO. COMM.
2. NAME OF OPERATOR Rex Monahan		6. IF INDIAN, ALLOTTEE OR TRIBE NAME
3. ADDRESS OF OPERATOR Box 1231, Sterling, Colorado 80751		7. UNIT AGREEMENT NAME
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements. See also space 17 below.) At surface SE SW Sec. 9-9N-53W At proposed prod. zone		8. FARM OR LEASE NAME Whittaker
14. PERMIT NO.		9. WELL NO. #1
15. ELEVATIONS (Show whether DF, RT, GR, etc.) 4083 KB		10. FIELD AND POOL, OR WILDCAT
16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data		11. SEC., T., E., M., OR BLK. AND SURVEY OR AREA Sec. 9-9N-53W
17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)		12. COUNTY Logan
		13. STATE Colorado

### NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐PULL OR ALTER CASING ☐FRACTURE TREAT ☐MULTIPLE COMPLETE ☐SHOOT OR ACIDIZE ☐ABANDON ☒REPAIR WELL ☐CHANGE PLANS ☐(Other) ☐

### SUBSEQUENT REPORT OF:


WATER SHUT-OFF ☐REPAIRING WELL ☐FRACTURE TREATMENT ☐ALTERING CASING ☐SHOOTING OR ACIDIZING ☐ABANDONMENT ☐(Other) ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

Date of work December 18, 1971

Run sand from PBTD of 4850' to 50' above "D" sand perforations, which are at 4724'-4728' and dump 10 sacks of cement.

Heavy mud to bottom of surface casing at 95'. Dump 15 sacks of cement in bottom of surface casing. Heavy mud in surface casing and 10 sacks of cement plug in top of surface casing. Cut off below ground level and weld on cap.



18. I hereby certify that the foregoing is true and correct

SIGNED

TITLE Operator

DATE Dec. 15, 1971

(This space for Federal or State office use)

APPROVED BY

TITLE

DIRECTOR

O &amp; G COMM. COMM.

DATE

DEC 16 1971

CONDITIONS OF APPROVAL, IF ANY: