

FORM  
5A

Rev  
09/20

## State of Colorado

### Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Document Number:

402828997

Date Received:

11/18/2021

### COMPLETED INTERVAL REPORT

The completed interval Report, Form 5A, shall be submitted within thirty (30) days of completing a formation (successful or not), when a formation is temporarily abandoned or permanently abandoned, for a recompletion, reperforation or restimulation, or when a formation is commingled. Fill out a section for each formation. Attach as many pages as required to fully describe the work. List in order of completion.

1. OGCC Operator Number: 100322  
2. Name of Operator: NOBLE ENERGY INC  
3. Address: 1001 NOBLE ENERGY WAY  
City: HOUSTON State: TX Zip: 77070  
4. Contact Name: Mosiah Montoya  
Phone: (303) 228-4200  
Fax: \_\_\_\_\_  
Email: denverregulatory@chevron.onmicrosoft.com

5. API Number 05-123-25057-00  
6. County: WELD  
7. Well Name: GUTTERSEN USX DD  
Well Number: 17-19  
8. Location: QtrQtr: NWNW Section: 17 Township: 3N Range: 63W Meridian: 6  
9. Field Name: WATTENBERG Field Code: 90750

### Completed Interval

FORMATION: CODELL Status: COMMINGLED Treatment Type: \_\_\_\_\_  
Treatment Date: 05/16/2011 End Date: 05/16/2011 Date this Formation was Completed: 06/10/2011  
Perforations Top: 6811 Bottom: 6820 No. Holes: 36 Hole size: 0.41 Open Hole: ☐

Describe the Formation Treatment, including the following: type of fluid used (gel, slickwater, etc.), type and concentration of acid used (HCl, HF, etc.), types and amounts of proppant(s) used, depth details of multiple zones, and method used to determine flowback volume.

This formation is commingled with another formation: ☒ Yes ☐ No

Total fluid used in treatment (bbl): \_\_\_\_\_ Max pressure during treatment (psi): \_\_\_\_\_  
Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): \_\_\_\_\_  
Type of gas used in treatment: \_\_\_\_\_ Min frac gradient (psi/ft): \_\_\_\_\_  
Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: \_\_\_\_\_  
Recycled or Reused Fluids used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_  
Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: \_\_\_\_\_  
Total proppant used (lbs): \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

#### Test Information:

Hours: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_  
Date: \_\_\_\_\_ Calculated 24 hour rate: Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_ GOR: \_\_\_\_\_  
Test Method: \_\_\_\_\_ Casing PSI: \_\_\_\_\_ Tubing PSI: \_\_\_\_\_ Choke Size: \_\_\_\_\_  
Gas Disposition: \_\_\_\_\_ Gas Type: \_\_\_\_\_ Btu Gas: \_\_\_\_\_ API Gravity Oil: \_\_\_\_\_  
Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_  
Reason for Non-Production: \_\_\_\_\_  
Date formation Abandoned: \_\_\_\_\_ Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt \_\_\_\_\_  
\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: DAKOTA Status: ABANDONED WELLBORE/COMPLETION Treatment Type: \_\_\_\_\_  
Treatment Date: \_\_\_\_\_ End Date: \_\_\_\_\_ Date this Formation was Completed: \_\_\_\_\_  
Perforations Top: 7482 Bottom: 7568 No. Holes: 40 Hole size: 0.42 Open Hole: ☐

Describe the Formation Treatment, including the following: type of fluid used (gel, slickwater, etc.), type and concentration of acid used (HCl, HF, etc.), types and amounts of proppant(s) used, depth details of multiple zones, and method used to determine flowback volume.

This formation is commingled with another formation: ☐ Yes ☒ No

Total fluid used in treatment (bbl): \_\_\_\_\_ Max pressure during treatment (psi): \_\_\_\_\_  
Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): \_\_\_\_\_  
Type of gas used in treatment: \_\_\_\_\_ Min frac gradient (psi/ft): \_\_\_\_\_  
Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: \_\_\_\_\_  
Recycled or Reused Fluids used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_  
Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: \_\_\_\_\_  
Total proppant used (lbs): \_\_\_\_\_

Fracture stimulations must be reported on FracFocus.org

**Test Information:**

Hours: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_  
Date: \_\_\_\_\_ Calculated 24 hour rate: Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_ GOR: \_\_\_\_\_  
Test Method: \_\_\_\_\_ Casing PSI: \_\_\_\_\_ Tubing PSI: \_\_\_\_\_ Choke Size: \_\_\_\_\_  
Gas Disposition: \_\_\_\_\_ Gas Type: \_\_\_\_\_ Btu Gas: \_\_\_\_\_ API Gravity Oil: \_\_\_\_\_  
Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_  
Reason for Non-Production: Dakota was perforated but never produced  
Date formation Abandoned: 07/03/2007 Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt \_\_\_\_\_  
\*\* Bridge Plug Depth: 7385 \*\* Sacks cement on top: 2 \*\* Wireline and Cement Job Summary must be attached.

FORMATION: J SAND Status: PRODUCING Treatment Type: \_\_\_\_\_  
Treatment Date: \_\_\_\_\_ End Date: \_\_\_\_\_ Date this Formation was Completed: 07/25/2007  
Perforations Top: 7264 Bottom: 7296 No. Holes: 72 Hole size: 0.42 Open Hole: ☐  
Describe the Formation Treatment, including the following: type of fluid used (gel, slickwater, etc.), type and concentration of acid used (HCl, HF, etc.), types and amounts of proppant(s) used, depth details of multiple zones, and method used to determine flowback volume.

This formation is commingled with another formation: ☐ Yes ☒ No  
Total fluid used in treatment (bbl): \_\_\_\_\_ Max pressure during treatment (psi): \_\_\_\_\_  
Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): \_\_\_\_\_  
Type of gas used in treatment: \_\_\_\_\_ Min frac gradient (psi/ft): \_\_\_\_\_  
Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: \_\_\_\_\_  
Recycled or Reused Fluids used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_  
Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: \_\_\_\_\_  
Total proppant used (lbs): \_\_\_\_\_

Fracture stimulations must be reported on FracFocus.org

**Test Information:**

Hours: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_  
Date: \_\_\_\_\_ Calculated 24 hour rate: Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_ GOR: \_\_\_\_\_  
Test Method: \_\_\_\_\_ Casing PSI: \_\_\_\_\_ Tubing PSI: \_\_\_\_\_ Choke Size: \_\_\_\_\_  
Gas Disposition: \_\_\_\_\_ Gas Type: \_\_\_\_\_ Btu Gas: \_\_\_\_\_ API Gravity Oil: \_\_\_\_\_  
Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_  
Reason for Non-Production: Cast Iron flowthrough plug  
Date formation Abandoned: \_\_\_\_\_ Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt \_\_\_\_\_  
\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: NIOBRARA-CODELL Status: PRODUCING Treatment Type: \_\_\_\_\_  
Treatment Date: \_\_\_\_\_ End Date: \_\_\_\_\_ Date this Formation was Completed: 06/10/2011  
Perforations Top: 6596 Bottom: 6820 No. Holes: 84 Hole size: \_\_\_\_\_ Open Hole: ☐  
Describe the Formation Treatment, including the following: type of fluid used (gel, slickwater, etc.), type and concentration of acid used (HCl, HF, etc.), types and amounts of proppant(s) used, depth details of multiple zones, and method used to determine flowback volume.

Describe the Formation Treatment, including the following: type of fluid used (gel, slickwater, etc.), type and concentration of acid used (HCl, HF, etc.), types and amounts of proppant(s) used, depth details of multiple zones, and method used to determine flowback volume.

This formation is commingled with another formation: ☒ Yes ☐ No

Total fluid used in treatment (bbl): \_\_\_\_\_ Max pressure during treatment (psi): \_\_\_\_\_  
Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): \_\_\_\_\_  
Type of gas used in treatment: \_\_\_\_\_ Min frac gradient (psi/ft): \_\_\_\_\_  
Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: \_\_\_\_\_  
Recycled or Reused Fluids used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_  
Fresh water used in treatment (bbl): \_\_\_\_\_ Disposition method for flowback: \_\_\_\_\_  
Total proppant used (lbs): \_\_\_\_\_

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Hours: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_  
Date: \_\_\_\_\_ Calculated 24 hour rate: Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_ GOR: \_\_\_\_\_  
Test Method: \_\_\_\_\_ Casing PSI: \_\_\_\_\_ Tubing PSI: \_\_\_\_\_ Choke Size: \_\_\_\_\_  
Gas Disposition: \_\_\_\_\_ Gas Type: \_\_\_\_\_ Btu Gas: \_\_\_\_\_ API Gravity Oil: \_\_\_\_\_  
Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_  
Reason for Non-Production: \_\_\_\_\_  
Date formation Abandoned: \_\_\_\_\_ Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt \_\_\_\_\_  
\*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

FORMATION: NIOBRARA Status: COMMINGLED Treatment Type: \_\_\_\_\_  
Treatment Date: 06/08/2011 End Date: 06/08/2011 Date this Formation was Completed: 06/10/2011  
Perforations Top: 6596 Bottom: 6692 No. Holes: 48 Hole size: 0.72 Open Hole: ☐

Describe the Formation Treatment, including the following: type of fluid used (gel, slickwater, etc.), type and concentration of acid used (HCl, HF, etc.), types and amounts of proppant(s) used, depth details of multiple zones, and method used to determine flowback volume.

227,558 lbs 20/40 Ottawa Sand

This formation is commingled with another formation: ☒ Yes ☐ No

Total fluid used in treatment (bbl): \_\_\_\_\_ Max pressure during treatment (psi): \_\_\_\_\_  
Total gas used in treatment (mcf): \_\_\_\_\_ Fluid density at initial fracture (lbs/gal): \_\_\_\_\_  
Type of gas used in treatment: \_\_\_\_\_ Min frac gradient (psi/ft): \_\_\_\_\_  
Total acid used in treatment (bbl): \_\_\_\_\_ Number of staged intervals: \_\_\_\_\_  
Recycled or Reused Fluids used in treatment (bbl): \_\_\_\_\_ Flowback volume recovered (bbl): \_\_\_\_\_  
Fresh water used in treatment (bbl): 6347 Disposition method for flowback: \_\_\_\_\_  
Total proppant used (lbs): 227558

**Fracture stimulations must be reported on FracFocus.org**

**Test Information:**

Hours: \_\_\_\_\_ Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_  
Date: \_\_\_\_\_ Calculated 24 hour rate: Bbl oil: \_\_\_\_\_ Mcf Gas: \_\_\_\_\_ Bbl H2O: \_\_\_\_\_ GOR: \_\_\_\_\_

Test Method: \_\_\_\_\_ Casing PSI: \_\_\_\_\_ Tubing PSI: \_\_\_\_\_ Choke Size: \_\_\_\_\_  
 Gas Disposition: \_\_\_\_\_ Gas Type: \_\_\_\_\_ Btu Gas: \_\_\_\_\_ API Gravity Oil: \_\_\_\_\_  
 Tubing Size: \_\_\_\_\_ Tubing Setting Depth: \_\_\_\_\_ Tbg setting date: \_\_\_\_\_ Packer Depth: \_\_\_\_\_  
 Reason for Non-Production:   
 Date formation Abandoned: \_\_\_\_\_ Squeeze: ☐ Yes ☐ No If yes, number of sacks cmt \_\_\_\_\_  
 \*\* Bridge Plug Depth: \_\_\_\_\_ \*\* Sacks cement on top: \_\_\_\_\_ \*\* Wireline and Cement Job Summary must be attached.

Comment:

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.  
 Signed: \_\_\_\_\_ Print Name: Julie Webb  
 Title: Sr. Regulatory Analyst Date: 11/18/2021 Email julie.webb@chevron.com  
 :

### **Attachment List**

<b><u>Att Doc Num</u></b>	<b><u>Name</u></b>
402828997	FORM 5A SUBMITTED

Total Attach: 1 Files

### **General Comments**

<b><u>User Group</u></b>	<b><u>Comment</u></b>	<b><u>Comment Date</u></b>
Permit	Permitting review complete.	01/07/2022
Permit	According to docnum: 1977258, the top perf of the Dakota should be 7482.	11/04/2021

Total: 2 comment(s)