



Locate  
Well  
Correctly

OFFICE OF STATE OIL INSPECTOR  
Oil and Gas Conservation  
Department

293-6

LOG OF OIL AND GAS WELL

RAMEY #5

BEST IMAGE  
AVAILABLE

Company British-American Oil Producing Co. Address P. O. Box 620, Casper, Wyoming  
State or Patented Patented Field Walker Block State Colorado  
Well No. 5 Sec. 21 T. 9N R. 53W Meridian County Logan

Location 355 Ft. (S) of N Line and 915 Ft. (W) of E Line of NW Elevation 4132' GL  
(Derrick floor relative to sea level)

The information given herewith is a complete and correct record of the well and all work done thereon so far as can be determined from all available records.

Date July 1, 1952

Signed *Thomas M. Stogian*  
Title District Superintendent

The summary on this page is for the condition of the well as above data.  
Commenced drilling Apr. 9, 1952 Finished drilling April 18, 19 52

#### OIL SANDS OR ZONES

No. 1, from 4783 to 4812	No. 4, from _____ to _____
No. 2, from 4885 to Not penetrated	No. 5, from _____ to _____
No. 3, from _____ to _____	No. 6, from _____ to _____

#### IMPORTANT WATER SANDS

No. 1, from _____ to _____	No. 3, from _____ to _____
No. 2, from _____ to _____	No. 4, from _____ to _____

#### CASING RECORD

Size	Weight per ft.	Threads per inch	Make	Amount	Kind of Shoe	Cut & Pulled from	Perforated From To	Purpose
9-5/8	25.4		Armco	200				
5 1/2	15.5	8 Rd	J-55		Baker			

#### MUDDING AND CEMENTING RECORD

Size	Where Set	No. Sacks of Cement	Methods used	Mud Gravity	Amount of Mud Used
9-5/8"	217 KB	160	HOWCO		
5 1/2"	4973 KB	250	HOWCO		

#### PLUGS AND ADAPTERS

Heaving plug-Material \_\_\_\_\_ Length \_\_\_\_\_ Depth Set \_\_\_\_\_  
Adapters-Material \_\_\_\_\_ Size \_\_\_\_\_

#### SHOOTING RECORD

Size	Shell Used	Explosive Used	Quantity	Date	Depth Shot	Depth Cleaned Out

#### TOOLS USED

Rotary Tools used from 0 ft. to 4975 ft. and from \_\_\_\_\_ ft. to \_\_\_\_\_ ft.  
Cable tools were used from 4903 ft. to 4962 ft. and from \_\_\_\_\_ ft. to \_\_\_\_\_ ft.

#### DATES

19 \_\_\_\_\_ Put to producing 6-14 19 52  
The production for the first 24 hours was 133 Barrels of fluid of which  
.925 % was oil, .075 % ~~water~~ ~~sediment~~ % sediment. Gravity 30, 38 Est.  
If gas well, cu. ft. per 24 hours \_\_\_\_\_ Gallons gasoline per 1,000 cu. ft.  
of gas \_\_\_\_\_ Rock Pressure, lbs. per sq. in. \_\_\_\_\_

#### EMPLOYEES

Herndon Drilling Company  
\_\_\_\_\_, Driller  
\_\_\_\_\_, Driller  
\_\_\_\_\_, Driller

#### FORMATION RECORD

From	To	Total Feet	Formation
0	222	222	Surface clay & gravel
222	4780	4558	Shale
4780	4817	37	Sand & sandy shale
4817	4895	78	Sandy shale
4895	4975	80	Sand & sandy shale