

Vision Energy, LLC
Calf Canyon 11-4A
Garfield County
NW SW Section 11, T6S, R102W
COC-10378
API # 05-045-6405

1. Perform Bradenhead test on well.
2. Doze brush and trees off of enough of location to be able to set rig, base beam and pump and pit.
3. Set a 5-1/2" CIBP at 5815'. Spot a minimum of 50' of cement on top of plug (6 sacks of Class II neat).
4. Pressure test 5 1/2" casing to 500psi. Contact BLM & COGCC for additional plugging requirements if unsuccessful.
5. Perforate 5 1/2" casing at 2815'
6. Set bottom of tubing at 2865'.
7. Spot a balanced plug a minimum of 100' from 2865' to 2765' (32 sacks of Class II neat cement) inside and outside of casing.
8. WOC at least 1.5 hours and then tag cement top. If not at 2765' or higher, top off with additional cement to get to 2765'.
9. Trip out of hole laying down pipe.
10. Perforate 5 1/2" casing at 950'.
11. Attempt to establish circulation through holes from 950' through bradenhead.
12. Spot a balanced plug from 950' up to 850' using a minimum of 32 sacks of Class II neat cement inside and outside of casing.
13. Wait at least 1.5 hours and then tag cement top. If not at 850' or higher, top off with additional cement to get to that depth.
14. Excavate around surface casing and cut off casing 4' below grade.
15. Top off the 5 1/2" and 5 1/2" X 8 5/8" annulus with cement from 50' back to surface.
16. Weld a steel marker plate with weep hole onto the casing stub. The marker plate is to be inscribed with the following information:

Maralex Resources, Inc./Vision Energy, LLC
Calf Canyon 11-4A
COC 10378
NWSW 11 6S 102W
05-045-6485

Regulatory Contacts:

BLM – Jim Annable O: 970.876.9033 C: 970.930.7188

COGCC – Aaron Katz O: 303.894.2100 ext. 5691 C: 970.765.6300