



00273120

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEYRECEIVED
SUBMIT IN TRIPLICATE*
(Other instructions on reverse side)

OCT 14 1980

Form approved.
Budget Bureau No. 42-R1424.

5. LEASE DESIGNATION AND SERIAL NO.

C-17366

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

1. OIL WELL <input type="checkbox"/> GAS WELL <input checked="" type="checkbox"/> OTHER <input type="checkbox"/> Dry Hole		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR C & K Petroleum, Inc.		8. FARM OR LEASE NAME Federal	
3. ADDRESS OF OPERATOR 1600 Broadway, Ste. 1700, Denver, Colorado 80202		9. WELL NO. 2-23X	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface 1400' FNL & 2020' FWL Sec. 23		10. FIELD AND POOL, OR WILDCAT Blue Gravel	
14. PERMIT NO. Colo. 7547		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6800' Ground	
		12. COUNTY OR PARISH Moffat	
		13. STATE Colorado	

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

☐
☐
☐
☐

PULL OR ALTER CASING

☐
☐
☐
☐

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON*

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

☐
☐
☐
☐

REPAIRING WELL

☐
☐
☐
☒

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Moved on well October 11, 1978 with workover rig. Ran tubing, loaded hole with 9 1/2#/gal. mud. Spotted 65 sx cement plug 4500'-3775'. Cut 4 1/2" casing off at 1300' and pulled. Placed 35 sx cement plug 1350'-1225'. Placed 35 sx cement plug 350'-270'. Set marker with 10 sx cement in top of surface casing. Cleaned up location. Plugged and Abandoned October 20, 1978.

DVR	
FJP	
HHM	
JAM	
JJD	
RLS	
CGM	

✓ BLM RELEASE LETTER REC'D ON 9-29-80

18. I hereby certify that the foregoing is true and correct

SIGNED

George E. Farmer

TITLE

Division Operations Mgr.

DATE

10/30/78

(This space for Federal or State office use)

APPROVED BY

TITLE

FOR

E. W. GUYNN
DISTRICT ENGINEER

DATE

OCT 9 1980

CONDITIONS OF APPROVAL IF ANY:

*See Instructions on Reverse Side

Colorado STATE O & G