
LOG MEASURED FROM RKB AT 28'
Tuvalu Timor Sea Basin
MAIN LOG



REPEAT SECTION

Database File	ocilas united b s 16-20-16c.db
Dataset Pathname	pass1.1
Presentation Format	xfore_ob_oasis sections (2)
Dataset Creation	Sat Jan 08 11:33:52 2022
Charted by	Depth in Feet scaled 1:240

Calibration Report

Database File	ocilas united b s 16-20-16c.db
Dataset Pathname	pass5.1
Dataset Creation	Sat Jan 08 11:46:06 2022

Gamma Ray Calibration Report

Serial Number	FWX05-066	
Tool Model	GCT375-5000	
Performed	Mon May 4 14:53:10 2020	
Calibrator Value	1.0	GAPI
Background Reading	0.0	cps
Calibrator Reading	1.0	cps
Sensitivity	0.5800	GAPI/cps

Segmented Cement Bond Log Calibration Report

Serial Number/	FWX05-055	
Tool Model	CBL	
Calibration Casing Diameter	5.500	in
Calibration Depth	350.071	ft

Master Calibration, performed Fri Jan 7 08:13:25 2022

	Raw (u)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	0.000	1.074	0.800	71.921	88.273	0.774
CAL	-0.000	1.194				
5'	-0.099	0.809	0.800	71.921	88.892	-0.829
SUM						
B1	0.001	1.055	0.000	71.921	68.243	-0.050
B2	0.000	1.051	0.000	71.921	68.418	-0.000
B3	0.000	1.061	0.000	71.921	65.932	-0.015
B4	-0.001	1.052	0.000	71.921	68.314	0.050
B5	0.000	1.056	0.000	71.921	68.056	-0.000
B6	0.001	1.056	0.000	71.921	71.543	-0.081
B7	0.000	1.002	0.000	71.921	71.822	-0.033
B8	0.000	1.058	0.000	71.921	68.026	-0.031

Internal Reference Calibration, performed (Not Performed)

	Raw (u)		Calibrated (u)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.000	-0.000	1.194	1.000	0.000

Air Zero Calibration, performed Tue Sep 21 11:19:14 2021

	Raw (u)		Calibrated (u)		Results	
	Zero		Zero		Offset	
3'	0.000		0.000		0.000	
5'	0.000		0.000		0.000	
SUM						
S1	0.000		0.000		0.000	
S2	0.000		0.000		0.000	
S3	0.000		0.000		0.000	
S4	0.000		0.000		0.000	
S5	0.000		0.000		0.000	
S6	0.000		0.000		0.000	
S7	0.000		0.000		0.000	
S8	0.000		0.000		0.000	

Log Variables

Database:C:\Program Data\Warrior\Data\ocilas united b s 16-20-16c.db
Dataset: \test\test\run1\pass3.5r .xxx

Top - Bottom

BOREID	BOTTEMP	CASEOD	CASETHICK	CASEWGHT	MAXAMPL	MINAMPL	MINATTN
in	degF	in	in	lb/ft	mV	mV	dB/ft
7.875	100	5.5	0.304	17	71.9	1	0.6

PERFS	PPT	SRFTEMP	TDEPTH
	usec	degF	ft
No	0	0	0

Variable Description

BOREID : Borehole I.D.
BOTTEMP : Bottom Hole Temperature
CASEOD : Casing O.D.
CASETHICK : Casing Thickness
CASEWGHT : Casing Weight
MAXAMPL : Maximum Amplitude
MINAMPL : Minimum Amplitude
MINATTN : Minimum Attenuation
PERFS : Perforation Flag
PPT : Predicted Pipe Time
SRFTEMP : Surface Temperature
TDEPTH : Total Depth

Company	EXTRACTION OIL AND GAS
Well	UNITED B 516-20-16C
Field	WATTENBERG
County	BROOMFIELD
State	COLORADO
Country	USA