

0	AMPS4	100
0	AMPS5	100
0	AMPS6	100
0	AMPS7	100
0	AMPS8	100

REPEAT SECTION

Database File	civitas vic east 21e-20-03.db
Dataset Pathname	pass4
Presentation Format	sfww_cbl_oasis-sectors (2)
Dataset Creation	Wed Jan 19 23:05:37 2022
Charted by	Depth in Feet scaled 1:240

-5	CCL	5	0	AMP (mV)	100	0	AMPS1	100	200	VDL (usec)	1200	1	RADIAL MAP	8	
0	GR (GAPI)	150	650	TT (usec)	150	0	AMPS2	100							
			0	AMPx5 (mV)	20	0	AMPS3	100							
						0	AMPS4	100							
						0	AMPS5	100							
						0	AMPS6	100							
						0	AMPS7	100							
						0	AMPS8	100							



-5	CCL	5	0	AMP (mV)	100	0	AMPS1	100	200	VDL (usec)	1200	1	RADIAL MAP	8	
0	GR (GAPI)	150	650	TT (usec)	150	0	AMPS2	100							
			0	AMPx5 (mV)	20	0	AMPS3	100							
						0	AMPS4	100							
						0	AMPS5	100							
						0	AMPS6	100							
						0	AMPS7	100							
						0	AMPS8	100							

Calibration Report

Database File	civitas vic east 21e-20-03.db
Dataset Pathname	pass5
Dataset Creation	Wed Jan 19 23:10:47 2022

Gamma Ray Calibration Report

Serial Number:	FW1905-098	
Tool Model:	GCT275-0000	
Performed:	Mon May 4 14:03:10 2020	
Calibrator Value:	1.0	GAPI
Background Reading:	0.0	cps
Calibrator Reading:	1.0	cps
Sensitivity:	0.5800	GAPI/cps

Segmented Cement Bond Log Calibration Report

Serial Number:	FW1905-055	
Tool Model:	Probe	
Calibration Casing Diameter:	5.500	in
Calibration Depth:	643.550	ft

Master Calibration, performed Wed Jan 19 21:36:49 2022:

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	0.000	1.065	0.800	71.921	66.795	0.774
CAL	-0.000	1.183				
5'	-0.000	0.916	0.800	71.921	77.654	0.826
SUM						
S1	0.001	1.065	0.000	71.921	67.547	-0.049
S2	0.001	1.141	0.000	71.921	63.076	-0.038
S3	0.000	1.108	0.000	71.921	64.953	-0.015
S4	-0.001	1.050	0.000	71.921	68.455	0.050
S5	0.000	1.002	0.000	71.921	71.808	-0.011
S6	0.001	0.979	0.000	71.921	73.538	-0.083
S7	0.000	0.980	0.000	71.921	73.457	-0.034
S8	0.000	1.045	0.000	71.921	68.855	-0.031

Internal Reference Calibration, performed (Not Performed):

	Raw (v)		Calibrated (v)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.000	-0.000	1.183	1.000	0.000

Air Zero Calibration, performed Tue Sep 21 11:19:14 2021:

	Raw (v)	Calibrated (v)	Results
	Zero	Zero	Offset
3'	0.000	0.000	0.000
5'	0.000	0.000	0.000
SUM			
S1	0.000	0.000	0.000
S2	0.000	0.000	0.000
S3	0.000	0.000	0.000
S4	0.000	0.000	0.000
S5	0.000	0.000	0.000
S6	0.000	0.000	0.000
S7	0.000	0.000	0.000
S8	0.000	0.000	0.000

Log Variables

DatabaseC:\ProgramData\Warrior\Data\civitas vic east 21e-20-03.db
Dataset field/well/run1/pass5/_vars_

Top - Bottom

BOREID	BOTTEMP	CASEOD	CASETHCK	CASEWGHT	MAXAMPL	MINAMPL	MINATTN
in	degF	in	in	lb/ft	mV	mV	db/ft
7.875	100	5.5	0.304	17	71.9	1	0.8

PERFS	PPT	SRFTEMP	TDEPTH
	usec	degF	ft
No	0	0	0

Variable Description

BOREID : Borehole I.D.
BOTTEMP : Bottom Hole Temperature
CASEOD : Casing O.D.
CASETHCK : Casing Thickness
CASEWGHT : Casing Weight
MAXAMPL : Maximum Amplitude
MINAMPL : Minimum Amplitude
MINATTN : Minimum Attenuation
PERFS : Perforation Flag
PPT : Predicted Pipe Time
SRFTEMP : Surface Temperature
TDEPTH : Total Depth

Company	EXTRACTION OIL & GAS, INC.
Well	VIC EAST 21E-20-03
Field	WATTENBERG
County	WELD
State	COLORADO
Country	USA