





REPEAT SECTION

Database File cicitas vic east 16e-20-01 db
Dataset Pathname pass6
Presentation Format sfwv_cbl_oasis-sectors (2)
Dataset Creation Wed Jan 19 14:39:55 2022
Charted by Depth in Feet scaled 1:240



Calibration Report

Database File cicitas vic east 16e-20-01.db
Dataset Pathname pass7
Dataset Creation Wed Jan 19 14:45:18 2022

Gamma Ray Calibration Report

Serial Number: FWT905-098
Tool Model: GGT275-50000
Performed: Mon May 4 14:03:10 2020

Calibrator Value: 1.0 GAPI

Background Reading: 0.0 cps
Calibrator Reading: 1.0 cps

Sensitivity: 0.5800 GAPI/cps

Segmented Cement Bond Log Calibration Report

Serial Number: FWT905-055
Tool Model: Probe

Calibration Casing Diameter: 5.500 in
Calibration Depth: 275.800 ft

Master Calibration, performed Wed Jan 19 13:18:06 2022:

	Raw (v)		Calibrated (mv)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
3'	0.000	1.014	0.800	71.921	70.165	0.773
CAL	-0.000	1.188				
5'	-0.000	0.873	0.800	71.921	81.480	0.827
SUM						
S1	0.001	1.000	0.000	71.921	71.954	-0.053
S2	0.001	1.053	0.000	71.921	68.346	-0.041
S3	0.000	1.057	0.000	71.921	68.050	-0.016
S4	-0.001	1.020	0.000	71.921	70.462	0.052
S5	0.000	0.969	0.000	71.921	74.231	-0.012
S6	0.001	0.936	0.000	71.921	76.896	-0.087
S7	0.000	0.926	0.000	71.921	77.706	-0.036
S8	0.000	0.988	0.000	71.921	72.856	-0.033

Internal Reference Calibration, performed (Not Performed):

	Raw (v)		Calibrated (v)		Results	
	Zero	Cal	Zero	Cal	Gain	Offset
CAL	0.000	0.000	-0.000	1.188	1.000	0.000

Air Zero Calibration, performed Tue Sep 21 11:19:14 2021:

	Raw (v)	Calibrated (v)	Results
	Zero	Zero	Offset
3'	0.000	0.000	0.000
5'	0.000	0.000	0.000
SUM			
S1	0.000	0.000	0.000
S2	0.000	0.000	0.000
S3	0.000	0.000	0.000
S4	0.000	0.000	0.000
S5	0.000	0.000	0.000
S6	0.000	0.000	0.000
S7	0.000	0.000	0.000
S8	0.000	0.000	0.000

Log Variables

DatabaseC:\ProgramData\Warrior\Data\cicitas vic east 16e-20-01.db
Dataset field/well/run1/pass7/_vars_

Top - Bottom

BOREID	BOTTEMP	CASEOD	CASETHCK	CASEWGHT	MAXAMPL	MINAMPL	MINATTN
in	degF	in	in	lb/ft	mV	mV	db/ft
7.875	100	5.5	0.361	20	71.9	1	0.8

PERFS	PPT	SRFTEMP	TDEPTH
	usec	degF	ft
No	0	0	0

Variable Description

BOREID : Borehole I.D.
BOTTEMP : Bottom Hole Temperature
CASEOD : Casing O.D.
CASETHCK : Casing Thickness
CASEWGHT : Casing Weight
MAXAMPL : Maximum Amplitude
MINAMPL : Minimum Amplitude
MINATTN : Minimum Attenuation
PERFS : Perforation Flag
PPT : Predicted Pipe Time
SRFTEMP : Surface Temperature
TDEPTH : Total Depth

Company	EXTRACTION OIL & GAS, INC.
Well	VIC EAST 16E-20-01
Field	WATTENBERG
County	WELD
State	COLORADO
Country	USA