

Well

Operator
Location
County
State
Field
Footages
At Surface
Elevations

WHEELER 32-1

EnCana Oil & Gas (USA) Inc.
SW NE Section 1-T1N-R69W, 6th P.M.
Boulder
Colorado
Wattenberg

1970' FNL & 2206' FEL
4979' KB
4963' GR

API 05-013-06507-00
Spud Date 02-21-2005
TD Date 02-28-2005

Log Tops

| | |
|--------------|---------|
| Sussex | 4273.9' |
| Sussex Mkr. | 4554.9' |
| Shannon | 4839.7' |
| Sharon Spgs. | 7207.5' |
| Niobrara | 7259.4' |
| Codell | 7591.8' |
| J Sand | 8022.9' |
| Log TD | 8190.0' |

Production Tubing

2-3/8" tubing, set @ 7253'



8189' — Driller's
TD



01622956

RECEIVED

MAR -8 06

COGCC



Surface Casing and Cement

8 5/8", 24#, landed @ 904', cemented with 388 sxs

Main Hole

7-7/8" to TD

Production Casing and Cement

4-1/2", 11.6#, landed @ 8186', cemented with 300 sxs

DV Tool

Set @ 5210', cemented above DV tool with 300 sxs

Perf'd Niobrara from 7262' - 7272', 7355' - 7385' @ 4 spf
Frac'd Niobrara with 181,692 gal frac fluid and 200,851# sand
on 11-29-05

CBP

Set @ 7485' on 11-24-05

Perf'd Codell from 7593' - 7613' @ 4 spf
Frac'd Codell with 111,426 gal frac fluid and 196,629# sand
on 03-13-05

J-Sand Perf'd from 8040' - 8060' @ 2 spf
Frac'd J Sand with 207,862 gal frac fluid and 300,700# sand
on 03-08-05