



MUSTANG

RESOURCES, LLC

EMERGENCY #1-888-291-8588

MEAD

24-14MV-6S-94W

API# 05-045-06557

SW SW SEC. 24 6S 94W

GARFIELD, CO

ACCESS FROM CR 320

EMS 911





PLAINS



17213

114718

210
Bbls

PRODUCED WATER

KEEP OUT OF REACH OF CHILDREN. FOR INDUSTRIAL USE ONLY.
SEE MATERIAL SAFETY DATA SHEET FOR ADDITIONAL INFORMATION.

EMERGENCY TELEPHONE (24 HOURS)
800-424-9300 (CHEMTREC)

WARNING

MAY CAUSE EYE AND SKIN IRRITATION.
MAY BE HARMFUL IF SWALLOWED.
MAY CONTAIN HIGHLY TOXIC AND
FLAMMABLE HYDROGEN SULFIDE (H₂S)
GAS IN HEADSPACE OF TANK,
TANK CAR, OR TANK TRUCK.



PRECAUTIONS

PROTECT EYES, SKIN AND CLOTHING FROM CONTACT WITH PRODUCT.
WEAR RECOMMENDED PROTECTIVE EQUIPMENT.
USE WITH ADEQUATE VENTILATION.
KEEP CONTAINER TIGHTLY CLOSED WHEN NOT IN USE.
WASH THOROUGHLY AFTER HANDLING.

FIRST AID

EYES: IMMEDIATELY FLUSH EYES WITH PLENTY OF CLEAR WATER
FOR 15 MINUTES. IF IRRITATION PERSISTS, CALL PHYSICIAN.
SKIN: IN CASE OF CONTACT, IMMEDIATELY WASH SKIN WITH SOAP
AND WATER. IN CASE OF INJECTION INTO OR UNDER THE SKIN,
OR INTO ANY PART OF THE BODY, INDIVIDUAL SHOULD BE
EVALUATED IMMEDIATELY BY A PHYSICIAN.
INHALATION: IF OVERCOME BY VAPOR, IMMEDIATELY MOVE TO
FRESH AIR AND CALL A PHYSICIAN. IF BREATHING IS IRREGULAR
OR HAS STOPPED, START RESUSCITATION, ADMINISTER OXYGEN,
IF AVAILABLE.

FIRE

FOAM, WATER SPRAY, DRY CHEMICAL, CARBON DIOXIDE
AND VAPORIZING LIQUID TYPE EXTINGUISHING AGENTS MAY ALL
BE SUITABLE FOR EXTINGUISHING FIRES INVOLVING THE TYPE
OF PRODUCT.

SPILLS

SHUT OFF AND ELIMINATE ALL IGNITION SOURCES. KEEP PEOPLE AWAY.
RECOVER FREE PRODUCT. ADD SAND, EARTH OR OTHER SUITABLE
ABSORBENT TO SPILL AREA. MINIMIZE SKIN CONTACT. VENTILATE
CONFINED SPACES. OPEN ALL WINDOWS AND DOORS. KEEP PRODUCT
OUT OF SEWERS AND WATERCOURSES BY DRAINING OR PUMPING.
ADVISE AUTHORITIES IF PRODUCT HAS ENTERED OR MAY ENTER
SEWER, WATERCOURSE, OR EXTENSIVE LAND AREA.



90
BB15

PRODUCED WATER

HAZARDOUS MATERIALS CLASSIFICATION
CLASIFICACIÓN DE MATERIALES PELIGROSOS

HEALTH HAZARD
4 - Deadly
3 - Extreme danger
2 - Hazardous
1 - Slightly hazardous
0 - Normal material

PELIGRO PARA LA SALUD
4 - Mortal
3 - Gravemente peligroso
2 - Peligroso
1 - Ligeramente peligroso
0 - Material normal

SPECIFIC HAZARD
Oxidizer OX
Acid ACID
Alkali ALK
Corrosive COR
Use NO WATER W
Radiation Hazard **

PELIGRO ESPECÍFICO
Oxidante OX
Ácido ACID
Alcalino ALK
Corrosivo COR
NO USAR AGUA W
Peligro de radiación **

FIRE HAZARD
Flash Points
4 - Below 73° F
3 - Below 100° F
2 - Below 200° F
1 - Above 200° F
0 - Will not burn

PELIGRO DE FUEGO
Puntos de inflamación
4 - Por debajo de 73°
3 - Por debajo de 100°
2 - Por debajo de 200°
1 - Por encima de 200°
0 - No arde

INSTABILITY
4 - May detonate
3 - Shock and heat may detonate
2 - Violent chemical change
1 - Unstable if heated
0 - Stable

INESTABILIDAD
4 - Puede explotar en caso de choque o calentamiento
3 - Puede explotar en caso de choque o calentamiento
2 - Cambio químico violento
1 - Inestable en caso de calentamiento
0 - Estable

