

JOB SUMMARY

HALLIBURTON LOCATION BRISTOL, CO



RECEIVED
1985
CONS. COMM.

WELL DATA

FIELD Wildcat SEC. 24 TWP. 33 RNS. 61W COUNTY ADAMS STATE CO

FORMATION NAME SURFIRE TYPE SAND

FORMATION THICKNESS FROM TO

INITIAL PROD: OIL SPD. WATER SPD. GAS MCFD

PRESENT PROD: OIL SPD. WATER SPD. GAS MCFD

COMPLETION DATE MUD TYPE MUD WT.

PACKER TYPE SET AT

BOTTOM HOLE TEMP. PRESSURE

MEAS. DATA TOTAL DEPTH

NEW USED	WEIGHT	SIZE	FROM	TO	MAXIMUM PSI ALLOWABLE
<u>20</u>	<u>16.6</u>	<u>4 1/2</u>	<u>0</u>	<u>7830</u>	<u>10500</u>
CASING					
LINER					
TUBING					
OPEN HOLE		<u>7 1/8</u>	<u>0</u>	<u>6725</u>	<u>SHOTS/FT.</u>
PERFORATIONS					
PERFORATIONS					
PERFORATIONS					

TOOLS AND ACCESSORIES

TYPE AND SIZE	QTY.	MAKE
FLOAT COLLAR		
FLOAT SHOE		
GUIDE SHOE		
CENTRALIZERS		
BOTTOM PLUG		
TOP PLUG		
HEAD		
PACKER		
OTHER		

MATERIALS

TREAT. FLUID DENSITY LB/GAL API

DISPL. FLUID DENSITY LB/GAL API

PROP. TYPE SIZE LB.

PROP. TYPE SIZE LB.

ACID TYPE GAL.

ACID TYPE GAL.

ACID TYPE GAL.

SURFACTANT TYPE GAL. IN

WET AGENT TYPE GAL. IN

FLUID LOSS ADD. TYPE GAL-LB. IN

GELLING AGENT TYPE GAL-LB. IN

FRIC. RED. AGENT TYPE GAL-LB. IN

BREAKER TYPE GAL-LB. IN

BLOCKING AGENT TYPE GAL-LB.

PERF PAC BALLS TYPE QTY.

OTHER

OTHER

JOB DATA

CALLER OUT	ON LOCATION	JOB STARTED	JOB COMPLETED
DATE <u>8/24/85</u> TIME <u>18 00</u>	DATE <u>8/26/85</u> TIME <u>21 00</u>	DATE <u>8/27/85</u> TIME <u>00 30</u>	DATE <u>8/27/85</u> TIME <u>00 40</u>

PERSONNEL AND SERVICE UNITS

NAME	UNIT NO. & TYPE	LOCATION
<u>B. ZEDMAN</u>	<u>16424613</u>	<u>BRISTOL CO</u>
<u>T. KENNEDY</u>	<u>TMS 58</u>	<u>CO</u>
<u>B. ANDREWS</u>	<u>0548</u>	<u>BRISTOL CO</u>
<u>B. KUTEL</u>		<u>CO</u>

DEPARTMENT CMT

DESCRIPTION OF JOB Plug to Abandon

JOB DONE THRU: TUBING ☒ CASING ☐ ANNULUS ☐ TDC/ANN. ☐

CUSTOMER REPRESENTATIVE Charles E. Murray

HALLIBURTON OPERATOR B. Benjamin COPIES REQUESTED 1

CEMENT DATA

STAGE	NUMBER OF BAGS	TYPE	API CLASS	BRAND	BULK BAGGED	ADDITIVES	YIELD CU.FT./SK.	MIXED LBS./GAL.
<u>1</u>	<u>20</u>	<u>II</u>		<u>POLARIS</u>	<u>E</u>	<u>NO ADD.</u>	<u>1.15</u>	<u>156</u>
<u>2</u>	<u>10</u>	<u>II</u>		<u>POLARIS</u>	<u>E</u>	<u>"</u>	<u>1.15</u>	<u>"</u>
<u>3</u>	<u>70</u>	<u>II</u>		<u>POLARIS</u>	<u>E</u>	<u>"</u>	<u>1.15</u>	<u>"</u>

PRESSURES IN PSI

CIRCULATING 800 DISPLACEMENT 200 SUMMARY

BREAKDOWN MAXIMUM 500

AVERAGE FRACTURE GRADIENT

SHUT-IN: INSTANT 3-MIN. 15-MIN.

HYDRAULIC HORSEPOWER

ORDERED AVAILABLE USED

AVERAGE RATES IN BPM

TREATING 8 1/2 DISPL. 5 1/2 OVERALL 8 1/2

CEMENT LEFT IN PIPE

PREFLUSH 40 TYPE Huo

LOAD & SHOT: DBL-GAL. PAB: DBL-GAL.

TREATMENT: DBL-GAL. DISPL. DBL-GAL. 10

CEMENT SLURRY 4.1

TOTAL VOLUME 54.1

REMARKS 30 SK LEFT on y. for J. for Top Su PLUGS

CUSTOMER

WELL NO. 1-24 JOB TYPE PTA DATE 8/20/85

HALLIBURTON SERVICES

JOB LOG

FORM 2015 R-2

WELL 1 24

CUSTOMER COASTAL OIL & GAS CO

JOB TYPE PLUG TO ABANDON

LEASE L&L LAND CO

COASTAL OIL & GAS CO

PLUG TO ABANDON

TEST NO. 289970

PAGE NO. 1

DATE 8/26/85

RECEIVED

[illegible]

CUSTOMER