

Lithology
Lithology Key
Sandstone
Siltstone
Claystone
Limestone
Dolomite
Coal
Anhydrite
Halite
Tuff
Chert
Porcelanite
Igneous
Metamorphic
Shale
Basement
Gamma Ray (GR)
Caliper (CALI)
Bit Size (BS)
Deep Resistivity (RDEP)
Medium Resistivity (RMED)
Shallow Resistivity (RSHA)
Density Correction (DRHO)
Photoelectric Factor (PEF)
Neutron Porosity (NPHI)
Density Porosity (DPHI)
Bulk Density (RHOB)
Compressional Slowness (DTC)
Shear Slowness (DTS)
Mud Weight (MW)
Drilling Rate of Penetration (ROP)
Hookload (HKLD)
Weight on Bit (WOB)
Torque (TQA)
Rotary Speed (RPM)
Standpipe Pressure (SPPA)
Pump Flow Rate (FLOW)
Gas Ratio (GAS_RATIO)
Total Gas (TGAS)
Propane (C3)
Butane (C4)
Pentane (C5)
Hexane (C6)
Heptane (C7)
Methane (C1)
Ethane (C2)
Isobutane (IC4)
Isopentane (IC5)
Isohexane (IC6)
Isoheptane (IC7)
Normal Butane (NC4)
Normal Pentane (NC5)
Normal Hexane (NC6)
Normal Heptane (NC7)
Cuttings Description
Sandstone: light gray to gray, fine to medium grained, subangular to subrounded, moderately sorted, calcareous cement, trace glauconite, trace pyrite, fair intergranular porosity, no visible hydrocarbon stain, no fluorescence
Siltstone: dark gray to brownish gray, firm to hard, blocky, micaceous, carbonaceous, interbedded with sandstone
Claystone: gray to dark gray, soft to firm, sticky, waxy, trace fossil fragments
Limestone: white to light gray, microcrystalline, mudstone, chalky, trace fossil fragments
Dolomite: light brown to tan, microcrystalline, sucrosic, trace vuggy porosity
Coal: black, brittle, vitreous luster, conchoidal fracture
Anhydrite: white, massive, soft, granular
Halite: clear to white, cubic crystals, salty taste
Tuff: light gray, fine grained, volcanic ash, soft, clay-like
Chert: gray to black, hard, conchoidal fracture, siliceous
Porcelanite: white to light gray, hard, brittle, siliceous
Igneous: various colors, crystalline, hard, intrusive or extrusive
Metamorphic: various colors, foliated or non-foliated, hard, crystalline
Shale: dark gray to black, fissile, carbonaceous, pyritic
Basement: crystalline, hard, igneous or metamorphic
Gamma Ray (GR): 0 to 150 API
Caliper (CALI): 6 to 16 in
Bit Size (BS): 6 to 16 in
Deep Resistivity (RDEP): 0.2 to 2000 ohm.m
Medium Resistivity (RMED): 0.2 to 2000 ohm.m
Shallow Resistivity (RSHA): 0.2 to 2000 ohm.m
Density Correction (DRHO): -0.25 to 0.25 g/cm3
Photoelectric Factor (PEF): 0 to 10 b/e
Neutron Porosity (NPHI): 0.45 to -0.15 v/v
Density Porosity (DPHI): 0.45 to -0.15 v/v
Bulk Density (RHOB): 1.95 to 2.95 g/cm3
Compressional Slowness (DTC): 140 to 40 us/ft
Shear Slowness (DTS): 240 to 80 us/ft
Mud Weight (MW): 8.5 to 12.5 ppg
Drilling Rate of Penetration (ROP): 0 to 300 m/hr
Hookload (HKLD): 100 to 400 klbf
Weight on Bit (WOB): 0 to 50 klbf
Torque (TQA): 0 to 20 kft.lbf
Rotary Speed (RPM): 0 to 200 rpm
Standpipe Pressure (SPPA): 0 to 5000 psi
Pump Flow Rate (FLOW): 0 to 1000 gpm
Gas Ratio (GAS_RATIO): 0 to 100 %
Total Gas (TGAS): 0 to 1000 units
Propane (C3): 0 to 500 units
Butane (C4): 0 to 500 units
Pentane (C5): 0 to 500 units
Hexane (C6): 0 to 500 units
Heptane (C7): 0 to 500 units
Methane (C1): 0 to 1000 units
Ethane (C2): 0 to 500 units
Isobutane (IC4): 0 to 500 units
Isopentane (IC5): 0 to 500 units
Isohexane (IC6): 0 to 500 units
Isoheptane (IC7): 0 to 500 units
Normal Butane (NC4): 0 to 500 units
Normal Pentane (NC5): 0 to 500 units
Normal Hexane (NC6): 0 to 500 units
Normal Heptane (NC7): 0 to 500 units
Cuttings Description
Sandstone: light gray to gray, fine to medium grained, subangular to subrounded, moderately sorted, calcareous cement, trace glauconite, trace pyrite, fair intergranular porosity, no visible hydrocarbon stain, no fluorescence
Siltstone: dark gray to brownish gray, firm to hard, blocky, micaceous, carbonaceous, interbedded with sandstone
Claystone: gray to dark gray, soft to firm, sticky, waxy, trace fossil fragments
Limestone: white to light gray, microcrystalline, mudstone, chalky, trace fossil fragments
Dolomite: light brown to tan, microcrystalline, sucrosic, trace vuggy porosity
Coal: black, brittle, vitreous luster, conchoidal fracture
Anhydrite: white, massive, soft, granular
Halite: clear to white, cubic crystals, salty taste
Tuff: light gray, fine grained, volcanic ash, soft, clay-like
Chert: gray to black, hard, conchoidal fracture, siliceous
Porcelanite: white to light gray, hard, brittle, siliceous
Igneous: various colors, crystalline, hard, intrusive or extrusive
Metamorphic: various colors, foliated or non-foliated, hard, crystalline
Shale: dark gray to black, fissile, carbonaceous, pyritic
Basement: crystalline, hard, igneous or metamorphic
Gamma Ray (GR): 0 to 150 API
Caliper (CALI): 6 to 16 in
Bit Size (BS): 6 to 16 in
Deep Resistivity (RDEP): 0.2 to 2000 ohm.m
Medium Resistivity (RMED): 0.2 to 2000 ohm.m
Shallow Resistivity (RSHA): 0.2 to 2000 ohm.m
Density Correction (DRHO): -0.25 to 0.25 g/cm3
Photoelectric Factor (PEF): 0 to 10 b/e
Neutron Porosity (NPHI): 0.45 to -0.15 v/v
Density Porosity (DPHI): 0.45 to -0.15 v/v
Bulk Density (RHOB): 1.95 to 2.95 g/cm3
Compressional Slowness (DTC): 140 to 40 us/ft
Shear Slowness (DTS): 240 to 80 us/ft
Mud Weight (MW): 8.5 to 12.5 ppg
Drilling Rate of Penetration (ROP): 0 to 300 m/hr
Hookload (HKLD): 100 to 400 klbf
Weight on Bit (WOB): 0 to 50 klbf
Torque (TQA): 0 to 20 kft.lbf
Rotary Speed (RPM): 0 to 200 rpm
Standpipe Pressure (SPPA): 0 to 5000 psi
Pump Flow Rate (FLOW): 0 to 1000 gpm
Gas Ratio (GAS_RATIO): 0 to 100 %
Total Gas (TGAS): 0 to 1000 units
Propane (C3): 0 to 500 units
Butane (C4): 0 to 500 units
Pentane (C5): 0 to 500 units
Hexane (C6): 0 to 500 units
Heptane (C7): 0 to 500 units
Methane (C1): 0 to 1000 units
Ethane (C2): 0 to 500 units
Isobutane (IC4): 0 to 500 units
Isopentane (IC5): 0 to 500 units
Isohexane (IC6): 0 to 500 units
Isoheptane (IC7): 0 to 500 units
Normal Butane (NC4): 0 to 500 units
Normal Pentane (NC5): 0 to 500 units
Normal Hexane (NC6): 0 to 500 units
Normal Heptane (NC7): 0 to 500 units





Distance Per Division: 10.000ft Wireline Log (2.50 cm)
Depth Reference: Driller's Depth
Reference Calibrator: 0.00 ft to 10,000.00 ft

Calibrations Performed

Calibrations Used in Processing

Internal Reference Calibration, performed After Performing Logging Operations

Run 1a

Date	Offset
17-JUL-2020	0.000

Calibrations Used

Pass	Date	Offset
1	17-JUL-2020	0.000
2	17-JUL-2020	0.000
3	17-JUL-2020	0.000
4	17-JUL-2020	0.000
5	17-JUL-2020	0.000