

STATE OF COLORADO
NATURAL RESOURCES COMMISSION
DEPARTMENT OF NATURAL RESOURCES

00108202
RECEIVED
NOV 14 1982



99999999

Indicate for Patented and Federal lands.
Indicate for State lands.

5. DEED DESIGNATION & SERIAL NO.

NA

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

NA

1. OIL WELL ☒ GAS WELL ☐ OTHER ☐

7. UNIT AGREEMENT NAME

NA

2. NAME OF OPERATOR

Anadarko Production Company

8. FARM OR LEASE NAME

L & L Land Company

3. ADDRESS OF OPERATOR

Box 351, Liberal, Kansas 67901

9. WELL NO.

A-1

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)

At surface 13.0' FNL & 1980' FWL - E/2 NW

At proposed prod. zone

10. FIELD AND POOL, OR WILDCAT

NE Hombre

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

26-3S-61W

14. PERMIT NO.

821616

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

5102 GI

12. COUNTY

Admas

13. STATE

Colorado

16. Check Appropriate Box To Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT*

(Other)

(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

18. Date of work

* Must be accompanied by a cement verification report.

Drilled to a total depth of 6789', well was P & A in the following manner:

By pumping through drill pipe spotted 50 sxs Class H at 6580', 50 sxs Class H at 3397', 50 sxs Class H at 670', 10 sxs Class H 40-0', 5 sxs each rathole and mousehole. 9.5# drilling mud between all plugs.

Plugging started 10/24/82, completed 9:15 am 10/25/82.

8-5/8" surface casing will be cut off 5" below ground level and capped with steel plate.



00401770

DVR	
FJP	
HHM	
JAM	
JJD	
RLS	
CGM	

19. I hereby certify that the foregoing is true and correct

SIGNED

Paul Campbell

TITLE Division Operations Manager

DATE 11/4/82

(This space for Federal or State office use)

DIRECTOR

APPROVED BY

TITLE O & G Cons. Comm.

DATE DEC 14 1982

CONDITIONS OF APPROVAL, IF ANY: