WELL NAME:	Anschutz Equus Farms 4-62-28-0108CS	**OPERATOR:**	Highpoint Operating Corporation
FIELD:	Wattenberg	**FORMATION:**	Niobrara
SHL:	qtr-qtr NWNW Section 28 Township 4N Range 62W		
BHL:	qtr-qtr NWNW Section 27 Township 4N Range 62W		
COUNTY:	Weld **STATE:** CO	**API:**	05-123-43686

not to scale

GROUND LEVEL:	4574
KELLY BUSHING:	4594
SPUD DATE:	1/12/2018
TD DATE:	2/10/2018

SURFACE CASING

SIZE:	9 5/8"
WEIGHT:	36#
GRADE:	J-55
HOLE DEPTH:	885'
CSG DEPTH:	885'
CEMENT:	346 sx
TOC:	Surface
HOLE SIZE:	12 1/4"

INTERMEDIATE CASING

SIZE:	7"
WEIGHT:	23#
GRADE:	P-110
HOLE DEPTH:	6628'
CSG DEPTH:	6628'
CEMENT:	635 sx
TOC:	1180'
HOLE SIZE:	8 3/4"

CONDUCTOR CASING

SIZE:	16"
WEIGHT:	65#
CSG DEPTH:	80'
CEMENT:	43 sx

PRODUCTION LINER

SIZE:	4 1/2"
WEIGHT:	11.6#
GRADE:	P-110
HOLE DEPTH:	16215'
LINER TOP:	5737'
LINER SHOE:	16215'
TOTAL DEPTH MD:	16220'
CEMENT:	693 sx
TOC:	5737'
HOLE SIZE:	6 1/8"

PRODUCTION TUBING

SIZE:	2 3/8"
WEIGHT:	4.5#
GRADE:	J-55
DEPTH:	6383'

FORMATION TOPS & PERFORATIONS

Niobrara	6248'
PERFORATIONS	6677'-16122'

FRAC DATA

1,119	BBLS ACID
180,149	BBLS FRESH WATER
181,268	BBLS TOTAL FLUID
13,006,679	# 20/40 MESH
1,326,705	# 100 MESH
14,333,384	# TOTAL SAND
79	# TOTAL STAGES