


COLORADO OIL



ON COMMISSION



99999999

FIELD INSPECTION REPORT

<input checked="" type="checkbox"/> NOTICE OF UNSATISFACTORY INSPECTION <input type="checkbox"/> NOTICE OF SATISFACTORY INSPECTION		1120 Lincoln Street, Suite 801 Denver, CO 80203 (303)894-2100	
API No. 05- (075 - 7194)		LEASE NAME: Casement	
LOCATION: SESE 32-12N-54		OPERATOR: British-American	
DATE: 10-10-96		INSPECTOR: Ed Brinkley	
Insp. Type: SR	Insp. Status: PA	PA: Y <input checked="" type="radio"/> N <input type="radio"/>	Pass/Fail: P <input checked="" type="radio"/> F <input type="radio"/> Viol: Y <input checked="" type="radio"/> N <input type="radio"/> NOV: Y <input type="radio"/> N <input type="radio"/>

INSPECTION ITEM	COMMENTS	INPUT
Well ID Signs (Rule 210)	(Check file for live operator)	
Pits (Reserve/Production) (Rule 902, 903, 904)	(Previous notice - no response.)	
Fences (Rule 604.C.(3), 1003.A)		
Tank Battery Equipment (Rule 604)		
Fire Walls/Berms/Dikes (Rule 604)		
General Housekeeping (Rule 603.G)	Cement pump base, anchors, steel guards, junk.	
Spills (Oil/Water) (Rule 908)		
Bradenhead (Rule 207)		
Drilling Well/Workover (Rule 315)		
Surface Rehabilitation (Rule 317)	grass/land area	
Miscellaneous		

CORRECTIVE ACTION REQUIRED: Remove cement and equipment restore surface to grass.	
Date Corrective Action Required By:	Date Remedied:

This report is a Notice of Inspection. The Commission requires that you correct any deficiencies shown on this report in a timely manner. Failure to comply may result in enforcement action by the Commission.

White

Site



00278632

COLORADO
LOGAN COUNTY
CLIFF FIELD (E)

PETROLEUM INFORMATION
DENVER CASPER
ROCKY MOUNTAIN
OIL INFORMATION

Twp 12N-54W
Section 32
C SE SE

05 075 7194

OPR: British-American

WELL #:

5 Casement

ELEV: 4458 KB

DSTS. & CORES:

SPUD: 5-25-55

COMPL: 6-16-55

*TOPS: Log-Sample

TD: 5620

PB: 5582

Niobrara 4563

Carlile 4931

Greenhorn 5144

Bentonite 5290

D Sand 5391

J Sand 5505

DST 5420-30, 90 min,
SI 20 min, strong blow
to weak, gas in 42 min,
reversed out 25 bbls
highly D & GC mud, rec
300' highly O & GC mud,
870' muddy wtr. PB
5582.

CSG: 9-5/8" @ 213 w/160
5 1/2" @ 5614

PERF: 2" tubing @ 5575

5424-30 w/4.

PROD. ZONE:

INIT. PROD: Pumped 401 BOPD.

6-30-55

(Contr: Sterling Drlg).

*For Electric Logs on Rocky Mountain Wells—Ask Us!

OR NO: 10558 (original over)

Field No: 11400

For CD: ~~DSND~~ DSND
JSD

P
P
H
H

05 075 7194