

OPERATOR: **K.P. Kauffman Company Inc.**

WELL: **COSSLETT #1**

FIELD: **SPINDLE**

API #: **05-123-08132**

LEASE #:

UIC #:

CNTY: **DACONO/WELD**

STATE: **CO**

SPUD: **11/16/1974**

COMP: **3/4/1975**

STATUS: **PR**

WBD DATE: **8/29/2022**

FTG:

Q-Q: **NENW**

SEC.: **2**

TWS: **1N**

RGE: **68W**

BY:

## CURRENT WELLBORE DIAGRAM

KBE: **5010** '

KB: **8** '

GLE: **5002** '

TD (ft): **5215** '

PBTD (ft): **5162** '

12.25" Hole  
8.625" 24# Csg @ **574** '  
Cmtd w/400 sxs

TOC @ **3437** '  
Calc Assuming 1.15 yield

7.875" Hole  
4.5" 10.5# Csg @ **5204** '  
Cmtd w/350 sxs

SUSSEX Perfs  
4648'-4666'

SHANNON Perfs  
5080'-5098'

PBTD (ft): **5162** '

TD (ft): **5215** '

### CASING RECORD

HOLE (in)	SIZE (in)	WT (lb/ft)	GRADE	TOP (ft)	BTM (ft)
<b>12 1/4</b>	<b>8 5/8</b>	<b>24</b>		<b>0</b>	<b>574</b>
<b>7 7/8</b>	<b>4 1/2</b>	<b>10.5</b>		<b>0</b>	<b>5204</b>

### TUBING RECORD

SIZE (in)	WT (lb/ft)	GRADE	JOINTS	BTM (ft)

### PERFORATION RECORD

ZONE	TOP (ft)	BTM (ft)	HOLES	STAGE	STATUS
<b>SUSSEX</b>	<b>4648</b>	<b>4666</b>	<b>15</b>		
<b>SHANNON</b>	<b>5080</b>	<b>5098</b>	<b>15</b>		