

FORM

6

Rev  
11/20

## State of Colorado

## Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203 Phone: (303) 894-2100 Fax: (303) 894-2109



DE	ET	OE	ES
----	----	----	----

Replug By Other Operator

Document Number:

403221567

Date Received:

## WELL ABANDONMENT REPORT

This form is to be submitted as an Intent to Abandon whenever an abandonment is planned on a borehole. After the abandonment is complete, this form shall again be submitted as a Subsequent Report of the actual work completed. The approved intent shall be valid for six months after the approval date, after that period, a new intent will be required. Attachments required with the Intent to Abandon are wellbore diagrams of the current configuration and the proposed configuration with plugs set.

A Subsequent Report of Abandonment shall indicate the actual work completed. Attachments required with a Subsequent Report are a wellbore diagram showing plugs that were set and casing remaining in the hole, the job summaries from all plugging contractors used, including wireline and cementing (third party verification) and any logs that may have been run during abandonment.

OGCC Operator Number: 10651

Contact Name: Brian Stanley

Name of Operator: VERDAD RESOURCES LLC

Phone: (435) 6406426

Address: 1125 17TH STREET SUITE 550

Fax:

City: DENVER State: CO Zip: 80202

Email: bstanley@verdadresources.com

For "Intent" 24 hour notice required,

Name: Medina, Justin

Tel: (720) 471-0006

COGCC contact:

Email: justin.medina@state.co.us

Type of Well Abandonment Report: ☒ Notice of Intent to Abandon ☐ Subsequent Report of Abandonment

API Number 05-123-12937-00

Well Name: JORDAN

Well Number: 34-9

Location: QtrQtr: SWSW Section: 34 Township: 1N Range: 65W Meridian: 6

County: WELD

Federal, Indian or State Lease Number:

Field Name: WATTENBERG

Field Number: 90750

## Only Complete the Following Background Information for Intent to Abandon

Latitude: 40.002110

Longitude: -104.657432

GPS Data: GPS Quality Value: 1.3 Type of GPS Quality Value: PDOP Date of Measurement: 11/04/2022

Reason for Abandonment: ☐ Dry ☐ Production Sub-economic ☐ Mechanical Problems☒ Other Re-enter to re-plugCasing to be pulled: ☐ Yes ☐ No Estimated Depth:Fish in Hole: ☐ Yes ☐ No If yes, explain details belowWellbore has Uncemented Casing leaks: ☐ Yes ☐ No If yes, explain details below

Details:

## Current and Previously Abandoned Zones

Formation	Perf. Top	Perf. Btm	Abandoned Date	Method of Isolation	Plug Depth
NIOBRARA	7246	7342	10/06/1986	SAND PLUG/CEMENT	7246

Total: 1 zone(s)

## Casing History

Casing Type	Size of Hole	Size of Casing	Grade	Wt/Ft	Csg/Liner Top	Setting Depth	Sacks Cmt	Cmt Btm	Cmt Top	Status
SURF	12+1/4	8+5/8	j55	24	0	218	200	218	0	VISU
1ST	7+7/8	4+1/2	j55	11.6	6520	7744	260	7744	6809	CBL
OPEN HOLE	7+7/8				218	6520				

## Plugging Procedure for Intent and Subsequent Report

CIBP #1: Depth \_\_\_\_\_ with \_\_\_\_\_ sacks cmt on top. CIBP #2: Depth \_\_\_\_\_ with \_\_\_\_\_ sacks cmt on top.  
CIBP #3: Depth \_\_\_\_\_ with \_\_\_\_\_ sacks cmt on top. CIBP #4: Depth \_\_\_\_\_ with \_\_\_\_\_ sacks cmt on top.  
CIBP #5: Depth \_\_\_\_\_ with \_\_\_\_\_ sacks cmt on top.

NOTE: Two(2) sacks cement required on all CIBPs.

Set	100	sks cmt from	6510	ft. to	6310	ft.	Plug Type:	OPEN HOLE	Plug Tagged:	<input checked="" type="checkbox"/>
Set	50	sks cmt from	2500	ft. to	2400	ft.	Plug Type:	OPEN HOLE	Plug Tagged:	<input checked="" type="checkbox"/>
Set	150	sks cmt from	1425	ft. to	1000	ft.	Plug Type:	OPEN HOLE	Plug Tagged:	<input checked="" type="checkbox"/>
Set	_____	sks cmt from	_____	ft. to	_____	ft.	Plug Type:	_____	Plug Tagged:	<input type="checkbox"/>
Set	_____	sks cmt from	_____	ft. to	_____	ft.	Plug Type:	_____	Plug Tagged:	<input type="checkbox"/>

Perforate and squeeze at \_\_\_\_\_ ft. with \_\_\_\_\_ sacks. Leave at least 100 ft. in casing \_\_\_\_\_ CICR Depth

Perforate and squeeze at \_\_\_\_\_ ft. with \_\_\_\_\_ sacks. Leave at least 100 ft. in casing \_\_\_\_\_ CICR Depth

Perforate and squeeze at \_\_\_\_\_ ft. with \_\_\_\_\_ sacks. Leave at least 100 ft. in casing \_\_\_\_\_ CICR Depth

(Cast Iron Cement Retainer Depth)

Set 125 sacks half in. half out surface casing from 350 ft. to 0 ft. Plug Tagged: ☐

Set \_\_\_\_\_ sacks at surface

Cut four feet below ground level, weld on plate Above Ground Dry-Hole Marker: ☐ Yes ☐ No

Set \_\_\_\_\_ sacks in rat hole Set \_\_\_\_\_ sacks in mouse hole

### Additional Plugging Information for Subsequent Report Only

Casing Recovered: \_\_\_\_\_ ft. of \_\_\_\_\_ inch casing

Surface Plug Setting Date: \_\_\_\_\_ Cut and Cap Date: \_\_\_\_\_ Number of Days from Setting Surface Plug to Capping or Sealing the Well: \_\_\_\_\_

\*Wireline Contractor: \_\_\_\_\_

\*Cementing Contractor: \_\_\_\_\_

Type of Cement and Additives Used: \_\_\_\_\_

Flowline/Pipeline has been abandoned per Rule 1105 ☐ Yes ☐ No

Technical Detail/Comments:

A closed-loop, recirculating returns system will be utilized.

1. Provide 48 hr notice Form 42 to COGCC prior to rig up per Form 6 COA
2. Familiarize all personnel with allowed access to location and areas allowed to be disturbed.
3. Secure permission to access area and identify prospective well locations via satellite and survey data.
4. Verify well location and excavate well.
5. Once permission to begin work is secure, excavate area around well to sufficient size for safe access of casing, Verify casing size, cut off cap, weld on slip collar w/ wellhead and riser, set cellar ring and back-fill.
6. MIRU WO Rig, beam, doghouse, BOP, accumulator, rig pump, shaker tank, rig tank, 9.5ppg water-based mud, pipe float, 3-1/8" collars, 2-7/8" work string, power swivel.
7. Make up BHA ; 2 7/8 EUE string, 8x 3-1/8" drill collars, Float, POBS, 6.5" roller-cone bit.
8. RIH and drill out cement plugs from 0-218' and 1060'-1150', noting tag depths of each plug. Circulate 2 bottoms up after falling through each plug.
9. Wash/Ream in open-hole to plug @ ~6520'. If tag is not achieved, call OGCC engineer.
10. Circulate and condition hole.
11. TOOH, Lay down BHA.
12. RIH w/ 4-3/4" tri-cone and float to ~6520'
13. Circulate and condition hole. MIRU cementers
14. Tie in cementers and pump 10bbls freshwater spacer, assuring returns, followed by 100sx Class G neat cement plug from 6510'-6310' (200' plug on top of existing). Displace to EOT with freshwater and shut down.
15. POOH and wait on cement 4 hours or cement company recommended time.
16. RIH and tag plug. If tagged below 6310', contact OGCC engineer for amended orders.
17. POOH/LD to 2500'.
18. Circulate and condition hole while MIRU cementers.
19. Tie in cementers and pump 10 bbls freshwater spacer followed by 50sx Class G neat cement plug from 2500'-2400'. Displace to EOT with freshwater and shut down.
20. POOH and wait on cement 4 hours or cement company recommended time.
21. RIH and tag plug. If tagged below 2400', contact OGCC engineer for amended plugging orders.
22. POOH and LD to 1425'.
23. Tie in cementers and pump 10 bbls freshwater spacer followed by 150sx Class G neat cement plug from 1450'-1000'. Displace to EOT with freshwater and shut down.
24. POOH and wait on cement 4 hours or cement company recommended time.
25. RIH and tag plug. If tagged below 1000', contact OGCC engineer for amended plugging orders.
26. POOH and LD tbg to 350' and circulate. MIRU cementers.
27. Tie in cementers, Begin pumping 10 bbls spacer followed by cement until returns taken to surface (125sks prescribed). Once good returns taken, SD cement and POOH. Top off as necessary.
28. RDMO Cementers, Rig, and supporting equipment. Tidy location and prep for reclamation.
29. After 5 days, verify TOC is within 5' of surface. Top off if needed. Excavate cellar ring and wellhead, cut off casing 6' below ground level and weld on cap with full legal description welded onto plate. Back fill hole.
30. Reclaim location.
31. Submit Form 6 Subsequent and Form 42 for completion of COA.

I hereby certify all statements made in this form are, to the best of my knowledge, true, correct, and complete.

Signed: \_\_\_\_\_ Print Name: Brian Stanley  
Title: Completion Engineer Date: \_\_\_\_\_ Email: bstanley@verdadresources.com

Based on the information provided herein, this Well Abandonment Report (Form 6) complies with COGCC Rules and applicable orders and is hereby approved.

COGCC Approved: \_\_\_\_\_ Date: \_\_\_\_\_

**CONDITIONS OF APPROVAL, IF ANY:** \_\_\_\_\_ Expiration Date: \_\_\_\_\_

COA Type	Description
----------	-------------

0 COA	
-------	--

### Attachment List

<u>Att Doc Num</u>	<u>Name</u>
403221688	WELLBORE DIAGRAM
403221689	WELLBORE DIAGRAM
403221690	PROPOSED PLUGGING PROCEDURE
403221691	SURFACE OWNER CONSENT
403221692	LOCATION PHOTO

Total Attach: 5 Files

### General Comments

<u>User Group</u>	<u>Comment</u>	<u>Comment Date</u>
		Stamp Upon Approval

Total: 0 comment(s)