

Duncan 1 - 6
1729' FNL, 664' FEL, SEC 19 T12N R100W
Moffat County, CO

GL @ 6854'
KB @ 6970'
COMPLETION DATE: 12/2002

UPDATED 2/12/2007

API #05-081-07100

SURFACE CASING

8-5/8" 24# K-55
SET @ 875'
CMT w/ 455 sx

Hole size: 12-1/4"

PROD. CASING

4 1/2", 11.6#, P-110
SET @ 4825'
CMT w/ 1050 sx

Hole size: 7-7/8"

PRODUCTION TBG

2 3/8" 4.7# L-80 EUE rd tbg

146 jts tbg
X nipple @ 4538
1 jt tbg
XN nipple @ 4570
1 jt tbg
1 collar
EOT @ 4603'

Wasatch A-5 perfs: 2027'-2032' w/ 4 SPF, 60 deg phasing, deep penetration
frac'd w/ 288 bbl fluid (ClearFrac), 182 Mcf N2, & 57,897# 20/40 sand

Wasatch A-9 perfs: 2658'-2663' w/ 4 SPF, 60 deg phasing, deep penetration
frac'd w/ 184 bbl fluid (ClearFrac), 92 Mcf N2, & 27,527# 20/40 sand

Wasatch A-9 perfs: 2822'-2827' w/ 4 SPF, 60 deg phasing, deep penetration
frac'd w/ 174 bbl fluid (ClearFrac), 90 Mcf N2, & 25,169# 20/40 sand

Wasatch A-11 perfs: 2965'-2970' w/ 4 SPF, 60 deg phasing, deep penetration
frac'd w/ 263 bbl fluid (ClearFrac), 175 Mcf N2, & 41,007# 20/40 sand

Wasatch A-12 perfs: 3107'-3112' w/ 4 SPF, 60 deg phasing, deep penetration
frac'd w/ 205 bbl fluid (ClearFrac), 121 Mcf N2, & 31,349# 20/40 sand

Wasatch A-14 perfs: 3410'-3415' w/ 4 SPF, 60 deg phasing, deep penetration
frac'd w/ 273 bbl fluid (ClearFrac), 207 Mcf N2, & 46,611# 20/40 sand

Wasatch A-15 perfs: 3495'-3500' w/ 4 SPF, 60 deg phasing, deep penetration
frac'd w/ 279 bbl liquid (ClearFrac), 198 Mcf N2, & 45,532# 20/40 sand

Ft. Union B1 perfs: 3986'-3990' w/ 6 SPF, 60 deg, regular penetration

Ft. Union B2 perfs: 4016'-4020' & 4050'-4060' w/ 6 SPF, 60 deg, regular pntntrn
frac'd w/ 515 bbl liquid (Guar gel), 643 Mcf N2, & 128,069# 20/40 sand

Lewis perfs: 4536'-4546', 4576'-4586', & 4606'-4614'

w/ 6 SPF, 60 deg, regular penetration

frac'd w/ 683 bbl liquid (Guar gel), 988 Mcf N2, & 175,337# 20/40 sand

PBTD @ 4775'

TD @ 4825'

