

Van Schaick A #6
SEC 19 T12N R100W
Moffat County, CO

API #05-081-07062
UPDATE: CSL 02/21/07
EDBL 2/10/2010

GL @ 6846'
KB @ 6862'

COMPLETION DATE:

SURFACE CASING

Well Bore Hole 11"
8 5/8" 24# J-55
SET @ 885'

PROD. CASING

Well Bore Hole 7.875
4 1/2" 11.6# N-80 @ 4630'

PRODUCTION TBG

KB to Hanger 16'
141 jts 2-3/8" tbg
X nipple @ 4433.81'
1 jt 2-3/8" tbg
XN nipple @ 4465.98'
1 jt 2-3/8" tbg @
1 notched collar @ 4498.39'
EOT @ 4498.79'

**Wasatch perms: 2440'-2445', 2520'-2525', 2785'-2790',
2980'-2985', 3235'-3240', 3435'-3440', & 3505'-3510'**
w/ 4 JPF, 120 deg phasing

2440-2455' - 30,137 #'s sand
2520-2525' - 26,071 #'s sand
2785-2790' 31,403 #'s sand
2980'-2985' - 57923 # sand
3235'-3240' - BH prop: 37,775 lb.
3435'-3440' - BH prop: 31,132 lb
3505'-3510' - BH prop: 33,709 lb.

Ft. Union perms: 4056'-4061'
w/ 4 JPF, 120 deg phasing - BH prop: 15,633 lb.

Lewis perms: 4540'-4550'
w/ 4 JPF, 120 deg phasing - 64,743# 20/40 sand

PBTD @ 4581'

TD @ 4630'

