
Schlumberger
Gamma Ray
Caliper
Bit Size
Deep Resistivity
Medium Resistivity
Shallow Resistivity
Neutron Porosity
Density Porosity
Density Correction
Photoelectric Factor
Delta-T
Main Pass
Repeat Section
Main Pass
Repeat Section
Company: Chevron
Well: Tahoe 17-2
Field: Tahoe
County: Gulf of Mexico
State: Offshore
Location: Tahoe 17-2
Service Order: 7000-SOR-00142
Run Number: 1
Date: 14-Jun-2019
Depth Datum: Mean Sea Level
Log Measured From: Rotary Table
Permanent Datum: Mean Sea Level
Elevation: 0 ft
Elevation: 0 ft
Elevation: 0 ft
Drilling Measured From: Rotary Table
Total Depth (Driller): 18,420 ft
Total Depth (Logger): 18,418 ft
Bottom Log Interval: 18,410 ft
Top Log Interval: 1,200 ft
Casing Driller Size @ Depth: 13.375 in @ 1,198 ft
Casing Logger Depth: 1,198 ft
Bit Size: 12.250 in
Type Fluid in Hole: SBM
Density: 11.6 ppg
Viscosity: 52 s/qt
PV: 24 cP
YP: 18 lbf/100ft²
Fluid Loss: 3.2 cc/30min
Solids: 18.4 %
Sand: 0.5 %
Chlorides: 28,000 mg/L
Calcium: 1,200 mg/L
Max Recorded Temperature: 268 °F
Max Recorded Temperature Depth: 18,402 ft
Equipment: Tahoe 17-2
Recorded By: J. Whitfield
Witnessed By: R. Castellano
Run 1 Main Pass
Run 1 Repeat Section
Run 2 Main Pass
Run 2 Repeat Section
Run 3 Main Pass
Run 3 Repeat Section
Run 4 Main Pass
Run 4 Repeat Section
Run 5 Main Pass
Run 5 Repeat Section
Run

3600
3700
3750
3800
3850
3900
3950
4000
4050
4100
4150
4200
4250
4300
4350
4400
4450
4500
4550
4600
4650
4700
4750
4800
WHIPSTOCK
Amplified Amplitude
Collar Locator
Amplitude (mV)
Variable Density (usec)
Gamma Ray (GAPI)
Amplified Amplitude (mV)
Travel Time (usec)
CCL
GR


4800
4850
4900
4950
5000
5050
5100
5150
5200
5250
5300
5350
5400
5450
5500
5550
5600
5650
5700
5750
5800
5850
5900
5950
6000
6050
6100
6150
6200
6250
6300
6350
6400
6450
6500
6550
6600
6650
6700
6750
6800