

GGU 12-29A Wellbore Diagram

Last Updated: 1/6/2023



Well	County		API	Mineral/Surface	
GGU 12-29A	Garfield		05-045-07724	FEE	
Spud Date	First Sales	Lease #	TOC	Location	
3/21/2001	5/3/2001		NA	NWSW 29 6S91W	
Top Perf	Bot Perf	Float Collar	Avg Inc	PBTD	TD
4,360	5,578				5,680

Wellbore details					
CASING DETAIL	Depth	Size	Weight	Grade	Thread
Conductor Csg					
Cement					
Hole size		Notes:			
Surface Csg	640	8 5/8	24.00		
Cement	320				
Hole size	12 1/4	Notes:			
Prod Csg	5,680	4 1/2	11.60		
Cement	1200				
Hole size	7 7/8	Notes:			
TUBING DETAIL	5,485	2 3/8	4.70	J-55	
Current EOT	92.4%	Notes:			

Stages and Perf intervals

Formation Tops

Wellbore Details

4,360 4,715
4,840 5,066
5,197 5,578

PBTD:

Wasatch 3,366
Ohio Creek 3,894

Williams Fork 5,184

TD: 5,680

Surf Csg: 8-5/8" 24# set @ 640'

Hole Size: 12-1/4"
Cement: 320 sks

TOC: NA

Tubing: 2-3/8" 4.7# J-55 set @ 5485'

Prod Csg: 4-1/2" 11.6# set @ 5680'
Hole Size: 7-7/8"
Cement: 1200 sks

Formation Top	Depth
Wasatch	3,366
Ohio Creek	3,894
Williams Fork	5,184