

State of Colorado
Oil and Gas Conservation Commission

1120 Lincoln Street, Suite 801, Denver, Colorado 80203
(303)894-2100 Fax: (303)894-2109



FOR OGCC USE ONLY

WELL ABANDONMENT REPORT

Submit original plus one copy. This form is to be submitted as an intent whenever a plugging is planned on a borehole. The approved intent shall be valid for six (6) months after the approval date; after that period a new intent will be required. After the plugging is complete, this form and one copy shall again be submitted along with third party cement verification as a subsequent report of the work as actually completed.

Date Received: 12/18/2000
Doc Num: 200012323

OGCC Operator Number: 5	Contact Name and Telephone	24-hour Contact (required)
Name of Operator: COLORADO OIL & GAS CONSERVATION COMMI	JAIME ADKINS	
Address: SUITE 801 1120 LINCOLN S	Phone: 303 894-2100	
City: DENVER State: CO Zip: 80203	Fax:	Tel:

API Number: 05-107-05095 00	OGCC Lease No.:	Other wells in this lease?
Well Name: BRADLEY	Well Number: 5	
Location (QtrQtr, Sec, Twp, Rng, Mer): NENW Sec 18 T 6N R 86W PM 6		
County: ROUTT	Federal, Indian, or State Lease Number:	
Field Name: TOW CREEK	Field Number: 83100	

Attachment Checklist	Doc Num

Subsequent Report of Abandonment

Only Complete the Following Background Information for Intent to Abandon

Reason for Abandonment:
Casing to Be Pulled: Top of Casing Cement:
Fish in Hole:
Wellbore has Uncemented Casing Leaks:
Details:

Current and Previously Abandoned Zones

Formation code	Perf Top	Perf Bottom	Date Abandoned	Method of Isolation	Plug Depth

Casing History

Casing String	Casing Size	Casing Depth	Cement Top	Stage Cement Top
SURF	10 3/4	220	0	
1ST	5 1/2	2736	2000	

Plugging Procedure for Intent and Subsequent Report

CIBP # 1: Depth 2550 ft. with 2 sacks cement on top.
Perforate and squeeze at 240 ft. with 50 sacks.
Set 10 sacks at surface.
Cut all casing strings four feet below ground level, weld on plate
Set sacks in rat hole. Set sacks in mouse hole.

Leave at least 100 ft. in casing.

NOTE: Two(2) sacks cement required on all CIBPs.

Dry-Hole Marker : No

Additional Plugging Information for Subsequent Report Only

Casing Recovered: ft. of inch casing.

Plugging Date: 10/31/2000

*Wireline Contractor:

*Cementing Contractor: RIPPY SALES AND SERVICE

Type of Cement and Additives Used: G

*Attach Job Summaries

I hereby certify that the statements made in this form are, to the best of my knowledge, true, correct, and complete.

Print Name: JAIME ADKINS

Signed?

Title: AREA ENGINEER

Date: 12/18/2000

OGCC Approved: DIMATTEE

Title:

Date: 12/18/2000

CONDITIONS OF APPROVAL, IF ANY:

ERF WELL PLUGGED AS PART OF CLAUDE ALLEN BOND CLAIM