



# **Laramie Energy, LLC**

**Mesa County, CO  
Hayward 0993 25-09 Pad  
Hayward 0993-25-16E**

**A-6**

**Plan: Design #3**

## **KLX Well Planning Report**

**25 October, 2021**





# Well Planning Report



<b>Database:</b>	EDM 5000.1 Single User Db	<b>Local Co-ordinate Reference:</b>	Well Hayward 0993-25-16E
<b>Company:</b>	Laramie Energy, LLC	<b>TVD Reference:</b>	RKB @ 8037.0usft (H&P #522)
<b>Project:</b>	Mesa County, CO	<b>MD Reference:</b>	RKB @ 8037.0usft (H&P #522)
<b>Site:</b>	Hayward 0993 25-09 Pad	<b>North Reference:</b>	True
<b>Well:</b>	Hayward 0993-25-16E	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	A-6		
<b>Design:</b>	Design #3		

Project	Mesa County, CO		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	Colorado Central Zone		

Site		Hayward 0993 25-09 Pad			
Site Position:		Northing:	1,519,030.59 usft	Latitude:	39.237495
From:	Lat/Long	Easting:	2,373,084.06 usft	Longitude:	-107.713617
Position Uncertainty:	0.0 usft	Slot Radius:	13-3/16 "	Grid Convergence:	-1.40 °

Well		Hayward 0993-25-16E				
Well Position	+N/-S	2,672.6 usft	Northing:	1,521,718.19 usft	Latitude:	39.244833
	+E/-W	-648.3 usft	Easting:	2,372,501.10 usft	Longitude:	-107.715906
Position Uncertainty		0.0 usft	Wellhead Elevation:		Ground Level:	8,007.0 usft

<b>Wellbore</b>	A-6
-----------------	-----

Magnetics	Model Name	Sample Date	Declination (°)	Dip Angle (°)	Field Strength (nT)
	HDGM2021	10/25/2021	8.82	65.17	50,981.10000000

<b>Design</b>	Design #3
---------------	-----------

Audit Notes:				
Version:	Phase:	PLAN	Tie On Depth:	0.0
Vertical Section:	Depth From (TVD) (usft)	+N/-S (usft)	+E/-W (usft)	Direction (°)
	0.0	0.0	0.0	155.52

Plan Sections										
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)	TFO (°)	Target
0.0	0.00	0.00	0.0	0.0	0.0	0.00	0.00	0.00	0.00	
250.0	0.00	0.00	250.0	0.0	0.0	0.00	0.00	0.00	0.00	
583.3	10.00	195.00	581.6	-28.0	-7.5	3.00	3.00	0.00	195.00	
1,163.1	26.33	173.45	1,131.1	-205.7	-5.9	3.00	2.82	-3.72	-33.02	
6,137.9	26.33	173.45	5,589.9	-2,397.8	245.6	0.00	0.00	0.00	0.00	
7,015.6	0.00	0.00	6,437.0	-2,594.6	268.2	3.00	-3.00	0.00	180.00	
8,965.6	0.00	0.00	8,387.0	-2,594.6	268.2	0.00	0.00	0.00	0.00	PBHL - Hayward 09



# Well Planning Report



<b>Database:</b>	EDM 5000.1 Single User Db	<b>Local Co-ordinate Reference:</b>	Well Hayward 0993-25-16E
<b>Company:</b>	Laramie Energy, LLC	<b>TVD Reference:</b>	RKB @ 8037.0usft (H&P #522)
<b>Project:</b>	Mesa County, CO	<b>MD Reference:</b>	RKB @ 8037.0usft (H&P #522)
<b>Site:</b>	Hayward 0993 25-09 Pad	<b>North Reference:</b>	True
<b>Well:</b>	Hayward 0993-25-16E	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	A-6		
<b>Design:</b>	Design #3		

## Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.0	0.00	0.00	0.0	0.0	0.0	0.0	0.00	0.00	0.00
100.0	0.00	0.00	100.0	0.0	0.0	0.0	0.00	0.00	0.00
200.0	0.00	0.00	200.0	0.0	0.0	0.0	0.00	0.00	0.00
<b>KOP / Build 3° / 100'</b>									
250.0	0.00	0.00	250.0	0.0	0.0	0.0	0.00	0.00	0.00
300.0	1.50	195.00	300.0	-0.6	-0.2	0.5	3.00	3.00	0.00
400.0	4.50	195.00	399.8	-5.7	-1.5	4.5	3.00	3.00	0.00
500.0	7.50	195.00	499.3	-15.8	-4.2	12.6	3.00	3.00	0.00
<b>EOB @ 10.00° Inc. / 195.00° Azm / Build 3° / 100'</b>									
583.3	10.00	195.00	581.6	-28.0	-7.5	22.4	3.00	3.00	0.00
600.0	10.42	193.49	598.0	-30.9	-8.2	24.7	3.00	2.54	-9.04
700.0	13.07	186.54	695.9	-50.9	-11.6	41.5	3.00	2.65	-6.95
800.0	15.85	181.94	792.8	-75.8	-13.4	63.4	3.00	2.77	-4.60
900.0	18.69	178.70	888.3	-105.5	-13.5	90.4	3.00	2.84	-3.24
1,000.0	21.57	176.29	982.1	-139.9	-11.9	122.3	3.00	2.88	-2.41
1,100.0	24.48	174.43	1,074.2	-178.8	-8.7	159.1	3.00	2.91	-1.86
<b>EOB @ 26.33° Inc. / 173.45° Azm</b>									
1,163.1	26.33	173.45	1,131.1	-205.7	-5.9	184.8	3.00	2.93	-1.54
1,200.0	26.33	173.45	1,164.2	-222.0	-4.0	200.4	0.00	0.00	0.00
1,300.0	26.33	173.45	1,253.9	-266.1	1.1	242.6	0.00	0.00	0.00
1,400.0	26.33	173.45	1,343.5	-310.1	6.1	284.8	0.00	0.00	0.00
1,500.0	26.33	173.45	1,433.1	-354.2	11.2	327.0	0.00	0.00	0.00
<b>8 5/8"</b>									
1,530.0	26.33	173.45	1,460.0	-367.4	12.7	339.6	0.00	0.00	0.00
1,600.0	26.33	173.45	1,522.7	-398.3	16.2	369.2	0.00	0.00	0.00
1,700.0	26.33	173.45	1,612.4	-442.3	21.3	411.4	0.00	0.00	0.00
1,800.0	26.33	173.45	1,702.0	-486.4	26.3	453.6	0.00	0.00	0.00
1,900.0	26.33	173.45	1,791.6	-530.5	31.4	495.8	0.00	0.00	0.00
2,000.0	26.33	173.45	1,881.2	-574.5	36.4	538.0	0.00	0.00	0.00
2,100.0	26.33	173.45	1,970.9	-618.6	41.5	580.2	0.00	0.00	0.00
2,200.0	26.33	173.45	2,060.5	-662.6	46.6	622.4	0.00	0.00	0.00
2,300.0	26.33	173.45	2,150.1	-706.7	51.6	664.5	0.00	0.00	0.00
2,400.0	26.33	173.45	2,239.7	-750.8	56.7	706.7	0.00	0.00	0.00
2,500.0	26.33	173.45	2,329.4	-794.8	61.7	748.9	0.00	0.00	0.00
2,600.0	26.33	173.45	2,419.0	-838.9	66.8	791.1	0.00	0.00	0.00
2,700.0	26.33	173.45	2,508.6	-883.0	71.8	833.3	0.00	0.00	0.00
2,800.0	26.33	173.45	2,598.3	-927.0	76.9	875.5	0.00	0.00	0.00
2,900.0	26.33	173.45	2,687.9	-971.1	81.9	917.7	0.00	0.00	0.00
3,000.0	26.33	173.45	2,777.5	-1,015.1	87.0	959.9	0.00	0.00	0.00
3,100.0	26.33	173.45	2,867.1	-1,059.2	92.1	1,002.1	0.00	0.00	0.00
3,200.0	26.33	173.45	2,956.8	-1,103.3	97.1	1,044.3	0.00	0.00	0.00
3,300.0	26.33	173.45	3,046.4	-1,147.3	102.2	1,086.5	0.00	0.00	0.00
3,400.0	26.33	173.45	3,136.0	-1,191.4	107.2	1,128.7	0.00	0.00	0.00
<b>G' Sand</b>									
3,401.1	26.33	173.45	3,137.0	-1,191.9	107.3	1,129.2	0.00	0.00	0.00
3,500.0	26.33	173.45	3,225.6	-1,235.5	112.3	1,170.9	0.00	0.00	0.00
3,600.0	26.33	173.45	3,315.3	-1,279.5	117.3	1,213.1	0.00	0.00	0.00
3,700.0	26.33	173.45	3,404.9	-1,323.6	122.4	1,255.3	0.00	0.00	0.00
3,800.0	26.33	173.45	3,494.5	-1,367.6	127.4	1,297.5	0.00	0.00	0.00
3,900.0	26.33	173.45	3,584.1	-1,411.7	132.5	1,339.7	0.00	0.00	0.00
4,000.0	26.33	173.45	3,673.8	-1,455.8	137.6	1,381.9	0.00	0.00	0.00
4,100.0	26.33	173.45	3,763.4	-1,499.8	142.6	1,424.1	0.00	0.00	0.00
4,200.0	26.33	173.45	3,853.0	-1,543.9	147.7	1,466.3	0.00	0.00	0.00
4,300.0	26.33	173.45	3,942.7	-1,588.0	152.7	1,508.5	0.00	0.00	0.00



# Well Planning Report



<b>Database:</b>	EDM 5000.1 Single User Db	<b>Local Co-ordinate Reference:</b>	Well Hayward 0993-25-16E
<b>Company:</b>	Laramie Energy, LLC	<b>TVD Reference:</b>	RKB @ 8037.0usft (H&P #522)
<b>Project:</b>	Mesa County, CO	<b>MD Reference:</b>	RKB @ 8037.0usft (H&P #522)
<b>Site:</b>	Hayward 0993 25-09 Pad	<b>North Reference:</b>	True
<b>Well:</b>	Hayward 0993-25-16E	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	A-6		
<b>Design:</b>	Design #3		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
4,400.0	26.33	173.45	4,032.3	-1,632.0	157.8	1,550.7	0.00	0.00	0.00
4,500.0	26.33	173.45	4,121.9	-1,676.1	162.8	1,592.9	0.00	0.00	0.00
4,600.0	26.33	173.45	4,211.5	-1,720.2	167.9	1,635.1	0.00	0.00	0.00
4,700.0	26.33	173.45	4,301.2	-1,764.2	172.9	1,677.3	0.00	0.00	0.00
4,800.0	26.33	173.45	4,390.8	-1,808.3	178.0	1,719.5	0.00	0.00	0.00
4,900.0	26.33	173.45	4,480.4	-1,852.3	183.1	1,761.7	0.00	0.00	0.00
5,000.0	26.33	173.45	4,570.0	-1,896.4	188.1	1,803.8	0.00	0.00	0.00
5,100.0	26.33	173.45	4,659.7	-1,940.5	193.2	1,846.0	0.00	0.00	0.00
5,200.0	26.33	173.45	4,749.3	-1,984.5	198.2	1,888.2	0.00	0.00	0.00
5,300.0	26.33	173.45	4,838.9	-2,028.6	203.3	1,930.4	0.00	0.00	0.00
5,400.0	26.33	173.45	4,928.5	-2,072.7	208.3	1,972.6	0.00	0.00	0.00
5,500.0	26.33	173.45	5,018.2	-2,116.7	213.4	2,014.8	0.00	0.00	0.00
<b>Ohio Creek</b>									
5,576.8	26.33	173.45	5,087.0	-2,150.6	217.3	2,047.2	0.00	0.00	0.00
5,600.0	26.33	173.45	5,107.8	-2,160.8	218.4	2,057.0	0.00	0.00	0.00
5,700.0	26.33	173.45	5,197.4	-2,204.8	223.5	2,099.2	0.00	0.00	0.00
5,800.0	26.33	173.45	5,287.0	-2,248.9	228.6	2,141.4	0.00	0.00	0.00
5,900.0	26.33	173.45	5,376.7	-2,293.0	233.6	2,183.6	0.00	0.00	0.00
<b>Williams Fork</b>									
5,967.3	26.33	173.45	5,437.0	-2,322.6	237.0	2,212.0	0.00	0.00	0.00
6,000.0	26.33	173.45	5,466.3	-2,337.0	238.7	2,225.8	0.00	0.00	0.00
6,100.0	26.33	173.45	5,555.9	-2,381.1	243.7	2,268.0	0.00	0.00	0.00
<b>Drop 3° /100'</b>									
6,137.9	26.33	173.45	5,589.9	-2,397.8	245.6	2,284.0	0.00	0.00	0.00
6,200.0	24.47	173.45	5,646.0	-2,424.3	248.7	2,309.3	3.00	-3.00	0.00
6,300.0	21.47	173.45	5,738.1	-2,463.0	253.1	2,346.5	3.00	-3.00	0.00
6,400.0	18.47	173.45	5,832.0	-2,496.9	257.0	2,378.9	3.00	-3.00	0.00
6,500.0	15.47	173.45	5,927.7	-2,525.9	260.3	2,406.7	3.00	-3.00	0.00
6,600.0	12.47	173.45	6,024.7	-2,549.9	263.1	2,429.7	3.00	-3.00	0.00
6,700.0	9.47	173.45	6,122.9	-2,568.8	265.3	2,447.8	3.00	-3.00	0.00
6,800.0	6.47	173.45	6,221.9	-2,582.6	266.8	2,460.9	3.00	-3.00	0.00
6,900.0	3.47	173.45	6,321.5	-2,591.2	267.8	2,469.2	3.00	-3.00	0.00
7,000.0	0.47	173.45	6,421.4	-2,594.6	268.2	2,472.5	3.00	-3.00	0.00
<b>EOD @ Vertical - TOG</b>									
7,015.6	0.00	0.00	6,437.0	-2,594.6	268.2	2,472.5	3.00	-3.00	-1,113.80
7,100.0	0.00	0.00	6,521.4	-2,594.6	268.2	2,472.5	0.00	0.00	0.00
7,200.0	0.00	0.00	6,621.4	-2,594.6	268.2	2,472.5	0.00	0.00	0.00
7,300.0	0.00	0.00	6,721.4	-2,594.6	268.2	2,472.5	0.00	0.00	0.00
7,400.0	0.00	0.00	6,821.4	-2,594.6	268.2	2,472.5	0.00	0.00	0.00
7,500.0	0.00	0.00	6,921.4	-2,594.6	268.2	2,472.5	0.00	0.00	0.00
7,600.0	0.00	0.00	7,021.4	-2,594.6	268.2	2,472.5	0.00	0.00	0.00
7,700.0	0.00	0.00	7,121.4	-2,594.6	268.2	2,472.5	0.00	0.00	0.00
7,800.0	0.00	0.00	7,221.4	-2,594.6	268.2	2,472.5	0.00	0.00	0.00
7,900.0	0.00	0.00	7,321.4	-2,594.6	268.2	2,472.5	0.00	0.00	0.00
8,000.0	0.00	0.00	7,421.4	-2,594.6	268.2	2,472.5	0.00	0.00	0.00
8,100.0	0.00	0.00	7,521.4	-2,594.6	268.2	2,472.5	0.00	0.00	0.00
8,200.0	0.00	0.00	7,621.4	-2,594.6	268.2	2,472.5	0.00	0.00	0.00
8,300.0	0.00	0.00	7,721.4	-2,594.6	268.2	2,472.5	0.00	0.00	0.00
<b>Cameo</b>									
8,365.6	0.00	0.00	7,787.0	-2,594.6	268.2	2,472.5	0.00	0.00	0.00
8,400.0	0.00	0.00	7,821.4	-2,594.6	268.2	2,472.5	0.00	0.00	0.00
8,500.0	0.00	0.00	7,921.4	-2,594.6	268.2	2,472.5	0.00	0.00	0.00
8,600.0	0.00	0.00	8,021.4	-2,594.6	268.2	2,472.5	0.00	0.00	0.00



# Well Planning Report



<b>Database:</b>	EDM 5000.1 Single User Db	<b>Local Co-ordinate Reference:</b>	Well Hayward 0993-25-16E
<b>Company:</b>	Laramie Energy, LLC	<b>TVD Reference:</b>	RKB @ 8037.0usft (H&P #522)
<b>Project:</b>	Mesa County, CO	<b>MD Reference:</b>	RKB @ 8037.0usft (H&P #522)
<b>Site:</b>	Hayward 0993 25-09 Pad	<b>North Reference:</b>	True
<b>Well:</b>	Hayward 0993-25-16E	<b>Survey Calculation Method:</b>	Minimum Curvature
<b>Wellbore:</b>	A-6		
<b>Design:</b>	Design #3		

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
8,700.0	0.00	0.00	8,121.4	-2,594.6	268.2	2,472.5	0.00	0.00	0.00
<b>Base Cameo Coal</b>									
8,745.6	0.00	0.00	8,167.0	-2,594.6	268.2	2,472.5	0.00	0.00	0.00
<b>Rollins</b>									
8,765.6	0.00	0.00	8,187.0	-2,594.6	268.2	2,472.5	0.00	0.00	0.00
8,800.0	0.00	0.00	8,221.4	-2,594.6	268.2	2,472.5	0.00	0.00	0.00
8,900.0	0.00	0.00	8,321.4	-2,594.6	268.2	2,472.5	0.00	0.00	0.00
<b>TD @ 8965.6' MD / 8387.0' TVD</b>									
8,965.6	0.00	0.00	8,387.0	-2,594.6	268.2	2,472.5	0.00	0.00	0.00

Design Targets									
Target Name	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
- hit/miss target									
- Shape									
PBHL - Hayward 0993	0.00	0.00	8,387.0	-2,594.6	268.2	1,519,117.78	2,372,705.96	39.237709	-107.714959
- plan hits target center									
- Circle (radius 65.0)									

Casing Points					
Measured Depth (usft)	Vertical Depth (usft)	Name	Casing Diameter (")	Hole Diameter (")	
1,530.0	1,460.0	8 5/8"	8-5/8	11	

Formations					
Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)
3,401.1	3,137.0	G' Sand			
5,576.8	5,087.0	Ohio Creek			
5,967.3	5,437.0	Williams Fork			
7,015.6	6,437.0	TOG			
8,365.6	7,787.0	Cameo			
8,745.6	8,167.0	Base Cameo Coal			
8,765.6	8,187.0	Rollins			

Plan Annotations				
Measured Depth (usft)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Comment
250.0	250.0	0.0	0.0	KOP / Build 3° / 100'
583.3	581.6	-28.0	-7.5	EOB @ 10.00° Inc. / 195.00° Azm / Build 3° / 100'
1,163.1	1,131.1	-205.7	-5.9	EOB @ 26.33° Inc. / 173.45° Azm
6,137.9	5,589.9	-2,397.8	245.6	Drop 3° / 100'
7,015.6	6,437.0	-2,594.6	268.2	EOD @ Vertical
8,965.6	8,387.0	-2,594.6	268.2	TD @ 8965.6' MD / 8387.0' TVD