

OPERATOR: K.P. Kauffman Company Inc.

WELL: Anderson 12-32

FIELD: WATTENBERG

API #: 05-123-23790

LEASE #:

UIC #:

CNTY: WELD

STATE: CO

SPUD: 1/25/2007

COMP: 1/31/2007

STATUS: TA

WBD DATE: 1/10/2023

FTG:

Q-Q: NWSW

SEC.: 32

TWS: 4N

RGE: 67W

BY:

WELLBORE DIAGRAM

KBE: 4973 '

KB: 12 '

GLE: 4961 '

TD (ft): 7907 '

PBTD (ft): 7848 '

12.25" Hole
8.625" 24# Csg @ 673 '
Cmtd w/480 sxs

TOC @ 3513 '
CBL

7.875" Hole
4.5" 11.6# Csg @ 7864 '
Cmtd w/775 sxs

Set RBP @ 7192 '

CODELL Perfs
7298'-7318'

PBTD (ft): 7848 '
TD (ft): 7907 '

CASING RECORD

HOLE (in)	SIZE (in)	WT (lb/ft)	GRADE	TOP (ft)	BTM (ft)
<u>12 1/4</u>	<u>8 5/8</u>	<u>24</u>		<u>0</u>	<u>673</u>
<u>7 7/8</u>	<u>4 1/2</u>	<u>11.6</u>		<u>0</u>	<u>7864</u>

TUBING RECORD

SIZE (in)	WT (lb/ft)	GRADE	JOINTS	BTM (ft)

PERFORATION RECORD

ZONE	TOP (ft)	BTM (ft)	HOLES	STAGE	STATUS
<u>CODELL</u>	<u>7298</u>	<u>7318</u>	<u>80</u>		

WELLWORK HISTORY

Treatment Summary:

3/27/2007:

CodeLL: Pumped 19,979 gal 7% KCl pre-pad, 94,661 gal silver stim w/ 242,820 # 20/40 mesh sand and 8,000 # 12/20 mesh SB, staged 1 ppg to 4 ppg, 2730 BLWTR

1/10/23:

RBP set @ 7192' for offset frac

Formation Tops:

Parkman 3671'
Sussex 4206'
Shannon 4664'
TP-Buttes 6017'
Niobrara 7006'
Fort Hays 7277'
Codell 7298'
J-Sand 7746'