



Base of Productive Zone (BPZ)  
 Sec: 16 Twp: 6N Rng: 64W Footage at BPZ: 352 FNL 200 FEL  
 Measured Depth of BPZ: 18065 True Vertical Depth of BPZ: 6775 FNL/FSL FEL/FWL

Bottom Hole Location (BHL)  
 Sec: 16 Twp: 6N Rng: 64W Footage at BHL: 352 FNL 200 FEL  
FNL/FSL FEL/FWL

**LOCAL GOVERNMENT PERMITTING INFORMATION**

County: WELD Municipality: N/A

Is the Surface Location of this Well in an area designated as one of State interest and subject to the requirements of § 24-65.1-108 C.R.S.? Yes

Per § 34-60-106(1)(f)(I)(A) C.R.S., the following questions pertain to the Relevant Local Government approval of the siting of the proposed Oil and Gas Location.

SB 19-181 provides that when “applying for a permit to drill,” operators must include proof that they sought a local government siting permit and the disposition of that permit application, or that the local government does not have siting regulations. § 34-60-106(1)(f)(I) (A) C.R.S.

Does the Relevant Local Government regulate the siting of Oil and Gas Locations, with respect to this Location?  Yes  No

If yes, in checking this box, I hereby certify that an application has been filed with the local government with jurisdiction to approve the siting of the proposed oil and gas location.

The disposition of the application filed with the Relevant Local Government is: Approved Date of Final Disposition: 01/08/2020

Comments: CDP WOGLA 1041WOGLA19-0042 filed 12/10/2019, recorded 1/8/2020. A site-specific WOGLA will be filed prior to commencement of operations.

**SURFACE AND MINERAL OWNERSHIP AT WELL’S OIL & GAS LOCATION**

Surface Owner of the land at this Well’s Oil and Gas Location:  Fee  State  Federal  Indian

Mineral Owner beneath this Well’s Oil and Gas Location:  Fee  State  Federal  Indian

Surface Owner Protection Bond (if applicable): \_\_\_\_\_ Surety ID Number (if applicable): \_\_\_\_\_

**MINERALS DEVELOPED BY WELL**

The ownership of all the minerals that will be developed by this Well is (check all that apply):

- Fee
- State
- Federal
- Indian
- N/A

## LEASE INFORMATION

Using standard QtrQtr, Section, Township, Range format describe one entire mineral lease as follows:

\* If this Well is within a unit, describe a lease that will be developed by the Well.

\* If this Well is not subject to a unit, describe the lease that will be produced by the Well.

(Attach a Lease Map or Lease Description or Lease if necessary.)

T6N-R64W, 6th P.M., Sec. 17: W/2NW/4, SE/4, all formations; Sec. 17: NE, E/2NW/4, SW/4, all formations below the base of the Codell formation

Total Acres in Described Lease: 240 Described Mineral Lease is:  Fee  State  Federal  Indian

Federal or State Lease # \_\_\_\_\_

## SAFETY SETBACK INFORMATION

Distance from Well to nearest:

Building: 641 Feet  
Building Unit: 833 Feet  
Public Road: 939 Feet  
Above Ground Utility: 924 Feet  
Railroad: 5280 Feet  
Property Line: 299 Feet

### INSTRUCTIONS:

- Specify all distances per Rule 308.b.(1).
- Enter 5280 for distance greater than 1 mile.
- Building - nearest building of any type. If nearest Building is a Building Unit, enter same distance for both.
- Building Unit – as defined in 100 Series Rules.

## OBJECTIVE FORMATIONS

| Objective Formation(s) | Formation Code | Spacing Order Number(s) | Unit Acreage Assigned to Well | Unit Configuration (N/2, SE/4, etc.) |
|------------------------|----------------|-------------------------|-------------------------------|--------------------------------------|
| NIOBRARA               | NBRR           | 407-3384                | 1280                          | 6N-64W-16: ALL; 17: ALL              |

Federal or State Unit Name (if appl): \_\_\_\_\_ Unit Number: \_\_\_\_\_

## SUBSURFACE MINERAL SETBACKS

Enter 5280 for distance greater than 1 mile.

Is this Well within a unit? Yes

If YES:

Enter the minimum distance from the Completed Zone of this Well to the Unit Boundary: 200 Feet

Enter the minimum distance from the Completed Zone of this Well to the Completed Zone of an offset Well within the same unit permitted or completed in the same formation: 635 Feet

If NO:

Enter the minimum distance from the Completed Zone of this Well to the Lease Line of the described lease: \_\_\_\_\_ Feet

Enter the minimum distance from the Completed Zone of this Well to the Completed Zone of an offset Well producing from the same lease and permitted or completed in the same formation: \_\_\_\_\_ Feet

## Exception Location

If this Well requires the approval of a Rule 401.c Exception Location, enter the Rule or spacing order number and attach the Exception Location Request and Waivers. \_\_\_\_\_





Based on the information provided herein, this Application for Permit-to-Drill complies with COGCC Rules, applicable orders, and SB 19-181 and is hereby approved.

COGCC Approved: \_\_\_\_\_ Director of COGCC Date: \_\_\_\_\_  
 Expiration Date: \_\_\_\_\_

**API NUMBER**  
 05

### Conditions Of Approval

All representations, stipulations and conditions of approval stated in the Form 2A for this location shall constitute representations, stipulations and conditions of approval for this Form 2 Permit-to-Drill and are enforceable to the same extent as all other representations, stipulations and conditions of approval stated in this Permit-to-Drill.

| <u>COA Type</u> | <u>Description</u> |
|-----------------|--------------------|
| 0 COA           |                    |

### Best Management Practices

| <u>No</u> | <u>BMP/COA Type</u>            | <u>Description</u>   |
|-----------|--------------------------------|--|
| 1         | Drilling/Completion Operations | One of the first wells drilled on the pad will be logged with Open Hole Resistivity Log and Gamma Ray Log from the kick-off point into the surface casing. All wells on the pad will have a cement bond log with gamma-ray run on production casing (or on intermediate casing if production liner is run) into the surface casing. The horizontal portion of every well will be logged with a measured-while-drilling gamma-ray log. The form 5, Completion Report, for each well on the pad will list all logs run and have those logs attached. The Form 5 for a well without open-hole logs shall clearly state "Alternative Logging Program - No open-hole logs were run" and shall clearly identify (by API#, well name & number) the well in which open-hole logs were run.   |
| 2         | Drilling/Completion Operations | If a skid is performed for the subject well, then the only required BOPE tests are for the BOPE connection bonnet seal breaks, as long as a full BOPE test was performed at the beginning of the pad, and as long as all necessary BOPE tests are completed at least every 30 days during the pad operations.  |
| 3         | Drilling/Completion Operations | Anti-collision: Prior to drilling operations, Operator will perform an anti-collision scan of existing offset wells that have the potential of being within close proximity of the proposed well. This anti-collision scan will include definitive MWD or gyro surveys of the offset wells with included error of uncertainty per survey instrument and compared against the proposed well path with its respective error of uncertainty. If current surveys do not exist for the offset wells, Operator may have gyro surveys conducted to verify bottom hole location. The proposed well will only be drilled if the anti-collision scan results indicate that there is not a risk for collision, or harm to people or the environment. For the proposed well, upon conclusion of drilling operations, an as constructed gyro survey will be submitted to COGCC with the Form 5. |
| 4         | Drilling/Completion Operations | Operator will log two (2) wells during the first rig occupation with open-hole resistivity log with gamma-ray log from the kick-off point into the surface casing for the two stratigraphically deepest wells on each side of the pad.   |

Total: 4 comment(s)

## Attachment List

| <u>Att Doc Num</u> | <u>Name</u>                |
|--------------------|----------------------------|
| 403295705          | OffsetWellEvaluations Data |
| 403295707          | WELL LOCATION PLAT         |
| 403295709          | DEVIATED DRILLING PLAN     |
| 403295710          | DIRECTIONAL DATA           |

Total Attach: 4 Files

## General Comments

| <u>User Group</u> | <u>Comment</u>   | <u>Comment Date</u> |
|-------------------|--|---------------------|
| Permit            | <p>ON HOLD: This application has been reviewed by COGCC staff and cannot be approved based on the information submitted; therefore, the COGCC is placing this form ON HOLD until additional information is received from the applicant. If the information is not received by June 15, 2023 these applications will be withdrawn.</p> <p>In compliance with § 24-65.1-108(1), C.R.S., the COGCC is providing this written request for all additional information necessary for the COGCC to respond to this application. The applicant may provide all requested additional information to COGCC via email. Upon receipt of all requested information, the COGCC will have 60 days in which to approve, deny, or request all additional information necessary to complete the regulatory review. If the applicant no longer requires this application be approved, the applicant may request to withdraw the application.</p> <p>In addition to all standard required information and attachments, the COGCC hereby confirms the following information is necessary for review.</p> <ol style="list-style-type: none"> <li>1. Remove Open Hole Logging Exception request letter.</li> <li>2. Add the standard COA for Open Hole Logging:<br/>Alternative Logging Program: One of the first wells drilled on the pad will be logged with Open Hole Resistivity Log and Gamma Ray Log from the kick-off point into the surface casing. All wells on the pad will have a cement bond log with gamma-ray run on production casing (or on intermediate casing if production liner is run) into the surface casing. The horizontal portion of every well will be logged with a measured-while-drilling gamma-ray log. The form 5, Completion Report, for each well on the pad will list all logs run and have those logs attached. The Form 5 for a well without open-hole logs shall clearly state "Alternative Logging Program - No open-hole logs were run" and shall clearly identify (by API#, well name &amp; number) the well in which open-hole logs were run."</li> <li>3. Add the additional COA for Open Hole Logging:<br/>Operator will log two (2) wells during the first rig occupation with open-hole resistivity log with gamma-ray log from the kick-off point into the surface casing for the two stratigraphically deepest wells on each side of the pad.</li> <li>4. Correct the Drilling and Spacing Unit number</li> <li>5. Correct the Footage at BPZ for each APD</li> <li>6. Correct the Footage at BHL for each APD</li> </ol> | 03/17/2023          |

Total: 1 comment(s)