

OIL AND GAS CONSERVATION COMMISSION  
OF THE STATE OF COLORADOfor Patented and Federal lands.  
for State lands.

RECEIVED

NOV 21 1973

## SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.  
Use "APPLICATION FOR PERMIT—" for such proposals.)

1.

OIL WELL ☒ GAS WELL ☐ OTHER ☐

2. NAME OF OPERATOR

Champlin Petroleum Company

3. ADDRESS OF OPERATOR

P. O. Box 1257, Englewood, Colorado

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.  
See also space 17 below.)

At surface

SW SW 660' S1y &amp; 660' W1y

At proposed prod. zone

14. PERMIT NO.

72680

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4704' G.L.

5. LEASE DESIGNATION AND SERIAL NO.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

Charles Jolly 14-8

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Ramp

11. SEC., T., R., M., OR BLK. AND  
SURVEY OR AREA

Section 8, T3S, R55W

12. COUNTY OR PARISH

Washington

13. STATE

Colorado

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

## NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON

REPAIR WELL

CHANGE PLANS

(Other)

## SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT

(Other)

(NOTE: Report results of multiple completion on Well  
Completion or Recompletion Report and Log form.)17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any  
proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones perti-  
nent to this work.)Date of work when approved

It is proposed to plug and abandon the subject well as follows:

1. Set 15 sack cement plug 4920' to 4723'.
2. Establish free point and shoot of casing approx. top of cement 4200'.
3. Plug No. 2 - 25 sacks at top of stub.  
Plug No. 3 - 25 sacks bottom surface casing (145')  
Plug No. 4 - 5 sacks top surface casing. Cut off 2' below ground and  
weld plate over top of casing.

DVR	<input checked="" type="checkbox"/>
FJP	<input checked="" type="checkbox"/>
HHM	<input checked="" type="checkbox"/>
JAM	<input checked="" type="checkbox"/>
JJD	<input checked="" type="checkbox"/>

18. I hereby certify that the foregoing is true and correct

SIGNED R. A. ScottTITLE Dist. Drlg. & Prod. Supt. DATE November 19, 1973

(This space for Federal or State office use)

APPROVED BY [Signature]  
CONDITIONS OF APPROVAL, IF ANY:

TITLE

DIRECTOR

DATE

NOV 28 1973

need plug

formerly temp 59