

OGC
REV



GAS CONSERVATION COMMISSION
DEPARTMENT OF NATURAL RESOURCES
THE STATE OF COLORADO

RECEIVED
FEB 13 1974

File in duplicate for Patented and Federal lands.
File in triplicate for State lands.

SUNDRY NOTICES AND REPORTS ON WELLS

(Do not use this form for proposals to drill or to deepen or plug back to a different reservoir.
Use "APPLICATION FOR PERMIT—" for such proposals.)

5. LEASE DESIGNATION AND SERIAL NO.
OIL & GAS CONS. COMM.

6. IF INDIAN, ALLOTTEE OR TRIBE NAME

7. UNIT AGREEMENT NAME

8. FARM OR LEASE NAME

C. L. Jolly

9. WELL NO.

5

10. FIELD AND POOL, OR WILDCAT

Ramp

11. SEC., T., R., M., OR BLK. AND SURVEY OR AREA

Section 8, T3S, R55W

12. COUNTY

Washington

13. STATE

Colorado

1. OIL WELL GAS WELL OTHER

2. NAME OF OPERATOR
Champlin Petroleum Company

3. ADDRESS OF OPERATOR
P. O. Box 1257, Englewood, Colorado 80110

4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.
See also space 17 below.)
At surface SW SW 660' FSL & 660' FWL

At proposed prod. zone

14. PERMIT NO.

72680

15. ELEVATIONS (Show whether DF, RT, GR, etc.)

4704' G. L.

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF

PULL OR ALTER CASING

FRACTURE TREAT

MULTIPLE COMPLETE

SHOOT OR ACIDIZE

ABANDON

REPAIR WELL

CHANGE PLANS

(Other)

SUBSEQUENT REPORT OF:

WATER SHUT-OFF

REPAIRING WELL

FRACTURE TREATMENT

ALTERING CASING

SHOOTING OR ACIDIZING

ABANDONMENT

(Other)

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)

Date of work January 1, 1974

Well was plugged and abandoned as follows:

1. Set 15 sack cement plug 4900' to 4720'.
2. Shot pipe off at 4070'.
3. Set 25 sack plug 4000' to 3925'.
4. Set 25 sack plug 150' to 75'.
5. Set 5 sack plug in top of surface casing.

DVR	<input checked="" type="checkbox"/>
FJP	<input checked="" type="checkbox"/>
HHM	<input checked="" type="checkbox"/>
JAM	<input checked="" type="checkbox"/>
JJD	<input checked="" type="checkbox"/>

18. I hereby certify that the foregoing is true and correct

SIGNED

R. A. Scott
R. A. SCOTT

TITLE Dist. Drlg. & Prod. Supt.

DATE 2-11-74

(This space for Federal or State office use)

APPROVED BY

M. Rogers
M. ROGERS

TITLE DIRECTOR

DIRECTOR

DATE

FEB 14 1974

CONDITIONS OF APPROVAL, IF ANY:

