

UNITED STATES
DEPARTMENT OF THE INTERIOR
GEOLOGICAL SURVEY

SUBMIT IN TRIPLICATE*
(Other instructions on re-
verse side)

Form approved.
Budget Bureau No. 42-R1424.



SEP 10 1974
CES AND REPORTS ON WELLS

also to drill or to deepen or plug back to a different reservoir.
ATION FOR PERMIT—" for such proposals.)

COLO. OIL & GAS CONS. COMM.

1. OIL WELL <input checked="" type="checkbox"/> GAS WELL <input type="checkbox"/> OTHER <input type="checkbox"/>		7. UNIT AGREEMENT NAME	
2. NAME OF OPERATOR Atlantic Richfield Company		8. FARM OR LEASE NAME U.S.A.	
3. ADDRESS OF OPERATOR 501 Lincoln Tower Bldg., 1860 Lincoln St., Denver, Colo. 80203		9. WELL NO. 1-22	
4. LOCATION OF WELL (Report location clearly and in accordance with any State requirements.* See also space 17 below.) At surface SE NE - 1990' f/North & 690' F/East lines Sec. 22		10. FIELD AND POOL, OR WILDCAT Buck Peak	
14. PERMIT NO. Colo. 74 653 Mr. Gwynn, 8/26/74		15. ELEVATIONS (Show whether DF, RT, GR, etc.) 6930' GL	
		12. COUNTY OR PARISH Moffat	13. STATE Colorado

16. Check Appropriate Box To Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

TEST WATER SHUT-OFF ☐
FRACTURE TREAT ☐
SHOOT OR ACIDIZE ☐
REPAIR WELL ☐
(Other) ☐

PULL OR ALTER CASING ☐
MULTIPLE COMPLETE ☐
ABANDON* ☐
CHANGE PLANS ☐

SUBSEQUENT REPORT OF:

WATER SHUT-OFF ☐
FRACTURE TREATMENT ☐
SHOOTING OR ACIDIZING ☐
(Other) ☒ **Spud & surf. casing**

REPAIRING WELL ☐
ALTERING CASING ☐
ABANDONMENT* ☐

(NOTE: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)

17. DESCRIBE PROPOSED OR COMPLETED OPERATIONS (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work. If well is directionally drilled, give subsurface locations and measured and true vertical depths for all markers and zones pertinent to this work.)*

Set 30' of 20" conductor. MI & HU rotary tools. Spud 8-3/4" hole @ 10:30 p.m. 9/3/74. Drld 8-3/4" hole to 361'. Reamed to 15" hole to 356'. Ran 8 jts 11-3/4" OD YS-95 60# 8rd ST&C casing set at 353.76' KB (342.36' GL), cemented w/ 300 sacks Class "G" w/ 2% CaCl & 1/4# Flocele per sack. Plug down 9:15 p.m. 9/4/74. WOC. Cement circulated.

Nippled up head & BOP. Tested blind rams, pipe rams, hydril, and casing @ 1000# f/ 20 min. each, all held O.K.. Tag cement @ 291'. Drld out 12:15 a.m. 9/6/74.

9/6/74 Drilling ahead @ 630' - 8-3/4" hole.

cc: Colo. Oil & Gas Cons. Comm.

DVR	
FJP	
HMT	✓
JAM	✓
JID	✓
GCH	
CGM	

18. I hereby certify that the foregoing is true and correct

SIGNED W. A. Wadsworth TITLE Dist. Prod. & Drlg. Supt. DATE 9/7/74

(This space for Federal or State office use)

APPROVED BY W. A. Rogers TITLE DIRECTOR DATE SEP 10 1974

CONDITIONS OF APPROVAL, IF ANY:

file