

OFFICE OF STATE OIL INSPECTOR
SUNDRY NOTICES AND REPORTS OF WELLS
LOCATED ON PRIVATE LANDS



(Indicate nature of data by checking below)

Notice of intention to drill.....
Notice of intention to change plans.....
Notice of date for test of water shut-off.....
Report on result of test of water shut-off.....
Notice of intention to re-drill or repair well.....
Notice of intention to clean out well.....
Statement of ~~shooting~~ Setting Casing..... XXXX
Statement of perforating.....
Notice to pull or otherwise alter casing.....
Notice of intention to abandon well.....
Report of work done on well since previous report.....

September 28 1951
Following is a (~~notice of intention to do work~~) (On land)
(report of work done) (patented) described as follows:

Colorado Logan Atwood
State County Field
J-9 Pomeroy SE $\frac{1}{4}$ SW $\frac{1}{4}$ SE $\frac{1}{4}$ 20 7N 53W 6th
(Well No.) (Lease) (Sec. and $\frac{1}{4}$ Sec.) (Twp.) (Range) (Meridian)
The well is located 330 ft. (N) of S and 1650 ft. (E) of E
(S) (W)

The elevation above sea level is 4100 (KB) ft.

Details of Plan of Work: (State names of and expected depths to objective sands:
Show sizes, weights, and lengths of proposed casings; indicate mudding jobs, cement-
ing points, and all other important proposed work.)

The above described well was drilled to a total depth of 4734 (KB), on September 24, 1951.

On September 25, 1951, the production casing consisting of 5-1/2" OD, 14#, J-55, 8Rd Thd. Casing totaling 4723, was landed @ 4733 (KB) and cemented with 150 sacks of cement. A Baker guide shoe was run on the first joint, and a Baker Float Collar was run between the first and the second joint. Centralizers were run at the following depths; 4723, 4703, 4683. Top and bottom plugs were used and the cement was in place at 2.30 P.M., on September 25, 1951. The cement was allowed to set for 48 hours at which time a pressure of 500 psi was applied to the casing for one hour. No leakage was noticed so the plug was drilled out to 4733 (KB). This well will be produced thru perforations in the casing.

Approved: OCT 18 1951

State Oil Inspector

Director

Company Trigood Oil Company

Address Box 1689, Casper, Wyoming

By J. L. Fusselman

Title Assistant Manager

Submit reports of proposed work, for approval, on this form in Duplicate.

JDM/ib SOI (2); Fld.; JLF; DF